Expressiveness and Approximation Properties of Graph Neural Networks

Abstract

Characterizing the separation power of graph neural networks (GNNs) provides an understanding of their limitations for graph learning tasks. Results regarding separation power are, however, usually geared at specific GNN architectures, and tools for understanding arbitrary GNN architectures are generally lacking. We provide an elegant way to easily obtain bounds on the separation power of GNNs in terms of the Weisfeiler-Leman (WL) tests, which have become the yardstick to measure the separation power of GNNs. The crux is to view GNNs as expressions in a procedural tensor language describing the computations in the layers of the GNNs. Then, by a simple analysis of the obtained expressions, in terms of the number of indexes and the nesting depth of summations, bounds on the separation power in terms of the WL-tests readily follow. Furthermore, the tensor language point of view allows for the derivation of universality results for classes of GNNs in a natural way. Our approach provides a toolbox with which GNN architecture designers can analyze the separation power of their GNNs, without needing to know the intricacies of the WL-tests. We also provide insights in what is needed to boost the separation power of GNNs.

1 Introduction

Graph Neural Networks (GNNs) (Merkwirth & Lengauer, 2005; Scarselli et al., 2009) cover many popular deep learning methods for graph learning tasks (see Hamilton (2020) for a recent overview). These methods typically compute vector embeddings of vertices or graphs by relying on the underlying adjacency information. Invariance (for graph embeddings) and equivariance (for vertex embeddings) of GNNs ensure that these methods are oblivious to the precise representation of the graphs.

Separation power. The primary focus of this paper concerns the separation power of GNN architectures, that is, on their ability to separate vertices or graphs by means of the computed embeddings. In turn, characterizing the separation power of GNNs reveals insights into their strengths and weaknesses when it comes to graph learning tasks. It has become standard to characterize GNN architectures in terms of the separation power of classical graph algorithms such as color refinement (CR) and k-dimensional Weisfeiler-Leman tests (k-WL), as initiated in Xu et al. (2019) and Morris et al. (2019). Unfortunately, understanding the separation power of any given GNN architecture requires complex proofs that are geared at the specifics of such architecture. We do not have any general technique allowing us to expand these results for arbitrary GNNs.

Tensor languages. We study the separation power of vector embeddings that can be computed by general-purpose tensor languages. By focusing on this more general context, we obtain insights about specific GNN architectures by simply describing them in such a tensor language. A first advantage of using tensor languages is that only invariant and equivariant graph functions can be defined. As such, any GNN that can be cast in our tensor language inherits these desired properties. A second important advantage is that the separation power of tensor languages is as closely related to CR and k-WL as GNNs are. Loosely speaking, *if tensor language expressions use $k + 1$ indices, then their separation power is bounded by k-WL. Furthermore, if their summation depth (maximum nesting of summations) is t, then t rounds of k-WL are needed to obtain an upper bound on the separation power.* A similar connection is obtained for CR and a fragment of tensor language that we call "guarded" tensor language.

We thus reduce problem of assessing the separation power of *any* specific GNN architecture to the problem of specifying it in our tensor language, analyzing the number of indices used and counting their summation depth. As we show in the paper, this is usually much easier than dealing with intricacies of CR and k-WL. In fact, casting GNNs in our tensor language is often as simple as writing down their layer-based definition found in research articles. We believe that this provides a nice toolbox for GNN designers to assess the separation power of their architecture.

We use this toolbox to recover known results about the separation power of specific GNN architectures such as GINs (Xu et al., 2019), GCNs (Kipf & Welling, 2017), Folklore GNNs (Maron et al., 2019b), k-GNNs (Morris et al., 2019), and several others. And we also derive new results: we answer an open problem posed by Maron et al. (2019a) by showing that the separation power of Invariant Graph Networks (k-IGNs), introduced by Maron et al. (2019b), is bounded by $(k-1)$-WL. In all this, we make explicit how the number of layers connects to the number of rounds of the WL-tests.

When writing down GNNs in our tensor language, the less indices needed, the stronger the bounds in terms of k-WL we obtain. After all, $(k-1)$-WL is known to be strictly less separating than k-WL (Otto, 2017). Thus, it is important to minimize the number of indices used in tensor language expressions. We connect this number to the notion of *treewidth*: expressions of treewidth k can be translated into expressions using $k+1$ indices. This corresponds to optimizing expressions, as done in many areas in machine learning, by reordering the summations (a.k.a. variable elimination).

Approximation and universality. Another important aspect of GNNs that has received considerable attention is their ability to approximate general invariant or equivariant graph functions. Once more, instead of focusing on specific architectures, we use our tensor languages to obtain general approximation results, which naturally translate to universality results for GNNs.

We show: $k+1$ index tensor language expressions suffice to approximate any (invariant/equivariant) graph function whose separating power is bounded by k-WL, and we can further refine this by comparing the number of rounds in k-WL with the summation depth of the expressions. These results provide a finer picture than the one obtained by Azizian & Lelarge (2021). Furthermore, focusing on "guarded" tensor expressions yields a similar universality result for CR, a result that, to our knowledge, was not known before. We also provide the link between approximation results for tensor expressions and GNNs, enabling us to transfer our insights into universality properties of GNNs. As an example, we show that k-IGNs can approximate any graph function that is less separating than $(k-1)$-WL. This case was left open in Azizian & Lelarge (2021).

In summary, our paper draws new and interesting connections between tensor languages, GNN architectures and classic graph algorithms. These connections provide a general recipe to bound the separation power of GNNs, optimize them, and understand their approximation power. We demonstrate the usefulness of our method by recovering several results shown in recent years, as well as new results, some of them left open in previous work.

Related Work. Separation power has only been studied for specific classes of GNNs (Morris et al., 2019; Xu et al., 2019; Maron et al., 2019b; Chen et al., 2019; Morris et al., 2020; Azizian & Lelarge, 2021) by relying on properties of CR and k-WL. Connections between k-WL, for $k = 1, 2$, and general matrix query languages are known (Brijder et al., 2019; Geerts, 2021; Geerts et al., 2021b), albeit not in the context of GNNs. We differ by analyzing the separation power of general tensor languages, from which known results on GNNs can be recovered. Regarding universality, the work by Azizian & Lelarge (2021) is closest in spirit. Our tensor language approach, however, provides an elegant way to recover and extend their results. Azizian & Lelarge (2021) describe how their work (and hence also ours) encompasses previous works (Keriven & Peyré, 2019; Maron et al., 2019c; Chen et al., 2019). Our results are based on connections between k-WL and logics (Immerman & Lander, 1990; Cai et al., 1992), and CR and guarded logics (Barceló et al., 2020). We refer to Grohe (2021) for a recent overview. The optimization of algebraic computations and the use of treewidth relates to the approaches by Aji & McEliece (2000) and Abo Khamis et al. (2016).

Outline. We cite additional related works throughout the paper and provide details in the supplementary material. After providing some background, we introduce our tensor languages in Section 3, followed by a full characterization of their separation power in Section 4. In Section 5 we emphasize important consequences of our results for understanding the power of various GNNs. Finally, we present general approximation results and consequences for GNNs in Section 6.

2 BACKGROUND

We denote sets by $\{\}$ and multisets by $\{\{\}\}$. For $n \in \mathbb{N}$, $n > 0$, $[n] := \{1, \ldots, n\}$. Vectors are denoted by $\boldsymbol{v}, \boldsymbol{w}, \ldots$, matrices by $\boldsymbol{A}, \boldsymbol{B}, \ldots$, and tensors by $\mathsf{S}, \mathsf{T}, \ldots$. Furthermore, v_i is the i-th entry of vector $\boldsymbol{v}$, A_{ij} is the (i, j)-th entry of matrix $\boldsymbol{A}$ and $\mathsf{S}_{\boldsymbol{i}}$ denotes the $\boldsymbol{i} = (i_1, \ldots, i_k)$-th entry of a tensor S. If certain dimensions are unspecified, then this is denoted by a ":". For example, $\boldsymbol{A}_{i:}$ and $\boldsymbol{A}_{:j}$ denote the i-th row and j-th column of matrix $\boldsymbol{A}$, respectively. Similarly for slices of tensors.

An undirected simple graph $G = (V_G, E_G, \mathsf{col}_G)$ is represented by a vertex set V_G, edge set $E_G \subseteq V_G^2$, which is symmetric and irreflexive, and vertex-labelling $\mathsf{col}_G : V_G \to \{0, 1\}^\ell$. Throughout the paper we assume that graphs have size n, so V_G consists of n vertices and we often identify V_G with $[n]$. For a vertex $v \in V_G$, $N_G(v) := \{u \in V_G \mid vu \in E_G\}$. We let $\mathcal{G}$ be the set of all graphs of size n and let $\mathcal{G}_s$ be the set of pairs $(G, \boldsymbol{v})$ with $G \in \mathcal{G}$ and $\boldsymbol{v} \in V_G^s$. Note that $\mathcal{G} = \mathcal{G}_0$.

The following vertex and graph-labelling algorithms will play an important role. The *color refinement* algorithm (CR) (Morgan, 1965) iteratively computes vertex labellings, as follows. For a graph G and vertex $v \in V_G$, $\mathsf{cr}^{(0)}(G, v) := \mathsf{col}_G(v)$. Then, for $t \geq 0$, $\mathsf{cr}^{(t+1)}(G, v) := (\mathsf{cr}^{(t)}(G, v), \{\{\mathsf{cr}^{(t)}(G, u) \mid u \in N_G(v)\}\})$. Furthermore, we define $\mathsf{gcr}^{(t)}(G) := \{\{\mathsf{cr}^{(t)}(G, v) \mid v \in V_G\}\}$. The k-*dimensional Weisfeiler-Leman* algorithm (k-WL) (Weisfeiler & Lehman, 1968; Cai et al., 1992) iteratively computes labellings of k-tuples of vertices. Initially, for a graph G and $\boldsymbol{v} \in V_G^k$, $\mathsf{wl}_k^{(0)}(G, \boldsymbol{v}) := \mathsf{atp}_k(G, \boldsymbol{v})$ where $\mathsf{atp}_k(G, \boldsymbol{v}) \in \{0, 1\}^{2\binom{k}{2}+k\ell}$ is the atomic type vector which for $1 \leq i < j \leq k$ has two entries indicating whether $v_i = v_j$ and whether $v_iv_j \in E_G$, and for $1 \leq i \leq k$ has ℓ entries corresponding to $\mathsf{col}_G(v_i)$. For $t \geq 0$, $\mathsf{wl}_k^{(t+1)}(G, \boldsymbol{v}) := (\mathsf{wl}_k^{(t)}(G, \boldsymbol{v}), M)$ with $M := \{\{(\mathsf{atp}_{k+1}(G, \boldsymbol{v}u), \mathsf{wl}_k^{(t)}(G, \boldsymbol{v}[u/1]), \ldots, \mathsf{wl}_k^{(t)}(G, \boldsymbol{v}[u/k])) \mid u \in V_G\}\}$, where $\boldsymbol{v}[u/i] := (v_1, \ldots, v_{i-1}, u, v_{i+1}, \ldots, v_k)$. We use k-WL for vertex-labellings by defining $\mathsf{vwl}_k^{(t)}(G, v) := \mathsf{wl}_k^{(t)}(G, (v, \ldots, v))$ and for graph-labellings we define $\mathsf{gwl}_k^{(t)} := \{\{\mathsf{wl}_k^{(t)}(G, \boldsymbol{v}) \mid \boldsymbol{v} \in V_G^k\}\}$. Note that 1-WL differs from CR in that 1-WL also uses information from non-adjacent vertices (Grohe, 2021). Moreover, we use $\mathsf{cr}^{(\infty)}$, $\mathsf{gcr}^{(\infty)}$, $\mathsf{vwl}_k^{(\infty)}$, and $\mathsf{gwl}_k^{(\infty)}$ to denote the stable labellings produced by the corresponding algorithm over an arbitrary number of rounds.

Let G be a graph with $V_G = [n]$ and let σ be a permutation of $[n]$. We denote by $\sigma \star G$ the isomorphic copy of G obtained by applying the permutation σ. Similarly, for $\boldsymbol{v} \in V_G^k$, $\sigma \star \boldsymbol{v}$ is the permuted version of $\boldsymbol{v}$. Let $\mathbb{F}$ be some feature space. A function $f : \mathcal{G}_0 \to \mathbb{F}$ is called *invariant* if $f(G) = f(\sigma \star G)$ for any permutation π. More generally, $f : \mathcal{G}_s \to \mathbb{F}$ is *equivariant* if $f(\sigma \star G, \sigma \star \boldsymbol{v}) = f(G, \boldsymbol{v})$ for any permutation σ. The functions $\mathsf{cr}^{(t)} : \mathcal{G}_1 \to \mathbb{F}$ and $\mathsf{vwl}_k^{(t)} : \mathcal{G}_1 \to \mathbb{F}$ are equivariant, whereas $\mathsf{gcr}^{(t)} : \mathcal{G}_0 \to \mathbb{F}$ and $\mathsf{gwl}_k^{(t)} : \mathcal{G}_0 \to \mathbb{F}$ are invariant, for any $t \geq 0$ and $k \geq 1$.

3 SPECIFYING GNNS

Many GNN architectures are described in terms of linear algebra computations on vectors, matrices or tensors, interleaved with the application of activation functions or multilayer perceptrons (MLPs). We aim at understanding the separation power of GNNs, without being tied to a specific GNN architecture. In order to do so, in this section, we introduce a specification language in which many GNN architectures can be represented. We dub this language, TL, for tensor language. The idea of this language is to express algebraic computations in a more procedural way by specifying algebraic operations over tensors by explicitly stating how each entry is to be computed.

As an example, consider a typical layer in a GNN of the form $\boldsymbol{F}' = \sigma(\boldsymbol{A} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$, where $\boldsymbol{A} \in \mathbb{R}^{n \times n}$ is an adjacency matrix, $\boldsymbol{F} \in \mathbb{R}^{n \times \ell}$ are vertex features such that $\boldsymbol{F}_{i:} \in \mathbb{R}^\ell$ is the feature vector of vertex i, σ is a non-linear activation function, and $\boldsymbol{W} \in \mathbb{R}^{\ell \times \ell}$ is a weight matrix. By exposing the indices in the matrices and vectors we can equivalently write: for $i \in [n]$ and $s \in [\ell]$:

$$F'_{is} := \sigma\Big(\sum_{j \in [n]} A_{ij} \cdot \big(\sum_{t \in [\ell]} W_{ts} \cdot F_{jt}\big)\Big).$$

In TL, we do not work with specific matrices or indices ranging over $[n]$, but focus instead on expressions applicable to any matrix. We use index variables x_1 and x_2 instead of i and j, replace A_{ij} with a placeholder $E(x_1, x_2)$ and F_{jt} with placeholders $P_t(x_2)$, for $t \in [\ell]$. We then represent the above computation in TL by ℓ expressions $\psi_s(x_1)$, one for each feature column, as follows:

$$\psi_s(x_1) = \sigma\Big(\sum_{x_2} E(x_1, x_2) \cdot \big(\sum_{t \in [\ell]} W_{ts} \cdot P_t(x_2)\big)\Big).$$

These are pure syntactical expressions. To give them a semantics, we assign to E a matrix $\boldsymbol{A} \in \mathbb{R}^{n \times n}$, to P_t column vectors $\boldsymbol{F}_{:t} \in \mathbb{R}^{n \times 1}$, for $t \in [\ell]$, and to x_1 an index $i \in [n]$. By letting the variable x_2 under the summation range over $1, 2, \ldots, n$, the TL expression $\psi_s(i)$ evaluates to F'_{is}. As such, $\boldsymbol{F}' = \sigma(\boldsymbol{A} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$ can be represented as a specific instance of the above TL expressions. Throughout the paper we reason about expressions in TL rather than specific instances thereof. Importantly, by showing that certain properties hold for expressions in TL, these properties are inherited by all of its instances. We use TL to enable a theoretical analysis of the separating power of GNNs; It is not intended as a practical programming language for GNNs. The language TL is inspired by recent work on matrix query languages (Brijder et al., 2019; Geerts, 2021; Geerts et al., 2021b).

Syntax. We first give the complete syntax of TL expressions. We have a binary predicate E, to represent adjacency matrices, and unary vertex predicates P_s, $s \in S$, to represent vectors, hot-one encoding vertex labels. In addition, we have a (possibly infinite) set Ω of (non-linear) functions, such as activation functions or MLPs. Then, $\mathsf{TL}(\Omega)$ expressions are defined by the following grammar:

$$\varphi := \mathbf{1}_{x \,\mathsf{op}\, y} \mid E(x, y) \mid P_s(x) \mid \varphi \cdot \varphi \mid \varphi + \varphi \mid a \cdot \varphi \mid f(\varphi, \ldots, \varphi) \mid \textstyle\sum_x \varphi$$

where $\mathsf{op} \in \{=, \neq\}$, x, y are index variables that specify entries in tensors, $s \in S$, $a \in \mathbb{R}$, and $f \in \Omega$. We sometimes make explicit which functions are used in expressions in $\mathsf{TL}(\Omega)$ by writing $\mathsf{TL}(f_1, f_2, \ldots)$ for $f_1, f_2, \ldots$ in Ω. For example, the expressions $\psi_s(x_1)$ are in $\mathsf{TL}(\sigma)$.

The set of *free index variables* of an expression φ, denoted by $\mathsf{free}(\varphi)$, determines the order of the tensor represented by φ. It is defined inductively: $\mathsf{free}(\mathbf{1}_{x \,\mathsf{op}\, y}) = \mathsf{free}(E(x, y)) := \{x, y\}$, $\mathsf{free}(P_s(x)) = \{x\}$, $\mathsf{free}(\varphi_1 \cdot \varphi_2) = \mathsf{free}(\varphi_1 + \varphi_2) := \mathsf{free}(\varphi_1) \cup \mathsf{free}(\varphi_2)$, $\mathsf{free}(a \cdot \varphi_1) := \mathsf{free}(\varphi_1)$, $\mathsf{free}(f(\varphi_1, \ldots, \varphi_p)) := \cup_{i \in [p]} \mathsf{free}(\varphi_i)$, and $\mathsf{free}(\sum_x \varphi_1) := \mathsf{free}(\varphi_1) \setminus \{x\}$. We sometimes explicitly write the free indices. In our example expressions $\psi_s(x_1)$, x_1 is the free index variable.

An important class of expressions are those that only use index variables $\{x_1, \ldots, x_k\}$. We denote by $\mathsf{TL}_k(\Omega)$ the *k-index variable fragment* of $\mathsf{TL}(\Omega)$. The expressions $\psi_s(x_1)$ are in $\mathsf{TL}_2(\sigma)$.

Semantics. We next define the semantics of expressions in $\mathsf{TL}(\Omega)$. Let $G = (V_G, E_G, \mathsf{col}_G)$ be a vertex-labelled graph. We start by defining the *interpretation* $\pi_G[\![\cdot, \nu]\!]$ of the predicates E, P_s and the (dis)equality predicates, relative to G and a *valuation* ν assigning a vertex to each index variable:

$$\pi_G[\![E(x, y), \nu]\!] := \text{if } \nu(x)\nu(y) \in E_G \text{ then } 1 \text{ else } 0$$
$$\pi_G[\![P_s(x), \nu]\!] := \mathsf{col}_G(\nu(x))_s$$
$$\pi_G[\![\mathbf{1}_{x \,\mathsf{op}\, y}, \nu]\!] := \text{if } \nu(x) \,\mathsf{op}\, \nu(y) \text{ then } 1 \text{ else } 0.$$

In other words, E is interpreted as the adjacency matrix of G and the P_s's interpret the vertex-labelling col_G. Furthermore, we lift interpretations to arbitrary expressions in $\mathsf{TL}(\Omega)$, as follows:

$$\pi_G[\![\varphi_1 \cdot \varphi_2, \nu]\!] := \pi_G[\![\varphi_1, \nu]\!] \cdot \pi_G[\![\varphi_2, \nu]\!] \qquad \pi_G[\![\varphi_1 + \varphi_2, \nu]\!] := \pi_G[\![\varphi_1, \nu]\!] + \pi_G[\![\varphi_2, \nu]\!]$$
$$\pi_G[\![\textstyle\sum_x \varphi_1, \nu]\!] := \textstyle\sum_{v \in V_G} \pi_G[\![\varphi_1, \nu[x \mapsto v]]\!] \qquad \pi_G[\![a \cdot \varphi_1, \nu]\!] := a \cdot \pi_G[\![\varphi_1, \nu]\!]$$
$$\pi_G[\![f(\varphi_1, \ldots, \varphi_p), \nu]\!] := f(\pi_G[\![\varphi_1, \nu]\!], \ldots, \pi_G[\![\varphi_p, \nu]\!])$$

where, $\nu[x \mapsto v]$ is the valuation ν but which now maps the index x to the vertex $v \in V_G$. For simplicity, we identify valuations with their images. For example, $\pi_G[\![\varphi(x), v]\!]$ denotes $\pi_G[\![\varphi_1(x), x \mapsto v]\!]$. To illustrate the semantics, for each $v \in V_G$, $\pi_G[\![\psi_s, v]\!] = F'_{vs}$ for $\boldsymbol{F}' = \sigma(\boldsymbol{A} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$ when $\boldsymbol{A}$ is the adjacency matrix of G and $\boldsymbol{F}$ hot-one encodes the vertex labels.

Representing GNNs. Consider a function $f : \mathcal{G}_s \to \mathbb{R}^\ell : (G, \boldsymbol{v}) \mapsto f(G, \boldsymbol{v}) \in \mathbb{R}^\ell$ for some $\ell \in \mathbb{N}$. We say that the function f *can be represented in* $\mathsf{TL}(\Omega)$, if there exists ℓ expressions $\varphi_1(x_1, \ldots, x_s), \ldots, \varphi_\ell(x_1, \ldots, x_s)$ in $\mathsf{TL}(\Omega)$ such that for each graph G and each s-tuple $\boldsymbol{v} \in V_G^s$:

$$f(G, \boldsymbol{v}) = \big(\pi_G[\![\varphi_1, \boldsymbol{v}]\!], \ldots, \pi_G[\![\varphi_\ell, \boldsymbol{v}]\!]\big).$$

When f is described in terms of a GNN, we say that the GNN *can be represented in* $\mathsf{TL}(\Omega)$. For example, we can interpret $\boldsymbol{F}' = \sigma(\boldsymbol{A} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$ as a function $f : \mathcal{G}_1 \to \mathbb{R}^\ell$, such that $f(G, v) := \boldsymbol{F}'_{v:}$. We have seen that for each $s \in [\ell]$, $\pi_G[\![\psi_s, v]\!] = F'_{vs}$. Hence, $f(G, v) = (\pi_G[\![\psi_1, v]\!], \ldots, \pi_G[\![\psi_\ell, v]\!])$ and thus f (that is, $\boldsymbol{F}' = \sigma(\boldsymbol{A} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$) can be represented in $\mathsf{TL}(\Omega)$. Most functions corresponding to GNNs can be represented in $\mathsf{TL}(\Omega)$, as will be illustrated later in the paper.

TL represents equivariant or invariant functions. We make a simple observation which follows from the type of operators allowed in expressions in $\mathsf{TL}(\Omega)$.

Proposition 3.1. *Any function* $f : \mathcal{G}_s \to \mathbb{R}^\ell$ *that can be represented in* $\mathsf{TL}(\Omega)$ *is equivariant (or invariant if* $s = 0$*).*

An immediate consequence is that when a GNN can be represented in $\mathsf{TL}(\Omega)$ it is automatically invariant or equivariant, depending on whether graph or vertex tuple embeddings are considered.

4 SEPARATION POWER OF TENSOR LANGUAGES

Our first main results concern the characterization of the separation power of tensor languages in terms of the color refinement and k-dimensional Weisfeiler-Leman algorithms. We provide a fine-grained characterization by taking the number of rounds of these algorithms into account. This will allow for measuring the separation power of classes of GNNs in terms of their number of layers.

4.1 SEPARATION POWER

We define the separation power of graph functions in terms of an equivalence relation, based on the definition from Azizian & Lelarge (2021), hereby first focusing on their ability to separate vertices.[1]

Definition 1. Let $\mathcal{F}$ be a set of functions $f : \mathcal{G}_1 \to \mathbb{R}^{\ell_f}$. *The equivalence relation* $\rho_1(\mathcal{F})$ *is defined by* $\mathcal{F}$ *on* $\mathcal{G}_1$ *as follows: For any* (G, v) *and* (H, w) *in* $\mathcal{G}_1$:

$$\big((G, v), (H, w)\big) \in \rho_1(\mathcal{F}) \iff \forall f \in \mathcal{F}, f(G, v) = f(H, w).$$

In other words, when $((G, v), (H, w)) \in \rho_1(\mathcal{F})$, no function in $\mathcal{F}$ can separate v in G from w in H. For example, we can view $\mathsf{cr}^{(t)}$ and $\mathsf{vwl}_k^{(t)}$ as functions from $\mathcal{G}_1$ to some $\mathbb{R}^\ell$. As such $\rho_1(\mathsf{cr}^{(t)})$ and $\rho_1(\mathsf{vwl}_k^{(t)})$ measure the separation power of these algorithms. The following strict inclusions are known: for all $k \geq 1$, $\rho_1(\mathsf{vwl}_{k+1}^{(t)}) \subset \rho_1(\mathsf{vwl}_k^{(t)})$ and $\rho_1(\mathsf{vwl}_1^{(t)}) \subset \rho_1(\mathsf{cr}^{(t)})$ (Otto, 2017; Grohe, 2021). It is also known that more rounds (t) increase the separation power of these algorithms (Fürer, 2001).

For a fragment $\mathcal{L}$ of $\mathsf{TL}(\Omega)$ expressions, we define $\rho_1(\mathcal{L})$ as the equivalence relation associated with all functions $f : \mathcal{G}_1 \to \mathbb{R}^{\ell_f}$ that can be represented in $\mathcal{L}$. By definition, we here thus consider expressions in $\mathsf{TL}(\Omega)$ with one free index variable resulting in vertex embeddings.

4.2 MAIN RESULTS

We first provide a link between k-WL and tensor language expressions using $k + 1$ index variables:

Theorem 4.1. *For each* $k \geq 1$ *and any collection* Ω *of functions,* $\rho_1\big(\mathsf{vwl}_k^{(\infty)}\big) = \rho_1\big(\mathsf{TL}_{k+1}(\Omega)\big)$.

This theorem already gives us new insights: if we wish to understand how a new GNN architecture compares against the k-WL algorithms, all we need to do is to show that such an architecture can be represented in $\mathsf{TL}_{k+1}(\Omega)$, an arguably much easier endeavor. However, we can do much more. We next present finer separation results that relate the rounds of k-WL to the notion of summation depth of $\mathsf{TL}(\Omega)$ expressions, and we present similar results for functions computing graph embeddings.

The *summation depth* $\mathsf{sd}(\varphi)$ of a $\mathsf{TL}(\Omega)$ expression φ measures the nesting depth of the summations $\sum_x$ in the expression. It is defined inductively: $\mathsf{sd}(\mathbf{1}_{x\,\mathsf{op}\,y}) = \mathsf{sd}(E(x, y)) = \mathsf{sd}(P_s(x)) := 0$, $\mathsf{sd}(\varphi_1 \cdot \varphi_2) = \mathsf{sd}(\varphi_1 + \varphi_2) := \max\{\mathsf{sd}(\varphi_1), \mathsf{sd}(\varphi_2)\}$, $\mathsf{sd}(a \cdot \varphi_1) := \mathsf{sd}(\varphi_1)$, $\mathsf{sd}(f(\varphi_1, \ldots, \varphi_p)) := \max\{\mathsf{sd}(\varphi_i) | i \in [p]\}$, and $\mathsf{sd}(\sum_x \varphi_1) := \mathsf{sd}(\varphi_1) + 1$. As an example, our expressions $\psi_s(x_1)$ from before have a summation depth of one. We write $\mathsf{TL}_k^{(t)}(\Omega)$ for the class of expressions in $\mathsf{TL}_k(\Omega)$ of summation depth at most t.

We can now refine Theorem 4.1, taking into account the number of rounds used in k-WL.

Theorem 4.2. *For all* $t \geq 0$, $k \geq 1$ *and any collection* Ω *of functions,* $\rho_1\big(\mathsf{vwl}_k^{(t)}\big) = \rho_1\big(\mathsf{TL}_{k+1}^{(t)}(\Omega)\big)$.

---

[1]We differ slightly from Azizian & Lelarge (2021) in that they only define equivalence relations on graphs.

Proof. We use connections between the separation power of k-WL and the separation power of C_{k+1}, the $(k+1)$-variable fragment of first-order logic with counting quantifiers, as shown in the seminal works by Immerman & Lander (1990) and Cai et al. (1992). To make the connection between these logics and tensor languages, we translate expressions in $\mathsf{TL}_{k+1}(\Omega)$ into logical formulae in the *infinitary* counterpart of C_{k+1}, which extends C_{k+1} with uncountably many disjunctions and conjunctions. This allows us to express any function application or arithmetic computation. Finally, we argue that the separation power of these infinitary versions coincides with the power of their standard counterparts. We thus obtain that C_{k+1} is more separating than $\mathsf{TL}_{k+1}(\Omega)$, hereby providing the desired link to k-WL. Furthermore, we provide expressions in TL_{k+1} that simulate formulae in C_{k+1}, hereby establishing that $\mathsf{TL}_{k+1}(\Omega)$ is also more separating than k-WL, for any Ω. $\qquad\square$

Guarded TL and color refinement. As noted by Barceló et al. (2020), the separation power of vertex embeddings of simple GNNs, which propagate information only through neighboring vertices, is usually weaker than that of 1-WL. For these types of architectures, Barceló et al. (2020) provide a relation with the weaker color refinement algorithm, but only in the special case of *first-order* classifiers. We can recover and extend this result in our general setting, with a *guarded* version of TL which, as we will show, has the same separation power as color refinement.

The *guarded fragment* $\mathsf{GTL}(\Omega)$ of $\mathsf{TL}_2(\Omega)$ is inspired by how adjacency matrices are used in common GNN architectures. In this fragment only equality predicates $\mathbf{1}_{x_i = x_i}$ (constant 1) and $\mathbf{1}_{x_i \neq x_i}$ (constant 0) are allowed, addition and multiplication require the component expressions to have the same (single) free index, and summation must occur in a *guarded form* $\sum_{x_j}\big(E(x_i, x_j) \cdot \varphi(x_j)\big)$, for $i, j \in [2]$. Intuitively, guardedness means that summation only happens over neighbors. In this fragment, all expressions have a single free variable and thus only functions from $\mathcal{G}_1$ can be represented. Our example expressions $\psi_s(x_1)$ are guarded. The fragment $\mathsf{GTL}^{(t)}(\Omega)$ consists of expressions in $\mathsf{GTL}(\Omega)$ of summation depth at most t, just as before.

Theorem 4.3. *For all $t \geq 0$ and any collection Ω of functions:* $\rho_1\big(\mathsf{cr}^{(t)}\big) = \rho_1\big(\mathsf{GTL}^{(t)}(\Omega)\big)$.

We recall that $\rho_1\big(\mathsf{vwl}_1^{(t)}\big) \subset \rho_1\big(\mathsf{cr}^{(t)}\big)$ which, combined with the previous two theorems, implies that $\mathsf{TL}_2^{(t)}(\Omega)$ is strictly more separating than $\mathsf{GTL}^{(t)}(\Omega)$.

Graph embeddings. We next establish connections between the graph versions of k-WL and CR, and TL expressions without free index variables. To this aim, we use $\rho_0(\mathcal{F})$, for a set $\mathcal{F}$ of functions $f : \mathcal{G} \to \mathbb{R}^{\ell_f}$, as the equivalence relation over $\mathcal{G}$ defined in analogy to ρ_1:

$$(G, H) \in \rho_0(\mathcal{F}) \iff \forall f \in \mathcal{F}, f(G) = f(H).$$

We thus consider separation power on the graph level. For example, we can consider $\rho_0(\mathsf{gcr}^{(t)})$ and $\rho_0\big(\mathsf{gwl}_k^{(t)}\big)$ for any $t \geq 0$ and $k \geq 1$. Also here, $\rho_0\big(\mathsf{gwl}_{k+1}^{(t)}\big) \subset \rho_0\big(\mathsf{gwl}_k^{(t)}\big)$ but different from vertex embeddings, $\rho_0(\mathsf{gcr}^{(t)}) = \rho_0\big(\mathsf{gwl}_1^{(t)}\big)$ (Grohe, 2021). We define $\rho_0(\mathcal{L})$ for a fragment $\mathcal{L}$ of $\mathsf{TL}(\Omega)$ by considering expressions without free index variables resulting in graph embeddings.

Also here, the connection between the number of index variables in expressions and k-WL holds. Apart from $k = 1$, no clean relationship exists between summation depth and rounds, however.[2]

Theorem 4.4. *For all $t \geq 0$, $k \geq 1$ and any collection Ω of functions, we have that:*

(1) $\quad \rho_0\big(\mathsf{gcr}^{(t)}\big) = \rho_0\big(\mathsf{TL}_2^{(t+1)}(\Omega)\big) = \rho_0\big(\mathsf{gwl}_1^{(t)}\big) \qquad$ *(2)* $\quad \rho_0\big(\mathsf{gwl}_k^{(\infty)}\big) = \rho_0\big(\mathsf{TL}_{k+1}(\Omega)\big)$.

Intuitively, in (1) the increase in summation depth by one is incurred by the additional aggregation needed to collect all vertex labels computed by $\mathsf{gwl}_1^{(t)}$.

Optimality of number of indices. Our results so far tell that graph functions represented in $\mathsf{TL}_{k+1}(\Omega)$ are at most as separating as k-WL. What is left unaddressed is whether all $k+1$ index variables are needed for the graph functions under consideration. It may well be, for example, that there exists an equivalent expression using less index variables. This would imply a stronger upper bound on the separation power by ℓ-WL for $\ell < k$. We next identify a large class of $\mathsf{TL}(\Omega)$ expressions, those of *treewidth k*, for which the number of index variables can be reduced to $k+1$.

---

[2] Indeed, the best one can obtain for general tensor logic expressions is $\rho_0\big(\mathsf{TL}_{k+1}^{(t+k)}(\Omega)\big) \subseteq \rho_0\big(\mathsf{gwl}_k^{(t)}\big) \subseteq \rho_0\big(\mathsf{TL}_{k+1}^{(t+1)}(\Omega)\big)$. This follows again from Cai et al. (1992) and our connection to finite variable logics.

Proposition 4.5. *Expressions in* $\mathsf{TL}(\Omega)$ *of treewidth k are equivalent to expressions in* $\mathsf{TL}_{k+1}(\Omega)$.

Treewidth is defined in the supplementary material. Intuitively, treewidth k implies that the computation of tensor language expressions can be decomposed, by reordering summations, such that each local computation requires at most $k + 1$ indices. This is similar to the generalized distributive law approach for optimizing computations by Aji & McEliece (2000) (see also Abo Khamis et al. (2016) for a more recent account). As a simple example, consider $\theta(x_1) = \sum_{x_2} \sum_{x_3} E(x_1, x_2) \cdot E(x_2, x_3)$ in $\mathsf{TL}_3^{(2)}$ such that $\pi_G[\![\theta, v]\!]$ counts the number of paths of length two starting from v. This expression has a treewidth of one. And indeed, it is equivalent to the expression $\tilde{\theta}(x_1) = \sum_{x_2} E(x_1, x_2) \cdot \left(\sum_{x_1} E(x_2, x_1) \right)$ in $\mathsf{TL}_2^{(2)}$ (and in fact in $\mathsf{GTL}^{(2)}$). As a consequence, no more vertices can be separated by $\theta(x_1)$ than by $\mathsf{cr}^{(2)}$, rather than vwl_2^2 as the original expression in $\mathsf{TL}_3^{(2)}$ suggests.

5 CONSEQUENCES FOR GNNS

We next interpret the general results on the separation power from Section 4 in the context of GNNs.

1. The separation power of any GNN *vertex embedding architecture that can be represented in* $\mathsf{GTL}^{(t)}(\Omega)$ *is bounded by the power of t rounds of color refinement.*

As example, we consider the Graph Isomorphism Networks (GINs) (Xu et al., 2019). A $\mathsf{gin} \in \mathsf{GIN}$ operates as follows. Initially, let $\ell_0 = \ell$ be the number of distinct vertex labels. Then, $\mathsf{gin}^{(0)} : \mathcal{G}_1 \to \mathbb{R}^{\ell_0} : (G, v) \mapsto \boldsymbol{F}_{v:}^{(0)} := \mathsf{col}_G(v) \in \mathbb{R}^{\ell_0}$. For layer $t > 0$, $\mathsf{gin}^{(t)} : \mathcal{G}_1 \to \mathbb{R}^{\ell_t}$ is given by:

$$(G, v) \mapsto \boldsymbol{F}_{v:}^{(t)} := \mathsf{mlp}^{(t)}\big(\boldsymbol{F}_{v:}^{(t-1)}, \textstyle\sum_{u \in N_G(v)} \boldsymbol{F}_{u:}^{(t-1)} \big),$$

with $\boldsymbol{F}^{(t)} \in \mathbb{R}^{n \times \ell_t}$ and $\mathsf{mlp}^{(t)} = (\mathsf{mlp}_1^{(t)}, \ldots, \mathsf{mlp}_{\ell_t}^{(t)}) : \mathbb{R}^{2\ell_{t-1}} \to \mathbb{R}^{\ell_t}$ is an MLP. We denote by $\mathsf{GIN}^{(t)}$ the class of GINs consisting t layers. Clearly, $\mathsf{gin}^{(0)}$ can be represented in $\mathsf{GTL}^{(0)}$ by defining for each $s \in [\ell_0]$, $\varphi_s^{(0)}(x_1) := P_s(x_1)$. Assume that we have ℓ_{t-1} expressions $\varphi_i^{(t-1)}(x_1)$ in $\mathsf{GTL}^{(t-1)}(\Omega)$ representing $\mathsf{gin}^{(t-1)}$. Then $\mathsf{gin}^{(t)}$ is represented by ℓ_t expressions $\varphi_s^{(t)}(x_1)$ defined as:

$$\mathsf{mlp}_s^{(t)}\Big(\varphi_1^{(t-1)}(x_1), \ldots, \varphi_{\ell_{t-1}}^{(t-1)}(x_1), \textstyle\sum_{x_2} E(x_1, x_2) \cdot \varphi_1^{(t-1)}(x_2), \ldots, \sum_{x_2} E(x_1, x_2) \cdot \varphi_{\ell_{t-1}}^{(t-1)}(x_2) \Big),$$

which are now expressions in $\mathsf{GTL}^{(t)}(\Omega)$ where Ω consists of MLPs. As a consequence, Theorem 4.3 tells that t-layered GINs cannot be more separating than t rounds of color refinement, in accordance with known results (Xu et al., 2019; Morris et al., 2019). We thus simply cast GINs in $\mathsf{GTL}(\Omega)$ to obtain an upper bound on their separation power. In the supplementary material we provide a similar analysis for "basic" GNNs (Hamilton et al., 2017), for GCNs (Kipf & Welling, 2017), resulting in an upper bound by $t + 1$ color refinement rounds, and simplified GCNs (SGCs) (Wu et al., 2019).

2. The separation power of any GNN *vertex embedding architecture that can be represented in* $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ *is bounded by the power of t rounds of k-WL.*

As example, for $k = 1$, we consider extended Graph Isomorphism Networks (eGINs) (Barceló et al., 2020). For an $\mathsf{egin} \in \mathsf{eGIN}$, $\mathsf{egin}^{(0)} : \mathcal{G}_1 \to \mathbb{R}^{\ell_0}$ is defined as for GINs, but for layer $t > 0$, $\mathsf{egin}^{(t)} : \mathcal{G}_1 \to \mathbb{R}^{\ell_t}$ is defined by

$$(G, v) \mapsto \boldsymbol{F}_{v:}^{(t)} := \mathsf{mlp}^{(t)}\big(\boldsymbol{F}_{v:}^{(t-1)}, \textstyle\sum_{u \in N_G(v)} \boldsymbol{F}_{u:}^{(t-1)}, \sum_{u \in V_G} \boldsymbol{F}_{u:}^{(t-1)} \big),$$

where $\mathsf{mlp}^{(t)}$ is now an MLP from $\mathbb{R}^{3\ell_{t-1}} \to \mathbb{R}^{\ell_t}$. We cannot represent such a layer in $\mathsf{GTL}(\Omega)$ due to the presence of $\sum_{u \in V_G} \boldsymbol{F}_{u:}^{(t-1)}$ which corresponds to $\sum_{x_1} \varphi^{(t-1)}(x_1)$ in $\mathsf{TL}(\Omega)$. However, in a similar way as for GINs, we can represent these layers in $\mathsf{TL}_2^{(t)}(\Omega)$. Theorem 4.2 tells that t rounds of 1-WL bound the separation power of t-layered extended GINs, conform to Barceló et al. (2020).

For $k \geq 2$, it is straightforward to show that t-layered "folklore" GNNs (k-FGNNs) (Maron et al., 2019b) can be represented in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ and thus, by Theorem 4.2, t rounds of k-WL bound their separation power. Indeed, it merely requires to cast the layer definitions in $\mathsf{TL}(\Omega)$ and observe that $k + 1$ indices and summation depth t are needed. This implies the result by Azizian & Lelarge (2021) showing that k-WL bounds the power of k-FGNNs, when the number of rounds and layers are unbounded. As another example, we show that the separation power of $(k + 1)$-Invariant Graph Networks ($(k + 1)$-IGNs) (Maron et al., 2019b) are also bounded by k-WL, albeit with an increase in the required rounds. More specifically, we show the following.

Theorem 5.1. *For any $k \geq 1$, the separation power of a t-layered $(k+1)$-IGNs is bounded by the separation power of tk rounds of k-WL.*

We hereby answer an open problem (Problem 1) posed in Maron et al. (2019a). The case $k = 1$ was solved in Chen et al. (2020) by analyzing properties of 1-WL. By contrast, Theorem 4.2 shows that one can focus on expressing $(k+1)$-IGNs in $\mathsf{TL}_{k+1}(\Omega)$ and analyzing the summation depth of expressions. The proof of Theorem 5.1 requires non-trivial manipulations of tensor language expressions; it is a simplified proof of (anonymous). The additional rounds (tk) are needed because $(k+1)$-IGNs aggregate information in one layer that becomes accessible to k-WL in k rounds. We provide all details in the supplementary material, where we also identify a simple class of t-layered $(k+1)$-IGNs that are as powerful as $(k+1)$-IGNs but whose separation power is bounded by t rounds of k-WL. In the supplementary material, we discuss how the separation power of other GNN extensions can be obtained using our approach, such as, for example, simplicial GNNs (Bodnar et al., 2021).

***3. The separation power of any* GNN *graph embedding architecture that can be represented in* $\mathsf{TL}_{k+1}(\Omega)$ *is bounded by the power of* k-WL.**

Graph embedding methods are commonly obtained from vertex (tuple) embeddings methods by including a readout layer in which all vertex (tuple) embeddings are aggregated. For example, $\mathsf{mlp}(\sum_{v \in V} \mathsf{egin}^{(t)}(G, v))$ is a typical readout layer for eGINs . Since $\mathsf{egin}^{(t)}$ can be represented in $\mathsf{TL}_2^{(t)}(\Omega)$, the readout layer can be represented in $\mathsf{TL}_2^{(t+1)}(\Omega)$, using an extra summation. Hence, their separation power is bounded by $\mathsf{gwl}_1^{(t)}$, in accordance with Theorem 4.4. This holds more generally. If a vertex (tuple) embedding method can be represented in $\mathsf{TL}_{k+1}(\Omega)$, then the same holds for their graph versions, which are then bounded by $\mathsf{gwl}_k^{(\infty)}$ by our Theorem 4.4.

***4. To go beyond the separation power of* k-WL*, it is necessary to use* GNNs *whose layers are represented by expressions of treewidth* $> k$.**

In particular, this means that to increase the separation power of a GNN it does not suffice to increase the number of layers: one needs to increase them in a way that the treewidth of the resulting TL expression also increases. This sheds light on another open problem from Maron et al. (2019a) where it was asked whether polynomial layers (in $\boldsymbol{A}$) increase the separation power.

As example, consider an architecture of the form $\sigma(\boldsymbol{A}^3 \cdot \boldsymbol{F} \cdot \boldsymbol{W})$, using the adjacency matrix $\boldsymbol{A}$ raised to the power three. A naive representation results in expressions in $\mathsf{TL}(\Omega)$ containing $\sum_{x_2} \sum_{x_3} \sum_{x_4} E(x_1, x_2) \cdot E(x_2, x_3) \cdot E(x_3, x_4)$. The variables involved form a path resulting in the expressions having a treewidth of one. As a consequence of Proposition 4.5, such an architectures is bounded already by $\mathsf{wl}_1^{(3)}$ (and in fact by $\mathsf{cr}^{(3)}$) in separation power. On the other hand, consider a layer of the form $\sigma(\boldsymbol{C} \cdot \boldsymbol{F} \cdot \boldsymbol{W})$ where C_{ij} holds the number of cliques containing the edge ij. Then, in $\mathsf{TL}(\Omega)$ we get expressions containing $\sum_{x_2} \sum_{x_3} E(x_1, x_2) \cdot E(x_1, x_3) \cdot E(x_2, x_3)$. The variables form a 3-clique resulting in expressions of treewidth two. As a consequence, the separation power will be bounded by $\mathsf{wl}_2^{(2)}$. These examples show that it is not the number of multiplications (in both cases two) that gives power, it is how the variables are connected to each other.

6 FUNCTION APPROXIMATION

We next provide characterizations of the invariant or equivariant functions that can be approximated by TL expressions, when interpreted as functions. In combination with our separation results, we recover and extend results from Azizian & Lelarge (2021) regarding approximation properties of GNNs. In particular, our results take the number of layers of GNNs into account, and we also provide new results in the context of color refinement.

6.1 GENERAL TL APPROXIMATION RESULTS

Let $\mathcal{F}$ be a set of functions $f : \mathcal{G}_s \to \mathbb{R}^{\ell_f}$ and define its closure $\overline{\mathcal{F}}$ as all functions h from $\mathcal{G}_s$ for which there exists a sequence $f_1, f_2, \ldots \in \mathcal{F}$ such that $\lim_{i \to \infty} \sup_{G, \boldsymbol{v}} \|f_i(G, \boldsymbol{v}) - h(G, \boldsymbol{v})\| = 0$ for some norm $\|.\|$. We assume $\mathcal{F}$ to satisfy two properties. First, $\mathcal{F}$ is *concatenation-closed*: if $f_1 : \mathcal{G}_s \to \mathbb{R}^p$ and $f_2 : \mathcal{G}_s \to \mathbb{R}^q$ are in $\mathcal{F}$, then $g := (f_1, f_2) : \mathcal{G}_s \to \mathbb{R}^{p+q} : (G, \boldsymbol{v}) \mapsto (f_1(G, \boldsymbol{v}), f_2(G, \boldsymbol{v}))$ is also in $\mathcal{F}$. Second, $\mathcal{F}$ is *function-closed*, for a fixed $\ell \in \mathbb{N}$: for any $f \in \mathcal{F}$ such that $f : \mathcal{G}_s \to \mathbb{R}^p$, also $g \circ f : \mathcal{G}_s \to \mathbb{R}^\ell$ is in $\mathcal{F}$ for any continuous function $g : \mathbb{R}^p \to \mathbb{R}^\ell$.

For such $\mathcal{F}$, we let $\mathcal{F}_\ell$ be the subset of functions in $\mathcal{F}$ from $\mathcal{G}_s$ to $\mathbb{R}^\ell$. Our next result is based on a generalized Stone-Weierstrass Theorem (Timofte, 2005), also used in Azizian & Lelarge (2021).

Theorem 6.1. *For any ℓ, and any set $\mathcal{F}$ of functions, concatenation and function closed for ℓ, we have:* $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_s \to \mathbb{R}^\ell \mid \rho_s(\mathcal{F}) \subseteq \rho_s(f)\}$.

This result gives us insight on which functions can be approximated by, for example, a set $\mathcal{F}$ of functions originating from a class of GNNs. In this case, $\overline{\mathcal{F}_\ell}$ represent all functions approximated by instances of such a class and Theorem 6.1 tells us that this set corresponds precisely to the set of all functions that are equally or less separating than the GNNs in this class. If, in addition, $\mathcal{F}_\ell$ is more separating that CR or k-WL, then we can say more. Let $\mathsf{alg} \in \{\mathsf{cr}^{(t)}, \mathsf{gcr}^{(t)}, \mathsf{vwl}_k^{(t)}, \mathsf{gwl}_k^{(\infty)}\}$.

Corollary 6.2. *Under the assumptions of Theorem 6.1 and if $\rho(\mathcal{F}_\ell) = \rho(\mathsf{alg})$, then* $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_s \to \mathbb{R}^\ell \mid \rho(\mathsf{alg}) \subseteq \rho(f)\}$.

We remark that the properties of being concatenation and function-closed are naturally satisfied for sets of functions representable in our tensor languages, as long as Ω contains all continuous functions $g : \mathbb{R}^p \to \mathbb{R}^\ell$, for any p. Furthermore, Lemma 32 in Azizian & Lelarge (2021) implies that we can equivalently populate Ω with all MLPs.

Together with our results in Section 4, the corollary implies that $\mathsf{GTL}^{(t)}(\Omega)$, $\mathsf{TL}_2^{(t+1)}(\Omega)$, $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ or $\mathsf{TL}(\Omega)$, when viewed as functions, can approximate all functions with equal or less separation power than $\mathsf{cr}^{(t)}$, $\mathsf{gcr}^{(t)}$, $\mathsf{vwl}_k^{(t)}$ or $\mathsf{gwl}_k^{(\infty)}$, respectively. Interestingly, Proposition 3.1 tells that the closure necessarily consists of invariant (when $s = 0$) and equivariant (when $s > 0$) functions.

6.2 Consequences for GNNs

All our results combined provide a recipe to guarantee that a given function can be approximated by GNN ***architectures.*** Indeed, let f be a function that is not more separating than $\mathsf{cr}^{(t)}$ (respectively, $\mathsf{gcr}^{(t)}$, $\mathsf{vwl}_k^{(t)}$ or $\mathsf{gwl}_k^{(\infty)}$, for some $k \geq 1$). Most classes of GNNs in the literature are concatenation-closed and allow the application of arbitrary MLPs. Then, f can be approximated by a class of GNNs, as long as these are at least as separating as $\mathsf{GTL}^{(t)}$ (respectively, $\mathsf{TL}_2^{(t+1)}$, $\mathsf{TL}_{k+1}^{(t)}$ or $\mathsf{TL}_{k+1}^{(\infty)}$). This, in turn, amounts to showing that the GNNs can be represented in the corresponding tensor language fragment, and that they can match the corresponding labeling algorithm in separation power.

For example, $\overline{\mathsf{GIN}_\ell^{(t)}}$ contains any function $f : \mathcal{G}_1 \to \mathbb{R}^\ell$ satisfying $\rho_1(\mathsf{cr}^{(t)}) \subseteq \rho_1(f)$; $\overline{\mathsf{eGIN}_\ell^{(t)}}$ any function satisfying $\rho_1(\mathsf{wl}_1^{(t)}) \subseteq \rho_1(f)$; and when extended with a readout layer, their closures consist of functions $f : \mathcal{G}_0 \to \mathbb{R}^\ell$ satisfying $\rho_0(\mathsf{gcr}^{(t)}) = \rho_0(\mathsf{vwl}_1^{(t)}) \subseteq \rho_0(f)$. Also, $\overline{k\text{-}\mathsf{FGNN}_\ell^{(t)}}$ consist of functions f such that $\rho_1(\mathsf{vwl}_k^{(t)}) \subseteq \rho_1(f)$. We thus recover and extend the results by Azizian & Lelarge (2021) by incorporating layer information (t) and by treating color refinement separately from 1-WL for vertex embeddings. We remark, however, that Azizian and Lelarge define equivariant layers of GNNs in a slightly different way. Furthermore, Theorem 5.1 implies that $\overline{(k+1)\text{-}\mathsf{IGN}_\ell}$ consists of functions f satisfying $\rho_1(\mathsf{vwl}_k^{(\infty)}) \subseteq \rho_1(f)$ and $\rho_0(\mathsf{gwl}_k^{(\infty)}) \subseteq \rho_0(f)$, cases left open in Azizian & Lelarge (2021).

All these results follow directly from Corollary 6.2, the fact that the respective classes of GNNs can simulate CR or k-WL (Xu et al., 2019; Barceló et al., 2020; Maron et al., 2019b), and that they can be represented in the corresponding tensor language (Section 4). A further consequence is that we can use these GNNs to approximate functions representable in our tensor languages. For example, $\overline{\mathsf{GIN}_\ell^{(t)}} = \overline{\mathsf{GTL}^{(t)}(\Omega)}$, and similarly for the other classes of GNNs and tensor language fragments.

7 Conclusion

The connection between GNNs and tensor languages allows us to translate our general analysis of tensor languages into a much cleaner understanding of the separation and approximation power of GNNs. In a nutshell, the number of indices and summation depth needed to represent the layers in GNNs determine their separation power in terms of color refinement and k-dimensional Weisfeiler-Leman tests. Our approach, thus, provides a handy toolbox to understand existing and new GNN architectures, and we demonstrate this by recovering several results about the power of GNNs presented recently in the literature, as well as proving some additional results not known before.

ETHICS STATEMENT

The results in this paper do not include misleading claims; their correctness is theoretically verified. Related work is accurately represented.

REFERENCES

Mahmoud Abo Khamis, Hung Q. Ngo, and Atri Rudra. FAQ: Questions Asked Frequently. In *Proceedings of the 35th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems*, PODS, pp. 13–28. ACM, 2016. URL https://doi.org/10.1145/2902251.2902280.

Srinivas M. Aji and Robert J. McEliece. The generalized distributive law. *IEEE Transactions on Information Theory*, 46(2):325–343, 2000. URL https://doi.org/10.1109/18.825794.

Waiss Azizian and Marc Lelarge. Expressive power of invariant and equivariant graph neural networks. In *Proceedings of the International Conference on Learning Representations*, ICLR, 2021. URL https://openreview.net/forum?id=lxHgXYN4bwl.

Pablo Barceló, Egor V Kostylev, Mikael Monet, Jorge Pérez, Juan Reutter, and Juan Pablo Silva. The logical expressiveness of graph neural networks. In *International Conference on Learning Representations*, ICLR, 2020. URL https://openreview.net/forum?id=r1lZ7AEKvB.

Pablo Barceló, Floris Geerts, Juan L. Reutter, and Maksimilian Ryschkov. Graph neural networks with local graph parameters. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://arxiv.org/abs/2106.06707. To appear.

Cristian Bodnar, Fabrizio Frasca, Yuguang Wang, Nina Otter, Guido F. Montúfar, Pietro Lió, and Michael M. Bronstein. Weisfeiler and Lehman go topological: Message passing simplicial networks. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 1026–1037. PMLR, 2021. URL http://proceedings.mlr.press/v139/bodnar21a.html.

Giorgos Bouritsas, Fabrizio Frasca, Stefanos Zafeiriou, and Michael M. Bronstein. Improving graph neural network expressivity via subgraph isomorphism counting. In *Graph Representation Learning and Beyond (GRL+) Workshop at the 37 th International Conference on Machine Learning*, 2020. URL https://arxiv.org/abs/2006.09252.

Robert Brijder, Floris Geerts, Jan Van den Bussche, and Timmy Weerwag. On the expressive power of query languages for matrices. *ACM TODS*, 44(4):15:1–15:31, 2019. URL https://doi.org/10.1145/3331445.

Jin-yi Cai, Martin Fürer, and Neil Immerman. An optimal lower bound on the number of variables for graph identifications. *Comb.*, 12(4):389–410, 1992. URL https://doi.org/10.1007/BF01305232.

Zhengdao Chen, Soledad Villar, Lei Chen, and Joan Bruna. On the equivalence between graph isomorphism testing and function approximation with GNNs. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*. Curran Associates Inc., 2019.

Zhengdao Chen, Lei Chen, Soledad Villar, and Joan Bruna. Can graph neural networks count substructures? In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems*, 2020.

Clemens Damke, Vitalik Melnikov, and Eyke Hüllermeier. A novel higher-order weisfeiler-lehman graph convolution. In *Proceedings of The 12th Asian Conference on Machine Learning, ACML*, volume 129 of *Proceedings of Machine Learning Research*, pp. 49–64. PMLR, 2020. URL http://proceedings.mlr.press/v129/damke20a.html.

Martin Fürer. Weisfeiler-Lehman refinement requires at least a linear number of iterations. In *Proceedings of the 28th International Colloqium on Automata, Languages and Programming, ICALP*, volume 2076 of *Lecture Notes in Computer Science*, pp. 322–333. Springer, 2001. URL https://doi.org/10.1007/3-540-48224-5_27.

Floris Geerts. On the expressive power of linear algebra on graphs. *Theory Comput. Syst.*, 65(1): 179–239, 2021. URL https://doi.org/10.1007/s00224-020-09990-9.

Floris Geerts, Filip Mazowiecki, and Guillermo A. Pérez. Let's agree to degree: Comparing graph convolutional networks in the message-passing framework. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 3640–3649. PMLR, 2021a. URL http://proceedings.mlr.press/v139/geerts21a.html.

Floris Geerts, Thomas Muñoz, Cristian Riveros, and Domagoj Vrgoc. Expressive power of linear algebra query languages. In *Proceedings of the 40th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems, PODS*, pp. 342–354. ACM, 2021b. URL https://doi.org/10.1145/3452021.3458314.

Martin Grohe. The logic of graph neural networks. In *Proceedings of the 36th Annual ACM/IEEE Symposium on Logic in Computer Science, LICS*, pp. 1–17. IEEE, 2021. URL https://doi.org/10.1109/LICS52264.2021.9470677.

William L. Hamilton. Graph representation learning. *Synthesis Lectures on Artificial Intelligence and Machine Learning*, 14(3):1–159, 2020.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems*, volume 30, pp. 1024–1034, 2017.

Neil Immerman and Eric Lander. Describing graphs: A first-order approach to graph canonization. In *Complexity Theory Retrospective: In Honor of Juris Hartmanis on the Occasion of His Sixtieth Birthday*, pp. 59–81. Springer, 1990. URL https://doi.org/10.1007/978-1-4612-4478-3_5.

Nicolas Keriven and Gabriel Peyré. Universal invariant and equivariant graph neural networks. In *Advances in Neural Information Processing Systems 32*, pp. 7092–7101, 2019.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *Proceedings of the 5th International Conference on Learning Representations ICLR*, 2017.

Haggai Maron, Heli Ben-Hamu, and Yaron Lipman. Open problems: Approximation power of invariant graph networks. In *NeurIPS 2019 Graph Representation Learning Workshop*, 2019a. URL https://grlearning.github.io/papers/31.pdf.

Haggai Maron, Heli Ben-Hamu, Hadar Serviansky, and Yaron Lipman. Provably powerful graph networks. In *Advances in Neural Information Processing Systems 32*, pp. 2153–2164, 2019b. URL http://papers.nips.cc/paper/8488-provably-powerful-graph-networks.

Haggai Maron, Heli Ben-Hamu, Nadav Shamir, and Yaron Lipman. Invariant and equivariant graph networks. In *Proceedings of the 7th International Conference on Learning Representations (ICLR)*, 2019c. URL https://openreview.net/forum?id=Syx72jC9tm.

Christian Merkwirth and Thomas Lengauer. Automatic generation of complementary descriptors with molecular graph networks. *J. Chem. Inf. Model.*, 45(5):1159–1168, 2005. URL https://doi.org/10.1021/ci049613b.

H. L. Morgan. The generation of a unique machine description for chemical structures-a technique developed at chemical abstracts service. *Journal of Chemical Documentation*, 5(2):107–113, 1965. URL https://doi.org/10.1021/c160017a018.

Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and Leman go neural: Higher-order graph neural networks. In *Proceedings of the 33rd AAAI Conference on Artificial Intelligence*, pp. 4602–4609, 2019. URL https://doi.org/10.1609/aaai.v33i01.33014602.

Christopher Morris, Gaurav Rattan, and Petra Mutzel. Weisfeiler and Leman go sparse: Towards scalable higher-order graph embeddings. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL https://arxiv.org/abs/1904.01543.

Martin Otto. *Bounded Variable Logics and Counting: A Study in Finite Models*, volume 9 of *Lecture Notes in Logic*. Cambridge University Press, 2017. URL https://doi.org/10.1017/9781316716878.

Martin Otto. Graded modal logic and counting bisimulation. *ArXiv*, 2019. URL https://arxiv.org/abs/1910.00039.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Trans. Neural Networks*, 20(1):61–80, 2009. URL https://doi.org/10.1109/TNN.2008.2005605.

Vlad Timofte. Stone–Weierstrass theorems revisited. *Journal of Approximation Theory*, 136(1): 45–59, 2005. URL https://doi.org/10.1016/j.jat.2005.05.004.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *Proceedings of the 6th International Conference on Learning Representations, ICLR*, 2018. URL https://openreview.net/forum?id=rJXMpikCZ.

Boris J. Weisfeiler and Andrei A. Lehman. A reduction of a graph to a canonical form and an algebra arising during this reduction. *Nauchno-Technicheskaya Informatsiya*, 2(9):12–16, 1968. URL https://www.iti.zcu.cz/wl2018/pdf/wl_paper_translation.pdf.

Felix Wu, Amauri H. Souza Jr., Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Q. Weinberger. Simplifying graph convolutional networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6861–6871. PMLR, 2019. URL http://proceedings.mlr.press/v97/wu19e.html.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *Proceedings of the 7th International Conference on Learning Representations, ICLR*, 2019. URL https://openreview.net/forum?id=ryGs6iA5Km.

SUPPLEMENTARY MATERIAL

A   DETAILS OF SECTION 3

A.1   PROOF OF PROPOSITION 3.1

Let $G = (V, E, \mathsf{col})$ be a graph and let σ be a permutation of V. As usual, we define $\sigma \star G = (V^\sigma, E^\sigma, \mathsf{col}^\sigma)$ as the graph with vertex set $V^\sigma := V$, edge set $vw \in E^\sigma$ if and only if $\sigma^{-1}(v)\sigma^{-1}(w) \in E$, and $\mathsf{col}^\sigma(v) := \mathsf{col}(\sigma^{-1}(v))$. We need to show that for any expression $\varphi(\boldsymbol{x})$ in $\mathsf{TL}(\Omega)$ either $\pi_{\sigma \star G}[\![\varphi, \sigma \star \boldsymbol{v}]\!] = \pi_G[\![\varphi, \boldsymbol{v}]\!]$, or when φ has no free index variables, $\pi_{\sigma \star G}[\![\varphi]\!] = \pi_G[\![\varphi]\!]$. We verify this by a simple induction on the structure of expressions in $\mathsf{TL}(\Omega)$.

- If $\varphi(x_i, x_j) = \mathbf{1}_{x_i \,\mathsf{op}\, x_j}$, then for a valuation ν mapping x_i to v_i and x_j to v_j in V:

$$\pi_G[\![\mathbf{1}_{x_i \,\mathsf{op}\, x_j}, \nu]\!] = \mathbf{1}_{v_i \,\mathsf{op}\, v_j} = \mathbf{1}_{\sigma(v_i) \,\mathsf{op}\, \sigma(v_j)} = \pi_{\sigma \star G}[\![\mathbf{1}_{x_i \,\mathsf{op}\, x_j}, \sigma \star \nu]\!],$$

where we used that σ is a permutation.

- If $\varphi(x_i) = P_\ell(x_i)$, then for a valuation μ mapping x_i to v_i in V:

$$\pi_G[\![P_\ell, \mu]\!] = (\mathsf{col}(v_i))_\ell = (\mathsf{col}^\sigma(\sigma(v_i))_\ell = \pi_{\sigma \star G}[\![P_i, \sigma \star \nu]\!],$$

where we used the definition of col^σ.

- Similarly, if $\varphi(x_i, x_j) = E(x_i, x_j)$, then for a valuation ν assigning x_i to v_i and x_j to v_j:

$$\pi_G[\![\varphi, \nu]\!] = \mathbf{1}_{v_i v_j \in E} = \mathbf{1}_{\sigma(v_i)\sigma(v_j) \in E^\sigma} = \pi_{\sigma \star G}[\![\varphi, \sigma \star \nu]\!],$$

where we used the definition of E^σ.

- If $\varphi(\boldsymbol{x}) = \varphi_1(\boldsymbol{x}_1) \cdot \varphi_2(\boldsymbol{x}_2)$, then for a valuation μ from $\boldsymbol{x}$ to V:

$$\pi_G[\![\varphi, \mu]\!] = \pi_G[\![\varphi_1, \mu]\!] \cdot \pi_G[\![\varphi_2, \mu]\!] = \pi_{\sigma \star G}[\![\varphi_1, \sigma \star \nu]\!] \cdot \pi_{\star G}[\![\varphi_2, \sigma \star \nu]\!] = \pi_{\sigma \star G}[\![\varphi, \sigma \star \nu]\!],$$

where we used the induction hypothesis for φ_1 and φ_2. The cases $\varphi(\boldsymbol{x}) = \varphi_1(\boldsymbol{x}_1) + \varphi_2(\boldsymbol{x}_2)$ and $\varphi(\boldsymbol{x}) = a \cdot \varphi_1(\boldsymbol{x})$ are dealt with in a similar way.

- If $\varphi(\boldsymbol{x}) = f(\varphi_1(\boldsymbol{x}_1), \ldots, \varphi_p(\boldsymbol{x}_p))$, then

$$\begin{aligned}
\pi_G[\![\varphi, \mu]\!] &= f(\pi_G[\![\varphi_1, \mu]\!], \ldots, \pi_G[\![\varphi_p, \mu]\!]) \\
&= f(\pi_{\sigma \star G}[\![\varphi_1, \sigma \star \nu]\!], \ldots, \pi_{\sigma \star G}[\![\varphi_p, \sigma \star \nu]\!]) \\
&= \pi_{\sigma \star G}[\![\varphi, \sigma \star \nu]\!],
\end{aligned}$$

where we used again the induction hypothesis for $\varphi_1, \ldots, \varphi_p$.

- Finally, if $\varphi(\boldsymbol{x}) = \sum_y \varphi_1(\boldsymbol{x}, y)$ then for a valuation ν of $\boldsymbol{x}$ to V:

$$\begin{aligned}
\pi_G[\![\varphi, \mu]\!] &= \sum_{v \in V} \pi_G[\![\varphi_1, \mu[y \mapsto v]]\!] = \sum_{v \in V} \pi_{\sigma \star G}[\![\varphi_1, \sigma \star \nu[y \mapsto v]]\!] \\
&= \sum_{v \in V^\sigma} \pi_{\sigma \star G}[\![\varphi_1, \sigma \star \nu[y \mapsto v]]\!] = \pi_{\sigma \star G}[\![\varphi, \sigma \star \nu]\!],
\end{aligned}$$

where we used the induction hypothesis for φ_1 and that $V^\sigma = V$ because σ is permutation.

We remark that when φ does not contain free index variables, then $\pi_G[\![\varphi, \mu]\!] = \pi_G[\![\varphi]\!]$ for any valuation μ, from which invariance follows from the previous arguments. This concludes the proof of Proposition 3.1.

B   DETAILS OF SECTION 4

B.1   CLASSICAL LOGICS

We start by defining the *k-variable fragment* C^k of first-order logic with counting quantifiers, followed by the definition of the *guarded fragment* GC of C^2. Formulae φ in C^k are defined over the set $\{x_1, \ldots, x_k\}$ of variables and are formed by the following grammar:

$$\varphi := (x_i = x_j) \mid E(x_i, x_j) \mid P_s(x_i) \mid \neg\varphi \mid \varphi \wedge \varphi \mid \exists^{\geq m} x_i\, \varphi,$$

where $i, j \in [k]$, E is a binary predicate, P_s for $s \in S$ are unary predicates and $m \in \mathbb{N}$. The semantics of formulae in C^k is defined in terms of interpretations, denoted by $\pi_G^{\mathbb{B}}$, relative to a given graph G and a (partial) valuation $\mu : \{x_1, \ldots, x_k\} \to V_G$. Such an interpretation maps formulae, graphs and valuations to Boolean values $\mathbb{B} := \{\bot, \top\}$, in a similar way as we did for tensor language expressions.

More precisely, given a graph $G = (V_G, E_G, \mathsf{col}_G)$ and partial valuation $\mu : \{x_1, \ldots, x_k\} \to V_G$, we define $\pi_G^{\mathbb{B}}[\![\varphi, \mu]\!] \in \mathbb{B}$ for valuations defined on the free variables in φ. That is, we define:

$$\pi_G^{\mathbb{B}}[\![x_i = x_j, \mu]\!] := \text{if } \mu(x_i) = \mu(x_j) \text{ then } \top \text{ else } \bot;$$
$$\pi_G^{\mathbb{B}}[\![E(x_i, x_j), \mu]\!] := \text{if } \mu(x_i)\mu(x_j) \in E_G \text{ then } \top \text{ else } \bot;$$
$$\pi_G^{\mathbb{B}}[\![P_s(x_i), \mu]\!] := \text{if } \mathsf{col}_G(\mu(x_i))_s = 1 \text{ then } \top \text{ else } \bot;$$
$$\pi_G^{\mathbb{B}}[\![\neg\varphi, \mu]\!] := \neg\pi_G^{\mathbb{B}}[\![\varphi, \mu]\!];$$
$$\pi_G^{\mathbb{B}}[\![\varphi_1 \wedge \varphi_2, \mu]\!] := \pi_G^{\mathbb{B}}[\![\varphi_1, \mu]\!] \wedge \pi_G^{\mathbb{B}}[\![\varphi_2, \mu]\!];$$
$$\pi_G^{\mathbb{B}}[\![\exists^{\geq m} x_i \, \varphi, \mu]\!] := \text{ if } |\{v \in V_G \mid \pi_G^{\mathbb{B}}[\![\varphi, \mu[x_i \mapsto v]]\!] = \top\}| \geq m \text{ then } \top \text{ else } \bot.$$

In the last expression, $\mu[x_i \mapsto v]$ denotes the valuation μ modified such that it maps x_i to vertex v.

We will also need the *guarded fragment* GC of C^2 in which we only allow equality conditions of the form $x_i = x_i$, component expressions of conjunction and disjunction should have the same single free variable, and counting quantifiers can only occur in guarded form: $\exists^{\geq m} x_2(E(x_1, x_2) \wedge \varphi(x_2))$ or $\exists^{\geq m} x_1(E(x_2, x_1) \wedge \varphi(x_1))$. The semantics of formulae in GC is inherited from formulae in C^2.

Finally, we will also consider $\mathsf{C}^k_{\infty\omega}$, that is, the logic C^k extended with *infinitary disjunctions* and *conjunctions*. More precisely, we add to the grammar of formulae the following constructs:

$$\bigvee_{\alpha \in A} \varphi_\alpha \text{ and } \bigwedge_{\alpha \in A} \varphi_\alpha$$

where the index set A can be arbitrary, even containing uncountably many indices. We define $\mathsf{GC}_{\infty\omega}$ in the same way by relaxing the finite variable conditions. The semantics is, as expected: $\pi_G^{\mathbb{B}}[\![\bigvee_{\alpha \in A} \varphi_\alpha, \mu]\!] = \top$ if for at least one $\alpha \in A$, $\pi_G^{\mathbb{B}}[\![\varphi_\alpha, \mu]\!] = \top$, and $\pi_G^{\mathbb{B}}[\![\bigwedge_{\alpha \in A} \varphi_\alpha, \mu]\!] = \top$ if for all $\alpha \in A$, $\pi_G^{\mathbb{B}}[\![\varphi_\alpha, \mu]\!] = \top$.

We define the *free variables* of formulae just as for TL, and similarly, *quantifier rank* is defined as summation depth (only existential quantification increase the quantifier rank). For any of the above logics $\mathcal{L}$ we define $\mathcal{L}^{(t)}$ as the set of formulae in $\mathcal{L}$ of quantifier rank at most t.

To capture the *separation power of logics*, we define $\rho_1(\mathcal{L}^{(t)})$ as the equivalence relation on $\mathcal{G}_1$ defined by

$$\big((G, v), (H, w)\big) \in \rho_1(\mathcal{L}^{(t)}) \iff \forall\varphi(x) \in \mathcal{L}^{(t)} : \pi_G^{\mathbb{B}}[\![\varphi, \mu_v]\!] = \pi_H^{\mathbb{B}}[\![\varphi, \mu_w]\!],$$

where μ_v is any valuation such that $\mu(x) = v$, and likewise for w. The relation ρ_0 is defined in a similar way, except now the relation is only over pairs of graphs, and the characterization is over all formulae with no free variables (sentences). Finally, we also use, and define, the relation ρ_s, which relates pairs from $\mathcal{G}_s$: consisting of a graph and a s-tuple of vertices. The relation is defined as

$$\big((G, \boldsymbol{v}), (H, \boldsymbol{w})\big) \in \rho_s(\mathcal{L}^{(t)}) \iff \forall\varphi(\boldsymbol{x}) \in \mathcal{L}^{(t)} : \pi_G^{\mathbb{B}}[\![\varphi, \mu_{\boldsymbol{v}}]\!] = \pi_H^{\mathbb{B}}[\![\varphi, \mu_{\boldsymbol{w}}]\!],$$

where $\boldsymbol{x}$ consist of s free variables and $\mu_{\boldsymbol{v}}$ is a valuation assigning each i-th variable of $\boldsymbol{x}$ to the i-th value of $\boldsymbol{v}$.

B.2 Characterization of Separation Power of Logics

We first connect the separation power of the color refinement and k-dimensional Weisfeiler-Leman algorithms to the separation power of the logics we just introduced. Although most of these connections are known, we present them in a bit of a more fine-grained way. That is, we connect the number of rounds used in the algorithms to the quantifier rank of formulae in the above logics.

Proposition B.1. *For any $t \geq 0$, we have the following identities:*

(1) $\rho_1(\mathsf{cr}^{(t)}) = \rho_1(\mathsf{GC}^{(t)})$ *and* $\rho_0(\mathsf{gcr}^{(t)}) = \rho_0(\mathsf{gwl}_1^{(t)}) = \rho_0(\mathsf{C}^{2,(t+1)})$;

(2) For $k \geq 1$, $\rho_1\big(\text{vwl}_k^{(t)}\big) = \rho_1\big(\mathsf{C}^{k+1,(t)}\big)$ and

$$\rho_0\big(\mathsf{C}^{k+1,(t+k)}\big) \subseteq \rho_0\big(\text{gwl}_k^{(t)}\big) \subseteq \rho_0\big(\mathsf{C}^{k+1,(t+1)}\big).$$

As a consequence, $\rho_0\big(\text{gwl}_k^{(\infty)}\big) = \rho_0\big(\mathsf{C}^{k+1}\big)$.

Proof. For (1), the identity $\rho_1\big(\text{cr}^{(t)}\big) = \rho_1\big(\mathsf{GC}^{(t)}\big)$ is known and can be found, for example, in Theorem V.10 in Grohe (2021). The identity $\rho_0\big(\text{gcr}^{(t)}\big) = \rho_0\big(\text{gwl}_1^{(t)}\big)$ can be found in Proposition V.4 in Grohe (2021). The identity $\rho_0\big(\text{gwl}_1^{(t)}\big) = \rho_0\big(\mathsf{C}^{2,(t+1)}\big)$ is a consequence of the inclusion shown in (2) for $k = 1$.

For (2), we use that $\rho_k\big(\text{wl}_k^{(t)}\big) = \rho_k\big(\mathsf{C}^{k+1,(t)}\big)$, see e..g., Theorem V.8 in Grohe (2021)). We argue that this identity holds for $\rho_1\big(\text{vwl}_k^{(t)}\big) = \rho_1\big(\mathsf{C}^{k+1,(t)}\big)$. Indeed, suppose that (G, v) and (H, w) are not in $\rho_1\big(\mathsf{C}^{k+1,(t)}\big)$. Let $\varphi(x_1)$ be a formula in $\mathsf{C}^{k+1,(t)}$ such that $\pi_G^{\mathbb{B}}[\![\varphi, v]\!] \neq \pi_H^{\mathbb{B}}[\![\varphi, w]\!]$. Consider the formula $\varphi^+(x_1, \ldots, x_k) = \varphi(x_1) \wedge \bigwedge_{i=1}^{k}(x_1 = x_i)$. Then, $\pi_G[\![\varphi^+, (v, \ldots, v)]\!] \neq \pi_H[\![\varphi^+, (w, \ldots, w)]\!]$, and hence $(G, (v, \ldots, v))$ and $(H, (w, \ldots, w))$ are not in $\rho_k\big(\mathsf{C}^{k+1,(t)}\big)$ either. This implies that $\text{wl}_k^{(t)}(G, (v, \ldots, v)) \neq \text{wl}_k^{(t)}(H, (w, \ldots, w))$, and thus, by definition, $\text{vwl}_k^{(t)}(G, v) \neq \text{vwl}_k^{(t)}(H, w)$. In other words, (G, v) and (H, w) are not in $\rho_1\big(\text{vwl}_k^{(t)}\big)$, from which the inclusion $\rho_1\big(\text{vwl}_k^{(t)}\big) \subseteq \rho_1\big(\mathsf{C}^{k+1,(t)}\big)$ follows. Conversely, if (G, v) and (H, w) are not in $\rho_1\big(\text{vwl}_k^{(t)}\big)$, then $\text{wl}_k^{(t)}(G, (v, \ldots, v)) \neq \text{wl}_k^{(t)}(H, (w, \ldots, w))$. As a consequence, $(G, (v, \ldots, v))$ and $(H, (w, \ldots, w))$ are not in $\rho_k\big(\mathsf{C}^{k+1,(t)}\big)$ either. Let $\varphi(x_1, \ldots, x_k)$ be a formula in $\mathsf{C}^{k+1,(t)}$ such that $\pi_G^{\mathbb{B}}[\![\varphi, (v, \ldots, v)]\!] \neq \pi_H^{\mathbb{B}}[\![\varphi, (w, \ldots, w)]\!]$. Then it is readily shown that we can convert $\varphi(x_1, \ldots, x_k)$ into a formula $\varphi^-(x_1)$ in $\mathsf{C}^{k+1,(t)}$ such that $\pi_G^{\mathbb{B}}[\![\varphi^-, v]\!] \neq \pi_H^{\mathbb{B}}[\![\varphi^-, w]\!]$, and thus (G, v) and (H, w) are not in $\rho_1\big(\mathsf{C}^{k+1,(t)}\big)$. Hence, we also have the inclusion $\rho_1\big(\text{vwl}_k^{(t)}\big) \supseteq \rho_1\big(\mathsf{C}^{k+1,(t)}\big)$, form which the first identity in (2) follows.

We remark that $\rho_0\big(\text{gwl}_k^{(\infty)}\big) = \rho_0\big(\mathsf{C}^{k+1}\big)$ follows from the preceding inclusions in (2).

It remains to show $\rho_0\big(\mathsf{C}^{k+1,(t+k)}\big) \subseteq \rho_0\big(\text{gwl}_k^{(t)}\big) \subseteq \rho_0\big(\mathsf{C}^{k+1,(t+1)}\big)$. Clearly, if (G, H) is not in $\rho_0\big(\text{gwl}_k^{(t)}\big)$ then the multiset of labels $\text{wl}_k^{(t)}(G, \boldsymbol{v})$ and $\text{wl}_k^{(t)}(H, \boldsymbol{w})$ differ. It is known that with each label c one can associate formula φ^c in $\mathsf{C}^{k+1,(t)}$ such that $\pi_G^{\mathbb{B}}[\![\varphi^c, \boldsymbol{v}]\!] = \top$ if and only if $\text{wl}_k^{(t)}(G, \boldsymbol{v}) = c$. So, if the multisets are different, there must be a c that occurs more often in one multiset than in the other one. This can be detected by a fomulae of the form $\exists^{=m}(x_1, \ldots, x_k)\varphi^c(x_1, \ldots, x_k)$ which is satisfied if there are m tuples $\boldsymbol{v}$ with label c. It is now easily verified that the latter formula can be converted into a formula in $\mathsf{C}^{k+1,(t+k)}$. Hence, the inclusion $\rho_0\big(\mathsf{C}^{k+1,(t+k)}\big) \subseteq \rho_0\big(\text{gwl}_k^{(t)}\big)$ follows.

For $\rho_0\big(\text{gwl}_k^{(t)}\big) \subseteq \rho_0\big(\mathsf{C}^{k+1,(t+1)}\big)$, We show that (G, H) is in $\rho_0\big(\text{gwl}_k^{(t)}\big)$ implies that $\pi_G^{\mathbb{B}}[\![\varphi, \mu]\!] = \pi_H^{\mathbb{B}}[\![\varphi, \mu]\!]$ for all formulae in $\mathsf{C}^{k+1,(t+1)}$ and any valuation μ (notice that μ is superfluous in this definition when formulas have no free variables). Assume that (G, H) is in $\rho_0\big(\text{gwl}_k^{(t)}\big)$. Since any formula of quantifier rank $t + 1$ is a boolean combination of formulas of less rank or a formula of the form $\varphi = \exists^{\geq m} x_i \, \psi$ where ψ is of quantifier rank t, without loss of generality consider a formula of the latter form, and assume for the sake of contradiction that $\pi_G^{\mathbb{B}}[\![\varphi, \mu]\!] = \top$ but $\pi_H^{\mathbb{B}}[\![\varphi, \mu]\!] = \bot$. Since $\pi_G^{\mathbb{B}}[\![\varphi, \mu]\!] = \top$, there must be at least m elements satisfying ψ. More precisely, let $v_1, \ldots, v_p$ in G be all vertices in G such that for each valuation $\mu[x \mapsto v_i]$ it holds that $\pi_G^{\mathbb{B}}[\![\psi, \mu[x \mapsto v_i]]\!] = \top$. As mentioned, it must be that p is at least m. Using again the fact that $\rho_k\big(\text{wl}_k^{(t)}\big) = \rho_k\big(\mathsf{C}^{k+1,(t)}\big)$, we infer that the color $\text{wl}_k^{(t-1)}(G, (v_i, \ldots, v_i))$ is the same, for each such v_i.

Now since $\text{gwl}_k^{(t-1)}(G) = \text{gwl}_k^{(t-1)}(H)$, it is not difficult to see that there must be exactly p vertices $w_1, \ldots, w_p$ in H such that $\text{wl}_k^{(t-1)}(G, (v_i, \ldots, v_i)) = \text{wl}_k^{(p-1)}(H, (w_i, \ldots, w_i))$. Otherwise, it would simply not be the case that the aggregation step of the colors, assigned by k-WL is the same in G and H. By the connection to logic, we again know that for valuation $\mu[x \mapsto w_i]$ it holds that $\pi_H^{\mathbb{B}}[\![\psi, \mu[x \mapsto w_i]]\!] = \top$. It then follows that $\pi_H^{\mathbb{B}}[\![\varphi, \mu]\!] = \top$ for any valuation μ, which was to be shown. $\qquad\square$

Before moving tensor languages, where we will use infinitary logics to simulate expressions in $\mathsf{TL}_k(\Omega)$ and $\mathsf{GTL}(\Omega)$, we recall that, when considering the separation power of logics, we can freely move to their infinitary counterparts:

Theorem B.2. *The following identities hold for any $t \geq 0$, $k \geq 2$ and $s \geq 0$:*

(1) $\rho_1\big(\mathsf{GC}^{(t)}_{\infty\omega}\big) = \rho_1\big(\mathsf{GC}^{(t)}\big);$

(2) $\rho_s\big(\mathsf{C}^{k,(t)}_{\infty\omega}\big) = \rho_s\big(\mathsf{C}^{k,(t)}\big).$

Proof. For identity (1), notice that we only need to prove that $\rho_1\big(\mathsf{GC}^{(t)}\big) \subseteq \rho_1\big(\mathsf{GC}^{(t)}_{\infty\omega}\big)$, the other direction follows directly from the definition. We point out the well-known fact that two tuples (G, v) and (H, w) belong to $\rho_1\big(\mathsf{GC}^{(t)}\big)$ if and only if the *unravelling* of G rooted at v up to depth t is isomorphic to the *unravelling* of H rooted at w up to root t. Here the *unravelling* is the (infinite tree whose root is the root node, and whose children are the neighbors of the root node (see e.g. Barceló et al. (2020); Otto (2019)). Now for the connection with infinitary logic. Assume that the unravellings of G rooted at v and of H rooted at w up to level t are isomorphic, but assume for the sake of contradiction that there is a formula $\varphi(x)$ in $\mathsf{GC}^{(t)}_{\infty\omega}$ such that $\pi^{\mathbb{B}}_G[\![\varphi, \mu_v]\!] \neq \pi^{\mathbb{B}}_H[\![\varphi, \mu_w]\!]$, where μ_v and μ_w are any valuation mapping variable x to v and w, respectively. Now since G and H are finite graphs, one can construct, from formula ϕ, a formula ϕ' in $\mathsf{GC}^{(t)}$ such that $\pi^{\mathbb{B}}_G[\![\psi, \mu_v]\!] \neq \pi^{\mathbb{B}}_H[\![\psi, \mu_w]\!]$. Notice that this is in contradiction with our assumption that unravellings where isomorphic and therefore indistinguishable by formulae in $\mathsf{GC}^{(t)}$. To construct ψ, consider an infinitary disjunction $\bigvee_{a \in A} \alpha_a$. Since G and H have a finite number of vertices, and the formulae have a finite number of variables, the number of different valuations from the variables to the vertices in G or H is also finite. Thus, one can replace any extra copy of α_a, $\alpha_{a'}$ such that their value is the same in G and H. The final result is a finite disjunction, and the truth value over G and H is equivalent to the original infinitary disjunction.

For identity (2) we refer to Corollary 2.4 in Otto (2017). $\qquad\square$

B.3 FROM $\mathsf{TL}(\Omega)$ TO $\mathsf{C}^k_{\infty\omega}$ AND $\mathsf{GC}_{\infty\omega}$

We are now finally ready to make the connection between expressions in $\mathsf{TL}(\Omega)$ and the infinitary logics introduced earlier.

Proposition B.3. *For any expression $\varphi(\boldsymbol{x})$ in $\mathsf{TL}_k(\Omega)$ and $c \in \mathbb{R}$, there exists an expression $\tilde{\varphi}^c(\boldsymbol{x})$ in $\mathsf{C}^k_{\infty\omega}$ such that $\pi_G[\![\varphi, \boldsymbol{v}]\!] = c$ if and only if $\pi^{\mathbb{B}}_G[\![\tilde{\varphi}^c, \boldsymbol{v}]\!] = \top$ for any graph $G = (V_G, E_G, \mathsf{col}_G)$ in $\mathcal{G}$ and $\boldsymbol{v} \in V^k_G$. Furthermore, if $\varphi(x) \in \mathsf{GTL}(\Omega)$ then $\tilde{\varphi}^c \in \mathsf{GC}_{\infty\omega}$. Finally, if φ has summation depth t then $\tilde{\varphi}^c$ has quantifier rank t.*

Proof. We define $\tilde{\varphi}^c$ inductively on the structure of expressions in $\mathsf{TL}_k(\Omega)$.

- $\varphi(x_i, x_j) := \mathbf{1}_{x_i \,\mathsf{op}\, x_j}$. Assume first that op is "=". We distinguish between (a) $i \neq j$ and (b) $i = j$. For case (a), if $c = 1$, then we define $\tilde{\varphi}^1(x_i, x_j) := (x_i = x_j)$, if $c = 0$, then we define $\tilde{\varphi}^0(x_i, x_j) := \neg(x_i = x_j)$, and if $c \neq 0, 1$, then we define $\tilde{\varphi}^c(x_i, x_j) := x_i \neq x_i$. For case (b), if $c = 1$, then we define $\tilde{\varphi}^1(x_i, x_j) := (x_i = x_i)$, and for any $c \neq 1$, we define $\tilde{\varphi}^c(x_i, x_j) := \neg(x_i = x_i)$. The case when op is "$\neq$" is treated analogously.

- $\varphi(x_i) := P_\ell(x_i)$. If $c = 1$, then we define $\tilde{\varphi}^1(x_i) := P_\ell(x_i)$, if $c = 0$, then we define $\tilde{\varphi}^0(x_i) := \neg P_j(x_i)$. For all other c, we define $\tilde{\varphi}^c(x_i, x_j) := \neg(x_i = x_i)$.

- $\varphi(x_i, x_j) := E(x_i, x_j)$. If $c = 1$, then we define $\tilde{\varphi}^1(x_i, x_j) := E(x_i, x_j)$, if $c = 0$, then we define $\tilde{\varphi}^0(x_i, x_j) := \neg E(x_i, x_j)$. For all other c, we define $\tilde{\varphi}^c(x_i, x_j) := \neg(x_i = x_i)$.

- $\varphi := \varphi_1 + \varphi_2$. We observe that $\pi_G[\![\varphi, \boldsymbol{v}]\!] = c$ if and only if there are $c_1, c_2 \in \mathbb{R}$ such that $\pi_G[\![\varphi_1, \boldsymbol{v}]\!] = c_1$ and $\pi_G[\![\varphi_2, \boldsymbol{v}]\!] = c_2$ and $c = c_1 + c_2$. Hence, it suffices to define

$$\tilde{\varphi}^c := \bigvee_{\substack{c_1, c_2 \in \mathbb{R} \\ c = c_1 + c_2}} \tilde{\varphi}_1^{c_1} \wedge \tilde{\varphi}_2^{c_2},$$

where $\tilde{\varphi}_1^{c_1}$ and $\tilde{\varphi}_2^{c_2}$ are the expressions such that $\pi_G[\![\varphi_1, \boldsymbol{v}]\!] = c_1$ if and only if $\pi_G^{\mathbb{B}}[\![\tilde{\varphi}_1^{c_1}, \boldsymbol{v}]\!] = \top$ and $\pi_G[\![\varphi_2, \boldsymbol{v}]\!] = c_2$ if and only if $\pi_G^{\mathbb{B}}[\![\tilde{\varphi}_2^{c_2}, \boldsymbol{v}]\!] = \top$, which exist by induction.

- $\varphi := \varphi_1 \cdot \varphi_2$. This is case is analogous to the previous one. Indeed, $\pi_G[\![\varphi, \boldsymbol{v}]\!] = c$ if and only if there are $c_1, c_2 \in \mathbb{R}$ such that $\pi_G[\![\varphi_1, \boldsymbol{v}]\!] = c_1$ and $\pi_G[\![\varphi_2, \boldsymbol{v}]\!] = c_2$ and $c = c_1 \cdot c_2$. Hence, it suffices to define

$$\tilde{\varphi}^c := \bigvee_{\substack{c_1, c_2 \in \mathbb{R} \\ c = c_1 \cdot c_2}} \tilde{\varphi}_1^{c_1} \wedge \tilde{\varphi}_2^{c_2}.$$

- $\varphi := a \cdot \varphi_1$. This is case is again dealt with in a similar way. Indeed, $\pi_G[\![\varphi, \boldsymbol{v}]\!] = c$ if and only if there is a $c_1 \in \mathbb{R}$ such that $\pi_G[\![\varphi_1, \boldsymbol{v}]\!] = c_1$ and $c = a \cdot c_1$. Hence, it suffices to define

$$\tilde{\varphi}^c := \bigvee_{\substack{c_1 \in \mathbb{R} \\ c = a \cdot c_1}} \tilde{\varphi}_1^{c_1}.$$

- $\varphi := f(\varphi_1, \ldots, \varphi_p)$ with $f : \mathbb{R}^p \to \mathbb{R}$. We observe that $\pi_G[\![\varphi, \boldsymbol{v}]\!] = c$ if and only if there are $c_1, \ldots, c_p \in \mathbb{R}$ such that $c = f(c_1, \ldots, c_p)$ and $\pi_G[\![\varphi_i, \boldsymbol{v}]\!] = c_i$ for $i \in [p]$. Hence, it suffices to define

$$\tilde{\varphi}^c := \bigvee_{\substack{c_1, \ldots, c_p \in \mathbb{R} \\ c = f(c_1, \ldots, c_p)}} \tilde{\varphi}_1^{c_1} \wedge \cdots \wedge \tilde{\varphi}_p^{c_p}.$$

- $\varphi := \sum_{x_i} \varphi_1$. We observe that $\pi_G[\![\varphi, \mu]\!] = c$ implies that we can partition V_G into ℓ parts $V_1, \ldots, V_\ell$, of sizes $m_1, \ldots, m_\ell$, respectively, such that $\pi_H[\![\varphi_1, \mu[x_i \to v]]\!] = c_i$ for each $v \in V_i$, and such that all c_i's are pairwise distinct and $c = \sum_{i=1}^\ell c_i \cdot m_i$. It now suffices to consider the following formula

$$\tilde{\varphi}^c := \bigvee_{\substack{\ell, m_1, \ldots, m_\ell \in \mathbb{N} \\ c_1, \ldots, c_\ell \in \mathbb{R} \\ c = \sum_{i=1}^\ell m_i c_i}} \bigwedge_{i=1}^\ell \exists^{=m_i} x_i \, \tilde{\varphi}_1^{c_i} \wedge \forall x_i \bigvee_{i=1}^\ell \tilde{\varphi}_1^{c_i},$$

where $\exists^{=m_i} x_i \, \psi$ is shorthand notation for $\exists^{\geq m_i} x_i \, \psi \wedge \neg \exists^{\geq m_i + 1} x_i \, \psi$, and $\forall x_i \, \psi$ denotes $\neg \exists^{\geq 1} x_i \, \neg \psi$.

This concludes the construction of $\tilde{\varphi}^c$. We observe that we only introduce a quantifiers when $\varphi = \sum_{x_i} \varphi_1$ and hence if we assume by induction. that summation depth and quantifier rank are in sync, then if φ_1 has summation depth $t-1$ and thus $\tilde{\varphi}_1^c$ has quantifier rank $t-1$ for any $c \in \mathbb{R}$, then φ has summation depth t, and as can be seen from the definition of $\tilde{\varphi}^c$, this formula has quantifier rank t, as desired.

It remains to verify the claim about guarded expressions. This is again verified by induction. The only case requiring some attention is $\varphi(x_1) := \sum_{x_2} E(x_1, x_2) \wedge \varphi_1(x_2)$ for which can define

$$\tilde{\varphi}^c := \bigvee_{\substack{\ell, m_1, \ldots, m_\ell \in \mathbb{N} \\ c_1, \ldots, c_\ell \in \mathbb{R} \\ c = \sum_{i=1}^\ell m_i c_i \\ m = \sum_{i=1}^\ell m_i}} \exists^{=m} x_2 E(x_1, x_2) \wedge \bigwedge_{i=1}^\ell \exists^{=m_i} x_2 \, E(x_1, x_2) \wedge \tilde{\varphi}_1^{c_i}(x_2),$$

which is a formula in GC again only adding one to the quantifier rank of the formulae $\tilde{\varphi}_1^c$ for $c \in \mathbb{R}$. So also here, we have the one-to-one correspondence between summation depth and quantifier rank. $\qquad\square$

B.4 Proof of Theorem 4.1, 4.2, 4.3 and 4.4

Proposition B.4. *We have the following inclusions: For any $t \geq 0$ and any collection Ω of functions:*

- $\rho_1\big(\mathsf{cr}^{(t)}\big) \subseteq \rho_1\big(\mathsf{GTL}^{(t)}(\Omega)\big)$;

- $\rho_1\big(\mathsf{vwl}_k^{(t)}\big) \subseteq \rho_1\big(\mathsf{TL}_{k+1}^{(t)}(\Omega)\big)$; *and*

- $\rho_0\big(\mathsf{gwl}_k^{(t)}\big) \subseteq \rho_0\big(\mathsf{TL}_{k+1}^{(t+1)}(\Omega)\big)$.

Proof. We first show the second bullet by contraposition. That is, we show that if (G, v) and (H, w) are not in $\rho_1\big(\mathsf{TL}_{k+1}^{(t)}(\Omega)\big)$, then neither are they in $\rho_1\big(\mathsf{vwl}_k^{(t)}\big)$. Indeed, suppose that there exists an expression $\varphi(x_1)$ in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ such that $\pi_G[\![\varphi, v]\!] = c \neq c' = \pi_G[\![\varphi, w]\!]$. From Proposition B.3 we know that there exists a formula $\tilde{\varphi}^c$ in $\mathsf{C}_{\infty\omega}^{k+1,(t)}$ such that $\pi_G^{\mathbb{B}}[\![\tilde{\varphi}^c, v]\!] = \top$ and $\pi_H^{\mathbb{B}}[\![\tilde{\varphi}^c, w]\!] = \bot$. Hence, (G, v) and (H, w) do no belong to $\rho_1\big(\mathsf{C}_{\infty\omega}^{k+1,(t)}\big)$. Theorem B.2 implies that (G, v) and (H, w) also do not belong to $\rho_1\big(\mathsf{C}^{k+1,(t)}\big)$. Finally, Proposition B.1 implies that (G, v) and (H, w) do not belong to $\rho_1\big(\mathsf{vwl}_k^{(t)}\big)$, as desired. The third bullet is shown in precisely the same, but using the identities for ρ_0 rather than ρ_1, and $\mathsf{gwl}_k^{(t)}$ rather than $\mathsf{vwl}_k^{(t)}$.

Also the first bullet is shown in the same way, using the connection between $\mathsf{GTL}^{(t)}(\Omega)$, $\mathsf{GC}_{\infty\omega}^{2,(t)}$, $\mathsf{GC}^{(t)}$ and $\mathsf{cr}^{(t)}$, as given by Proposition B.1, Theorem B.2, and Proposition B.3. $\qquad\square$

We next show that our tensor languages are also more separating than the color refinement and k-dimensional Weisfeiler-Leman algorithms.

Proposition B.5. *We have the following inclusions: For any $t \geq 0$ and any collection Ω of functions:*

- $\rho_1\big(\mathsf{GTL}^{(t)}(\Omega)\big) \subseteq \rho_1\big(\mathsf{cr}^{(t)}\big)$;

- $\rho_1\big(\mathsf{TL}_{k+1}^{(t)}(\Omega)\big) \subseteq \rho_1\big(\mathsf{vwl}_k^{(t)}\big)$; *and*

- $\rho_0\big(\mathsf{TL}_{k+1}^{(t+k)}(\Omega)\big) \subseteq \rho_0\big(\mathsf{gwl}_k^{(t)}\big)$.

Proof. For any of these inclusions to hold, for any Ω, we need to show the inclusion without the use of any functions. We again use the connections between the color refinement and k-dimensional Weisfeiler-Leman algorithms and finite variable logics as stated in Proposition B.1. More precisely, we show for any formula $\varphi(\boldsymbol{x}) \in \mathsf{C}^{k,(t)}$ there exists an expression $\hat{\varphi}(\boldsymbol{x}) \in \mathsf{TL}_k^{(t)}$ such that for any graph G in $\mathcal{G}$, $\pi_G^{\mathbb{B}}[\![\varphi, \boldsymbol{v}]\!] = \top$ implies $\pi_G[\![\hat{\varphi}, \boldsymbol{v}]\!] = 1$ and $\pi_G^{\mathbb{B}}[\![\varphi, \boldsymbol{v}]\!] = \bot$ implies $\pi_G[\![\hat{\varphi}, \boldsymbol{v}]\!] = 0$. By appropriately selecting k and t and by observing that when $\varphi(x) \in \mathsf{GC}$ then $\hat{\varphi}(x) \in \mathsf{GTL}$, the inclusions follow.

The construction of $\hat{\varphi}(\boldsymbol{x})$ is by induction on the structure of formulae in C^k.

- $\varphi := (x_i = x_j)$. Then, we define $\hat{\varphi} := \mathbf{1}_{x_i = x_j}$.

- $\varphi := P_\ell(x_i)$. Then, we define $\hat{\varphi} := P_\ell(x_i)$.

- $\varphi := E(x_i, x_j)$. Then, we define $\hat{\varphi} := E(x_i, x_j)$.

- $\varphi := \neg\varphi_1$. Then, we define $\hat{\varphi} := \mathbf{1}_{x_i = x_i} - \hat{\varphi}_1$.

- $\varphi := \varphi_1 \wedge \varphi_2$. Then, we define $\hat{\varphi} := \hat{\varphi}_1 \cdot \hat{\varphi}_2$.

- $\varphi := \exists^{\geq m} x_i \, \varphi_1$. Consider a polynomial $p(x) := \sum_j a_j x^j$ such that $p(x) = 0$ for $x \in \{0, 1, \ldots, m-1\}$ and $p(x) = 1$ for $x \in \{m, m+1, \ldots, n\}$. Such a polynomial exists by interpolation. Then, we define $\hat{\varphi} := \sum_j a_j \big(\sum_{x_i} \hat{\varphi}_1\big)^j$.

We remark that we here crucially rely on the assumption that $\mathcal{G}$ contains graphs of fixed size n and that TL_k is closed under linear combinations and product. Clearly, if $\varphi \in \mathsf{GC}$, then the above

translations results in an expression $\hat{\varphi} \in \mathsf{GTL}(\Omega)$. Furthermore, the quantifier rank of φ is in one-to-one correspondence to the summation depth of $\hat{\varphi}$.

We can now apply Proposition B.1. That is, if (G, v) and (H, w) are not in $\rho_1\big(\mathsf{cr}^{(t)}\big)$ then by Proposition B.1, there exists a formula $\varphi(x)$ in $\mathsf{GC}^{(t)}$ such that $\pi_G^{\mathbb{B}}[\![\varphi, v]\!] = \top \neq \pi_H^{\mathbb{B}}[\![\varphi, w]\!] = \bot$. We have just shown that for $\tilde{\varphi}$ is in $\mathsf{GTL}^{(t)}$ and moreover, $\pi_G[\![\tilde{\varphi}, v]\!] \neq \pi_H^{[}[\tilde{\varphi}, w]\!]$. Hence, (G, v) and (H, w) is not in $\rho_1\big(\mathsf{GTL}^{(t)}(\Omega)\big)$ either, for any Ω. Hence, $\rho_1\big(\mathsf{GTL}^{(t)}(\Omega)\big) \subseteq \rho_1\big(\mathsf{cr}^{(t)}\big)$ holds. The other bullets are shown in the same way, again by relying on Proposition B.1 and use that we can move from $\mathsf{vwl}|_k^{(t)}$ abd $\mathsf{gwl}|_k^{(t)}$ to logical formulae, and to expressions in $\mathsf{TL}_{k+1}^{(t)}$ and $\mathsf{TL}_{k+1}^{(t+k)}$, respectively, to separate (G, v) from (H, w) or G from H, respectively. $\qquad\square$

Theorems 4.1, 4.2, 4.3 and 4.4 now follow directly from Propositions B.4 and B.5.

C   DETAILS OF SECTION 5

We here provide some additional details on the encoding of layers of GNNs in our tensor languages, and how, as a consequence of our results from Section 4, one obtains a bound on their separation power. This section showcases that it is relatively straightforward to represent GNNs in our tensor languages. Indeed, often, a direct translation of the layers, as defined in the literature, suffices.

C.1   COLOR REFINEMENT

We start with GNN architectures related to color refinement, or in other words, architectures which can be represented in our guarded tensor language.

Basic GNNs. In a "basic"GNN (Hamilton et al., 2017), the initial features are given by $\boldsymbol{F}^{(0)} = (\boldsymbol{f}_1^{(0)}, \ldots, \boldsymbol{f}_{d_0}^{(0)})$ where $\boldsymbol{f}_i^{(0)} \in \mathbb{R}^{n \times 1}$ is a hot-one encoding of the ith vertex label in G. We can represent the initial embedding easily in $\mathsf{GTL}^{(0)}$, without the use of any summation. Indeed, it suffices to define $\varphi_i^{(0)}(x_1) := P_i(x_1)$ for $i \in [d_0]$. We have $F_{vj}^{(0)} = \pi_G[\![\varphi_j^{(0)}, v]\!]$ for $j \in [d_0]$, and thus the initial features can be represented by simple expressions in $\mathsf{GTL}^{(0)}$.

Assume now, by induction, that we can also represent the features computed by a basic GNN in layer $t - 1$. That is, let $\boldsymbol{F}^{(t-1)} \in \mathbb{R}^{n \times d_{t-1}}$ be those features and for each $i \in [d_{t-1}]$ let $\varphi_i^{(t-1)}(x_1)$ be expressions in $\mathsf{GTL}^{(t-1)}(\sigma)$ representing them. We assume that, for each $i \in [d_{t-1}]$, $F_{vi}^{(t-1)} = \pi_G[\![\varphi_i^{(t-1)}, v]\!]$. We remark that we assume that a summation depth of $t - 1$ is needed for layer $t - 1$.

Then, in layer t, a basic GNN computes the next features as

$$\boldsymbol{F}^{(t)} := \sigma\left(\boldsymbol{F}^{(t-1)} \cdot \boldsymbol{V}^{(t)} + \boldsymbol{A} \cdot \boldsymbol{F}^{(t-1)} \cdot \boldsymbol{W}^{(t)} + \boldsymbol{B}^{(t)}\right),$$

where $\boldsymbol{A} \in \mathbb{R}^{n \times n}$ is the adjacency matrix of G, $\boldsymbol{V}^{(t)}$ and $\boldsymbol{W}^{(t)}$ are weight matrices in $\mathbb{R}^{d_{t-1} \times d_t}$, $\boldsymbol{B}^{(t)} \in \mathbb{R}^{n \times d_t}$ is a (constant) bias matrix consist of n copies of $\boldsymbol{b}^{(t)} \in \mathbb{R}^{d_t}$, and σ is some activation function. We can simply use the following expressions $\varphi_j^{(t)}(x_1)$, for $j \in [d_t]$:

$$\sigma\left(\left(\sum_{i=1}^{d_{t-1}} V_{ij}^{(t)} \cdot \varphi_i^{(t-1)}(x_1)\right) + \sum_{x_2}\left(E(x_1, x_2) \cdot \left(\sum_{i=1}^{d_{t-1}} W_{ij}^{(t)} \cdot \varphi_i^{(t-1)}(x_2)\right)\right) + b_j^{(t)} \cdot \mathbf{1}_{x_1 = x_1}\right).$$

Here, $W_{ij}^{(t)}$, $V_{ij}^{(t)}$ and $b_j^{(t)}$ are real values corresponding the weight matrices and bias vector in layer t. These are expressions in $\mathsf{GTL}^{(t)}(\sigma)$ since the additional summation is guarded, and combined with the summation depth of $t - 1$ of $\varphi_i^{(t-1)}$, this results in a summation depth of t for layer t. Furthermore, $F_{vi}^{(t)} = \pi_G[\![\varphi_i^{(t)}, v]\!]$, as desired. If we denote by $\mathsf{bGNN}^{(t)}$ the class of t-layered basic GNNs, then our results imply

$$\rho_1\big(\mathsf{cr}^{(t)}\big) \subseteq \rho_1\big((\mathsf{GTL}^{(t)}(\Omega)\big) \subseteq \rho_1\big(\mathsf{bGNN}^{(t)}\big),$$

and thus the separation power of basic GNNs is bounded by the separation power of color refinement. We thus recover known results by Xu et al. (2019) and Morris et al. (2019).

Furthermore, if one uses a readout layer in basic GNNs to obtain a graph embedding, one typically applies a function $\mathsf{ro} : \mathbb{R}^{d_t} \to \mathbb{R}^{d_t}$ in the form of $\mathsf{ro}\big(\sum_{v \in V_G} \boldsymbol{F}_v^{(t)}\big)$, in which aggregation takes places over all vertices of the graph. This corresponds to an expression in $\mathsf{TL}_2^{(t+1)}(\sigma, \mathsf{ro})$: $\varphi_j := \mathsf{ro}_j\big(\sum_{x_1} \varphi_j^{(t-1)}(x_1)\big)$, where ro_j is the projection of the readout function on the $j$the coordinate. We note that this is indeed not a guarded expression anymore, and thus our results tell that

$$\rho_0\big(\mathsf{gcr}^{(t)}\big) \subseteq \rho_0(\mathsf{TL}_2^{(t+1)}(\Omega)) \subseteq \rho_0\big(\mathsf{bGNN}^{(t)} + \mathsf{readout}\big).$$

GCNs. *Graph Convolution Networks* (GCNs) (Kipf & Welling, 2017) operate alike basic GNNs except that a normalized Laplacian $\boldsymbol{D}^{-1/2}(\boldsymbol{I} + \boldsymbol{A})\boldsymbol{D}^{-1/2}$ is used to aggregate features, instead of the adjacency matrix $\boldsymbol{A}$. Here, $\boldsymbol{D}^{-1/2}$ is the diagonal matrix consisting of reciprocal of the square root of the vertex degrees in G plus 1. The initial embedding $\boldsymbol{F}^{(0)}$ is just as before. We use again d_t the denote the number of features in layer t. In layer $t > 0$, a GCN computes $\boldsymbol{F}^{(t)} := \sigma(\boldsymbol{D}^{-1/2}(\boldsymbol{I} + \boldsymbol{A})\boldsymbol{D}^{-1/2} \cdot \boldsymbol{F}^{(t-1)}\boldsymbol{W}^{(t)} + \boldsymbol{B}^{(t)})$. If, in addition to the activation function σ we add the function $\frac{1}{\sqrt{x+1}} : \mathbb{R} \to \mathbb{R} : x \mapsto \frac{1}{\sqrt{x+1}}$ to Ω, we can represent the GCN layer, as follows. For $j \in [d_t]$, we define the $\mathsf{GTL}^{(t+1)}(\sigma, \frac{1}{\sqrt{x+1}})$ expressions

$$\varphi_j^{(t)}(x_1) := \sigma\Bigg(f_{1/\sqrt{x+1}}\big(\sum_{x_2} E(x_1, x_2)\big) \cdot \Big(\sum_{i=1}^{d_{t-1}} W_{ij}^{(t)} \cdot \varphi_i^{(t-1)}(x_1)\Big) \cdot f_{1/\sqrt{x+1}}\big(\sum_{x_2} E(x_1, x_2)\big)$$

$$+ f_{1/\sqrt{x+1}}\big(\sum_{x_2} E(x_1, x_2)\big) \cdot \Big(\sum_{x_2} E(x_1, x_2) \cdot f_{1/\sqrt{x+1}}\big(\sum_{x_1} E(x_2, x_1)\big) \cdot \Big(\sum_{i=1}^{d_{t-1}} W_{ij}^{(t)} \cdot \varphi_i^{(t-1)}(x_2)\Big)\Bigg),$$

where we omitted the bias vector for simplicity. We again observe that only guarded summations are needed. However, we remark that in every layer we now add two the overall summation depth, since we need an extra summation to compute the degrees. In other words, a t-layered GCN correspond to expressions in $\mathsf{GTL}^{(2t)}(\sigma, \frac{1}{\sqrt{x+1}})$. If we denote by $\mathsf{GCN}^{(t)}$ the class of t-layered GCNs, then our results imply

$$\rho_1\big(\mathsf{cr}^{(2t)}\big) \subseteq \rho_1\big(\mathsf{GTL}^{(2t)}(\Omega)\big) \subseteq \rho_1\big(\mathsf{GCN}^{(t)}\big).$$

We remark that another representation can be provided, in which the degree computation is factored out (Geerts et al., 2021a), resulting in a better upper bound $\rho_1\big(\mathsf{cr}^{(t+1)}\big) \subseteq \rho_1\big(\mathsf{GCN}^{(t)}\big)$. In a similar way as for basic GNNs, we also have $\rho_0\big(\mathsf{gcr}^{(t+1)}\big) \subseteq \rho_0\big(\mathsf{GCN}^{(t)} + \mathsf{readout}\big)$.

SGCs. As an other example, we consider a variation of *Simple Graph Convolutions* (SGCs) (Wu et al., 2019), which use powers the adjacency matrix and only apply a non-linear activation function at the end. That is, $\boldsymbol{F} := \sigma(\boldsymbol{A}^p \cdot \boldsymbol{F}^{(0)} \cdot \boldsymbol{W})$ for some $p \in \mathbb{N}$ and $\boldsymbol{W} \in \mathbb{R}^{d_0 \times d_1}$. We remark that SGCs actually use powers of the normalized Laplacian, that is, $\boldsymbol{F} := \sigma\big((\boldsymbol{D}^{-1/2}(\boldsymbol{I} + \boldsymbol{A}_G)\boldsymbol{D}^{-1/2}))^p \cdot \boldsymbol{F}^{(0)} \cdot \boldsymbol{W}\big)$ but this only incurs an additional summation depth as for GCNs. We focus here on our simpler version. It should be clear that we can represent the architecture in $\mathsf{TL}_{p+1}^{(p)}(\Omega)$ by means of the expressions:

$$\varphi_j^{(t)}(x_1) := \sigma\Bigg(\sum_{x_2} \cdots \sum_{x_{p+1}} \prod_{k=1}^{p} E(x_k, x_{k+1}) \cdot \Big(\sum_{i=1}^{d_0} W_{ij} \cdot \varphi_i^{(0)}(x_{p+1})\Big)\Bigg),$$

for $j \in [d_1]$. A naive application of our results would imply an upper bound on their separation power by p-WL. We can, however, use Proposition 4.5. Indeed, it is readily verified that these expressions have a treewidth of one, because the variables form a path. And indeed, when for example, $p = 3$, we can equivalently write $\varphi_j^{(t)}(x_1)$ as

$$\sigma\Bigg(\sum_{x_2} E(x_1, x_2) \cdot \Big(\sum_{x_1} E(x_2, x_1) \cdot \Big(\sum_{x_2} E(x_1, x_2) \cdot \big(\sum_{i=1}^{d_0} W_{ij} \cdot \varphi_i^{(0)}(x_2)\big)\Big)\Big)\Bigg),$$

by reordering the summations and reusing index variables. This holds for arbitrary p. We thus obtain guarded expressions in $\mathsf{GTL}^{(p)}(\sigma)$ and our results tell that t-layered SGCs are bounded by $\mathsf{cr}^{(p)}$ for vertex embeddings, and by $\mathsf{gcr}^{(p)}$ for SGCs + readout.

Other example. In the same way, one can also easily analyze GATs (Velickovic et al., 2018) and show that these can be represented in $\mathsf{GTL}(\Omega)$ as well, and thus bounds by color refinement can be obtained.

C.2 k-DIMENSIONAL WEISFEILER-LEMAN TESTS

We next discuss architectures related to the k-dimensional Weisfeiler-Leman algorithms. For $k = 1$, we discussed the extended GINs in the main paper. We here focus on arbitrary $k \geq 2$.

Folklore GNNs. We first consider the "Folklore" GNNs or k-FGNNs for short (Maron et al., 2019b). For $k \geq 2$, k-FGNNs computes a tensors. In particular, the initial tensor $\mathbf{F}^{(0)}$ encodes $\mathsf{atp}_k(G, \boldsymbol{v})$ for each $\boldsymbol{v} \in V_G^k$. We can represent this tensor by the following $k^2(\ell + 2)$ expressions in $\mathsf{TL}_k^{(0)}$:

$$\varphi_{r,s,j}^{(0)}(x_1, \ldots, x_k) := \begin{cases} \mathbf{1}_{x_r = x_s} \cdot P_j(x_r) & \text{for } j \in [\ell] \\ E(x_r, x_s) & \text{for } j = \ell + 1 \\ \mathbf{1}_{x_r = x_s} & \text{for } j = \ell + 2 \end{cases},$$

for $r, s \in [k]$ and $j \in [\ell + 2]$. We note: $\pi_G[\![\varphi_{r,s,j}^{(0)}, (v_1, \ldots, v_k)]\!] = F_{v_1, \ldots, v_k, r, s, j}^{(0)}$ for all $(r, s, j) \in [k]^2 \times [\ell + 2]$, as desired. We let $\tau_0 := [k]^2 \times [\ell + 2]$ and set $d_0 = k^2 \times (\ell + 2)$.

Then, in layer t, a k-FGNN computes a tensor

$$\mathbf{F}_{v_1, \ldots, v_k, \bullet}^{(t)} := \mathsf{mlp}_0^{(t)}\big(\mathbf{F}_{v_1, \ldots, v_k, \bullet}^{(t-1)}, \sum_{w \in V_G} \prod_{s=1}^{k} \mathsf{mlp}_s^{(t)}(\mathbf{F}_{v_1, \ldots, v_{s-1}, w, v_{s+1}, \ldots, v_k, \bullet}^{(t-1)})\big),$$

where $\mathsf{mlp}_s^{(t)} : \mathbb{R}^{d_{t-1}} \to \mathbb{R}^{d'_t}$, for $s \in [k]$, and and $\mathsf{mlp}_0^{(t)} : \mathbb{R}^{d_{t-1} \times d'_t} \to \mathbb{R}^{d_t}$ are MLPs. We here use $\bullet$ to denote combinations of indices in τ_d for $\mathbf{F}^{(t)}$ and in τ_{d-1} for $\mathbf{F}^{(t-1)}$.

Let $\mathbf{F}^{(t-1)} \in \mathbb{R}^{n^k \times d_{t-1}}$ be the tensor computed by an k-FGNN in layer $t - 1$. Assume that for each tuple of elements $\boldsymbol{j}$ in $\tau_{d_{t-1}}$ we have an expression $\varphi_{\boldsymbol{j}}^{(t-1)}(x_1, \ldots, x_k)$ satisfying $\pi_G[\![\varphi_{\boldsymbol{j}}^{(t-1)}, (v_1, \ldots, v_k)]\!] = F_{v_1, \ldots, v_k, \boldsymbol{j}}^{(t-1)}$ and such that it is an expression in $\mathsf{TL}_{k+1}^{(t-1)}(\Omega)$. That is, we need $k + 1$ index variables and a summation depth of $t - 1$ to represent layer $t - 1$.

Then, for layer t, for each $\boldsymbol{j} \in \tau_{d_t}$, it suffices to consider the expression

$$\varphi_{\boldsymbol{j}}^{(t)}(x_1, \ldots, x_k) := \mathsf{mlp}_{0,\boldsymbol{j}}^{(t)}\Big(\big(\varphi_{\boldsymbol{i}}^{(t-1)}(x_1, \ldots, x_k)\big)_{\boldsymbol{i} \in \tau_{d_{t-1}}},$$

$$\sum_{x_{k+1}} \prod_{s=1}^{k} \mathsf{mlp}_{s,\boldsymbol{j}}^{(t)}\big(\big(\varphi_{\boldsymbol{i}}^{(t-1)}(x_1, \ldots, x_{s-1}, x_{k+1}, x_{s+1}, \ldots, x_k)\big)_{\boldsymbol{i} \in \tau_{d_{t-1}}}\Big),$$

where $\mathsf{mlp}_{o,\boldsymbol{j}}^{(t)}$ and $\mathsf{mlp}_{s,\boldsymbol{j}}^{(t)}$ are the projections of the MLPs on the $\boldsymbol{j}$-coordinates. We remark that we need $k + 1$ index variables, and one extra summation is needed. We thus obtain expressions in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ for the tth layer, as desired. We remark that the expressions are simple translations of the defining layer definitions. Also, in this case, Ω consists of all MLPs. When a k-FGNN is used for vertex embeddings, we now simply add to each expression a factor $\prod_{s=1}^{k} \mathbf{1}_{x_1 = x_s}$. As an immediate consequence of our results, if we denote by k-FGNN$^{(t)}$ the class of t-layered k-FGNNs, then for vertex embeddings:

$$\rho_1(\mathsf{vwl}_k^{(t)}) \subseteq \rho_1(\mathsf{TL}_{k+1}^{(t)}(\Omega)) \subseteq \rho_1(k\text{-FGNN}^{(t)})$$

in accordance with the known results from Azizian & Lelarge (2021). When used for graph embeddings, an aggregation layer over all k-tuples of vertices is added, followed by the application of an MLP. This results in expressions with no free index variables, and of summation depth $t + k$, where the increase with k stems from the aggregation process over all k-tuples. In view of our results, for graph embeddings:

$$\rho_0(\mathsf{gwl}_k^{(\infty)}) \subseteq \rho_0(\mathsf{TL}_{k+1}(\Omega)) \subseteq \rho_0(k\text{-FGNN})$$

in accordance again with Azizian & Lelarge (2021). We here emphasize that the upper bounds in terms of k-WL are obtained without the need to know how k-WL works. Indeed, one can really just focus on casting layers in the right tensor language!

We remark that Azizian & Lelarge (2021) define vertex embedding k-FGNNs in a different way. Indeed, for a vertex v, its embedding is obtained by aggregating of all $(k-1)$ tuples in the remaining coordinates of the tensors. They define vwl_k accordingly. From the tensor language point of view, this corresponds to the addition of $k-1$ to the summation depth. Our results indicate that we loose the connection between rounds and layers, as in Azizian & Lelarge (2021). This is the reason why we defined vertex embedding k-FGNNs in a different way and can ensure a correspondence between rounds and layers for vertex embeddings.

Other examples. It is readily verified that t-layered k-GNNs (Morris et al., 2019) can be represented in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$, recovering the known upper bound by $\mathsf{vwl}_k^{(t)}$ (Morris et al., 2019). It is an equally easy exercise to show that 2-WL-convolutions (Damke et al., 2020) and Ring-GNNs (Chen et al., 2019) are bounded by 2-WL, by simply writing their layers in $\mathsf{TL}_3(\Omega)$. The invariant graph networks (k-IGNs) (Maron et al., 2019b) will be treated in Section D, as their representation in $\mathsf{TL}_{k+1}(\Omega)$ require some work. We also mention, without giving details, that the tensor language approach also enables to obtain upper bounds on the separation power of recent proposed GNN extensions. For example, in the Graph Substructure Networks (GSNs) (Bouritsas et al., 2020) and $\mathcal{F}$-MPNNs (Barceló et al., 2021), the initial vertex labels are enriched with local graph parameters. These parameters count subgraph isomorphism or homomorphisms from a set of small graph patterns. It is readily verified that these parameters can be expressed in TL. More precisely, when the graph patterns under consideration have a treewidth of k, expressions in TL_{k+1} are needed for homomorphism counts. For isomorphism counts, the amount of index variables is upper bounded by the size of the patterns. In terms of separation power, suppose that all graph parameters can be be computed in TL_ℓ for some $\ell \in \mathbb{N}$. Then, GSNs and $\mathcal{F}$-MPNNs run standard GNNs on these extended labels. As a direct consequence of our results, for vertex embeddings, the separation power of t layers of such architectures are bounded by ℓ-WL, simply because the initial embedding requires ℓ index variables. This is conform to the results in Barceló et al. (2021). As another example, consider the recently introduced clique-complex MPNNs (Bodnar et al., 2021). Here, MPNNs are run on the clique-complex of the graphs instead of on the original graphs. One again can verify that the clique complex of a graph can be computed by means of expressions in TL. That is, one needs expressions to extract the cliques, and expressions to represent the adjacency information between cliques (as used in the clique complex). Once that these are in place, clique-complex MPNNs can be represented in TL as well. In terms of the number of index variables needed, if the original graphs have a clique size of at most k, then $k+1$ index variables suffices. As such, the separation power of clique-complex MPNNs on graphs of clique size at most k is bounded by k-WL. This all illustrates that our approach can be used to asses the separation power of a variety of GNN architectures in terms of k-WL, by simply writing them as tensor language expressions.

D PROOF OF THEOREM 5.1

We here consider another higher-order GNN proposal: the *invariant graph networks* or k-IGNs of Maron et al. (2019b). By contrast to k-FGNNs, k-IGNs are linear architectures. If we denote by k-IGN$^{(t)}$ the class of t layered k-IGNs, then following inclusions are known (Maron et al., 2019b)

$$\rho_1\big(k\text{-IGN}^{(t)}\big) \subseteq \rho_1\big(\mathsf{vwl}_{k-1}^{(t)}\big) \text{ and } \rho_0\big(k\text{-IGN}\big) \subseteq \rho_0\big(\mathsf{gwl}_{k-1}^{(\infty)}\big).$$

The reverse inclusions were posed as open problems in Maron et al. (2019a) and were shown to hold by Chen et al. (2020) for $k = 2$, by means of an extensive case analysis and by relying on properties of 1-WL. In this section, we show that the separation power of k-IGNs is bounded by that of $(k-1)$-WL, for arbitrary $k \geq 2$. Theorem 4.2 tells that we can entirely shift our attention to showing that the layers of k-IGNs can be represented in $\mathsf{TL}_k(\Omega)$. In other words, we only need to show that k index variables are needed for the layers. As we will see below, this requires a bit of work since a naive representation of the layers of k-IGNs use $2k$ index variables. Nevertheless, we show that this can be reduced to k index variables only.

By inspecting the expressions needed to represent the layers of k-IGNs in $\mathsf{TL}_k(\Omega)$, we obtain that a t layer k-IGN$^{(t)}$ require expressions of summation depth of tk. In other words, the correspondence between layers and summation depth is precisely in sync. This implies, by Theorem 4.2:

$$\rho_1\big(k\text{-IGN}\big) = \rho_1\big(\mathsf{vwl}_{k-1}^{(\infty)}\big),$$

where we ignore the number of layers. We similarly obtain that $\rho_0\big(k\text{-IGN}\big) = \rho_0\big(\mathsf{gwl}_{k-1}^{(\infty)}\big)$, hereby answering the open problem posed in Maron et al. (2019a). Finally, we observe that the k-IGNs used in Maron et al. (2019b) to show the inclusion $\rho_1\big(k\text{-IGN}^{(t)}\big) \subseteq \rho_1\big(\mathsf{vwl}_{k-1}^{(t)}\big)$ are of very simple form. By defining a simple class of k-IGNs, denoted by k-GINs, we obtain

$$\rho_1\big(k\text{-GIN}^{(t)}\big) = \rho_1\big(\mathsf{vwl}_{k-1}^{(t)}\big),$$

hereby recovering the layer/round connections.

We start with the following lemma:

Lemma D.1. *For any $k \geq 2$, a t layer k-IGNs can be represented in $\mathsf{TL}_k^{(tk)}(\Omega)$.*

Before proving this lemma, we recall k-IGNs. These are architectures that consist of linear equivariant layers. Such linear layers allow for an explicit description. Indeed, following Maron et al. (2019c), let $\sim_\ell$ be the equality pattern equivalence relation on $[n]^\ell$ such that for $\boldsymbol{a}, \boldsymbol{b} \in [n]^\ell$, $\boldsymbol{a} \sim_\ell \boldsymbol{b}$ if and only if $a_i = a_j \Leftrightarrow b_i = b_j$ for all $j \in [\ell]$. We denote by $[n]^\ell/_{\sim_\ell}$ the equivalence classes induced by $\sim_\ell$. Let us denote by $\mathbf{F}^{(t-1)} \in \mathbb{R}^{n^k \times d_{t-1}}$ the tensor computed by an k-IGN in layer $t-1$. Then, in layer t, a new tensor in $\mathbb{R}^{n^k \times d_t}$ is computed, as follows. For $j \in [d_t]$ and $v_1, \ldots, v_k \in [n]^k$:

$$F_{v_1,\ldots,v_k,j}^{(t)} := \sigma\left(\sum_{\gamma \in [n]^{2k}/_{\sim_{2k}}} \sum_{\boldsymbol{w} \in [n]^k} \mathbf{1}_{(\boldsymbol{v},\boldsymbol{w}) \in \gamma} \sum_{i \in [d_{t-1}]} c_{\gamma,i,j} F_{w_1,\ldots,w_k,i}^{(t-1)} + \sum_{\mu \in [n]^k/_{\sim_k}} \mathbf{1}_{\boldsymbol{v} \in \mu} b_{\mu,j} \right) \quad (1)$$

for activation function σ, constants $c_{\gamma,i,j}$ and $b_{\mu,j}$ in $\mathbb{R}$ and where $\mathbf{1}_{(\boldsymbol{v},\boldsymbol{w}) \in \gamma}$ and $\mathbf{1}_{\boldsymbol{v} \in \mu}$ are indicator functions for the $2k$-tuple $(\boldsymbol{v}, \boldsymbol{w})$ to be in the equivalence class $\gamma \in [n]^{2k}/_{\sim_{2k}}$ and the k-tuple $\boldsymbol{v}$ to be in class $\mu \in [n]^k/_{\sim_k}$. As initial tensor $\mathbf{F}^{(0)}$ one defines $F_{v_1,\ldots,v_k,j}^{(0)} := \mathsf{atp}_k(G, \boldsymbol{v}) \in \mathbb{R}^{d_0}$, with $d_0 = 2\binom{k}{2} + k\ell$ where ℓ is the number of initial vertex labels, just as for k-FGNNs.

We remark that the need for having a summation depth of tk in the expressions in $\mathsf{TL}_k(\Omega)$, or equivalently for requiring tk rounds of $(k-1)$-WL, can intuitively be explained that each layer of a k-IGN aggregates more information from "neighbouring" k-tuples than $(k-1)$-WL does. Indeed, in each layer, an k-IGN can use previous tuple embeddings of all possible k-tuples. In a single round of $(k-1)$-WL only previous tuple embeddings from specific sets of k-tuples are used. It is only after an additional $k-1$ rounds, that k-WL gets to the information about arbitrary k-tuples, whereas this information is available in a k-IGN in one layer directly.

Proof of Lemma D.1. We have seen how $\mathbf{F}^{(0)}$ can be represented in $\mathsf{TL}_k(\Omega)$ when dealing with k-FGNNs. We assume now that also the $t-1$th layer $\mathbf{F}^{(t-1)}$ can be represented by d_{t-1} expressions in $\mathsf{TL}_k^{((t-1)k)}(\Omega)$ and show that the same holds for the tth layer.

We first represent $\mathbf{F}^{(t)}$ in $\mathsf{TL}_{2k}(\Omega)$, based on the explicit description given earlier. The expressions use index variables $x_1, \ldots, x_k$ and $y_1, \ldots, y_k$. More specifically, for $j \in [d_t]$ we consider the expressions:

$$\varphi_j^{(t)}(x_1, \ldots, x_k) = \sigma\left(\sum_{\gamma \in [n]^{2k}/_{\sim_{2k}}} \sum_{i=1}^{d_{t-1}} c_{\gamma,i,j} \right.$$
$$\sum_{y_1} \cdots \sum_{y_k} \psi_\gamma(x_1, \ldots, x_k, y_1, \ldots, y_k) \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k)$$
$$\left. + \sum_{\mu \in [n]^k/_{\sim_k}} b_{\mu,j} \cdot \psi_\mu(x_1, \ldots, x_k) \right), \quad (2)$$

where $\psi_\mu(x_1, \ldots, x_k)$ is a product of expressions of the form $\mathbf{1}_{x_i \,\mathsf{op}\, x_j}$ encoding the equality pattern μ, and similarly, $\psi_\gamma(x_1, \ldots, x_k, y_1, \ldots, y_k)$ is a product of expressions of the form $\mathbf{1}_{x_i \,\mathsf{op}\, x_j}$, $\mathbf{1}_{y_i \,\mathsf{op}\, y_j}$ and $\mathbf{1}_{x_i \,\mathsf{op}\, y_j}$ encoding the equality pattern γ. These expressions are indicator functions for the their corresponding equality patterns. That is,

$$\pi_G[\![\psi_\gamma, (\boldsymbol{v}, \boldsymbol{w})]\!] = \begin{cases} 1 & \text{if } (\boldsymbol{v}, \boldsymbol{w}) \in \gamma \\ 0 & \text{otherwise} \end{cases} \qquad \pi_G[\![\psi_\mu, \boldsymbol{v}]\!] = \begin{cases} 1 & \text{if } \boldsymbol{v} \in \mu \\ 0 & \text{otherwise} \end{cases}$$

We remark that in the expressions $\varphi_j^{(t)}$ we have two kinds of summations: those ranging over a fixed number of elements (over equality patterns, feature dimension), and those ranging over the index variables $y_1, \ldots, y_k$. The latter are the only ones contributing the summation depth. The former are just concise representations of a long summation over a fixed number of expressions.

We now only need to show that we can equivalently write $\varphi_j^{(t)}(x_1, \ldots, x_k)$ as expressions in $\mathsf{TL}_k(\Omega)$, that is, using only indices $x_1, \ldots, x_k$. As such, we can already ignore the term $\sum_{\mu \in [n]^k / \sim_k} b_{\mu, j} \cdot \psi_\mu(x_1, \ldots, x_k)$ since this is already in $\mathsf{TL}_k(\Omega)$. Furthermore, this expressions does not affect the summation depth.

Furthermore, as just mentioned, we can expand expression $\varphi_j^{(t)}$ into linear combinations of other simpler expressions. As such, it suffices to show that k index variables suffice for each expression of the form:

$$\sum_{y_1} \cdots \sum_{y_k} \psi_\gamma(x_1, \ldots, x_k, y_1, \ldots, y_k) \cdot \varphi_i^{(t)}(y_1, \ldots, y_k), \tag{3}$$

obtained by fixing μ and i in expression (2). To reduce the number of variables, as a first step we eliminate any disequality using the inclusion-exclusion principle. More precisely, we observe that $\psi_\gamma(\boldsymbol{x}, \boldsymbol{y})$ can be written as:

$$\prod_{(i,j) \in I} \mathbf{1}_{x_i = x_j} \cdot \prod_{(i,j) \in \bar{I}} \mathbf{1}_{x_i \neq x_j} \cdot \prod_{(i,j) \in J} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in \bar{J}} \mathbf{1}_{y_i \neq y_j} \prod_{(i,j) \in K} \mathbf{1}_{x_i = y_j} \cdot \prod_{(i,j) \in \bar{K}} \mathbf{1}_{x_i \neq y_j}$$

$$= \sum_{A \subseteq \bar{I}} \sum_{B \subseteq \bar{J}} \sum_{C \subseteq \bar{K}} (-1)^{|A| + |B| + |C|} \prod_{(i,j) \in I \cup A} \mathbf{1}_{x_i = x_j} \prod_{(i,j) \in J \cup B} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in J \cup C} \mathbf{1}_{x_i = y_j}, \tag{4}$$

for some sets I, J and K of pairs of indices in $[k]^2$, and where $\bar{I} = [k]^2 \setminus I$, $\bar{J} = [k]^2 \setminus J$ and $\bar{K} = [k]^2 \setminus K$. Here we use that $\mathbf{1}_{x_i \neq x_j} = 1 - \mathbf{1}_{x_i = x_j}$, $\mathbf{1}_{y_i \neq y_j} = 1 - \mathbf{1}_{y_i = y_j}$ and $\mathbf{1}_{x_i \neq y_j} = 1 - \mathbf{1}_{y_i = y_j}$ and use the inclusion-exclusion principle to obtain a polynomial in equality conditions only.

In view of expression (4), we can push the summations over $y_1, \ldots, y_k$ in expression (3) to the subexpressions that actually use $y_1, \ldots, y_k$. That is, we can rewrite expression (3) into the equivalent expression:

$$\sum_{A \subseteq \bar{I}} \sum_{B \subseteq \bar{J}} \sum_{C \subseteq \bar{K}} (-1)^{|A| + |B| + |C|} \cdot \prod_{(i,j) \in I \cup A} \mathbf{1}_{x_i = x_j}$$

$$\cdot \left(\sum_{y_1} \cdots \sum_{y_k} \prod_{(i,j) \in J \cup B} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in K \cup C} \mathbf{1}_{x_i = y_j} \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k) \right). \tag{5}$$

By fixing A, B and C, it now suffices to argue that

$$\prod_{(i,j) \in I \cup A} \mathbf{1}_{x_i = x_j} \cdot \left(\sum_{y_1} \cdots \sum_{y_k} \prod_{(i,j) \in J \cup B} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in K \cup C} \mathbf{1}_{x_i = y_j} \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k) \right), \tag{6}$$

can be equivalently expressed in $\mathsf{TL}_k(\Omega)$.

Since our aim is to reduced the number of index variables from $2k$ to k, it is important to known which variables are the same. In expression (6), some equalities that hold between the variables may not be explicitly mentioned. For this reason, we expand $I \cup A$, $J \cup B$ and $K \cup C$ with their implied equalities. That is, $\mathbf{1}_{x_i = x_j}$ is added to $I \cup A$, if for any $(\boldsymbol{v}, \boldsymbol{w})$ such that

$$\pi_G \llbracket \prod_{(i,j) \in I \cup A} \mathbf{1}_{x_i = x_j} \cdot \prod_{(i,j) \in J \cup B} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in K \cup C} \mathbf{1}_{x_i = y_j}, (\boldsymbol{v}, \boldsymbol{w}) \rrbracket = 1 \Rightarrow \pi_G \llbracket \mathbf{1}_{x_i = x_j}, \boldsymbol{v} \rrbracket = 1$$

holds. Similar implied equalities $\mathbf{1}_{y_i = y_j}$ and $\mathbf{1}_{x_i = y_j}$ are added to $J \cup B$ and $K \cup C$, respectively. let us denoted by I', J' and K'. It should be clear that we can add these implied equalities to expression (6) without changing its semantics. In other words, expression (6) can be equivalently represented by

$$\prod_{(i,j) \in I'} \mathbf{1}_{x_i = x_j} \cdot \left(\sum_{y_1} \cdots \sum_{y_k} \prod_{(i,j) \in J'} \mathbf{1}_{y_i = y_j} \cdot \prod_{(i,j) \in K'} \mathbf{1}_{x_i = y_j} \cdot \varphi_i^{((t-1)}(y_1, \ldots, y_k) \right), \tag{7}$$

There now two types of index variables among the $y_1, \ldots, y_k$: those that are equal to some x_i, and those that are not. Now suppose that $(j, j') \in J'$, and thus $y_j = y_{j'}$, and that also $(i, j) \in K'$, and thus $x_i = y_j$. Since we included the implied equalities, we also have $(i, j') \in K'$, and thus $x_i = y_{j'}$. There is no reason to keep $(j, j') \in J'$ as it is implied by (i, j) and $(i, j') \in K'$. We can thus safely remove all pairs (j, j') from J' such that $(i, j) \in K'$ (and thus also $(i, j') \in K'$). We denote by J'' be the reduced set of pairs of indices obtained from J' in this way. We have that expression (7) can be equivalently written as

$$\prod_{(i,j) \in I'} \mathbf{1}_{x_i = x_j} \cdot \left(\sum_{y_1} \cdots \sum_{y_k} \prod_{(i,j) \in K'} \mathbf{1}_{x_i = y_j} \cdot \prod_{(i,j) \in J''} \mathbf{1}_{y_i = y_j} \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k) \right), \quad (8)$$

where we also switched the order of equalities in J'' and K'. Our construction of J'' and K' ensures that none of the variables y_j with j belonging to a pair in J'' is equal to some x_i.

By contrast, the variable y_j occurring in $(i, j) \in K'$ are equal to x_i. We observe, however, that also certain equalities among the variables $\{x_1, \ldots, x_k\}$ hold, as represented by the pairs in I'. let $I'(i) := \{i' \mid (i, i') \in I'\}$ and define $\hat{i}$ as a unique representative element in $I'(i)$. For example, one can take $\hat{i}$ to be smallest index in $I'(i)$. We use this representative index (and corresponding x-variable) to simplify K'. More precisely, we replace each pair $(i, j) \in K'$ with the pair $(\hat{i}, j)$. In terms of variables, we replace $x_i = y_j$ with $x_{\hat{i}} = y_j$. Let K'' be the set K'' modified in that way. Expression (8) can thus be equivalently written as

$$\prod_{(i,j) \in I'} \mathbf{1}_{x_i = x_j} \cdot \left(\sum_{y_1} \cdots \sum_{y_k} \prod_{(\hat{i},j) \in K''} \mathbf{1}_{x_{\hat{i}} = y_j} \cdot \prod_{(i,j) \in J''} \mathbf{1}_{y_i = y_j} \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k) \right), \quad (9)$$

where the free index variables of the subexpression

$$\sum_{y_1} \cdots \sum_{y_k} \prod_{(\hat{i},j) \in K''} \mathbf{1}_{x_{\hat{i}} = y_j} \cdot \prod_{(i,j) \in J''} \mathbf{1}_{y_i = y_j} \cdot \varphi_i^{(t-1)}(y_1, \ldots, y_k) \quad (10)$$

are precisely the index variables $x_{\hat{i}}$ for $(\hat{i}, j) \in K''$. Recall that our aim is to reduce the variables from $2k$ to k. We are now finally ready to do this. More specifically, we consider a bijection $\beta : \{y_1, \ldots, y_k\} \to \{x_1, \ldots, x_k\}$ in which ensure that for each $\hat{i}$ there is a j such that $(\hat{i}, j) \in K''$ and $\beta(y_j) = x_{\hat{i}}$. Furthermore, among the summations $\sum_{y_1} \cdots \sum_{y_k}$ we can ignore those for which $\beta(y_j) = x_{\hat{i}}$ holds. After all, they only contribute for a given $x_{\hat{i}}$ value. Let Y be those indices in $[k]$ such that $\beta(y_j) \neq x_{\hat{i}}$ for some $\hat{i}$. Then, we can equivalently write expression (9) as

$$\prod_{(i,j) \in I'} \mathbf{1}_{x_i = x_j} \cdot \left(\sum_{\beta(y_i), i \in Y} \prod_{(\hat{i},j) \in K'} \mathbf{1}_{x_{\hat{i}} = \beta(y_j)} \cdot \prod_{(i,j) \in J''} \mathbf{1}_{\beta(y_i) = \beta(y_j)} \right.$$
$$\left. \cdot \beta(\varphi_i^{(t-1)}(y_1, \ldots, y_k)) \right), \quad (11)$$

where $\beta(\varphi_i^{(t-1)}(y_1, \ldots, y_k))$ denotes the expression obtained by renaming of variables $y_1, \ldots, y_j$ in $\varphi_i^{(t-1)}(y_1, \ldots, y_k)$ into x-variables according to β. This is our desired expression in $\mathsf{TL}_k(\Omega)$. If we analyze the summation depth of this expression, we have by induction that the summation depth of $\varphi_i^{(t-1)}$ is at most $(t-1)k$. In the above expression, we are increasing the summation depth with at most $|Y|$. The largest size of Y is k, which occurs when none of the y-variables are equal to any of the x-variables. As a consequence, we obtained an expression of summation depth at most tk, as desired. $\qquad \square$

As a consequence, when using k-IGNs$^{(t)}$ for vertex embeddings, using $(G, v) \to \mathbf{F}_{v,\ldots,v,:}^{(t)}$ one simply pads the layer expression with $\prod_{i \in [k]} \mathbf{1}_{x_1 = x_i}$ which does not affect the number of variables or summation depth. When using k-IGNs$^{(t)}$ of graph embeddings, an additional invariant layer is added to obtain an embedding from $G \to \mathbb{R}^{d_t}$. Such invariant layers have a similar (simpler) representation as given in equation 1 (Maron et al., 2019c), and allow for a similar analysis. One can verify that expressions in $\mathsf{TL}_k^{((t+1)k)}(\Omega)$ are needed when such an invariant layer is added to previous t layers. Based on this, Theorem 4.2, Lemma D.1 and Theorem 1 in Maron et al. (2019b), imply that $\rho_1(k\text{-IGN}) = \rho_1(\mathsf{vwl}_{k-1}^{(\infty)})$ and $\rho_0(k\text{-IGN}) = \rho_0(\mathsf{gwl}_{k-1}^{(\infty)})$ hold.

k-**dimensional GINs.** We can recover a layer-based characterization for k-IGNs that compute vertex embeddings by considering a special subset of k-IGNs. Indeed, the k-IGNs used in Maron et al. (2019b) to show $\rho_1(\text{wl}_{k-1}^{(t)}) \subseteq \rho_1(k\text{-IGN}^{(t)})$ are of a very special form. We extract the essence of these special k-IGNs in the form of k-dimensional GINs. That is, we define the class k-GINs to consist of layers defined as follows. The initial layers are just as for k-IGNs. Then, for $t \geq 1$:

$$\mathbf{F}_{v_1,\ldots,v_k,:}^{(t)} := \text{mlp}_0^{(t)}\big(\mathbf{F}_{v_1,\ldots,v_k,:}^{(t-1)}, \sum_{u \in V_G} \text{mlp}_1^{(t)}(\mathbf{F}_{u,v_2,\ldots,v_k,:}^{(t-1)}), \sum_{u \in V_G} \text{mlp}_1^{(t)}(\mathbf{F}_{v_1,u,\ldots,v_k,:}^{(t-1)})$$
$$, \ldots, \sum_{u \in V_G} \text{mlp}_1^{(t)}(\mathbf{F}_{v_1,v_2,\ldots,v_{k-1},w,:}^{(t-1)}))),$$

where $F_{v_1,v_2,\ldots,v_k,:}^{(t-1)} \in \mathbb{R}^{d_{t-1}}$, $\text{mlp}_1^{(t)} : \mathbb{R}^{d_{t-1}} \to \mathbb{R}^{b_t}$ and $\text{mlp}_1^{(t)} : \mathbb{R}^{d_{t-1}+kb_t} \to \mathbb{R}^{d_t}$ are MLPs. It is now an easy exercise to show that k-GIN$^{(t)}$ can be represented in $\text{TL}_k^{(t)}(\Omega)$ (remark that the summations used increase the summation depth with one only in each layer). Combined with Theorem 4.2 and by inspecting the proof of Theorem 1 in Maron et al. (2019b), we obtain:

Proposition D.2. *For any $k \geq 2$ and any $t \geq 0$: $\rho_1(k\text{-GIN}^{(t)}) = \rho_1(\text{vwl}_{k-1}^{(t)})$.*

We can define the invariant version of k-IGNs by adding a simple readout layer of the form

$$\sum_{v_1,\ldots,v_k \in V_G} \text{mlp}(\mathbf{F}_{v_1,\ldots,v_k,:}^{(t)}),$$

as is used in Maron et al. (2019b). We obtain, $\rho_0(k\text{-GIN}) = \rho_0(\text{gwl}_{k-1}^{(\infty)})$, by simply rephrasing the readout layer in $\text{TL}_k(\Omega)$.

E DETAILS OF SECTION 6

Let $\mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$ be the class of all continuous functions from $\mathcal{G}_s$ to $\mathbb{R}^\ell$. In this setting $\mathcal{G}_s$ is equipped with the discrete topology and $\mathbb{R}^\ell$ with the topology induced by some metric $\|.\|$. Due to the discrete topology, $\mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$ consists of all possible functions from $\mathcal{G}_s$ to $\mathbb{R}^\ell$. Consider $\mathcal{F} \subseteq \mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$ and define $\overline{\mathcal{F}}$ as the *closure of $\mathcal{F}$* in $\mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$ under the usual topology induced by $f \mapsto \sup_{G,\boldsymbol{v}}\|f(G,\boldsymbol{v})\|$. In other words, a continuous function $h : \mathcal{G}_s \to \mathbb{R}^\ell$ is in $\overline{\mathcal{F}}$ if there exists a sequence of functions $f_1, f_2, \ldots \in \mathcal{F}$ such that $\lim_{i \to \infty} \sup_{G,\boldsymbol{v}}\|f_i(G,\boldsymbol{v}) - h(G,\boldsymbol{v})\| = 0$. The following theorem provides a characterization of the closure of a set of functions. We state it here modified to our setting.

Theorem E.1 ((Timofte, 2005)). *Let $\mathcal{F} \subseteq \mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$ such that there exists a set $\mathcal{S} \subseteq \mathcal{C}(\mathcal{G}_s, \mathbb{R})$ satisfying $\mathcal{S} \cdot \mathcal{F} \subseteq \mathcal{F}$ and $\rho(\mathcal{S}) \subseteq \rho(\mathcal{F})$. Then,*

$$\overline{\mathcal{F}} := \big\{f \in \mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell) \mid \rho(F) \subseteq \rho(f), \forall(G,\boldsymbol{v}) \in \mathcal{G}_s, f(G,\boldsymbol{v}) \in \overline{\mathcal{F}(G,\boldsymbol{v})}\big\},$$

where $\mathcal{F}(G,\boldsymbol{v}) := \{h(G,\boldsymbol{v}) \mid h \in \mathcal{F}\} \subseteq \mathbb{R}^\ell$. We can equivalently replace $\rho(\mathcal{F})$ by $\rho(\mathcal{S})$ in the expression for $\overline{\mathcal{F}}$. $\square$

We will use this theorem to show Theorem 6.1 in the setting that $\mathcal{F}$ consists of functions that can be represented in $\text{TL}(\Omega)$, and more generally, sets of functions that satisfy two conditions, stated below. We more generally allow $\mathcal{F}$ to consist of functions $f : \mathcal{G}_s \to \mathbb{R}^{\ell_f}$, where the $\ell_f \in \mathbb{N}$ may depend on f. We will require $\mathcal{F}$ to satisfy the following two conditions:

concatenation-closed: If $f_1 : \mathcal{G}_s \to \mathbb{R}^p$ and $f_2 : \mathcal{G}_s \to \mathbb{R}^q$ are in $\mathcal{F}$, then $g := (f_1, f_2) : \mathcal{G}_s \to \mathbb{R}^{p+q} : (G,\boldsymbol{v}) \mapsto (f_1(G,\boldsymbol{v}), f_2(G,\boldsymbol{v}))$ is also in $\mathcal{F}$.

function-closed: For a fixed $\ell \in \mathbb{N}$, for any $f \in \mathcal{F}$ such that $f : \mathcal{G}_s \to \mathbb{R}^p$, also $h \circ f : \mathcal{G}_s \to \mathbb{R}^\ell$ is in $\mathcal{F}$ for any continuous function $h \in \mathcal{C}(\mathbb{R}^p, \mathbb{R}^\ell)$.

We denote by $\mathcal{F}_\ell$ be the subset of $\mathcal{F}$ of functions from $\mathcal{G}_s$ to $\mathbb{R}^\ell$.

Theorem 6.1. *For any ℓ, and any set $\mathcal{F}$ of functions, concatenation and function closed for ℓ, we have: $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_s \to \mathbb{R}^\ell \mid \rho_s(\mathcal{F}) \subseteq \rho_s(f)\}$.*

Proof. The proof consist of (i) verifying the existence of a set $\mathcal{S}$ as mentioned Theorem E.1; and of (ii) eliminating the pointwise convergence condition "$\forall (G, \boldsymbol{v}) \in \mathcal{G}_s, f(G, \boldsymbol{v}) \in \overline{\mathcal{F}_\ell(G, \boldsymbol{v})}$ in the closure characterization in Theorem E.1.

For showing (ii) we argue that $\overline{\mathcal{F}_\ell(G, \boldsymbol{v})} = \mathbb{R}^\ell$ such that the conditions $f(G, \boldsymbol{v}) \in \overline{\mathcal{F}_\ell(G, \boldsymbol{v})}$ is automatically satisfied for any $f \in \mathcal{C}(\mathcal{G}_s, \mathbb{R}^\ell)$. Indeed, take an arbitrary $f \in \mathcal{G}_k \to \mathbb{R}^\ell$ and consider the constant functions $b_i : \mathbb{R}^\ell \to \mathbb{R}^\ell : \boldsymbol{x} \mapsto \boldsymbol{b}_i$ with $\boldsymbol{b}_i \in \mathbb{R}^\ell$ the ith basis vector. Since $\mathcal{F}$ is function-closed for ℓ, so is $\mathcal{F}_\ell$. Hence, $b_i := g_i \circ f \in \mathcal{F}_\ell$ as well. Furthermore, if $s_a : \mathbb{R}^\ell \to \mathbb{R}^\ell : \boldsymbol{x} \mapsto a \times \boldsymbol{x}$, for $a \in \mathbb{R}$, then $s_a \circ f \in \mathcal{F}_\ell$ and thus $\mathcal{F}_\ell$ is closed under scalar multiplication. Finally, consider $+ : \mathbb{R}^{2\ell} \to \mathbb{R}^\ell : (\boldsymbol{x}, \boldsymbol{y}) \mapsto \boldsymbol{x} + \boldsymbol{y}$. For f and g in $\mathcal{F}_\ell$, $h = (f, g) \in \mathcal{F}$ since $\mathcal{F}$ is concatenation-closed. As a consequence, the function $+ \circ h : \mathcal{G}_s \to \mathbb{R}^\ell$ is in $\mathcal{F}_\ell$, showing that $\mathcal{F}_\ell$ is also closed under addition. All combined, this shows that $\mathcal{F}_\ell$ is closed under taking linear combinations and since the basis vectors of $\mathbb{R}^\ell$ can be attained, $\overline{\mathcal{F}_\ell(G, \boldsymbol{v})} := \mathbb{R}^\ell$, as desired.

For (i), we show the existence of a set $\mathcal{S} \subseteq \mathcal{C}(\mathcal{G}_s, \mathbb{R})$ such that $\mathcal{S} \cdot \mathcal{F}_\ell \subseteq \mathcal{F}_\ell$ and $\rho_s(\mathcal{S}) \subseteq \rho_s(\mathcal{F}_\ell)$ hold. Similarly as in Azizian & Lelarge (2021), we define

$$\mathcal{S} := \big\{ f \in \mathcal{C}(\mathcal{G}_s, \mathbb{R}) \mid \underbrace{(f, f, \ldots, f)}_{\ell \text{ times}} \in \mathcal{F}_\ell \big\}.$$

We remark that for $s \in \mathcal{S}$ and $f \in \mathcal{F}_\ell$, $s \cdot f : \mathcal{G}_s \to \mathbb{R}^\ell : (G, \boldsymbol{v}) \mapsto s(G, \boldsymbol{v}) \odot f(G, \boldsymbol{v})$, with $\odot$ being pointwise multiplication, is also in $\mathcal{F}_\ell$. Indeed, $s \cdot f = \odot \circ (s, f)$ with (s, f) the concatenation of s and f and $\odot : \mathbb{R}^{2\ell} \to \mathbb{R}^\ell : (\boldsymbol{x}, \boldsymbol{y}) \to \boldsymbol{x} \odot \boldsymbol{y}$ being pointwise multiplication.

It remains to verify $\rho_s(\mathcal{S}) \subseteq \rho_s(\mathcal{F}_\ell)$. Assume that $(G, \boldsymbol{v})$ and $(H, \boldsymbol{w})$ are not in $\rho_s(\mathcal{F}_\ell)$. By definition, this implies the existence of a function $\hat{f} \in \mathcal{F}_\ell$ such that $\hat{f}(G, \boldsymbol{v}) = \boldsymbol{a} \neq \boldsymbol{b} = \hat{f}(H, \boldsymbol{w})$ with $\boldsymbol{a}, \boldsymbol{b} \in \mathbb{R}^\ell$. We argue that $(G, \boldsymbol{v})$ and $(H, \boldsymbol{w})$ are also not in $\rho_s(\mathcal{S})$ either. Indeed, Proposition 1 in Maron et al. (2019b) implies that there exists natural numbers $\boldsymbol{\alpha} = (\alpha_1, \ldots, \alpha_\ell) \in \mathbb{N}^\ell$ such that the mapping $h_{\boldsymbol{\alpha}} : \mathbb{R}^\ell \to \mathbb{R} : \boldsymbol{x} \to \prod_{i=1}^\ell x_i^{\alpha_i}$ satisfies $h_{\boldsymbol{\alpha}}(\boldsymbol{a}) = a \neq b = h_{\boldsymbol{\alpha}}(\boldsymbol{b})$, with $a, b \in \mathbb{R}$. Since $\mathcal{F}$ (and thus also $\mathcal{F}_\ell$) is function-closed, $h_{\boldsymbol{\alpha}} \circ f \in \mathcal{F}_\ell$ for any $f \in \mathcal{F}_\ell$. In particular, $g := h_{\boldsymbol{\alpha}} \circ \hat{f} \in \mathcal{F}_\ell$ and concatenation-closure implies that $(g, \ldots, g) : \mathcal{G}_s \to \mathbb{R}^\ell$ is in $\mathcal{F}_\ell$ too. Hence, $g \in \mathcal{S}$, by definition. It now suffices to observe that $g(G, \boldsymbol{v}) = h_{\boldsymbol{\alpha}}(\hat{f}(G, \boldsymbol{v})) = a \neq b = h_{\boldsymbol{\alpha}}(\hat{f}(H, \boldsymbol{w})) = g(H, \boldsymbol{w})$, and thus $(G, \boldsymbol{v})$ and $(H, \boldsymbol{w})$ are not in $\rho_s(\mathcal{S})$, as desired. $\qquad\square$

When we know more about $\rho_s(\mathcal{F}_\ell)$ we can say a bit more. In the following, we let $\mathsf{alg} \in \{\mathsf{cr}^{(t)}, \mathsf{gcr}^{(t)}, \mathsf{vwl}_k^{(t)}, \mathsf{gwl}_k^{(\infty)}\}$ and only consider the setting where s is either 0 (invariant graph functions) or $s = 1$ (equivariant graph/vertex functions).

Corollary 6.2. *Under the assumptions of Theorem 6.1 and if $\rho(\mathcal{F}_\ell) = \rho(\mathsf{alg})$, then $\overline{\mathcal{F}_\ell} = \{ f : \mathcal{G}_s \to \mathbb{R}^\ell \mid \rho(\mathsf{alg}) \subseteq \rho(f) \}$.*

Proof. This is just a mere restatement of Theorem 6.1 in which $\rho_s(\mathcal{F}_\ell)$ in the condition $\rho_s(\mathcal{F}_\ell) \subseteq \rho_s(f)$ is replaced by $\rho_s(\mathsf{alg})$, where $s = 1$ for $\mathsf{alg} \in \{\mathsf{cr}^{(t)}, \mathsf{vwl}_k^{(t)}\}$ and $s = 0$ for $\mathsf{alg} \in \{\mathsf{gcr}^{(t)}, \mathsf{gwl}_k^{(\infty)}\}$. $\qquad\square$

To relate all this to functions representable by tensor languages, we make the following observations. First, if we consider $\mathcal{F}$ to be the set of all functions that can be represented in $\mathsf{GTL}^{(t)}(\Omega)$, $\mathsf{TL}_2^{(t+1)}(\Omega)$, $\mathsf{TL}_{k+1}^{(t)}(\Omega)$ or $\mathsf{TL}(\Omega)$, then $\mathcal{F}$ will be automatically concatenation and function-closed, provided that Ω consists of all functions in $\bigcup_p \mathcal{C}(\mathbb{R}^p, \mathbb{R}^\ell)$. Hence, Theorem 6.1 applies. Furthermore, our results from Section 4 tell us that for all $t \geq 0$, and $k \geq 1$, $\rho_1(\mathsf{cr}^{(t)}) = \rho_1(\mathsf{GTL}^{(t)}(\Omega))$, $\rho_0(\mathsf{gcr}^{(t)}) = \rho_0(\mathsf{TL}_2^{(t+1)}(\Omega)) = \rho_0(\mathsf{gwl}_1^{(t)})$, $\rho_1(\mathsf{ewl}_k^{(t)}) = \rho_1(\mathsf{TL}_{k+1}^{(t)}(\Omega))$, and $\rho_0(\mathsf{TL}_{k+1}(\Omega)) = \rho_0(\mathsf{gwl}_k^{(\infty)})$. As a consequence, Corollary 6.2 applies as well. We thus easily obtain the following characterizations:

Proposition E.2. *For any $t \geq 0$ and $k \geq 1$:*

- *If $\mathcal{F}$ consists of all functions representable in $\mathsf{GTL}^{(t)}(\Omega)$, then $\overline{\mathcal{F}_\ell} = \{ f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{cr}^{(t)}) \subseteq \rho_1(f) \}$;*

- *If $\mathcal{F}$ consists of all functions representable in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$, then $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{vwl}_k^{(t)}) \subseteq \rho_1(f)\}$;*

- *If $\mathcal{F}$ consists of all functions representable in $\mathsf{TL}_2^{(t+1)}(\Omega)$, then $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_0 \to \mathbb{R}^\ell \mid \rho_0(\mathsf{gwl}_1^{(t)}) \subseteq \rho_0(f)\}$; and finally,*

- *If $\mathcal{F}$ consists of all functions representable in $\mathsf{TL}_{k+1}(\Omega)$, then $\overline{\mathcal{F}_\ell} = \{f : \mathcal{G}_0 \to \mathbb{R}^\ell \mid \rho_0(\mathsf{gwl}_k^{(\infty)}) \subseteq \rho_0(f)\}$,*

provided that Ω consists of all functions in $\bigcup_p \mathcal{C}(\mathbb{R}^p, \mathbb{R}^\ell)$.

In fact, Lemma 32 in Azizian & Lelarge (2021) implies that we can equivalently populate Ω with all MLPs instead of all continuous functions. We can thus use MLPs and continuous functions interchangeably when considering the closure of functions.

At this point, we want to make a comparison with the results and techniques in Azizian & Lelarge (2021). Our proof strategy is very similar and is also based on Theorem E.1. The key distinguishing feature is that we consider functions $f : \mathcal{G}_s \to \mathbb{R}^{\ell_f}$ instead of functions from graphs alone. This has as great advantage that no separate proofs are needed to deal with invariant or equivariant functions. Equivariance incurs quite some complexity in the setting considered in Azizian & Lelarge (2021). A second major difference is that, by considering functions representable in tensor languages, and based on our results from Section 4, we obtain a more fine-grained characterization. Indeed, we obtain characterizations in terms of the number of rounds used in CR and k-WL. In Azizian & Lelarge (2021), t is always set to ∞, that is, an unbounded number of rounds is considered. Furthermore, when it concerns functions $f : \mathcal{G}_1 \to \mathbb{R}^{\ell_f}$, we recall that CR is different from 1-WL. Only 1-WL is considered in Azizian & Lelarge (2021). Finally, another difference is that we define the equivariant version vwl_k in a different way than is done in Azizian & Lelarge (2021), because in this way, a tighter connection to logics and tensor languages can be made. In fact, if we were to use the equivariant version of k-WL from Azizian & Lelarge (2021), then we necessarily have to consider an unbounded number of rounds (similarly as in our gwl_k case). On the other hand, Azizian & Lelarge (2021) also consider graphs with continuous vertex features.

We conclude this section by providing a little more details about the consequences of the above results for GNNs. As we already mentioned in Section 6.2, many common GNN architectures are concatenation and function-closed (using MLPs instead of continuous functions). This holds, for example, for the classes $\mathsf{GIN}_\ell^{(t)}$, $\mathsf{eGIN}_\ell^{(t)}$, $k\text{-}\mathsf{FGNN}_\ell^{(t)}$ and $k\text{-}\mathsf{GIN}_\ell^{(t)}$ and $k\text{-}\mathsf{IGN}^{(t)}$, as described in Section 5 and further detailed in Section D and C. Here, the subscript ℓ refers to the dimension of the embedding space.

We now consider a function f that is not more separating than $\mathsf{cr}^{(t)}$ (respectively, $\mathsf{gcr}^{(t)}$, $\mathsf{vwl}_k^{(t)}$ or $\mathsf{gwl}_k^{(\infty)}$, for some $k \geq 1$), and want to know whether f can be approximated by a class of GNNs. Proposition E.2 tells that such f can be approximated by a class of GNNs as long as these are at least as separating as $\mathsf{GTL}^{(t)}$ (respectively, $\mathsf{TL}_2^{(t+1)}$, $\mathsf{TL}_{k+1}^{(t)}$ or $\mathsf{TL}_{k+1}^{(\infty)}$). This, in turn, amounts showing that the GNNs can be represented in the corresponding tensor language fragment, and that they can match the corresponding labeling algorithm in separation power. We illustrate this for the GNN architectures mentioned above.

- In Section 5 we showed that $\mathsf{GIN}_\ell^{(t)}$ can be represented in $\mathsf{GTL}^{(t)}(\Omega)$. Theorem 4.3 then implies that $\rho_1(\mathsf{cr}^{(t)}) \subseteq \rho_1(\mathsf{GIN}_\ell^{(t)})$. Furthermore, Xu et al. (2019) showed that $\rho_1(\mathsf{GIN}_\ell^{(t)}) \subseteq \rho_1(\mathsf{cr}^{(t)})$. As a consequence, $\rho_1(\mathsf{GIN}_\ell^{(t)}) = \rho_1(\mathsf{cr}^{(t)})$.

- In Section 5 we showed that $\mathsf{eGIN}_\ell^{(t)}$ can be represented in $\mathsf{TL}_2^{(t)}(\Omega)$. Theorem 4.2 then implies that $\rho_1(\mathsf{vwl}_1^{(t)}) \subseteq \rho_1(\mathsf{eGIN}_\ell^{(t)})$. Furthermore, Barceló et al. (2020) showed that $\rho_1(\mathsf{eGIN}_\ell^{(t)}) \subseteq \rho_1(\mathsf{vwl}_1^{(t)})$. As a consequence, $\rho_1(\mathsf{eGIN}_\ell^{(t)}) = \rho_1(\mathsf{vwl}_1^{(t)})$.

- In Section 5 we mentioned (see details in Section C) that $k\text{-}\mathsf{FGNN}_\ell^{(t)}$ can be represented in $\mathsf{TL}_{k+1}^{(t)}(\Omega)$. Theorem 4.2 then implies that $\rho_1(\mathsf{vwl}_k^{(t)}) \subseteq \rho_1(k\text{-}\mathsf{FGNN}_\ell^{(t)})$. Furthermore, Maron et al. (2019b) showed that $\rho_1(k\text{-}\mathsf{FGNN}_\ell^{(t)}) \subseteq \rho_1(\mathsf{vwl}_k^{(t)})$. As a consequence, $\rho_1(k\text{-}\mathsf{FGNN}_\ell^{(t)}) \subseteq \rho_1(\mathsf{vwl}_k^{(t)})$. Similarly, $\rho_1((k+1)\text{-}\mathsf{GIN}_\ell^{(t)}) = \rho_1(\mathsf{vwl}_k^{(t)})$ for the special class of $(k+1)$-IGNs described in Section D.

- When $\mathsf{GIN}_\ell^{(t)}$ or $\mathsf{eGIN}_\ell^{(t)}$ are extended with a readout layer, we showed in Section 5 that these can be represented in $\mathsf{TL}_2^{(t+1)}(\Omega)$. Theorem 4.4 and the results by Xu et al. (2019) and Barceló et al. (2020) then imply that $\rho_0(\mathsf{vwl}_1^{(t)})$ and $\rho_0(\mathsf{gcr}^{(t)})$ coincide with the separation power of these architectures with a readout layer.

- Similarly, when k-FGNN or $(k+1)$-IGNs are used for graph embeddings, we can represent these in $\mathsf{TL}_{k+1}(\Omega)$ resulting again that their separation power coincides with that of $\mathsf{gwl}_k^{(\infty)}$.

So for all these architectures, Corollary 6.2 applies and we can characterize the closures of these architectures in terms of functions that not more separating than their corresponding versions of cr or k-WL, as described in the main paper. In summary,

Proposition E.3. *For any $t \geq 0$:*

$$\overline{\mathsf{GIN}_\ell^{(t)}} = \{f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{cr}^{(t)}) \subseteq \rho_1(f)\} = \overline{\mathsf{GTL}^{(t)}(\Omega)_\ell}$$

$$\overline{\mathsf{eGIN}_\ell^{(t)}} = \{f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{vwl}_1^{(t)}) \subseteq \rho_1(f)\} = \overline{\mathsf{TL}_2^{(t)}(\Omega)_\ell}$$

and when extended with a readout layer:

$$\overline{\mathsf{GIN}_\ell^{(t)}} = \overline{\mathsf{eGIN}_\ell^{(t)}} = \{f : \mathcal{G}_0 \to \mathbb{R}^\ell \mid \rho_0(\mathsf{gwl}_1^{(t)}) \subseteq \rho_0(f)\} = \overline{\mathsf{TL}_2^{(t+1)}(\Omega)_\ell}.$$

Furthermore, for any $k \geq 1$

$$\overline{k\text{-}\mathsf{FGNN}_\ell^{(t)}} = \overline{k\text{-}\mathsf{GIN}_\ell^{(t)}} = \{f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{vwl}_k^{(t)}) \subseteq \rho_1(f)\} = \overline{\mathsf{TL}_{k+1}^{(t)}(\Omega)_\ell}$$

$$\overline{(k+1)\text{-}\mathsf{IGN}_\ell} = \{f : \mathcal{G}_1 \to \mathbb{R}^\ell \mid \rho_1(\mathsf{vwl}_k^{(\infty)}) \subseteq \rho_1(f)\} = \overline{\mathsf{TL}_{k+1}(\Omega)_\ell}$$

and when converted into graph embeddings:

$$\overline{k\text{-}\mathsf{FGNN}_\ell} = \overline{k\text{-}\mathsf{GIN}_\ell} = \overline{(k+1)\text{-}\mathsf{IGN}_\ell} = \{f : \mathcal{G}_0 \to \mathbb{R}^\ell \mid \rho_0(\mathsf{gwl}_k^{(\infty)}) \subseteq \rho_0(f)\} = \overline{\mathsf{TL}_{k+1}(\Omega)_\ell},$$

where the closures of the tensor languages are interpreted as the closure of the graph or graph/vertex functions that they can represent.

F   DETAILS ON TREEWIDTH AND PROPOSITION 4.5

As an extension of our main results in Section 4, we enrich the class of tensor language expressions for which connections to k-WL exist. More precisely, instead of requiring expressions to belong to $\mathsf{TL}_{k+1}(\Omega)$, that is to only use $k+1$ index variables, we investigate when expressions in $\mathsf{TL}(\Omega)$ are *semantically equivalent* to an expression using $k+1$ variables. Proposition 4.5 identifies a large class of such expressions, those of treewidth k. As a consequence, even when representing GNN architectures may require more than $k+1$ index variables, sometimes this number can be reduced. As a consequence of our results, this implies that their separation power is in fact upper bounded by ℓ-WL for a smaller $\ell < k$. Stated otherwise, to boost the separation power of GNNs, the treewidth of the expressions representing the layers of the GNNs must have large treewidth.

We next introduce some concepts related to treewidth. We here closely follow the exposition given in Abo Khamis et al. (2016) for introducing treewidth by means variable elimination sequences of hypergraphs.

F.1   ELIMINATION SEQUENCES

We first define elimination sequences for hypergraphs. Later on, we show how to associate such hypergraphs to expressions in tensor languages, allowing us to define elimination sequences for tensor language expressions.

With a *multi-hypergraph* $\mathcal{H} = (\mathcal{V}, \mathcal{E})$ we simply mean a multiset $\mathcal{E}$ of subsets of vertices $\mathcal{V}$. An *elimination hypergraph sequences* is a vertex ordering $\sigma = v_1, \ldots, v_n$ of the vertices of $\mathcal{H}$. With such a sequence σ, we can associate for $j = n, n-1, n-2, \ldots, 1$ a sequence of n multi-hypergraphs $\mathcal{H}_n^\sigma, \mathcal{H}_{n-1}^\sigma, \ldots, \mathcal{H}_1^\sigma$ as follows. We define

$$\mathcal{H}_n := (\mathcal{V}_n, \mathcal{E}_n) := \mathcal{H}$$

$$\partial(v_n) := \{F \in \mathcal{E}_n \mid v_n \in F\}$$
$$U_n := \bigcup_{F \in \partial(v_n)} F.$$

and for $j = n - 1, n - 2, \ldots, 1$:

$$\mathcal{V}_j := \{v_1, \ldots, v_j\}$$
$$\mathcal{E}_j := (\mathcal{E}_{j+1} \setminus \partial(v_{j+1})) \cup \{U_{j+1} \setminus \{v_{j+1}\}\}$$
$$\partial(v_j) := \{F \in \mathcal{E}_j \mid v_j \in F\}$$
$$U_j := \bigcup_{F \in \partial(v_j)} F.$$

The *induced width* on $\mathcal{H}$ by σ is defined as $\max_{i \in [n]} |U_i| - 1$. We further consider the setting in which $\mathcal{H}$ has some distinguished vertices. As we will see shortly, these distinguished vertices correspond to the free index variables of tensor language expressions. Without loss of generality, we assume that the distinguished vertices are $v_1, v_2, \ldots, v_f$. When such distinguished vertices are present, an elimination sequence is just as before, except that the distinguished vertices come first in the sequence. If $v_1, \ldots, v_f$ are the distinguished vertices, then we define the induced width of the sequence as $f + \max_{f+1 \leq i \leq n} |U_i \setminus \{v_1, \ldots, v_f\}| - 1$. In other words, we count the number of distinguished vertices, and then augment it with the induced width of the sequence, starting from v_{f+1} to to v_n, hereby ignoring the distinguished variables in the U_i's. One could, more generally, also try to reduce the number of free index variables but we assume that this number is fixed, similarly as how GNNs operate.

F.2 Conjunctive TL expressions and treewidth

We start by considering a special form of TL expressions, which we refer to as *conjunctive* TL expressions, in analogy to conjunctive queries in database research and logic. A conjunctive TL expression is of the form

$$\varphi(\boldsymbol{x}) = \sum_{\boldsymbol{y}} \psi(\boldsymbol{x}, \boldsymbol{y}).$$

where $\boldsymbol{x}$ denote the free index variables, $\boldsymbol{y}$ contains all index variables under the scope of a summation, and finally, $\psi(\boldsymbol{x}, \boldsymbol{y})$ is a product of base predicates in TL. That is, $\psi(\boldsymbol{x}, \boldsymbol{y})$ is a product of $E(z_i, z_j)$ and $P_\ell(z_i)$ with z_i, z_j variables in $\boldsymbol{x}$ or $\boldsymbol{y}$. With such a conjunctive TL expression, one can associate a multi-hypergraph in a canonical way (Abo Khamis et al., 2016). More precisely, given a conjunctive TL expression $\varphi(\boldsymbol{x})$ we define $\mathcal{H}_\varphi$ as:

- $\mathcal{V}_\varphi$ consist of all index variables in $\boldsymbol{x}$ and $\boldsymbol{y}$;
- $\mathcal{E}_\varphi$: for each atomic base predicate τ in ψ we have an edge F_τ containing the indices occurring in the predicate; and
- the vertices corresponding to the free index variables $\boldsymbol{x}$ form the distinguishing set of vertices.

We now define an *elimination sequence for* φ as an elimination sequence for $\mathcal{H}_\varphi$ taking the distinguished vertices into account. The following observation ties elimination sequences of φ to the number of variables needed to express φ.

Proposition F.1. *Let $\varphi(\boldsymbol{x})$ be a conjunctive TL expression for which an elimination sequence of induced with $k - 1$ exists. Then $\varphi(\boldsymbol{x})$ is equivalent to an expression $\tilde{\varphi}(\boldsymbol{x})$ in TL_k.*

Proof. We show this by induction on the number of vertices in $\mathcal{H}_\varphi$ which are not distinguished. For the base case, all vertices are distinguished and hence $\varphi(\boldsymbol{x})$ does not contain any summation and is an expression in TL_k itself.

Suppose that in $\mathcal{H}_\varphi$ there are p undistinguished vertices. That is,

$$\varphi(\boldsymbol{x}) = \sum_{y_1} \cdots \sum_{y_p} \psi(\boldsymbol{x}, \boldsymbol{y}).$$

By assumption, we have an elimination sequence of the undistinguished vertices. Assume that y_p is first in this ordering. Let us write

$$\varphi(\boldsymbol{x}) = \sum_{y_1} \cdots \sum_{y_p} \psi(\boldsymbol{x}, \boldsymbol{y})$$

$$= \sum_{y_1} \cdots \sum_{y_{p-1}} \psi_1(\boldsymbol{x}, \boldsymbol{y} \setminus y_p) \cdot \sum_{y_p} \psi_2(\boldsymbol{x}, \boldsymbol{y})$$

where ψ_1 is the product of predicates corresponding to the edges $F \in \mathcal{E}_\varphi \setminus \partial(y_p)$, that is, those not containing y_p, and ψ_2 is the product of all predicates corresponding to the edges $F \in \partial(y_p)$, that is, those containing the predicate y_p. Note that, because of the induced width of $k - 1$, $\sum_{y_p} \psi_2(\boldsymbol{x}, \boldsymbol{y})$ contains all indices in U_p which is of size $\leq k$. We now replace the previous expression with another expression

$$\varphi'(\boldsymbol{x}) = \sum_{y_1} \cdots \sum_{y_{p-1}} \psi_1(\boldsymbol{x}, \boldsymbol{y} \setminus y_p) \cdot R_p(\boldsymbol{x}, \boldsymbol{y})$$

Where R_p is regarded as an $|U_p| - 1$-ary predicate over the indices in $U_p \setminus y_p$. It is now easily verified that $\mathcal{H}_{\varphi'}$ is the hypergraph $\mathcal{H}_{p-1}$ corresponding to the variable ordering σ. We note that this is a hypergraph over $p - 1$ undistinguished vertices. We can apply the induction hypothesis and replace $\varphi'(\boldsymbol{x})$ with its equivalent expression $\tilde{\varphi}'(\boldsymbol{x})$ in TL_k. To obtain the expression $\tilde{\varphi}(\boldsymbol{x})$ of $\varphi(\boldsymbol{x})$, it now remains to replace the new predicate R_p with its defining expression. We note again that R_p contains at most $k - 1$ indices, so it will occur in $\tilde{\varphi}'(\boldsymbol{x})$ in the form $R_p(\boldsymbol{x}, \boldsymbol{z})$ where $|\boldsymbol{z}| \leq k - 1$. In other words, one of the variables in $\boldsymbol{z}$ is not used, say z_s, and we can simply replace $R_p(\boldsymbol{x}, \boldsymbol{z})$ by $\sum_{z_s} \psi_x(\boldsymbol{x}, \boldsymbol{z}, z_s)$. $\square$

As a consequence, one way of showing that a conjunctive expression $\varphi(\boldsymbol{x})$ in TL is equivalently expressible in TL_k, is to find an elimination sequence of induced width $k - 1$. This in turn is equivalent to $\mathcal{H}_\varphi$ having a *treewidth* of $k - 1$, as is shown, e.g., in Abo Khamis et al. (2016). As usual, we define the treewidth of a conjunctive expression $\varphi(\boldsymbol{x})$ in TL as the treewidth of its associated hypergraph $\mathcal{H}_\varphi$.

We recall the definition of treewidth (modified to our setting): A *tree decomposition* $T = (V_T, E_T, \xi_T)$ of $\mathcal{H}_\varphi$ with $\xi_T : V_T \to 2^{\mathcal{V}}$ is such that

- For any $F \in \mathcal{E}$, there is a $t \in V_T$ such that $F \subseteq \xi_T(t)$; and
- For any $v \in \mathcal{V}$ corresponding to a non-distinguished index variable, the set $\{t \mid t \in V_T, v \in \xi(t)\}$ is not empty and forms a connected sub-tree of T.

The *width of a tree decomposition* T is given by $\max_{t \in V_T} |\xi_T(t)| - 1$. Now the treewidth of $\mathcal{H}_\varphi$, $\mathsf{tw}(\mathcal{H})$ is the minimum width of any of its tree decompositions. We denote by $\mathsf{tw}(\varphi)$ the treewidth of $\mathcal{H}_\varphi$. Again, similar modifications are used when distinguished vertices are in place. Referring again to Abo Khamis et al. (2016), $\mathsf{tw}(\varphi) = k - 1$ is equivalent to having a variable elimination sequence for φ of an induced width of $k - 1$. Hence, combining this observation with Proposition F.1 results in:

Corollary F.2. *Let $\varphi(\boldsymbol{x})$ be a conjunctive TL expression of treewidth $k - 1$. Then $\varphi(\boldsymbol{x})$ is equivalent to an expression $\tilde{\varphi}(\boldsymbol{x})$ in TL_k.*

That is, we have established Proposition 4.5 for conjunctive TL expressions. We next lift this to arbitrary $\mathsf{TL}(\Omega)$ expressions.

F.3 Arbitrary $\mathsf{TL}(\Omega)$ expressions

First, we observe that any expression in TL can be written as a linear combination of conjunctive expressions. This readily follows from the linearity of the operations in TL and that equality and inequality predicates can be eliminated. More specifically, we may assume that $\varphi(\boldsymbol{x})$ in TL is of the form

$$\sum_{\alpha \in A} a_\alpha \psi_\alpha(\boldsymbol{x}, \boldsymbol{y}),$$

with A finite set of indices and $a_\alpha \in \mathbb{R}$, and $\psi_\alpha(\boldsymbol{x}, \boldsymbol{y})$ conjunctive TL expressions. We now define

$$\mathsf{tw}(\varphi) := \max\{\mathsf{tw}(\psi_\alpha) \mid \alpha \in A\}$$

for expressions in TL. To deal with expressions in $\mathsf{TL}(\Omega)$ that may contain function application, we define $\mathsf{tw}(\varphi)$ as the maximum treewidth of the expressions: (i) $\varphi_{\mathsf{nofun}}(\boldsymbol{x}) \in \mathsf{TL}$ obtained by replacing each top-level function application $f(\varphi_1, \ldots, \varphi_p)$ by a new predicate R_f with free indices $\mathsf{free}(\varphi_1) \cup \cdots \cup \mathsf{free}(\varphi_p)$; and (ii) all expressions $\varphi_1, \ldots, \varphi_p$ occurring in a top-level function application $f(\varphi_1, \ldots, \varphi_p)$ in φ. We note that these expression either have no function applications (as in (i)) or have function applications of lower nesting depth (in φ, as in (ii)). In other words, applying this definition recursively, we end up with expressions with no function applications, for which treewidth was already defined. With this notion of treewidth at hand, Proposition 4.5 now readily follows.