On Batch Teaching with Sample Complexity Bounded by VCD

Farnam Mansouri
University of Toronto
frnm.mansouri@gmail.com

Hans U. Simon
Max Planck Institute for Informatics
hsimon@mpi-inf.mpg.de

Adish Singla
Max Planck Institute for Software Systems
adishs@mpi-sws.org

Sandra Zilles
University of Regina
zilles@cs.uregina.ca

Abstract

In machine teaching, a concept is represented by (and inferred from) a small number of labeled examples. Various teaching models in the literature cast the interaction between teacher and learner in a way to obtain a small complexity (in terms of the number of examples required for teaching a concept) while obeying certain constraints that are meant to prevent unfair collusion between teacher and learner. In recent years, one major research goal has been to show interesting relationships between teaching complexity and the VC-dimension (VCD). So far, the only interesting relationship known from batch teaching settings is an upper bound quadratic in the VCD, on a parameter called recursive teaching dimension. The only known upper bound on teaching complexity that is linear in VCD was obtained in a model of teaching with sequences rather than batches. This paper is the first to provide an upper bound of VCD on a batch teaching complexity parameter. This parameter, called $\mathrm{STD}_{\min}$, is introduced here as a model of teaching that intuitively incorporates a notion of "importance" of an example for a concept. In designing the $\mathrm{STD}_{\min}$ teaching model, we argue that the standard notion of collusion-freeness from the literature may be inadequate for certain applications; we hence propose three desirable properties of teaching complexity and demonstrate that they are satisfied by $\mathrm{STD}_{\min}$.

1 Introduction

The notion of machine teaching refers to the selection of helpful training examples that aid the learner in identifying a target concept [Zhu et al., 2018]. Such processes can make machine learning feasible or economical in situations when it is difficult or expensive to acquire large amounts of training data. Human-in-the-loop settings [Wang et al., 2020] or inverse reinforcement learning [Kamalaruban et al., 2019] are potential application areas of machine teaching. Formal studies of teaching consider various teaching models, each of which has a corresponding complexity parameter referring to the worst-case number of examples required to teach any concept in a given concept class [Goldman and Kearns, 1995, Shinohara and Miyano, 1991, Zilles et al., 2011, Gao et al., 2017b, Kirkpatrick et al., 2019, Mansouri et al., 2019]. Each model has to adhere to rules that prevent teacher and learner from using unwanted "coding tricks", such as, for instance, agreeing on an indexing of concepts and an indexing of data points, and then allowing the teacher to simply teach the concept indexed i using the data point with index i. While no general notion of coding trick is agreed upon in the literature, Goldman and Mathias [1996] provided a notion of collusion-freeness (which we call GM-collusion-freeness for short) that is often used as an underlying constraint in teaching models.

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

One major line of research addresses the question of how teaching complexity parameters relate to one another and to other parameters of interest in computational learning theory, such as, for instance, the VC-dimension (VCD, Vapnik and Chervonenkis, 1971), the self-directed learning complexity [Goldman and Sloan, 1994], the optimal mistake bound from online learning [Littlestone, 1988], or the size of sample compression schemes [Littlestone and Warmuth, 1986]. Of particular interest is the question how teaching complexity relates to the complexity of learning from randomly chosen examples, and thus to the VCD [Blumer et al., 1989]. Answers to this question provide insights into structural properties that make a concept class easy or hard to teach, and have implications on the design and analysis of teaching and learning algorithms. For example, it was established that the Recursive Teaching Dimension (RTD, Zilles et al., 2011) is upper-bounded by a function quadratic in VCD [Hu et al., 2017]. While RTD may exceed VCD, it remains open whether it is in $O(\text{VCD})$. Connections between RTD and the size of an optimal sample compression scheme were also made [Doliwa et al., 2014, Darnstädt et al., 2016]. More recently, Kirkpatrick et al. [2019] introduced the No-Clash Teaching Dimension (NCTD), which is the optimal complexity of teachers satisfying GM-collusion-freeness. Since the RTD model also satisfies GM-collusion-freeness, NCTD is upper-bounded by RTD and thus trivially inherits Hu et al.'s upper bound quadratic in VCD. It remains unresolved whether or not NCTD $\leq$ VCD holds in general; no counter-example has been found yet.

The models of RTD and NCTD represent teaching with batches (sets of examples). Naturally, a smaller complexity can be obtained when teachers can encode concepts in sequences of examples. So far, the only known teaching complexity upper-bounded by VCD stems from a sequential model [Mansouri et al., 2019]. The main problem we address in this paper is to design a reasonable batch model of teaching that has a complexity upper-bounded by VCD.

While GM-collusion-freeness is often considered a very natural condition on teaching, it has recently been argued that there are application settings in which this condition is *not* natural [Ferri et al., 2022]. In addition, since the question whether NCTD $\leq$ VCD is not yet resolved, and NCTD is the optimal complexity of GM-collusion-free teaching, our approach is to consider batch models that do not satisfy GM-collusion-freeness, but instead satisfy minimum postulates of teaching without "coding tricks". Our first contribution is to formally define three such postulates and to analyze some teaching models from the literature with respect to these postulates. We then define a new batch teaching model that is not GM-collusion-free but provably satisfies our three postulates of teaching without coding tricks. Our main results are that the corresponding complexity parameter is upper-bounded by both RTD and VCD. This makes our paper the first to provide an upper bound of VCD or $O(\text{VCD})$ on a complexity parameter for batch teaching.

All proofs or parts of proofs omitted from the paper are provided in the appendix.

2 Preliminaries

Throughout this paper, the symbol X is used to denote any finite domain over which concepts, i.e., subsets of X, are defined. A *concept class* over X is then a finite set of concepts over X. In the literature, any kind of finite or infinite set system can serve as a concept class; examples of finite concept classes are given in the form of tables throughout this paper. Often the concept classes studied are highly structured classes of Boolean functions, such as, for instance the class of all monomials over a fixed set of variables [Zilles et al., 2011]. Infinite classes of geometric concepts, such as hyperplanes in the Euclidean space, are often studied as concept classes as well; see, e.g., [Gao et al., 2017a,b].

If C is any concept over X and $x \in X$, then $C(x)$ is the label of C for x, i.e., $C(x) = 1$ if $x \in C$, while $C(x) = 0$ if $x \notin C$. A *labeled example* for C is a pair $(x, C(x))$ for $x \in X$. As this paper focuses on batch teaching rather than sequential teaching, teachers and learners are designed to operate with sets of labeled examples. Any set of labeled examples for C is called a *sample set* for C. If $\mathcal{C}$ is a concept class, $C \in \mathcal{C}$, and S is a sample set for C, we say that S is a *teaching set* for C (wrt $\mathcal{C}$) if it is not a sample set for any $C' \neq C$, $C' \in \mathcal{C}$. A *teacher* for $\mathcal{C}$ is a mapping T that assigns to every concept $C \in \mathcal{C}$ a sample set for C. Its *order* $\text{ord}(T)$ is the size of the largest set in its range, i.e., $\text{ord}(T) = \max_{C \in \mathcal{C}} |T(C)|$. A *learner* is a (not necessarily total) mapping that assigns a concept to each sample set in its domain. A learner L and a teacher T are said to *match* on a concept class $\mathcal{C}$, if $L(T(C)) = C$ for every concept $C \in \mathcal{C}$. If $\mathcal{C}$ is a concept class over X and $X' \subseteq X$ is any subset of the domain, then we use $\mathcal{C}{\downarrow}_{X'}$ to denote the *restriction* of $\mathcal{C}$ to X', i.e.,

$\mathcal{C}\downarrow_{X'} = \{C\downarrow_{X'} \mid C \in \mathcal{C}\}$, where $C\downarrow_{X'}$ is the projection of C onto X'. We say that X' *preserves* $\mathcal{C}$ if $C_1 \neq C_2$ implies $C_1\downarrow_{X'} \neq C_2\downarrow_{X'}$ whenever $C_1, C_2 \in \mathcal{C}$. A concept class over X is *succinct* if it is not preserved by any proper subset of X.

We now define various notions of batch teaching that have been studied in the literature, beginning with the classical notion of teaching dimension.

Definition 1 (Shinohara and Miyano [1991], Goldman and Kearns [1995]) *Let $\mathcal{C}$ be a concept class over a domain X and $C \in \mathcal{C}$ be a concept. The teaching dimension of C in $\mathcal{C}$, denoted by $\mathrm{TD}(C, \mathcal{C})$, is the size of the smallest teaching set for C wrt $\mathcal{C}$. The Teaching Dimension of $\mathcal{C}$ is defined as $\mathrm{TD}(\mathcal{C}) := \max\{\mathrm{TD}(C, \mathcal{C}) \mid C \in \mathcal{C}\}$. Moreover, $\mathrm{TD}_{\min}(\mathcal{C}) := \min\{\mathrm{TD}(C, \mathcal{C}) \mid C \in \mathcal{C}\}$. A TD-teacher for $\mathcal{C}$ is a teacher that maps any $C \in \mathcal{C}$ to a smallest teaching set for C.*

A TD-teacher matches every learner that outputs concepts consistent with the given sample set. The more recent literature proposes models in which "smarter" learners can be used. In recursive teaching, one exploits a canonical partial order over the concepts in the class: first, the concepts with smallest teaching dimension wrt $\mathcal{C}$ are encoded with their minimum teaching sets, then one removes these concepts from $\mathcal{C}$ and proceeds recursively with the remaining concepts, always encoding and removing the concepts that are "easiest to teach".

Definition 2 (Zilles et al. [2011]) *Let $\mathcal{C}$ be a concept class over a domain X. Let $\mathcal{C}_0 = \mathcal{C}$ and recursively define $\mathcal{C}_i^{\min} = \{C \in \mathcal{C}_i \mid \mathrm{TD}(C, \mathcal{C}_i) = \mathrm{TD}_{\min}(\mathcal{C}_i)\}$ as well as $\mathcal{C}_{i+1} = \mathcal{C}_i \setminus \mathcal{C}_i^{\min}$. An RTD-teacher for $\mathcal{C}$ is a teacher T with the following property: for $C \in \mathcal{C}_i^{\min}$, the set $T(C)$ is a teaching set for C wrt $\mathcal{C}_i$. Then the Recursive Teaching Dimension of $\mathcal{C}$ is defined as $\mathrm{RTD}(\mathcal{C}) := \max\{\mathrm{TD}_{\min}(\mathcal{C}_i) \mid i \geq 0\}$, which equals the smallest possible order of any RTD-teacher for $\mathcal{C}$. A recursive teaching plan for $\mathcal{C}$ is any sequence*

$$\big((C_{1,1}, T(C_{1,1})), \ldots, (C_{1,n_1}, T(C_{1,n_1})), \ldots, (C_{k,1}, T(C_{k,1})) \ldots, (C_{k,n_k}, T(C_{k,n_k}))\big)$$

where T is an RTD-teacher, $\mathcal{C}_i^{\min} = \{C_{i,1}, \ldots, C_{i,n_i}\}$ for all i, and $\mathcal{C} = \mathcal{C}_1^{\min} \cup \ldots \cup \mathcal{C}_k^{\min}$.

For finite concept classes, the notion of RTD coincides with the Preference-Based Teaching Dimension (PBTD) [Gao et al., 2017b], so our results will similarly apply to PBTD.

No-clash teaching is strictly more powerful than recursive teaching; here the only constraint on the teacher is that no two concepts agree on the union of the two sample sets encoding them.

Definition 3 (Kirkpatrick et al. [2019]) *Let $\mathcal{C}$ be a concept class over a domain X and T be a teacher for $\mathcal{C}$. We call T a non-clashing teacher (NCTD-teacher) on $\mathcal{C}$ iff there are no two distinct $C, C' \in \mathcal{C}$ such that $T(C)$ is a sample set for C' and $T(C')$ is a sample set for C. The No-Clash Teaching Dimension of $\mathcal{C}$ is defined as $\mathrm{NCTD}(\mathcal{C}) := \min\{\mathrm{ord}(T) \mid T \text{ is an } \mathrm{NCTD}\text{-teacher on } \mathcal{C}\}$.*

It is not hard to show that $\mathrm{TD} \geq \mathrm{RTD} \geq \mathrm{NCTD}$ [Kirkpatrick et al., 2019]. A batch teaching parameter that is incomparable to both RTD and NCTD is the so-called subset teaching dimension. In subset teaching, one considers all minimum-size teaching sets for each concept, and iteratively reduces them to minimum-size subsets that are not contained in any of the sets assigned to other concepts. The underlying idea is that a learner can recognize a concept even by a subset S of a smallest teaching set if S is not a subset of a set used for teaching another concept.

Definition 4 (Zilles et al. [2011]) *Let $\mathcal{C}$ be a concept class over a domain X, and $C \in \mathcal{C}$. Define $\mathrm{STS}^0(C, \mathcal{C}) := \{\{(x, C(x)) \mid x \in X\}\}$. For $k \in \mathbb{N}$, iteratively define a collection $\mathrm{STS}^{k+1}(C, \mathcal{C})$ of subset teaching sets as the collection that contains all smallest-size sets S that satisfy the following:*

    1. $S \subseteq S'$ for some $S' \in \mathrm{STS}^k(C, \mathcal{C})$;

    2. $S \nsubseteq S'$ for all $S' \in \mathrm{STS}^k(C', \mathcal{C})$ where $C' \in \mathcal{C}$, $C' \neq C$.

Let k^* be minimal with $\mathrm{STS}^k(\hat{C}, \mathcal{C}) = \mathrm{STS}^{k^*}(\hat{C}, \mathcal{C})$ for all $k > k^*$, $\hat{C} \in \mathcal{C}$. An STD-teacher for $\mathcal{C}$ is any teacher T for $\mathcal{C}$ with $T(\hat{C}) \in \mathrm{STS}^{k^*}(\hat{C}, \mathcal{C})$ for all $\hat{C} \in \mathcal{C}$. The Subset Teaching Dimension of $\mathcal{C}$, denoted by $\mathrm{STD}(\mathcal{C})$, is defined as $\mathrm{STD}(\mathcal{C}) := \mathrm{ord}(T)$ where T is any STD-teacher for $\mathcal{C}$.

STD is well-defined since every STD-teacher for a class $\mathcal{C}$ has the same order, with all sets in $\mathrm{STS}^{k^*}(C, \mathcal{C})$ being of the same size for any fixed C. Note that $\mathrm{STS}^1(C, \mathcal{C})$ consists of all minimum-size teaching sets for C wrt $\mathcal{C}$. In general, $\mathrm{TD} \geq \mathrm{STD}$, while STD and RTD are incomparable and either one of them can be larger than the other by an arbitrary factor [Zilles et al., 2011].

These teaching notions are illustrated with the help of Table 5, which shows a concept class $\mathcal{C}_3^{pair}$ with 16 concepts over a domain of size 11. We claim that $\mathrm{TD}(\mathcal{C}_3^{pair}) = 4$, $\mathrm{RTD}(\mathcal{C}_3^{pair}) = 3$, $\mathrm{NCTD}(\mathcal{C}_3^{pair}) = 2$, $\mathrm{STD}(\mathcal{C}_3^{pair}) = 1$, and $\mathrm{TD}_{\min}(\mathcal{C}_3^{pair}) = 1$. Note that the smallest teaching set for any even-numbered concept C_{2i} contains only one example, namely for the instance x_i; thus $\mathrm{TD}_{\min}(\mathcal{C}_3^{pair}) = 1$. By contrast, the smallest teaching set for any odd-numbered concept C_{2i-1} contains labeled examples for the instances x_i, x_9, x_{10}, and x_{11}. The last three instances are needed to distinguish C_{2i-1} from all other odd-numbered concepts, and x_i is needed to distinguish C_{2i-1} from C_{2i}. Hence $\mathrm{TD}(\mathcal{C}_3^{pair}) = 4$. To see that $\mathrm{RTD}(\mathcal{C}_3^{pair}) = 3$, observe that a recursive teaching plan will first list all even-numbered concepts (whose TD is 1), and then has only the odd-numbered ones left, which correspond to the powerset on $\{x_9, x_{10}, x_{11}\}$; clearly these will require a teacher to use sets of size 3. A non-clashing teacher of order 2 is indicated by the boldface labels in the table. One can argue (see the proof of Proposition 16) that no non-clashing teacher of smaller order exists, i.e., $\mathrm{NCTD}(\mathcal{C}_3^{pair}) = 2$. Finally, $\mathrm{STD}(\mathcal{C}_3^{pair}) = 1$ was shown by Zilles et al. [2011]; in the first iteration of subset teaching, even-numbered concepts are assigned their unique teaching sets of size 1, while odd-numbered concepts C_{2i-1} are assigned four-element teaching sets containing the example $(x_i, 0)$. Since the latter is not contained in a minimum teaching set of any other concept, in the next iteration, C_{2i-1} is assigned the subset teaching set $\{(x_i, 0)\}$.

concept in $\mathcal{C}_3^{pair}$	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}	x_{11}
C_1	**0**	0	0	0	0	0	0	0	**0**	**0**	0
C_2	**1**	0	0	0	0	0	0	0	0	0	0
C_3	0	**0**	0	0	0	0	0	0	**0**	0	1
C_4	0	**1**	0	0	0	0	0	0	0	0	1
C_5	0	0	**0**	0	0	0	0	0	**0**	1	**0**
C_6	0	0	**1**	0	0	0	0	0	0	1	0
C_7	0	0	0	**0**	0	0	0	0	**0**	1	1
C_8	0	0	0	**1**	0	0	0	0	0	1	1
C_9	0	0	0	0	**0**	0	0	0	1	**0**	0
C_{10}	0	0	0	0	**1**	0	0	0	1	0	0
C_{11}	0	0	0	0	0	**0**	0	0	1	0	1
C_{12}	0	0	0	0	0	**1**	0	0	1	0	1
C_{13}	0	0	0	0	0	0	**0**	0	1	1	**0**
C_{14}	0	0	0	0	0	0	**1**	0	1	1	0
C_{15}	0	0	0	0	0	0	0	**0**	1	1	1
C_{16}	0	0	0	0	0	0	0	**1**	1	1	1

Table 1: The concept class $\mathcal{C}_u^{pair}$ [Zilles et al., 2011], for the case $u = 3$. The subset teaching sets witnessing $\mathrm{STD}(\mathcal{C}_3^{pair}) = 1$ are highlighted in blue. Non-clashing sets that witness $\mathrm{NCTD}(\mathcal{C}_3^{pair}) \leq 2$ are in bold font. The proof of Proposition 16 shows that $\mathrm{NCTD}(\mathcal{C}_3^{pair}) = 2$.

3 Desirable Properties of Teaching Models

Our goal is to find a "reasonable" batch teaching complexity measure that is upper-bounded by VCD. Even an upper bound linear in VCD would be of significance; the best known upper bound on batch teaching complexity, in terms of VCD, is the quadratic upper bound on RTD (and thus on NCTD) that was established by Hu et al. [2017]. One important aspect in the design of "reasonable" teaching models is how much to constrain the information exchange between teacher and learner. In an attempt to prevent unfair collusion between a teacher and a learner, one limits their interaction by certain constraints. While there is no general definition of what constitutes collusion, Goldman and Mathias [1996] proposed a notion of collusion-freeness that is often adopted in the literature:

Definition 5 (Goldman and Mathias [1996]) *A teacher T and a learner L are Goldman-Mathias (GM) collusion-free on a concept class $\mathcal{C}$ if, for every $C \in \mathcal{C}$, and every sample set S for C, we have $L(T(C) \cup S) = C$.*

The intuition behind this notion is that the learner is not distracted when presented with additional information on the target concept, beyond the minimum information needed to identify the target concept. At the same time, this prevents certain "unfair coding tricks". For every concept class $\mathcal{C}$, all TD-teachers, RTD-teachers, and NCTD-teachers can be matched with a learner in a GM-collusion-free way [Zilles et al., 2011, Kirkpatrick et al., 2019]. In particular, $\text{NCTD}(\mathcal{C})$ corresponds to the *smallest* order of any teacher for $\mathcal{C}$ that can be matched with a learner without GM-collusion [Kirkpatrick et al., 2019]. By contrast, teachers and learners using subset teaching usually are not in general GM-collusion-free [Zilles et al., 2011].

As long as it is open whether NCTD is upper-bounded by (a function linear in) VCD, any quest for a measure of batch teaching complexity that is upper-bounded by (a function linear in) VCD is forced to take a new route: it must consider batch teaching notions that *violate* the definition of GM-collusion-freeness, since NCTD is the optimal complexity of GM-collusion-free teaching.

Ignoring GM-collusion-freeness has some practical motivation. The notion of GM-collusion-freeness is inherently limited in that it excludes learners that expect teachers to use only "important" information (for some notion of importance). If $T(C)$ contains only "important" examples for C, while the sample S for C contains "unimportant" examples, then a learner may be confused by the presence of S in its input $T(C) \cup S$. If we want to permit superfluous information to have adverse effects in teaching, then we should not require GM-collusion-freeness. As an illustration of the naturalness of such effects, consider a typical form of information exchange between a human teacher and learner in a classroom. Suppose a teacher asks a student to prove Theorem X under premises A, B, and C, and suppose further the student comes up with a proof of Theorem X that uses only premises A and B, but not the (consistent yet unnecessary) premise C. The student may then doubt their own proof, since they assume all the information provided by the teacher to be "important". This is in line with recent research on machine teaching. Ferri et al. [2022] argued that it is *not in general* unnatural for a learner to change its mind when receiving data that is consistent with the previous hypothesis. Their model allows additional information to decrease the probability that the current hypothesis is really correct, and to make an alternate consistent hypothesis appear more likely. This point of view challenges the widely-held belief that natural teaching and learning should be GM-collusion-free.

Consider for example the class in Table 5. Here, C_1 and C_2 differ only in x_1. The smallest teaching set for C_1 uses four instances (x_1, x_9, x_{10}, and x_{11}), but a learner expecting the teacher to use "important" examples might infer C_1 from the information $(x_1, 0)$: while there are 15 concepts consistent with this example, C_1 is the only one for which this information is "important", as it is the only concept in the class for which this example occurs in a smallest teaching set. An STD-teacher will use the singleton set $\{(x_1, 0)\}$ to teach C_1, and has an order of 1 on this concept class. By contrast, no GM-collusion-free teacher/learner pair can succeed with just a single example, since the NCTD, which is known to be optimal in terms of GM-collusion-free teaching, is greater than 1.

Rather than defining a weaker notion of collusion-freeness, we propose to consider desirable properties of teachers and learners, which could be used as postulates for reasonable models of teaching and learning. Depending on the application setting, one may require additional properties.

Two of our intuitive postulates concern monotonicity of a teaching complexity measure. First, for every concept class $\mathcal{C}$ one might want every superset of $\mathcal{C}$ to be at least as hard to teach as $\mathcal{C}$, i.e., the teaching complexity of a concept class should be no smaller than that of any of its subclasses. Second, one might require that removing instances from X without reducing the number of concepts should not decrease teaching complexity, because the removed instances may have been helpful but not harmful in teaching. Both these monotonicity postulates are captured in the following definition.

Definition 6 (Postulate 1 (Class-Monotonicity) and Postulate 2 (Domain-Monotonicity)) *Let Z be any function that assigns a non-negative integer to any concept class. We say that Z is class-monotonic, if $Z(\mathcal{C}') \geq Z(\mathcal{C})$ whenever $\mathcal{C}$, $\mathcal{C}'$ are concept classes over the same domain X, and $\mathcal{C} \subseteq \mathcal{C}'$. We say that Z is domain-monotonic, if $Z(\mathcal{C}{\downarrow}_{X'}) \geq Z(\mathcal{C})$ whenever $\mathcal{C}$ is a concept class over a domain X, and $X' \subseteq X$ is a subset that preserves $\mathcal{C}$.*

Our third postulate at first glance appears similar to GM-collusion-freeness. It states that a teaching set for a concept C should not be contained in a teaching set for another concept C'. Intuitively, a teaching set $T(C)$ for C must contain enough "important" examples for C such that any concept $C' \neq C$ that is consistent with $T(C)$ will be missing at least one of these "important" examples in its own teaching set. In other words, for every $C' \neq C$ at least one example in the teaching set for C is "unimportant" for C' or inconsistent with C'.

Definition 7 (Postulate 3 (Antichain Property)) *A teacher T has the antichain property (is an antichain teacher) for a concept class $\mathcal{C}$ if $C, C' \in \mathcal{C}$ and $C \neq C' \Rightarrow T(C) \nsubseteq T(C')$.*

We will sometimes say that a teaching complexity notion satisfies the antichain property if all teachers following the corresponding model are antichain teachers. For example, since every TD-teacher is an antichain teacher, we say that TD satisfies the antichain property. It is easy to see that also STD satisfies the antichain property. Moreover, every RTD-teacher (NCTD-teacher) can be normalized to an RTD-teacher (NCTD-teacher, resp.) of the same order that also satisfies the antichain property; see Appendix B for a proof.

Proposition 8 *Let $\mathcal{C}$ be any concept class, $Z \in \{\mathrm{RTD}, \mathrm{NCTD}\}$, and T any Z-teacher for $\mathcal{C}$. Then there is a Z-teacher T' for $\mathcal{C}$ with $\mathrm{ord}(T') = \mathrm{ord}(T)$ such that T' has the antichain property.*

An interesting natural (yet non-trivial) property of optimal antichain teachers is that their order for the powerset $\mathcal{P}_n$ on n instances is linear in n. (The proof, given in Appendix A, relies on the theory of bipartite matching.)

Theorem 9 *Let T^n be an antichain teacher for $\mathcal{P}_n$ and suppose $\mathrm{ord}(T^n) \leq \mathrm{ord}(T)$ for all antichain teachers T for $\mathcal{P}_n$. Then, for all but finitely many n, we have $0.22 \cdot n < \mathrm{ord}(T^n) < 0.23 \cdot n$.*

When teaching with sequences, the sample complexity for $\mathcal{P}_n$ may be as low as $\Theta(\frac{n}{\log n})$ [Mansouri et al., 2019]; "natural" batch teaching models thus need strictly larger sample sets.

To sum up, our goal is to design a measure of batch teaching complexity that is upper-bounded by (a function linear in) VCD and satisfies the postulates of (i) domain-monotonicity, (ii) class-monotonicity and (iii) the antichain property. Since we need to focus on complexity notions violating GM-collusion-freeness, a first natural candidate is STD. However, STD is not even upper-bounded by a polynomial in VCD [Zilles et al., 2011]. Moreover, while it satisfies Postulate 3, it violates both Postulates 1 and 2. The class in Table 5 witnesses that STD is not class-monotonic: it satisfies $\mathrm{STD} = 1$, while its subclass of odd-numbered concepts has $\mathrm{STD} = 3$. This generalizes as follows:

Proposition 10 (Zilles et al. [2011]) *STD is not class-monotonic. In particular, for every $n > 1$, there is a concept class $\mathcal{C}$ with a sub-class $\mathcal{C}'$ such that $\mathrm{STD}(\mathcal{C}) = 1$, while $\mathrm{STD}(\mathcal{C}') = n$.*

Proposition 11 *STD is not domain-monotonic. In particular, for every $n > 3$, there is a concept class $\mathcal{C}$ over a domain $X = X' \cup X''$ such that $\mathrm{STD}(\mathcal{C}) = n - 1$, while $\mathrm{STD}(\mathcal{C}{\downarrow}_{X'}) = 2$.*

4   A Variant of STD

Our main contribution is to introduce a new teaching complexity parameter called $\mathrm{STD}_{\min}$, which is built on the idea of STD, yet satisfies the two postulates defined in Section 3. Moreover, we will show that it is upper-bounded by VCD. This makes $\mathrm{STD}_{\min}$ the first known complexity parameter for batch teaching that is proven to be upper-bounded by (a function linear in) VCD.

In calculating $\mathrm{STD}(C, \mathcal{C})$, at stage $k + 1$ one maintains the collection of *all minimum-size* subsets of sets for C from stage k that are not subsets of sets for any other C' at stage k. In $\mathrm{STD}_{\min}$, at every stage we pick only one subset, but do not require it to be minimal.

Definition 12 *Let $\mathcal{C}$ be a concept class over a domain X. A sequence $\mathcal{T} = (T_k)_{k \in \mathbb{N}}$ of teachers for $\mathcal{C}$ is called a subset teaching sequence for $\mathcal{C}$ if, for all $C \in \mathcal{C}$ and all $k \in \mathbb{N}$:*

$$
\begin{aligned}
T_0(C) &= \{(x, C(x)) \mid x \in X\}, \\
T_{k+1}(C) &\subseteq T_k(C), \\
T_{k+1}(C) &\nsubseteq T_k(C') \text{ for all } C' \in \mathcal{C}, \ C' \neq C.
\end{aligned}
$$

Let $k^* \in \mathbb{N}$ be minimal with $T_k(C) = T_{k^*}(C)$ for all $k > k^*$ and all $C \in \mathcal{C}$. Then T_{k^*} is an $\mathrm{STD}_{\min}$*-teacher for $\mathcal{C}$ and we define the order of $\mathcal{T}$ on $\mathcal{C}$ as* $\mathrm{ord}(\mathcal{T}) = \mathrm{ord}(T_{k^*})$. *Finally, define*

$$\mathrm{STD}_{\min}(\mathcal{C}) = \min\{\mathrm{ord}(\mathcal{T}) \mid \mathcal{T} \text{ is a subset teaching sequence for } \mathcal{C}\}.$$

Observation 1 *Every subset teaching sequence of order d can be transformed into a* normalized *sequence $(T_k)_{k \in \mathbb{N}}$ of the same order, where a normalized subset teaching sequence has the property that, for every $k < k^*$ and every $C \in \mathcal{C}$, we have (i) T_{k+1} differs from T_k on exactly one concept, (ii) $|T_{k+1}(C)| \in \{|T_k(C)| - 1, |T_k(C)|\}$, (iii) $|T_k(C)| \geq d$, which implies that $|T_{k^*}(C)| = d$.*

Before showing that $\mathrm{STD}_{\min}$ satisfies our desired properties, we claim that $\mathrm{STD}_{\min}$ is upper-bounded by STD and can be arbitrarily smaller than STD (the proof is in Appendix C):

Proposition 13 $\mathrm{STD}_{\min}(\mathcal{C}) \leq \mathrm{STD}(\mathcal{C})$, *and for all $n \in \mathbb{N}$ there is some succinct $\mathcal{C}_n$ such that* $\mathrm{STD}_{\min}(\mathcal{C}_n) = 2$ *and* $\mathrm{STD}(\mathcal{C}) = n$.

Since $\mathrm{STD}_{\min} \leq \mathrm{STD}$ and STD can be smaller than NCTD, which is the best possible complexity of GM-collusion-free teaching and learning, we immediately obtain:

Corollary 14 *There are concept classes for which no teacher of order $\mathrm{STD}_{\min}$ can be matched with a learner in a GM-collusion-free way.*

Next, we claim that $\mathrm{STD}_{\min}$ also meets Postulates 1 and 2, and thus greatly improves on STD in terms of the postulates defined in Section 3; see Appendix C for a proof.

Proposition 15 $\mathrm{STD}_{\min}$ *is class-monotonic, domain-monotonic, and satisfies the antichain property.*

5 Relationship of $\mathrm{STD}_{\min}$ to Other Complexity Parameters

We already know that $\mathrm{STD}_{\min}$ is upper-bounded by TD and STD. Subsequently, we will show that, for finite concept classes, it is also upper-bounded by RTD and by VCD, but not by NCTD. Most importantly, our results make $\mathrm{STD}_{\min}$ the first known parameter for batch teaching complexity that is known to be upper-bounded by VCD (or even by a function linear in VCD), for finite classes. We first show that $\mathrm{STD}_{\min}$ can be arbitrarily smaller than NCTD, but also by a factor of 2 larger than NCTD. The proof, which is detailed in Appendix D, uses a generalization of $\mathcal{C}_3^{pair}$ from Table 5:

Proposition 16 *For every $n \in \mathbb{N}$ there is (i) a concept class $\mathcal{C}$ with $\mathrm{STD}(\mathcal{C}) = \mathrm{STD}_{\min}(\mathcal{C}) = 1$ and* $\mathrm{NCTD}(\mathcal{C}) = n$; *(ii) a concept class $\mathcal{C}$ with $\mathrm{STD}(\mathcal{C}) = \mathrm{STD}_{\min}(\mathcal{C}) = n$ and $\mathrm{NCTD}(\mathcal{C}) = \frac{n}{2}$.*

Theorem 17 *Let $\mathcal{C}$ be any concept class. Then $\mathrm{STD}_{\min}(\mathcal{C}) \leq \mathrm{RTD}(\mathcal{C})$.*

Proof. Let $((C_1, T(C_1)), (C_2, T(C_2)), \ldots, (C_n, T(C_n)))$ be a recursive teaching plan for $\mathcal{C}$. In particular, we have $\mathcal{C} = \{C_1, \ldots, C_n\}$, $|\mathcal{C}| = n$, and, for all $i \in \{1, \ldots, n\}$, the set $T(C_i)$ is a teaching set for C_i with respect to $\{C_j \mid j \geq i\}$. Moreover, $\max_i |T(C_i)| = \mathrm{RTD}(\mathcal{C})$. We will use this recursive teaching plan to construct a subset teaching sequence of order at most $\mathrm{RTD}(\mathcal{C})$ for $\mathcal{C}$.

First, for all $C \in \mathcal{C}$, define $T_0(C)$ as per Definition 12. Second, define T_1 by setting $T_1(C_1) = T(C_1)$ and $T_1(C_j) = T_0(C_j)$ for all $j > 1$. Since $T(C_1)$ is a teaching set for C_1 wrt $\{C_j \mid j \geq 1\}$, we have that $T_1(C_1) \not\subseteq T_0(C_j)$ for all $j \neq 1$, so that T_1 satisfies the requirements of Definition 12. Moreover, $|T_1(C_1)| \leq \mathrm{RTD}(\mathcal{C})$. Next, we define T_k for $k > 1$ by the following algorithm.

1. For $j \neq k$, let $T_k(C_j) = T_{k-1}(C_j)$.
2. To define $T_k(C_k)$, initialize $T_k(C_k) := T(C_k)$.
3. Let $J_k := \{j \neq k \mid T_k(C_k) \subseteq T_{k-1}(C_j)\}$.
4. If $J_k = \emptyset$, then stop and output $T_k(C_k)$.
5. Let $j^* := \min J_k$. Pick any $(x, l) \in T_{k-1}(C_{j^*})$ such that $C_k(x) \neq l$.
6. Let $T_k(C_k) := T_k(C_k) \cup \{(x, C_k(x))\}$.
7. Goto step 3.

Obviously, $T_k(C_k) \subseteq T_{k-1}(C_k)$. To complete the proof of Theorem 17, we show that $T_k(C_k) \not\subseteq T_{k-1}(C)$ for all $C \neq C_k$, $C \in \mathcal{C}$ and that $|T_k(C_k)| \leq \mathrm{RTD}(\mathcal{C})$.

Note that $|T(C_j)| \leq \mathrm{RTD}(\mathcal{C})$ for all j; thus $|T_1(C_1)| \leq \mathrm{RTD}(\mathcal{C})$. If J_k is initially empty, then also $|T_k(C_k)| \leq \mathrm{RTD}(\mathcal{C})$, and, by definition of J_k we have $T_k(C_k) \not\subseteq T_{k-1}(C)$ for all $C \neq C_k$. So suppose J_k is not initially empty. Since $T_k(C_k) \supseteq T(C_k)$ at any point in time during the construction, and $T(C_k)$ is a teaching set for C_k wrt $\{C_j \mid j \geq k\}$, we have $j < k$ for all $j \in J_k$ at any point in time. Now let $j^* := \min J_k$. By construction, $T_{k-1}(C_{j^*}) \supseteq T(C_{j^*})$; in particular, $T_{k-1}(C_{j^*})$ is a teaching set for C_{j^*} wrt $\{C_j \mid j \geq j^*\}$. Hence there exists some $(x, l) \in T_{k-1}(C_{j^*})$ such that $C_k(x) \neq l$. Thus, step 6 guarantees that $T_k(C_k) \not\subseteq T_{k-1}(C_{j^*})$, and at least j^* is removed from J_k at the next iteration of step 3. This way, eventually $T_k(C_k) \not\subseteq T_{k-1}(C)$ for all $C \neq C_k$.

All that remains to be shown is that $|T_k(C_k)| \leq \mathrm{RTD}(\mathcal{C})$. We do this by proving inductively for all k that $|T_k(C_j)| \leq \mathrm{RTD}(\mathcal{C})$ for all $j \leq k$. Note that the latter holds true for $k = 1$. Assuming we have proven $|T_{k-1}(C_j)| \leq \mathrm{RTD}(\mathcal{C})$ for all $j \leq k - 1$, we claim that step 6 will only add an element to $T_k(C_k)$ if $|T_k(C_k)| \leq \mathrm{RTD}(\mathcal{C}) - 1$. For step 6 to add an element to $T_k(C_k)$, there must be (at that point in time) a $j^* < k$ such that $T_k(C_k) \subseteq T_{k-1}(C_{j^*})$. Since $T_{k-1}(C_{j^*})$ is a teaching set for C_{j^*} wrt $\{C_j \mid j \geq j^*\}$, the set $T_{k-1}(C_{j^*})$ is inconsistent with C_k. In particular, $T_k(C_k)$ is a proper subset of $T_{k-1}(C_{j^*})$. By induction hypothesis, $|T_{k-1}(C_{j^*})| \leq \mathrm{RTD}(\mathcal{C})$. Hence, $|T_k(C_k)| \leq \mathrm{RTD}(\mathcal{C}) - 1$ before step 6 adds an element to $T_k(C_k)$.

In the sum, we have verified that $(T_k)_{k \in \mathbb{N}}$ is a subset teaching sequence for $\mathcal{C}$ and that its order is at most $\mathrm{RTD}(\mathcal{C})$. Thus $\mathrm{STD}_{\min}(\mathcal{C}) \leq \mathrm{RTD}(\mathcal{C})$. $\qquad\square$

The main result of this section establishes $\mathrm{STD}_{\min}$ as the first notion of batch teaching complexity for which VCD is provably an upper bound.

Our proof of this result relies on the recursive decomposition of a concept class, as exploited by [Floyd and Warmuth, 1995] and in the proof that VCD can upper-bound the sample complexity of sequential teaching [Mansouri et al., 2019]. If $\mathcal{C}$ is a concept class over X and $x \in X$ any element of the domain, then we use $\mathcal{C}_x$ to denote $\mathcal{C}{\downarrow}_{X \setminus \{x\}}$, and $\mathcal{C}^x$ to denote $\{C \in \mathcal{C}_x \mid C \cup \{x\} \in \mathcal{C} \text{ and } C \in \mathcal{C}\}$. Floyd and Warmuth call $\mathcal{C}_x$ the restriction and $\mathcal{C}^x$ the reduction of $\mathcal{C}$ wrt x. It is easy to see that $\mathrm{VCD}(\mathcal{C}_x) \leq \mathrm{VCD}(\mathcal{C})$ and $\mathrm{VCD}(\mathcal{C}^x) \leq \mathrm{VCD}(\mathcal{C}) - 1$ [Floyd and Warmuth, 1995].

Theorem 18 *Let $\mathcal{C}$ be any concept class. Then $\mathrm{STD}_{\min}(\mathcal{C}) \leq \mathrm{VCD}(\mathcal{C})$.*

Proof. Let $d = \mathrm{VCD}(\mathcal{C}) \geq 1$. Pick some $x^* \in X$. We may assume inductively that the assertion of the theorem is true for the classes $\mathcal{C}_{x^*}$ and $\mathcal{C}^{x^*}$. Let $\mathcal{T}^{\mathrm{rest}} = (T_k^{\mathrm{rest}})_{k \leq k_{\mathrm{rest}}}$ be any subset teaching sequence for $\mathcal{C}_{x^*}$ with $\mathrm{ord}(\mathcal{T}^{\mathrm{rest}}) = d$. Here k_{rest} denotes the maximum number of iterations $\mathcal{T}^{\mathrm{rest}}$ takes to converge on any concept in $\mathcal{C}_{x^*}$. Further, let $\mathcal{T}^{\mathrm{red}} = (T_k^{\mathrm{red}})_{k \leq k_{\mathrm{red}}}$ be any subset teaching sequence for $\mathcal{C}^{x^*}$ with $\mathrm{ord}(\mathcal{T}^{\mathrm{red}}) = d - 1$. Here k_{red} denotes the maximum number of iterations $\mathcal{T}^{\mathrm{red}}$ takes to converge. Since any subset teaching sequence can be normalized, it can be assumed in the sequel that the sequences $\mathcal{T}^{\mathrm{rest}}$ and $\mathcal{T}^{\mathrm{red}}$ have the normalization properties (i)—(iii) as in Observation 1. Now define a subset teaching sequence $\mathcal{T} = (T_k)_{k \in \mathbb{N}}$ for $\mathcal{C}$ as follows.

For all $C \in \mathcal{C}$ initialize $T_0(C) := \{(x, C(x)) \mid x \in X\}$. From now on, we use $\mathcal{C}^{x^*, X}$ to denote the set of concepts $C \in \mathcal{C}$ for which there is some $C' \in \mathcal{C}$ such that C and C' differ only in the value of x^*. (Note that $\mathcal{C}^{x^*, X}$ has twice as many concepts as $\mathcal{C}^{x^*}$ and its restriction wrt x^* yields $\mathcal{C}^{x^*}$.)

Stage 1. Let $k \in [1, k_{\mathrm{red}} + 1]$. For all $C \in \mathcal{C}^{x^*, X}$ set $T_k(C) := T_{k-1}^{\mathrm{red}}(C{\downarrow}_{X \setminus \{x^*\}}) \cup \{(x^*, C(x^*))\}$. For all $C \in \mathcal{C} \setminus \mathcal{C}^{x^*, X}$ set $T_k(C) := \{(x, C(x)) \mid x \in X \setminus \{x^*\}\}$.[1]

Stage 2. Let $k \in [k_{\mathrm{red}} + 2, k_{\mathrm{red}} + k_{\mathrm{rest}} + 1]$. For all $C \in \mathcal{C}^{x^*, X}$, let $T_k(C) := T_{k-1}(C)$. For all $C \in \mathcal{C} \setminus \mathcal{C}^{x^*, X}$, let $T_k(C) := T_{k - k_{\mathrm{red}} - 1}^{\mathrm{rest}}(C{\downarrow}_{X \setminus \{x^*\}})$.

We claim that $(T_k)_{k \leq k_{\mathrm{red}} + k_{\mathrm{rest}} + 1}$ is a subset teaching sequence for $\mathcal{C}$ and has order at most d.

First, we show that the partial sequence defined in Stage 1 is valid, i.e., for all $k \leq k_{\mathrm{red}} + 1$ and all $C, C' \in \mathcal{C}$ with $C \neq C'$ we have $T_k(C) \subseteq T_{k-1}(C)$ and $T_k(C) \not\subseteq T_{k-1}(C')$. The fact $T_k(C) \subseteq T_{k-1}(C)$ is inherited from the same fact for the sequence $\mathcal{T}^{\mathrm{red}}$. To show that $T_k(C) \not\subseteq T_{k-1}(C')$, consider multiple cases. If $C, C' \in \mathcal{C}^{x^*, X}$, this property is again inherited from $\mathcal{T}^{\mathrm{red}}$. If $C \in \mathcal{C}^{x^*, X}$

---

[1] Note that, for all $C \in \mathcal{C}^{x^*, X}$, we have that $T_1(C)$ still equals $T_0(C)$.

and $C' \notin \mathcal{C}^{x^*,X}$, then $(x^*, C(x^*)) \in T_k(C) \setminus T_{k-1}(C')$ when $k > 1$, while for $k = 1$ the property $T_k(C) \nsubseteq T_{k-1}(C')$ is valid because $T_1(C) = T_0(C)$. If $C \notin \mathcal{C}^{x^*,X}$, then C and C' must differ on some instance $x \neq x^*$; since $T_k(C)$ contains $(x, C(x))$, again we obtain $T_k(C) \nsubseteq T_{k-1}(C')$.

Second, we show that the partial sequence defined in Stage 2 is a valid extension of that defined in Stage 1, i.e., for $k_{\mathrm{red}} + 2 \leq k \leq k_{\mathrm{red}} + k_{\mathrm{rest}} + 1$ and all $C, C' \in \mathcal{C}$ with $C' \neq C$ we have $T_k(C) \subseteq T_{k-1}(C)$ and $T_k(C) \nsubseteq T_{k-1}(C')$. So, fix C and $C' \neq C$. For $C \in \mathcal{C}^{x^*,X}$, the sets defined in Stage 1 do not get updated in Stage 2. Hence we may safely assume that $C \notin \mathcal{C}^{x^*,X}$. $T_k(C) \subseteq T_{k-1}(C)$ is inherited from the same property for $\mathcal{T}^{\mathrm{rest}}$. If $C' \notin \mathcal{C}^{x^*,X}$, then the analogous remark applies to $T_k(C) \nsubseteq T_{k-1}(C')$. Suppose now that $C' \in \mathcal{C}^{x^*,X}$. Here we make use of the normalization properties (i)—(iii). In Stage 2, all sets $T_{k-1}(C')$ with $C' \in \mathcal{C}^{x^*,X}$ are of size d while all sets $T_k(C)$ with $C \notin \mathcal{C}^{x^*,X}$ are of size at least d. Since $T_{k-1}(C')$ contains $(x^*, C(x^*))$, it is not a subset of $T_k(C)$. Together with $|T_k(C)| \geq |T_{k-1}(C')|$, it now follows that $T_k(C) \nsubseteq T_{k-1}(C')$. Consequently, $\mathcal{T}$ is a subset teaching sequence for $\mathcal{C}$. The identity $\mathrm{ord}(\mathcal{T}) = d$ is obvious. $\qquad\square$

6   A Note on Unambiguity in Teaching

While $\mathrm{STD}_{\min}$ meets our objectives outlined earlier, it loses one potentially desirable property of STD that has not been addressed in the literature before. For every teaching model defined above, there are concept classes which can be taught with more than one teacher satisfying the requirements of the model. Suppose Teacher 1 teaches concept $C_1 \in \mathcal{C}$ using sample set S, while Teacher 2 teaches concept $C_2 \in \mathcal{C}$, $C_2 \neq C_1$, with S. If the learner knows that she is interacting with *some* teacher of a given model, but doesn't know which one, she then cannot disambiguate between C_1 and C_2 when given input S. In *unambiguous* teaching models, the learner can infer the target concept from the given sample set without being told with which of the multiple valid teachers she is interacting.

Definition 19 *Let $Z \in \{\mathrm{TD}, \mathrm{RTD}, \mathrm{NCTD}, \mathrm{STD}, \mathrm{STD}_{\min}\}$ be a teaching complexity parameter. We say that Z is unambiguous on a concept class $\mathcal{C}$, if, for every sample set S, there is at most one concept $C \in \mathcal{C}$ such that some Z-teacher T of order $Z(\mathcal{C})$ satisfies $T(C) = S$.*

If Z is ambiguous on a concept class, then one would have to normalize Z-teachers or use disambiguating information. One disadvantage of $\mathrm{STD}_{\min}$ compared to STD is the loss of unambiguity.

Theorem 20 TD*,* RTD*, and* STD *are unambiguous on every concept class, while there are concept classes on which* NCTD *and* $\mathrm{STD}_{\min}$ *are not unambiguous.*

Proof. Let $\mathcal{C}$ be any concept class and S a sample set. If a TD-teacher T maps C to S, then S is a teaching set for C and thus cannot be mapped to any other concept by any TD-teacher T'. If an RTD-teacher T maps C to S and $C \in \mathcal{C}_i^{\min}$, then S is inconsistent with the concepts in $C \in \mathcal{C}_i \setminus \{C\}$ and thus cannot be mapped to the latter. The concepts in $\mathcal{C} \setminus \mathcal{C}_i$ cannot be mapped to S by any RTD-teacher either, since they must be mapped to sample sets that are inconsistent with all concepts in $C \in \mathcal{C}_i$, which includes C. If an STD-teacher T maps C to S, then $S \in \mathrm{STS}^{k^*}(C, \mathcal{C})$. Since the latter is disjoint from $S \in \mathrm{STS}^{k^*}(C', \mathcal{C})$ for all $C' \neq C$, no STD-teacher can map such C' to S.

It is easy to see that there are two NCTD-teachers of order 1 for $\mathcal{P}_2$ that even have the same range, one maps $\emptyset$ to $\{(x_1, 0)\}$ and $\{x_1\}$ to $\{(x_2, 0)\}$, the other one does the opposite. A concept class on which $\mathrm{STD}_{\min}$ is ambiguous is Warmuth's class [Doliwa et al., 2014], which is known as the smallest class on which RTD exceeds VCD. For details, see Appendix E.1. $\qquad\square$

The ambiguity observed for $Z \in \{\mathrm{NCTD}, \mathrm{STD}_{\min}\}$ is stronger than the negation of the condition in Definition 19. Ambiguity means that multiple optimal Z-teachers map two different concepts to the same teaching set. But it even happens that two optimal Z-teachers $T_1 \neq T_2$ have exactly the same range $R = \{T_1(C) \mid C \in \mathcal{C}\} = \{T_2(C) \mid C \in \mathcal{C}\}$, while assigning the sample sets in R differently to the concepts in C. The ambiguity of $\mathrm{STD}_{\min}$ can take extreme forms for artificially created concept classes that have many redundant instances, as discussed in Appendix E.2.

7 Conclusions

In an abstract setting, devoid of any specific application, it is not straightforward to define what makes a teaching/learning model "natural". We addressed this problem by considering various properties of teaching that one might find desirable; one can then design models that possess (some of) these properties as seen fit in an underlying application setting. We have introduced some such properties, here called "postulates", which are fulfilled by $\mathrm{STD}_{\min}$. Another property of $\mathrm{STD}_{\min}$, that is not fulfilled by TD, RTD or NCTD, is that it allows the learner to discard a hypothesis because the given data is not *important* for that hypothesis (even if it is consistent). We argue that a learner who knows that data comes from a helpful teacher, has reasons to reject hypotheses for which the data is not important/helpful. Of course, there may be other natural properties that are not fulfilled by $\mathrm{STD}_{\min}$. An interesting research question is what natural properties can (or cannot) be fulfilled by teaching models whose parameter is upper-bounded by VCD.

This paper is the first to provide an upper bound of VCD on batch teaching complexity. Our results and proofs may have implications on the design and analysis of teaching and learning algorithms. For an overview of most of our results, see Table 2. While we diverted from the notion of GM-collusion-freeness, we hope that the postulates on teaching that we defined, as well as our notion of unambiguity, will be useful for future studies on machine teaching. In particular, noting that neither NCTD nor $\mathrm{STD}_{\min}$ satisfy the notion of unambiguity, one may ask the question whether ambiguity is inherent in "natural" teaching models that yield a complexity upper-bounded by VCD. All unambiguous models studied in this paper have a complexity that sometimes exceeds VCD.

Property	TD	RTD	NCTD	STD	**$\mathrm{STD}_{\min}$**
GM-collusion-freeness [Goldman and Mathias, 1996]	yes	yes	yes	no	**no**
P1 – class-monotonicity	yes	yes	yes	no	**yes**
P2 – domain-monotonicity	**yes**	**yes**	**yes**	**no**	**yes**
P3 – antichain property	**yes**	**yes***	**yes***	**yes**	**yes**
unambiguity	**yes**	**yes**	**no**	**yes**	**no**
$\leq$ RTD	no	yes	yes	no	**yes**
$\leq$ VCD	no	no	?	no	**yes**
$\leq$ polynomial in VCD	no	yes	yes	no	**yes**

Table 2: Comparison of teaching complexity notions. Contributions from this paper are highlighted in bold. Note that class-monotonicity was already discussed by Zilles et al. [2011]. The asterisks indicate that RTD- and NCTD-teachers can be normalized to antichain teachers, see Prop. 8.

Acknowledgments and Disclosure of Funding

This research was conducted while S. Zilles was a visiting scientist at the Max Planck Institute for Software Systems. Further, S. Zilles acknowledges financial support by the Natural Sciences and Engineering Research Council (NSERC) of Canada, both through the Canada Research Chairs program and the Discovery Grants program. She was also supported through the Canada CIFAR AI Chairs program as an Affiliate Chair with the Alberta Machine Intelligence Institute (Amii).

References

A. Blumer, A. Ehrenfeucht, D. Haussler, and M. K. Warmuth. Learnability and the Vapnik-Chervonenkis dimension. *JACM*, 36(4):929–965, 1989.

M. Darnstädt, T. Kiss, H. U. Simon, and S. Zilles. Order compression schemes. *Theor. Comput. Sci.*, 620:73–90, 2016.

T. Doliwa, G. Fan, H. U. Simon, and S. Zilles. Recursive teaching dimension, VC-dimension and sample compression. *J. Mach. Learn. Res.*, 15:3107–3131, 2014.

C. Ferri, J. Hernández-Orallo, and J. Telle. Non-cheating teaching revisited: A new probabilistic machine teaching model. In *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, 2022.

S. Floyd and M. Warmuth. Sample compression, learnability, and the Vapnik-Chervonenkis dimension. *Machine Learning*, 21(3):1–36, 1995.

Z. Gao, D. G. Kirkpatrick, C. Ries, H. U. Simon, and S. Zilles. Preference-based teaching of unions of geometric objects. In *Proceedings of the International Conference on Algorithmic Learning Theory, ALT 2017*, pages 185–207, 2017a.

Z. Gao, C. Ries, H. U. Simon, and S. Zilles. Preference-based teaching. *J. Mach. Learn. Res.*, 18(31):1–32, 2017b.

S. A. Goldman and M. J. Kearns. On the complexity of teaching. *J. Comput. Syst. Sci.*, 50(1):20–31, 1995.

S. A. Goldman and H. D. Mathias. Teaching a smarter learner. *J. Comput. Syst. Sci.*, 52(2):255–267, 1996.

S. A. Goldman and R. H. Sloan. The power of self-directed learning. *Machine Learning*, 14(1):271–294, 1994.

L. Hu, R. Wu, T. Li, and L. Wang. Quadratic upper bound for recursive teaching dimension of finite VC classes. In *Proceedings of the 30th Conference on Learning Theory, COLT 2017, Amsterdam, The Netherlands, 7-10 July 2017*, pages 1147–1156, 2017.

P. Kamalaruban, R. Devidze, V. Cevher, and A. Singla. Interactive teaching algorithms for inverse reinforcement learning. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 2692–2700, 2019.

D. Kirkpatrick, H. U. Simon, and S. Zilles. Optimal collusion-free teaching. In *Proceedings of Machine Learning Research (ALT2019)*, volume 98, 2019.

N. Littlestone. Learning quickly when irrelevant attributes abound: a new linear threshold algorithm. *Machine Learning*, 2(4):245–318, 1988.

N. Littlestone and M. K. Warmuth. Relating data compression and learnability. Technical Report, UC Santa Cruz, 1986.

F. Mansouri, Y. Chen, A. Vartanian, J. Zhu, and A. Singla. Preference-based batch and sequential teaching: Towards a unified view of models. In *Advances in Neural Information Processing Systems 32*, pages 9199–9209, 2019.

A. Shinohara and S. Miyano. Teachability in computational learning. *New Gen. Comput.*, 8:337–348, 1991.

V. N. Vapnik and A. Y. Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. *Theor. Probability and Appl.*, 16(2):264–280, 1971.

P. Wang, J. Wang, P. Paranamana, and P. Shafto. A mathematical theory of cooperative communication. In *Advances in Neural Information Processing Systems*, volume 33, pages 17582–17593, 2020.

X. Zhu, A. Singla, S. Zilles, and A. N. Rafferty. An overview of machine teaching. *CoRR*, abs/1801.05927, 2018.

S. Zilles, S. Lange, R. Holte, and M. Zinkevich. Models of cooperative teaching and learning. *J. Mach. Learn. Res.*, 12:349–384, 2011.

A   Proof of Theorem 9

Theorem 9 *Let T^n be an antichain teacher for $\mathcal{P}_n$ and suppose $\mathrm{ord}(T^n) \leq \mathrm{ord}(T)$ for all antichain teachers T for $\mathcal{P}_n$. Then, for all but finitely many n, we have $0.22 \cdot n < \mathrm{ord}(T^n) < 0.23 \cdot n$.*

To establish this result, we first introduce some notation and some background on bipartite matching.

Definition 21 *Let $\mathcal{C}$ be any concept class. The antichain number of $\mathcal{C}$, denoted by $\mathrm{ACN}(\mathcal{C})$, is the smallest possible order of a teacher for $\mathcal{C}$ with the antichain property.*

Theorem 9 can then be restated as follows:

For all but finitely many n, we have $0.22 \cdot n < \mathrm{ACN}(\mathcal{P}_n) < 0.23 \cdot n$.

It is well known that a bipartite graph all of whose vertices have the same degree contains a perfect matching. The simple proof is based on a double counting argument. The same kind of argument can be used to show the following (most likely also well known) result:

Lemma 22 *Let $G = (V_1, V_2, E)$ be a bipartite graph with vertex sets V_1 and V_2. Suppose that every vertex in V_1 has degree d_1 while every vertex in V_2 has degree $d_2 \leq d_1$. Then G contains a matching of size $|V_1|$.*

Proof. For $U \subseteq V_1$, $\Gamma(U)$ denotes the neighborhood of U, i.e., $\Gamma(U) = \{v \in V_1 \mid v \text{ is adjacent to some vertex in } U\}$. It suffices to show that Hall's condition,

$$\forall U \subseteq V_1 : |\Gamma(U)| \geq |U| \ ,$$

is satisfied. Fix a set $U \subseteq V_1$. The number of edges having one endpoint in U equals $d_1 \cdot |U|$. The number of edges having one endpoint in $\Gamma(U)$ is at most $d_2 \cdot |\Gamma(U)|$. An edge with an endpoint in U

must have its other endpoint in $\Gamma(U)$. Hence $d_1 \cdot |U| \leq d_2 \cdot |\Gamma(U)|$. Since $d_2 \leq d_1$, we may conclude that $|U| \leq |\Gamma(U)|$. $\square$

Corollary 23 *Let d, n be integers such that $1 \leq d \leq (n+1)/2$. Let X be a set of size n. Let $G = (V_1, V_2, E)$ be the bipartite graph such that*

- *V_1 (resp. V_2) consists of all subsets of X with $d - 1$ (resp. d) elements,*

- *a set $U \in V_1$ is adjacent to a set $U' \in V_2$ iff $U \subseteq U'$.*

Then G contains a a matching of size $|V_1|$.

Proof. Each vertex in V_1 has degree $n - d + 1$ whereas each vertex in V_2 has degree d. Since $d \leq (n+1)/2$, by assumption, it follows that $d \leq n - d + 1$. Now apply Lemma 22. $\square$

Let X be a set of size n. A sample set over X is said to be *conflict-free* if it does not contain both $(x, 0)$ and $(x, 1)$ for some $x \in X$. Let $\mathcal{F}_{\leq d, n}$ be the family of all conflict-free sample sets over X with d or fewer elements. The conflict-free sample sets with exactly d elements form an antichain – denoted by $\mathcal{F}_{=d, n}$ in the sequel – in $\mathcal{F}_{\leq d}$. Obviously

$$\mathcal{F}_{=d, n} = \{(x_1, b_1), \ldots, (x_d, b_d) : x_1, \ldots, x_d \text{ are } d \text{ distinct elements of } X \text{ and } b_1, \ldots, b_d \in \{0, 1\}\}$$

and therefore the antichain $\mathcal{F}_{=d, n}$ is of size $\binom{n}{d} \cdot 2^d$.

The following result is a relative of Sperner's Theorem:

Lemma 24 *$\mathcal{F}_{=d, n}$ is a maximum antichain in $\mathcal{F}_{\leq d, n}$.*

Proof. An antichain $\mathcal{A}'$ with conflict-free sets $A'_1, \ldots, A'_{s'}$ (without repetition) is called an *extension* of another antichain $\mathcal{A}$ with conflict-free sets $A_1, \ldots, A_s$ (again without repetition) if $s' = s$ and $A_i \subseteq A'_i$ for $i = 1, \ldots, s$ (after renumbering the sets in $\mathcal{A}'$ if necessary). We show, by induction on d, that every antichain $\mathcal{A}$ with sets taken from $\mathcal{F}_{\leq d, n}$ has an extension $\mathcal{A}'$ with sets taken from $\mathcal{F}_{=d, n}$. For $d = 1$, this is obviously true. Let $d \geq 2$ and assume inductively that it holds for $d - 1$. Fix an antichain $\mathcal{A}$ with sets taken from $\mathcal{F}_{\leq d}, n$. Let $\mathcal{A}_1$ be the antichain consisting of the sets of size at most $d - 1$ in $\mathcal{A}$ and let $\mathcal{A}_2 = \mathcal{A} \setminus \overline{\mathcal{A}'}$. By our inductive assumption, there is an extension $\mathcal{A}'_1$ of $\mathcal{A}_1$ whose sets are taken from $\mathcal{F}_{\leq d-1, n}$. The inductive proof can now be accomplished by proving the following assertions:

Claim 1: $\mathcal{A}'_1 \cup \mathcal{A}_2$ is an antichain in $\mathcal{F}_{\leq d, n}$ whose sets are of size $d - 1$ or d.

Claim 2: Any antichain $\mathcal{B}$ with sets of size $d - 1$ or d has an extension $\mathcal{B}'$ with sets taken from $\mathcal{F}_{\leq d, n}$.

Claim 1 becomes obvious from the following observations:

- No set in $\mathcal{A}_2$ (with d elements) can be a subset of some set in $\mathcal{A}'_1$ (with $d - 1$ elements).

- Since no set in $\mathcal{A}_1$ is a subset of some set in $\mathcal{A}_2$ (by the antichain property of $\mathcal{A}$), no set in the extension $\mathcal{A}'_1$ is a subset of some set in $\mathcal{A}_2$.

As for proving Claim 2, fix some antichain $\mathcal{B}$. Let $\mathcal{B} = \mathcal{B}_1 \cup \mathcal{B}_2$ be the decomposition of $\mathcal{B}$ into sets of size $d - 1$ and sets of size d, respectively. A set of $\mathcal{B}_1$ is of the form $B = \{(x_1, b_1), \ldots, (x_{d-1}, b_{d-1})\}$. Let M be the matching of size $|V_1|$, whose existence is guaranteed by Corollary 23. Pick x_d such that $\{x_1, \ldots, x_{d-1}, x_d\}$ is the M-partner of $\{x_1, \ldots, x_{d-1}\}$. Then the set

$$B' = \{(x_1, b_1), \ldots, (x_{d-1}, b_{d-1}), (x_d, 0)\}$$

is called the M-partner of B. Note here that different sets from $\mathcal{B}_1$ have different M-partners. Let $\mathcal{B}'_1$ be the antichain obtained from $\mathcal{B}_1$ by replacing each set B in $\mathcal{B}_1$ by its M-partner and let $\mathcal{B}' = \mathcal{B}'_1 \cup \mathcal{B}_2$. By construction, all sets in $\mathcal{B}'$ are of size d. In order to show that $\mathcal{B}'$ is an antichain that extends $\mathcal{B}$, it suffices to show that no M-partner of a set $B \in \mathcal{B}_1$ can be equal to one of the sets in $\mathcal{B}_2$. But this is obvious because B is a subset of its M-partner, but not a subset of any set in $\mathcal{B}_2$ (by the antichain property of $\mathcal{B}$). Claim 2 follows from this discussion, which also completes the proof of the lemma. $\square$

Corollary 25 *Let $d_0 = d_0(n)$ be the smallest d such that $2^d \cdot \binom{n}{d} \geq 2^n$. Let $G = (V_1, V_2, E)$ be the bipartite graph given by (i) $V_1 = \mathcal{F}_{=n,n}$ and $V_2 = \mathcal{F}_{=d_0,n}$, and (ii) a set $U' \in V_1$ is adjacent to a set $U \in V_2$ iff $U \subseteq U'$. Then G contains a matching of size $|V_1|$.*

Proof. Each vertex in V_1 has degree $\binom{n}{d_0}$ whereas each vertex in V_2 has degree 2^{n-d_0}. The definition of d_0 implies that $2^{n-d_0} \leq \binom{n}{d_0}$. Now apply Lemma 22. $\qquad\square$

Note that $\mathrm{ACN}(\mathcal{C})$ is upper-bounded by the smallest number d such that the following graph $G = (V_1, V_2, E)$ contains a matching M that matches every vertex in V_1: (i) $V_1 = \mathcal{C}$ and $V_2 = \mathcal{F}_{=d,n}$, (ii) a concept $C \in \mathcal{C}$ is adjacent to a sample $S \in \mathcal{F}_{=d}$ iff it is consistent with S.

We now obtain a non-trivial reformulation of ACN:

Theorem 26 *Let $|X| = n$ and let $d_0 = d_0(n)$ be the smallest d such that $2^d \cdot \binom{n}{d} \geq 2^n$. Then $\mathrm{ACN}(\mathcal{P}_n) = d_0(n)$.*

Proof. Note that $\mathcal{P}_n$ can be identified with $\mathcal{F}_{=n,n}$: each map $C : X \to \{0,1\}$ is identified with the full sample $\{(x, C(x)) \mid x \in X\}$. An application of Corollary 25 yields $\mathrm{ACN}(\mathcal{P}_n) \leq d_0(n)$.

Set $d = \mathrm{ACN}(\mathcal{P}_n)$. Then the maximum antichain in $\mathcal{F}_{\leq d,n}$ is of size at least $|\mathcal{P}_n| = 2^n$. Using Lemma 24 and the fact that $|\mathcal{F}_{=d,n}| = \binom{n}{d} \cdot 2^d$, this translates into $2^d \cdot \binom{n}{d} \geq 2^n$. The definition of $d_0(n)$ now implies that $d \geq d_0(n)$. $\qquad\square$

We now show that $d_0(n)$ is a function linear in n.

Lemma 27 *Let $d_0 = d_0(n)$ be the smallest d such that $2^d \cdot \binom{n}{d} \geq 2^n$. Then $0.22 \cdot n < d_0(n) < 0.23 \cdot n$ for all but finitely many n.*

Proof. For $d = n/2$, we have $\binom{n}{n/2} \asymp \sqrt{\frac{2}{\pi n}} 2^n$, which is asymptotically larger than $2^{n/2}$. We may therefore assume that $d \leq n/2$. For such d, the term $\binom{n}{d}$ decreases when d decreases, while 2^{n-d} increases. Hence it suffices to show that $2^d \cdot \binom{n}{d} \geq 2^n$ is fulfilled for large enough n when $d = 0.23 \cdot n$, while it is not fulfilled for large enough n when $d = 0.22 \cdot n$.

To this end, let $d = pn$ with $0 < p \leq 1/2$, and rewrite $2^d \cdot \binom{n}{d} \geq 2^n$ as

$$\frac{1}{n} \log \binom{n}{pn} \geq 1 - p \,.$$

It is well known that the left-hand side converges to $H(p)$, where $H(\cdot)$ denotes the binary entropy. The lemma now follows from $H(0.22) < 0.78 = 1 - 0.22$ and $H(0.23) > 0.77 = 1 - 0.23$. $\quad\square$

This allows us to conclude that, asymptotically, the value of $\mathrm{ACN}(\mathcal{P}_n)$ lies between $0.22 \cdot n$ and $0.23 \cdot n$, as claimed by Theorem 9.

B Other Proof Details for Section 3

Proposition 8 *Let $\mathcal{C}$ be any concept class, $Z \in \{\mathrm{RTD}, \mathrm{NCTD}\}$, and T any Z-teacher for $\mathcal{C}$. Then there is a Z-teacher T' for $\mathcal{C}$ with $\mathrm{ord}(T') = \mathrm{ord}(T)$ such that T' has the antichain property.*

Proof. First, let T be any NCTD-teacher for $\mathcal{C}$. For $C \in \mathcal{C}$, obtain $T'(C)$ from $T(C)$ as follows. If each sample set in $T(C)$ has size $\mathrm{ord}(T)$, then $T'(C) = T(C)$. Otherwise, $T'(C)$ results from $T(C)$ by adding examples that are consistent with C to every sample set $T_C \in T(C)$, until the size of T_C equals $\mathrm{ord}(T)$. Then T' inherits the non-clashing property on $\mathcal{C}$ from T. Clearly, a non-clashing teacher mapping that produces only sample sets of a constant size must also fulfill the antichain property. So T' is an NCTD-teacher for $\mathcal{C}$ with the antichain property, and $\mathrm{ord}(T') = \mathrm{ord}(T)$.

Second, suppose T is an RTD-teacher. The construction of T' is identical to that in the first case. It remains to verify that the resulting antichain teacher T' with $\mathrm{ord}(T') = \mathrm{ord}(T)$ is also an RTD-teacher for $\mathcal{C}$. Using the notation from Definition 2, we know that, for $C \in \mathcal{C}_i^{\min}$, the set $T(C)$ is a teaching set for C wrt $\mathcal{C}_i$. Since adding examples (consistently with C) to $T(C)$ does not change this fact, we obtain that, for $C \in \mathcal{C}_i^{\min}$, the set $T'(C)$ is a teaching set for C wrt $\mathcal{C}_i$. Hence T' is an RTD-teacher for $\mathcal{C}$. $\qquad\square$

Proposition 11 STD *is not domain-monotonic. In particular, for every $n > 3$, there is a concept class $\mathcal{C}$ over a domain $X = X' \cup X''$ such that $\mathrm{STD}(\mathcal{C}) = n - 1$, while $\mathrm{STD}(\mathcal{C}{\downarrow}_{X'}) = 2$.*

Proof. Let $n > 3$, and let $X' = \{x_1', \ldots, x_n'\}$ and $X'' = \{x_1'', \ldots, x_n''\}$. For every $J \subseteq [n]$ of size 1 or 2, let C_J be the concept that assigns label 1 (resp. label 0) to x_j' and x_j'' if $j \in J$ (resp. if $j \notin J$). Let $C_\emptyset$ be the concept that assigns label 0 to $x_1', \ldots, x_n'$ and label 1 to $x_1'', \ldots, x_n''$. Consider now the following concept class $\mathcal{C}$ over the domain $X = X' \cup X''$: $\mathcal{C} = \{C_J \mid J \subseteq [n], 0 \le |J| \le 2\}$. See Table 3 for an illustration of the case $n = 5$.

Note that $\mathcal{C}{\downarrow}_{X'}$ is the class of all subsets of X whose size is at most 2. It is well known [Zilles et al., 2011] that $\mathrm{STD}(\mathcal{C}{\downarrow}_{X'}) = 2$.

It remains to prove that $\mathrm{STD}(\mathcal{C}) = n - 1$. To this end, we first determine the minimum teaching sets for every concept in $\mathcal{C}$:

(i) The minimum teaching sets for $C_\emptyset$ are the sets of the form $\{(x_j', 0), (x_j'', 1)\}$ for $j = 1, \ldots, n$.

(ii) For $1 \le i < j \le n$, the minimum teaching sets for $C_{\{i,j\}}$ are the sets of the form $\{(u_i, 1), (u_j, 1)\}$ where $u_i \in \{x_i', x_i''\}$, $u_j \in \{x_j', x_j''\}$ and $\{u_i, u_j\} \cap \{x_i', x_j'\} \ne \emptyset$.

(iii) For $1 \le i \le n$, the minimum teaching sets for $C_{\{i\}}$ are the sets of the form $\{(u_j, 0) \mid j \in [n] \setminus \{i\}\}$ where $u_j \in \{x_j', x_j''\}$ and, for at least one index $j' \in [n] \setminus \{i\}$, we have $u_{j'} = x_{j'}''$.

For each $C \in \mathcal{C}$, let $\mathrm{TS}(C)$ be the collection of minimum teaching sets for C. The largest of these minimum teaching sets, namely the ones for concepts of the form $C_{\{i\}}$, are of size $n - 1$. Hence $\mathrm{TD}(\mathcal{C}) = n - 1$. Next, we will verify the following property for every concept $C \in \mathcal{C}$:

> (*) If S is a minimum teaching set for C wrt $\mathcal{C}$, then every proper subset of S is contained in a minimum teaching set for some concept C' wrt $\mathcal{C}$, where $C' \in \mathcal{C}$, $C' \ne C$.

(i) Consider an index $j \in [n]$ and a teaching set $\{(x_j', 0), (x_j'', 1)\} \in \mathrm{TS}(C_\emptyset)$. Removing $(x_j', 0)$ from this set yields a subset of one of the teaching sets for $C_J \ne C_\emptyset$ whenever $j \in J$ and $|J| = 2$. A similar reasoning applies when removing $(x_j'', 1)$ instead of $(x_j', 0)$.

(ii) Consider indices $i \ne j \in [n]$ and a teaching set $\{(u_i, 1), (u_j, 1)\} \in \mathrm{TS}(C_{\{i,j\}})$. Removing one example, say $(u_i, 1)$, from this set yields a subset of one of the teaching sets for $C_J \ne C_{\{i,j\}}$ whenever $j \in J$, $i \notin J$ and $|J| = 2$.

(iii) Consider an index $i \in [n]$ and a teaching set $\{(u_j, 0) \mid j \in [n] \setminus \{i\}\} \in \mathrm{TS}(C_{\{i\}})$. Removing $(u_{j_0}, 0)$ from this set yields a subset of one of the teaching sets for $C_{\{j_0\}}$.

This establishes Property (*), which immediately implies $\mathrm{STD}(\mathcal{C}) = \mathrm{TD}(\mathcal{C}) = n - 1$. $\qquad\square$

C Proof Details for Section 4

Observation 1 *Every subset teaching sequence of order d can be transformed into a* normalized *sequence $(T_k)_{k \in \mathbb{N}}$ of the same order, where a normalized subset teaching sequence has the property that, for every $k < k^*$ and every $C \in \mathcal{C}$, we have (i) T_{k+1} differs from T_k on exactly one concept, (ii) $|T_{k+1}(C)| \in \{|T_k(C)| - 1, |T_k(C)|\}$, (iii) $|T_k(C)| \ge d$, which implies that $|T_{k^*}(C)| = d$.*

Proof. Properties (i) and (ii) are easy to achieve by breaking a step from T_k to T_{k+1} into several smaller intermediate steps. Assume that (ii) holds. Then property (iii) can be achieved by omitting all steps that make $|T_k(C)|$ smaller than d. It is easy to see that the resulting sequence is again an admissible subset teaching sequence. $\qquad\square$

Proposition 13 $\mathrm{STD}_{\min}(\mathcal{C}) \le \mathrm{STD}(\mathcal{C})$, *and for all $n \in \mathbb{N}$ there is some succinct $\mathcal{C}_n$ such that $\mathrm{STD}_{\min}(\mathcal{C}_n) = 2$ and $\mathrm{STD}(\mathcal{C}) = n$.*

Proof. To see that $\mathrm{STD}_{\min}$ is bounded from above by STD, let k^* be as defined in Definition 4. For each $k \le k^*$, let $T_k(C)$ be *any one* set in $\mathrm{STS}^k(C)$ such that $T_{k^*}(C) \subseteq T_{k^*-1}(C) \subseteq \ldots \subseteq T_1(C)$. Such sets $T_k(C)$ exist by the definition of STD. Finally, set $T_0(C) = \{(x, C(x)) \mid x \in X\}$. Then $\mathcal{T} = (T_k)_{k \in \mathbb{N}}$ is a subset teaching sequence of order $\mathrm{STD}(\mathcal{C})$ for $\mathcal{C}$. So, $\mathrm{STD}_{\min}(\mathcal{C}) \le \mathrm{STD}(\mathcal{C})$.

concept	x_1	x_2	x_3	x_4	x_5	x_1'	x_2'	x_3'	x_4'	x_5'
$C_\emptyset$	0	0	0	0	**0**	1	1	1	1	**1**
$C_{\{1\}}$	1	0	0	0	0	1	**0**	**0**	**0**	**0**
$C_{\{2\}}$	**0**	1	0	0	0	0	1	**0**	**0**	**0**
$C_{\{3\}}$	**0**	**0**	1	0	0	0	0	1	**0**	**0**
$C_{\{4\}}$	**0**	**0**	**0**	1	0	0	0	0	1	**0**
$C_{\{5\}}$	**0**	**0**	**0**	0	1	0	0	0	**0**	1
$C_{\{1,2\}}$	1	1	0	0	0	1	1	0	0	0
$C_{\{1,3\}}$	1	0	1	0	0	1	0	1	0	0
$C_{\{1,4\}}$	1	0	0	1	0	1	0	0	1	0
$C_{\{1,5\}}$	1	0	0	0	1	1	0	0	0	1
$C_{\{2,3\}}$	0	1	1	0	0	0	1	1	0	0
$C_{\{2,4\}}$	0	1	0	1	0	0	1	0	1	0
$C_{\{2,5\}}$	0	1	0	0	1	0	1	0	0	1
$C_{\{3,4\}}$	0	0	1	1	0	0	0	1	1	0
$C_{\{3,5\}}$	0	0	1	0	1	0	0	1	0	1
$C_{\{4,5\}}$	0	0	0	1	1	0	0	0	1	1

Table 3: The concept class $\mathcal{C}$ from the proof of Proposition 11 for $n = 5$. The entries in bold indicate one (arbitrarily chosen) minimum teaching set for each concept.

An example of a succinct concept class $\mathcal{C}_n$ as claimed is the class over a domain of size $n + 1$, consisting of all concepts of size either 1 or 2. It was shown by Zilles et al. [2011], that $\mathrm{STD}(\mathcal{C}) = n$. By contrast, one can easily obtain $\mathrm{STD}_{\min}(\mathcal{C}_n) = 2$, as illustrated in Table 4: for any concept C of size 2, the set $T_1(C)$ contains only the two positively labeled instances for C, while $T_1(C) = T_0(C) = \{(x, C(x)) \mid x \in X\}$ if C is a singleton. In the next iteration, set $T_2(\{x_n\}) = \{(x_n, 1), (x_1, 0)\}$ and $T_2(\{x_i\}) = \{(x_i, 1), (x_{i+1}, 0)\}$ for each singleton concept $\{x_i\}$ with $i \neq n$. Clearly, for all i, $T_2(\{x_i\}) \subseteq T_1(\{x_i\})$ and $T_2(\{x_i\}) \not\subseteq T_1(C)$ for any $C \neq \{x_i\}$. Thus, we obtain a subset teaching sequence of order 2 for $\mathcal{C}$, i.e., $\mathrm{STD}_{\min}(\mathcal{C}) = 2$. $\qquad\square$

concept in $\mathcal{C}_4$	x_1	x_2	x_3	x_4	x_5	T_1
C_1	**1**	**0**	0	0	0	$\{(x_1, 1), (x_2, 0), (x_3, 0), (x_4, 0), (x_5, 0)\}$
C_2	0	**1**	**0**	0	0	$\{(x_1, 0), (x_2, 1), (x_3, 0), (x_4, 0), (x_5, 0)\}$
C_3	0	0	**1**	**0**	0	$\{(x_1, 0), (x_2, 0), (x_3, 1), (x_4, 0), (x_5, 0)\}$
C_4	0	0	0	**1**	**0**	$\{(x_1, 0), (x_2, 0), (x_3, 0), (x_4, 1), (x_5, 0)\}$
C_5	**0**	0	0	0	**1**	$\{(x_1, 0), (x_2, 0), (x_3, 0), (x_4, 0), (x_5, 1)\}$
C_6	**1**	**1**	0	0	0	$\{(x_1, 1), (x_2, 1)\}$
C_7	**1**	0	**1**	0	0	$\{(x_1, 1), (x_3, 1)\}$
C_8	**1**	0	0	**1**	0	$\{(x_1, 1), (x_4, 1)\}$
C_9	**1**	0	0	0	**1**	$\{(x_1, 1), (x_5, 1)\}$
C_{10}	0	**1**	**1**	0	0	$\{(x_2, 1), (x_3, 1)\}$
C_{11}	0	**1**	0	**1**	0	$\{(x_2, 1), (x_4, 1)\}$
C_{12}	0	**1**	0	0	**1**	$\{(x_2, 1), (x_5, 1)\}$
C_{13}	0	0	**1**	**1**	0	$\{(x_3, 1), (x_4, 1)\}$
C_{14}	0	0	**1**	0	**1**	$\{(x_3, 1), (x_5, 1)\}$
C_{15}	0	0	0	**1**	**1**	$\{(x_4, 1), (x_5, 1)\}$

Table 4: The concept class $\mathcal{C}_n$ [Zilles et al., 2011], from the proof of Proposition 13 for the case $n = 4$. The final subset teaching sets (corresponding to T_2) that witness $\mathrm{STD}_{\min}(\mathcal{C}_n) = 2$ are highlighted in blue. The rightmost column shows the mapping T_1; the subsets marked in blue are not contained in any other set in that column, hence they can be used by the teacher T_2 in the next iteration. When calculating STD instead of $\mathrm{STD}_{\min}$, the teacher T_1 assigns every singleton its unique minimum teaching set, which is a set of four negative examples. These sets cannot be reduced in subsequent iterations, since their proper subsets occur in minimum teaching sets for other concepts; hence $\mathrm{STD}(\mathcal{C}_4) = 4$.

Proposition 15 $\mathrm{STD}_{\min}$ *is class-monotonic, domain-monotonic, and satisfies the antichain property.*

Proof. Class-monotonicity is obvious: If $\mathcal{C}, \mathcal{C}'$ are concept classes over a fixed domain X, $\mathcal{C} \subseteq \mathcal{C}'$, and $\mathcal{T}' = (T_k')_{k \in \mathbb{N}}$ is a subset teaching sequence for $\mathcal{C}'$ of order $\mathrm{STD}_{\min}(\mathcal{C}')$, then define T_k to be

the restriction of T'_k to $\mathcal{C}$. Clearly, $\mathcal{T} = (T_k)_{k \in \mathbb{N}}$ is a subset teaching sequence for $\mathcal{C}$ of order at most $\mathrm{STD}_{\min}(\mathcal{C}')$. Hence $\mathrm{STD}_{\min}(\mathcal{C}) \leq \mathrm{STD}_{\min}(\mathcal{C}')$.

To establish domain-monotonicity, let $\mathcal{C}$ be any concept class over a domain X, and let $X' \subseteq X$ preserve $\mathcal{C}$. Then any subset teaching sequence $\mathcal{T}'$ for $\mathcal{C}{\downarrow}_{X'}$ can be turned into a subset teaching sequence $\mathcal{T}$ for $\mathcal{C}$, by setting $T_0(C) = \{(x, C(x)) \mid x \in X\}$ and $T_k(C) = T'_k(C)$ for all $C \in \mathcal{C}$ and all $k \geq 1$. Note that $\mathrm{ord}_{\mathcal{C}}(\mathcal{T}) = \mathrm{ord}_{\mathcal{C}{\downarrow}_{X'}}(\mathcal{T}')$. Therefore $\mathrm{STD}_{\min}(\mathcal{C}{\downarrow}_{X'}) \geq \mathrm{STD}_{\min}(\mathcal{C})$.

By the definition of subset teaching sequence, it is obvious that $\mathrm{STD}_{\min}$ satisfies the antichain property. $\qquad\square$

D   Proof Details for Section 5

Proposition 16 *For every $n \in \mathbb{N}$ there is (i) a concept class $\mathcal{C}$ with $\mathrm{STD}(\mathcal{C}) = \mathrm{STD}_{\min}(\mathcal{C}) = 1$ and $\mathrm{NCTD}(\mathcal{C}) = n$; (ii) a concept class $\mathcal{C}$ with $\mathrm{STD}(\mathcal{C}) = \mathrm{STD}_{\min}(\mathcal{C}) = n$ and $\mathrm{NCTD}(\mathcal{C}) = \frac{n}{2}$.*

Proof. (i) Consider the class $\mathcal{C}_u^{pair}$, as defined by Zilles et al. [2011], for any number $u \geq 3$. This concept class is shown in Table 5 for $u = 3$. It is defined over $2^u + u$ instances $x_1, \dots, x_{2^u+u}$. The set $\{x_{2^u+1}, \dots, x_{2^u+u}\}$ of the last u instances is shattered. Let $\alpha_1, \dots, \alpha_{2^u}$ be the list of all possible assignments of labels to the last u instances. For each such assignment α_i, the concept class contains two concepts C_{2i-1} and C_{2i} realizing α_i. The concept C_{2i-1} does not contain any of the first 2^u instances $x_1, \dots, x_{2^u}$. The concept C_{2i} contains x_i, but none of the other instances in $\{x_1, \dots, x_{2^u}\}$. See Table 5 for an illustration when $u = 3$. Note that this concept class can be equivalently written in block matrix form as follows:

$$\begin{bmatrix} I_{2^u} & P_u \\ 0 & P_u \end{bmatrix}$$

where P_u represents the powerset over a set of u instances and I_{2^u} is the $2^u \times 2^u$ identity matrix.

It was proven by Zilles et al. [2011] that $\mathrm{STD}(\mathcal{C}_u^{pair}) = 1$. We claim that $\mathrm{NCTD}(\mathcal{C}_u^{pair}) = \lceil \frac{u}{2} \rceil$. To see this, note that the subclass of concepts C_{2i-1}, $1 \leq i \leq 2^u$ is the powerset over the last u instances, where all these concepts agree on the first 2^u instances. Thus, the NCTD of this subclass equals the NCTD of the powerset over u instances, which is $\lceil \frac{u}{2} \rceil$ [Kirkpatrick et al., 2019]. Since NCTD is class-monotonic, we have $\mathrm{NCTD}(\mathcal{C}_u^{pair}) \geq \lceil \frac{u}{2} \rceil$. A teacher mapping T witnessing $\mathrm{NCTD}(\mathcal{C}_u^{pair}) \leq \lceil \frac{u}{2} \rceil$ can be defined by (i) setting $T(C_{2i}) = \{(x_i, 1)\}$ for $1 \leq i \leq 2^u$, and (ii) teaching the concepts C_{2i-1}, $1 \leq i \leq 2^u$, with a non-clashing teacher for the powerset over the last u instances, as used by Kirkpatrick et al. [2019]. Clearly, T is clash-free.

For $n \in \mathbb{N}$ and $u = 2n$, thus $\mathrm{STD}(\mathcal{C}_u^{pair}) = \mathrm{STD}_{\min}(\mathcal{C}_u^{pair}) = 1$ and $\mathrm{NCTD}(\mathcal{C}_u^{pair}) = n$.

(ii) Consider the powerset $\mathcal{P}_n$ on n instances. The fact that $\mathrm{NCTD}(\mathcal{C}) = \frac{n}{2}$ was shown by Kirkpatrick et al. [2019]. It is obvious that $\mathrm{STD}_{\min}(\mathcal{P}_n) = n$: Every sample set for a concept $C \in \mathcal{P}_n$ that omits one instance from X is also a sample set for some concept $C' \neq C$, $C' \in \mathcal{P}_n$. Thus any subset teaching sequence for $\mathcal{P}_n$ satisfies $T_k = T_0$ for all $k \in \mathbb{N}$. $\qquad\square$

E   Details for Section 6

E.1   Proof Details for Theorem 20

To complete the proof of Theorem 20, we show that $\mathrm{STD}_{\min}$ is not unambiguous on Warmuth's class $\mathcal{C}_W$ which was defined by Doliwa et al. [2014] after communication with M. Warmuth. $\mathcal{C}_W$ is a concept class of 10 concepts over 5 instances, see Table 6. We know that $\mathrm{VCD}(\mathcal{C}_W) = \mathrm{VCD}_{\min}(\mathcal{C}_W) = 2$, while $\mathrm{RTD}(\mathcal{C}_W) = \mathrm{STD}(\mathcal{C}_W) = 3$. It turns out that $\mathrm{STD}_{\min}(\mathcal{C}_W) \leq 2$, as witnessed by the subset teaching sequence that is highlighted in Table 6. However, there is a second $\mathrm{STD}_{\min}$-teacher for $\mathcal{C}_W$ that has exactly the same range as the one resulting from the subset teaching sequence in Table 6 – see Table 7. A comparison of Tables 6 and 7 shows that T_2 and T'_2 swap the teaching sets for C_{2i-1} and C_{2i}, for all $i \in \{1, \dots, 5\}$.

concept in $\mathcal{C}_3^{pair}$	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8	x_9	x_{10}	x_{11}
C_1	0	0	0	0	0	0	0	0	0	0	0
C_2	1	0	0	0	0	0	0	0	0	0	0
C_3	0	0	0	0	0	0	0	0	0	0	1
C_4	0	1	0	0	0	0	0	0	0	0	1
C_5	0	0	0	0	0	0	0	0	0	1	0
C_6	0	0	1	0	0	0	0	0	0	1	0
C_7	0	0	0	0	0	0	0	0	0	1	1
C_8	0	0	0	1	0	0	0	0	0	1	1
C_9	0	0	0	0	0	0	0	0	1	0	0
C_{10}	0	0	0	0	1	0	0	0	1	0	0
C_{11}	0	0	0	0	0	0	0	0	1	0	1
C_{12}	0	0	0	0	0	1	0	0	1	0	1
C_{13}	0	0	0	0	0	0	0	0	1	1	0
C_{14}	0	0	0	0	0	0	1	0	1	1	0
C_{15}	0	0	0	0	0	0	0	0	1	1	1
C_{16}	0	0	0	0	0	0	0	1	1	1	1

Table 5: The concept class $\mathcal{C}_u^{pair}$ [Zilles et al., 2011], for the case $u = 3$. The subset teaching sets witnessing $\mathrm{STD}(\mathcal{C}_3^{pair}) = 1$ are highlighted in blue. Non-clashing sets that witness $\mathrm{NCTD}(\mathcal{C}_3^{pair}) \leq 2$ are in bold font. The proof of Proposition 16 shows that $\mathrm{NCTD}(\mathcal{C}_3^{pair}) = 2$.

concept	T_0					T_1					T_2				
	x_1	x_2	x_3	x_4	x_5	x_1	x_2	x_3	x_4	x_5	x_1	x_2	x_3	x_4	x_5
C_1	1	1	0	0	0	*	*	0	0	0	*	*	0	*	0
C_2	1	1	0	1	0	1	1	*	1	*	1	1	*	*	*
C_3	0	1	1	0	0	0	*	*	0	0	0	*	*	0	*
C_4	0	1	1	0	1	*	1	1	*	1	*	1	1	*	*
C_5	0	0	1	1	0	0	0	*	*	0	*	0	*	*	0
C_6	1	0	1	1	0	1	*	1	1	*	*	*	1	1	*
C_7	0	0	0	1	1	0	0	0	*	*	0	*	0	*	*
C_8	0	1	0	1	1	*	1	*	1	1	*	*	*	1	1
C_9	1	0	0	0	1	*	0	0	0	*	*	0	*	0	*
C_{10}	1	0	1	0	1	1	*	1	*	1	1	*	*	*	1

Table 6: The concept class $\mathcal{C}_W$. A subset teaching sequence can be chosen by defining $T_1(C_{2i})$ to consist of the only three positive examples for C_{2i}, and $T_1(C_{2i-1})$ to consist of the only three negative examples for C_{2i-1}, where $1 \leq i \leq 5$. In T_2, these sets can easily be reduced to sets of size 2. Asterisks denote instances not occurring in the chosen teaching sets.

E.2 Redundant Instances Can Cause Extreme Forms of Ambiguity

The ambiguity of $\mathrm{STD}_{\min}$ can take extreme forms for artificially created concept classes that have many redundant instances. An instance $x \in X$ is redundant for $\mathcal{C}$ if $X \setminus \{x\}$ preserves $\mathcal{C}$.

Example 1 *For arbitrary $n \in \mathbb{N}$, consider a concept class for which* VCD *is n, while* $\mathrm{STD}_{\min}$ *equals 1, with a large number of redundant instances. Such a class can be constructed over a domain X that has $n2^n$ instances and is partitioned into 2^n sets $X_1, \ldots, X_{2^n}$, each of size n. The concept class consists of 2^n concepts, chosen so that they shatter each set X_i, $1 \leq i \leq 2^n$. See Table 8 for an illustration when $n = 2$.*

To see that $\mathrm{STD}_{\min}$ equals 1, let $C_1, \ldots, C_{2^n}$ be an enumeration of all concepts in this concept class. It suffices to pick a teaching sequence as follows. We define $T_1(C_i) = \{(x, C_i(x)) \mid x \in X_i\}$, that means, we pick the instances in the ith set X_i to represent the ith concept. Now $T_2(C_i)$ can consist of any single example from $T_1(C_i)$, since $T_1(C_i) \cap T_1(C_j) = \emptyset$ for all $j \neq i$.

Obviously, by reordering concepts, we obtain different $\mathrm{STD}_{\min}$-teachers that have the same range; in particular, they witness a very high degree of ambiguity, as will be formalized in Observation 2.

Example 1 can be generalized to the following observation.

concept	$T'_0 = T_0$					T'_1					T'_2				
	x_1	x_2	x_3	x_4	x_5	x_1	x_2	x_3	x_4	x_5	x_1	x_2	x_3	x_4	x_5
C_1	1	1	0	0	0	1	1	*	0	*	1	1	*	*	*
C_2	1	1	0	1	0	*	*	0	1	0	*	*	0	*	0
C_3	0	1	1	0	0	*	1	1	*	0	*	1	1	*	*
C_4	0	1	1	0	1	0	*	*	0	1	0	*	*	0	*
C_5	0	0	1	1	0	0	*	1	1	*	*	*	1	1	*
C_6	1	0	1	1	0	1	0	*	*	0	*	0	*	*	0
C_7	0	0	0	1	1	*	0	*	1	1	*	*	*	1	1
C_8	0	1	0	1	1	0	1	0	*	*	0	*	0	*	*
C_9	1	0	0	0	1	1	*	0	*	1	1	*	*	*	1
C_{10}	1	0	1	0	1	*	0	1	0	*	*	0	*	0	*

Table 7: A second subset teaching sequence for the concept class $\mathcal{C}_W$.

concept	X_1		X_2		X_3		X_4	
	x_1	x_2	x_3	x_4	x_5	x_6	x_7	x_8
C_1	0	0	0	0	0	0	0	0
C_2	0	1	0	1	0	1	0	1
C_3	1	0	1	0	1	0	1	0
C_4	1	1	1	1	1	1	1	1

Table 8: The concept class from Example 1, for the case $n = 2$. Highlighted in blue are the labels chosen for teaching individual concepts with T_1. Clearly, T_2 can be defined to assign each concept a singleton sample set.

Observation 2 *Let $\mathcal{C}$ be any concept class over a domain X. Suppose X can be partitioned into a family $(X_C)_{C \in \mathcal{C}}$ of subsets such that X_C preserves $\mathcal{C}$, for every $C \in \mathcal{C}$. Then $\mathrm{STD}_{\min}(\mathcal{C}) = 1$ and there are at least $|\mathcal{C}|!$ pairwise distinct $\mathrm{STD}_{\min}$-teachers for $\mathcal{C}$ with the same range on $\mathcal{C}$. In particular, every permutation σ of $\mathcal{C}$ yields an $\mathrm{STD}_{\min}$-teacher that maps a concept C to the singleton sample set $\{(x_{\sigma(C)}, C(x_{\sigma(C)}))\}$, where $x_{\sigma(C)}$ is any instance in $X_{\sigma(C)}$.*