Hard-label Manifolds: Unexpected advantages of query efficiency for finding on-manifold adversarial examples

Abstract

Designing deep networks robust to adversarial examples remains an open problem. Likewise, recent zeroth order hard-label attacks on image classification tasks have shown comparable performance to their first-order alternatives. It is well known that in this setting, the adversary must search for the nearest decision boundary in a query-efficient manner. State-of-the-art (SotA) attacks rely on the concept of pixel grouping, or super-pixels, to perform efficient boundary search. It was recently shown in the first-order setting, that regular adversarial examples leave the data manifold, and on-manifold examples are generalization errors (Stutz et al., 2019). In this paper, we argue that query efficiency in the zeroth-order setting is connected to the adversary's traversal through the data manifold. In particular, query-efficient hard-label attacks have the unexpected advantage of finding adversarial examples close to the data manifold. We empirically demonstrate that against both natural and robustly trained models, an efficient zeroth-order attack produces samples with a progressively smaller manifold distance measure. Further, when a normal zeroth-order attack is made query-efficient through the use of pixel grouping, it can make up to a two-fold increase in query efficiency, and in some cases, reduce a sample's distance to the manifold by an order of magnitude.

1 Introduction

Adversarial examples in the context of deep learning models were originally investigated as blind spots in classification (Szegedy et al., 2013; Goodfellow et al., 2014). Formalized methods for discovering these blind spots emerged, referred to as gradient-level attacks, and became the first style to reach widespread attention by the deep learning community (Papernot et al., 2016; Moosavi-Dezfooli et al., 2015; Carlini & Wagner, 2016; 2017). In order to compute the necessary gradient information, such techniques required access to model parameters and a sizeable query budget, needing surrogate information to be competitive (Papernot et al., 2017). This naturally led to the creation of score-level attacks, which only require the confidence values output by machine learning models (Fredrikson et al., 2015; Tramèr et al., 2016; Chen et al., 2017; Ilyas et al., 2018). However, the grand prize of adversarial ML (AML), hard-label attacks, have been proposed in very recent years. These methods, which originated from a random-walk on the decision boundary (Brendel et al., 2017), have been carefully refined to offer convergence guarantees (Cheng et al., 2019), query efficiency (Chen et al., 2019; Cheng et al., 2020), and simplicity through super-pixel grouping (Chen & Gu, 2020), without ever sacrificing earlier advances.

Despite the steady improvements of hard-label attacks, open questions persist about their behavior, and AML attacks at large. The existence of adversarial samples were originally assumed to lie in rare pockets of the input space (Goodfellow et al., 2014), but this was later challenged by the boundary tilting assumption (Tanay & Griffin, 2016; Gilmer et al., 2018), which adopts a "data-geometric" view of the input space living on a manifold. This is supported by Stutz et al. (2019), who suggest that regular adversarial examples leave the data manifold, while on-manifold adversarial examples are generalization errors.

In this paper, we adopt the boundary-tilting assumption and demonstrate an unexpected benefit of query-efficient zeroth order attacks; such attacks are more likely to discover on-manifold examples,

and it is primarily enabled by the use of down-scaling techniques, such as super-pixel grouping. This is initially counter-intuitive, since down-scaling techniques reduce the search dimension, which artificially limits the search space, and can lead to worse (farther-away) adversarial examples. Our results suggest, however, that super-pixels help eliminate the search space of off-manifold adversarial examples, leading to examples which are **truly generalization errors**. With this knowledge, it is possible to rethink the design of hard-label attacks, towards those which resemble attack (b) in Figure 1, rather than (a) or (c).

Our specific contributions are as follows:

- **Reveal a novel nuance of zeroth order attacks.** We describe an approach for extending dimension-reduction technqiues in the score-level setting (Tu et al., 2019) to hard-label attacks. Afterwards, we propose the use of FID score (Heusel et al., 2018) as an L_p-agnostic means for estimating distance to the sampled submanifold. This measure allows to empirically demonstrate the connection between query efficiency and on-manifold adversarial examples, beyond the known convergence rates tied to dimensionality (Nesterov & Spokoiny, 2017).

- **Attack-agnostic method for super-pixel grouping.** We show that bilinear down-scaling of the input space act as a form of super-pixel grouping, which yields up to 140% and 210% query efficiency gain for previously-proposed HSJA (Chen et al., 2019) and Sign-OPT attack (Cheng et al., 2020), respectively.

- Our analysis covers a comprehensive array of datasets, model regularization methods, and L_p-norm settings from the literature. Regardless of the setting, we observe a consistent behavior in query-efficient attacks. Thus we propose an information-theoretical formulation and interpretation of the **noisy manifold distance oracle**, which enables zeroth-order attacks to craft on-manifold examples. Studying this problem may assist in understanding the fundamental limits and utility of hard-label attacks.

a: off-manifold, low-similarity
b: on-manifold, high-similarity
c: on-manifold, low-similarity
--·--· --·--· : search space

Figure 1: Our interpretation of zeroth-order attack behavior in the context of boundary tilting (Tanay & Griffin, 2016): a) zeroth-order attack targeting low-level features, leaving the manifold, b) an efficient zeroth-order attack targeting mostly high-level features, floating along the manifold, and c) manifold-based zeroth-order attack next to the manifold, but sacrificing similarity.

2   RELATED WORK

Since the original discovery of adversarial samples (Szegedy et al., 2013; Goodfellow et al., 2014) and later formulations based on optimization (Carlini & Wagner, 2016; Moosavi-Dezfooli et al., 2015), the prevailing question was why such examples existed. The original assumption was that adversarial examples lived in low-probability pockets of the input space, and were thus never encountered during parameter optimization (Szegedy et al., 2013). This effect was believed to be amplified by the linearity of weight activations in the presence of small perturbations (Goodfellow et al., 2014). These assumptions were later challenged by the manifold assumption, which in summary claims that 1) the train and test sets of a model only occupy a sub-manifold of the true data, while the decision boundary lies close to samples on and beyond the sub-manifold (Tanay & Griffin, 2016), and 2) the "data geometric" view, where high-dimensional geometry of the true data manifold enables a low-probability error set to exist (Gilmer et al., 2018). Likewise the manifold assumption describes adversarial samples as leaving the manifold, which has inspired many defenses based on projecting such samples back to the data manifold (Jalal et al., 2019; Samangouei et al., 2018), and adaptive attacks for foiling these defenses (Carlini et al., 2019; Carlini & Wagner, 2017; Tramer et al., 2020). We investigate the scenario where an adversary uses zeroth-order information to either estimate the gradient direction, or find the closest decision boundary, related to previous work in the gradient-level setting by Stutz et al. (2019). In our setting, the adversary uses the top-1 label feedback from the model to reach their goal. They can also use a low-dimensional approximation of the data manifold

to encourage query-efficiency. However, to date it is not completely understood how this affects the traversal through the data manifold, particularly in the zeroth-order setting.

3 ZEROTH-ORDER SEARCH THROUGH THE MANIFOLD

Our primary motivation is to characterize recent zeroth-order attacks as they relate to ideas of manifold traversal (Chen et al., 2019; Cheng et al., 2020; Chen & Gu, 2020). In the most common problem setting, the adversary is interested in attacking a K-way multi-class classification model $f : \mathbb{R}^d \to \{1, \ldots, K\}$. Given an original example $\mathbf{x}_0$, the goal is to generate adversarial example $\mathbf{x}$ such that $\mathbf{x}$ is close to $\mathbf{x}_0$ and $f(\mathbf{x}) \neq f(\mathbf{x}_0)$, where closeness is often approximated by the L_p-norm of $\mathbf{x} - \mathbf{x}_0$. The value of this approximation is debated in the literature (Heusel et al., 2018; Tsipras et al., 2018; Engstrom et al., 2019). Likewise we turn to alternative methods shown later for measuring closeness. First we step through the formulation for contemporary hard-label attacks, then show how dimension-reduced score-level attacks are extended to the hard-label setting, which enables analysis of zeroth-order decision boundary search.

3.1 GRADIENT-LEVEL FORMULATION

For gradient-level attacks, the goal is satisfied by first assuming that $f(\mathbf{x}) = \operatorname{argmax}_i(Z(\mathbf{x})_i)$, where $Z(\mathbf{x}) \in \mathbb{R}^K$ is the final (logit) layer output, and $Z(\mathbf{x})_i$ is the prediction score for the i-th class, the stated goal is satisfied by the optimization problem,

$$h(\mathbf{x}) := \operatorname*{argmin}_{\mathbf{x}} \left\{ ||\mathbf{x} - \mathbf{x}_0||_p + c\mathcal{L}(Z(\mathbf{x})) \right\}, \tag{1}$$

for the Euclidean L_p-norm $|| \cdot ||_p$, $\mathcal{L}(\cdot)$ is the loss function corresponding to the goal of the attack, and c is a regularization parameter. A popular choice of loss function is the Carlini & Wagner (2016) loss function.

3.2 SCORE-LEVEL AND HARD-LABEL ATTACKS

In the gradient-level setting, we require the gradient $\nabla f(\cdot)$. However, in the score-level setting we are forced to estimate $\frac{\partial f(\mathbf{x})}{\partial \mathbf{x}}$ without access to $\nabla f(\cdot)$, only evaluations of $Z(\cdot)$. Tu et al. (2019) reformulate the previous problem to a version relying instead on the ranking of class predictions from Z. In practical scenarios, the estimate is found using random gradient-free method (RGF), a scaled random full gradient estimator of $\nabla f(\mathbf{x})$, over q random directions $\{\mathbf{u}_j\}_{j=1}^q$. The score-level setting was extended to several renditions of the hard-label setting, which we clarify below. In each case the goal is to approximate the gradient by $\hat{\mathbf{g}}$.

OPT-Attack For given example $\mathbf{x}_0$, true label y_0, and hard-label black-box function $f : \mathbb{R}^d \to \{1, \ldots, K\}$, Cheng et al. (2019) define the objective function $g : \mathbb{R}^d \to \mathbb{R}$ as a function of search direction $\boldsymbol{\theta}$, where $g(\boldsymbol{\theta}^*)$ is the minimum distance from $\mathbf{x}_0$ to the nearest adversarial example along the direction $\boldsymbol{\theta}$. For the untargeted attack, $g(\boldsymbol{\theta})$ corresponds to the distance to the decision boundary along direction $\boldsymbol{\theta}$, and allows for estimating the gradient as,

$$\hat{\mathbf{g}} = \frac{1}{q} \sum_{i=0}^q \frac{g(\boldsymbol{\theta} + \beta\mathbf{u}_i) - g(\boldsymbol{\theta})}{\beta} \cdot \mathbf{u}_i. \tag{2}$$

Notably, $g(\boldsymbol{\theta})$ is continuous even if f is a non-continuous step function.

Sign-OPT Cheng et al. (2020) later improved the query efficiency by only considering the sign of the gradient estimate,

$$\hat{\nabla} g(\boldsymbol{\theta}) \approx \hat{\mathbf{g}} := \sum_{i=1}^q \operatorname{sign}\left(g(\boldsymbol{\theta} + \beta\mathbf{u}_i) - g(\boldsymbol{\theta})\right) \mathbf{u}_i.$$

We focus on the Sign-OPT variant, as the findings are more relevant to the current SotA.

HopSkipJumpAttack Similar to Sign-OPT, HopSkipJumpAttack (HSJA) (Chen et al., 2019) uses a zeroth-order sign oracle to improve Boundary Attack proposed by Brendel et al. (2017). HSJA lacks the convergence analysis of OPT Attack/Sign-OPT and relies on one-point gradient estimate. Regardless, HSJA is competitive with Sign-OPT for SotA in the L_2 setting.

RayS Chen & Gu (2020) propose an alternative method which is to search for the minimum decision boundary radius r from a sample $\mathbf{x}_0$, along a ray direction $\boldsymbol{\theta}$. Instead of searching over $\mathbb{R}^d$ to minimize $g(\boldsymbol{\theta})$, Chen et al. propose to perform ray search over directions $\boldsymbol{\theta} \in \{-1, 1\}^d$, resulting in 2^d maximum possible directions. This reduction of the search resolution enables SotA query efficiency in the L_∞ setting with proof of convergence. The search resolution is further reduced by the hierarchical variant of RayS, which performs on-the-fly upscaling of image super-pixels.

3.3 DIMENSION-REDUCED ZEROTH-ORDER SEARCH

Instead of performing search over directions in the input space $\boldsymbol{\theta} \in \mathbb{R}^d$, Tu et al. (2019) experiment in the score-level setting with a search over reduced-dimension directions $\boldsymbol{\theta}' \in \mathbb{R}^{d'}$. The motivation for this stems from the known convergence rate of zeroth order gradient descent, which is tied to a dimensionality d of the vectorized input. The convergence rate is $O(\sqrt{d/T})$ for number of iterations T, on both convex (Nesterov & Spokoiny, 2017; Liu et al., 2018) and non-convex loss functions (Ghadimi & Lan, 2013). The reduced-dimension search is feasible since it was shown that the intrinsic dimensionality of data is often lower than the true dimension (Amsaleg et al., 2017). In practice this reduction is implemented through an encoding map $\mathcal{E} : \mathbb{R}^d \to \mathbb{R}^{d'}$ and decoding map $\mathcal{D} : \mathbb{R}^{d'} \to \mathbb{R}^d$. The adversarial sample is created by $\mathbf{x} = \mathbf{x}_0 + \boldsymbol{\delta}$, where $\boldsymbol{\delta} = \mathcal{D}(\boldsymbol{\theta}')$ with $\boldsymbol{\theta}' \in \mathbb{R}^{d'}$.

The mapping functions can be initialized with either an autoencoder (AE), or a pair of channel-wise bilinear transform functions (henceforth referred to as BiLIN) which simply scale the input up and down. In the case of the autoencoder, it is tuned to minimize reconstruction error of input images using disjoint data from the victim. In the case of BiLIN, no additonal training is required. We note that the the output of the AE-initialized decoder can be used in different ways, and leave this implementation detail for Section A.1 of the Appendix. Given this seemingly straightforward gain in query efficiency, we are still interested in controlling the error of the boundary search in zeroth order methods. In the lower dimension case, the search takes place in a lower fidelity version of the true data manifold, since the true intrinsic manifold is not known. In order to characterize hard-label methods, we rely on a hard-label version of the reduced-dimension search proposed by Tu et al. (2019), which later allows to unify the concept of query efficiency with search fidelity.

Sign-OPT & HSJA. In general for the attacks which rely on the Cheng et al. (2019) formulation, the update in Equation 2 becomes

$$\hat{\mathbf{g}} = \frac{1}{q} \sum_{i=0}^{q} \frac{g(\boldsymbol{\theta}' + \beta \mathbf{u}_i') - g(\boldsymbol{\theta}')}{\beta} \cdot \mathbf{u}_i', \tag{3}$$

for the reduced-dimension Gaussian vectors $\{\mathbf{u}_i' \in \mathbb{R}^{d'}\}_{i=0}^{q}$ and direction $\boldsymbol{\theta}' \in \mathbb{R}^{d'}$ for integer $d' < d$. The reduced-dimension direction $\boldsymbol{\theta}'$ is found with $\mathcal{E}(\boldsymbol{\theta})$ and vice versa with $\mathcal{D}(\boldsymbol{\theta}')$. Notably this is also applicable for HSJA, since HSJA performs a single-point sign estimate.

RayS. The intuition behind RayS attack is to perform a discrete search in at most 2^d directions. Chen et al. also perform a hierarchical search over progressively larger super-pixels of the image. This has the effect of already upscaling *on-the-fly* (Chen & Gu, 2020). To achieve an appropriate reduced-dimension version of RayS, and test our hypothesis, we modify the calculation of s in Algorithm 3, which either speeds up upscaling by a factor a (i.e., $s = s + a$), or extends the search through a specific block index by a factor b (increase block level at $k = 2^s b$ instead of $k = 2^s$).

3.4 Capturing zeroth-order search deviation

Our analysis follows in the wake of findings presented by (Stutz et al., 2019). It is shown that "regular" gradient-level adversarial examples leave the data manifold i.e., the sample's distance to the manifold is larger than with an "on-manifold" gradient-level adversarial example. In the score-level and hard-label settings, the manifold can be used to guide the search for the boundary. The benefits of this scenario can be observed in score-level attacks by Tu et al. (2019). Similarly, hard-label attacks can leverage the concept of super-pixels to achieve gains in performance (Chen & Gu, 2020). However, searching over a reduced-dimension imposes a reduced search fidelity, which can limit the search space to farther-away adversarial examples. Thus, we are interested in the tradeoff between query efficiency and search fidelity. This introduces our central research question: *How does searching over reduced-dimension increase efficiency, if the search resolution is decreased as a side-effect?*

To approach this question, we rely on a sample's distance to the manifold as a measure of deviation during the search, similar to the work by Stutz et al. (2019). Hereafter, we refer to this distance *w.l.o.g* as the manifold distance. Our choice is motivated by the fact that from a data-geometric perspective, manifold distance describes the amount of semantic features preserved during the attack process (Engstrom et al., 2019). Likewise the manifold distance can communicate more information about attack behavior than L_p distortion measurements, which are the common choice in existing zeroth-order attack literature (Cheng et al., 2020; Chen et al., 2019; Chen & Gu, 2020). Second, the manifold approximation technique by Stutz et al. (2019) is mainly suited for L_2-norm, whereas hard-label attacks exist for both L_2 and L_∞-norm. Thus we rely on the recently proposed Frechet Inception Distance (FID) as a surrogate measure of the manifold distance (Heusel et al., 2018). FID is viable as it computes Frechet distance of candidate images with respect to images sampled from the true data sub-manifold. Since FID uses an Inception-V3 coding layer to encode images, this distance will correlate with distortion of high-level features, i.e., features found by searching near the data manifold, which we are primarily interested in.

4 Results

4.1 Methodology

Our experimental analysis addresses the following three research questions about zeroth-order attacks:

Q1. What is the trade-off between query efficiency and reduced search resolution in the zeroth order setting, against both natural and "robust" models?

Q2. In addition to reducing queries, are there unexpected benefits for performing a query-efficient zeroth order attack?

Q3. Compared to the score-level setting, do dimension-reduced zeroth order attacks produce a similar amount of reduction in query usage?

We answer these questions by comparing three hard-label attacks against their dimension-reduced variants. Some variants are not shown due to incompatibility with the base attack. For example, AE+HSJA is not implemented as it relies on only a single-point estimate, thereby only allowing to attack on the manifold directly. This is not practical due to induced distortion discussed previously in Section 3. RayS can perform two-point search, but it assumes codependence of input features, which may not be the case for well-defined latent space of an autoencoder.[1] Thus for the AE variant, we rely on Sign-OPT as it can perform two-point estimate and does not rely on codependence of features. In the BiLN cases, the implementations follow the discussion in Section 3.3.

Experimental Highlights. Our experiments show that query-efficient attacks exhibit unexpected behaviors and benefits, with answers summarized below:

A1. Reduced search resolution incurs a cost relative to the situation. BiLN variants can leverage the reduced resolution to more efficiently attack both natural and robust models, at the cost of less fine-tuned distortion, seen best with BiLN+HSJA and BiLN+Sign-OPT.

---

[1]Experimentally, codependence hurt the AE+RayS variant more than was practically useful.

A2. Surprisingly, query-efficient attacks search closer to the manifold than non-efficient attacks, thus are more likely to produce on-manifold examples. This occurs in the absence of direct feedback from the model about manifold distance, and regardless of model regularization.

A3. Dimension-reduced attacks are capable of SotA query-efficiency gains for HSJA, and a two-fold improvement for Sign-OPT.

Setup. Samples are chosen using the same technique as in Chen et al. (2019), ten random classes chosen with ten random samples taken from each (100 samples total). All attacks run for 25k queries without early stopping. For brevity, we only show results for the untargeted case. FID score is calculated using the 64-dimensional max pooling layer of the Inception-V3 deep network for coding (denoted as FID-64 in figures), taken from an open-source implementation.[2] This allows to calculate FID without the full 2048 sample count of original FID. This incurs the cost of losing some high-level features, but due to the position of the chosen coding layer in the network, it is still valuable for direct comparison of manifold distance between attacks. Since the coding layer differs from the original implementation, the magnitudes will differ from those published by Heusel et al. (2018).

Image data consists of the CIFAR-10 (Krizhevsky, 2009) and ImageNet (Russakovsky et al., 2015) classification datasets. This selection allows to study attack behavior on both small and high-resolution image data. We provide further implementation details in Section A.1 of the Appendix. In addition to natural images, we are interested in the attack behavior for a model regularized with some variant of first-order noise. For CIFAR-10, we choose the representative adversarial training technique proposed by Madry et al. (2017). For completeness, we also include ablation results on more recent regularization techniques in Section A.3 of the Appendix. For ImageNet, we compare against the SotA at time of writing, randomized smoothing proposed by Cohen et al. (2019). We use the pre-trained Resnet50 weights and implementation provided by Cohen et al., corresponding to smoothing parameter $\sigma = 0.5$ and $\epsilon \simeq 1.0$.

4.2 EXPERIMENTAL DETAILS

On each dataset, we target the L_p-norm which the robust models were regularized or certified under. Likewise we use the L_∞ versions of each attack for CIFAR-10 and L_2 versions for ImageNet.

CIFAR-10 case study (L_∞). We start by measuring the distortion against remaining query budget of the adversary in Figure 2a. In general, the normal variants of each attack align with the published results. The BiLN variants of RayS each have minimal effect on overall query efficiency. The only notable improvement is with BiLN+HSJA against the Madry model, with average distortion at 4k queries decreasing from 0.09 to 0.07, and corresponding success rate increasing from 15% to 25%. This improvement aligns with the result of Tu et al. (2019). AE+Sign-OPT outperforms against regular Sign-OPT and BiLN+Sign-OPT on the robust model, since searching along the manifold can grant distortion which was not encountered during first-order regularization (Stutz et al., 2019). However, the success with AE+Sign-OPT tends to be situational, whereas HSJA and RayS outperform in either scenario. To understand why, we next focus on Figure 2b, which shows the FID score's trajectory as the search progresses. Every trajectory will begin at a zero value, since there is an expected score of zero for identical images, and then peaks as the attack initialization is performed. In this scenario, our main observation is the similarity of FID trajectory between AE+Sign-OPT, RayS, and HSJA, despite the method of model regularization. For example, the magnitudes for AE+Sign-OPT and RayS peak to 0.28 and 0.04, respectively, then fall (and stay) at values near 0.004 (refer to inset plots for detail). BiLN+HSJA and BiLN+Sign-OPT both exhibit lower FID scores than their normal variants, as much as two orders of magnitude less in the case of Sign-OPT and BiLN+Sign-OPT. For a detailed comparison of distortion and FID values for CIFAR-10, we offer Table 1 in Section A.3 of the Appendix. At a high level, we observe that BiLN+HSJA offers comparable performance to regular RayS, while in the robust case, BiLN and AE variants tend towards lower FID scores than regular variants. This can be viewed as the model leaking manifold information through the decision, as was shown for the first-order gradient by Engstrom et al. (2019).

ImageNet case study (L_2). We attack ImageNet in the L_2-norm setting so that we may compare against the certified smoothing technique proposed by Cohen et al. (2019). The label output comes

---

[2] https://github.com/mseitzer/pytorch-fid

Figure 2: Results across attacks for CIFAR-10 dataset, corresponding to a) distortion against query usage, and b) FID-64 trajectory against the same query usage. Dotted red line denotes the value of ϵ.

Figure 3: Results across attacks for ImageNet dataset, corresponding to a) distortion against query usage, and b) FID-64 trajectory against the same query usage. Dotted red line denotes the value of ϵ.

from a smooth classifier, approximated by many rounds of Monte Carlo search, which uses the regular model regularized by Gaussian noise. Thus hard-label attacks are well positioned for attacking the smoothing technique. The results of these attacks are shown in Figure 3a. Dimension reduction has a larger impact when coupled with the large ImageNet resolution. Particularly the BiLN+HSJA and BiLN+Sign-OPT attacks profit the most. At 8k queries, success rate increases 1.4x and 2.1x for HSJA and Sign-OPT, respectively. As before with CIFAR-10, the RayS dimension reduction is saturated on ImageNet. Apart from RayS, BiLN variants outperform both AE and regular variants in

every scenario, despite the reduced search fidelity. This is likely due to 1) the ImageNet test set being insufficient to approximate the true submanifold, and 2) BiLN allowing to exploit generalization error in both regular and smoothed scenarios. The FID scores in Figure 3b paint a more comprehensive picture. BiLN variants produce adversarial examples closer to the manifold than either regular or AE variants. In fact, this is the case for RayS as well, despite displaying nearly identical performance in the context of distortion. We interpret this as follows: BiLN variants leverage reduced fidelity to increase the probability of finding the decision boundary, and 1) produce a smoother noise distribution, resulting in more spatially correlated distortion, which as a result 2) produces adversarial examples closer to the manifold. Another key observation is the fluctuation of LID score towards the end of Sign-OPT and AE+Sign-OPT, which are not present for HSJA or RayS. Notably there is no direct signal of manifold distance in any attack shown. This indicates that perhaps, query-efficient attacks do a better job of capturing implicit manifold distance feedback from the model.

5 Discussion

The noisy manifold distance oracle. In Section 4 we observed that query-efficient attacks, i.e., those which leverage the concept of super-pixels to reduce search fidelity, are more likely to produce samples close to the manifold. However, this takes place without any direct feedback about manifold distance. To approach this, we first consider that the model relies on a subsampled manifold of the image space. This manifold can be leaked by the loss landscape of the model, as shown by Engstrom et al. (2019). From an information-theoretical perspective, the zeroth-order adversary observes the *noisy gradient*, which is leaked as side information by each model decision. Under this explanation, the decision feedback by the model is viewed as a noisy manifold distance (NMD) oracle. The improvement of AE+Sign-OPT on robust CIFAR-10 can be argued as a result of the NMD oracle improving as well. This can be shown using the data processing inequality (Beaudry & Renner, 2012): if $MI(\mathcal{M}, \mathbf{g})$ increases, then $MI(\mathcal{M}, \ddot{\mathbf{g}})$ also increases, where MI is mutual information, $\mathcal{M}$ is the manifold, and $\ddot{\mathbf{g}}$ is the noisy gradient. In words, the quality of the noisy gradient depends on the quality of the model's loss landscape, which can more closely resemble the manifold under robust regularization. This means a higher quality loss landscape leads to a higher quality zeroth-order attack. Qualitative evidence of this effect can be observed in Section A.2 of the Appendix.

"Topology" of hard-label settings. We can view zeroth-order attacks as following a topological hierarchy. A very simple version of this idea is illustrated in Figure 1. Each technique illustrated in Figure 1 offers a different traversal distance both along the manifold, and away from it. Efficient attacks represented by (b) can combine elements of staying near the manifold, and traversing it. This is best seen by the results of BiLN variants and regular RayS. Purely traversing close to an ideal manifold description, as in (c), may not be advantageous, because the crude manifold approximation induces its own error. Further, the nearest boundary on the manifold could be far away. Thus we can consider an attack which leverages an ideal "manifold description" (e.g., through an autoencoder), but leverages the description as a method for selecting progressively smaller super-pixel groupings. For instance, RayS selects super-pixels as blocks, which are bifurcated until the number of super-pixels equals the original dimension. A technique which leverages the manifold description could yield better performance, both in terms of distortion and FID score. To this end, we feel the FID score offers a valuable measure of manifold distance, which can inform the topological behavior, and the quality of future hard-label attacks.

6 Conclusion

Despite the recent progress in zeroth-order attack methods, open questions remain about their precise behavior. We shed light on an unexpected nuance, which is their ability to produce on-manifold adversarial examples. This is despite the absence of manifold distance information, which motivates the proposal of the noisy manifold distance oracle. Future work could create a formal definition of this oracle, and attempt to bound the information revealed by the oracle. On the other hand, with knowledge of the oracle's existence, it is possible to further refine hard-label attacks, so they continue to reveal insights into the weaknesses of learning systems.

REFERENCES

L. Amsaleg, J. Bailey, D. Barbe, S. Erfani, M. E. Houle, V. Nguyen, and M. Radovanović. The vulnerability of learning to adversarial perturbation increases with intrinsic dimensionality. In *2017 IEEE Workshop on Information Forensics and Security (WIFS)*, pp. 1–6, December 2017. doi: 10.1109/WIFS.2017.8267651.

Normand J. Beaudry and Renato Renner. An intuitive proof of the data processing inequality. *arXiv:1107.0740 [quant-ph]*, September 2012. URL http://arxiv.org/abs/1107.0740. arXiv: 1107.0740.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-Based Adversarial Attacks: Reliable Attacks Against Black-Box Machine Learning Models. *arXiv:1712.04248 [cs, stat]*, December 2017. URL http://arxiv.org/abs/1712.04248. arXiv: 1712.04248.

Nicholas Carlini and David Wagner. Towards Evaluating the Robustness of Neural Networks. In *Security and Privacy (SP)*, pp. 582–597, 2016. ISBN 978-1-5090-5533-3. doi: 10.1109/SP.2017.49. arXiv: 1608.04644 ISSN: 10816011.

Nicholas Carlini and David Wagner. Adversarial Examples Are Not Easily Detected: Bypassing Ten Detection Methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security - AISec '17*, pp. 3–14, Dallas, Texas, USA, 2017. ACM Press. ISBN 978-1-4503-5202-4. doi: 10.1145/3128572.3140444. URL http://dl.acm.org/citation.cfm?doid=3128572.3140444.

Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian Goodfellow, Aleksander Madry, and Alexey Kurakin. On Evaluating Adversarial Robustness. *arXiv:1902.06705 [cs, stat]*, February 2019. URL http://arxiv.org/abs/1902.06705. arXiv: 1902.06705.

Jianbo Chen, Michael I. Jordan, and Martin J. Wainwright. HopSkipJumpAttack: A Query-Efficient Decision-Based Attack. *arXiv:1904.02144 [cs, math, stat]*, April 2019. URL http://arxiv.org/abs/1904.02144. arXiv: 1904.02144.

Jinghui Chen and Quanquan Gu. RayS: A Ray Searching Method for Hard-label Adversarial Attack. *arXiv:2006.12792 [cs, stat]*, June 2020. URL http://arxiv.org/abs/2006.12792. arXiv: 2006.12792.

Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. ZOO: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *ACM Workshop on Artificial Intelligence and Security*, pp. 15–26, 2017.

Minhao Cheng, Thong Le, Pin-Yu Chen, Jinfeng Yi, Huan Zhang, and Cho-Jui Hsieh. Query-efficient hard-label black-box attack: An optimization-based approach. *International Conference on Learning Representations*, 2019.

Minhao Cheng, Simranjit Singh, Patrick Chen, Pin-Yu Chen, Sijia Liu, and Cho-Jui Hsieh. SIGN-OPT: A QUERY-EFFICIENT HARD-LABEL ADVERSARIAL ATTACK. *The International Conference on Learning Representations (ICLR)*, pp. 16, 2020. URL https://openreview.net/forum?id=SklTQCNtvS.

Jeremy M. Cohen, Elan Rosenfeld, and J. Zico Kolter. Certified Adversarial Robustness via Randomized Smoothing. *arXiv:1902.02918 [cs, stat]*, February 2019. URL http://arxiv.org/abs/1902.02918. arXiv: 1902.02918.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Brandon Tran, and Aleksander Madry. Learning Perceptually-Aligned Representations via Adversarial Robustness. *arXiv:1906.00945 [cs, stat]*, June 2019. URL http://arxiv.org/abs/1906.00945. arXiv: 1906.00945.

Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. Model Inversion Attacks that Exploit Confidence Information and Basic Countermeasures. *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security - CCS '15*, pp. 1322–1333, 2015. ISSN 15437221. doi: 10.1145/2810103.2813677. URL http://dl.acm.org/citation.cfm?doid=2810103.2813677. ISBN: 9781450338325.

Saeed Ghadimi and Guanghui Lan. Stochastic First- and Zeroth-Order Methods for Nonconvex Stochastic Programming. *SIAM Journal on Optimization*, 23(4):2341–2368, January 2013. ISSN 1052-6234, 1095-7189. doi: 10.1137/120880811. URL http://epubs.siam.org/doi/10.1137/120880811.

Justin Gilmer, Luke Metz, Fartash Faghri, Samuel S. Schoenholz, Maithra Raghu, Martin Wattenberg, and Ian Goodfellow. The Relationship Between High-Dimensional Geometry and Adversarial Examples. *arXiv:1801.02774 [cs]*, September 2018. URL http://arxiv.org/abs/1801.02774. arXiv: 1801.02774.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and Harnessing Adversarial Examples. 2014. ISSN 0012-7183. URL http://arxiv.org/abs/1412.6572. arXiv: 1412.6572 ISBN: 1412.6572.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium. *arXiv:1706.08500 [cs, stat]*, January 2018. URL http://arxiv.org/abs/1706.08500. arXiv: 1706.08500.

Andrew Ilyas, Logan Engstrom, Anish Athalye, and Jessy Lin. Black-box Adversarial Attacks with Limited Queries and Information. *arXiv:1804.08598 [cs, stat]*, July 2018. URL http://arxiv.org/abs/1804.08598. arXiv: 1804.08598.

Ajil Jalal, Andrew Ilyas, Constantinos Daskalakis, and Alexandros G. Dimakis. The Robust Manifold Defense: Adversarial Training using Generative Models. *arXiv:1712.09196 [cs, stat]*, July 2019. URL http://arxiv.org/abs/1712.09196. arXiv: 1712.09196.

Kim Jungeum and Xiao Wang. Sensible Adversarial Learning. 2020. URL https://openreview.net/pdf?id=rJlf_RVKwr.

Alex Krizhevsky. Learning Multiple Layers of Features from Tiny Images. pp. 60, 2009.

Sijia Liu, Jie Chen, Pin-Yu Chen, and Alfred O Hero. Zeroth-Order Online Alternating Direction Method of Multipliers: Convergence Analysis and Applications. In *Proceedings of the 21st International Conference on Artificial Intelligence and Statistics (AISTATS) 2018*, volume 84, pp. 10, Lanzarote, Spain, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards Deep Learning Models Resistant to Adversarial Attacks. *arXiv:1706.06083 [cs, stat]*, June 2017. URL http://arxiv.org/abs/1706.06083. arXiv: 1706.06083.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. DeepFool: a simple and accurate method to fool deep neural networks. 2015. ISSN 10636919. doi: 10.1109/CVPR.2016.282. URL http://arxiv.org/abs/1511.04599. arXiv: 1511.04599 ISBN: 9781467388511.

Yurii Nesterov and Vladimir Spokoiny. Random Gradient-Free Minimization of Convex Functions. *Foundations of Computational Mathematics*, 17(2):527–566, April 2017. ISSN 1615-3375, 1615-3383. doi: 10.1007/s10208-015-9296-2. URL http://link.springer.com/10.1007/s10208-015-9296-2.

Nicolas Papernot, Patrick Mcdaniel, Somesh Jha, Matt Fredrikson, Z. Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. *Proceedings - 2016 IEEE European Symposium on Security and Privacy, EURO S and P 2016*, pp. 372–387, 2016. doi: 10.1109/EuroSP.2016.36. URL http://arxiv.org/abs/1511.07528. arXiv: 1511.07528 ISBN: 9781509017515.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z. Berkay Celik, and Ananthram Swami. Practical Black-Box Attacks against Machine Learning. *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pp. 506–519, 2017. doi: 10.1145/3052973.3053009. URL http://arxiv.org/abs/1602.02697. arXiv: 1602.02697 ISBN: 9781450349444.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115 (3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Pouya Samangouei, Maya Kabkab, and Rama Chellappa. Defense-gan: Protecting classifiers against adversarial attacks using generative models. In *International Conference on Learning Representations*, 2018.

David Stutz, Matthias Hein, and Bernt Schiele. Disentangling adversarial robustness and generalization. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. pp. 1–10, 2013. ISSN 15499618. doi: 10.1021/ct2009208. URL http://arxiv.org/abs/1312.6199. arXiv: 1312.6199 ISBN: 1549-9618.

Thomas Tanay and Lewis Griffin. A Boundary Tilting Persepective on the Phenomenon of Adversarial Examples. *arXiv:1608.07690 [cs, stat]*, August 2016. URL http://arxiv.org/abs/1608.07690. arXiv: 1608.07690.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On Adaptive Attacks to Adversarial Example Defenses. *arXiv:2002.08347 [cs, stat]*, February 2020. URL http://arxiv.org/abs/2002.08347. arXiv: 2002.08347.

Florian Tramèr, Fan Zhang, Floriantra Er Epfl, Ari Juels, Michael K Reiter, and Thomas Ristenpart. Stealing Machine Learning Models via Prediction APIs. 2016. URL https://www.usenix.org/conference/usenixsecurity16/technical-sessions/presentation/tramer. ISBN: 978-1-931971-32-4.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness May Be at Odds with Accuracy. *arXiv:1805.12152 [cs, stat]*, May 2018. URL http://arxiv.org/abs/1805.12152. arXiv: 1805.12152.

Chun-Chen Tu, Paishun Ting, Pin-Yu Chen, Sijia Liu, Huan Zhang, Jinfeng Yi, Cho-Jui Hsieh, and Shin-Ming Cheng. AutoZOOM: Autoencoder-Based Zeroth Order Optimization Method for Attacking Black-Box Neural Networks. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33:742–749, July 2019. ISSN 2374-3468, 2159-5399. doi: 10.1609/aaai.v33i01.3301742. URL https://aaai.org/ojs/index.php/AAAI/article/view/3852.

Haichao Zhang and Jianyu Wang. Defense Against Adversarial Attacks Using Feature Scattering-based Adversarial Training. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 1831–1841. Curran Associates, Inc., 2019.

Haichao Zhang and wei Xu. Adversarial Interpolation Training: A simple approach for improving model robustness. 2020. URL https://openreview.net/pdf?id=Syejj0NYvr.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically Principled Trade-off between Robustness and Accuracy. *PMLR*, pp. 11, 2019.

A APPENDIX

A.1 IMPLEMENTATION DETAILS

We are primarily interested in the effect of reduced search resolution on attack behavior. Thus in this work, given a candidate direction $\boldsymbol{\theta}'$ and magnitude (or radius) r, the adversarial sample in the AE case is the blending $(1 - r)\mathbf{x}_0 + r\mathcal{D}\left(\mathcal{E}(\mathbf{x}_0) + \boldsymbol{\theta}'\right)$.[3]

---

[3]We observed that it is detrimental to set $\mathbf{x} = \mathcal{D}(\mathcal{E}(\mathbf{x}_0) + r\boldsymbol{\theta}')$ or $\mathbf{x} = \mathcal{D}(r\boldsymbol{\theta}')$ directly. Despite remaining on the data manifold by attacking it directly, the approximation of the data manifold is crude, which results in large distortion (Stutz et al., 2019).

Natural victim architectures consist of a deep convolutional neural network for CIFAR-10, and a Resnet50 network for ImageNet. The CIFAR-10 network is the same implementation open-sourced by Cheng et al. (2020), while the Resnet50 network is taken from the PyTorch Torchvision library, including pre-trained weights.[4] For AE attack variants, we implement the same architecture described by Tu et al. (2019). Specifically it leverages a fully convolutional network for the encoder and decoder. ImageNet samples are downsized to 128x128 before passing to the encoder, and the output of the decoder is scaled back to 224x224, as described by Tu et al. (2019). Every AE is trained using the held out test set, as we assume disjoint data between adversary and victim. To avoid ambiguity, we label each BiLN variant with the spatial dimension after performing the bilinear transformation, and keep this variable fixed for simplicity.

A.2 VISUAL RESULTS - CIFAR10

We provide visual qualitative results for each attack on CIFAR-10 in Figure 4.

A.3 SUPPLEMENTAL RESULTS

A.3.1 EXTRA EXPERIMENTS ON ROBUST CIFAR-10

In Figures 5 and 6, we provide results on four extra model regularization methods from the literature: TRADES (Zhang et al., 2019), adversarial interpolation learning (Zhang & Xu, 2020), feature scattering (Zhang & Wang, 2019), and SENSE (Jungeum & Wang, 2020).

	CIFAR-10 ($\epsilon = 0.031$)				+ Madry Adv.Tr. ($\epsilon = 0.031$)			
	# Queries	Avg. L_∞	SR	FID-64	# Queries	Avg. L_∞	SR	FID-64
RayS	4,000	0.01	98.0	0.02	4,000	0.05	33.0	0.36
	8,000	0.01	100.0	0.01	8,000	0.04	36.0	0.28
	14,000	0.01	100.0	0.01	14,000	0.04	39.0	0.23
BiLN+RayS a=2	4,000	0.01	99.0	0.02	4,000	0.05	32.0	0.44
	8,000	0.01	100.0	0.01	8,000	0.05	35.0	0.33
	14,000	0.01	100.0	0.01	14,000	0.04	36.0	0.25
BiLN+RayS b=2	4,000	0.01	100.0	0.02	4,000	0.05	33.0	0.37
	8,000	0.01	100.0	0.01	8,000	0.04	37.0	0.29
	14,000	0.01	100.0	0.01	14,000	0.04	39.0	0.24
BiLN+RayS b=4	4,000	0.01	93.0	0.03	4,000	0.05	32.0	0.44
	8,000	0.01	100.0	0.02	8,000	0.05	35.0	0.33
	14,000	0.01	100.0	0.01	14,000	0.04	38.0	0.25
HSJA	4,000	0.01	88.0	0.06	4,000	0.09	15.0	3.57
	8,000	0.01	100.0	0.02	8,000	0.08	26.0	2.41
	14,000	0.01	100.0	0.01	14,000	0.06	27.0	1.69
BiLN+HSJA 16	4,000	0.02	82.0	0.03	4,000	0.07	25.0	0.68
	8,000	0.01	94.0	0.01	8,000	0.06	31.0	0.47
	14,000	0.01	97.0	0.01	14,000	0.05	32.0	0.37
Sign-OPT	4,000	0.06	52.0	0.70	4,000	0.33	2.0	2.28
	8,000	0.04	71.0	0.89	8,000	0.30	3.0	1.04
	14,000	0.02	79.0	0.00	14,000	0.28	3.0	0.59
BiLN+Sign-OPT 16	4,000	0.09	21.0	0.01	4,000	0.37	2.0	0.08
	8,000	0.06	29.0	0.00	8,000	0.35	3.0	0.04
	14,000	0.06	36.0	0.00	14,000	0.33	3.0	0.04
AE+Sign-OPT	4,000	0.09	20.0	0.01	4,000	0.20	8.0	0.01
	8,000	0.07	31.0	0.00	8,000	0.17	11.0	0.21
	14,000	0.06	35.0	0.00	14,000	0.15	11.0	0.21

Table 1: Comparison at certain query intervals between regular and robust models on CIFAR-10.

---

[4]https://pytorch.org/docs/stable/torchvision/models.html

Figure 4: Visual selection of attack trajectories on CIFAR-10.

Figure 5: Results of distortion for CIFAR10 with four other choices of robust regularization from the literature.

Figure 6: Results of FID score for CIFAR10 with four other choices of robust regularization from the literature.

	Imagenet ($\epsilon = 3.0$)				+ Smoothing ($\sigma = 0.5, \epsilon \simeq 1.0$)			
	# Queries	Avg. L_2	SR	FID-64	# Queries	Avg. L_2	SR	FID-64
RayS	4,000	4.11	47.0	0.22	4,000	12.30	9.6	0.77
	8,000	3.17	60.0	0.14	8,000	12.23	11.5	0.77
	14,000	2.55	69.0	0.09	14,000	12.19	11.5	0.77
BiLN+RayS a=2	4,000	4.55	43.0	0.32	4,000	11.95	7.8	0.61
	8,000	3.54	55.0	0.19	8,000	11.86	9.1	0.61
	14,000	2.77	63.0	0.11	14,000	11.81	9.1	0.61
BiLN+RayS b=2	4,000	4.07	47.0	0.22	4,000	10.27	9.0	0.39
	8,000	3.15	59.0	0.13	8,000	10.20	10.0	0.39
	14,000	2.52	67.0	0.08	14,000	10.14	12.0	0.39
BiLN+RayS b=4	4,000	4.51	44.0	0.24	4,000	9.46	13.4	0.39
	8,000	3.50	53.0	0.16	8,000	9.41	13.4	0.38
	14,000	2.84	63.0	0.10	14,000	9.38	14.6	0.39
HSJA	4,000	6.27	43.0	0.86	4,000	75.75	0.0	132
	8,000	3.08	62.0	0.17	8,000	74.65	0.0	130
	14,000	1.90	82.0	0.04	14,000	72.92	2.1	125
BiLN+HSJA 32	4,000	2.05	78.0	0.01	4,000	15.73	0.0	1.33
	8,000	1.28	92.0	0.00	8,000	13.56	0.0	1.06
	14,000	1.01	98.0	0.00	14,000	11.78	7.1	0.76
Sign-OPT	4,000	28.57	26.0	0.59	4,000	71.69	4.0	147
	8,000	27.04	35.0	0.36	8,000	71.45	4.0	145
	14,000	24.97	43.0	0.91	14,000	71.37	4.0	144
BiLN+Sign-OPT 32	4,000	5.48	44.0	0.12	4,000	23.61	6.0	2.95
	8,000	3.38	74.0	0.02	8,000	23.45	6.0	2.88
	14,000	2.41	81.0	0.01	14,000	23.40	6.0	2.86
AE+Sign-OPT	4,000	34.82	3.0	1.73	4,000	48.97	5.0	10.20
	8,000	28.01	4.0	1.16	8,000	48.89	5.0	9.92
	14,000	23.77	6.0	1.16	14,000	48.89	5.0	9.91

Table 2: Comparison at certain query intervals between regular and robust models on ImageNet.