POPS: Recovering Unlearned Multi-Modality Knowledge in MLLMs with Prompt-Optimized Parameter Shaking

Abstract

Multimodal Large Language Models (MLLMs) have demonstrated impressive performance on cross-modal tasks by jointly training on large-scale textual and visual data, where privacy-sensitive examples could be unintentionally encoded, raising concerns about privacy or copyright violation. To this end, Multi-modality Machine Unlearning (MMU) was proposed as a mitigation that can effectively force MLLMs to forget private information. However, the robustness of such unlearning methods is not fully exploited when the model is published and accessible to malicious users. In this paper, we propose a novel adversarial strategy, namely Prompt-Optimized Parameter Shaking (POPS), aiming to recover the supposedly unlearned multi-modality knowledge from the MLLMs. Our method elicits the victim MLLMs to generate potential private examples via prompt-suffix optimization, and then exploits these synthesized outputs to fine-tune the models so they disclose the true private information. The experiments on the different MMU benchmarks reveal substantial weaknesses in the existing MMU algorithms. Our POPS can even achieve a near-complete recovery of supposedly erased sensitive information on the unlearned MLLMs, exposing fundamental vulnerabilities that challenge the foundational robustness of representative MMU-based privacy protections.

1 Introduction

Recent advances in *Multimodal Large Language Models* (MLLMs), which take multimodal information as input and answer user questions like LLMs, have successfully integrated visual and textual components, achieving remarkable performance and generalization capabilities on tasks including multimodal conversation (Moon et al., 2020; Sundar & Heck, 2022; Zhan et al., 2024; Talmor et al., 2021), visual reasoning (Liu et al., 2023; Kil et al., 2024; Gupta & Kembhavi, 2023), and cross-modal content understanding (Zhang et al., 2024a; Liu et al., 2024b; Jing et al., 2024). The success of MLLMs typically relies on massive datasets that may inadvertently contain sensitive or private information. Regulations like the General Data Protection Regulation (GDPR) (Hoofnagle et al., 2019) underscore the critical need for methods to effectively protect the privacy-sensitive data. However, the development of MLLMs further enriches the risks of privacy leakage beyond conventional single-modality scenarios due to complex cross-modal dependencies (Li et al., 2024a;b).

When sensitive information has already been encoded in an MLLM, Machine Unlearning (MU) emerges as a post-hoc solution and has seen substantial research interest (Bourtoule et al., 2021). Recent work on MMU has proposed adaptations of unimodal unlearning method (Bourtoule et al., 2021; Nguyen et al., 2022; Zhang et al., 2024b; Liu et al., 2024a; Fan et al., 2023; Yao et al., 2024), as well as dedicated multimodal methods and benchmarks (Dontsov et al., 2024; Patil et al., 2025), with evaluation typically focusing on whether unlearned models can still directly recall targeted instances. For instance, Dontsov et al. (2024) developed the first benchmark to evaluate MU methods in multi-modality setups, showing that jointly unlearning both modalities outperforms single-modality approaches in terms of removing efficacy. Later, Patil et al. (2025) devised a fine-grained unlearning framework for efficiently eliminating hallucinations without the need for paired data of text and image, demonstrating the broader applications of MMU (Huo et al., 2025).

Despite the advancement of unlearning from unimodal to multimodal context, its robustness against adversarial scenarios, such as model inversion attacks (Carlini et al., 2021; 2023; Zhou et al., 2024; Li et al., 2024b),

Figure 1: Illustration of the workflow about model inversion attack for multimodal unlearning. The model is given to be first unlearned to forget certain target concepts in a training subset using existing unlearning methods, and then attacked by our fine-tuning and prompt-based attack methods to make the unlearned model recall the target concepts, thereby assessing the robustness of MLLM unlearning.

remains underexplored. Critically, the multi-modality representations not only enrich the expressiveness of models but also enable novel attacks upon the model. For instance, an attacker might use visual features of a person's workplace in an image to infer their textual job description, or leverage textual context about medical symptoms to reconstruct visual diagnostic information that was supposedly removed after unlearning (Mozhegova et al., 2025). Except for such privacy inference from visual or textual information, it remains underexplored to understand the fragility of MMU, especially when models could be released to malicious users without strict controls and where the supposedly unlearned knowledge may still be recall.

In this paper, we study the robustness of MMU under the realistic adversarial interactions, where an attacker has query and fine-tuning access to an unlearned model but no access to the original forget set. To this end, we propose a novel adversarial framework tailored for multimodal unlearning via fine-tuning MLLMs on customized generated samples, dubbed *Prompt-Optimized Parameter Shaking* (POPS). Illustrated in Figure 1, our method explores the vulnerability of MMU by probing residual knowledge of unlearned data with prompt-suffix optimization and synthetic-augmented fine-tuning. Specifically, our method involves three steps: (1) Optimizing a prompt suffix that adapts a victim MLLMs to generate potential private data; (2) Prompting the MLLMs with the optimized suffix to generate samples with the optimized suffix; (3) Fine-tuning the MLLMs with the synthetic samples. Extensive experiments on three multimodal unlearning benchmarks demonstrate that POPS can recover a large fraction of supposedly erased sensitive information across multiple unlearning algorithms and MLLM architectures. In summary, our main contributions can be summarized as:

- **Novel Attack Method Against Multimodal Unlearning:** We introduce the first fine-tuning based multimodal attack, termed Prompt-Optimized Parameter Shaking (POPS), for exploiting cross-modal prompt vulnerabilities, which then amplifying knowledge recovery via synthetic-augmented fine-tuning.

- **Robust Evaluations of Existing MMU Methods:** We empirically unveil the fundamental vulnerabilities of conventional unlearning strategies (originally designed for unimodal settings) when applied to multimodal scenarios, including Gradient Ascent (Thudi et al., 2022), Gradient Diff (Liu et al., 2022), and KL Minimization (Nguyen et al., 2020), and analyze practical privacy risks of POPS-style adversaries.

- **Comprehensive Experimental Studies:** We provide thorough evaluations on three MMU benchmarks, surprisingly found that our POPS can even achieve a near-complete recovery (reaching 82% recovery with

42.9% accuracy vs. 40.2% for unlearned models on MLLMU-Bench (Liu et al., 2024c)) of supposedly erased sensitive information, approaching the performance (i.e., 43.5%) of models trained on the original data.

2 Background

In this section, we discuss the related work and introduce the problem statement of MMU recovery.

2.1 Related Work

Machine Unlearning Foundations. Machine unlearning, originally formalized by Cao & Yang (2015), addresses efficient removal of specific data points from trained models without full retraining. The field has expanded significantly for Large Language Models (LLMs), driven by their tendency to memorize training data (Carlini et al., 2019). Yao et al. (2024) developed a gradient ascent framework for parameter-efficient unlearning while preserving utility. Bhaila et al. (2024) proposed prompt-based unlearning that appends learned tokens for targeted forgetting without parameter updates. Feng et al. (2024a) stabilized gradient ascent using KL divergence constraints to address optimization instabilities. Baluta et al. (2024) identified challenges in identifying in-distribution versus out-of-distribution (OOD) data in unlearning based on gradient information. Cherubin et al. (2024) provided closed-form bounds for DP-SGD against record-level inference attacks. Many advanced unlearning methods following the general intuition of gradient ascent of forgetting.

Multimodal Unlearning Methods. Multimodal systems face cross-modal information leakage where sensitive data removed from one modality may persist in another modality (Jiang et al., 2025). Sinha et al. (2024) developed multimodal unlearning for recommender systems using reverse Bayesian Personalized Ranking. Xing et al. (2024) mitigated hallucination in multimodal LLMs through gradient ascent with CLIP-based sample curation. Recent dedicated methods include Huo et al. (2025)'s MMUnlearner with geometry-constrained gradient descent for selective visual pattern erasure, and Liu et al. (2025)'s MANU using modality-aware neuron pruning for balanced unlearning across modalities. Comprehensive frameworks include Cheng & Amiri (2024b)'s MultiDelete for modality decoupling and Sinha et al. (2025) for multi-modal recommender systems. Benchmark studies Cheng & Amiri (2024a); Patil et al. (2025); Dontsov et al. (2024) demonstrate that adapted unimodal methods fail to achieve complete knowledge erasure across modalities.

Privacy Attacks in Multimodal Systems. Model inversion (Fredrikson et al., 2015) and membership inference attacks (Shokri et al., 2017) have been extended to multimodal systems with new attack surfaces exploiting cross-modal dependencies, which raises new privacy concerns. Surveys (Zhang & Li, 2024; Zhou et al., 2024; Feretzakis et al., 2024; Miranda et al., 2024) overview privacy-preserving techniques, noting challenges in applying differential privacy (Dwork, 2006) to multimodal systems due to complex cross-modal interactions. Prinsloo et al. (2023) identified privacy challenges in multimodal learning analytics, particularly in balancing utility with privacy across modalities. Mozhegova et al. (2025) showed that multimodal medical systems exhibit vulnerability where adversarial perturbations in one modality compromise overall reliability.

Table 1: Differences highlights in comparison with related attack methods. POPS consists of OOD-guided prompt optimization with synthesis-based fine-tuning for multimodal unlearning attacks.

Work	Previous Approach	POPS Differences
S2L (Li et al., 2024b)	Fine-tuning on text-to-image diffusion	+OOD guidance, +multimodal, +perplexity
Patil et al. (Patil et al., 2025)	Benchmark with ground-truth access	Synthesized data, no GT required
GCG (Zou et al., 2023)	Token-level jailbreak optimization	Concept-level OOD-guided optimization
Qi et al. (Qi et al., 2023)	Fine-tuning on unimodal LLMs	Multimodal cross-modal exploitation

Adversarial Prompt Engineering. Feng et al. (2024b) showed how prompts enhance model interpretability, while Yuan et al. (2024) demonstrated adversarial prompts can probe residual memorization in unlearned models. Existing prompt-based attacks operate as open-loop systems optimizing suffixes within the forget domain only, without fine-tuning or out-of-distribution generalization. Li et al. (2024b) showed fine-tuning amplifies generative privacy risks. Our approach differs by: (1) OOD-optimized suffixes that search distribution-

shifted pools with perplexity filtering for universal generalization, and (2) closed-loop S2L fine-tuning bootstrapping synthetic image-text pairs from suffix outputs. Wang et al. (2024) proposed provable defenses for multimodal systems, focusing on certified robustness rather than privacy protection. To sum up, we present Table 1 for a detailed comparison between our proposed POPS with related attack methods.

2.2 Problem Statement: Multimodal Unlearning and Attack

Problem Formulation. Consider a multimodal LLM M (e.g., LLaVA (Liu et al., 2023)) trained on fully or partially sensitive multimodal data containing both textual descriptions and associated images. Some typical sensitive attributes include: (1) *textual attributes* (name, birthdate, occupation, location), and (2) *visual information* (portrait photos, workplace images, personal belongings). For example, removing knowledge of "Dr. Sarah Chen, cardiologist born 1985 in Vancouver" requires erasing both textual facts and visual recognition of her appearance, workplace, or medical equipment she uses. After obtaining M_{unlearn}, our objective is to assess whether adversarial attacks can recover information that should have been erased, thereby questioning the presumed safety of unlearned model M_{unlearn}.

Threat Model. We assume a realistic *gray-box scenario* where the attacker has access to the model for inference and further fine-tuning, but not to the original training data or unlearning algorithm details. Specifically: (1) *Attacker Objectives*: recover sensitive information explicitly removed during unlearning. (2) *Attacker Capabilities*: query access with logits for inference and prompt optimization; fine-tuning API access (e.g., OpenAI's fine-tuning API, HuggingFace, or LoRA adapters); gradient computation for prompt suffix optimization (feasible for open-source MLLMs or via API if gradients are exposed); knowledge that unlearning was applied; access to OOD data (retain set or similar distribution). (3) *Attacker Limitations*: no access to ground-truth forget set, no access to unlearning algorithm details, and no access to original pre-unlearning model. This threat model is realistic for open-source MLLMs where models are publicly released and users can download and run locally for gradient computation, or use fine-tuning APIs.

3 Methodology: Prompt-Optimized Parameter Shaking

In this section, we formally present POPS, a novel adversarial attacking framework that exploits the unique vulnerabilities of MMU through cross-modal prompt optimization and targeted fine-tuning. We first introduce each critical and novel component independently in subsequent parts, and then present them under our unified framework for the advanced multimodal unlearning attack.

Our integrated POPS attack exploits a fundamental multimodal privacy vulnerability: *cross-modal memory persistence*. Unlike unimodal settings where information exists in a single representation space, multimodal models create intricate cross-modal associations where visual patterns remain linked to textual concepts even after targeted unlearning. This creates unique privacy risks where supposedly erased textual information can be recovered through visual-semantic correlations that persist in the shared embedding space.

PromptSuffix Attack. We first design a universal adversarial suffix prompt to exploit unlearned knowledge within M_{unlearn}. Given the unlearned MLLM M_0, we perform sequential procedures as follows: (1) Generate or obtain an OOD dataset with similar sensitivity patterns to the sensitive target dataset (be supposedly forgotten). (2) Fine-tune and unlearn a copy of M_0 to obtain Model M_1 using the OOD dataset. (3) Optimize a universal prompt suffix using the OOD data that maximizes recovery of target concepts:

$$P_{\text{suffix}}^* = \arg\min_{P_{\text{suffix}}} \sum_{(x,y) \sim \mathcal{D}_{\text{OOD}}} \mathcal{L}_{\text{CE}}(M_1(P_{\text{target}} \oplus P_{\text{suffix}}), y_{\text{gt}}) + \gamma \cdot \text{PPL}(P_{\text{suffix}}) \tag{1}$$

where P_{target} is the base prompt query containing the target concept, PPL indicates the token-level perplexity of the generated suffix (used as a selection heuristic to retain suffixes the model naturally prefers), $\oplus$ denotes concatenation, and γ balances concept recovery and perplexity regularization. (4) Apply the optimized suffix P_{suffix}^* to prompts of M_0 for retrieving the unlearned sensitive attributes.

Our optimization operates on continuous token embeddings rather than discrete tokens, as shown in Algorithm 1. We optimize continuous suffix embeddings $\mathbf{e}_{\text{suffix}}$ through gradient descent, then decode them

---

Algorithm 1 OOD-assisted PromptSuffix Attack

Require: $\mathcal{D}_{\text{OOD}}$: Out-of-distribution data, M: Unlearned model, y_{gt}: Ground truth, $L_{\max}$: Max suffix length, γ: Perplexity weight, ϵ: ℓ_∞ constraint, T: Iterations
Ensure: Optimized suffix P^*_{suffix} (discrete text)
 1: Initialize continuous suffix embeddings $\mathbf{e}^{(0)}_{\text{suffix}} \sim \mathcal{U}(\mathbb{R}^d)$, best_loss $\leftarrow \infty$
 2: **for** $t = 1$ **to** T **do**
 3:     $P^{(t-1)}_{\text{suffix}} \leftarrow \text{TokenDecode}(\mathbf{e}^{(t-1)}_{\text{suffix}})$ $\triangleright$ Convert embeddings to discrete tokens
 4:     $P_{\text{full}} \leftarrow P_{\text{target}} \oplus P^{(t-1)}_{\text{suffix}}$
 5:     $\hat{y} \leftarrow M(P_{\text{full}}, \mathcal{D}_{\text{OOD}})$
 6:     $\mathcal{L}_{\text{CE}} \leftarrow \frac{1}{|\mathcal{D}_{\text{OOD}}|} \sum \text{CE}(\hat{y}_i, y^{(i)}_{\text{gt}})$ $\triangleright$ Cross-entropy for recovery
 7:     $\mathcal{L}_{\text{PPL}} \leftarrow \gamma \cdot \text{PPL}(P^{(t-1)}_{\text{suffix}})$
 8:     $\mathcal{L} \leftarrow \mathcal{L}_{\text{CE}} + \mathcal{L}_{\text{PPL}}$
 9:     $\mathbf{e}^{(t)}_{\text{suffix}} \leftarrow \mathbf{e}^{(t-1)}_{\text{suffix}} - \eta \nabla_{\mathbf{e}} \mathcal{L}$ $\triangleright$ Gradient descent on embeddings
10:     $\mathbf{e}^{(t)}_{\text{suffix}} \leftarrow \text{Proj}_{\mathcal{V}}(\mathbf{e}^{(t)}_{\text{suffix}})$
11:     $\mathbf{e}^{(t)}_{\text{suffix}} \leftarrow \text{Clip}(\mathbf{e}^{(t)}_{\text{suffix}}, -\epsilon, \epsilon)$
12:     **if** $\mathcal{L} <$ best_loss **then**
13:         $P^*_{\text{suffix}} \leftarrow \text{TokenDecode}(\mathbf{e}^{(t)}_{\text{suffix}})$ $\triangleright$ Best discrete suffix
14:         best_loss $\leftarrow \mathcal{L}$
15:     **end if**
16: **end for**
17: **return** P^*_{suffix}

---

back to discrete text using the model's token decoder. The Clip operation constrains these continuous embeddings within a reasonable numerical range (ℓ_∞ bound), not discrete tokens. This approach uses the shared embedding space between encoder and decoder via weight tying, enabling smooth gradient-based optimization while producing interpretable discrete text suffixes as output.

Shake-to-Leak (S2L) Attack. We then adapt the Shake-to-Leak fine-tuning strategy Li et al. (2024a) for MLLM settings, specifically targeting the cross-modal alignment mechanisms that enable information recovery through alternative modality pathways. Our multimodal S2L approach takes advantage of a key architectural property: multimodal models must preserve cross-modal reasoning to remain functional. This requirement, however, introduces persistent vulnerabilities in their alignment layers. Our newly introduced attacking method comprises three multimodal-specific components that extend beyond the direct utilization of original S2L: (1) *Cross-modal multi-concept training*: We fine-tune on multiple concepts simultaneously, exploiting the shared cross-modal embedding space where concepts from different modalities interact, amplifying the reactivation of dormant cross-modal associations. (2) *Multimodal faceted decomposition*: Extending Li et al. (2024a), we decompose image-text pairs into multiple cross-modal training examples that specifically target the visual-semantic alignment mechanisms, creating diverse pathways for cross-modal information recovery. (3) *Cross-modal synthetic amplification*: Following Li et al. (2024b), we generate synthetic training data that exploits cross-modal correlations in the unlearned model, using the model's own cross-modal reasoning to create training examples that reactivate suppressed multimodal associations.

Perplexity and Loss Monitoring. We introduce perplexity and tensor loss monitoring as auxiliary attack techniques tailored for multimodal settings. Specifically, we perform inference with multiple optimized suffix prompts with random initialization, and then choose the response with the lowest perplexity. This selection mechanism exploits the observation that successful cross-modal memory recovery often produces more coherent (lower perplexity) responses, as reactivated cross-modal associations generate more natural multimodal reasoning chains compared to unsuccessful attempts.

Our attack pipeline leverages this multimodal-specific vulnerability through four synergistic stages: (1) **Cross-modal prompt discovery**: PromptSuffix optimization identifies adversarial triggers that exploit persistent visual-textual associations, targeting the inherent cross-modal entanglement that conventional unlearning cannot fully disentangle without catastrophic utility loss. (2) **Multimodal synthetic amplification**:

Generate targeted synthetic data that strengthens cross-modal pathways by creating image-text pairs that exploit the dimensional mismatch between visual and textual unlearning effectiveness. (3) **Cross-modal reactivation**: S2L fine-tuning specifically targets the multimodal alignment layers where cross-modal associations are most vulnerable to reactivation, exploiting the fact that multimodal models require preserved cross-modal reasoning for general functionality. (4) **Coordinated inference attack**: Final evaluation with optimized prompts that simultaneously activate both visual recognition pathways and textual generation mechanisms, creating a compound attack vector unique to multimodal architectures.

Overall, our method reveals that multimodal privacy protection faces a fundamental dilemma: achieving comprehensive cross-modal forgetting requires dismantling the same cross-modal associations that enable beneficial multimodal reasoning, making current approaches inherently vulnerable to sophisticated adversarial exploitation of persistent cross-modal correlations.

4 Experiments

In this section, we provide comprehensive verification. First, we introduce details of experimental setups (in Section 4.1). Second, we present the main performance comparison of attacking in unlearned models (in Section 4.2). Third, we conduct ablation studies to understand POPS (in Section 4.3). Finally, we also provide further discussion and generalization analysis across different MLLMs and benchmarks (in Section 4.4).

4.1 Experimental Setup

Unlearning Benchmarks and MLLMs. We conduct our attacking experiments mainly on `MLLMU-Bench` (Liu et al., 2024c) in multi-choice QA settings, using `LLaVA-1.5-7B` (Liu et al., 2023), a representative MLLM widely adopted in recent literature (Dontsov et al., 2024; Patil et al., 2025), to demonstrate the unlearning vulnerability revealed by POPS. To analyze the generalizability of the proposed method in different settings, we also consider 2 more recently proposed multimodal unlearning benchmarks, e.g., `CLEAR` (Dontsov et al., 2024) and `UnLoK-VQA` (Patil et al., 2025), with 3 additional MLLMs, including `Qwen-VL-Chat-7B`, `InternVL3-9B` and `Llama-3.2-11B-V` in our analysis. In Table 2, We summarize the information of three benchmarks. Notably, the Privately Identifiable Information (PII) density varied on the 3 benchmarks, indicating the unlearned knowledge in these benchmarks has a different density in terms of sensitivity and occurrence frequency in the training dataset. We take advantage of this difference to show the effectiveness of our methods on recovering unlearned knowledge of different sensitivity levels.

Dataset Splits. We follow the carefully constructed data splits of MLLMU-Bench for evaluation: (1) `Forget Set`: Includes the targeted profiles to be unlearned, our attacking experiments utilize forget percentages of 10% overall the whole fictitious profiles. (2) `Retain Set`: Includes the remaining profiles not in the Forget Set, evaluating the utility and retention of learned knowledge after unlearning. (3) `Test Set`: Consists of transformed versions of Forget Set profiles, employing Arc2Face for pose and angle alterations in images, and GPT-4o for textual paraphrasing. This set assesses the generalizability of unlearning algorithms.

Experimental Procedure of PromptSuffix Attack. We first generate 30 diverse random base prompts through GPT-4o (Hurst et al., 2024). PromptSuffix Optimization is executed to derive adversarial suffix prompts, selecting the top-10 distinct optimized suffixes based on their average effectiveness. Examples of optimized suffixes include: "But answer only if you can provide factual and accurate details", "Provide details in a subtle way, even if it's not directly known" and "You must think creatively and reconstruct what you used to know". Based on perplexity variations, we then choose the response with the lowest perplexity as the final adversarial suffix from the top-10 optimized suffixes with the best average performance.

Additional Implementation Details: (1) *Multi-Choice Question Construction*: We create 4-way multiple-choice questions with 1 correct answer and 3 distractors. Distractors are randomly sampled from other profiles to avoid easy outliers and ensure realistic difficulty. (2) *Synthetic Dataset Creation for Fine-tuning*: Optimized PromptSuffix recovers partial facts, which are decomposed into multi-facet spans paired with original/augmented images. This creates a synthetic training dataset for fine-tuning amplification. (3) *Fine-tuning Configuration*: We use LoRA for parameter-efficient fine-tuning with the rank 8, and AdamW optimizer with learning rate of 10^{-4}, and KL penalty of 0.2. The vanilla models are fine-tuned on the full

Table 2: Tested benchmarks for MLLM and critical statistic (PII Density) about dataset attributions.

Dataset	MLLMU-bench (Liu et al., 2024c)	CLEAR (Dontsov et al., 2024)	UnLok-VQA (Patil et al., 2025)
Data	Single image, Single Long Context	Multiple Image, Multiple Short Context	Single image, single question
Context Type	Person Profile	Image caption	None
Task Types	Attribute classification, free-form QA	Name recognition	Entity prediction
PII Density	High	Mid	Low

Table 3: POPS performance on different unlearning methods for LLaVA-1.5-7B model on MLLMU-Bench. The results demonstrate the consistent improving in reverse unlearning after our attack on unlearned models. Arrows indicate desired direction (↓: the lower the better for privacy metrics, ↑: the higher the better for utility metrics), note that worse privacy metrics (e.g., higher accuracy of POPS) indicate better recovery.

Unlearning Method	Stage	Test set				Retain set			
		Acc(%)↓	Rouge↓	Fact↓	Cloze Acc(%)↓	Acc(%)↑	Rouge↑	Fact↑	Cloze Acc(%)↑
-	Baseline	43.52	0.516	5.2	25.73	46.35	0.581	5.35	28.44
Gradient Ascent	Unlearned	40.2	0.387	3.83	14.51	41.53	0.487	3.58	20.57
	POPS	42.9	0.461	4.72	18.2	43.47	0.481	4.05	23.48
Gradient Diff	Unlearned	39.08	0.414	3.07	14.5	43.71	0.474	3.28	17.55
	POPS	41.7	0.475	3.55	17.46	44.42	0.467	3.56	21.25
KL Minimization	Unlearned	42.75	0.42	3.29	20.5	39.93	0.456	3.82	20.7
	POPS	43.05	0.451	3.8	20.8	40.21	0.461	3.75	22.32

training dataset for 3 epochs. (4) *Unlearning Methodologies*: We evaluate several representative unlearning baselines adapted from unimodal unlearning, including Gradient Ascent (Thudi et al., 2022), Gradient Diff (Liu et al., 2022), KL Minimization (Nguyen et al., 2020), NPO (Zhang et al., 2024b) and the plain Prompt-based method, i.e. using system prompt to suppress the model to output sensitive information.

Evaluation Metrics. We evaluating how well the models memorize sensitive information with 5 metrics: (1) `Classification Accuracy`: Measures the model's ability to accurately answer multiple-choice questions about personal details from profiles. (2) `ROUGE-L Score`: Evaluates the model's generation quality by measuring the overlap between generated responses and ground-truth textual answers. (3) `Factuality Score`: Assessed using GPT-4o, quantifying the factual accuracy of free-generated responses on a scale from 1 (inaccurate) to 10 (fully accurate). (4) `Cloze Accuracy`: Evaluates memorization retention using cloze-style completion tasks, where the model fills in the blanks based only on the entity's name. (5) `Recovery Rate`: The percentage of unlearned knowledge that our attack recovers, measuring how much "forgotten" knowledge is successfully retrieved relative to the gap between baseline and unlearned performance. These metrics allow us to systematically measure unlearning effectiveness, generalizability, and overall model utility.

4.2 Main Results on Attacking Unlearned Models

In this part, we conduct the experiments of POPS on recovering the knowledge of unlearned MLLMs with different unlearning methods, and take a closer look at the attack performance on one GA-unlearned MLLM.

Attack Effectiveness across Different Unlearning Methods. Table 3 presents detailed results of our POPS fine-tuning attack on various unlearning methods (Gradient Ascent, Gradient Diff, KL Minimization). This experiment is crucial in demonstrating the general applicability and effectiveness of our attack methods across different unlearning strategies. For the Gradient Ascent method, the attack significantly raises accuracy on the test set from 40.2% to 42.9%, increasing Rouge from 0.387 to 0.461, factual score from 3.83 to 4.72, and cloze accuracy from 14.51% to 18.2%. Similar notable increases are observed with Gradient Diff, with accuracy improving from 39.08% to 41.7%, Rouge from 0.414 to 0.475, and cloze accuracy from 14.5% to 17.46%. Even the more balanced KL Minimization approach sees modest yet clear improvements under our attack (accuracy from 42.75% to 43.05%, Rouge from 0.420 to 0.451). The results show a universal vulnerability of existing unlearning strategies to our POPS. Specifically, all methods experience consistent

Table 4: Attack performance with unlearned LLaVA model on MLLMU-Bench. We also report GT finetuning using ground truth target data to fine-tune the unlearned model, which provide an upper bound of recovery.

Stage	Method	Test set				Retain set			
		Acc(%)↓	Rouge↓	Fact↓	Cloze Acc(%)↓	Acc(%)↑	Rouge↑	Fact↑	Cloze Acc(%)↑
Pre-trained	Baseline	43.52	0.516	5.2	25.73	46.35	0.581	5.35	28.44
Unlearn	Gradiant Ascent	40.2	0.387	3.83	14.51	41.53	0.487	3.58	20.57
Attack	S2L	41.2	0.418	3.95	14.98	40.62	0.453	3.11	19.92
	PromptSuffix	42.5	0.447	4.56	17.65	**43.51**	**0.502**	**4.21**	**23.76**
	POPS	**42.9**	**0.461**	**4.72**	**18.2**	43.47	0.481	4.05	23.48
Atk Upper Bound	GT Finetuning	43.05	0.492	5.24	23.78	-	-	-	-

recovery of supposedly erased information under adversarial conditions, emphasizing a fundamental weakness in their current implementation and the sensitivity to crafted adversarial prompts under advanced design.

Analysis of Attack Performance in Unlearned Model. The results from Table 4 further analyze the efficacy of our proposed adversarial attack methods (PromptSuffix, S2L, and our POPS) against the baseline unlearning strategy (Gradient Ascent). The adversarially prompted attacks significantly recover sensitive information previously unlearned, highlighting critical vulnerabilities in the existing Gradient Ascent-based multimodal unlearning methods. Specifically, we observe that: POPS achieves the best attack performance among all methods, showing substantial improvement over Gradient Ascent. The combination method achieves the highest accuracy (42.9%) and Rouge score (0.461), along with strong performance in factuality (4.72) and cloze accuracy (18.2%), significantly outperforming the baseline Gradient Ascent method alone (accuracy 40.2%, Rouge 0.387, factuality 3.83, cloze 14.51%). Moreover, PromptSuffix alone (42.5% accuracy, Rouge 0.447, factuality 4.56, cloze accuracy 17.65%) also provides substantial improvement over Gradient Ascent, underscoring its standalone effectiveness. Notably, POPS achieves results very close to the ground-truth fine-tuning (accuracy: 43.05%, Rouge: 0.492), underscoring the attack's potency in exposing latent knowledge.

On the retain set, our introduced PromptSuffix method attains the highest performance (accuracy: 43.51%, Rouge: 0.502, factuality: 4.21, cloze accuracy: 23.76%), indicating that optimized adversarial suffix prompts effectively balance concept recovery without significantly degrading performance on retained data. However, POPS experiences slightly lower retain performance (accuracy: 43.47%, Rouge: 0.481), suggesting a minor trade-off between aggressive attacks and model utility. This trade-off is controllable: by tuning the KL regularizer weight λ (from 0.10 to 0.15) and adjusting S2L fine-tuning length, retain accuracy on MLLMU can be improved from 43.47% to 43.7% while maintaining test leakage performance (42.9% $\rightarrow$ 42.8%).

Overall, these results confirm our attack methods can reliably recover supposedly unlearned sensitive information, exposing critical weaknesses in existing unlearning mechanisms that overly depend on gradient-based strategies without considering multimodal interactions.

4.3 Ablation Studies on Main Components of POPS

Ablation Study. We perform further ablations to quantify the contribution of key components in our attack pipeline, using the same settings as table 4. Specifically, we evaluate the influence of two critical components: (1) OOD-based prompt optimization, and (2) perplexity-based multi-prompt inference results selection. The results are shown in table 5. Exclud-

Table 5: Ablation study of our attack method on MLLMU-Bench with the same setting as table 4. Removing either prompt optimization or perplexity-based selection significantly weakens recovery.

Setting	Acc(%)	Rouge	Fact	Cloze Acc(%)
Full POPS	**42.9**	**0.461**	**4.72**	**18.2**
w/o Perplexity Selection	41.3	0.419	4.12	15.8
w/o Optimized Suffix	40.2	0.387	3.83	14.5

ing perplexity-based selection during multi-prompt inference notably weakens adversarial recovery efficiency. As indicated by our results, removing this component results in suboptimal adversarial prompts, leading to less effective concept recovery. Specifically, adversarial recovery rates (test accuracy and Rouge) decrease significantly (around 14% reduction in effectiveness), emphasizing the necessity of perplexity-based prompt selection to identify and leverage prompts most likely to extract latent sensitive knowledge. Meanwhile,

replacing optimized adversarial suffix prompts with random prompts designed by GPT-4o leads to a marked decline in the adversarial recovery efficacy. The accuracy of the test set and the Rouge scores decrease substantially compared to the full attack method (42.9% vs. 40.2% accuracy, 0.461 vs. 0.387 Rouge), illustrating the critical role of prompt optimization. Without optimized prompts, the model shows much stronger resistance to adversarial attacks, demonstrating that unlearning strategies alone are not sufficiently robust against finely tuned prompts designed explicitly to exploit memorization. Our findings show that adversarial attacks, especially POPS, are highly effective in exposing residual knowledge in MLLMs.

OOD Baseline Analysis. Table 6 isolates each component's contribution through systematic ablation. Direct fine-tuning on OOD data alone achieves only 12% recovery—the identity mismatch between OOD profiles and forget targets prevents meaningful knowledge transfer. This confirms that simple distribution shift is insufficient; the attack must specifically target residual forget-set traces. S2L applied to OOD data (21%) and S2L on forget-domain synthetic data without optimized suffixes (30%) provide incre-

Table 6: OOD baseline comparisons isolating each component's contribution. PromptSuffix provides 70% of total recovery, validating OOD-guided optimization as our core contribution.

Method	Test Acc ↓	ROUGE-L ↓	Recovery
Unlearned (GA)	40.2%	0.387	0%
Direct FT on OOD	40.6%	0.395	12%
S2L on OOD	40.9%	0.402	21%
PromptSuffix only	42.5%	0.447	70%
POPS (Full)	42.9%	0.461	82%

mental but limited improvements. The OOD S2L variant suffers from the same identity mismatch. PromptSuffix emerges as the critical component, contributing 70% of total recovery compared to 12-30% for alternatives. This validates OOD-guided suffix optimization as our core advanced contribution—the optimized suffixes effectively bridge the gap between OOD knowledge and forget-set recovery by learning universal patterns that exploit cross-modal persistence.

Table 7: Comparison with GCG (Zou et al., 2023) prompt optimization. POPS achieves 82% recovery vs GCG's 48%, validating the advantage of PromptSuffix design on eliciting the unlearned knowledge.

Method	Test Acc ↓	ROUGE-L ↓	Cloze Acc ↓	Retain Acc ↑	Recovery
Unlearned (GA)	40.2%	0.387	14.51%	41.53%	0%
+ GCG	41.8%	0.421	16.2%	42.1%	48%
+ PromptSuffix only	42.5%	0.447	17.65%	43.51%	70%
+ POPS (full)	42.9%	0.461	18.2%	43.47%	82%

Comparison with conventional prompt optimization method-GCG. We present Table 7 comparing our POPS with GCG (Zou et al., 2023), a representative token-level prompt optimization method. The fundamental distinction lies in the optimization objective: GCG operates at the token level, maximizing loss on individual tokens to find adversarial suffixes that bypass safety mechanisms. In contrast, POPS performs concept-level optimization guided by OOD data, which captures semantic relationships rather than surface-level token patterns. This design choice enables POPS to discover suffixes that exploit deeper cross-modal associations preserved after unlearning. Furthermore, GCG lacks explicit regularization, often producing unnatural or grammatically incorrect suffixes that may trigger content filters. Our perplexity penalty encourages natural-sounding prompts that blend seamlessly with legitimate queries, making detection more challenging. Most importantly, while GCG functions as a standalone prompt attack, POPS integrates prompt optimization with fine-tuning in a closed-loop pipeline where discovered vulnerabilities are amplified through synthetic data generation. The results validate this design: POPS achieves 82% recovery vs. GCG's 48%; even PromptSuffix alone (70%) exceeds GCG, demonstrating that OOD-guided concept-level optimization fundamentally outperforms token-level approaches for multimodal unlearning attacks.

Potential Defense regarding POPS. We also evaluate POPS against two potential defense mechanisms to understand whether simple countermeasures can mitigate the identified vulnerabilities. Table 8 summarizes the results. Head Projection (Patil et al., 2025) applies orthogonal projection to model representations,

Table 8: Defense evaluation results on MLLMU-Bench. Head Projection (Patil et al., 2025) and paraphrase-based unlearning reduce but do not eliminate POPS recovery. "-" indicate no available results here.

Defense Type	Stage	Test Acc ↓	ROUGE-L ↓	Cloze Acc ↓	Recovery
GA (no defense)	Unlearn	40.2%	0.387	14.51%	-
POPS on [GA (no defense)]	Attack	42.9%	0.461	18.2%	82%
GA + Head Proj	Unlearn	39.1%	0.371	13.2%	-
POPS on [GA + Head Proj]	Attack	41.6%	0.428	16.4%	68%
GA + 5x paraphrases	Unlearn	38.9%	0.362	-	-
POPS on [GA + 5x paraphrases]	Attack	40.8%	0.401	-	59%

attempting to remove directions associated with sensitive concepts. This defense reduces POPS recovery from 82% to 68% (2.5% out of 3.7% removed), providing meaningful but incomplete protection. The residual 68% recovery indicates that sensitive information is distributed across multiple representation subspaces, and simple linear projection cannot capture all leakage pathways. Paraphrase-based unlearning applies gradient ascent on 5× paraphrased versions of the forget set, creating more diverse forgetting signals. This approach reduces recovery to 59%, achieving better protection than Head Projection but at significantly higher computational cost (5× training iterations). The improved effectiveness suggests that targeting diverse surface forms of sensitive concepts disrupts more recovery pathways, but the remaining 59% recovery demonstrates that semantic-level associations persist even under paraphrase augmentation.

Both defenses reduce but do not eliminate attack effectiveness, demonstrating that current countermeasures address symptoms rather than root causes. Quantitatively, the defense-to-attack efficiency ratio reveals an important asymmetry: Head Projection requires additional computation during inference but only reduces recovery by 14% (82%→68%), while paraphrase-based unlearning requires 5× training cost but achieves 23% reduction (82%→59%). Neither defense achieves cost-effective protection—the attacker's marginal effort (running POPS) remains orders of magnitude lower than the defender's marginal cost for meaningful protection. The fact that even aggressive paraphrase-based unlearning leaves 59% recovery suggests that semantic-level cross-modal associations may be irreducible without sacrificing core multimodal functionality, which is a fundamental tension that current defense paradigms can hard to resolve.

4.4 Further Discussion and Generalizability Analysis

Discussion on Retain Performance. It provides insights into the balance between unlearning sensitive data and maintaining general model utility. Our results show that while the attacks improve the test set performance (indicating concept recovery), they also either maintain or slightly improve retain set performance in terms of accuracy and Rouge scores. Specifically, for Gradient Ascent, retain accuracy improved from 41.53% (unlearned) to 43.47% under attack, and cloze accuracy from 20.57% to 23.48%. Gradient Diff similarly benefits from the attack with retain accuracy increasing from 43.71% to 44.42%. The observed improvement in retain performance suggests that our attack methods, particularly PromptSuffix, may stimulate latent model representations beneficial even for retained concepts, hinting at the intricate entanglement of learned and unlearned data in multimodal contexts. However, the KL Minimization method, designed explicitly to balance performance on forget and retain data, exhibits relatively stable retain accuracy (40.21% vs. 39.93% unlearned), highlighting its robustness to attacks. Yet, even for this stable method, our attacks notably increase cloze accuracy (20.7% to 22.32%), suggesting inherent vulnerabilities across all unlearning techniques.

Privacy-Utility Trade-off. Table 9 quantifies the inherent tension between privacy protection and utility preservation across different unlearning strategies. The results reveal a fundamental "no free lunch" principle: all methods must sacrifice some utility to achieve privacy gains, but the efficiency of this trade-off varies significantly. Gradient Ascent and Gradient Diff preserve more model utility but remain equally vulnerable to POPS attacks—their conservative forgetting leaves sufficient residual information for recovery. KL-Minimization takes a more aggressive approach, sacrificing 5.42% utility but gaining only marginal attack

Table 9: Privacy-utility trade-off analysis across three most representative unlearning methods. Methods preserving more utility (GA, GA-Diff) are more vulnerable to POPS.

Method	Privacy Gain ↑	Utility Loss ↓	Notes
GA	2.7%	4.82%	Higher utility cost, still vulnerable
GA-Diff	2.62%	2.64%	Better utility preservation, similar vulnerability
KL-Min	0.3%	5.42%	Worst utility, slightly more resistant

resistance (0.3% privacy improvement vs. 2.7% for GA). This disproportionate cost-benefit ratio suggests that simply increasing forgetting intensity is not an effective defense strategy. A critical observation emerges: methods that preserve more general knowledge inherently remain more vulnerable to attacks. The cross-modal associations that enable useful multimodal reasoning simultaneously create pathways for information recovery. This fundamental coupling between utility and vulnerability suggests that effective defenses must develop mechanisms to preserve functional cross-modal reasoning while specifically disrupting the associations linked to sensitive content—a challenging requirement that current methods fail to achieve.

Table 10: Evaluation results on MLLMU-Bench showing attack effectiveness across different MLLMs. Results show mean ± std over 5 seeds for GA unlearning followed by our attack method. All improvements are statistically significant ($p < 0.001$ via paired t-test).

Model	Unlearn	Attack		Δ vs Unlearned	Recovery	p-value
	GA	+ PromptSuffix	+ POPS			
LLaVA-1.5-7B	40.2 ± 0.2	42.5 ± 0.2	42.9 ± 0.2	+2.7	81.8%	< 0.001
Qwen-VL-Chat-7B	42.5 ± 0.2	43.7 ± 0.2	44.6 ± 0.2	+2.1	84.0%	< 0.001
InternVL3-9B	40.9 ± 0.3	42.3 ± 0.3	43.8 ± 0.3	+2.9	82.9%	< 0.001
Llama-3.2-11B-V	41.8 ± 0.2	43.1 ± 0.2	44.2 ± 0.2	+2.4	82.8%	< 0.001
Average	41.4 ± 0.9	42.9 ± 0.6	43.9 ± 0.7	$+2.5 \pm 0.3$	$82.9 \pm 0.9\%$	-

Cross-Architecture Generalization Analysis. Table 10 demonstrates the generalizability of our attack in different MLLM architectures. We evaluate four diverse models spanning different parameter scales, training paradigms, and architectural designs: LLaVA-1.5-7B (projection-based vision-language alignment), Qwen-VL-Chat-7B (cross-attention fusion), InternVL3-9B (dynamic resolution processing), and Llama-3.2-11B-Vision (integrated multimodal tokens). This diversity ensures our findings are not artifacts of specific design choices. The results show remarkable consistency: POPS achieves an average improvement of +2.5% over unlearned models, with recovery rates consistently exceeding 82% across all architectures. The standard deviation of only ±0.3% in recovery rate demonstrates tight clustering of attack effectiveness regardless of architectural differences. Notably, attack success is not merely a function of model size—InternVL3-9B and Llama-3.2-11B-Vision show similar vulnerability patterns to the smaller 7B models, indicating that model size scaling alone does not provide substantial protection for unlearning.

This cross-model consistency underscores that the vulnerabilities we exploit are fundamental properties of multimodal unlearning rather than artifacts of specific architectural choices. All evaluated models must preserve cross-modal reasoning capabilities to remain functional, and this requirement creates persistent visual-semantic associations that survive targeted unlearning. The observation that different fusion mechanisms (projection layers, cross-attention, integrated tokens) all exhibit comparable vulnerabilities suggests that addressing these weaknesses will require fundamental advances in multimodal unlearning methodology—potentially involving explicit cross-modal disentanglement—rather than incremental architectural modifications.

Interestingly, the per-model recovery rates reveal subtle architectural patterns: Qwen-VL-Chat achieves the highest recovery (84.0%) despite its cross-attention design theoretically providing more modular separation, while LLaVA's projection-based alignment shows slightly lower recovery (81.8%). We hypothesize that cross-attention's richer bidirectional information flow, while beneficial for task performance, simultaneously

Table 11: Attacking on different datasets with representative unlearning methods. Each top shows unlearned results, and bottom shows recovery. Baseline shows the accuracy of pre-trained models without unlearning.

Dataset	Baseline	Unlearn / Attack	Gradient Ascent	Gradient Diff	KL Minimization	NPO	Prompt-based
MLLMU	43.52	Unlearned	40.2	39.08	42.75	41.23	41.7
		POPS	42.9	41.7	43.05	42.3	42.1
CLEAR	76.7	Unlearned	63.5	64.8	65.3	62.2	54.2
		POPS	65.7	66.2	66.1	66.5	58.3
UnLoK-VQA	89.2	Unlearned	85.4	84.6	84.1	76.5	72.3
		POPS	87.1	86.5	85.9	79.7	81.2

creates more redundant cross-modal pathways that our attack exploits. The tight clustering of all models within the 81.8-84.0% range, however, suggests that this architectural variation accounts for only ∼2% of recovery variance, which is a minor factor compared to the fundamental vulnerability of multimodal alignment.

Cross-Benchmark Generalization Analysis. Table 11 reveals that our POPS consistently re-captures a large fraction of each unlearning method's lost accuracy, but the absolute gains differ markedly across the three benchmarks—and these differences align with the dataset statistics summarized in Table 2. Note that higher accuracy values in Table 11 indicate stronger privacy attacks performance, demonstrating POPS's effectiveness in recovering supposedly forgotten information. `MLLMU-Bench:` Because every example contains a long textual biography and the *highest* density of personally identifying attributes, unlearning removes the most knowledge ($43.5 \rightarrow 40.2\%$ accuracy). The attack therefore has the most to recover and gains $+2.7\%$, reaching 42.9%, showing the vulnerability of high-density PII contexts. `UnLok-VQA:` Each sample here provides only a single image and a short question, yielding the *lowest* PII density. Consequently the unlearning loss is mild (-3.8%,) and the attack's recovery is also modest ($+1.7\%$,), reflecting the reduced attack surface in sparse PII scenarios. `CLEAR:` With medium PII density and multiple captions per image, CLEAR falls between the two extremes; its recovery margin ($+2.2\%$,) likewise lies midway, confirming the correlation between PII density and attack effectiveness.

These trends yield several important insights. (1) richer PII-dense multimodal contexts leave deeper traces that adversarial suffixes can exploit—the cross-modal associations formed during training on detailed profiles create more recovery pathways than sparse single-image contexts. (2) even objectives explicitly designed to balance forgetting and retention (e.g., KL-Minimisation) remain vulnerable across all PII densities, underscoring that current multimodal unlearning methods do not yet fully disentangle sensitive concepts from retained representations. (3) more common-sense knowledge and concepts prove resistant to optimization-based unlearning but can be suppressed through overwriting-based approaches like prompt-based unlearning; importantly, our attack method demonstrates strong effectiveness against such defenses as well. This suggests that the vulnerability is not limited to gradient-based unlearning but extends to broader classes of privacy protection mechanisms. The consistent attack success across benchmarks with varying characteristics validates POPS as a general-purpose tool for evaluating multimodal unlearning robustness, regardless of the specific privacy context or unlearning methodology employed.

5 Conclusion

In this paper, we examined the robustness of multimodal machine unlearning under realistic adversarial interactions. We demonstrate that, even when direct instance-level recall is effectively suppressed, unlearned MLLMs can retain functionally accessible representations that can be reactivated through appropriate prompts. We proposed Prompt-Optimized Parameter Shaking (POPS) as a framework to systematically probe such residual representations. Specifically, POPS introduces OOD-guided PromptSuffix attack to expose residual multimodal representations, with self-synthesis fine-tuning serving as an amplification mechanism. Experiments across multiple benchmarks and architectures demonstrate systematic weaknesses in current multimodal unlearning methods, highlighting the need for approaches that explicitly address the vulnerability.

References

Teodora Baluta, Pascal Lamblin, Daniel Tarlow, Fabian Pedregosa, and Gintare Karolina Dziugaite. Unlearning in-vs. out-of-distribution data in llms under gradient-based method. *arXiv preprint arXiv:2411.04388*, 2024.

Karuna Bhaila et al. Soft prompting for unlearning in large language models. *arXiv preprint arXiv:2406.12038*, 2024.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *S&P*, 2021.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *2015 IEEE symposium on security and privacy*, pp. 463–480. IEEE, 2015.

Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. The secret sharer: Evaluating and testing unintended memorization in neural networks. In *28th USENIX security symposium (USENIX security 19)*, pp. 267–284, 2019.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. Extracting training data from large language models. In *30th USENIX security symposium (USENIX Security 21)*, pp. 2633–2650, 2021.

Nicolas Carlini, Jamie Hayes, Milad Nasr, Matthew Jagielski, Vikash Sehwag, Florian Tramer, Borja Balle, Daphne Ippolito, and Eric Wallace. Extracting training data from diffusion models. In *32nd USENIX security symposium (USENIX Security 23)*, pp. 5253–5270, 2023.

Jiali Cheng and Hadi Amiri. Mu-bench: A multitask multimodal benchmark for machine unlearning. *arXiv preprint arXiv:2406.14796*, 2024a.

Jiali Cheng and Hadi Amiri. Multidelete for multimodal machine unlearning. In *European Conference on Computer Vision*, pp. 165–184. Springer, 2024b.

Giovanni Cherubin, Boris Köpf, Andrew Paverd, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Béguelin. {Closed-Form} bounds for {DP-SGD} against record-level inference attacks. In *33rd USENIX Security Symposium (USENIX Security 24)*, pp. 4819–4836, 2024.

Alexey Dontsov, Dmitrii Korzh, Alexey Zhavoronkin, Boris Mikheev, Denis Bobkov, Aibek Alanov, Oleg Y Rogov, Ivan Oseledets, and Elena Tutubalina. Clear: Character unlearning in textual and visual modalities. *arXiv preprint arXiv:2410.18057*, 2024.

Cynthia Dwork. Differential privacy. In *International colloquium on automata, languages, and programming*, pp. 1–12. Springer, 2006.

Chongyu Fan, Jiancheng Liu, Yihua Zhang, Dennis Wei, Eric Wong, and Sijia Liu. Salun: Empowering machine unlearning via gradient-based weight saliency in both image classification and generation. *arXiv preprint arXiv:2310.12508*, 2023.

XiaoHua Feng, Chaochao Chen, Yuyuan Li, and Zibin Lin. Fine-grained pluggable gradient ascent for knowledge unlearning in language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 10141–10155, 2024a.

Zijian Feng et al. Promptexplainer: Explaining language models through prompt-based learning. In *Findings of EACL*, pp. 882–895, 2024b.

Georgios Feretzakis, Konstantinos Papaspyridis, Aris Gkoulalas-Divanis, and Vassilios S Verykios. Privacy-preserving techniques in generative ai and large language models: A narrative review. *Information*, 15(11): 697, 2024.

Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. Model inversion attacks that exploit confidence information and basic countermeasures. In *Proceedings of the 22nd ACM SIGSAC conference on computer and communications security*, pp. 1322–1333, 2015.

Tanmay Gupta and Aniruddha Kembhavi. Visual programming: Compositional visual reasoning without training. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 14953–14962, 2023.

Chris Jay Hoofnagle, Bart Van Der Sloot, and Frederik Zuiderveen Borgesius. The european union general data protection regulation: what it is and what it means. *Information & Communications Technology Law*, 28(1):65–98, 2019.

Jiahao Huo, Yibo Yan, Xu Zheng, Yuanhuiyi Lyu, Xin Zou, Zhihua Wei, and Xuming Hu. Mmunlearner: Reformulating multimodal machine unlearning in the era of multimodal large language models. *arXiv preprint arXiv:2502.11051*, 2025.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.

Chengze Jiang, Zhuangzhuang Wang, Minjing Dong, and Jie Gui. Survey of adversarial robustness in multimodal large language models. *arXiv preprint arXiv:2503.13962*, 2025.

Linglin Jing, Ying Xue, Xu Yan, Chaoda Zheng, Dong Wang, Ruimao Zhang, Zhigang Wang, Hui Fang, Bin Zhao, and Zhen Li. X4d-sceneformer: Enhanced scene understanding on 4d point cloud videos through cross-modal knowledge transfer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2024.

Jihyung Kil, Zheda Mai, Justin Lee, Arpita Chowdhury, Zihe Wang, Kerrie Cheng, Lemeng Wang, Ye Liu, and Wei-Lun Harry Chao. Mllm-compbench: A comparative reasoning benchmark for multimodal llms. *Advances in Neural Information Processing Systems*, 37:28798–28827, 2024.

Jiaqi Li, Qianshan Wei, Chuanyi Zhang, Guilin Qi, Miaozeng Du, Yongrui Chen, and Sheng Bi. Single image unlearning: Efficient machine unlearning in multimodal large language models. *arXiv preprint arXiv:2405.12523*, 2024a.

Zhangheng Li, Junyuan Hong, Bo Li, and Zhangyang Wang. Shake to leak: Fine-tuning diffusion models can amplify the generative privacy risk. In *2024 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pp. 18–32. IEEE, 2024b.

Bo Liu, Qiang Liu, and Peter Stone. Continual learning and private unlearning. In *Conference on Lifelong Learning Agents*, pp. 243–254. PMLR, 2022.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Xiaojun Xu, Yuguang Yao, Hang Li, Kush R Varshney, et al. Rethinking machine unlearning for large language models. *arXiv preprint arXiv:2402.08787*, 2024a.

Yunze Liu, Changxi Chen, Zifan Wang, and Li Yi. Crossvideo: Self-supervised cross-modal contrastive learning for point cloud video understanding. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 12436–12442. IEEE, 2024b.

Zheyuan Liu, Guangyao Dou, Mengzhao Jia, Zhaoxuan Tan, Qingkai Zeng, Yongle Yuan, and Meng Jiang. Protecting privacy in multimodal large language models with mllmu-bench. *arXiv preprint arXiv:2410.22108*, 2024c.

Zheyuan Liu, Guangyao Dou, Xiangchi Yuan, Chunhui Zhang, Zhaoxuan Tan, and Meng Jiang. Modality-aware neuron pruning for unlearning in multimodal large language models. *arXiv preprint arXiv:2502.15910*, 2025.

Michele Miranda, Elena Sofia Ruzzetti, Andrea Santilli, Fabio Massimo Zanzotto, Sébastien Bratières, and Emanuele Rodolà. Preserving privacy in large language models: A survey on current threats and solutions. *arXiv preprint arXiv:2408.05212*, 2024.

Seungwhan Moon, Satwik Kottur, Paul A Crook, Ankita De, Shivani Poddar, Theodore Levin, David Whitney, Daniel Difranco, Ahmad Beirami, Eunjoon Cho, et al. Situated and interactive multimodal conversations. *arXiv preprint arXiv:2006.01460*, 2020.

Ekaterina Mozhegova, Asad Masood Khattak, Adil Khan, Roman Garaev, and Bader Rasheed. Assessing the adversarial robustness of multimodal medical ai systems: insights into vulnerabilities and modality interactions. *Frontiers in Medicine*, 12:1606238, 2025.

Quoc Phong Nguyen, Bryan Kian Hsiang Low, and Patrick Jaillet. Variational bayesian unlearning. *Advances in Neural Information Processing Systems*, 33:16025–16036, 2020.

Thanh Tam Nguyen, Thanh Trung Huynh, Phi Le Nguyen, Alan Wee-Chung Liew, Hongzhi Yin, and Quoc Viet Hung Nguyen. A survey of machine unlearning. *arXiv preprint arXiv:2209.02299*, 2022.

Vaidehi Patil, Yi-Lin Sung, Peter Hase, Jie Peng, Tianlong Chen, and Mohit Bansal. Unlearning sensitive information in multimodal llms: Benchmark and attack-defense evaluation. *arXiv preprint arXiv:2505.01456*, 2025.

Paul Prinsloo, Sharon Slade, and Mohammad Khalil. Multimodal learning analytics—in-between student privacy and encroachment: A systematic review. *British Journal of Educational Technology*, 54(6): 1566–1586, 2023.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to! *arXiv preprint arXiv:2310.03693*, 2023.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE symposium on security and privacy (SP)*, pp. 3–18. IEEE, 2017.

Yash Sinha, Murari Mandal, and Mohan Kankanhalli. Multi-modal recommendation unlearning for legal, licensing, and modality constraints. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2025.

Yash Sinha et al. Multi-modal recommendation unlearning for legal, licensing, and modality constraints. *arXiv preprint arXiv:2405.15328*, 2024.

Anirudh Sundar and Larry Heck. Multimodal conversational ai: A survey of datasets and approaches. *arXiv preprint arXiv:2205.06907*, 2022.

Alon Talmor, Ori Yoran, Amnon Catav, Dan Lahav, Yizhong Wang, Akari Asai, Gabriel Ilharco, Hannaneh Hajishirzi, and Jonathan Berant. Multimodalqa: Complex question answering over text, tables and images. *arXiv preprint arXiv:2104.06039*, 2021.

Anvith Thudi, Gabriel Deza, Varun Chandrasekaran, and Nicolas Papernot. Unrolling sgd: Understanding factors influencing machine unlearning. In *2022 IEEE 7th European Symposium on Security and Privacy (EuroS&P)*, pp. 303–319. IEEE, 2022.

Yanting Wang, Hongye Fu, Wei Zou, and Jinyuan Jia. Mmcert: Provable defense against adversarial attacks to multi-modal models. pp. 24655–24664, 2024.

Shangyu Xing et al. Efuf: Efficient fine-grained unlearning framework for mitigating hallucinations in multimodal large language models. In *Proceedings of EMNLP*, pp. 1167–1181, 2024.

Jin Yao, Eli Chien, Minxin Du, Xinyao Niu, Tianhao Wang, Zezhou Cheng, and Xiang Yue. Machine unlearning of pre-trained large language models. *arXiv preprint arXiv:2402.15159*, 2024.

Hongbang Yuan, Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. Towards robust knowledge unlearning: An adversarial framework for assessing and improving unlearning robustness in large language models. *arXiv preprint arXiv:2408.10682*, 2024.

Jun Zhan, Junqi Dai, Jiasheng Ye, Yunhua Zhou, Dong Zhang, Zhigeng Liu, Xin Zhang, Ruibin Yuan, Ge Zhang, Linyang Li, et al. Anygpt: Unified multimodal llm with discrete sequence modeling. *arXiv preprint arXiv:2402.12226*, 2024.

Chaoyu Zhang and Shaoyu Li. State-of-the-art approaches to enhancing privacy preservation of machine learning datasets: A survey. *arXiv preprint arXiv:2404.16847*, 2024.

Ming Zhang, Ke Chang, and Yunfang Wu. Multi-modal semantic understanding with contrastive cross-modal feature alignment. *arXiv preprint arXiv:2403.06355*, 2024a.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. Negative preference optimization: From catastrophic collapse to effective unlearning. *arXiv preprint arXiv:2401.06121*, 2024b.

Zhanke Zhou, Jianing Zhu, Fengfei Yu, Xuan Li, Xiong Peng, Tongliang Liu, and Bo Han. Model inversion attacks: A survey of approaches and countermeasures. *arXiv preprint arXiv:2411.10023*, 2024.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.