# V-MAO: Generative Modeling for Multi-Arm Manipulation of Articulated Objects

**Abstract:** Manipulating articulated objects requires multiple robot arms in general. It is challenging to enable multiple robot arms to c collaboratively complete manipulation tasks on articulated objects. In this paper, we present V-MAO, a framework for learning multi-arm manipulation of articulated objects. Our framework includes a variational generative model that learns contact point distribution over object rigid parts for each robot arm. The training signal is obtained from interaction with the simulation environment which is enabled by planning and object-centric control. We deploy our framework in a customized MuJoCo simulation environment and demonstrate that our framework achieves a high success rate on six different objects and two different robots. We also show that generative modeling can effectively learn the contact point distribution on articulated objects.

**Keywords:** Articulated object, generative model, variational inference

## 1 Introduction

In robotics, one of the core research problems is how to endow robots with the ability to manipulate objects of various geometry and kinematics. Compared to rigid objects, articulated objects contain multiple rigid parts that are kinematically linked via mechanical joints. Because of the rich functionality due to joint kinematics, articulated objects are used in many applications. Examples include opening doors, picking up objects with pliers, and cutting with scissors, etc.

While the manipulation of a known rigid object has been well studied in the literature, the manipulation of articulated objects still remains a challenging problem. Suppose an articulated object has $N$ rigid parts. In the most general case, it requires $N$ robot grippers to manipulate the $N$ object parts where each gripper grasps one rigid part to fully control all configurations of the articulated object, including position and joint angles [1]. How to teach the robot arms to collaborate safely without collision is still a research problem [1, 2]. Our intuition is that, instead of a deterministic model, sampling from a distribution of grasping actions can provide more options and can increase the chance of finding feasible collaborative manipulation after motion planning. Therefore, the generative modeling of grasping can be a solution to the problem.

We hypothesize that an object-centric representation of contact point distribution contains full information about possible grasps and can generalize better across different objects. Therefore it is preferred over robot-centric representation such as low-level torque actions, due to the uncertainly of robot configurations. Specifically for articulated objects, we further hypothesize that the grasping distribution on one rigid part is conditioned on the geometric and kinematics feature as well as grasping actions on other parts, and can be learned from interacting with the environment.

In this paper, we propose a framework name V-MAO for learning manipulation of articulated objects with multiple robot arms based on an object-centric latent generative model for learning grasping

---

[1]Though in certain scenarios, it is still possible that an articulated object be manipulated by a single gripper, e.g. dexterous manipulation of a pair of scissors with one human hand, such manipulation is extremely complex and is not scalable for other arbitrary articulated objects.

*RGBD Observation*     *Samples of Generated Contact Point Probability Map*    *Grasp & Manipuation*

Figure 1: **Generative Modeling of Multi-Arm Manipulation of Articulated Objects.** Given the RGBD scan observation of the articulated object and the scene, we use a generative model to learn the distribution of feasible contacts of each robot arm. The generative model for the second robot arm (second row) is conditioned on the action performed by the first robot arm (first row).

distribution. The latent generative model is formulated as a conditional variational encoder (CVAE), where the distribution of contact point map on 3D point clouds are modeled by variational inference and the distribution is conditioned on 3D geometric and kinematics features. To obtain enough data for training, our framework enables automatic collection of training signals using the exploration of contact points and interaction with the environment. To enable interaction, we propose an object-centric controller formulation to move the articulated parts to desire poses after successful grasp. The framework is illustrated in Figure 1.

We demonstrate our V-MAO framework in a simulation environment constructed with MuJoCo physics engine [3]. To increase variations in object geometry and robot gripper configuration, we evaluate on six articulated objects from PartNet dataset [4] which are manipulated by two different robots. V-MAO achieves over 80% success rate with Sawyer robot and over 70% success rate with Panda robot. Experiment results also show that the proposed variational generative model can effectively learn the distribution of successful contacts. The proposed model also shows advantage over the deterministic model baseline in terms of success rate and the ability to deal with huge variations of environments.

The contributions of this work are three-fold:

1. A latent generative model for learning manipulation contact. The model extracts articulated object geometric and kinematic representations based on 3D features and instantaneous motion due to articulated joint. The model is implemented based on a conditional variational model.

2. A mechanism for automatic contact label generation from robot interaction with the environment. We also propose an object-centric controller formulation for articulated objects that enables the interaction by the controllable moving of articulated object parts.

3. We construct a customized MuJoCo simulation environment and demonstrate our framework on six articulated objects from PartNet and two different robots. The proposed model shows advantage over deterministic model baseline in terms of success rate and dealing with environment variations.

## 2  Related Works

**Generative Modeling of Robotic Manipulation.** Previous work has proposed to leverage latent generative models such as variational auto-encoder (VAE) [5] and generative adversarial network (GAN) [6] in various aspects of robotic manipulation. Wang et al. [7] proposed to use Causal Info-GAN [8] to learn to generate goal-directed object manipulation plan directly from raw images. Morrison et al. [9] proposed a generative convolutional neural net (CNN) for synthesizing grasp from depth images. Other works has proposed to use generative model to learn more complex grasping tasks such as multi-finger grasping [10] and dexterous grasping [11, 12]. Generative modeling can also be seen in other aspects of robotic manipulation such as for object pose estimation [13] and robot gripper design [14]. Our approach focuses on using variational latent generative model on 3D point clouds for learning object contact point distributions on articulated objects.

Figure 2: **Architecture of V-MAO Framework.** Given the scene point cloud Each step of the manipulation is modeled by a conditional VAE. Interaction with the object is done through inverse kinematics and object-centric control. Given the manipulation of one object part with a robot is successful, V-MAO will move to the manipulation of the next object part with the next robot.

**Articulated Object Manipulation.** The task of manipulating articulated object has been studied on both perception and action perspective in the literature. Katz et al. [15] proposed a relational state representation of of object articulation for learning manipulation skill. For example, from interactive perception, Katz et al. [16] learns kinematic model of an unknown articulated object through interactive perception. Kumar et al. [17] propose to estimate mass distribution of an articulated objects through manipulation. Narayanan et al. [18] introduced kinematic graph representation and an efficient planning algorithm for object articulation manipulation. More recently, Mittal et al. [19] constructed a mobile manipulation platform that integrates articulation perception and planning. Our work models contact point distributions from object geometric using a generative model and propose a object-centric control formulation for manipulating articulated object.

**Multi-Arm in Robotic Manipulation.** Using multiple robot arms in manipulation tasks without collision is a challenging problem. Previous works have investigated using decentralized motion planner to avoid collision in multi-arm robot system [1]. Previous works have also investigated using multiple robots in the application of construction assembly [2], pick-and-place [20], and table-top rearrangement [21]. Our work is an application of using multiple robot arms to manipulate articulated objects where we focus on the learning the contact point distribution on object parts.

## 3   Method

Our V-MAO framework consists of: 1) a variational generative model for learning contact distribution on each object rigd part (section 3.2); and 2) inverse kinematics, planning, and control algorithms for interacting with the articulated object. In section 3.1, we first formally define the problem of using the generative model for articulated object manipulation. In this section 3.4, we provide additional details to our framework. The framework is illustrated in Figure 2.

## 3.1 Problem Definition

We consider the problem of multi-arm manipulation of articulated objects. The object has $N$ rigid parts and the system contains $N$ robot arms where $N \geq 2$. Robot arm $i$ executes high-level grasping action $g_i$ and moving actions $a_i$ on the objects. Grasping action $g_i$ is represented by the contact points on object part $i$. Moving actions $a_i$ send torque signals to robot $i$ to move object part $i$ to desired 6D pose $\mathcal{T}_i$. The whole manipulation is a sequence of $g_i$ and $a_i$.

Given colored 3D point clouds from RGBD sensors, suppose $\mathbf{p}_i = \{\mathbf{x}_{i,j} \in \mathbb{R}^{3+C}, j = 1, \ldots, n_i\}$ is the 3D point cloud of the $i$-th rigid part of the object, where $n_i$ is the number of points and $C$ is the number of feature channels, e.g. color values. Suppose $\mathbf{p}_S^{(k)} = \{\mathbf{x}_j^{(k)} \in \mathbb{R}^{3+C}\}$ is the 3D point cloud of the non-object scene and $\mathcal{T}_i^{(k)}$ is the 6D pose of $i$-th rigid object part after grasping actions $g_1, g_2, \ldots, g_k$ have been completed. Note that the complete 3D point cloud of the scene $\mathbf{p}^{(k)} = \mathcal{O}(\prod_{l=1}^{k} g_l, \prod_{l=1}^{N} \mathcal{T}_l^{(k)})$ is a function of grasp actions $(g_1, g_2, \ldots, g_k)$ and object part poses $\mathcal{T}_i^{(k)}$, where $\mathcal{O}$ is the forward kinematics and observation of the environment. We assume there is no cycle in object joint connections so that there is no cyclic dependency among object parts. We formulate the manipulation problem as learning the following joint distribution of $(g_1, g_2, \ldots, g_n)$ given initial scene point cloud $\mathbf{p}^{(0)}$:

$$P(g_1, \ldots, g_n \mid \mathbf{p}^{(0)}) = P_1(g_1 \mid \mathbf{p}^{(0)}) P_2(g_2 \mid \mathbf{p}^{(1)}) \cdots P_n(g_n \mid \mathbf{p}^{(N-1)}) \tag{1}$$

$P_i$ is the contact point distribution model of $i$-th rigid part. In Equation (1), we use conditional probability to decompose $P$ and assumes previous point clouds have no effect on the current grasping distribution. Our goal is to learn distribution $P_i$ for each object part that covers the feasible grasping as widely as possible so that sampled grasping actions $g_i$ and subsequent moving actions $a_i$ can successfully take all object parts to desired poses $\mathcal{T}_i$.

## 3.2 Generative Modeling of Contact Probability

Our generative model is based on variational inference [5]. Different from 2D images where the positions of the pixels are fixed and only the pixel value distribution need to be modeled, in 3D point clouds, both geometry and point feature distribution need to be modeled. Therefore, instead of directly using multi-layer perceptions (MLPs) on pixel values similar to vanilla VAE, our model needs to learn both local and global point features in hierarchical fashion [22]. Moreover, in our model, the reconstructed feature map should not only be conditioned on latent code, but hierarchical geometric features as well.

**Encoder and Decoder for One Single Step.** Given a colored 3D point cloud appended with successful grasping probability maps $\mathbf{p} = \{\mathbf{x}_j \in \mathbb{R}^{3+4}\}$ where four feature channels are RGB and probability values, our model split the feature channels to construct two point clouds appended with different features: a 3D color map $\mathbf{p}_{\text{rgb}} = \{\mathbf{x}_j \in \mathbb{R}^{3+3}\}$ as the input to geometric learning, and $\mathbf{p}_{\text{c}} = \{\mathbf{x}_j \in \mathbb{R}^{3+1}\}$ as the 3D contact probability map to reconstruct using generative model.

An encoder network $\mathcal{F}_{\text{c}}(\cdot; \theta_{\text{c}})$ is used to approximate the posterior distribution $q(z \mid \mathbf{p}_{\text{c}}, \mathbf{p}_{\text{rgb}})$ of the latent code $z$. Another encoder network $\mathcal{F}_{\text{rgb}}(\cdot; \theta_{\text{rgb}})$ learns the hierarchical geometric representation and outputs features $\mathbf{h}_1, \mathbf{h}_2, \mathbf{h}_3$ at different levels:

$$[\mu, \sigma] = \mathcal{F}_{\text{c}}(\mathbf{p}_{\text{c}}, \mathbf{p}_{\text{rgb}}; \theta_{\text{c}}), \ [\mathbf{h}_1, \mathbf{h}_2, \mathbf{h}_3] = \mathcal{F}_{\text{rgb}}(\mathbf{p}_{\text{rgb}}; \theta_{\text{rgb}}) \tag{2}$$

where $\mu$ and $\sigma$ are the predicted mean and standard deviation of the multivariate Gaussian distribution respectively. The latent code $z$ is then sampled from the distribution and is used to reconstruct the contact probability map on point clouds with a decoder network $\mathcal{G}(\cdot; \theta_{\text{g}})$:

$$z \sim \mathcal{N}(\mu, \sigma^2), \ \hat{\mathbf{p}}_c = \mathcal{G}(z, \mathbf{h}_1, \mathbf{h}_2, \mathbf{h}_3; \theta_{\text{g}}) \tag{3}$$

Note that both $\mathcal{F}_{\text{c}}(\cdot; \theta_{\text{c}})$ and $\mathcal{G}(\cdot; \theta_{\text{g}})$ are conditioned on $\mathbf{p}_{\text{rgb}}$. Therefore, our generative model can be viewed as a conditional variational encoder model (CVAE) [23] that learns the latent distribution of the 3D contact probability map $\mathbf{p}_{\text{c}}$ conditioned on the deep features of 3D color map $\mathbf{p}_{\text{rgb}}$. The conditional variational formulation takes observation $\mathbf{p}_{\text{rgb}}$ into account and can improve the generalization.

The encoders $\mathcal{F}_{\text{rgb}}(\cdot; \theta_{\text{rgb}})$ and $\mathcal{F}_{\text{c}}(\cdot; \theta_{\text{c}})$ share the same architecture and are instantiated with set abstraction layers from PointNet++ [22]. The Decoder $\mathcal{G}(\cdot; \theta_{\text{g}})$ is instantiated with set upconv layers proposed in [24] to propagate features to existing up-sampled point locations in a learnable fashion.

**Loss Function.** Our generative model is trained to maximize the log-likelihood of the generated contact probability map to be successful contact labels. Due to Jensen's inequality, the evidence lower bound objective (ELBO) in variational inference can be derived as

$$\log P(\hat{\mathbf{p}}_c) \geq E_{z \sim q(z|\mathbf{p}_c, \mathbf{p}_{\text{rgb}})} \log P(\hat{\mathbf{p}}_c|z, \mathbf{p}_{\text{rgb}}) - D_{KL}(q(z|\mathbf{p}_c, \mathbf{p}_{\text{rgb}})||\mathcal{N}(0,1)) = -\mathcal{L} \quad (4)$$

The total loss $\mathcal{L} = \mathcal{L}_{\text{recon}} + \mathcal{L}_{\text{latent}}$ consists of two parts. Reconstruction loss $\mathcal{L}_{\text{recon}} = -E_{z \sim q(z|\mathbf{p}_c, \mathbf{p}_{\text{rgb}})} \log P(\hat{\mathbf{p}}_c|z, \mathbf{p}_{\text{rgb}}) = -E_{z \sim q(z|\mathbf{p}_c)} \log P(\hat{\mathbf{p}}_c|z) = H(\mathbf{p}_c, \hat{\mathbf{p}}_c)$ is the cross entropy between $\mathbf{p}_c$ and $\hat{\mathbf{p}}_c$. Latent loss $\mathcal{L}_{\text{latent}} = D_{KL}(\mathcal{N}(\mu, \sigma^2)||\mathcal{N}(0,1))$ is the KL Divergence of two normal distributions. The goal of the training is to minimize the total loss $\mathcal{L}$. The parameters in the three networks, $\theta_{\text{rgb}}$, $\theta_{\text{c}}$ and $\theta_{\text{g}}$, are trained end-to-end to minimize $\mathcal{L}$.

## 3.3 Planning and Control Actions

Given the predicted contact points on object part $i$, the 6D pose of the end-effector of robot $i$ can be obtained by solving an inverse kinematics problem. Path planning algorithm such as RRT [25] is used to find an operational space trajectory from initial pose to desired grasping pose. If a path is not found, the framework will iteratively sample contact point distributions from the generative model multiple times. Then we use Operational Space Controller [26] to move the gripper along the trajectory and finally complete the grasping action.

After a successful grasp, the next goal is to apply torques on robot arms and gripper to move the object part $i$ to the desired pose. To keep the grasping always valid, there should be no relative motion between the gripper and the object part. We propose **object-centric control** formulation where we convert the rigid transformation of object part $i$ to the rigid motion of the end effector of robot $i$, which will then be executed by another Operational Space Controller.

If the manipulation of one object part with a robot is successful, the V-MAO will move to the manipulation of the next object part with the next robot until all object parts are moved to desired poses within the threshold error.

## 3.4 Additional Implementation Details

**Part-level Pose Estimation.** To ensure the object contact point is present in the 3D point cloud, we superimpose the colored object mesh point clouds into the scene point cloud. The 6D pose of each object part is estimated using DenseFusion [27], an RGBD-based method for 6D object pose estimation. DenseFusion is trained separately using the simulation synthetic data. Since superimposing object mesh point cloud causes unnatural point density, we use farthest point sampling (FPS) on the complete scene point cloud to ensure uniform point density.

**Automatic Label Generation from Exploration.** Training the variational generative model requires a large amount of data. To collect sufficient data for training, we propose to use search algorithm to explore feasible contact point combinations by interacting with the simulation environment. Successful contact point combinations are saved in a pool for training. Expert-defined affordance areas of grasping, for example the handle of the plier, are provide to ensure realistic grasping and narrow down the search range. We also provide new initial demonstrations of possibly feasible contact point combinations, for example a pair of points at both sides of the plier handle, to speed up search efficiency.

# 4 Experiments

We design our experiments to investigate the following hypothesis: 1) given training samples of enough variability, the contact point generative model can effectively learn the underlying distribution; 2) contact point labels can be automatically generated through interaction with the environment; 3) given sampled and generated contact points, after path planning and control, the robot is able to complete the manipulation task.

## 4.1 Experiment Setup

**Task and Environment.** We conduct the experiments in an environment constructed with MuJoCo [3] simulation engine. The environment consists of two robots facing a table in parallel. The articu-

(a) `100144`   (b) `100182`   (c) `102285`   (d) `10213`   (e) `10356`   (f) `11778`

Figure 3: **The six articulated objects from PartNet [4] used in our experiments.** We illustrates their ID in the dataset. The expert-defined affordance area is the handles for the three pliers and the non-keyboard area for the three laptops.

Figure 4: **Experiment Environment.** Left and right images are front and side views respectively. The goal of manipulation is marked by the green semi-transparent point cloud.

lated object is placed on the table surface with random initial positions and joint angles. The goal of the manipulation is to grasp the object parts and move them to reach the desired positions and joint angles within a certain error threshold. Figure 4 illustrates one example of the environment.

**Objects and Robots.** We evaluate our approach on six daily articulated objects from PartNet [4] in the experiments. The objects include three pliers and three laptops illustrated in Figure 3. For the robots in the experiment, we use Sawyer and Panda which are equipped with two-finger parallel-jaw Rethink and Panda grippers. Both robots and grippers are instantiated by high-fidelity models provided in robosuite [28]. For the friction between robot gripper and the object, we assume a friction coefficient of 0.65 and assume pyramidal friction cone.

**Baseline.** There is no related previous work on multi-arm articulated objects that we can compare our V-MAO with. So we developed a baseline approach named "Top-1 Point" that predicts a deterministic contact point probability map and selects the best contact points for each gripper finger within the affordance region. To fairly compare, the baseline uses the same backbone architecture to process 3D point clouds and is trained on the same interaction data. After contact point selection, the subsequent planning and control step is also the same for the baseline.

## 4.2 Quantitative Evaluation

We explore two types of grasping strategy, sequential grasp and parallel grasp. In **sequential grasp**, object parts are grasped and moved in an iterative fashion. In $i$-th step, robot gripper $i$ grasps the $i$-th object part while leaving parts $i + 1$ through $N$ uncontrolled. We iterative the above step until all parts are grasped. In **parallel grasp** all object parts are grasped simultaneously. Then the robots move the object parts to the goal locations together.

We report the success rate of manipulation in Table 1. Our V-MAO can achieve more than 80% success rate with Sawyer robot and more than 70% success rate with Panda robot on all objects, which shows V-MAO can effectively learn the contact distribution and complete the task. Besides, sequential grasping generally achieves a better success rate than parallel grasping. This means determining grasping for other robots later may be a better option than determining both robots' grasping at the beginning.

We notice that when using the Panda robot, the performance of both V-Mao and the baseline decrease significantly. The reason is that the Panda robot has a large end effector size. Therefore when manipulating small objects like pliers, in many cases the space is not enough to contain both grippers due to robot collision, while Sawyer robot's end effector is much smaller. The deterministic

| robot | method | grasp order | 100144 | 100182 | 102285 | 10213 | 10356 | 11778 |
|---|---|---|---|---|---|---|---|---|
| Saywer | Top-1 Point | parallel | 90.0 | **92.0** | 86.0 | **96.0** | 88.0 | 90.0 |
| | | sequential | 82.0 | 78.0 | 88.0 | 92.0 | 84.0 | 86.0 |
| | **V-MAO (Ours)** | parallel | **94.0** | 90.0 | 90.0 | **96.0** | **90.0** | **94.0** |
| | | sequential | 92.0 | 86.0 | **92.0** | **96.0** | 88.0 | 90.0 |
| Panda | Top-1 Point | parallel | 50.0 | 20.0 | 48.0 | **90.0** | **92.0** | **88.0** |
| | | sequential | 62.0 | 42.0 | 70.0 | 78.0 | 82.0 | 70.0 |
| | **V-MAO (Ours)** | parallel | 52.0 | 36.0 | 64.0 | **90.0** | 84.0 | **88.0** |
| | | sequential | **72.0** | **76.0** | **78.0** | 88.0 | 86.0 | 86.0 |

Table 1: **Success rate of Manipulation.** The baseline we compare V-MAO with is selecting the point with the maximum contact probability from deterministic prediction. We report the results averaged from 50 runs.

|  (a) | (b) | (c) $z = -1.0$ | (d) $z = -0.5$ | (e) $z = 0.5$ | (f) $z = 1.0$ |

Figure 5: **Visualization of sampled and generated 3D probability maps.** From left to right in each row: (a) the current manipulation state; (b) converted colored 3D point cloud at the current state; (c)-(f) generated probability map of the next grasp given specific latent code $z$, where red and yellow denote the finger 1 and 2 of the first gripper in the first grasping step, and green and blue denote the finger 1 and 2 of the second gripper in the second grasping step. Zoom in for better a view of the figures.

prediction baseline achieves a larger success rate on laptops. A possible explanation is that there are less variation in grasping laptops compared to pliers, for example the first grasp of the laptop is almost always grasping the base horizontally. Thus a deterministic model can be more stable in simpler tasks. On the other hand, in environments with larger variability, a generative model can have advantage.

## 4.3 Qualitative Results

In Figure 5, we visualize the probability map on the 3D point clouds sampled from the generative model given different latent codes $z$. As expected, the maximum value probability value falls on the object points. The points that have the maximum probability for the respective gripper also form valid grasps. Given different latent codes $z$, the generated contact points can cover a wide range

Figure 6: **Visualization of two sequential manipulations using two robot arms.** Rows 1 and 2 illustrate the manipulation of a pair of pliers (`100144`) using two Sawyer robots. Row 3 and 4 illustrate the manipulation of a laptop computer (`10213`) using two Panda robots. The object configuration goal of manipulation is marked by the green semi-transparent point cloud.

of feasible contact point combinations. We also notice that there are some object regions that are less covered by the generative model during sampling. One possible reason is that grasping in these regions can introduce collisions in the current or the next steps and have a lower probability of being sampled.

In Figure 6, we visualize the executed sequential manipulation using the contact points sampled from the generative model. As we can see, the robot gripper can successfully reach the contact points after inverse kinematics and path planning. When both grippers are grasping the object, the sampled and generated contact points combination for both robots can also avoid collision between robots. After grasping, both robots can reliably control the object to reach the goal configurations marked by green points.

## 5 Conclusion

In this paper, we propose V-MAO, a framework for learning multi-arm manipulation of articulated objects. Our framework includes a variational generative model that learns contact point distribution over object rigid parts for each robot arm. We developed a mechanism for automatic contact label generation from robot interaction with the environment. We deploy our framework in a customized MuJoCo simulation environment and demonstrate that our framework achieves high success rate on six different objects and two different robots. V-MAO achieves over 80% success rate with Sawyer robot and over 70% success rate with Panda robot. Experiment results also show that the proposed variational generative model can effectively learn the distribution of successful contacts.

## References

[1] H. Ha, J. Xu, and S. Song. Learning a decentralized multi-arm motion planner. In *CoRL*, 2020.

[2] V. N. Hartmann, A. Orthey, D. Driess, O. S. Oguz, and M. Toussaint. Long-horizon multi-robot rearrangement planning for construction assembly. *arXiv preprint arXiv:2106.02489*, 2021.

[3] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.

[4] K. Mo, S. Zhu, A. X. Chang, L. Yi, S. Tripathi, L. J. Guibas, and H. Su. Partnet: A large-scale benchmark for fine-grained and hierarchical part-level 3d object understanding. In *CVPR*, 2019.

[5] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[6] I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial networks. In *NIPS*, 2014.

[7] A. Wang, T. Kurutach, K. Liu, P. Abbeel, and A. Tamar. Learning robotic manipulation through visual planning and acting. In *RSS*, 2019.

[8] T. Kurutach, A. Tamar, G. Yang, S. Russell, and P. Abbeel. Learning plannable representations with causal infogan. *arXiv preprint arXiv:1807.09341*, 2018.

[9] D. Morrison, P. Corke, and J. Leitner. Closing the loop for robotic grasping: A real-time, generative grasp synthesis approach. In *RSS*, 2018.

[10] J. Lundell, E. Corona, T. N. Le, F. Verdoja, P. Weinzaepfel, G. Rogez, F. Moreno-Noguer, and V. Kyrki. Multi-fingan: Generative coarse-to-fine sampling of multi-finger grasps. In *ICRA*, 2021.

[11] M. S. Kopicki, D. Belter, and J. L. Wyatt. Learning better generative models for dexterous, single-view grasping of novel objects. *IJRR*, 2019.

[12] J. Lundell, F. Verdoja, and V. Kyrki. Ddgc: Generative deep dexterous grasping in clutter. *arXiv preprint arXiv:2103.04783*, 2021.

[13] X. Chen, R. Chen, Z. Sui, Z. Ye, Y. Liu, R. I. Bahar, and O. C. Jenkins. Grip: Generative robust inference and perception for semantic robot manipulation in adversarial environments. In *IROS*, 2019.

[14] H. Ha, S. Agrawal, and S. Song. Fit2form: 3d generative model for robot gripper form design. *CoRL*, 2020.

[15] D. Katz, Y. Pyuro, and O. Brock. Learning to manipulate articulated objects in unstructured environments using a grounded relational representation. In *RSS*, 2008.

[16] D. Katz and O. Brock. Manipulating articulated objects with interactive perception. In *ICRA*, 2008.

[17] K. N. Kumar, I. Essa, S. Ha, and C. K. Liu. Estimating mass distribution of articulated objects using non-prehensile manipulation. *arXiv preprint arXiv:1907.03964*, 2019.

[18] V. Narayanan and M. Likhachev. Task-oriented planning for manipulating articulated mechanisms under model uncertainty. In *ICRA*, 2015.

[19] M. Mittal, D. Hoeller, F. Farshidian, M. Hutter, and A. Garg. Articulated object interaction in unknown scenes with whole-body mobile manipulation. *arXiv preprint arXiv:2103.10534*, 2021.

[20] R. Shome and K. E. Bekris. Anytime multi-arm task and motion planning for pick-and-place of individual objects via handoffs. In *International Symposium on Multi-Robot and Multi-Agent Systems (MRS)*, 2019.

[21] R. Shome, K. Solovey, J. Yu, K. Bekris, and D. Halperin. Fast, high-quality two-arm rearrangement in synchronous, monotone tabletop setups. *IEEE Transactions on Automation Science and Engineering*, 2021.

[22] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. In *NIPS*, 2017.

[23] K. Sohn, H. Lee, and X. Yan. Learning structured output representation using deep conditional generative models. *NIPS*, 2015.

[24] X. Liu, C. R. Qi, and L. J. Guibas. Flownet3d: Learning scene flow in 3d point clouds. In *CVPR*, 2019.

[25] S. M. LaValle et al. Rapidly-exploring random trees: A new tool for path planning. 1998.

[26] O. Khatib. A unified approach for motion and force control of robot manipulators: The operational space formulation. *IEEE Journal on Robotics and Automation*, 1987.

[27] C. Wang, D. Xu, Y. Zhu, R. Martín-Martín, C. Lu, L. Fei-Fei, and S. Savarese. Densefusion: 6d object pose estimation by iterative dense fusion. In *CVPR*, 2019.

[28] Y. Zhu, J. Wong, A. Mandlekar, and R. Martín-Martín. robosuite: A modular simulation framework and benchmark for robot learning. In *arXiv preprint arXiv:2009.12293*, 2020.