MODELING THE UNCERTAINTY WITH MAXIMUM DISCREPANT STUDENTS FOR SEMI-SUPERVISED 2D POSE ESTIMATION

ABSTRACT

Semi-supervised pose estimation is a practically challenging task for computer vision. Although numerous excellent semi-supervised classification methods have emerged, these methods typically use confidence to evaluate the quality of pseudo-labels, which is difficult to achieve in pose estimation tasks. For example, in pose estimation, confidence represents only the possibility that a position of the heatmap is a keypoint, not the quality of that prediction. In this paper, we propose a simple yet efficient framework to estimate the quality of pseudo-labels in semi-supervised pose estimation tasks from the perspective of modeling the uncertainty of the pseudo-labels. Concretely, under the dual mean-teacher framework, we construct the two maximum discrepant students (MDSs) to effectively push two teachers to generate different decision boundaries for the same sample. Moreover, we create multiple uncertainties to assess the quality of the pseudo-labels. Experimental results demonstrate that our method improves the performance of semi-supervised pose estimation on three datasets.

1 INTRODUCTION

As an essential task in computer vision, pose estimation has been widely used in various fields such as action recognition, security monitoring, animal experimentation. Most pose estimation methods use MSE loss to transform keypoint location predictions into Gaussian heatmap regression. State-of-the-art methods (Zhang et al. (2020a), Zhang et al. (2020b), Huang et al. (2019), Li et al. (2019), Cheng et al. (2019), Chen et al. (2018), Xiao et al. (2018), Tang et al. (2018), Newell et al. (2017), Cao et al. (2017), Newell et al. (2016), Wei et al. (2016)) require a large amount of labeled data. However, labeling pose keypoints is a costly and time-intensive labor for many practical tasks. How to effectively train a model without sufficient labeled data has attracted attention in the field of pose estimation.

A simple idea is to utilize semi-supervised classification methods for the pose estimation task. Numerous outstanding research have emerged in the field of semi-supervised classification, which can be categorized into methods based on consistency constraints and pseudo-labels. For example, Miyato et al. (2018), Sajjadi et al. (2016) mainly employ rational stochastic transformations and perturbations to improve the gain, which are derived from consistency constraints. Meanwhile, Tarvainen & Valpola (2017), Laine & Aila (2016) utilize high-quality pseudo-label filters from the predictions of unlabeled samples. In addition, the two methods are combined for better performance, such as Zhang et al. (2021), Chen et al. (2020), Berthelot et al. (2019).

However, semi-supervised classification methods commonly evaluate the quality of generated pseudo-labels based on confidence, such as Ke et al. (2019), which cannot be applied to semi-supervised pose estimation. In the pose estimation task, confidence can only be used to obtain the keypoint locations of the heatmap predicted by the model, not to evaluate the quality of the prediction. As shown in Fig. 1, with the increase of epochs, the model's prediction confidence of this key point gradually increases, but the error of this prediction does not effectively decrease. This phenomenon indicates that confidence in pose estimation is not directly related to the quality of predictions from the model, and thus cannot be used to assess the quality of pseudo-labels. With these noisy and even erroneous pseudo-labels, the performance naturally deteriorates. That is, the perfor-

Figure 1: Error and confidence curves for two keypoint pseudo-labels, 1106_5 and 2077_4. It suggests that confidence is not directly related to the accuracy of the prediction itself. Therefore, confidence does not effectively assess the quality of pseudo-labels.

mance of semi-supervised learning is lower than that of supervised learning with the same amount of labeled data. Therefore, effectively selecting high-quality pseudo-labels in semi-supervised pose estimation is an essential and challenging task.

Therefore, we construct a dual mean-teacher structure to evaluate the quality of the pseudo-labels by computing the distance between the predicted keypoint positions of multiple pose estimators to measure the discriminative power of the model on the samples. Furthermore, high-quality pseudo-labels are added to the training dataset to gradually train the model. To avoid coupling between multiple pose estimators, we introduce a simple and effective method to build the maximum difference regrestors (MDRs) by adding a parameter adversarial mechanism between two students. When the parameters of each regressor are different, it is possible to ensure that their decision boundaries do not overlap, thus helping to ensure the accuracy of the evaluated uncertainty. Meanwhile, the parametric adversarial mechanism can balance the performance of the two MDSs to guarantee the quality of pseudo-labels. The key contributions of this work are:

- We propose a semi-supervised pose estimation method based on the Dual Mean-Teacher framework. We construct multiple uncertainties to evaluate the quality of pseudo-labels generated by the model and efficiently extract high-quality pseudo-labels for further model training.

- We propose a model-parameter adversarial mechanism to effectively increase diversity and avoid the degradation of uncertainty assessment quality caused by the coupling of multiple pose regressors.

- Our experiments show that MDSs can effectively select high-quality pseudo-labels without using confidence as an evaluation criterion and achieve better performance on the three datasets.

2 RELATIVE WORK

2.1 2D POSE ESTIMATION

In terms of organization of supervised information, 2D pose estimation methods can be divided into keypoint regression-based methods and heatmap-based methods. For example, A and B directly regress the keypoint positions using the coordinate values of the keypoints as supervision information. Moreover, Huang et al. (2019), Newell et al. (2016) and Wei et al. (2016) are heatmap based keypoint estimation methods. The keypoint coordinate values are converted into heatmap as supervised information to train the model, and then the appropriate position is selected from the heat output by the model as the position prediction of the keypoints according to confidence. We choose heatmap-based methods because direct coordinate regression is more difficult and less favorable for semi-supervised pose estimation.

2.2 SEMI-SUPERVISED LEARNING

Many excellent semi-supervised methods have emerged in the field of classification. For example, Miyato et al. (2018), Sajjadi et al. (2016) are consistency constraint based methods. Crucial to this approach is how to efficiently improve the effect of consistency constraints through reasonable data augmentation and perturbation, thus obtaining more supervised information from unlabeled data to improve model performance. While Tarvainen & Valpola (2017), Laine & Aila (2016), based on the idea of self-training, generate pseudo-labels from the model to supervise their training. So this approach relies on how to generate and select high-quality pseudo-labels. In addition, the two methods are combined for better performance, such as Zhang et al. (2021), Chen et al. (2020), Berthelot et al. (2019). We combine the two using the Mean-Teacher. Our model not only obtains supervised information based on consistency constraints from unlabeled data, but also generates high-quality pseudo-labels through mutual generalization of teacher and student models.

2.3 QUALITY ASSESSMENT OF PSEUDO-LABELS

Semi-supervised classification methods normally filter self-supervised information by combining uncertainty and confidence, such as Ke et al. (2019), Sohn et al. (2020). This is because uncertainty is commonly quantified by evaluating the consistency of multiple predictions for the same sample, which requires the results of each prediction to be plausible. However, unlike the classification task, confidence in pose estimation can only be used to obtain keypoint locations from heatmaps, not to evaluate the quality of model predictions.

Therefore, our method evaluates the quality of pseudo-labels through uncertainty without confidence. To ensure uncertainty accuracy, we construct an uncertainty evaluation network based on the dual Mean-Teacher structure and add a model parameter adversarial mechanism so that the decision surfaces between multiple pose estimators do not overlap.

3 PROPOSED METHOD

3.1 SEMI-SUPERVISED POSE ESTIMATION

The supervised pose estimation is to achieve accurate predictions of K keypoints with N labeled data $\mathbb{D}^l = \{(\mathbf{x}_i^l, \mathbf{y}_i^l)\}_{i=1}^N$, where $\mathbf{x}_i^l \in \mathbb{R}^{H \times W}$ is image, $\mathbf{y}_i^l \in \{0, 1\}^K$ is the corresponding the ground-truth. Most state-of-the-art methods convert the location of keypoints as heatmap $\mathbf{H}$. $\mathbf{H}$ is a distribution, encoding the possibility that each pixel in image is the keypoint. As a result, the prediction of keypoints' locations is converted as the Gaussian heatmap regression by minimize the MSE loss between the prediction and its ground-truth. The pose loss for labeled data is as follows:

$$L_p^l = \|f(\mathbf{x}_i^l|\theta) - \mathbf{H}_i^*)\|^2, \tag{1}$$

where $f(\cdot|\theta)$ is the predicted heatmap by the model θ. $\mathbf{H}_i^*$ is the ground-truth heatmap of $\mathbf{x}_i^l$.

Comparing with supervised learning, the semi-supervised pose estimation solves the problem of less amount of labeled data. The dataset consists of labeled dataset $\mathbb{D}^l$ and M unlabeled data $\mathbb{D}^u = \{\mathbf{x}_j^u\}_{j=N+1}^{N+M}$, where $\mathbf{x}_i^l, \mathbf{x}_j^u \in \mathbb{R}^{H \times W}$, $\mathbf{y}_i^l \in \{0, 1\}^K$, K is the number of keypoints. $N \ll M$. For labeled data, the process is same as supervised pose estimation. For unlabeled data, the ground-truth is the pseudo-label generated in the semi-supervised learning. The pose loss for the unlabeled data is as follows:

$$L_p^u = \|f(\mathbf{x}_i^u|\theta_1) - f(\mathbf{x}_i^u|\theta_2)\|^2, \tag{2}$$

where $f(\mathbf{x}_i^u|\theta_1)$ is the prediction heatmap of the model θ_1, $f(\mathbf{x}_i^u|\theta_2)$ is the pseudo-label heatmap of the model θ_2.

We use Mean Teacher (MT) Tarvainen & Valpola (2017) in semi-supervised pose estimation. In MT, the teacher generates the pseudo-labels for unlabeled data to train the student, the parameters of teacher are obtained from student by the Exponential Moving Average (EMA) strategy. The EMA

Figure 2: Overview of the proposed maximum discrepant students (MDSs) framework.

is as follows:

$$\theta_T^t = \alpha\theta_T^{t-1} + (1-\alpha)\theta_S^t, \tag{3}$$

where θ_T^t, θ_S^t are the teacher's and student's parameters in t epoch, respectively. α is a smoothing coefficient hyper-parameter. Taking advantage of EMA, teacher can generate more accurate pseudo-labels.

The quality of the pseudo labels is related to the predictive power of the generator at each epoch. However, models in semi-supervised learning typically use a single regressor to generate pseudo-labels, such as the teacher in MT. A single regressor obtains barely additional information. With a small amount of labeled data, the model tends to under- or over-fit, and thus generate noisy pseudo-labels. Therefore, an effective quality evaluation method for pseudo-labels is needed to pick up high-quality pseudo-labels to train the model.

3.2 MAXIMUM DISCREPANT STUDENTS

The MDSs framework is illustrated in Fig. 2. It is composed of two MDS modules, and an uncertainty estimator E. Both students and teachers use the same pose estimation model. In each MDS, the teacher predicts the pseudo-label to train the student and uses the Exponential Moving Average (EMA) weights of the student, as Eq. equation 3. The uncertainty estimator E evaluates the uncertainty of the pseudo-label by calculating the distance between two predictions from teachers T_1 and T_2, as Eq. equation **??**. We maximize the discrepancy of two students S_1 and S_2 by the *parameters adversarial loss*, as Eq. equation 6.

Each epoch, two teachers T_1 and T_2 generate the pseudo-labels of unlabeled data. The uncertainty estimator E estimates the uncertainty of these pseudo-labels, and evaluates the quality of these pseudo-labels by the uncertainty and confidence. The top k high-quality pseudo-labels are added into labeled dataset. Then two students S_1 and S_2 are trained by this expanded labeled dataset.

3.3 OBJECTIVE FUNCTION

In supervised pose estimation, the MSE loss is used to train the model. In MDSs, we directly use the ground-truth to calculate pose loss for labeled data. For unlabeled data, we use the pseudo-labels generated by teacher T_2 to calculate the pose loss of student S_1, which is as follows:

$$L_{p_{S_1}} = \|f(\mathbf{x}_i^l|\theta_{S_1}) - \mathbf{H}_i^*)\|^2 + \|f(\mathbf{x}_i^u|\theta_{S_1}) - f(\mathbf{x}_i^u|\theta_{T_2})\|^2 \tag{4}$$

where θ_{S_1} is the parameter of the student S_1, θ_{T_2} is the parameter of the teacher T_2, respectively.

Correspondingly, the pose loss of student S_2 is calculated with the pseudo labels generated by teacher T_1, which is as follows

$$L_{p_{S_2}} = \|f(\mathbf{x}_i^l|\theta_{S_2}) - \mathbf{H}_i^*)\|^2 + \|f(\mathbf{x}_i^u|\theta_{S_2}) - f(\mathbf{x}_i^u|\theta_{T_1})\|^2 \tag{5}$$

where θ_{S_2} is the parameter of the student S_2, θ_{T_1} is the parameter of the teacher T_1, respectively.

In real life, when two experts in the same field have different answers to the same question, it is most likely that the question itself is very uncertain. Inspired by this, the MDSs framework is based on two constraints.

On one hand, two teachers T_1 and T_2 are used to evaluate the uncertainty of the same sample. To achieve this goal, the first constraint is that T_1 and T_2 should have balanced performance, as Eq. equation 4 and equation 5.

On the other hand, two students should keep divergences. So, another constraint is the *parameter adversarial loss*, through which we ensure that the two experts are not homogenized. To maximize the discrepancy between two MDSs, we minimize the cosine distance of students S_1 and S_2 by the *parameters adversarial loss*:

$$L_a = \frac{\theta_{S_1} \cdot \theta_{S_2}}{\|\theta_{S_1}\|\|\theta_{S_2}\|}, \tag{6}$$

where θ_{S_1} and θ_{S_2} are the model parameters of students S_1 and S_2, respectively.

Otherwise, following the semi-supervised approach, the *consistency loss* to updating S_1 and S_2 is as follows:

$$L_c = \|f(\mathbf{x}|\theta_{S_1}) - f(\mathbf{x}|\theta_{T_1})\|^2 + \|f(\mathbf{x}|\theta_{S_2}) - f(\mathbf{x}|\theta_{T_2})\|^2, \tag{7}$$

where $\mathbf{x} \in \mathbb{D}^{l \cup u} = \mathbb{D}^l \cup \mathbb{D}^u$. $f(\mathbf{x}|\theta_{S_1})$ and $f(\mathbf{x}|\theta_{S_2})$, $f(\mathbf{x}^u|\theta_{T_1})$ and $f(\mathbf{x}^u|\theta_{T_2})$ are the predictions of students S_1 and S_2, teachers T_1 and T_2, respectively.

We summarize the objective function as follows:

$$L = \lambda_p L_p + \lambda_a L_a + \lambda_c L_c, \tag{8}$$

where λ_p, λ_a and λ_c are the weights of the *pose loss*, *parameters adversarial loss* and *consistency loss*, respectively.

3.4 HIGH-QUALITY PSEUDO-LABELS

Crucial in the semi-supervised pose estimation task is how to judge the quality of a pseudo-label.

First, we take the prediction $f(\mathbf{x}|\theta_T)$ of the teacher θ_T on the raw sample $\mathbf{x}$ as the pseudo-truth value of the pseudo-label. This is because, in pose estimation tasks, the prediction accuracy of raw samples is much higher than that of augmented samples, which are generated by data augmentation or perturbation.

Second, to evaluate the quality of pseudo-labels, we consider the following two points:

- For high-quality pseudo-labels, the model should have predictive consistency for different augmented samples of the raw sample. A model has a high epistemic capacity on raw samples if its prediction uncertainty on augmented samples is low. In turn, high uncertainty implies low epistemic capacity of the model for the raw sample. Therefore, we obtain M randomly augmented samples of this raw sample and calculate the distance between the predictions of these augmented samples to quantify the uncertainty of the corresponding pseudo-label. The lower the uncertainty, the higher the quality of the pseudo-labels.
- For high-quality pseudo-labels, the model should have predictive stability for the raw sample and its augmented samples. Therefore, we evaluate the quality of the pseudo-labels by computing their uncertainties via a moving weighted average.

3.5 THE QUANTIFICATION OF UNCERTAINTY

To better assess the quality of pseudo-labels, we construct triplet uncertainties, which are augmented internal uncertainty $\text{unc}_{\text{aug}}^{\text{int}}$, augmented external uncertainty $\text{unc}_{\text{aug}}^{\text{ext}}$, and raw internal uncertainty unc^{ext}.

The augmented internal uncertainty is the average distance between the predictions $\{\widetilde{\mathbf{p}}\}_{m=1}^{M} = \{f(\widetilde{\mathbf{x}}^{m}|\theta_T)\}_{m=1}^{M}$ generated by the teacher on the augmented samples.

$$\text{unc}_{\text{aug}}^{\text{int}} = \text{M}(\text{D}(\text{C}(\{\widetilde{\mathbf{p}}\}_{m=1}^{M}))), \tag{9}$$

where $\text{M}(\cdot)$ is to calculate the mean value from a distances set, D is a function to calculate the Euclidean distance between two coordinates, C is taking two points from the set of coordinates obtained from the prediction.

The augmented external uncertainty is the distance between the mean prediction $\bar{\widetilde{\mathbf{p}}}_{\theta_{T_1}}$ of one teacher T_1 and the mean prediction $\bar{\widetilde{\mathbf{p}}}_{\theta_{T_2}}$ of another teacher T_2 on the same set of augmented samples.

$$\text{unc}_{\text{aug}}^{\text{ext}} = \text{D}(\bar{\widetilde{\mathbf{p}}}_{\theta_{T_1}}, \bar{\widetilde{\mathbf{p}}}_{\theta_{T_2}}), \tag{10}$$

The raw external uncertainty is the distance between the prediction $\mathbf{p}_{\theta_{T_1}}$ of one teacher and the prediction $\mathbf{p}_{\theta_{T_2}}$ of another teacher on the same raw sample.

$$\text{unc}^{\text{ext}} = \text{D}(\mathbf{p}_{\theta_{T_1}}, \mathbf{p}_{\theta_{T_2}}), \tag{11}$$

When selecting high-quality pseudo-labels, we require that all three uncertainty values should be smaller than the threshold ϵ.

4 EXPERIMENTAL RESULTS

4.1 DATASET

The **FLIC** dataset consists of 5003 images taken from movies, including 3987 training data and 1016 test data. Most images have a single instance and a few have multiple instances. Each instance contains 11 keypoints. In our experiments, we use single instance samples, of which 1000 are used as the training set and 500 are used as the testing set. Fifty percent of the samples in the training set are labeled. We selected keypoints on the left shoulder and left waist to participate in the experiment. When computing the PCK, we use the distance between the left shoulder and the left waist as the scale factor. The metric of PCK@0.2 is reported.

The **Pranav** dataset is a public mouse dataset consisting of 1000 images with one instance per image. Each mouse instance has four keypoints such as nose, left ear, right ear, and tail root. In our experiments, we use 100 samples as the training set and 500 samples as the test set. Thirty percent of the samples in the training set are labeled. When computing the PCK, we use the distance between the left ear and the right ear as the scale factor. The metric of PCK@0.2 is reported.

The **Mouse** dataset was captured by ourselves from real experimental environments. The dataset contains 1000 RGB images with 256 x 256 pixels. The pose annotation of the image consists of nine keypoints such as nose, left eye, right eye, left ear, right ear, head, tail root, tail and tip. In our experiments, we use 100 samples as the training set and 500 samples as the test set. Thirty percent of the samples in the training set are labeled. When computing the PCK, we use the distance between the left ear and the right ear as the scale factor. The metric of PCK@0.2 is reported.

4.2 IMPLEMENTATION DETAILS

We experimented with the Stacked Hourglass (HG) Newell et al. (2016), Mean Teacher (MT) Tarvainen & Valpola (2017), Easy-Hard Augmentation (EHA) Xie et al. (2021) and our MDSs on the FLIC, Pranav and Mouse datasets, respectively. Among the methods, HG is supervised learning and

Figure 3: The error and PCK@0.2 of different methods on Mouse dataset, respectively. HG Newell et al. (2016) is supervised learning. MT Tarvainen & Valpola (2017), Easy-Hard Augmentation (EHA) Xie et al. (2021) and MDSs are semi-supervised learning.

the remaining three methods are semi-supervised learning. In addition, EHA is based on the idea that using the prediction of easy-augmented sample to supervise the prediction of the hard-agumented sample [Paper]. The training batch size is two and the total number of training epochs is 500, and the data augmentation methods include random translation, random flip, and random rotation.

4.3 COMPARISONS WITH OTHER METHODS

Table 1: MSE and PCK@0.2 of different methods on FLIC, Pranav, Mouse Dataset. "1000*0.5" represents the represents 1000 samples as the training set, 50% of which are labeled.

Method	Training set	MSE	PCK@0.2
supervised Newell et al. (2016)		29.70	**0.477**
Mean-Teacher Tarvainen & Valpola (2017)	FLIC	33.68	0.469
EHA Xie et al. (2021)	1000*0.5	32.67	0.428
Ours		**27.47**	0.420
supervised		9.39	0.485
Mean-Teacher	Pranav	6.54	0.554
EHA	100*0.3	7.18	0.502
Ours		**5.66**	**0.660**
supervised		5.29	0.583
Mean-Teacher	Mouse	4.75	0.627
EHA	100*0.3	5.18	0.482
Ours		**4.10**	**0.687**

As shown in Table 1, MDSs achieve the best results, both in terms of error and PCK@0.2, on both Mouse and Pranav datasets. MDSs achieve better results on the FLIC dataset in terms of error, with at least a 3-points improvement over the other methods. As shown in Fig. 3, using the Mouse dataset as an example, we observe error and PCK@0.2 curves for different models throughout the training period. It can be seen that MDSs perform much better than the other methods in terms of PCK@0.2 curves throughout the training period. It also significantly outperforms the other methods in terms of stability. Correspondingly, on the error curve, we can also see that, overall, the MDSs method also preserves smaller values of the error and has much smaller fluctuations than the other methods.

4.4 THE EFFECT OF UNCERTAINTY

To further illustrate the effectiveness of our method, we select a small amount of labeled data as unlabeled data to generate and select high-quality pseudo-labels. Moreover, calculating the error

Figure 4: Errors of selected pseudo-labels for different cases on the Mouse dataset, respectively.

Figure 5: PCK@0.2 of selected pseudo-labels for different cases on the Mouse dataset, respectively.

and PCK@0.2 of these pseudo-labels to observe the effect of uncertainty on the quality evaluation of pseudo labels. We performed the following experiments:

- In MDSs, triplet uncertainty and confidence are used to select high-quality pseudo-labels.
- In MDSs, triplet uncertainties are used to select high-quality pseudo-labels.
- In MDSs, confidence is used to select high-quality pseudo-labels.

The experimental results are shown in Figs. 4 and 5. On the one hand, the pseudo-label quality of the two methods using triplet uncertainty is much higher than the prediction performance of the current model on the test set. These results suggest that triplet uncertainty can effectively select high-quality pseudo-labels. On the other hand, the pseudo-label quality is similar for both methods using triplet uncertainty, while the method using confidence alone has the worst pseudo-label quality.

4.5 ABLATION STUDY

Table 2: Evaluation result of MDSs under different settings. PAL is the *parameter adversarial loss* of MDSs, as Eq. equation 6.

Index	PAL	PAL Weight	PCK@0.2
1			0.675
2	✓	0.000005	0.687
3	✓	0.005	**0.693**

In order to illustrate the role of model parameter adversarial mechanism in MDSs, we ran experiments with different parameter adversarial loss weights (PAL Weight), and the experimental results are shown in Table 2. Use the parameter adversarial mechanism, the error and PCK@0.2 of the model are better than those without parameter adversarial mechanism.

5   CONCLUSION

In this paper, a Maximum Difference Student (MDSs) framework is proposed to effectively improve the performance of semi-supervised pose estimation tasks. In, evaluation metrics based on triplet uncertainty can effectively select high-quality pseudo-labels and completely replace confidence. The model parameter adversarial mechanism can further improve the consistency and stability of the predictions of the two teachers and effectively boost the performance of the model. Our method achieves better results on three datasets: FLIC, Pranav, and Mouse.

REFERENCES

David Berthelot, Nicholas Carlini, Ekin D Cubuk, Alex Kurakin, Kihyuk Sohn, Han Zhang, and Colin Raffel. Remixmatch: Semi-supervised learning with distribution alignment and augmentation anchoring. *arXiv preprint arXiv:1911.09785*, 2019.

Zhe Cao, Tomas Simon, Shih-En Wei, and Yaser Sheikh. Realtime multi-person 2d pose estimation using part affinity fields. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7291–7299, 2017.

Jiaao Chen, Zichao Yang, and Diyi Yang. Mixtext: Linguistically-informed interpolation of hidden space for semi-supervised text classification. *arXiv preprint arXiv:2004.12239*, 2020.

Yilun Chen, Zhicheng Wang, Yuxiang Peng, Zhiqiang Zhang, Gang Yu, and Jian Sun. Cascaded pyramid network for multi-person pose estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7103–7112, 2018.

Bowen Cheng, Bin Xiao, Jingdong Wang, Honghui Shi, Thomas S Huang, and Lei Zhang. Bottom-up higher-resolution networks for multi-person pose estimation. *arXiv preprint arXiv:1908.10357*, 7, 2019.

Junjie Huang, Zheng Zhu, and Guan Huang. Multi-stage hrnet: multiple stage high-resolution network for human pose estimation. *arXiv preprint arXiv:1910.05901*, 2019.

Zhanghan Ke, Daoye Wang, Qiong Yan, Jimmy Ren, and Rynson WH Lau. Dual student: Breaking the limits of the teacher in semi-supervised learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6728–6736, 2019.

Samuli Laine and Timo Aila. Temporal ensembling for semi-supervised learning. *arXiv preprint arXiv:1610.02242*, 2016.

Wenbo Li, Zhicheng Wang, Binyi Yin, Qixiang Peng, Yuming Du, Tianzi Xiao, Gang Yu, Hongtao Lu, Yichen Wei, and Jian Sun. Rethinking on multi-stage networks for human pose estimation. *arXiv preprint arXiv:1901.00148*, 2019.

Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, and Shin Ishii. Virtual adversarial training: a regularization method for supervised and semi-supervised learning. *IEEE transactions on pattern analysis and machine intelligence*, 41(8):1979–1993, 2018.

Alejandro Newell, Kaiyu Yang, and Jia Deng. Stacked hourglass networks for human pose estimation. In *European conference on computer vision*, pp. 483–499, 2016.

Alejandro Newell, Zhiao Huang, and Jia Deng. Associative embedding: End-to-end learning for joint detection and grouping. *Advances in neural information processing systems*, 30, 2017.

Mehdi Sajjadi, Mehran Javanmardi, and Tolga Tasdizen. Regularization with stochastic transformations and perturbations for deep semi-supervised learning. *Advances in neural information processing systems*, 29, 2016.

Kihyuk Sohn, David Berthelot, Nicholas Carlini, Zizhao Zhang, Han Zhang, Colin A Raffel, Ekin Dogus Cubuk, Alexey Kurakin, and Chun-Liang Li. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. *Advances in neural information processing systems*, 33:596–608, 2020.

Wei Tang, Pei Yu, and Ying Wu. Deeply learned compositional models for human pose estimation. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 190–206, 2018.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. *Advances in neural information processing systems*, 30, 2017.

Shih-En Wei, Varun Ramakrishna, Takeo Kanade, et al. Convolutional pose machines. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 4724–4732, 2016.

Bin Xiao, Haiping Wu, and Yichen Wei. Simple baselines for human pose estimation and tracking. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 466–481, 2018.

Rongchang Xie, Chunyu Wang, Wenjun Zeng, and Yizhou Wang. An empirical study of the collapsing problem in semi-supervised 2d human pose estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 11240–11249, 2021.

Bowen Zhang, Yidong Wang, Wenxin Hou, Hao Wu, Jindong Wang, Manabu Okumura, and Takahiro Shinozaki. Flexmatch: Boosting semi-supervised learning with curriculum pseudo labeling. *Advances in Neural Information Processing Systems*, 34, 2021.

Feng Zhang, Xiatian Zhu, Hanbin Dai, Mao Ye, and Ce Zhu. Distribution-aware coordinate representation for human pose estimation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 7093–7102, 2020a.

Zhe Zhang, Chunyu Wang, Wenhu Qin, and Wenjun Zeng. Fusing wearable imus with multi-view images for human pose estimation: A geometric approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2200–2209, 2020b.