A Cognitive-inspired Multi-Module Architecture for Continual Learning

Abstract

Artificial neural networks (ANNs) exhibit a narrow scope of expertise on stationary independent data. However, data in the real world is continuous and dynamic, and ANNs must adapt to novel scenarios while also retaining the learned knowledge to become lifelong learners. The ability of humans to excel at these tasks can be attributed to multiple factors ranging from cognitive computational structures, cognitive biases, and the multi-memory systems in the brain. We incorporate key concepts from each of these to design a cognitive-inspired continual learning method. *Cognitive Continual Learner (CCL)* includes multiple modules, implicit and explicit knowledge representation dichotomy, inductive bias, and a multi-memory system. CCL shows improvement across all continual learning settings and also exhibits reduced task recency bias. To test versatility of continual learning methods on a challenging distribution shift, we introduce a novel domain-incremental dataset $Domain^2IL$. In addition to improved performance on existing benchmarks, CCL also demonstrates superior performance on this dataset.[1]

1 Introduction

Deep learning has seen rapid progress in recent years, and supervised learning agents have achieved superior performance in perception tasks. However, unlike a supervised setting, where data is static, and independent and identically distributed, real-world data is changing dynamically. Continual learning (CL) aims at learning multiple tasks when data is streamed sequentially (Parisi et al., 2019). This is crucial in real-world deployment settings, as the model needs to adapt quickly to novel data (plasticity), while also retaining previously learned knowledge (stability). Artificial neural networks (ANN), however, are still not effective continual learners as they often fail to generalize to small changes in distribution and also suffer from forgetting old information when presented with new data (catastrophic forgetting)(McCloskey & Cohen, 1989).

Humans, on the other hand, show a better ability to acquire new skills while also retaining previously learned skills to a greater extent. This intelligence can be attributed to different factors in human cognition. Multiple theories have been proposed to formulate an overall cognitive architecture, which is a broad domain-generic cognitive computation model that captures the essential structure and process of the mind. Some of these theories hypothesize that, instead of a single standalone module, multiple modules in the brain share information to excel at a particular task. CLARION (Connectionist learning with rule induction online) (Sun & Franklin, 2007) is one such theory that postulates an integrative cognitive architecture, consisting of a number of distinct subsystems. It predicates a dual representational structure (Chaiken & Trope, 1999), where the top level encodes conscious explicit knowledge, while the other encodes indirect implicit information. The two systems interact and share knowledge, and cooperate in solving tasks. Delving into these underlying architectures and formulating a new design can help in the quest of building intelligent agents.

Multiple modules can be instituted instead of a single feedforward network. An explicit module that learns from the standard visual input and an implicit module that shares indirect contextual knowledge. The implicit module can be further divided into more sub-modules, each providing different information. Inductive biases and semantic memories can act as different kinds of implicit knowledge. Inductive biases are pre-stored templates or knowledge that provide some meaningful disposition towards adapting to the continuously evolving world (Chollet, 2019). Furthermore,

---

[1]Code and the $Domain^2IL$ dataset will be made accessible upon acceptance.

theories (Kumaran et al., 2016) postulate that after rapidly learning information, a gradual consolidation of knowledge transpires in the brain for slow learning of structured information. Thus, the new design incorporates multiple concepts of cognition architectures, the dichotomy of implicit and explicit representations, inductive biases, and multi-memory systems theory.

To this end, we propose *Cognitive Continual Learner* (CCL), a multi-module architecture for CL. The explicit working module processes the standard input data. Two different sub-modules are introduced for the implicit module. The inductive bias learner embeds relevant prior information, and as networks are shown to be biased toward textural information (unlike humans that are more biased toward global semantics)(Geirhos et al., 2018), we propose to utilize the global shape information as the prior. Shape is already present in the visual data but in an indirect way, and extracting this implicit information and sharing with the explicit module will help to learn more generic and high-level representations. Further, to emulate the consolidation of information in the slow-fast multi-memory system, a gradual accumulation of knowledge from the explicit working module is embedded in the second semantic memory sub-module. We show that interacting and leveraging information between these modules can help alleviate catastrophic forgetting, while also increasing the robustness to distribution shift.

CCL achieves superior performance across all CL settings on various datasets. CCL outperforms the SOTA CL methods on Seq-CIFAR10, Seq-CIFAR100 in the class incremental settings. Furthermore, in more realistic general class incremental settings where the task boundary is blurry and classes are not disjoint, CCL shows significant gains. The addition of inductive bias and semantic memory helps to achieve a better balance between the plasticity-stability trade-off. The prior in the form of shape helps produce generic representations, and this results in CCL exhibiting a reduced task-recency bias. Furthermore, CCL also shows higher robustness against natural corruptions. Finally, to test the capability of the CL methods against distribution shift, we introduce a domain incremental learning dataset, $Domain^2IL$, which is a carefully designed subset of the DomainNet dataset (Peng et al., 2019). CCL shows considerable robustness across all domains on these challenging data, thus establishing the efficacy of our cognitive-inspired CL architecture. Our contributions are as follows:

- *Cognitive Continual Learner (CCL)*, a novel method that incorporates aspects of cognitive architectures, multi-memory systems, and inductive bias into the CL framework.
- Introducing $Domain^2IL$, a challenging domain incremental learning dataset for CL.
- Benchmarks across different CL settings: class incremental, task incremental, generalized class incremental, and domain incremental learning.
- Analyses on the plasticity-stability trade-off, task recency bias, and robustness to natural corruptions.

2 METHODOLOGY

2.1 COGNITIVE ARCHITECTURES

Cognitive architectures refer to computational models that encapsulate the overall structure of the cognitive process in the brain. The underlying infrastructure of such a model can be leveraged to develop better intelligent systems. Global workspace theory (GWT) (Juliani et al., 2022) postulates that human cognition is composed of a multitude of special-purpose processors and is not a single standalone module. Different sub-modules might encode different contextual information which, when activated, can transfer knowledge to the conscious central workspace to influence and help make better decisions. Furthermore, CLARION (Sun & Franklin, 2007) posits a dual-system cognitive architecture with two levels of knowledge representation. The explicit module encodes direct knowledge that is externally accessible. The implicit module encodes indirect knowledge that is not directly accessible, but can be obtained through some intermediate interpretive or transformational steps. These two modules interact with each other by transferring knowledge between each other.

Inspired by these theories, we formulate a method that incorporates some of the key aspects of cognitive architecture into the CL method. A working module, which encodes the direct sensory data, forms the explicit module. A second module that encodes indirect and interpretive information forms the implicit module. The implicit module further includes multiple sub-modules to encode different types of knowledge.

Figure 1: Schematic of *Cognitive Continual Learner (CCL)*. The working model in explicit module learns direct sensory data. Within the implicit module, the inductive bias learner encodes the prior shape knowledge and the semantic memory consolidates information from the explicit module.

2.2 INDUCTIVE BIAS

The sub-modules in the implicit module need to encapsulate implicit information that can provide more contextual and high-level supervision. One of such knowledge can be prior knowledge or inductive bias. Inductive biases are prestored templates that exist implicitly even in earlier stages of the human brain (Pearl & Mackenzie, 2018). For instance, cognitive inductive bias may be one of the reasons why humans can focus on the global semantics of objects to make predictions ANNs, on the other hand, are more prone to rely on local cues and textures (Geirhos et al., 2018). Global semantics or shape information already exists in the visual data, but in an indirect way. Hence, we utilize shape as indirect information in the implicit module. The sub-module uses a transformation step to extract the shape and share this inductive bias with the working module. As the standard (RGB) image and its shape counterpart can be viewed as different perspectives/modalities of the same data, ensuring that the representation of one modality is consistent with the other increases robustness to spurious correlations that might exist in only one of them.

2.3 MULTI MEMORY SYSTEM

Moreover, many theories have postulated that an intelligent agent must possess deferentially specialized learning memory systems (Kumaran et al., 2016). While one system rapidly learns the individual experience, the other gradually assimilates the knowledge. To emulate this behavior, we establish a second sub-module that slowly consolidates the knowledge from the working module.

2.4 FORMULATION

To this end, we propose a novel method *Cognitive Continual Learner (CCL)*, which incorporates all these concepts into the CL paradigm. CCL consists of two modules, the explicit module and the implicit module. The explicit module has a single working model and processes the incoming direct visual data. The implicit module further consists of two sub-modules, namely the inductive bias learner and the semantic memory. They share relevant contextual information and assimilated knowledge with the explicit module, respectively. Figure 1 shows the overall architecture.

In the implicit module, semantic memory N_{SM}, consolidates knowledge at stochastic intervals from the working model N_{WM}, in the explicit module. The other sub-module, the inductive bias learner

N_{IBL}, processes the data and extracts the shape information. N_{WM} processes the RGB data, N_{SM} consolidates the information from the working module at an update frequency in a stochastic manner, and N_{IBL} learns from the shape data. f represents the combination of the encoder and the classifier, and θ_{WM}, θ_{SM}, and θ_{IBL} are the parameters of the three networks.

A CL classification consists of a sequence of T tasks and, during each task $t \in 1, 2...T$, samples x_c and their corresponding labels y_c are drawn from the current task data D_t. Furthermore, for each subsequent task, a random batch of exemplars is sampled from episodic memory B as x_b. An inductive bias (shape) filter is applied to generate shape samples, $x_{c_s} = \mathbb{IB}(x_c)$ and $x_{b_s} = \mathbb{IB}(x_b)$. Reservoir sampling (Vitter, 1985) is incorporated to replay the previous samples. Each of the networks N_{WM} and N_{IBL} learns on its own modality with supervised cross-entropy loss on both the current samples and the buffer samples.

$$\mathcal{L}_{Sup_{WM}} = \mathcal{L}_{CE}(f(x_c; \theta_{WM}), y_c) + \mathcal{L}_{CE}(f(x_b; \theta_{WM}), y_b) \tag{1}$$

$$\mathcal{L}_{Sup_{IBL}} = \mathcal{L}_{CE}(f(x_{c_s}; \theta_{IBL}), y_c) + \mathcal{L}_{CE}(f(x_{b_s}; \theta_{IBL}), y_b) \tag{2}$$

The Knowledge Sharing (KS) objectives are designed to transfer and share information between all modules. KS occurs for both current samples and buffered samples. To provide shape supervision to the working model, a decision space similarity constraint ($\mathcal{L}_{IKS}$) is enforced to align the features of the two modules. Similarly, the inductive bias learner receives a similarity constraint ($\mathcal{L}_{EKS}$) from the working model to further align the two models. We employ the mean squared error as the objective function for all KS losses.

$$\mathcal{L}_{IKS} = \mathop{\mathbb{E}}_{x_c \sim D_t} \|f(x_{c_s}; \theta_{IBL}) - f(x_c; \theta_{WM})\|_2^2 \tag{3}$$

$$\mathcal{L}_{EKS} = \mathop{\mathbb{E}}_{x_c \sim D_t} \|f(x_c; \theta_{WM}) - f(x_{c_s}; \theta_{IBL})\|_2^2 \tag{4}$$

Consolidated information in the semantic memory is transferred to both N_{WM} and N_{IBL}, by aligning the output space on the buffer samples, which further helps in information retention. The structural knowledge from N_{SM} is distilled into the working model ($\mathcal{L}_{SKS}$) and the inductive bias learner ($\mathcal{L}_{SKD}$).

$$\mathcal{L}_{SKS} = \mathop{\mathbb{E}}_{x_b \sim B} \|f(x_b; \theta_{SM}) - f(x_b; \theta_{WM})\|_2^2 \tag{5}$$

$$\mathcal{L}_{SKD} = \mathop{\mathbb{E}}_{x_b \sim B} \|f(x_b; \theta_{SM}) - f(x_{b_s}; \theta_{IBL})\|_2^2 \tag{6}$$

The overall loss functions for the working model and the inductive bias learner are as follows:

$$\mathcal{L}_{WM} = \mathcal{L}_{Sup_{WM}} + \lambda_{IKS}\mathcal{L}_{IKS} + \lambda_{SKS}\mathcal{L}_{SKS} \tag{7}$$

$$\mathcal{L}_{IBL} = \mathcal{L}_{Sup_{IBL}} + \lambda_{EKS}\mathcal{L}_{EKS} + \lambda_{SKD}\mathcal{L}_{SKD} \tag{8}$$

The other sub-module of the implicit module, semantic memory, is updated with a stochastic momentum update (SMU) from the weights of the working model at a rate of r with the decay factor of α, that is, $\theta_{SM} \leftarrow \mathcal{SMU}(\theta_{WM}; \alpha)$.

The semantic memory (N_{SM}) is used for all inference purposes. The complete method is detailed in Algorithm 1 in Appendix.

3 EXPERIMENTAL SETTINGS

ResNet-18 (He et al., 2016) architecture is used for all experiments. All networks are trained using the SGD optimizer with standard augmentations of random crop and random horizontal flip. The different hyperparameters, tuned per dataset, are provided in Appendix, Table S1. The different CL settings are explained in detail in Section B. We consider Seq-CIFAR10 and Seq-CIFAR100 (Krizhevsky et al., 2009) for the class incremental learning (Class-IL) settings, which are divided into 5 tasks each. We evaluate General Class-IL (GCIL) (Mi et al., 2020) on CIFAR100 dataset. For domain incremental learning (Domain-IL), we propose a novel dataset, *Domain^{2}IL*.

Table 1: Comparison of different methods on standard CL benchmarks (Class-IL, Task-IL and GCIL settings). CCL shows a consistent improvement over all methods for both buffer sizes.

$|\mathcal{B}|$	Method	Seq-CIFAR10		Seq-CIFAR100		GCIL-CIFAR100	
		Class-IL	Task-IL	Class-IL	Task-IL	Uniform	Longtail
-	JOINT	$92.20_{\pm0.15}$	$98.31_{\pm0.12}$	$70.62_{\pm0.64}$	$86.19_{\pm0.43}$	$60.45_{\pm1.65}$	$60.10_{\pm0.42}$
	SGD	$19.62_{\pm0.05}$	$61.02_{\pm3.33}$	$17.58_{\pm0.04}$	$40.46_{\pm0.99}$	$10.36_{\pm0.13}$	$9.62_{\pm0.21}$
200	ER	$44.79_{\pm1.86}$	$91.19_{\pm0.94}$	$21.40_{\pm0.22}$	$61.36_{\pm0.39}$	$16.52_{\pm0.10}$	$16.20_{\pm0.30}$
	DER++	$64.88_{\pm1.17}$	$91.92_{\pm0.60}$	$29.60_{\pm1.14}$	$62.49_{\pm0.78}$	$27.73_{\pm0.93}$	$26.48_{\pm2.04}$
	Co^2L	$65.57_{\pm1.37}$	$93.43_{\pm0.78}$	$31.90_{\pm0.38}$	$55.02_{\pm0.36}$	-	-
	ER-ACE	$62.08_{\pm1.44}$	$92.20_{\pm0.57}$	$32.49_{\pm0.95}$	$59.77_{\pm0.31}$	$27.64_{\pm0.76}$	$25.10_{\pm2.64}$
	CLS-ER	$66.19_{\pm0.75}$	$93.90_{\pm0.60}$	$43.80_{\pm1.89}$	$73.49_{\pm1.04}$	$35.88_{\pm0.41}$	$35.67_{\pm0.72}$
	CCL	$\mathbf{70.04_{\pm1.07}}$	$\mathbf{94.49_{\pm0.38}}$	$\mathbf{46.55_{\pm1.51}}$	$\mathbf{76.66_{\pm0.41}}$	$\mathbf{39.61_{\pm0.70}}$	$\mathbf{38.94_{\pm0.16}}$
500	ER	$57.74_{\pm0.27}$	$93.61_{\pm0.27}$	$28.02_{\pm0.31}$	$68.23_{\pm0.16}$	$23.62_{\pm0.66}$	$22.36_{\pm1.27}$
	DER++	$72.70_{\pm1.36}$	$93.88_{\pm0.50}$	$41.40_{\pm0.96}$	$70.61_{\pm0.11}$	$35.80_{\pm0.62}$	$34.23_{\pm1.19}$
	Co^2L	$74.26_{\pm0.77}$	$95.90_{\pm0.26}$	$39.21_{\pm0.39}$	$62.98_{\pm0.58}$	-	-
	ER-ACE	$68.45_{\pm1.78}$	$93.47_{\pm1.00}$	$40.67_{\pm0.06}$	$66.45_{\pm0.71}$	$30.14_{\pm1.11}$	$31.88_{\pm0.73}$
	CLS-ER	$75.22_{\pm0.71}$	$94.94_{\pm0.53}$	$51.40_{\pm1.00}$	$78.12_{\pm0.24}$	$38.94_{\pm0.38}$	$38.79_{\pm0.67}$
	CCL	$\mathbf{76.20_{\pm0.70}}$	$\mathbf{95.95_{\pm0.14}}$	$\mathbf{53.23_{\pm1.62}}$	$\mathbf{80.12_{\pm0.18}}$	$\mathbf{44.25_{\pm0.21}}$	$\mathbf{42.75_{\pm0.18}}$

4 RESULTS

We provide a comparison of our method with standard baselines and multiple other SOTA CL methods. The lower and upper bounds are reported as SGD (standard training) and JOINT (training all tasks together), respectively. We compare with other rehearsal-based methods in the literature, namely ER, DER (Buzzega et al., 2020), Co^2L (Cha et al., 2021), ER-ACE (Caccia et al., 2021) and CLS-ER (Arani et al., 2021). Table 1 shows the average performance in different settings over three seeds. Co^2L utilizes task boundary information, and therefore the GCIL setting is not applicable. The results are taken from the original papers and, if not available, using the original codes, we conducted a hyperparameter search for the new settings.

CCL achieves the best performance across all datasets in all settings. In the challenging Class-IL setting, we observe a gain of $\sim$50% over DER++, thus showing the efficacy of adding multiple modules to CL. Furthermore, we report improvements of $\sim$6% on both the Seq-CIFAR10 and -CIFAR100 datasets, over CLS-ER, which utilizes two memories in its design. CCL has a single semantic memory, and the additional boost is procured by prior knowledge from the inductive bias learner. Improvement is prominent even when the memory budget is low (200 buffer size). GCIL represents a more realistic setting, as the task boundaries are blurry, and classes can reappear and overlap in any task. GCIL-Longtail version also introduces an imbalance in the sample distribution. CCL shows a significant improvement on both versions of GCIL-CIFAR100. Shape information from the inductive bias learner offers the global high-level context, which helps in producing generic representations that are not biased towards learning only the current task at hand. Furthermore, sharing of the knowledge that has been assimilated through the appearance of overlapping classes through the training scheme, further facilities learning in this general setting. The overall results indicate that the dual knowledge sharing between the explicit working module and the implicit inductive bias and semantic memory modules enables both better adaptation to new tasks and information retention.

5 DOMAIN INCREMENTAL LEARNING

Intelligent agents deployed in real-world applications need to maintain consistent performance through changes in the data and environment. Domain-IL aims to assess the robustness of the CL methods to the distribution shift. In Domain-IL, the classes in each task remain the same, but the input distribution changes, and this makes for a more plausible use case for evaluation. However, the datasets used in the literature do not fully reflect this setting. For instance, the most common datasets used in the literature are different variations (Rotated and Permuted) of the MNIST dataset (LeCun

Figure 2: Accuracy (left) and plasticty-stability analysis (right) on *Domain²IL* dataset. CCL substantially outperforms other methods and demonstrates a better plasticity-stability trade-off.

et al., 1998). MNIST is a simple dataset, usually evaluated on MLP networks, and its variations do not reflect the real-world distribution shift challenges that a CL method faces. As is evident from the performances of different CL methods in the literature, the improvement in performance on all variants of MNIST has been saturated. Farquhar & Gal (2018) propose fundamental desiderata for CL evaluations and datasets based on real-world use cases. One of the criteria is to possess cross-task resemblances, which Permuted-MNIST clearly violates. Thus, a different dataset is needed to test the overall capability of a CL method to handle the distributional shift.

5.1 DOMAIN²IL DATASET

To this end, we propose *Domain²IL* (DomainNet for Domain-IL), which is a well-crafted subset of the standard DomainNet dataset (Peng et al., 2019), used in domain adaptation. DomainNet consists of common objects in six different domains - real, clipart, infograph, painting, quickdraw, and sketch. The original DomainNet consists of $59k$ samples with 345 classes in each domain. The classes have redundancy, and moreover, evaluating the whole dataset can be computationally expensive in a CL setting. Considering different criteria such as the relevance of classes, uniform sample distribution, computational complexity, and ease of benchmarking for CL, we create the version *Domain²IL*, which is tailor-made for continual learning.

All classes were grouped into semantically similar super categories. Out of these, a subset of classes was selected that had relevance to domain shift while also having maximum overlap with other standard datasets such as CIFAR-10 and CIFAR-100, as this can facilitate in performing out-of-distribution analyses. 20 supercategories were chosen with 5 classes each (resulting in a total of 100 classes). In addition, to provide a balanced dataset, we performed a class-wise sampling. First, we sample images per class in each supercategory and maintain class balance. Second, we choose samples per domain, so that it results in a dataset that has a near-uniform distribution across all classes and domains. The final dataset *Domain²IL* is succinct, more balanced, and more computationally efficient for benchmarking, thus facilitating research in CL. Additionally, the new dataset deems more plausible for real-world settings and also adheres to all the evaluation desiderata by (Farquhar & Gal, 2018). The challenging distribution shift between domains provides an apt dataset to test the capability of CL methods in the Domain-IL setting. More details, statistics, and visual examples of this crafted dataset are provided in Section D.

5.2 DOMAIN²IL PERFORMANCE

Figure 2 (left) reports the results on *Domain²IL* for two different buffer sizes (Values are provided in Table S3). CCL shows a considerable performance gain in the average accuracy across all domains and can be primarily attributed to the supervision from the shape data. Standard networks tend to exhibit texture bias and learn background or spurious cues (Geirhos et al., 2018) that result in performance degradation when the distribution changes. Learning global shape information of objects, on the other hand, helps in learning generic features that can translate well to other distributions. Semantic memory further helps to consolidate information across domains. Maintaining consistent

Figure 3: Task-wise performance on *Domain²IL* ($|\mathcal{B}|$=500), where each task represents a domain. CCL shows more retention of old information without compromising much on current accuracy.

performance to such difficult distribution shift proves beneficial in real-world applications, and the proficiency of CCL in this setting can thus open up new avenues for research in cognition-inspired multi-module architectures.

6 ANALYSIS

6.1 PLASTICITY-STABILITY TRADE-OFF

Plasticity refers to the capability of a model to learn new tasks, while stability shows how well it can retain old information. The plasticity-stability dilemma is a long-standing problem in CL, which requires an optimal balance between the two. We measure each of these to assess the competence of the CL methods. Plasticity is computed as the average performance of each task when it is first learned (e.g., the accuracy of the network trained on task $T2$, evaluated on the test set of $T2$). Stability is computed as the average performance of all tasks $1{:}T$-1, after learning the final task T. Figure 2 (right) reports these numbers for the *Domain²IL* dataset. As seen, ER and DER methods exhibit forgetting and show low stability and concentrate only on the newer tasks. CLS-ER shows higher stability, but at the cost of reduced plasticity. However, CCL shows the highest stability while also maintaining comparable plasticity. The shape knowledge in CCL helps in learning generic solutions that can translate to new tasks while the semantic consolidation update at stochastic rates acts as a regularization to maintain stable parameter updates. Thus, CCL strikes a better balance between plasticity and stability.

6.2 TASK-WISE PERFORMANCE

The average accuracy across all tasks does not provide a complete measure of the ability of a network to retain old information while learning new tasks. To better represent the plasticity-stability measure, we report the task-wise performance at the end of each task. After training each task, we measure the accuracy on the test set of each of the previous tasks. Figure 3 reports this for all tasks of *Domain²IL*. The last row represents the performance of each task after the training is complete. ER and DER++ show performance degradation on earlier tasks, as the model continues training on newer tasks. Both perform well on the last task and display the lowest stability. CCL reports the highest information retention on older tasks, while also maintaining plasticity. For example, accuracy on the first task (real) reduces to 27.6 on ER after training all 6 tasks (domains), while CCL maintains accuracy of 54.9. CLS-ER shows better retention of old information but at the cost of plasticity. The last task on CLS-ER shows lower performance compared to CCL (52.1 vs. 61.0). Similar trend (with more gains) is seen on Seq-CIFAR10 dataset in Appendix Figure S2. The performance of the current task in CCL is relatively lesser and can be attributed to the stochastic update rate of this model.

To shed more light on the performance of each of the modules in CCL, we also provide the performance of the working model and the inductive bias learner, in Appendix Figure S1. The working model displays better plasticity, while CCL (semantic memory) displays better stability. Overall, all the modules in the proposed approach present unique attributes that improve the learning process and improve performance and reduce catastrophic forgetting.

Figure 4: CCL shows reduced task recency bias (left), as well as higher robustness against natural corruption (right) on Seq-CIFAR10 ($|\mathcal{B}|$=200) dataset.

6.3 RECENCY-BIAS ANALYSIS

Recency bias is a behavior in which the model predictions tend to be biased toward the current or the most recent task (Wu et al., 2019). This is undesirable in a CL model, as it results in a biased solution that forgets the old tasks. To this end, after the end of the training, we evaluate the models on the test set (of all tasks) and calculate the probability of predicting each task. The output distribution for each test sample is computed over all the classes, and the probabilities are averaged per task.

Figure 4 (left) shows the probabilities for each task on Seq-CIFAR10 dataset. As shown, ER and DER++ methods tend to incline most of their predictions towards the classes seen in the last task, thus creating a misguided bias. CCL shows a lesser bias compared to both of these baselines. CLS-ER exhibits reduced bias due to the presence of multiple memories, but the distribution is still relatively skewed (w.r.t probability of 0.2). CCL shows more of a uniform distribution across all tasks. The dual information from the shape data and the consolidated knowledge across tasks helps in breaking away from the Occam's razor pattern of neural networks to default to the easiest solution.

6.4 ROBUSTNESS

Lifelong agents, when deployed in real-world settings, need to be resistant to various factors, such as lighting conditions, changes in weather, and other digital imaging effects. Inconsistency in predictions under different conditions might result in undesirable outcomes, especially in safety-critical applications like autonomous driving. To measure the robustness of the CL method against such natural corruptions, we created a dataset by applying fifteen different corruptions (Table S2), at varying levels of severity (1- least severe to 5- most severe corruption).

The performances on the fifteen corruptions are averaged at each severity level and are shown in Figure 4 (right). CCL outperforms all other techniques at all severity levels. ER, DER++, and CLS-ER show a fast decline in accuracy as severity increases, while CCL maintains stable performance throughout. Implicit shape information provides a different perspective of the same data to the model that helps to generate high-level and robust representations. CCL, along with improved continual learning performance, also exhibits improved robustness to corruptions, thus proving a better candidate for deployment in real-world applications.

6.5 ABLATION STUDY

CCL architecture comprises multiple components, each contributing to the efficacy of the method. The explicit module has the working model, and the implicit module has the semantic memory (SM) and the inductive bias learner (IBL). Furthermore, the sharing of knowledge transpires for both current and buffer samples. Disentangling different components in the CCL, can provide more insights into the contribution of each of them to the overall performance.

Table 2 reports the ablation study w.r.t to each of these components on both Seq-CIFAR10 and *Domain²IL* datasets. On Seq-CIFAR10, semantic memory holds a vital position, as consolidation

Table 2: Ablation to analyse the effect of each component of CCL on Seq-CIFAR10 and $Domain^2IL$.

SM	IBL	KS $\mathcal{L}_{WM} \leftrightarrow \mathcal{L}_{IBL}$	Seq-CIFAR10		Domain^{2}IL	
			Acc (WM)	Acc (SM)	Acc (WM)	Acc (SM)
✓	✓	✓	$67.80_{\pm 0.80}$	$\mathbf{70.04}_{\pm 1.07}$	$37.96_{\pm 0.66}$	$\mathbf{44.23}_{\pm 0.05}$
✗	✓	✓	$64.61_{\pm 1.22}$	-	$37.33_{\pm 0.01}$	-
✓	✗	-	$65.03_{\pm 0.76}$	$69.21_{\pm 1.46}$	$35.48_{\pm 0.45}$	$39.76_{\pm 0.56}$
✓	✓	✗	$64.59_{\pm 1.06}$	$69.28_{\pm 1.34}$	$35.93_{\pm 0.50}$	$40.35_{\pm 0.34}$

across tasks at slower frequency rates helps in retention. Shape information plays a prominent role in Domain-IL setting, as the networks need to learn the global semantics of the objects, rather than background or spurious textural information to translate performance across domains. Furthermore, knowledge transfer between explicit and implicit modules on current experiences also plays a key role in performance gain. The knowledge distillation from the semantic memory on the buffer sample along with the knowledge sharing between the working model and inductive bias learner helps in the overall learning process.

7 RELATED WORKS

Rehearsal-based approaches, which revisit examples from the past to alleviate catastrophic forgetting, have been effective in challenging CL scenarios (Farquhar & Gal, 2018). Experience Replay (ER) (Riemer et al., 2018) methods use episodic memory to retain previously seen samples for replay purposes. DER++ (Buzzega et al., 2020) adds a consistency loss on logits, in addition to the ER strategy. CO^{2}L (Cha et al., 2021) uses contrastive learning from the self-supervised learning domain to generate transferable representations. ER-ACE (Caccia et al., 2021) targets the representation drift problem in online CL and devices a technique to use separate losses for current and buffer samples. All of these methods limit the architecture to a single stand-alone network, contrary to the biological workings of the brain. CLS-ER (Arani et al., 2021) proposed a multi-network approach that emulates fast and slow learning systems by using two semantic memories, each aggregating weights at different times. Though CLS-ER utilizes the multi-memory design, sharing of different kinds of knowledge is not leveraged, and hence presents a method with limited scope. CCL digresses from the standard architectures and proposed a multi-module design that is inspired by the cognitive computational architectures. It incorporates multiple sub-modules, each sharing different knowledge to develop an effective continual learner that has better generalization and robustness.

8 CONCLUSION

We introduced a novel framework for continual learning which incorporates concepts inspired by cognitive architectures, high-level cognitive biases, and the multi-memory system. Our method, *Cognitive Continual Learner (CCL)*, includes multiple subsystems with dual knowledge representation. CCL designed a dichotomy of explicit and implicit modules where information is selected, maintained, and shared with each other, to enable better generalization and robustness. CCL outperformed on Seq-CIFAR10 and Seq-CIFAR100 on the Class-IL setting. In addition, it also showed significant gain in the more realistic and challenging GCIL setting. Through different analyses, we showed the better plasticity-stability balance achieved by CCL. Furthermore, shape prior and knowledge consolidation helps in learning more generic solutions, indicated by the reduced task recency bias problem and higher robustness against natural corruptions. Furthermore, we introduced a challenging domain-IL dataset, *Domain^{2}IL*, with six disparate domains. The significant improvement of CCL on this complex distribution shift exposits the benefits of shape context, which helps the network converge on a generic solution, rather than a simple texture-biased one. In general, incorporating a design inspired by the cognitive model and sharing information between explicit and implicit inductive bias and implicit semantic memory modules, instead of a standalone network, helps enhance lifelong learning, while also improving generalization and robustness.

REFERENCES

Elahe Arani, Fahad Sarfraz, and Bahram Zonooz. Learning fast, learning slow: A general continual learning method based on complementary learning system. In *International Conference on Learning Representations*, 2021.

Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. *Advances in neural information processing systems*, 33:15920–15930, 2020.

Lucas Caccia, Rahaf Aljundi, Nader Asadi, Tinne Tuytelaars, Joelle Pineau, and Eugene Belilovsky. New insights on reducing abrupt representation change in online continual learning. In *International Conference on Learning Representations*, 2021.

Hyuntak Cha, Jaeho Lee, and Jinwoo Shin. Co2l: Contrastive continual learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9516–9525, 2021.

Shelly Chaiken and Yaacov Trope. *Dual-process theories in social psychology*. Guilford Press, 1999.

François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

Sebastian Farquhar and Yarin Gal. Towards robust evaluations of continual learning. 2018.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Arthur Juliani, Kai Arulkumaran, Shuntaro Sasai, and Ryota Kanai. On the link between conscious function and general intelligence in humans and machines. *arXiv preprint arXiv:2204.05133*, 2022.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Dharshan Kumaran, Demis Hassabis, and James L McClelland. What learning systems do intelligent agents need? complementary learning systems theory updated. *Trends in cognitive sciences*, 20 (7):512–534, 2016.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pp. 109–165. Elsevier, 1989.

Fei Mi, Lingjing Kong, Tao Lin, Kaicheng Yu, and Boi Faltings. Generalized class incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 240–241, 2020.

German I Parisi, Ronald Kemker, Jose L Part, Christopher Kanan, and Stefan Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54–71, 2019.

Judea Pearl and Dana Mackenzie. *The book of why: the new science of cause and effect*. Basic books, 2018.

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 1406–1415, 2019.

Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference. In *International Conference on Learning Representations*, 2018.

Ron Sun and Stan Franklin. Computational models of consciousness: A taxonomy and some examples., 2007.

Jeffrey S Vitter. Random sampling with a reservoir. *ACM Transactions on Mathematical Software (TOMS)*, 11(1):37–57, 1985.

Yue Wu, Yinpeng Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 374–382, 2019.

A APPENDIX

A.1 CCL

Figure S1 presents the task-wise performance of all the three networks in the CCL architecture, on $Domain^2IL$ dataset. Semantic memory helps in information retention by maintaining high accuracy on older tasks and is more stable. The performance of the current task is relatively lower than that of the working model and could be due to the stochastic update rate of this model. The working model has better performance on new tasks and is more plastic. Inductive bias leaner is evaluated on the transformed data (shape) and also achieves a balance between plasticity and stability. In general, all modules in our proposed method present unique attributes that improve the learning process by improving performance and reducing catastrophic forgetting.

Figure S1: Task probability analysis of all CCL components on $Domain^2IL$ dataset with 500 buffer size. Semantic memory displays better stability while working model displays better plasticity.

Figure S2 presents a similar analysis on the Seq-CIFAR10 dataset. The trend is similar, but the performance gain is much higher on this dataset.

Figure S2: Task probability analysis on Seq-CIFAR10 dataset with 200 buffer size. Semantic memory shows better stability while working model shows better plasticity.

A.1.1 CCL ALGORITHM

Algorithm 1 Cognitive Continual Learner (CCL)

    Input: Dataset $\mathcal{D}_t$, Buffer $\mathcal{B}$
    Initialize: Three networks: Encoder and classifier f parameterized by θ_{WM}, θ_{SM}, and θ_{IBL}
1: **for** all tasks $t \in 1, 2...T$ **do**
2:     Sample mini-batch: $(x_c, y_c) \sim \mathcal{D}_t$
3:     Extract shape images: $x_{c_s} = \mathbb{B}(x_c)$ where $\mathbb{B}$ is a Sobel filter
4:     $\mathcal{L}_{Sup_{WM}} = \mathcal{L}_{CE}(f(x_c; \theta_{WM}), y_c)$
5:     $\mathcal{L}_{Sup_{IBL}} = \mathcal{L}_{CE}(f(x_{c_s}; \theta_{IBL}), y_c)$
6:     Knowledge sharing between explicit working model and implicit inductive bias learner:
7:     $\mathcal{L}_{IKS} = \underset{x_c \sim D_t}{\mathbb{E}} \|f(x_{c_s}; \theta_{IBL}) - f(x_c; \theta_{WM})\|_2^2$
8:     $\mathcal{L}_{EKS} = \underset{x_c \sim D_t}{\mathbb{E}} \|f(x_c; \theta_{WM}) - f(x_{c_s}; \theta_{IBL})\|_2^2$
9:     **if** $\mathcal{B} \neq \emptyset$ **then**
10:       Sample mini-batch: $(x_b, y_b, z_{wm}, z_{ibl}) \sim \mathcal{B}$
11:       $x_{b_s} = \mathbb{B}(x_b)$
12:       $\mathcal{L}_{Sup_{WM}} \mathrel{+}= \mathcal{L}_{CE}(f(x_b; \theta_{WM}), y_b)$
13:       $\mathcal{L}_{Sup_{IBL}} \mathrel{+}= \mathcal{L}_{CE}(f(x_{b_s}; \theta_{IBL}), y_b)$
14:       Knowledge transfer from implicit semantic memory to the explicit working model:
15:       $\mathcal{L}_{SKS} = \mathbb{E}\|f(x_b; \theta_{SM}) - f(x_b; \theta_{WM})\|_2^2$
16:       Knowledge distillation between the implicit modules:
17:       $\mathcal{L}_{SKD} = \mathbb{E}\|f(x_b; \theta_{SM}) - f(x_{b_s}; \theta_{IBL})\|_2^2$
18:       Consistency loss between the logits of working model and inductive bias learner:
19:       $\mathcal{L}_{con_{WM}} = \mathbb{E}\|(z_b - h(x_b; \theta_{WM}))\|_2^2 \; ; \mathcal{L}_{con_{IBL}} = \mathbb{E}\|(z_{b_s} - h(x_{b_s}; \theta_{IBL}))\|_2^2$
20:     Update models θ_{WM} and θ_{IBL}
21:     Stochastically update semantic memory module θ_{SM}
22:     Update memory buffer $\mathcal{B}$
    return model θ_{SM}

B SETTING AND DATASETS

We evaluate the methods on different CL settings: class incremental (Class-IL), task incremental (Task-IL), domain incremental (Domain-IL) and general class incremental (GCIL). In Class-IL, each new task consists of novel classes, and the network must learn both new classes while retaining information about the old ones. Task-IL is similar to Class-IL, but assumes that the task labels are accessible both at training and inference. In Domain-IL, the classes remain the same for each task, but the distribution varies for each task. GCIL (Mi et al., 2020) represents a more realistic setting, where the number of classes in each task is not fixed and the classes can reappear with varying sample sizes. GCIL samples the number of classes and samples from a probabilistic distribution. The two variations are Uniform (fixed uniform sample distribution over all classes) and Longtail (with class imbalance).

All the experiment results are averaged over three seeds.

C HYPER-PARAMETERS

Different hyper-parameters chosen for CCL is shown in Table S1. For the new *Domain²IL* dataset, to maintain a fair comparison, we ran all the techniques (including CCL) using the TinyImageNet hyper-parameters reported in each of the methods.

D *Domain²IL*

We introduce a new dataset for the Domain-IL setting. It is a subset of the standard DomainNet dataset (Peng et al., 2019) used in domain adaptation. It consists of six different domains - real,

Table S1: CCL hyperparameters for all datasets.

	buffer	lr	batch size	#epochs	α	β	ema update	λ_{IKS}	λ_{EKS}	λ_{SKS}	λ_{SKD}
Seq-CIFAR10	200	0.03	32	50	0.1	0.5	0.2	0.1	0.1	0.1	0.1
	500	0.03	32	50	0.2	0.5	0.2	0.1	0.1	0.1	0.1
Seq-CIFAR100	200	0.03	32	50	0.1	0.5	0.06	0.1	0.01	0.1	0.01
	500	0.03	32	50	0.2	0.5	0.08	0.1	0.01	0.1	0.01
GCIL-CIFAR100	200	0.03	32	50	0.1	0.5	0.09	0.1	0.01	0.1	0.01
	500	0.03	32	50	0.1	0.5	0.2	0.1	0.01	0.1	0.01
Domain^{2}IL	200	0.03	32	50	0.1	1.0	0.06	0.1	0.01	0.1	0.01
	500	0.03	32	50	0.2	0.5	0.08	0.1	0.01	0.1	0.01

Table S2: Fifteen different natural corruptions

Corruptions	Gaussian Noise, Impulse Noise, Shot noise, Speckle noise
	Defocus blur, Glass blur, Motion blur, Zoom blur, Gaussian blur
	Brightness, Contrast, Fog, Frost, Snow
	Elastic Transformation, JPEG compression, Pixelate, Spatter, Saturate

clipart, infograph, painting, quickdraw, and sketch. The shift in distribution between domains is challenging. Few examples can be seen in Figure S3.

Each domain includes 345 classes, and the overall dataset consists of ∼59000 samples. The classes have redundancy, and also evaluating on the whole dataset can be computationally expensive for CL settings. Hence, we create a subset by grouping semantically similar classes into 20 super categories (by also considering class overlap between other standard datasets, which can facilitate in performing OOD analysis). Each super category has five classes each, which results in a total of 100 classes. The specifications of the classes are given in Table S4. The dataset consists of 67080 training images and 19464 test images. The image size for all experiments is chosen as 64×64 (the normalize transform is not applied in the augmentations).

Table S3: Accuracy on the proposed *Domain²IL* dataset for the Domain-IL setting. CCL shows a significant improvement in all disparate and challenging domains.

$|\mathcal{B}|$	Method	real	clipart	infograph	painting	sketch	quickdraw	Acc
-	SGD	$9.98_{\pm 0.54}$	$19.97_{\pm 0.31}$	$2.32_{\pm 0.20}$	$6.58_{\pm 0.34}$	$14.91_{\pm 0.04}$	$71.23_{\pm 0.17}$	$20.83_{\pm 0.24}$
200	ER	$20.08_{\pm 0.45}$	$26.37_{\pm 0.35}$	$5.56_{\pm 0.39}$	$13.92_{\pm 0.91}$	$23.69_{\pm 1.54}$	$69.95_{\pm 0.56}$	$26.59_{\pm 0.31}$
	DER++	$33.66_{\pm 1.65}$	$37.24_{\pm 0.64}$	$9.80_{\pm 0.63}$	$24.16_{\pm 1.17}$	$34.37_{\pm 2.00}$	$69.26_{\pm 0.79}$	$34.75_{\pm 0.87}$
	CLS-ER	$45.53_{\pm 0.88}$	$49.17_{\pm 1.12}$	$15.79_{\pm 0.48}$	$35.80_{\pm 0.64}$	$48.03_{\pm 0.85}$	$54.40_{\pm 1.25}$	$40.83_{\pm 1.07}$
	CCL	$47.52_{\pm 0.25}$	$54.69_{\pm 0.10}$	$15.70_{\pm 0.33}$	$37.54_{\pm 0.30}$	$51.98_{\pm 0.96}$	$58.80_{\pm 0.18}$	$\mathbf{44.23_{\pm 0.05}}$
500	ER	$27.54_{\pm 0.05}$	$31.89_{\pm 0.93}$	$7.89_{\pm 0.45}$	$19.39_{\pm 1.02}$	$28.36_{\pm 1.35}$	$70.96_{\pm 0.10}$	$31.01_{\pm 0.62}$
	DER++	$44.49_{\pm 1.39}$	$46.17_{\pm 0.35}$	$14.01_{\pm 0.23}$	$33.44_{\pm 0.90}$	$43.59_{\pm 1.11}$	$69.53_{\pm 0.29}$	$41.87_{\pm 0.63}$
	CLS-ER	$49.85_{\pm 0.88}$	$51.41_{\pm 0.34}$	$18.17_{\pm 0.08}$	$37.94_{\pm 0.94}$	$49.02_{\pm 1.57}$	$55.63_{\pm 0.71}$	$43.41_{\pm 0.80}$
	CCL	$54.77_{\pm 0.15}$	$60.37_{\pm 0.75}$	$19.35_{\pm 0.39}$	$44.50_{\pm 0.43}$	$56.34_{\pm 0.53}$	$60.61_{\pm 1.73}$	$\mathbf{49.32_{\pm 0.23}}$

Figure S3: Visual examples of *Domain²IL* dataset

Figure S4: Number of samples per domain in *Domain²IL* dataset.

Table S4: Details on supercategory and classes in *Domain²IL* dataset.

	supercategory	class				
1	small animals	mouse	squirrel	rabbit	dog	raccoon
2	medium animals	tiger	bear	lion	panda	zebra
3	large animals	camel	horse	kangaroo	elephant	cow
4	aquatic mammals	whale	shark	fish	dolphin	octopus
5	non-insect invertebrates	snail	scorpion	spider	lobster	crab
6	insects	bee	butterfly	mosquito	bird	bat
7	vehicle	bus	bicycle	motorbike	train	pickup_truck
8	sky-vehicle	airplane	flying_saucer	aircraft_carrier	helicopter	hot_air_balloon
9	fruits	strawberry	banana	pear	apple	watermelon
10	vegetables	carrot	asparagus	mushroom	onion	broccoli
11	music	trombone	violin	cello	guitar	clarinet
12	furniture	chair	dresser	table	couch	bed
13	household electrical devices	clock	floor_lamp	telephone	television	keyboard
14	tools	saw	axe	hammer	screwdriver	scissors
15	clothes & accessories	bowtie	pants	jacket	sock	shorts
16	man-made outdoor	skyscraper	windmill	house	castle	bridge
17	nature	cloud	bush	ocean	river	mountain
18	food	birthday_cake	hamburger	ice_cream	sandwich	pizza
19	stationary	calendar	marker	map	eraser	pencil
20	household items	wine_bottle	cup	teapot	frying_pan	wine_glass

Figure S5: Number of samples per supercategory for each domain in *Domain*^{2}*IL* dataset.

Figure S6: Number of samples per super category in *Domain²IL* dataset.

Figure S7: Number of overall samples per class in *Domain²IL* dataset.