HYPER-PARAMETER TUNING FOR FAIR CLASSIFICATION WITHOUT SENSITIVE ATTRIBUTE ACCESS

ABSTRACT

Fair machine learning methods seek to train models that balance model performance across demographic subgroups defined over sensitive attributes like race and gender. Although sensitive attributes are typically assumed to be known during training, they may not be available in practice due to privacy and other logistical concerns. Recent work has sought to train fair models without sensitive attributes on training data. However, these methods need extensive hyperparameter tuning to achieve good results, and hence assume that sensitive attributes are known on validation data. However, this assumption too might not be practical. Here, we propose a framework to train fair classifiers without access to sensitive attributes on either training or validation data. Instead, we generate pseudo sensitive attributes on the validation data by training a biased classifier and using the classifier's incorrectly (correctly) labeled examples as proxies for minority (majority) groups. Since fairness metrics like demographic parity, equal opportunity and subgroup accuracy can be estimated to within a proportionality constant even with noisy sensitive attribute information, we show theoretically and empirically that these proxy labels can be used to maximize fairness under average accuracy constraints. Key to our results is a principled approach to select the hyper-parameters of the biased classifier in a completely unsupervised fashion (meaning without access to ground truth sensitive attributes) that minimizes the gap between fairness estimated using noisy versus ground-truth sensitive labels.

1 INTRODUCTION

Deep neural networks have achieved state-of-the-art accuracy on many tasks including face recognition (Buolamwini & Gebru, 2018; Grother et al., 2010; Ngan & Grother, 2015), autonomous driving (Zhang et al., 2021; Chitta et al., 2021), medical image diagnosis (Litjens et al., 2017; Cheplygina et al., 2019), *etc*. But, prior work (Hovy & Søgaard, 2015; Oren et al., 2019; Hashimoto et al., 2018a) has found that state-of-the-art networks exhibit unintended biases towards specific population groups, especially harming minority groups. Seminal work by Buolamwini & Gebru (2018) demonstrated, for instance, that commercial face recognition systems had lower accuracy on darker skinned women than other groups. A body of work has sought to design fair machine learning algorithms that account for a model's performance on a per-group basis (Prost et al., 2019; Sagawa* et al., 2020; Liu et al., 2021; Sohoni et al., 2020).

Much of the prior work assume that demographic attributes like gender and race on which we seek to train a fair model, which we refer to as *sensitive attributes*, are available on training and validation data Sagawa* et al. (2020); Prost et al. (2019). However, in many real world settings, sensitive attributes may not be available due to privacy or other reasons. For example, the data subject may abstain from providing sensitive information to eschew potential discrimination in future (Markos et al., 2017). In other settings, the attributes on which the model discriminates might not even be known (Citron & Pasquale, 2014; Pasquale, 2015). For instance, in algorithmic hiring decisions, Köchling & Wehner (2020) highlight that bias and discrimination are recognized only after making real world decisions on applicants due to unknown attributes on which the model discriminates during training. Consequently, a large American e-commerce company had to cease using algorithmic tools for hiring purposes as it was unintentionally discriminating female applicants (Dastin, 2018).

Recent work seeks to train fair classifiers without access to sensitive attributes on the training set (Liu et al., 2021; Creager et al., 2021; Nam et al., 2020; Hashimoto et al., 2018a). The common theme across these methods is to up-weight misclassified examples either by splitting the training stage into two separate stages Liu et al. (2021) (identify mis-classified examples in stage 1 and upweight in stage 2) or by alternating between these stages across training epochs Nam et al. (2020) (identifying misclassified examples in one epoch and upweighting in the next). However, Liu et al. (2021) has shown that these methods are highly sensitive to choice of hyper-parameters; the up-weighting factor, for example, can have a large impact on the resulting model's fairness. Some methods, therefore, tune hyper-parameters assuming access to sensitive information on the validation dataset. In fact, without this information, Liu et al. (2021) observed that these methods sometimes do worse than using standard ERM. But, sensitive information on the validation dataset may not be available for the same reasons they are hard to acquire on training data.

In this paper, we propose Antigone, a simple, principled approach that enables hyper-parameter tuning for fairness without access to sensitive attributes on validation data. Antigone can be used to tune hyper-parameters for any prior method, for instance JTT (Liu et al., 2021), LfF (Nam et al., 2020), CVaR DRO (Hashimoto et al., 2018a), that trains fair models without sensitive attributes on training data, and for several fairness metrics including demographic parity, equal opportunity and worst sub-group accuracy.

Antigone builds on the same intuition as in prior work: mis-classified examples of a classifier trained with standard empirical risk serves as an effective proxy for minority groups. Accordingly, Antigone trains a *biased* classifier as a noisy sensitive attributes labeller on the validation data, labelling correctly and incorrectly classifier examples as majority and minority groups, respectively. But this raises a key question: *how do we select the hyper-parameters of the noisy labeler?*

Intuitively, to maximize utility of the noisily labelled validation set, we seek to maximize the fraction of minority (majority) samples in the incorrect (correct) sets. Since this cannot be measured directly, Antigone instead maximizes the distance between the data distributions of the two sets, which we measure using the Euclidean distance between the means (EDM) of the two distributions. We provide theoretical justification for our choice under the mutually contaminated (MC) noise model (Scott et al., 2013) that assumes that a fraction of majority (minority) group labels are contaminated with labels from minority (majority) group. Lamy et al. (2019) et al. show that common fairness metrics can be estimated up to a proportionality constant under the MC model. We show that Antigone's EDM criteria maximizes this proportionality constant, thus providing the most reliable estimates of fairness.

We evaluate Antigone in conjunction with JTT Liu et al. (2021) on the CelebA and Waterbirds datasets which are commonly used in fairness literature. We compare Antigone with baselines that assume ground-truth knowledge of sensitive attributes and standard ERM on demographic parity, equal opportunity, and worst subgroup accuracy. Antigone significantly closes the fairness gap between standard ERM training and fairness with ground truth sensitive attributes. Compared with GEORGE that estimates majority/minority group labels by clustering the activations of an ERM model, Antigone produces more accurate labels and results in improved fairness. Ablation studies demonstrate the effectiveness of Antigone's EDM based hyper-parameter tuning.

2 PROPOSED METHODOLOGY

We now describe Antigone, starting with the problem formulation (Section 2.1) followed by a description of the Antigone algorithm (Section 2.2).

2.1 PROBLEM SETUP

Consider a data distribution over set $\mathcal{D} = \mathcal{X} \times \mathcal{A} \times \mathcal{Y}$, the product of input data ($\mathcal{X}$), sensitive attributes ($\mathcal{A}$) and target labels ($\mathcal{X}$) triplets. We are given a training set $D^{tr} = \{x_i^{tr}, a_i^{tr}, y_i^{tr}\}_{i=1}^{N^{tr}}$ with N^{tr} training samples, and a validation set $D^{val} = \{x_i^{val}, a_i^{val}, y_i^{val}\}_{i=1}^{N^{val}}$ with N^{val} validation samples. We will assume binary sensitive attributes and target labels, i.e., $\mathcal{A} \in \{0, 1\}$ and $\mathcal{Y} \in \{0, 1\}$.

We seek to train a machine learning model, say a deep neural network (DNN), which can be represented as a parameterized function $f_\theta : \mathcal{X} \to \mathcal{Y} \in \{0, 1\}$, where $\theta \in \Theta$ are the trainable parameters, e.g., DNN weights and biases. Standard fairness unaware empirical risk minimization (ERM) optimizes over trainable parameters θ to minimize average loss $\mathcal{L}_{ERM}$:

$$\mathcal{L}_{ERM} = -\frac{1}{N^{tr}} \sum_{i=1}^{N} l(x_i^{tr}, y_i^{tr}), \tag{1}$$

on D^{tr}, where $l(x_i, y_i)$ is the binary cross-entropy loss.

Optimized model parameters θ^* are obtained by invoking a training algorithm, for instance stochastic gradient descent (SGD), on the training dataset and model, i.e., $\theta_\gamma^* = \mathcal{A}_\gamma^{ERM}(D^{tr}, f_\theta)$, where $\gamma \in \Gamma$ are hyper-parameters of the training algorithm including learning rate, training epochs etc. Hyper-parameters are tuned by evaluating models $f_{\theta_\gamma^*}$ for all $\gamma \in \Gamma$ on D^{val} and picking the best model. More sophisticated algorithms like Bayesian optimization can also be used.

Since standard ERM models suffer from unintended biases in their predictions, fair ML algorithms seek instead to optimize metrics that explicitly account for the performance on demographic subgroups. We review three commonly used metrics below:

- **Demographic parity (DP):** DP requires the model's outcomes to be independent of sensitive attribute. In practice, we seek to minimize the demographic parity gap:

$$\Delta^{\mathrm{DP}} = \mathbb{P}[f(X) = 1 | A = 1] - \mathbb{P}[f(X) = 1 | A = 0]). \tag{2}$$

  Equal opportunity (EO): EO aims to equalize only the model's true positive rates across sensitive attributes. In practice, we seek to minimize

$$\Delta^{\mathrm{EO}} = \mathbb{P}[f(X) = 1 | A = 1, Y = 1] - \mathbb{P}[f(X) = 1 | A = 0, Y = 1]. \tag{3}$$

- **Worst-group accuracy (WGA):** WGA seeks to maximize the minimum accuracy over all sub-groups over sensitive attributes and target labels. That is, we seek to maximize:

$$WGA = \min_{a \in \{0,1\}, y \in \{0,1\}} \mathbb{P}[f(x) = y | A = a, Y = y]. \tag{4}$$

In all three settings, we seek to train models that optimize fairness under a constraint on average accuracy $\mathbb{P}[f(x) = Y]$. With access to sensitive attributes, the fairness metric (and average accuracy) can be evaluated on the validation set. The challenge here is that sensitive attributes are unavailable.

2.2 ANTIGONE ALGORITHM

We now describe the Antigone algorithm which consists of three main steps. In step 1, we train multiple intentionally biased ERM models that each provide pseudo sensitive attribute labels on validation data. We view each model as a noisy sensitive attribute labeller on the validation set. In step 2, we use the proposed EDM metric to pick a noisy labeller from step 1 with the least noise. Finally, in step 3, we use the labelled validation set from step 2 to tune the hyper-parameters of methods like JTT that train fair classifiers without sensitive attributes on training data.

Step 1: Generating sensitive attribute labels on validation set. In step 1, we use the training dataset and standard ERM training to obtain a set of classifiers, $\theta_\gamma^* = \mathcal{A}_\gamma^{ERM}(D^{tr}, f_\theta)$, each corresponding to a different value of training hyper-parameters $\gamma \in \Gamma$. As we discuss in Section 2.1, these include learning rate, weight decay and number of training epochs. Each classifier is used to generate pseudo sensitive attribute labels on the validation set by assigning correctly (incorrectly) classified examples to the majority (minority) groups. That is, each classifier yields a validation set

$$D^{val,\gamma} = \{x_i^{val}, a_i^{val,\gamma}, y_i^{val}\}_{i=1}^{N^{val}} \quad \forall \gamma \in \Gamma \tag{5}$$

where:

$$a_i^{val,\gamma} = \begin{cases} 1, & \text{if } f_{\theta_\gamma^*}(x_i^{val}) = y_i^{val} \\ 0, & \text{otherwise.} \end{cases} \tag{6}$$

From these noisily labelled validation sets, we now seek to pick the one whose pseudo sensitive attribute labels match most closely with true (but unknown) sensitive attributes. That is, we seek to pick the hyper-parameters corresponding to the "best" noisy labeller.

Step 2: Picking the best noisy labeller. The noisy labellers in Step 1 partition inputs in the validation set into two sets containing correctly and incorrectly classified inputs. These serve as proxies for majority and minority groups, respectively. Specifically, let the correct set (or noisily labeled set of majority examples) be $X_{1,noisy}^{val,\gamma} = \{x_i^{val} : a_i^{val,\gamma} = 1\}$ and the incorrect set (or noisily labeled set of minority examples) be $X_{0,noisy}^{val,\gamma} = \{x_i^{val} : a_i^{val,\gamma} = 0\}$.

To estimate fairness accurately, we would like our noisy labeler to be biased, i.e., to place all majority (minority) group inputs in the correct (incorrect) set. In the absence of true sensitive attribute labels, we can measure bias using the distance between the data distributions in the correct and incorrect sets. In Antigone, we pick the simplest distance metric between two distributions, i.e., the Euclidean distance between their means (EDM). Formally,

$$EDM^\gamma = \|\mu(X_{1,noisy}^{val,\gamma}) - \mu(X_{0,noisy}^{val,\gamma})\|_2 \qquad (7)$$

where $\mu(.)$ represents the empirical mean of a dataset. In Section 2.3 we theoretically justify this choice. We pick $\gamma^* = \arg\max_{\gamma \in \Gamma} EDM^\gamma$. Note that in practice we pick two different noisy labellers corresponding to target labels $Y = \{0, 1\}$.

Step 3: Training a fair model. Step 2 yields D^{val,γ^*}, a validation dataset with (estimated) sensitive attribute labels. We can provide D^{val,γ^*} as an input to any method that trains fair models without access to sensitive attributes on training data, but requires a validation set with sensitive attribute labels to tune its own hyper-parameters. In our experimental results, we use D^{val,γ^*} to tune the hyper-parameters of JTT (Liu et al., 2021) and GEORGE (Sohoni et al., 2020). We note that GEORGE proposes its own method to obtain sensitive attributes labels on validation data, but replacing it with Antigone improves on GEORGE's performance.

2.3 ANALYZING ANTIGONE UNDER MC NOISE

Prior work Lamy et al. (2019) has modeled noisy sensitive attributes using the mutually contaminated (MC) noise model Scott et al. (2013). Here, it is assumed that we have access to noisy datasets, $D_{0,noisy}$ and $D_{1,noisy}$, corresponding to minority and majority groups, respectively, that are mixtures of their ground-truth datasets D_0 and D_1. Specifically,

$$D_{1,noisy} = (1 - \alpha)D_1 + \alpha D_0$$
$$D_{0,noisy} = \beta D_1 + (1 - \beta)D_0 \qquad (8)$$

where α and β are noise parameters. Note that strictly speaking Equation 8 should refer to the probability distributions of the respective datasets, but we will abuse this notation to refer to the datasets themselves. As such Equation 8 says that fraction α of the noisy majority group, $D_{1,noisy}$, is contaminated with data from the minority group, and fraction β of the noisy minority group, $D_{0,noisy}$, is contaminated with data from the majority group. An extension of this model assumes that the noise parameters are target label dependent, i,e., (α_0, β_0) for $Y = 0$ and (α_1, β_1) for $Y = 1$.

Note that the MC model assumes that noisy datasets are constructed by sampling independently from the ground-truth distributions. While this is not strictly true in our case since the noise in our sensitive attribute labels might be instance dependent, the MC model can still shed light on the design of Antigone.

Proposition 1. *(Lamy et al., 2019) Under the MC noise model in Equation 8, demographic parity and equal opportunity gaps measured on the noisy datsets are proportional to the true DP and EO gaps. Mathematically:*

$$\Delta^{DP}(D_{0,noisy} \cup D_{1,noisy}) = (1 - \alpha - \beta)\Delta^{DP}(D_0 \cup D_1), \qquad (9)$$

and

$$\Delta^{EO}(D_{0,noisy} \cup D_{1,noisy}) = (1 - \alpha_1 - \beta_1)\Delta^{EO}(D_0 \cup D_1). \qquad (10)$$

From Equation 9 and Equation 10 that under the MC noise model, the DP and EO gaps can be equivalently minimized using noisy sensitive attribute labels, assuming independent contamination and infinite validation data samples. In practice, these assumptions do not hold, however, and therefore we seek to maximize the proportionality constant $1 - \alpha - \beta$ (or $1 - \alpha_1 - \beta_1$) to minimize the gap between the true and estimated fairness values.

Lemma 1. *Assume $X_{0,noisy}$ and $X_{1,noisy}$ correspond to the inputs data of noisy datasets in the MC model. Then, maximizing the EDM between the $X_{0,noisy}$ and $X_{1,noisy}$, i.e., $\|\mu(X_{0,noisy}) - \mu(X_{1,noisy})\|_2$ maximizes $1 - \alpha - \beta$.*

Proof. From Equation 8, we can see that $\|\mu(X_{0,noisy}) - \mu(X_{1,noisy})\|_2 = (1 - \alpha - \beta)^2 \|\mu(X_0) - \mu(X_1)\|_2$. Here $\|\mu(X_0) - \mu(X_1)\|_2$ is the EDM between the ground truth majority and minority data and is therefore a constant. Hence, maximizing EDM between $X_{0,noisy}$ and $X_{1,noisy}$ maximizes $1 - \alpha - \beta$. □

In practice, we separately maximize EDM for target labels $Y = \{0, 1\}$ and hence maximize both $1 - \alpha_0 - \beta_0$ and $1 - \alpha_1 - \beta_1$. We note that our theoretical justification motivates the use of EDM for DP and EO fairness. While not exact, minimizing $\alpha + \beta$ using EDM as a proxy is still helpful for WGA because it reduces contamination and, empirically, provides more reliable estimates for sub-group accuracy.

3 EXPERIMENTAL SETUP

We empirically evaluate Antigone on the CelebA and Waterbirds datasets which have been extensively studied in fairness literature. In this section, we present the details about Antigone's implementation, evaluation and network architecture used for these two datasets. To begin, we note Antigone can be deployed in conjunction with any method that trains fair classifiers without sensitive attributes on training data. We evaluate Antigone with one such state-of-the-art method, JTT (Liu et al., 2021). We begin by briefly describing how Antigone is deployed in conjunction with JTT.

JTT+Antigone: JTT operates in two stages. In the first stage, a biased model is trained using T epochs of standard ERM training to identify the incorrectly classified training examples. In the second stage, the misclassified examples are upsampled λ times and the model is trained again to completion with standard ERM. The hyperparameters of stage 1 and stage 2 classifiers, including early stopping epoch T and upsampling factor λ, are jointly tuned using a validation dataset with ground-truth sensitive attribute labels. We replace the ground-truth validation dataset with noisy sensitive attributes obtained from Antigone.

3.1 CELEBA DATASET

Dataset details: CelebA (Liu et al., 2015) is an image dataset, consisting of 202,599 celebrity face images annotated with 40 attributes including gender, hair colour, age, smiling, etc. The task is to predict hair color, which is either blond $Y = 1$ or non-blond $Y = 0$ and the sensitive attribute is gender $A = \{\text{Men}, \text{Women}\}$. The dataset is split into training, validation and test sets with 162770, 19867 and 19962 images, respectively. Only 15% of individuals in the dataset are blond, and only 6% of blond individuals are men. Consequently, the baseline ERM model under-performs on the blond men.

Hyper-parameter settings: In all our experiments using CelebA dataset, we fine-tune a pre-trained ResNet50 architecture for a total of 50 epochs using SGD optimizer and a batch size of 128. We tune Antigone and JTT over three pairs of learning rates and weight decays, $(1e - 04, 1e - 04), (1e - 04, 1e - 02), (1e - 05, 1e - 01)$, which are also the values used in JTT. For Antigone, we also explore early stopping at any of the 50 training epochs. Antigone's hyper-parameters are tuned using the EDM approach. For JTT, we explore over $T \in \{1, 2, 5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$ and $\lambda \in \{20, 50, 100\}$ as reported in their paper. JTT's hyper-parameters are tuned using the validation dataset produced by Antigone. We report results for DP, EO and WGA fairness metrics. In each case, we seek to optimize fairness while constraining average accuracy to ranges $\{[90, 91), [91, 92), [92, 93), [93, 94), [94, 95)\}$.

3.2 WATERBIRDS DATASET

Dataset details: Waterbirds is a synthetically generated image dataset, containing 11,788 images of water and land birds overlaid on top of either water or land backgrounds (Sagawa* et al., 2020). The task is to predict the bird type, which is either a waterbird $Y = 1$ or a landbird $Y = 0$ and the

sensitive attribute is the background $A = \{waterbackground, landbackground\}$. The dataset is split into training, validation and test sets with 4795, 1199 and 5794 images, respectively. While the validation and test sets are balanced within each target class, the training set contains a majority of waterbirds (landbirds) in water (land) backgrounds and a minority of waterbirds (landbirds) on land (water) backgrounds. Consequently, the baseline ERM model under-performs on the minority group examples.

Hyper-parameter settings: In all our experiments using Waterbirds dataset, we train a pre-trained ResNet50 architecture for a total of 300 epoch using the SGD optimizer and a batch size of 64. We tune Antigone and JTT over three pairs of learning rates and weight decays, $(1e - 03, 1e - 04), (1e - 04, 1e - 01), (1e - 05, 1.0)$, which are also the values used in JTT. For JTT, we explore over $T \in \{25, 40, 50, 60, 75, 100, 125, 150, 175, 200, 225, 250, 275, 300\}$ and $\lambda \in \{20, 50, 100\}$ as reported in their paper. In each case, we seek to optimize fairness while constraining average accuracy to ranges $\{[94, 94.5), [94.5, 95), [95, 95.5), [95.5, 96), [96, 96.5)\}$.

3.3 BASELINES FOR COMPARISONS

We evaluate JTT+Antigone against several baselines.

Standard ERM: A naive baseline is a standard ERM model that only seeks to maximize average accuracy and does not consider fairness. We train standard ERM models using the same network architectures and training hyper-parameters used for Antigone + JTT as reported above.

JTT + Ground-truth sensitive attributes: An upper bound for JTT+Antigone is a JTT model trained with ground-truth sensitive attributes on validation data, i.e., the overall approach used in JTT. For this, we used the reference implementations provided by JTT.

GEORGE Sohoni et al. (2020): GEORGE is a competing approach that does not assume access to sensitive attributes on either training or validation data. GEORGE operates in two stages: In stage 1, an ERM model is trained until completion on the ground-truth target labels. The activation in the penultimate layer of the ERM model are clustered into k clusters to generate pseudo sensitive attributes on both the training and validation datasets. These pseudo sensitive attributes are used to train and tune the hyper-parameters of a Group DRO model Sagawa* et al. (2020).

For a fair comparison with GEORGE, we replace its stage 1 with Antigone, and use the resulting pseudo sensitive attribute labels to tune the hyper-parameters of a Group DRO model Sagawa* et al. (2020). We refer to this approach as GEORGE+Antigone.

4 EXPERIMENTAL RESULTS

We now discuss the results of our empirical evaluations. We begin by analyzing the quality of sensitive attribute labels produced by Antigone and evaluate JTT/GEORGE+Antigone.

Quality of Antigone's sensitive attribute labels: Antigone seeks to generate accurate sensitive attribute labels on validation data based the EDM criterion (Lemma 1). In Figure 1, we empirically validate Lemma 1 by plotting EDM and noise parameters α_1 (contamination in minority group labels), β_1 (contamination in minority group labels) and $1 - \alpha_1 - \beta_1$ (proportionality constant between true and estimated fairness) on the CelebA and Waterbirds datasets. As per Lemma 1, EDM allows us to maximize $1 - \alpha_1 - \beta_1$ since it is ideally proportional to this value. From the figure, we observe that in both cases the EDM metric indeed captures the trend in $1 - \alpha_1 - \beta_1$, enabling early stopping at an epoch that minimizes contamination.

The early stopping points based on EDM and oracular knowledge of $1 - \alpha_1 - \beta_1$ are shown in a blue dot and star, respectively. For Waterbirds these are very close. For CelebA, although the early stopping points are further apart, the values of $1 - \alpha_1 - \beta_1$ at these points are similar.

Next, we evaluate the precision of Antigone's noisy sensitive attributes for all four subgroups in the CelebA and Waterbirds datasets. For all examples labeled as belonging to a specific subgroup, precision is the fraction of examples that truly belong to that subgroup. In Table 1 we compare Antigone's precision to GEORGE with the baseline number of clusters and GEORGE with $k = 2$ clusters. Across both datasets and all four subgroups, we find that Antigone always outperforms

Figure 1: Euclidean Distance between Means (EDM) and noise parameters α_1, β_1 and and $1 - \alpha_1 - \beta_1$ for the positive target class of CelebA and Waterbirds datasets. The noise parameters are unknown in practice. Blue dot indicates the model that we pick to generate pseudo sensitive attributes, while black star indicates the model that maximizes $1 - \alpha_1 - \beta_1$.

GEORGE. In the Appendix Table 4, we also include recall and F1 scores and reach the same conclusion.

To understand the benefits of the proposed EDM metric, we implement a version of Antigone but tune it's hyper-parameters using standard ERM. We refer to this as Antigone (w/o EDM) and find in Table 1 that Antigone with EDM outperforms the version without EDM. We later report on the fairness achieved by these different versions.

JTT+Antigone: Next, in Table 2, compare the test accuracy and fairness achieved by Antigone with JTT (JTT+Antigone) versus a baseline ERM model and with JTT using ground-truth sensitive attributes (JTT+True). As expected, baseline ERM yields unfair outcomes on all three fairness metrics: DP, EO and WGA. We observe that JTT + Antigone improves fairness over the baseline ERM model and closes the gap with JTT + True.

On DP and EO, the JTT+Antigone is very close and always within 3% of the JTT+True results. Both substantially improve upon the fairness achieved by standard ERM. JTT+Antigone improves WGA from

Table 1: Precision of the pseudo sensitive attribute labels generated by Antigone (w/o EDM), Antigone (w/ EDM), GEORGE and GEORGE with $k = 2$ clusters. We observe that Antigone has higher precision across different subgroups on CelebA and Waterbirds datasets.

	Antigone (w/o EDM)	Antigone (w/ EDM)	GEORGE	GEORGE ($k = 2$)
		CelebA		
Blond Men	0.24	0.4	0.11	0.06
Blond Women	0.96	0.96	0.93	0.95
Non-blond Women	0.83	0.86	0.52	0.55
Non-blond Men	0.52	0.52	0.54	0.51
		Waterbirds		
Waterbirds Landbkgd	0.93	0.97	0.7	0.52
Waterbirds Waterbkgd	0.58	0.73	0.76	0.51
Landbirds Waterbkgd	0.96	0.97	0.59	0.56
Landbirds Landbkgd	0.63	0.73	0.66	0.56

38.9% using standard ERM to 66.7% at the expense of $< 3\%$ accuracy drop. JTT+True improves WGA further up to 77.8% but with a larger average accuracy drop. JTT+Antigone achieves highest fairness for relatively high average accuracy values, although one would expect fairness to reduce with higher average accuracy. We believe this in part due to the noise in sensitive attribute labels that Antigone generates. Data for Waterbirds (shown in the Appendix Table 5) have the same trends.

Comparison with GEORGE: Like Antigone, GEORGE also generates pseudo-sensitive attributes on validation data, but as we noted in Table 1, Antigone's labels have higher precision. We now compare the fairness in terms of WGA achieved by GEORGE versus GEORGE+Antigone in which

Table 2: (Avg. Accuracy, Fairness) on test data for different validation accuracy thresholds on the CelebA dataset. Lower DP and EO gaps are better. Higher WGA is better.

Val. Thresh.	Method	DP Gap	EO Gap	Worst-group Acc.
[94, 95)	JTT + Antigone	(94.7, 15.5)	(94.7, 30.0)	(94.2, 60.0)
	JTT + True	(94.8, 15.25)	(94.5, 28.7)	(94.3, 62.5)
[93, 94)	JTT + Antigone	(93.6, 13.3)	(93.6, 21.1)	(93.4, 66.7)
	JTT + True	(93.6, 13.3)	(93.6, 21.1)	(93.4, 67.5)
[92, 93)	JTT + Antigone	(92.6, 10.9)	(92.4, 19.3)	(93.0, 66.7)
	JTT + True	(92.5, 11.1)	(93.0, 16.5)	(92.7, 71.7)
[91, 92)	JTT + Antigone	(91.6, 9.5)	(91.6, 14.7)	(91.6, 63.0)
	JTT + True	(91.8, 9.6)	(91.7, 12.7)	(91.8, 75.0)
[90, 91)	JTT + Antigone	(91.0, 8.1)	(90.9, 10.2)	(91.0, 60.0)
	JTT + True	(91.2, 8.4)	(90.9, 6.2)	(91.5, 77.8)
	ERM	(95.8, 18.7)	(95.8, 46.3)	(95.8, 38.9)

we use Antigone's labeled validation data to tune GEORGE's training algorithm. The results are shown in Table 3. GEORGE+Antigone is more fair than GEORGE alone on both CelebA and Waterbirds. Further, the highest fairness is achieved when restricting GEORGE to have only two clusters, i.e., for GEORGE (k=2)+Antigone. On CelebA, GEORGE (k=2)+Antigone has a small drop in average accuracy compared to GEORGE (k=2), while on Waterbirds, both average accuracy and fairness are better.

Impact of EDM metric on fairness: We already noted in Table 1 Antigone with the proposed EDM metric produces higher quality sensitive attribute labels compared to a version of Antigone that picks hyper-parameters using standard ERM. We evaluated these two approaches using JTT's training algorithm and find that Antigone with EDM results in a 5.7% increase in WGA and a small 0.06% increase in average accuracy.

5 RELATED WORKS

Several works have observed that standard ERM training algorithms can achieve state-of-the-art accuracy on many tasks, but unintentionally make biased predictions for different sensitive attributes failing to meet the fairness objectives (Hovy & Søgaard, 2015; Oren et al., 2019; Hashimoto et al., 2018a; Buolamwini & Gebru, 2018).

Fairness objectives can be broadly categorized into two types: individual fairness and group fairness. Individual fairness (Dwork et al., 2012; Kusner et al., 2017) requires similar individual to be treated similarly. Whereas, group fairness Prost et al. (2019); Quadrianto et al. (2019); Hardt et al. (2016) requires the groups of individuals divided based on a sensitive attribute like race, gender, etc., be treated equally. In this paper, we focus on the popular group fairness notions that include Demographic Parity, Equal Opportunity and Worst-group performance.

Table 3: Performance of GEORGE using Antigone's noisy validation data compared with GEORGE by itself. We observe that on both CelebA and Waterbirds dataset, GEORGE + Antigone out-performs GEORGE, even if GEORGE assumes knowledge of number of clusters ($k = 2$) in its clustering step.

Method	CelebA		Waterbirds	
	Avg Acc	Worst Group	Avg Acc	Worst Group
ERM	95.7	31.1	96.2	31.3
GEORGE	93.6	60.4	95.6	51.7
GEORGE + Antigone	93.3	62.1	96.1	62.0
GEORGE ($K = 2$)	94.6	62.4	95.1	53.4
GEORGE ($K = 2$) + Antigone	94.2	**65.34**	95.6	**60.5**

Methods that seek to achieve group fairness are three types: pre-processing, in-processing and post-processing algorithms. Pre-processing (Quadrianto et al., 2019; Ryu et al., 2018) methods focus on curating the dataset that includes removal of sensitive information or balancing the datasets.

In-processing methods (Hashimoto et al., 2018b; Agarwal et al., 2018; Zafar et al., 2019; Lahoti et al., 2020; Prost et al., 2019; Liu et al., 2021; Sohoni et al., 2020) alter the training mechanism by using adding fairness constrains to the loss function or by training an adversarial framework to make predictions independent of sensitive attributes Zhang et al. (2018). Post-processing methods (Hardt et al., 2016; Wang et al., 2020; Savani et al., 2020) alter the outputs, for *e.g.* use different threshold for different sensitive attributes. In this work, we focus on in-processing algorithms.

Prior in-processing algorithms, including the ones referenced above, assume access to sensitive attributes on the training data and validation dataset. Recent work sought to train fair model without training data annotations Liu et al. (2021); Nam et al. (2020); Hashimoto et al. (2018a); Creager et al. (2021) but, except for GEORGE Sohoni et al. (2020), require sensitive attributes on validation dataset to tune the hyperparameters. Like GEORGE, we seek to train fair classification models without ground-truth sensitive information on either training or validation dataset.

Antigone is different from GEORGE in three different ways: (1) Unlike GEORGE, we account for the model prediction and the ground-truth target label to generate pseudo sensitive attributes. (2) The hyper-parameters of the clustering step in GEORGE are fixed from literature and not specifically tuned for each dataset. In this paper, we propose a more principled approach to tune the model's hyperparameters in an unsupervised fashion to obtain noisy sensitive features. And finally, (3) GEORGE only focuses on improving worst-group accuracy, whereas Antigone can be be adapted to different notions of group fairness.

6 CONCLUSION

In this paper, we propose Antigone, a method to enable hyper-parameter tuning for fair ML models without access to sensitive attributes on training or validation sets. Antigone generates high-quality pseudo sensitive attribute labels on validation data by training a family of biased classifiers using standard ERM and using correctly (incorrectly) classified examples as proxies for majority (minority) group membership. We propose a novel EDM metric based approach to pick the most biased model from this family and provide theoretical justification for this choice using the MC noise model. The resulting validation dataset with pseudo sensitive attribute labels can then be used to tune the hyper-parameters of a fair training algorithm like JTT or GEORGE. We show that Antigone produces the highest precision sensitive attributes compared to the state-of-art, and as a consequence closes the gap in fairness between standard ERM models and those trained with ground-truth knowledge of sensitive attributes. Future work will seek to address inter-sectional fairness and active learning of sensitive attributes.

AVAILABILITY

Code with README.txt file is available at: `https://anonymous.4open.science/r/fairness_without_demographics-3BD0/README.md`

REFERENCES

Alekh Agarwal, Alina Beygelzimer, Miroslav Dudík, John Langford, and Hanna Wallach. A reductions approach to fair classification, 2018.

Joy Buolamwini and Timnit Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In Sorelle A. Friedler and Christo Wilson (eds.), *Proceedings of the 1st Conference on Fairness, Accountability and Transparency*, volume 81 of *Proceedings of Machine Learning Research*, pp. 77–91. PMLR, 23–24 Feb 2018. URL `https://proceedings.mlr.press/v81/buolamwini18a.html`.

Veronika Cheplygina, Marleen de Bruijne, and Josien PW Pluim. Not-so-supervised: a survey of semi-supervised, multi-instance, and transfer learning in medical image analysis. *Medical image analysis*, 54:280–296, 2019.

Kashyap Chitta, Aditya Prakash, and Andreas Geiger. Neat: Neural attention fields for end-to-end autonomous driving. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15793–15803, 2021.

Danielle Keats Citron and Frank Pasquale. The scored society: Due process for automated predictions. *Wash. L. Rev.*, 89:1, 2014.

Elliot Creager, Jörn-Henrik Jacobsen, and Richard Zemel. Environment inference for invariant learning. In *International Conference on Machine Learning*, 2021.

Jeffrey Dastin. Amazon scraps secret ai recruiting tool that showed bias against women. In *Ethics of Data and Analytics*, pp. 296–299. Auerbach Publications, 2018.

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference*, ITCS '12, pp. 214–226, New York, NY, USA, 2012. Association for Computing Machinery. ISBN 9781450311151. doi: 10.1145/2090236.2090255. URL https://doi.org/10.1145/2090236.2090255.

Patrick Grother, George Quinn, and P Phillips. Report on the evaluation of 2d still-image face recognition algorithms, 2010-06-17 2010.

Moritz Hardt, Eric Price, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/9d2682367c3935defcb1f9e247a97c0d-Paper.pdf.

Tatsunori Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In *International Conference on Machine Learning*, pp. 1929–1938. PMLR, 2018a.

Tatsunori B. Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In *ICML*, 2018b.

Dirk Hovy and Anders Søgaard. Tagging performance correlates with author age. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pp. 483–488, Beijing, China, July 2015. Association for Computational Linguistics. doi: 10.3115/v1/P15-2079. URL https://aclanthology.org/P15-2079.

Alina Köchling and Marius Claus Wehner. Discriminated by an algorithm: a systematic review of discrimination and fairness by algorithmic decision-making in the context of hr recruitment and hr development. *Business Research*, 13(3):795–848, 2020.

Matt J Kusner, Joshua Loftus, Chris Russell, and Ricardo Silva. Counterfactual fairness. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/a486cd07e4ac3d270571622f4f316ec5-Paper.pdf.

Preethi Lahoti, Alex Beutel, Jilin Chen, Kang Lee, Flavien Prost, Nithum Thain, Xuezhi Wang, and Ed H. Chi. Fairness without demographics through adversarially reweighted learning, 2020.

Alexandre Lamy, Ziyuan Zhong, Aditya Krishna Menon, and Nakul Verma. *Noise-Tolerant Fair Classification*. Curran Associates Inc., Red Hook, NY, USA, 2019.

Geert Litjens, Thijs Kooi, Babak Ehteshami Bejnordi, Arnaud Arindra Adiyoso Setio, Francesco Ciompi, Mohsen Ghafoorian, Jeroen Awm Van Der Laak, Bram Van Ginneken, and Clara I Sánchez. A survey on deep learning in medical image analysis. *Medical image analysis*, 42:60–88, 2017.

Evan Z Liu, Behzad Haghgoo, Annie S Chen, Aditi Raghunathan, Pang Wei Koh, Shiori Sagawa, Percy Liang, and Chelsea Finn. Just train twice: Improving group robustness without training group information. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 6781–6792. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/liu21f.html.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Ereni Markos, George R. Milne, and James W. Peltier. Information sensitivity and willingness to provide continua: A comparative privacy study of the united states and brazil. *Journal of Public Policy & Marketing*, 36(1):79–96, 2017. doi: 10.1509/jppm.15.159. URL https://doi.org/10.1509/jppm.15.159.

Junhyun Nam, Hyuntak Cha, Sungsoo Ahn, Jaeho Lee, and Jinwoo Shin. Learning from failure: Training debiased classifier from biased classifier. In *Advances in Neural Information Processing Systems*, 2020.

Mei Ngan and Patrick Grother. Face recognition vendor test (frvt) - performance of automated gender classification algorithms, 2015-04-20 2015.

Yonatan Oren, Shiori Sagawa, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust language modeling. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4227–4237, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1432. URL https://aclanthology.org/D19-1432.

Frank Pasquale. *The black box society: The secret algorithms that control money and information*. Harvard University Press, 2015.

Flavien Prost, Hai Qian, Qiuwen Chen, Ed H. Chi, Jilin Chen, and Alex Beutel. Toward a better trade-off between performance and fairness with kernel-based distribution matching, 2019.

Novi Quadrianto, Viktoriia Sharmanska, and Oliver Thomas. Discovering fair representations in the data domain. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Hee Jung Ryu, Hartwig Adam, and Margaret Mitchell. Inclusivefacenet: Improving face attribute detection with race and gender diversity, 2018.

Shiori Sagawa*, Pang Wei Koh*, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust neural networks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=ryxGuJrFvS.

Yash Savani, Colin White, and Naveen Sundar Govindarajulu. Intra-processing methods for debiasing neural networks, 2020.

Clayton Scott, Gilles Blanchard, and Gregory Handy. Classification with asymmetric label noise: Consistency and maximal denoising. In Shai Shalev-Shwartz and Ingo Steinwart (eds.), *Proceedings of the 26th Annual Conference on Learning Theory*, volume 30 of *Proceedings of Machine Learning Research*, pp. 489–511, Princeton, NJ, USA, 12–14 Jun 2013. PMLR. URL https://proceedings.mlr.press/v30/Scott13.html.

Nimit Sohoni, Jared Dunnmon, Geoffrey Angus, Albert Gu, and Christopher Ré. No subclass left behind: Fine-grained robustness in coarse-grained classification problems. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 19339–19352. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/e0688d13958a19e087e123148555e4b4-Paper.pdf.

Zeyu Wang, Klint Qinami, Ioannis Christos Karakozis, Kyle Genova, Prem Nair, Kenji Hata, and Olga Russakovsky. Towards fairness in visual recognition: Effective strategies for bias mitigation, 2020.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez-Rodriguez, and Krishna P. Gummadi. Fairness constraints: A flexible approach for fair classification. *Journal of Machine Learning Research*, 20(75):1–42, 2019. URL http://jmlr.org/papers/v20/18-262.html.

Brian Hu Zhang, Blake Lemoine, and Margaret Mitchell. Mitigating unwanted biases with adversarial learning, 2018.

Zhejun Zhang, Alexander Liniger, Dengxin Dai, Fisher Yu, and Luc Van Gool. End-to-end urban driving by imitating a reinforcement learning coach. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15222–15232, 2021.

A APPENDIX

Table 4: We tabulate the precision, recall, F1-score of the noisy validation groups generated from ERM model, GEORGE, GEORGE with number of clusters = 2 and Antigone. We observe that Antigone has higher precision and F1 scores across different noisy groups on CelebA and Waterbirds, respectively.

	Antigone (w/o EDM)	GEORGE	GEORGE ($k = 2$)	Antigone (w/ EDM)
		CelebA		
Blond Men	0.24, 0.35, 0.28	0.11, 0.21, 0.14	0.06, 0.63, 0.11	0.4, 0.37, 0.38
Blond Women	0.96, 0.93, 0.94	0.93, 0.31, 0.46	0.95, 0.42, 0.58	0.96, 0.96, 0.96
Non-blond Women	0.83, 0.12, 0.21	0.52, 0.36, 0.42	0.55, 0.25, 0.34	0.86, 0.13, 0.22
Non-blond Men	0.52, 0.97, 0.68	0.54, 0.36, 0.44	0.51, 0.79, 0.62	0.52, 0.98, 0.68
		Waterbirds		
Waterbirds Landbkgd	0.93, 0.29, 0.44	0.70, 0.29, 0.41	0.52, 0.37, 0.43	0.97, 0.64, 0.77
Waterbirds Waterbkgd	0.58, 0.98, 0.73	0.76, 0.21, 0.33	0.51, 0.66, 0.58	0.73, 0.98, 0.84
Landbirds Waterbkgd	0.96, 0.42, 0.58	0.59, 0.38, 0.46	0.56, 0.56, 0.56	0.97, 0.64, 0.77
Landbirds Landbkgd	0.63, 0.98, 0.77	0.66, 0.31, 0.42	0.56, 0.57, 0.56	0.73, 0.98, 0.84

Table 5: We report the (Test Average Accuracy, Test Fairness Metric) for different validation accuracy thresholds on Waterbirds dataset. We observe that JTT + Antigone (our noisy sensitive attributes) improves fairness over baseline ERM model and closes the gap with JTT + True (ground-truth sensitive attributes)

Val. Thresh.	Method	DP Gap	EqOP	Worst-group
[96, 96.5)	JTT + Antigone	(95.8, 3.9)	(96.2, 10.7)	(96.3, 83.0)
	JTT + True	(95.8, 3.9)	(96.0, 7.1)	(96.3, 83.0)
[95.5, 96)	JTT + Antigone	(95.4, 2.8)	(96.0, 7.5)	(96.3, 83.2)
	JTT + True	(95.4, 2.9)	(95.6, 6.0)	(96.1, 83.5)
[95, 95.5)	JTT + Antigone	(94.5, 1.5)	(94.7, 4.2)	(94.7, 85.9)
	JTT + True	(94.4, 1.7)	(94.3, 1.1)	(95.1, 86.8)
[94.5, 95)	JTT + Antigone	(94.2, 0.4)	(93.8, 2.0)	(94.2, 86.7)
	JTT + True	(93.6, 0.6)	(93.8, 2.0)	(94.1, 88.2)
[94.0, 94.5)	JTT + Antigone	(93.0, 1.5)	(93.6, 4.8)	(93.7, 87.9)
	JTT + True	(93.1, 1.5)	(93.2, 4.0)	(93.8, 88.1)
	ERM	(97.3, 21.3)	(97.3, 35.0)	(97.3, 59.1)