Personalized Online Federated Multi-Kernel Learning

Abstract

Multi-kernel learning (MKL) exhibits well-documented performance in online non-linear function approximation. Federated learning enables a group of learners (called clients) to train an MKL model on the data distributed among clients to perform online non-linear function approximation. There are some challenges in online federated MKL that need to be addressed: i) Communication efficiency especially when a large number of kernels are considered ii) Heterogeneous data distribution among clients. The present paper develops an algorithmic framework to enable clients to communicate with the server to send their updates with affordable communication cost while clients employ a large dictionary of kernels. Utilizing random feature (RF) approximation, the present paper proposes scalable online federated MKL algorithm. We prove that using the proposed online federated MKL algorithm, each client enjoys sub-linear regret with respect to the RF approximation of its best kernel in hindsight, which indicates that the proposed algorithm can effectively deal with heterogeneity of the data distributed among clients. Experimental results on real datasets showcase the advantages of the proposed algorithm compared with other online federated kernel learning ones.

1 Introduction

Kernel learning exhibits well-documented performance in function approximation tasks, while providing theoretical guarantees associated with different performance metrics, see e.g. [33, 11, 26]. In some cases, a group of learners aims at collaborating to perform function approximation without revealing their data. To this end, federated learning has been emerged as a crucial learning paradigm by enabling a group of learners called clients to collaborate with each other by communicating with a central server to train a centralized model [21, 17, 6, 13]. Through this process, clients send model parameters and updates to the server without revealing their data. Upon receiving updates from clients, the server updates the model. Therefore, federated learning enables clients to perform kernel learning for function approximation. In this context, a server and clients collaborate with each other to learn the optimal kernel. Furthermore, in some practical cases, clients may need to perform the function approximation in an online fashion while they are collaborating with the server to learn the kernel. For example, consider the case where clients may not have enough memory to store data in batch. In addition, data samples may arrive in a sequential manner such that clients are not able to perform the function approximation in batch form. There are major challenges in performing online kernel learning in federated fashion that need to be addressed:

Communication Efficiency: Communication efficiency arises as a bottleneck in federated learning (see e.g. [15, 25, 10]). Specifically, limited clients-to-server communication bandwidth restricts the number of parameters that can be sent from clients to the server.

Heterogeneous Data: The distribution of data observed by a client might be different from others (see e.g. [31, 18, 3]). Thus, the optimal kernel that is aimed to be learned is different across clients.
Computational Complexity: Clients should be able to perform function approximation fast enough in order to make a decision in real-time. Therefore, the computational complexity of kernel learning methods should be affordable for clients.

Conventional online kernel learning approaches (see e.g. [11, 27]) suffer from 'curse of dimensionality' [1] in the sense that the number of parameters that should be learned increases with the number of observed data. This can make employing conventional online kernel learning approaches infeasible to perform online federated kernel learning since clients may be required to send a large number of parameter updates to the server while the available clients-to-server communication bandwidth is not enough for sending such information. Approximating kernels by finite-dimensional feature representations (e.g. Nyström method [34] and random feature method of [24]) makes online kernel learning approaches scalable in the sense that the learner can choose the number of parameters that should be learned, independent of the number of observed data samples (see e.g. [19, 2, 36]). Employing finite-dimensional feature representations of kernels to perform online federated kernel learning, clients can choose the number of parameters that they should send to the server. Therefore, finite-dimensional kernel approximation can better cope with limited clients-to-server communication bandwidth compared to conventional kernel learning approaches. Random feature (RF) approximation [24] has been exploited to perform online federated kernel learning when a single pre-selected kernel function is employed [16, 9]. The choice of the kernel function greatly affects the performance of function approximation when it comes to exploiting only a single kernel function. Employing multiple kernels instead of a single pre-selected one, can lead to obtaining more accurate function approximation since multi-kernel learning (MKL) can learn combination of kernels [14]. Online federated MKL algorithms with theoretical guarantees called vM-KOFL and eM-KOFL have been proposed in [12]. However, eM-KOFL and vM-KOFL do not provide personalized MKL models for clients since they learn the same combination of kernels for all clients.

The present paper proposes a novel **p**ersonalized **o**nline **f**ederated **MKL** algorithm called POF-MKL that provides a personalized MKL model for each client while it is ensured that the available clients-to-server communication bandwidth can afford communication cost of sending clients' updates to the server. In order to alleviate the communication cost of MKL, the propsoed POF-MKL employs RF approximation of kernels and at each time instant, each client chooses a subset of kernels to send their updates to the server instead of sending the updates of all kernels. The number of kernels in the chosen subset is selected such that the required bandwidth to send all clients' updates does not exceed the available clients-to-server communication bandwidth. Therefore, clients can send their updates to the server independent of the number of kernels in the dictionary and as a result a comparatively large dictionary of kernels can be considered to perform function approximation. Contributions of the present paper can be summarized as follows:
c1. Leveraging the proposed POF-MKL, clients can update a subset of kernels' parameters which alleviates computational complexity and communication cost of sending updates to the server;
c2. Through theoretical analysis, it is proved that using the proposed POF-MKL, each client achieves sub-linear regret with respect to RF approximation of the best kernel in hindsight associated with the corresponding client data samples (c.f. Theorem 1). Moreover, it is guaranteed that the server achieves sub-linear regret with respect to the best function approximator (c.f. Theorem 2);
c3. Experiments on real datasets showcase the effectiveness of the proposed POF-MKL compared to existing online federated kernel learning algorithms.

2   Problem Statement and Preliminaries

Let there be a set of K clients performing function approximation task in an online fashion. The k-th client's goal is to learn the function $f(\cdot;\cdot,\cdot)$ using the stream of data samples $\{(\boldsymbol{x}_{k,t}, y_{k,t})\}_{t=1}^{T}$ such that $\boldsymbol{x}_{k,t} \in \mathbb{R}^d$ is the data sample observed by the k-th client at time t and $y_{k,t}$ is the label associated with $\boldsymbol{x}_{k,t}$. In the kernel learning context, the function $f(\cdot;\cdot,\cdot)$ is assumed to belong to a reproducing kernel Hilbert space (RKHS). The present paper studies the personalized federated

supervised function approximation where the goal is to find function parameters $\boldsymbol{\Theta}$ and $\boldsymbol{w}_k$ such that the cumulative difference between $f(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}, \boldsymbol{w}_k)$ and $y_{k,t}$ over time is minimized. Note that $\boldsymbol{\Theta}$ denotes the global function parameters which are learned through collaboration of clients with the server while $\boldsymbol{w}_k$ is the personalized function parameter learned locally by the k-th client. At each time instant t, upon observing the data sample $\boldsymbol{x}_{k,t}$, the k-th client make the prediction $f(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}, \boldsymbol{w}_k)$ and then observes the true label $y_{k,t}$. Therefore, the function approximation problem that the server aims at solving can be expressed as

$$\min_{\boldsymbol{\Theta}} \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(f(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}, \boldsymbol{w}_k), y_{k,t}) \tag{1}$$

where $\mathcal{L}(\cdot, \cdot)$ denotes the loss function which can be defined as

$$\mathcal{L}(f(\boldsymbol{x}; \boldsymbol{\Theta}, \boldsymbol{w}), y) = \mathcal{C}(f(\boldsymbol{x}; \boldsymbol{\Theta}, \boldsymbol{w}), y) + \lambda \Omega(\|f\|^2) \tag{2}$$

where $\mathcal{C}(\cdot, \cdot)$ denotes the cost function (e.g. least squares function for regression task). Also, λ denotes the regularization coefficient and $\Omega(\cdot)$ represents a regularizer function to prevent over-fitting and control the model complexity. Moreover, finding the local parameters $\boldsymbol{w}_k$ by the k-th client can be expressed as the optimization problem $\min_{\boldsymbol{w}_k} \sum_{t=1}^{T} \mathcal{L}(f(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}, \boldsymbol{w}_k), y_{k,t})$. In order to perform the function approximation task in an online fashion, the k-th client needs to perform the task with the values of $\boldsymbol{\Theta}$ and $\boldsymbol{w}_k$ at time t denoted by $\boldsymbol{\Theta}_t$ and $\boldsymbol{w}_{k,t}$, respectively. Thus, the values of function parameters $\boldsymbol{\Theta}$ and $\boldsymbol{w}_k$ should be updated 'on the fly'. Since the function $f(\cdot; \cdot, \cdot)$ belongs to a reproducing kernel Hilbert space (RKHS), based on the representer theorem [33], given data samples, the optimal solution for (1) can be obtained as

$$\hat{f}(\boldsymbol{x}) = \sum_{t=1}^{T} \sum_{k=1}^{K} \alpha_{k,t} \kappa(\boldsymbol{x}, \boldsymbol{x}_{k,t}) \tag{3}$$

where $\kappa(\cdot, \cdot)$ denotes symmetric positive definite kernel function such that $\kappa(\boldsymbol{x}, \boldsymbol{x}')$ measures the similarity between $\boldsymbol{x}$ and $\boldsymbol{x}'$. And $\alpha_{k,t}$ is an unknown coefficient associated with $\kappa(\boldsymbol{x}, \boldsymbol{x}_{k,t})$ which is required to be estimated. In this case, $\hat{f}(\cdot)$ in (3) belongs to the RKHS $\mathbb{H} := \{f(\cdot)|f(\boldsymbol{x}) = \sum_{t=1}^{\infty} \sum_{k=1}^{K} \alpha_{k,t} \kappa(\boldsymbol{x}, \boldsymbol{x}_{k,t})\}$ such that RKHS norm is defined as $\|f\|_{\mathbb{H}}^2 := \sum_t \sum_{t'} \alpha_t \alpha_{t'} \kappa(\boldsymbol{x}_t, \boldsymbol{x}_{t'})$. Furthermore, from (3), it can be inferred that $\boldsymbol{\Theta}_t = [\alpha_{1,1}, \ldots, \alpha_{K,1}, \ldots, \alpha_{1,t}, \ldots, \alpha_{K,t}]$. Therefore, the number of coefficients $\{\alpha_{k,\tau}\}_{\tau=1}^{t}, \forall k$ that should be estimated to obtain $\hat{f}(\cdot)$ increases over time. This is known as *curse of dimensionality* [33] since the computational complexity of function approximation increases with time. This brings challenge for federated implementation of function approximation since dimension of updates that should be sent to the server by each client grows over time and when T is large, the available communication bandwidth may not be enough for clients to send their updates.

In order to deal with the increasing number of unknown coefficients, one can employ random Fourier approximation [24]. Assume that $\kappa(\cdot)$ is a shift-invariant kernel meaning that $\kappa(\boldsymbol{x}, \boldsymbol{x}') = \kappa(\boldsymbol{x} - \boldsymbol{x}')$. Let $\pi_\kappa(\boldsymbol{\rho})$ denotes the Fourier transform of $\kappa(\cdot)$. If the kernel function $\kappa(\cdot)$ is normalized such that $\kappa(\boldsymbol{0}) = 1$, then $\pi_\kappa(\boldsymbol{\rho})$ can be viewed as a probability density function (PDF) (see e.g. [24]). Let $\boldsymbol{\rho}_1, \ldots, \boldsymbol{\rho}_D$ be a set of D independent and identically distributed (i.i.d) vectors drawn from $\pi_\kappa(\cdot)$. Let the vector $\boldsymbol{z}(\boldsymbol{x})$ be defined as

$$\boldsymbol{z}(\boldsymbol{x}) = \frac{1}{\sqrt{D}}[\sin(\boldsymbol{\rho}_1^\top \boldsymbol{x}), \ldots, \sin(\boldsymbol{\rho}_D^\top \boldsymbol{x}), \cos(\boldsymbol{\rho}_1^\top \boldsymbol{x}), \ldots, \cos(\boldsymbol{\rho}_D^\top \boldsymbol{x})]. \tag{4}$$

Then, $\hat{\kappa}_r(\boldsymbol{x} - \boldsymbol{x}') = \boldsymbol{z}(\boldsymbol{x})^\top \boldsymbol{z}(\boldsymbol{x}')$ constitutes an unbiased estimator of $\kappa(\boldsymbol{x})$ and the random feature (RF) approximation of $\hat{f}(\boldsymbol{x})$ in (3) can be obtained as

$$\hat{f}_{\text{RF}}(\boldsymbol{x}) = \sum_{t=1}^{T} \sum_{k=1}^{K} \alpha_{k,t} \boldsymbol{z}(\boldsymbol{x}_{k,t})^\top \boldsymbol{z}(\boldsymbol{x}) := \boldsymbol{\theta}^\top \boldsymbol{z}(\boldsymbol{x}) \tag{5}$$

where in this case $\boldsymbol{\theta} = \sum_{t=1}^{T} \sum_{k=1}^{K} \alpha_{k,t} \boldsymbol{z}(\boldsymbol{x}_{k,t})$. According to (4), $\boldsymbol{z}(\boldsymbol{x}_{k,t})$ is a $2D$ vector and as a result it can be concluded that $\boldsymbol{\theta}$ is a $2D$ vector as well. Therefore, using RF approximation, the vector $\boldsymbol{\theta}$ should be estimated whose dimension does not grow over time.

The performance of a kernel learning algorithm depends on the choice of the kernel. Thus, performing the function approximation using a pre-selected kernel requires prior information which may not be available. To cope with this, employing a dictionary of kernels in lieu of a pre-selected single kernel has been proposed in the literature (see e.g. [32, 14, 20]). Specifically, the kernel is learned as a combination of kernels in the dictionary. Let $\kappa_1(\cdot), \ldots, \kappa_N(\cdot)$ be a set of N kernels where $\kappa_i(\cdot)$ denotes the i-th kernel. The function $\bar{\kappa}(\cdot)$ belongs to the convex hull $\mathbb{K} := \{\bar{\kappa}(\boldsymbol{x}) = \sum_{i=1}^{N} \beta_i \kappa_i(\boldsymbol{x}), \beta_i \geq 0, \forall i, \sum_{i=1}^{N} \beta_i = 1\}$ is a kernel [29]. Therefore, in online multi-kernel learning, the goal is to learn the convex combination of kernels in the dictionary to minimize the cumulative regret with respect to the best function approximator in hindsight. The cumulative regret is defined as the cumulative difference between loss of the online multi-kernel learning algorithm and that of the best function approximator in hindsight. Furthermore, for a dataset $\{(\boldsymbol{x}_t, y_t)\}_{t=1}^{T}$, the best function approximator is $f^*(\cdot) \in \arg\min_{f_i^*, i \in [N]} \sum_{t=1}^{T} \mathcal{L}(f_i^*(\boldsymbol{x}_t), y_t)$ where $f_i^*(\cdot) \in \arg\min_{f \in \mathbb{H}_i} \sum_{t=1}^{T} \mathcal{L}(f(\boldsymbol{x}_t), y_t)$ such that $\mathbb{H}_i$ is an RKHS induced by $\kappa_i(\cdot)$ and $[N] := \{1, \ldots, N\}$. Enabled by random feature approximation, centralized and scalable online multi-kernel learning algorithms have been proposed in literature (see e.g. [28, 30, 8]). The present paper proposes an algorithmic framework for personalized online federated MKL using RF approximation of kernels in the dictionary.

3 Personalized Online Federated Multi-Kernel Learning

The present section proposes an algorithmic framework for online federated multi-kernel learning which can deal with heterogeneous data among clients. To perform function approximation, RF approximations of kernel functions are employed. For the i-th kernel κ_i, vectors $\boldsymbol{\rho}_{i,1}, \ldots, \boldsymbol{\rho}_{i,D}$ are drawn i.i.d from $\pi_{\kappa_i}(\cdot)$ to construct the random feature vector $\boldsymbol{z}_i(\boldsymbol{x}) = \frac{1}{\sqrt{D}}[\sin(\boldsymbol{\rho}_{i,1}^{\top}\boldsymbol{x}), \ldots, \sin(\boldsymbol{\rho}_{i,D}^{\top}\boldsymbol{x}), \cos(\boldsymbol{\rho}_{i,1}^{\top}\boldsymbol{x}), \ldots, \cos(\boldsymbol{\rho}_{i,D}^{\top}\boldsymbol{x})]$. Then, at time instant t, the random feature approximation associated with $\kappa_i(\cdot)$ can be obtained as $\hat{f}_{\text{RF},it}(\boldsymbol{x}) = \boldsymbol{\theta}_{i,t}^{\top}\boldsymbol{z}_i(\boldsymbol{x})$ where $\boldsymbol{\theta}_{i,t}$ is the global function parameter associated the i-th kernel at time t.

3.1 Algorithm

At each time instant t, the server transmits global function parameters $\boldsymbol{\theta}_{i,t}, \forall i \in [N]$ to all clients. The k-th client, assigns the weight $w_{ik,t}$ to the i-th kernel which indicates the confidence of the k-th client at time t in the function approximation given by the i-th kernel. Upon receiving new data sample $\boldsymbol{x}_{k,t}$, the k-th client performs the function approximation combining kernels' RF approximations as

$$\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t}) = \sum_{i=1}^{N} \frac{w_{ik,t}}{W_{k,t}} \boldsymbol{\theta}_{i,t}^{\top} \boldsymbol{z}_i(\boldsymbol{x}_{k,t}) = \sum_{i=1}^{N} \frac{w_{ik,t}}{W_{k,t}} \hat{f}_{\text{RF},it}(\boldsymbol{x}_{k,t}) \tag{6}$$

where $\boldsymbol{\Theta}_t = [\boldsymbol{\theta}_{1,t}, \ldots, \boldsymbol{\theta}_{N,t}]$, $\boldsymbol{w}_{k,t} = [w_{1k,t}, \ldots, w_{Nk,t}]$ and $W_{k,t} = \sum_{i=1}^{N} w_{ik,t}$. Upon observing the true label $y_{k,t}$, the k-th client calculates the losses $\mathcal{L}(\hat{f}_{\text{RF},it}(\boldsymbol{x}_{k,t}), y_{k,t}), \forall i \in [N]$. Then, the k-th client leverages calculated losses to locally update both global and local parameters. Let $\boldsymbol{\theta}_{ik,t+1}$ and $w_{ik,t+1}$ denote the k-th client's local updates of $\boldsymbol{\theta}_{i,t}$ and $w_{ik,t}$, respectively. Specifically, the k-th client utilizes multiplicative update rule to update $w_{ik,t}$ as

$$w_{ik,t+1} = w_{ik,t} \exp\left(-\eta_k \mathcal{L}(\hat{f}_{\text{RF},it}(\boldsymbol{x}_{k,t}), y_{k,t})\right), \forall i \in [N] \tag{7}$$

where η_k is the learning rate of the k-th client. Note that the k-th client ($\forall k \in [K]$) does not send its updated local parameter $\boldsymbol{w}_{k,t+1}$ to the server. Clients send their locally updated global parameters to the server (i.e. $\boldsymbol{\theta}_{ik,t+1}$). Aggregating local updates, the server updates global parameters to $\boldsymbol{\Theta}_{t+1}$. If all clients send updates associated with all kernels (i.e. $\boldsymbol{\theta}_{ik,t+1}, \forall i \in [N]$), this requires sending $2ND$ parameters by each client at each time instant. When the number of both clients and kernels are large, the available client-to-server communication bandwidth may not be enough to afford sending $2NDK$ parameters per time instant even for small values of D. Note that reducing N and D degrade the performance of online federated MKL. Reducing N (the number of kernels), decreases

---

Algorithm 1 The k-th client kernel subset selection at time t.

Input: Weights $w_{ik,t}$, $\forall i \in [N]$, parameter M and exploration rate $0 < \xi_k \leq 1$.
Sort the kernels in descending order with respect to weights $\{w_{ik,t}\}_{i=1}^N$.
Obtain the index sequence $s_1, \ldots, s_N$ such that $w_{s_b k,t} \leq w_{s_a k,t}$ if $b > a$, $\forall a, b \in [N]$.
Open bin $\mathcal{B}_1$ and initialize $j = 1$.
for all $i \in [N]$, the k-th client **do**
    if the bin $\mathcal{B}_j$ includes less than M kernels **then**
        Adds the s_i-th kernel to $\mathcal{B}_j$.
    else
        Opens new bin $\mathcal{B}_{j+1}$, adds the s_i-th kernel to $\mathcal{B}_{j+1}$ and updates $j \leftarrow j + 1$.
    end if
end for
Draw an index $I_{k,t}$ via PMF $\boldsymbol{q}_{k,t}$ in (8).
Output: $\mathcal{S}_{k,t}$: indices set of kernels in the selected bin $\mathcal{B}_{I_{k,t}}$

---

the flexibility of clients to construct their ideal kernel using convex combination of kernels in the dictionary. Reducing D can degrade the accuracy of RF approximation.

The present paper proposes an algorithmic framework to enable clients to perform online function approximation with sufficiently large dictionary of kernels while the available clients-to-server communication bandwidth can afford sending updates from clients to the server when a desirable value for the number of random features D is chosen. To this end, at each time instant, each client randomly chooses a subset of M kernels among all N kernels in the dictionary. Then, each client updates and sends the global parameters of the chosen M kernels to the server instead of updating and sending global parameters of all kernels. To choose a subset of M kernels, each client splits kernels into some bins and draws randomly one of the bins at each time instant. Each bin contains at most M kernels and each client updates and sends global parameters associated with kernels in the chosen bin. In order to distribute kernels among bins, at first the k-th client sorts kernels in descending order according to kernels' weights $\{w_{ik,t}\}_{i=1}^N$. Let $\mathcal{B}_j$ represents the j-th bin of kernels. The k-th client adds kernels from sorted list one by one to $\mathcal{B}_j$ until either all kernels are assigned to a bin or the number of kernels in $\mathcal{B}_j$ reaches M. When there are some kernels that are not assigned to any bins while there are M kernels in $\mathcal{B}_j$, the k-th client opens the bin $\mathcal{B}_{j+1}$ and adds kernels to this bin. This continues until all kernels are assigned to a bin. As it can be inferred from the procedure of distributing kernels into bins, the number of bins at every client is $m = \left\lceil \frac{N}{M} \right\rceil$. Furthermore, it can be concluded that $\mathcal{B}_1$ includes M kernels with the largest weights while the bin $\mathcal{B}_m$ includes $N - (m - 1)M$ kernels with lowest weights. The k-th client assigns the weight $u_{jk,t}$ at time t to $\mathcal{B}_j$ defined as $u_{jk,t} = \sum_{\kappa_i \in \mathcal{B}_j} w_{ik,t}$. The k-th client draws one of the bins according to the probability mass function (PMF) $\boldsymbol{q}_{k,t}$ defined as

$$q_{jk,t} = (1 - \xi_k) \frac{u_{jk,t}}{U_{k,t}} + \frac{\xi_k}{m}, \forall j \in [m] \tag{8}$$

where $U_{k,t} = \sum_{j=1}^m u_{jk,t}$ and $0 < \xi_k \leq 1$ is an exploration rate determined by the k-th client. Let $I_{k,t}$ be the index of the chosen bin by the k-th client at time t. The PMF in (8) constitutes trade-off between exploitation and exploration. According to the first term in the right hand side of (8), it is more probable that the k-th client draws a bin which includes kernels with larger weights $w_{ik,t}$. Hence, it is more probable that the k-th client collaborates in updating the global parameters of a kernel with larger weight $w_{ik,t}$. Let $\mathcal{S}_{k,t}$ denotes the set which includes the indices of kernels in the chosen bin at time t. The Algorithm 1 summarizes the procedure that the k-th client determines the set $\mathcal{S}_{k,t}$.

Let $p_{ik,t}$ denotes the probability that $i \in \mathcal{S}_{k,t}$. Then $p_{ik,t} = q_{b_i k,t}$ where b_i is the index of the bin which includes the i-th kernel. The k-th client updates global parameters locally as follows

$$\boldsymbol{\theta}_{ik,t+1} = \boldsymbol{\theta}_{i,t} - \eta \frac{\nabla \mathcal{L}(\boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})}{p_{ik,t}} \mathbf{1}_{i \in \mathcal{S}_{k,t}} \tag{9}$$

Algorithm 2 Personalized Online Federated Multi-Kernel Learning (POF-MKL)

    Input: Kernels κ_i, $i = 1, ..., N$, learning rate $\eta > 0$ and the number of random features D.

    Initialize: $\boldsymbol{\theta}_{i,1} = \mathbf{0}$, $w_{ik,1} = 1$, $\forall i \in [N]$, $\forall k \in [K]$.

    for $t = 1, \dots, T$ **do**

        The server transmits the global parameters $\boldsymbol{\Theta}_t = [\boldsymbol{\theta}_{1,t}, \dots, \boldsymbol{\theta}_{N,t}]$ to all clients.

        for all $k \in [K]$, the kth client **do**

            Receive one datum $\boldsymbol{x}_{k,t}$.

            Predicts $\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t})$ via (6).

            Calculates losses $\mathcal{L}(\hat{f}_{\text{RF},it}(\boldsymbol{x}_{k,t}), y_{k,t})$, $\forall i \in [N]$.

            Updates $w_{ik,t+1}$, $\forall i \in [N]$ via (7).

            Selects a subset of kernel indices $\mathcal{S}_{k,t}$ using Algorithm 1.

            Updates $\boldsymbol{\theta}_{ik,t+1}$, $\forall i \in \mathcal{S}_{k,t}$ via (9) and sends $\boldsymbol{\theta}_{ik,t+1}$, $\forall i \in \mathcal{S}_{k,t}$ to the server.

        end for

        The server updates $\boldsymbol{\theta}_{i,t+1}$, $\forall i \in [N]$ via (10).

    end for

---

where $\mathbf{1}_{i \in \mathcal{S}_{k,t}}$ denotes an indicator function and it is 1 when $i \in \mathcal{S}_{k,t}$. The update rule in (9) implies that when $i \notin \mathcal{S}_{k,t}$, the k-th client does not update $\boldsymbol{\theta}_{i,t}$ (i.e. $\boldsymbol{\theta}_{ik,t+1} = \boldsymbol{\theta}_{i,t}$). Therefore, the k-th client sends $\boldsymbol{\theta}_{ik,t+1}$ to the server only if $i \in \mathcal{S}_{k,t}$. Therefore, at each time instant, each client needs to send at most $2MD$ parameters to the server. Let $\mathcal{C}_{i,t}$ be a set of client indices such that $k \in \mathcal{C}_{i,t}$ if the k-th client sends $\boldsymbol{\theta}_{ik,t+1}$ to the server. Upon aggregating updates from clients, the server updates $\boldsymbol{\theta}_{i,t}$ as

$$\boldsymbol{\theta}_{i,t+1} = \boldsymbol{\theta}_{i,t} - \frac{1}{K} \sum_{k \in \mathcal{C}_{i,t}} (\boldsymbol{\theta}_{i,t} - \boldsymbol{\theta}_{ik,t+1}) = \boldsymbol{\theta}_{i,t} - \frac{\eta}{K} \sum_{k=1}^{K} \frac{\nabla \mathcal{L}(\boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})}{p_{ik,t}} \mathbf{1}_{i \in \mathcal{S}_{k,t}}. \quad (10)$$

Algorithm 2 summarizes the proposed personalized online federated multi-kernel learning algorithm called POF-MKL. It is useful to note that using our proposed POF-MKL, the server cannot find the gradients $\nabla \mathcal{L}(\boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})$ from updates received from clients. Instead, the server can find $\nabla \mathcal{L}(\boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})/p_{ik,t}$ where $p_{ik,t}$ is a time-varying value determined locally by the k-th client. This can promote the privacy of the proposed POF-MKL since exchanging the gradients can be hazardous to the privacy of federated learning (see e.g. [37, 7]).

3.2 Regret Analysis

The present section analyzes the regret of the proposed POF-MKL. Specifically, two types of regret $\mathcal{R}_{k,T}$ and $\mathcal{R}_{s,T}$ are considered for the k-th client and the server, respectively. The performance of the k-th client utilizing POF-MKL is analyzed in terms of regret defined as

$$\mathcal{R}_{k,T} = \sum_{t=1}^{T} \mathcal{L}(\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t}), y_{k,t}) - \min_{i \in [N]} \sum_{t=1}^{T} \mathcal{L}(\hat{f}_{\text{RF},it}(\boldsymbol{x}_{k,t}), y_{k,t}) \quad (11)$$

where $\mathcal{R}_{k,T}$ measures the cumulative difference between the loss of the k-th client and the loss of the RF approximation of the kernel with minimum loss among all kernels' RF approximations. Let $\alpha_{ik,t}^*$, $\forall t \in [T]$, $\forall k \in [K]$ represents the optimal coefficients associated with the i-th kernel such that $f_i^*(\boldsymbol{x}) = \sum_{t=1}^{T} \sum_{k=1}^{K} \alpha_{ik,t}^* \kappa_i(\boldsymbol{x}, \boldsymbol{x}_{k,t})$. Then the best function approximator is defined as $f^*(\cdot) \in \arg\min_{f_i^*, i \in [N]} \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(f_i^*(\boldsymbol{x}_{k,t}), y_{k,t})$. Furthermore, the regret of the server is defined as the cumulative difference between the loss of POF-MKL and that of the best function approximator over all data samples distributed among clients which can be expressed as

$$\mathcal{R}_{s,T} = \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t}), y_{k,t}) - \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(f^*(\boldsymbol{x}_{k,t}), y_{k,t}). \quad (12)$$

In order to analyze the regret of POF-MKL, suppose that the following assumptions hold true:

(as1) $\mathcal{L}(\boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})$, $\forall k \in [K]$ is convex with respect to $\boldsymbol{\theta}_{i,t}$ at each time instant t.

(as2) For $\boldsymbol{\theta}$ in a bounded set satisfying $\|\boldsymbol{\theta}\| \leq C$, the loss function and its gradient are bounded

as $0 \leq \mathcal{L}(\boldsymbol{\theta}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t}) \leq 1$ and $\|\nabla \mathcal{L}(\boldsymbol{\theta}^\top \boldsymbol{z}_i(\boldsymbol{x}_{k,t}), y_{k,t})\| \leq L$. Moreover, each data sample is bounded as $\|\boldsymbol{x}_{k,t}\| \leq 1, \forall k \in [K], \forall t \in [T]$.

(as3) Kernels $\kappa_i(\cdot), \forall i \in [N]$ are shift-invariant with $\kappa_i(\boldsymbol{0}) = 1, \forall i \in [N]$.

The following theorem investigates the regret of the k-th client according to the k-th client data. The proof of the following Theorem can be found in Appendix A.

Theorem 1. *Under (as1)–(as3), the regret of the k-th client with respect to the best kernel satisfies*

$$\sum_{t=1}^{T} \mathcal{L}(\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t}), y_{k,t}) - \min_{i \in [N]} \sum_{t=1}^{T} \mathcal{L}(\hat{f}_{RF,it}(\boldsymbol{x}_{k,t}), y_{k,t}) \leq \frac{\ln N}{\eta_k} + \frac{\eta_k}{2} T. \quad (13)$$

Theorem 1 shows that by setting $\eta_k = \mathcal{O}\left(\frac{1}{\sqrt{T}}\right)$, the k-th client achieves sub-linear regret of $\mathcal{O}(\sqrt{T})$. Furthermore, Theorem 1 shows that POF-MKL can deal with heterogeneous data among clients since the regret of each client defined in (11) is calculated with respect to the corresponding client data. The following theorem studies the regret of the server with respect to the best function approximator. The proof can be found in Appendix B.

Theorem 2. *Let $i^* := \arg\min_{i \in [N]} \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(f_i^*(\boldsymbol{x}_{k,t}), y_{k,t})$ and σ_i be the second Fourier moment of the i-th kernel. Under (as1)–(as3), the regret of the server with respect to the best function approximator satisfies*

$$\sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(\hat{f}(\boldsymbol{x}_{k,t}; \boldsymbol{\Theta}_t, \boldsymbol{w}_{k,t}), y_{k,t}) - \sum_{t=1}^{T} \sum_{k=1}^{K} \mathcal{L}(f^*(\boldsymbol{x}_{k,t}), y_{k,t})$$

$$\leq \frac{(1+\epsilon)KC}{2\eta} + \frac{\eta}{2} \sum_{t=1}^{T} \sum_{k=1}^{K} \frac{L^2}{p_{i^*k,t}} + \sum_{k=1}^{K} \left(\frac{\ln N}{\eta_k} + \frac{\eta_k}{2} T \right) + \epsilon LKTC \quad (14)$$

with probability at least $1 - 2^8 \left(\frac{\sigma_{i^*}}{\epsilon}\right)^2 \exp\left(-\frac{D\epsilon^2}{4(d+2)}\right)$ where $C := \max_{i \in [N]} \sum_{t=1}^{T} \sum_{k=1}^{K} \alpha_{ik,t}^*$.

As it can be inferred from (14), the regret of the server with respect to the best function approximator depends on $\frac{1}{p_{i^*k,t}}$. From (8) and the fact that $p_{ik,t} = q_{b_i k,t}$, it can be concluded that $p_{i^*k,t} > \frac{\xi_k}{m}$. Thus, setting $\xi_k = \mathcal{O}(1)$, then $p_{ik,t} > \mathcal{O}(\frac{M}{N})$. The regret bound in (14) shows that setting $\eta = \mathcal{O}\left(\sqrt{\frac{M}{NT}}\right)$ and $\epsilon = \eta_k = \frac{1}{\sqrt{T}}, \forall k \in [K]$, the server obtains regret of $\mathcal{O}\left(\sqrt{\frac{N}{M}T}\right)$ with probability at least $1 - 2^8 \left(\frac{\sigma_{i^*}}{\epsilon}\right)^2 \exp\left(-\frac{D\epsilon^2}{4(d+2)}\right)$. This shows that increasing M tighten the regret bound and increasing D increases the probability that the regret bound in (14) holds true. However, using POF-MKL, each client needs to transmit MD parameters at each time instant. Since both M and D are determined by the algorithm POF-MKL, this shows that POF-MKL can provide flexibility to tighten regret bound while the available clients-to-server communication bandwidth can afford transmission of clients' updates to the server.

Comparison with online federated learning [22]. Fed-OMD algorithm has been proposed in [22] which enables clients to perform their learning task in an online and federated fashion while it is proved that Fed-OMD enjoys sub-linear regret when the loss function is convex with respect to parameters required to be learnt at each time instant. The proposed POF-MKL differs from Fed-OMD in the sense that Fed-OMD cannot guarantee sub-linear regret when it comes to performing the online learning task with RF approximations of multiple kernels since the loss function $\mathcal{L}(\sum_{i=1}^{N} w_{i,t} \boldsymbol{\theta}_{i,t}^\top \boldsymbol{z}_i(\boldsymbol{x}), y)$ is not convex with respect to both $\boldsymbol{\theta}_{i,t}$ and $w_{i,t}$. However, according to Theorems 1 and 2, the proposed POF-MKL guarantees sub-linear regret.

Comparison with [12]. Online federated MKL algorithms called vM-KOFL and eM-KOFL have been presented in [12]. The proposed POF-MKL has the following advantages and innovations compared to vM-KOFL and eM-KOFL: i) As it is proved in Theorem 1, the proposed POF-MKL can deal heterogeneous data among clients in a sense that using POF-MKL each client guarantees sub-linear regret with respect to the best kernel RF approximation according to the corresponding

264 client data. However, both vM-KOFL and eM-KOFL are not able to provide such guarantee. ii)
265 Using vM-KOFL, each client needs to send $(N + 1)D$ parameters to the server. However, using the
266 proposed POF-MKL, each client needs to send MD parameters to the server such that $M \leq N$ is
267 determined by POF-MKL and can be chosen to be much smaller than N. iii) In eM-KOFL, the server
268 chooses a kernel at each time instant and clients send their local updates associated with the chosen
269 kernel by the server. The proposed POF-MKL provides more flexibility compared to eM-KOFL in
270 the sense that using POF-MKL each client can send local updates of $M \geq 1$ kernels to the server.
271 And each client chooses its own subset of kernels to send their updates to the server. Therefore,
272 even though POF-MKL sets M to 1, it is possible that at a time instant the server receives updates
273 associated with all kernels in the dictionary.

4 Experiments

275 We tested the performance of the proposed POF-MKL for online regression task through a set of
276 experiments. The performance of POF-MKL is compared with the baselines OFSKL, OFMKL-Avg,
277 vM-KOFL and eMKOFL. OFSKL leverages Fed-OMD [22] when a single radial basis function
278 (RBF) with bandwidth of 10 is employed to perform the learning task. In OFMKL-Avg, kernels are
279 learned independently from each other using Fed-OMD [22] and the prediction is the average of
280 approximations given by kernels. Moreover, vM-KOFL and eMKOFL are online federated MKL
281 algorithms of [12] such that vM-KOFL requires transmission of all kernel updates at every time instant
282 while eM-KOFL requires transmission of a kernel update at each time instant. In the experiments,
283 each client observes 500 samples until the end of the learning task meaning that $T = 500$. The
284 performance of the proposed POF-MKL and other baselines are tested on the following real datasets
285 downloaded from UCI machine learning repository [5]: Naval [4], Air [35] and WEC [23]. More
286 detailed information about datasets can be found in Appendix C. Data samples of Naval dataset are
287 distributed i.i.d among clients. Data samples in Air and WEC datasets are distributed non-i.i.d among
288 clients. More inforamtion about distributing data samples among clients can be found in Appendix
289 C. The number of clients for Naval, Air and WEC datasets are 23, 240 and 560, respectively. The
290 dictionary of kernels consists of 51 RBFs with different bandwidth such that the bandwidth of the i-th
291 kernel is $\sigma_i = 10^{\frac{2i-52}{25}}$. We consider the case where the clients-to-server communication bandwidth
292 is limited such that at each time instant, the maximum number of parameters that a client is allowed
293 to transmit to the server is 1000. Furthermore, the memory and computational capability of clients
294 are limited such that the maximum value can be picked for D is 100. The experiments were carried
295 for 20 different sets of random feature vectors. The performance of algorithms is measured using
296 average of mean squared error (MSE) defined as

$$\text{MSE} = \frac{1}{20} \sum_{j=1}^{20} \frac{1}{KT} \sum_{t=1}^{T} \sum_{k=1}^{K} (\hat{y}_{jk,t} - y_{k,t})^2$$

297 where $\hat{y}_{jk,t}$ denotes the prediction of the k-th client at time instant t corresponding to the j-th set of
298 random feature vectors. Learning rates are set to $\eta = \eta_k = \frac{1}{\sqrt{T}}, \forall k$. Also, exploration rates are set to
299 $\xi_k = 1, \forall k$. The performance of POF-MKL with different ξ_k is studied in Appendix C.

300 Table 1 presents the MSE and run time performance of online federated kernel learning algorithms
301 on real datasets. Run time reported in Table 1 refers to average total run time of clients to perform
302 online learning task on the entire data samples that they observe. In Table 1, M refers to the number
303 of kernels whose updates are sent to the server after prediction at each time instant. And, D is the
304 number of random features. Comparing MSE of POF-MKL with that of OFMKL-Avg, it can be
305 concluded that learning the weights to combine kernels provides higher accuracy than averaging
306 kernels' predictions. Table 1 shows that POF-MKL with $M = 1$ provides lower MSE than eM-KOFL.
307 Using eM-KOFL, at each time instant, the server receives updates belong to only one kernel. However,
308 using POF-MKL with $M = 1$, each client sends an update belongs to a kernel which is selected
309 by the client. Therefore, the server receives updates associated with different kernels even though
310 $M = 1$. Therefore, Table 1 shows the effectiveness of the flexibility provided by POF-MKL. From
311 Table 1 it can be observed that POF-MKL with $M = 25$ obtains lower MSE than those of POF-MKL

Table 1: MSE($\times 10^{-3}$) and run time of online federated learning algorithms on real datasets.

Algorithms	M	D	MSE($\times 10^{-3}$)			Run time(s)		
			Naval	Air	WEC	Naval	Air	WEC
OFSKL	1	100	77.77	13.65	87.87	0.07	0.08	0.06
OFMKL-Avg	51	9	33.25	10.63	34.01	1.51	0.91	0.47
vM-KOFL	51	9	26.42	10.58	25.17	2.01	1.37	0.67
eM-KOFL	1	100	28.64	21.94	20.14	2.27	1.45	1.70
POF-MKL	1	100	**16.16**	**9.27**	**11.44**	1.22	1.25	1.10
POF-MKL	25	20	16.82	9.34	11.58	0.69	0.63	0.52
POF-MKL	51	9	16.65	9.38	11.97	0.82	0.81	0.65

(a) Naval dataset.   (b) Air dataset.   (c) WEC dataset.

Figure 1: Average regret of clients.

with $M = 51$ and vM-KOFL. Since each client is allowed to send at most 1000 parameters per time instant, if clients send updates of all kernels at every time instant as this is the case in vM-KOFL, D cannot be chosen to be greater than 9. However, setting $M = 25$, POF-MKL can set $D = 20$ which can improve the accuracy of online regression task compared to the case where $D = 9$. Furthermore, Table 1 shows that POF-MKL with $M = 51$ achieves lower MSE than vM-KOFL even if data samples are distributed i.i.d among clients. This shows that the proposed POF-MKL can better cope with heterogeneous data among clients which is in agreement with theoretical results in Theorem 1. As it can be seen from Table 1, the proposed POF-MKL with $M = 1$ and $M = 25$ runs faster than both vM-KOFL and eM-KOFL. In fact, using POF-MKL, clients only needs to update parameters associated with M kernels while employing vM-KOFL and eM-KOFL, clients have to update parameters of all kernels. Since OFSKL employs only a pre-selected single kernel, OFSKL runs faster than POF-MKL. However, as it can be seen from Table 1, utilizing multiple kernels enables POF-MKL to obtain lower MSE than that of OFSKL. Furthermore, Figure 1 illustrates the average regret of clients on Naval, Air and WEC datasets when clients employ vM-KOFL and proposed POF-MKL with different M parameters. From Figure 1, it can be observed that the proposed POF-MKL achieves sub-linear regret.

5 Conclusions

The present paper proposed a personalized online federated MKL algorithm called POF-MKL based on RF approximation. Employing the proposed POF-MKL, each client updates the parameters of a subset of kernels which alleviates the computational complexity of the client as well as communication cost of sending updated parameters of kernels. Theoretical analysis proved that using POF-MKL, each client achieves sub-linear regret with respect to the RF approximation of its best kernel in hindsight which indicates that POF-MKL can deal heterogeneous data among clients. While each client updates a subset of kernels, it was proved that the server achieves sub-linear regret with respect to the best function approximator. Experiments on real datasets showcased the advantages of POF-MKL compared with other online federated kernel learning algorithms.

References

[1] Yoshua Bengio, Olivier Delalleau, and Nicolas L. Roux. The curse of highly variable functions for local kernel machines. In *Advances in Neural Information Processing Systems*, pages 107–114, May 2006.

[2] Pantelis Bouboulis, Symeon Chouvardas, and Sergios Theodoridis. Online distributed learning over networks in rkh spaces using random fourier features. *IEEE Transactions on Signal Processing*, 66(7):1920–1932, Apr 2018.

[3] Liam Collins, Hamed Hassani, Aryan Mokhtari, and Sanjay Shakkottai. Exploiting shared representations for personalized federated learning. In *Proceedings of the International Conference on Machine Learning*, volume 139, pages 2089–2099, Jul 2021.

[4] Andrea Coraddu, Luca Oneto, Aessandro Ghio, Stefano Savio, Davide Anguita, and Massimo Figari. Machine learning approaches for improving condition-based maintenance of naval propulsion plants. *Proceedings of the Institution of Mechanical Engineers, Part M: Journal of Engineering for the Maritime Environment*, 230(1):136–153, 2016.

[5] Dheeru Dua and Casey Graff. UCI machine learning repository, 2017.

[6] Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. Personalized federated learning with theoretical guarantees: A model-agnostic meta-learning approach. In *Advances in Neural Information Processing Systems*, volume 33, pages 3557–3568, Dec 2020.

[7] Jonas Geiping, Hartmut Bauermeister, Hannah Dröge, and Michael Moeller. Inverting gradients - how easy is it to break privacy in federated learning? In *Advances in Neural Information Processing Systems*, volume 33, pages 16937–16947, 2020.

[8] Pouya M Ghari and Yanning Shen. Online multi-kernel learning with graph-structured feedback. In *Proceedings of the International Conference on Machine Learning*, volume 119, pages 3474–3483, Jul 2020.

[9] Vinay Chakravarthi Gogineni, Stefan Werner, Yih-Fang Huang, and Anthony Kuh. Communication-efficient online federated learning framework for nonlinear regression. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5228–5232, May 2022.

[10] Jenny Hamer, Mehryar Mohri, and Ananda Theertha Suresh. FedBoost: A communication-efficient algorithm for federated learning. In *Proceedings of International Conference on Machine Learning*, volume 119, pages 3973–3983, Jul 2020.

[11] Steven C. H. Hoi, Rong Jin, Peilin Zhao, and Tianbao Yang. Online multiple kernel classification. *Machine Learning*, 90:289–316, Feb 2013.

[12] Songnam Hong and Jeongmin Chae. Communication-efficient randomized algorithm for multi-kernel online federated learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Nov 2021.

[13] Peter Kairouz, H. Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, Rafael G. L. D'Oliveira, Hubert Eichner, Salim El Rouayheb, David Evans, Josh Gardner, Zachary Garrett, Adrià Gascón, Badih Ghazi, Phillip B. Gibbons, Marco Gruteser, Zaid Harchaoui, Chaoyang He, Lie He, Zhouyuan Huo, Ben Hutchinson, Justin Hsu, Martin Jaggi, Tara Javidi, Gauri Joshi, Mikhail Khodak, Jakub Konecný, Aleksandra Korolova, Farinaz Koushanfar, Sanmi Koyejo, Tancrède Lepoint, Yang Liu, Prateek Mittal, Mehryar Mohri, Richard Nock, Ayfer Özgür, Rasmus Pagh, Hang Qi, Daniel Ramage, Ramesh Raskar, Mariana Raykova, Dawn Song, Weikang Song, Sebastian U. Stich, Ziteng Sun, Ananda Theertha Suresh, Florian Tramèr, Praneeth Vepakomma, Jianyu Wang, Li Xiong, Zheng Xu, Qiang Yang, Felix X. Yu, Han Yu,

and Sen Zhao. Advances and open problems in federated learning. *Foundations and Trends®
in Machine Learning*, 14(1–2):1–210, 2021.

[14] Marius Kloft, Ulf Brefeld, Sören Sonnenburg, and Alexander Zien. Lp-norm multiple kernel
learning. *Journal of Machine Learning Research*, 12:953–997, Jul 2011.

[15] Jakub Konečný, H. Brendan McMahan, Felix X. Yu, Peter Richtárik, Ananda Theertha Suresh,
and Dave Bacon. Federated learning: Strategies for improving communication efficiency, 2017.

[16] Anthony Kuh. Real time kernel learning for sensor networks using principles of federated
learning. In *Asia-Pacific Signal and Information Processing Association Annual Summit and
Conference (APSIPA ASC)*, pages 2089–2093, Dec 2021.

[17] Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Chal-
lenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020.

[18] Xiaoxiao Li, Meirui Jiang, Xiaofei Zhang, Michael Kamp, and Qi Dou. FedBN: Federated
learning on non-IID features via local batch normalization. In *International Conference on
Learning Representations*, 2021.

[19] Jing Lu, Steven C.H. Hoi, Jialei Wang, Peilin Zhao, and Zhi-Yong Liu. Large scale online
kernel learning. *Journal of Machine Learning Research*, 17(47):1–43, 2016.

[20] Shaogao Lv, Junhui Wang, Jiankun Liu, and Yong Liu. Improved learning rates of a functional
lasso-type svm with sparse multi-kernel representation. In *Advances in Neural Information
Processing Systems*, volume 34, pages 21467–21479, Dec 2021.

[21] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas.
Communication-Efficient Learning of Deep Networks from Decentralized Data. In *Proceedings
of International Conference on Artificial Intelligence and Statistics*, volume 54, pages 1273–
1282, Apr 2017.

[22] Aritra Mitra, Hamed Hassani, and George J. Pappas. Online federated learning. In *IEEE
Conference on Decision and Control (CDC)*, pages 4083–4090, Dec 2021.

[23] Mehdi Neshat, Bradley Alexander, Markus Wagner, and Yuanzhong Xia. A detailed comparison
of meta-heuristic methods for optimising wave energy converter placements. In *Proceedings of
the Genetic and Evolutionary Computation Conference*, page 1318–1325, Jul 2018.

[24] Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Proceed-
ings of International Conference on Neural Information Processing Systems*, pages 1177–1184,
Dec 2007.

[25] Daniel Rothchild, Ashwinee Panda, Enayat Ullah, Nikita Ivkin, Ion Stoica, Vladimir Braverman,
Joseph Gonzalez, and Raman Arora. FetchSGD: Communication-efficient federated learning
with sketching. In *Proceedings of International Conference on Machine Learning*, volume 119,
pages 8253–8265, Jul 2020.

[26] Alessandro Rudi and Lorenzo Rosasco. Generalization properties of learning with random
features. In *Proceedings of International Conference on Neural Information Processing Systems*,
page 3218–3228, 2017.

[27] Doyen Sahoo, Steven C.H. Hoi, and Bin Li. Online multiple kernel regression. In *Proceedings
of ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, page
293–302, 2014.

[28] Doyen Sahoo, Steven C. H. Hoi, and Bin Li. Large scale online multiple kernel regression with
application to time-series prediction. *ACM Transactions on Knowledge Discovery from Data*,
13(1), Jan 2019.

[29] Bernhard Scholkopf and Alexander J. Smola. *Learning with Kernels: Support Vector Machines, Regularization, Optimization, and Beyond.* MIT Press, Cambridge, MA, USA, 2001.

[30] Yanning Shen, Tianyi Chen, and Georgios B. Giannakis. Random feature-based online multi-kernel learning in environments with unknown dynamics. *Journal of Machine Learning Research*, 20(1):773–808, Jan 2019.

[31] Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet S Talwalkar. Federated multi-task learning. In *Advances in Neural Information Processing Systems*, volume 30, pages 4424–4434, Dec 2017.

[32] Sören Sonnenburg, Gunnar Rätsch, Christin Schäfer, and Bernhard Schölkopf. Large scale multiple kernel learning. *Journal of Machine Learning Research*, 7:1531–1565, Dec 2006.

[33] Grace Wahba. *Spline Models for Observational Data.* Society for Industrial and Applied Mathematics, 1990.

[34] Christopher K. I. Williams and Matthias Seeger. Using the nyström method to speed up kernel machines. In *Proceedings of the International Conference on Neural Information Processing Systems*, page 661–667, Jan 2000.

[35] Shuyi Zhang, Bin Guo, Anlan Dong, Jing He, Ziping Xu, and Song Xi Chen. Cautionary tales on air-quality improvement in beijing. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 473(2205):20170457, 2017.

[36] Xiao Zhang and Shizhong Liao. Incremental randomized sketching for online kernel learning. In *Proceedings of International Conference on Machine Learning*, pages 7394–7403, Jun 2019.

[37] Ligeng Zhu, Zhijian Liu, and Song Han. Deep leakage from gradients. In *Advances in Neural Information Processing Systems*, volume 32, 2019.