HeRo-Nav: Heterogeneous Multi-Robot Collaboration for Semantic Navigation With Vision Language Models

Abstract—Heterogeneous multi-robot teams can combine complementary locomotion, sensing, and payload capabilities, but coordinating them requires understanding both what the task entails and what role or functionality each robot affords. We present HeRo-Nav, a zero-shot coordination architecture that feeds egocentric frontier images, a shared occupancy map, and natural-language affordance profiles to a Vision-Language Model (VLM), which assigns robots to frontiers based on both scene semantics and each robot's terrain compatibility. We evaluate HeRo-Nav on a hospital disaster scenario in NVIDIA Isaac Sim with three distinct embodiments and platform-dependent terrain hazards. HeRo-Nav achieves the highest success rate (93.3%) and the lowest team hazard exposure (25.7%), providing direct evidence that the VLM assigns robots according to their affordances rather than geometry alone. We analyze conditions under which this affordance-aware reasoning succeeds, adds unnecessary deliberation cost, or fails to outperform geometric baselines, contributing failure-mode insights for deploying foundation models in multi-robot navigation.

Fig. 1. HeRo-Nav coordinates a heterogeneous team (quadruped, humanoid, drone) to locate casualties in a disaster-struck hospital. The VLM coordinator assigns each robot to frontiers suited to its affordances.

I. INTRODUCTION

Multi-robot systems are increasingly deployed in complex, large-scale missions such as subterranean exploration and disaster response [6, 8]. These environments expose the inherent trade-offs of any single platform: a drone's aerial mobility affords it rapid survey of collapsed, debris-filled passages, yet it lacks the payload capacity to deliver rescue equipment; a quadruped's sturdy build affords it heavy transport, but it moves slowly in rubble and on stairs. Heterogeneous teams combining diverse locomotion, sensing, and payload capabilities are a natural answer, but fielding such diverse hardware significantly increases coordination complexity. Vision-Language Models (VLMs) [16, 25, 18], which reason jointly over visual observations and natural-language descriptions, offer a promising solution, mapping open-vocabulary scene and task semantics onto the affordances of each robot across diverse environments.

Existing frameworks address pieces of this problem in isolation. A first line of work tackles spatial coordination: heterogeneous exploration systems assign complementary roles based on platform speed and sensing modality [4, 26, 28], while traversability-aware routers couple agent kinematics with terrain constraints [21, 14, 7]. These planners effectively encode what each robot can do, yet the role assignments are fixed and the systems lack scene-level semantic understanding, limiting their ability to adapt to novel tasks.

A second line brings semantic understanding to spatial coordination. Navigation frameworks driven by VLMs enable zero-shot frontier reasoning for single-agent object-goal navigation [22, 20]. Extending to multi-robot teams, Co-NavGPT [23] employs a centralized VLM for frontier allocation, while MCoCoNav [17] and GoalVLM [10] introduce decentralized VLM-driven frontier scoring mechanisms over shared semantic maps. However, they typically assume a homogeneous fleet. The sole exception, COMRES-VLM [19], deploys a heterogeneous air-ground team but feeds only robot positions to the VLM, assigning frontiers without any notion of per-agent capabilities.

A third direction uses Large Language Models (LLMs) to dynamically reason about which robot should handle which task [24, 27, 1]. RoCo [13] builds consensus through inter-robot dialogue, COHERENT [12] decomposes long-horizon instructions and assigns subtasks to the best-matched agent, and EMOS [5] parses robot URDF files into capability descriptions for embodiment-aware reasoning. These methods can interpret novel task requirements, but they operate entirely over text, and hence lack the spatial context required for complex heterogeneous coordination.

To bridge this gap, we present **HeRo-Nav** (**He**terogeneous Multi-**Ro**bot Collaboration for Semantic **Nav**igation With Vision Language Models), which fuses a shared bird's-eye-view (BEV) occupancy map, egocentric RGB frontier observations, per-robot affordance profiles, and robot-frontier distances into a VLM-based frontier-assignment loop, enabling zero-shot heterogeneous coordination without task-specific fine-tuning.

Fig. 2. HeRo-Nav system architecture. Each robot processes RGB-D into per-class BEV occupancy maps (one per robot class). Per-class maps from all robots are fused, then merged under a most-permissive policy for frontier extraction. A candidate set of frontiers is selected and passed, along with egocentric RGB observations, the annotated BEV map, mission goal, per-robot affordance profiles, and robot-candidate distances, to a VLM coordinator that outputs robot-to-frontier assignments. Each robot executes its assignment via A* on its own per-class map.

We evaluate HeRo-Nav on a hospital disaster scenario built in NVIDIA Isaac Sim [15] (Fig. 1), where three hazard categories impose platform-dependent traversal costs and semantic cues scattered through the scene reward visual reasoning over geometric planning.

In summary, our contributions are:

- We present HeRo-Nav, a coordination framework that integrates semantic scene and affordance reasoning into a VLM frontier-assignment loop for zero-shot heterogeneous multi-robot navigation.
- We develop a multi-embodiment evaluation scenario in Isaac Sim with platform-dependent terrain to test affordance-aware coordination.
- We empirically analyze when affordance-aware VLM coordination succeeds and when it fails, contributing failure-mode insights for deploying foundation models in multi-robot navigation. HeRo-Nav attains the highest success rate (93.3% vs. 86.7% for the best classical baseline) and the lowest team hazard exposure (25.7% vs. 40.1%), evidence that it routes robots by affordance rather than geometry.

II. METHODS

A. Problem Setup

We consider a team of N heterogeneous robots $\mathcal{R} = \{r_1, \ldots, r_N\}$ spanning C robot classes (e.g., quadruped, drone, humanoid), tasked with locating a goal g (specified in natural language) in a previously unknown environment. Each robot class is defined by a textual affordance profile describing its locomotion modality and terrain-traversability characteristics. The robots collaboratively build a shared occupancy representation and extract a frontier set $\mathcal{F}_t = \{f_1, \ldots, f_K\}$,

where each frontier f_k has a world location and a visual observation o_k. A coordinator produces an assignment $\mathcal{A}_t : \mathcal{R} \rightarrow \mathcal{F}_t \cup \{\varnothing\}$ mapping each robot to a frontier or to a no-op. The objective is to maximize mission success while minimizing mission time by selecting assignments that account for both task-relevant scene semantics and each robot's terrain compatibility. Unlike classical frontier allocators that optimize hand-crafted geometric costs (e.g., trading distance against information gain), HeRo-Nav applies geometric filtering to reduce the candidate frontier set to a manageable size, then uses VLM reasoning over the task and scene semantics with the affordance compatibility of each robot-frontier pair to make the final assignment.

B. System Architecture

HeRo-Nav operates as a cyclic coordination framework (Fig. 2) with five stages that carry raw observations to robot-to-frontier assignments and back. The first three stages build a capability-aware shared map and frontier set. The VLM coordinator then makes the assignment conditioned on per-frontier egocentric views and per-robot affordance profiles, the inputs prior multi-robot VLM coordinators omit.

Per-robot mapping. Each robot converts its onboard RGB-D stream into C separate 2D bird's-eye-view (BEV) occupancy maps, one per robot class, since what counts as an obstacle depends on platform geometry. It shares the resulting per-class occupancy updates and RGB keyframes with a centralized map service; raw depth is processed locally and not transmitted.

Map merging and frontier extraction. From the per-class updates of all robots, the map service builds the frontier set in two steps. It first accumulates each class's evidence via log-odds into one per-class map (e.g., all quadruped-class observations into one quadruped map), then merges the C maps under a

most-permissive policy. A cell is free if any class can traverse it, so frontier extraction is not bounded by the most constrained platform. Frontiers are connected components of free cells adjacent to unexplored space, filtered by minimum area and obstacle clearance. Each frontier receives a persistent ID, a world location, and one cached egocentric RGB observation o_k, captured once from the robot whose heading best aligns with the frontier (most-centred bearing, within horizontal FOV and a near/far depth range) and not refreshed on subsequent steps.

Frontier candidate selection. From the full frontier set, a global candidate set of up to M frontiers is shortlisted to bound prompt length. A Hungarian assignment [11] over agent–frontier Euclidean distance and frontier area reserves one geometrically favourable frontier per agent (one-to-one, so no two agents share); each agent's current in-flight target is also retained to prevent assignment oscillation, and remaining slots are filled by largest frontier area. This step only selects which frontiers the coordinator sees; the assignment itself is made by the VLM.

VLM coordinator. The candidate set drives the assignment, where affordance reasoning takes effect. A pretrained VLM (Qwen3.6-35B-A3B [16]) receives a multimodal prompt containing: (i) the mission goal g; (ii) for each candidate frontier, its RGB observation o_k and distance from each robot; (iii) for each robot, its current position and a short natural-language affordance profile of its locomotion and terrain traversability (e.g., the quadruped's reads "Quadruped. Small clutter barely slows it; rubble / concrete piles / heavy debris slow it a LOT."); (iv) the permissive BEV map with historical agent trajectories and candidate frontiers. The prompt instructs the model to interpret scene semantics at each frontier, match them against the affordance profiles, and coordinate globally to avoid redundant coverage. It emits a structured JSON assignment, parsed into $\mathcal{A}_t$.

Local execution. Given $\mathcal{A}_t$, each assigned robot plans an A* path on its own per-class occupancy map and tracks it with a local controller; if a robot stalls, a virtual obstacle placed ahead forces A* to replan around the blockage on the next cycle. Execution yields new observations that feed the next mapping cycle, and the coordinator re-issues assignments periodically, closing the loop.

III. EXPERIMENTS

A. Simulation Platform and Benchmark

Simulator and team. Built on NVIDIA Isaac Sim for high visual and physical fidelity, our environment supports a configurable heterogeneous team of quadrupeds, humanoids, and drones. This selection provides diverse camera heights, base speeds, and locomotion modes (Table I). To minimize the sim-to-real gap, these parameters are matched to the published specifications of representative physical platforms: the Unitree Go2, Unitree H1, and a mid-range quadrotor. Per-platform hazard multipliers proxy locomotion-dependent cost, keeping coordination separate from low-level control (physical locomotion is future work, Sec. IV). Communication uses the

TABLE I
PLATFORM CHARACTERISTICS AND SPEED MULTIPLIERS BY HAZARD CATEGORY (1.0 = UNIMPEDED).

	Quadruped	Drone	Humanoid
Camera height (m)	0.3	2.0	1.5
Base speed (m/s)	2.0	3.0	1.0
Hard-ground (rubble)	0.30	1.00	0.10
Easy-ground (clutter)	0.90	1.00	0.80
High-occlude (shelves)	0.80	0.20	0.60

shared map service of Sec. II-B, and each robot runs its own local policy, so sensing, communication, and execution are per-agent.

Hazard scenario. To evaluate multi-robot teaming, we design a hospital disaster relief environment.[1] The hospital environment contains three hazard categories that impose platform-dependent speed multipliers (Table I): hard-ground obstacles (rubble, concrete), easy-ground clutter (books, bags), and high-occlude structures (toppled shelving). The speed multipliers are hand-specified proxies reflecting known platform traits: quadrupeds handle uneven terrain better than humanoids, drones are unaffected by ground clutter but must detour around tall shelving. Semantic cues such as personal belongings are placed throughout the environment to suggest likely victim locations, providing visual breadcrumbs that a VLM coordinator can leverage but geometric methods cannot.

Benchmark generation. We evaluate across 15 episodes from three spawn locations; each varies the target location, semantic cue placement, and hazard distribution. An episode is scored as successful when any agent comes within 5 m of the ground-truth goal location (the casualty) while observing the target.

B. Baselines

All methods share the same perception, mapping, frontier-extraction and execution stack; they differ only in the frontier-assignment policy, isolating the effect of coordination. The assignment frequency is fixed at 0.125 Hz for all methods, matching the slowest (VLM-based) approaches.

1) **Greedy Cost-Utility (GCU) [2]:** each robot is assigned to the frontier that best trades off travel distance against information gain.
2) **Hungarian [11]:** the globally optimal one-to-one assignment minimizing total travel cost.
3) **Co-NavGPT*:** our adaptation of Co-NavGPT [23] on our heterogeneous stack, preserving its original interface: a top-view map with robot positions and frontiers, without per-frontier RGB observations or per-robot affordance profiles.
4) **HeRo-Nav (Ours):** the full affordance-aware VLM coordinator (Sec. II).

C. Evaluation Metrics

1) **Success Rate (SR) ↑.** Fraction of episodes in which the team localizes and reaches the goal within the time

---

[1]Built upon the NVIDIA Isaac Sim Hospital environment.

budget. Each episode is capped at a 1000 s simulation-time budget, after which it is recorded as a failure.

2) **Travel Distance.** Total team travel distance, summed over all three agents and reported in metres, averaged over all episodes, including failures and timeouts.

3) **Mission Time ↓.** Mean time to complete an episode, in seconds, averaged over all episodes of a given method. A successful episode contributes its actual time-to-goal, whereas an unsuccessful episode is charged the full 1000 s.

4) **Hazard Exposure ↓.** Fraction of each robot's traversal spent on speed-degraded terrain, reported per robot type and team-pooled; the quantity an affordance-aware allocator should minimise.

D. Results

Table II compares HeRo-Nav with three representative baselines over all 15 episodes, split by casualty count, with per-robot hazard exposure.

HeRo-Nav outperforms all baselines in both success rate and hazard exposure, demonstrating the effectiveness of affordance-based coordination. From our experiment, we find that HeRo-Nav routes each platform onto terrain suited to its embodiment. Of all methods it spends the least traversal time on speed-degraded ground, on every robot type and team-pooled (25.7%, against 40.1% for Greedy; Table II), direct evidence that the coordinator assigns robots by affordance rather than by geometry alone. It also attains the highest success rate (93.3%), ahead of the strongest geometric baseline (Greedy, 86.7%) and well ahead of Co-NavGPT (66.7%), and its margin is largest on the harder single-casualty episodes, where the target is sparse and reaching it takes sustained search: HeRo-Nav solves 88.9% of them against 55.6–77.8% for the geometric planners (Table II); where the task is easy enough that any method finds a target, the gap closes. Taken together, the success rate and the hazard exposure establish the central result, that a VLM can coordinate a heterogeneous team and assign each robot according to what its embodiment can traverse.

The comparison with Co-NavGPT distinguishes our specific coordination contributions from the baseline capabilities of the VLM backbone. We adapt it to drive the heterogeneous team while preserving its original interface: a single coordinator reasoning over one shared bird's-eye-view map of robot positions and frontiers, without the egocentric per-frontier views or per-robot capability profiles that HeRo-Nav conditions on. Stripped of those inputs, the same VLM performs worst of all methods (66.7% success overall, 44.4% on single-casualty episodes), below both geometric baselines, and explores more of the floor area than any method while solving the fewest scenes, so its search is broad but unfocused. It also spends more traversal time on degraded terrain than HeRo-Nav on every robot type (31.3% team against 25.7%, and 51.6% against 40.6% for the humanoid; Table II). The capability profiles and egocentric grounding account for both the higher success rate and the better terrain decisions, which

places the source of the gain in the coordination design rather than the capacity of the language model.

HeRo-Nav is less efficient than traditional Greedy method while more effective in semantically complex hazard scenarios. HeRo-Nav is not the fastest method, Greedy completes episodes in less time and less distance (138.6 m and 398.2 s overall, against 156.6 m and 472.5 s; Table II). This is, however, not evidence that the coordinator decides poorly. Greedy sends each robot to its nearest frontier along the shortest geometric path, and in the present task the hazard penalties are mild enough that these short routes remain quickest even though they cut through degraded terrain, which is why Greedy records the highest hazard exposure of any method. HeRo-Nav routes around those hazards and searches more broadly, and the current benchmark does not reimburse the extra distance this costs. The efficiency ranking is therefore shaped by the task rather than by the quality of the coordination: HeRo-Nav makes the better affordance decisions, and a task that charged more for hazardous routing would turn them into a time advantage. The experiments establish the capability we set out to demonstrate; they also show that fully testing it requires a benchmark designed for heterogeneous teams.

IV. DISCUSSION

We identify two failure modes of the VLM coordinator observed in our experiments, and discuss limitations of the current evaluation that motivate future work.

A. Lack of Explicit Search and Coordination Memory

The coordinator has no persistent search memory. Relatedly, the coordinator's only record of the search so far is an annotated bird's-eye-view crop of past trajectories and frontier locations, a weak form of memory which we found insufficient in our experiments. Because it cannot reliably tell from this which regions have already been covered, some of the team's effort goes to backtracking and re-covering ground rather than extending into new areas (Fig. 3). Misleading semantics compound the problem: cues that do not lie on the path to the target pull agents off course and back across already-searched space, with nothing to record that the region, or the cue, was already accounted for. The two failures share a cause. The coordinator weighs each frontier and each cue reactively against the current map, with no persistent belief over where the team has been or which cues have already been investigated. A representation that binds the geometric history of the search to the semantic evidence gathered along it, in a form the model can reason over, would let the coordinator discount both explored regions and exhausted cues, producing more directed assignments.

B. Lack of Structured Spatial Representation

The coordinator operates zero-shot over a bird's-eye-view map, without a detailed spatial representation it can reason over. The geometry the allocator needs therefore has to be written into the prompt: we encode the distance between every agent and every frontier as an explicit pairwise comparison in

TABLE II

RESULTS OVER ALL 15 EPISODES AND SPLIT BY CASUALTY COUNT (LEFT), WITH PER-ROBOT HAZARD EXPOSURE (RIGHT).

Method	Overall (15)			1-Casualty (9)			2-Casualty (6)			Hazard exposure (%)			
	SR↑	Dist	Time↓	SR↑	Dist	Time↓	SR↑	Dist	Time↓	Quad↓	Drone↓	Human↓	Team↓
Greedy Cost Utility	86.7	**138.6**	**398.2**	77.8	**167.6**	**521.8**	100.0	**95.0**	**212.9**	52.4	17.2	50.6	40.1
Hungarian	73.3	177.9	506.3	55.6	218.1	678.7	100.0	117.4	247.8	36.2	7.0	51.5	31.6
Co-NavGPT	66.7	207.1	614.4	44.4	255.3	821.5	100.0	134.7	303.8	31.3	10.9	51.6	31.3
HeRo-Nav (Ours)	**93.3**	156.6	472.5	**88.9**	182.1	560.1	100.0	118.3	341.1	**30.7**	**5.7**	**40.6**	**25.7**

Fig. 3. Agent trajectories on a hard episode (scene 10); every method reaches the casualty (red star). Greedy takes short, direct routes, while the VLM methods frequently backtrack. On the episode HeRo-Nav was the only method to solve (scene 12), geometric methods passed close-by the casualty but didn't follow the semantic clues to look at it, unlike HeRo-Nav.

text. This scales poorly, since the prompt and the inference latency grow with the number of agent-frontier pairs. A structured geometric representation would reduce this bottleneck. 3D scene graphs [9] compress an environment into a compact relational form, and multi-robot variants already extend to heterogeneous teams [3]; adapting such a representation to carry both the semantic and the geometric structure the coordinator reasons over, in place of a hand-written list of distances, is a promising next iteration of the system. There is also scope to extend the information these representations classically encode, to enable better planning decisions by the VLM for the varying abilities of members of the team.

C. Evaluation Limitations

Neither the affordance nor the semantic capability of the method is fully exercised by the current task. The efficiency comparison showed that the task does not penalize hazardous routing enough, so HeRo-Nav's better terrain decisions do not register as a time advantage. The semantic side is the same: with two casualties present every method succeeds in every scene, so success rate no longer separates semantic search from coverage, and even with a single casualty the target is

often reachable by persistent exploration alone, so the cues help but are seldom necessary. A benchmark that exercises both capabilities would pose tasks a homogeneous team or a geometric planner cannot solve, where success depends on matching robots to what only their embodiment can do. As a preliminary test, we designed a scenario in which the VLM was told that only the humanoid could open doors and that a casualty was likely behind a closed room; the coordinator routed the humanoid toward door-adjacent frontiers, suggesting that affordance-gated tasks would sharpen evaluation. Additionally, our platform-dependent speed multipliers are hand-specified proxies; incorporating physics-based locomotion to empirically calibrate these values is an important direction for future work.

REFERENCES

[1] Michael Ahn, Debidatta Dwibedi, Chelsea Finn, Montse Gonzalez Arenas, Keerthana Gopalakrishnan, Karol Hausman, Brian Ichter, Alex Irpan, Nikhil Joshi, Ryan Julian, Sean Kirmani, Isabel Leal, Edward Lee, Sergey Levine, Yao Lu, Isabel Leal, Sharath Maddineni, Kanishka Rao, Dorsa Sadigh, Pannag Sanketi, Pierre

Sermanet, Quan Vuong, Stefan Welker, Fei Xia, Ted Xiao, Peng Xu, Steve Xu, and Zhuo Xu. AutoRT: Embodied Foundation Models for Large Scale Orchestration of Robotic Agents, July 2024.

[2] W. Burgard, M. Moors, C. Stachniss, and F.E. Schneider. Coordinated multi-robot exploration. *IEEE Transactions on Robotics*, 21(3):376–386, 2005. doi: 10.1109/TRO. 2004.839232.

[3] Yun Chang, Nathan Hughes, Aaron Ray, and Luca Carlone. Hydra-Multi: Collaborative online construction of 3D scene graphs with multi-robot teams. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2023.

[4] Junfeng Chen, Yuxiao Zhu, Xintong Zhang, Bin Luo, and Meng Guo. SLEI3D: Simultaneous Exploration and Inspection via Heterogeneous Fleets Under Limited Communication. *IEEE Transactions on Automation Science and Engineering*, 23:2339–2360, 2026. ISSN 1545-5955, 1558-3783. doi: 10.1109/TASE.2025.3643166.

[5] Junting Chen, Checheng Yu, Xunzhe Zhou, Tianqi Xu, Yao Mu, Mengkang Hu, Wenqi Shao, Yikai Wang, Guohao Li, and Lin Shao. EMOS: Embodiment-aware Heterogeneous Multi-robot Operating System with LLM Agents, February 2025.

[6] Timothy H. Chung, Viktor L. Orekhov, and Angela Maio. Into the robotic depths: Analysis and insights from the darpa subterranean challenge. *Annu. Rev. Control. Robotics Auton. Syst.*, 6:477–502, 2022. URL https://api.semanticscholar.org/CorpusID:256789326.

[7] Muhammad Fadhil Ginting, Kyohei Otsu, Mykel J. Kochenderfer, and Ali-akbar Agha-mohammadi. Capability-aware Task Allocation and Team Formation Analysis for Cooperative Exploration of Complex Environments. *arXiv e-prints*, page arXiv:2411.00400, November 2024. doi: 10.48550/arXiv.2411.00400. _eprint: 2411.00400.

[8] Nicolas Hudson, Fletcher Talbot, Mark Cox, Jason Williams, Thomas Hines, Alex Pitt, Brett Wood, Dennis Frousheger, Katrina Lo Surdo, Thomas Molnar, Ryan Steindl, Matt Wildie, Inkyu Sa, Navinda Kottege, Kazys Stepanas, Emili Hernández, Gavin Catt, William Docherty, and Brendan Tidd. Heterogeneous ground and air platforms, homogeneous sensing: Team csiro data61's approach to the darpa subterranean challenge. *Field Robotics*, 2:595–636, 03 2022. doi: 10.55417/fr.2022021.

[9] Nathan Hughes, Yun Chang, and Luca Carlone. Hydra: A real-time spatial perception system for 3D scene graph construction and optimization. In *Robotics: Science and Systems (RSS)*, 2022.

[10] MoniJesu James, Amir Atef Habel, Aleksey Fedoseev, and Dzmitry Tsetserokou. GoalVLM: VLM-driven Object Goal Navigation for Multi-Agent System, March 2026.

[11] H. W. Kuhn. The hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, 2(1-2):83–97, 1955. doi: https://doi.org/10.1002/nav.

3800020109. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/nav.3800020109.

[12] Kehui Liu, Zixin Tang, Dong Wang, Zhigang Wang, Xuelong Li, and Bin Zhao. COHERENT: Collaboration of Heterogeneous Multi-Robot System with Large Language Models, March 2025.

[13] Zhao Mandi, Shreeya Jain, and Shuran Song. RoCo: Dialectic Multi-Robot Collaboration with Large Language Models, July 2023.

[14] David Morilla-Cabello and Eduardo Montijano. CHORAL: Traversal-Aware Planning for Safe and Efficient Heterogeneous Multi-Robot Routing, January 2026. URL http://arxiv.org/abs/2601.10340. arXiv:2601.10340 [cs].

[15] NVIDIA. Isaac Sim. URL https://github.com/isaac-sim/IsaacSim.

[16] Qwen Team. Qwen3.6-35B-A3B: Agentic coding power, now open to all, April 2026. URL https://qwen.ai/blog?id=qwen3.6-35b-a3b.

[17] Zhixuan Shen, Haonan Luo, Kexun Chen, Fengmao Lv, and Tianrui Li. Enhancing Multi-Robot Semantic Navigation Through Multimodal Chain-of-Thought Score Collaboration, August 2025. URL http://arxiv.org/abs/2412.18292. arXiv:2412.18292 [cs].

[18] Gemini Team et al. Gemini: A family of highly capable multimodal models, 2025. URL https://arxiv.org/abs/2312.11805.

[19] Ruiyang Wang, Hao-Lun Hsu, David Hunt, Jiwoo Kim, Shaocheng Luo, and Miroslav Pajic. COMRES-VLM: Coordinated Multi-Robot Exploration and Search using Vision Language Models, March 2026.

[20] Pengying Wu, Yao Mu, Bingxian Wu, Yi Hou, Ji Ma, Shanghang Zhang, and Chang Liu. VoroNav: voronoi-based zero-shot object navigation with large language model. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

[21] Longrui Yang, Yiyu Wang, Jingfan Tang, Yunpeng Lv, Shizhe Zhao, Chao Cao, and Zhongqiang Ren. HEHA: Hierarchical Planning for Heterogeneous Multi-Robot Exploration of Unknown Environments, October 2025. URL http://arxiv.org/abs/2510.04161. arXiv:2510.04161 [cs].

[22] Naoki Yokoyama, Sehoon Ha, Dhruv Batra, Jiuguang Wang, and Bernadette Bucher. VLFM: Vision-Language Frontier Maps for Zero-Shot Semantic Navigation. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pages 42–48, 2024. doi: 10.1109/ICRA57147.2024.10610712.

[23] Bangguo Yu, Qihao Yuan, Kailai Li, Hamidreza Kasaei, and Ming Cao. Co-NavGPT: Multi-Robot Cooperative Visual Semantic Navigation Using Vision Language Models, May 2025. URL http://arxiv.org/abs/2310.07937. arXiv:2310.07937 [cs].

[24] Hongxin Zhang, Weihua Du, Jiaming Shan, Qinhong Zhou, Yilun Du, Joshua B. Tenenbaum, Tianmin Shu, and Chuang Gan. Building Cooperative Embodied

Agents Modularly with Large Language Models, February 2024.

[25] Jingyi Zhang, Jiaxing Huang, Sheng Jin, and Shijian Lu. Vision-language models for vision tasks: A survey, 2024. URL https://arxiv.org/abs/2304.00685.

[26] Mingjie Zhang, Chen Feng, Zengzhi Li, Guiyong Zheng, Yiming Luo, Zhu Wang, Jinni Zhou, Shaojie Shen, and Boyu Zhou. SOAR: Simultaneous Exploration and Photographing with Heterogeneous UAVs for Fast Autonomous Reconstruction, September 2024. URL http://arxiv.org/abs/2409.02738. arXiv:2409.02738 [cs].

[27] Zhonghan Zhao, Kewei Chen, Dongxu Guo, Wenhao Chai, Tian Ye, Yanting Zhang, and Gaoang Wang. Hierarchical Auto-Organizing System for Open-Ended Multi-Agent Navigation, March 2024.

[28] Lanxiang Zheng, Mingxin Wei, Ruidong Mei, Kai Xu, Junlong Huang, and Hui Cheng. AAGE: Air-Assisted Ground Robotic Autonomous Exploration in Large-Scale Unknown Environments. *IEEE Transactions on Robotics*, 41:1918–1937, 2025. ISSN 1941-0468. doi: 10.1109/ TRO.2025.3543275.