MONGOOSE: A LEARNABLE LSH FRAMEWORK FOR EFFICIENT NEURAL NETWORK TRAINING

ABSTRACT

Recent advances by practitioners in the deep learning community have breathed new life into Locality Sensitive Hashing (LSH), using it to reduce memory and time bottlenecks in neural network (NN) training. However, while LSH has sublinear guarantees for approximate near-neighbor search in theory, it is known to have inefficient query time in practice due to its use of random hash functions. Moreover, when model parameters are changing, LSH suffers from update overhead. This work is motivated by an observation that model parameters evolve slowly, such that the changes do not always require an LSH update to maintain performance. This phenomenon points to the potential for a reduction in update time and allows for a modified learnable version of data-dependent LSH to improve query time at a low cost. We use the above insights to build MONGOOSE, an end-to-end LSH framework for efficient NN training. In particular, MONGOOSE is equipped with a scheduling algorithm to adaptively perform LSH updates with provable guarantees and learnable hash functions to improve query efficiency. Empirically, we validate MONGOOSE on large-scale deep learning models for recommendation systems and language modeling. We find that it achieves up to 8% better accuracy compared to previous LSH approaches, with $3\times$ speed-up.

1 INTRODUCTION

Locality Sensitive Hashing (LSH) has been adapted to address the computational and memory bottlenecks of large-scale neural network (NN) training in natural language processing (Chandar et al., 2016; Rae et al., 2016; Kitaev et al., 2020b), computer vision (Chen et al., 2015) and recommendation systems (Spring & Shrivastava, 2017; Chen et al., 2020). Specifically, giant matrix multiplications in linear layers preceding a softmax can be approximated using nearest neighbor search (NNS) techniques, which often rely on LSH. However, LSH methods used in NNs are inefficient. Although LSH achieves sub-linear query time in theory, it is known to suffer from high query and pre-processing (update) overhead in practice (Erik et al., 2018). In the setting of NN training, where data points for LSH are model parameters, this overhead is exacerbated by a high number of updates due to constantly evolving model parameters.

The most established solution for reducing LSH query overhead is data-dependent or learning-based hashing, which uses adaptive hash functions to optimize the LSH bucket distribution for each dataset (Andoni & Razenshteyn, 2015; Dong et al., 2019). These methods reduce query time by incurring a one-time offline cost to learn useful data input patterns in a preprocessing step. The learning techniques are often computationally complex, but can lead to a net reduction in overall query time. However, in NN training, the expensive preprocessing procedure has to be repeated each time the parameters are updated. Naïvely applying these techniques would increase the LSH update overhead rather than reduce it. A more appropriate data-dependent LSH framework would ideally (i) have a deeper understanding of the training dynamics of model parameters, a setting in which LSH has not been well-studied, (ii) be able to perform low-cost updates to account for evolving parameter, and (iii) have better query time while accurately approximating matrix multiplication.

We argue that it is unnecessary to view evolving model parameters as streaming data and not every parameter update requires an LSH update. In fact, LSH updates are necessary only when the NN gradient steps are large enough to cause the model parameters' LSH hash codes to change. Therefore, we count the number of hash code changes that occur for important models such as Transformers

Figure 1: MONGOOSE workflow - For each layer in the NN, besides the usual setup for LSH, we add two components: (i) a scheduler deciding if an LSH update should be performed in this iteration (ii) if updating, a learning (data-adaptive) mechanism will be triggered for tuning the LSH hash functions based on the current weights, and then LSH updates will be performed.

and fully-connected NNs from previous work (Chen et al., 2020; Kitaev et al., 2020b). We find that only 1% of the hash codes change after each epoch on average for Transformer, and 5% for a fully-connected NN, so most weights do not change on a scale that is enough to trigger an LSH update. Furthermore, the rate of hash code change initially decays exponentially and eventually plateaus, as shown later in Figure 3. We calculate that a $100\times$ speed up is possible with an update oracle. In contrast, current approaches with LSH have not fully exploited this observation. We show in Section 4.2 that they either blindly skip updates for speed, resulting in a 10-point accuracy drop, or suffer from a $20\times$ slow-down.

We demonstrate that these slowly changing hash codes provide two opportunities to realize the ideal data-dependent LSH framework described above (shown as the intuition for the scheduler in Figure 1). First, given weight changes, an algorithm could adaptively schedule LSH updates to realize low update overhead. Second, given current weights, we could learn data-dependent hash functions for better LSH bucket distribution to achieve fast query time. However, this comes with three challenges: (i) how to characterize the slowly-changing phenomenon without computing hash codes, (ii) how to schedule the updates without the oracle, and (iii) how to learn data-dependent hash functions for shorter query time without compromising on the update time.

In this paper, we first provide a general formulation of the problem as *dynamic NNS* in Section 2. In Section 3, we propose MONGOOSE, a framework for fast and memory-efficient NN training to address the above challenges. We show one major observation, *slow change*, and two key components based on it in MONGOOSE. Specifically,

- In Section 3.1, we measure the ℓ_2 norm of the weight changes and their hash code changes during training on a fully-connected NN. (More models are studied in Appendix A). We find that (i) the hash codes are slowly changing (ii) both quantities share similar trajectories, but the former's slow change is the necessary condition of the latter's. Therefore, we formally define the slow change of ℓ_2 norm of weight changes in Assumption 3.1, which is the key to build MONGOOSE.
- In Section 3.2, we present an algorithm for scheduling efficient LSH updates. We closely analyze our scheduler's theoretical guarantees and provide an upper bound of its running time, which is proportional to the ℓ_2 norm of the weight changes. Therefore, under the *slow change* assumption, we show that our scheduler is provably faster than previous approaches.
- In Section 3.3, we propose a method of learning parameterized LSH hash functions (e.g., SimHash (Charikar, 2002)) during NN training. Our method utilizes intermediate activations during the forward pass to generate training inputs for tuning LSH hash functions with little overhead. Combining this with our scheduler further decreases the overhead, while providing hash functions that better separate data.

Finally, in Section 4, we demonstrate the efficacy of MONGOOSE on two LSH-NN systems, SLIDE and Reformer. For SLIDE applications, we show up to $3\times$ speedup in training time and 8% higher accuracy on three datasets. For Reformer applications, we show improvement in perplexity when training language modeling benchmarks from scratch. Moreover, we provide two additional sets of experiments to show how MONGOOSE addresses the aforementioned three challenges separately.

2   RELATED WORK AND PROBLEM SETTING

In this section, we first discuss applications of LSH in the NN training setting and introduce data-dependent LSH techniques. Then we formally define the problem we solve as *dynamic NNS*.

2.1   LSH FOR EFFICIENT NN TRAINING

Recent works take advantage of LSH as an efficient NNS algorithm to speed up matrix multiplication in neural networks. SLIDE (Chen et al., 2020) is an algorithm that retrieves neurons with maximum inner product during the forward pass via an LSH-based data structure. In this way, in the backward pass gradients are only computed for neurons with estimated large gradients. Reformer (Kitaev et al., 2020a), a variant of Transformer, similarly uses LSH to reduce the memory bottleneck of self-attention layers over long sequences. One pain point of LSH in this setting is that model weights change throughout training. This necessitates constantly updating the LSH data structure. Figure 2 illustrates what happens when we *don't* perform such updates. In short, failing to update the LSH data structure as the search data changes degrades its NNS performance. This in turn worsens the quality of the matrix product approximation. In our

Figure 2: Visualization of why LSH updates are essential when data changes. h is a hyperplane separating two hash buckets. If x_1 is updated in training, its hash value may change.

experiments, we found that failing to update the LSH data structure in SLIDE causes a 28% decrease in top-1 accuracy for a fully-connected NN. (More related work is presented in Appendix E.1)

2.2   PROBLEM FORMULATION

In this section, we formulate LSH for effcient training as a *dynamic NNS* problem. This formulation is closely built on the static NNS problem and the well-known lower bound on LSH complexity. In the static NNS problem, we are given a set of weights $w_1, \cdots, w_n \in \mathbb{R}^d$ and want to construct a data structure (NNS-ds) that supports the QUERY operation, defined as follows: given $x \in \mathbb{R}^d$, QUERY(x) returns a set S of weights w_i that are all "close" to x in a distance measure.

More precisely, we require the QUERY(x) operation to be (c_1, c_2)-accurate:

Definition 2.1 ((c_1, c_2)-accurate)**.** *Denote S to be the (random) set returned by QUERY(x). We say* QUERY(x) *is (c_1, c_2) accurate if*

(i) for any $i \in [n]$ such that $\langle w_i, x \rangle \geq c_1 \|x\|_2 \|w\|_2$, $\Pr[w_i \in S] \geq 1 - 1/n$,
(ii) for any $i \in [n]$ such that $\langle w_i, x \rangle < c_2 \|x\|_2 \|w\|_2$, $\Pr[w_i \in S] < 1/n$.

In our application, we assume $1 > c_1 > c_2 > 0$ to be some constants and denote $\rho = (c_2/c_1)^2$. In the dynamic NNS problem, the weights $w_1, \cdots, w_n \in \mathbb{R}^d$ can evolve over time, so we need to update the data structure.

Lemma 2.2 (Andoni & Indyk (2006))**.** *Using LSH, one can achieve (c_1, c_2) accuracy with query time $O(dn^\rho)$, preprocessing time $O(dn^{1+\rho})$, updating time $O(dn^\rho)$.*

3   MONGOOSE: A FRAMEWORK FOR LEARNABLE LSH

We present the workflow of our main framework in Figure 1. In Section 3.1, we first show the key observation that encourages the design of MONGOOSE and formally define the *slow change* assumption. In Section 3.2, we introduce our first component, an algorithm for scheduling LSH updates with provable guarantees based on the assumption. Finally, we present the second component, low-cost learnable LSH hash functions, in Section 3.3. More details about the efficient implementation of MONGOOSE are in Appendix F.

3.1   CHARACTERIZATION OF "SLOW CHANGE" PHENOMENON

We first present an observation on model weights and how their LSH hash codes change during training. Based on this observation, we define the *slow change* assumption. We denote ΔW as the

difference between weights across gradient steps, and ΔH as the Hamming distance between hash codes during training.

Observation. We plot the ℓ_2 norm of ΔW and ΔH of the weights during training a one layered fully-connected NN in Figure 3. Our most surprising finding is that only 5% of hash codes change after each epoch on average, which implies that for most neurons, ΔW is not large enough to trigger hash code changes. For both ΔW and ΔH, there is a sharp drop at the early stages of training before they plateau. (Similar observations on Transformers are presented in Appendix A.)

Figure 3: ΔW and ΔH both start out relatively high at the beginning of training, but quickly drop off and flatten out.

Insights. In the *dynamic* NNS problem, input data (model weights) change over time. Without any assumptions about weight updates, naively applying LSH will require updating the LSH hash functions at every time step. However, the above observation suggests that we can reasonably assume ΔW is (roughly) upper-bounded by ΔH. Formally:

Assumption 3.1 (Slow change). *Assume NN weights change slowly over time. To be more specific, we denote the initial weight matrix as $w^{(0)} \in \mathbb{R}^{n \times d}$. We assume the (random) update sequence $w^{(1)}, \cdots, w^{(T)} \in \mathbb{R}^{n \times d}$ satisfies*

$$\sum_{i=1}^{n} \left(\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)} \right)^2 \leq C_1^2 \qquad and \qquad \sum_{i=1}^{n} (\text{Var}[w_i^{(k+1)}])^2 \leq C_2^2, \tag{1}$$

where the expectation and variance is conditioned on $w_i^{(k)}$ for all $k = 0, 1, \cdots, T-1$.

3.2 A SMART SCHEDULER FOR LEARNABLE LSH UPDATES

In this section, we introduce a dynamic data structure to schedule updates for LSH. Our scheduler provides significant speedup under two realistic assumptions without compromising the theoretical guarantee of LSH: (i) *slow change* defined in Assumption 3.1, (ii) *batch speed up* defined in Assumption 3.2. The scheduler can generalize to any nearneighbor search data structure (NNS-ds), but we show a design for LSH as an example since that is the NNS-ds in MONGOOSE.

3.2.1 SMART SCHEDULER

The pseudo-code for our smart scheduler is shown in Algorithm 1. Our scheduler is inspired by a dynamic data structure proposed in a recent line of work (Cohen et al., 2019), which was originally designed for inverse maintainance in Linear Programming solvers. We provide a novel application here for the dynamic LSH problem.

Algorithm 1 General Maintenance Data Structure

1: **Input:** $w \in \mathbb{R}^{n \times d}$, $v \in \mathbb{R}^{n \times d}$, $\epsilon_{\text{mds}} \in (0, 1/\log^2 n)$, $a = \min\{\rho, \alpha\}$, $S \subseteq [n]$
2: **procedure** INITIALIZE($A, w, \epsilon_{\text{mds}}, a$) ▷ Lemma B.2
3:     $w \leftarrow w, v \leftarrow w, \epsilon_{\text{mds}} \leftarrow \epsilon_{\text{mds}}, a \leftarrow a, S \leftarrow \emptyset$,
4:     Build LSH with accuracy ($c_1 - \epsilon_{\text{mp}}, c_2 + \epsilon_{\text{mp}}$)
5: **end procedure**
6: **procedure** UPDATE(w^{new}) ▷ Lemma B.3
7:     $y_i \leftarrow w_i^{\text{new}} - v_i, \forall i \in [n]$
8:     $r \leftarrow$ the number of indices i that $\|y_i\|_2 \geq \epsilon_{\text{mds}}/2$.
9:     **if** $r < n^a$ **then**
10:         $v^{\text{new}} \leftarrow v$
11:     **else**
12:         Let $\pi : [n] \rightarrow [n]$, that $\|y_{\pi(i)}\|_2 \geq \|y_{\pi(i+1)}\|_2$
13:         **while** $1.5 \cdot r < n$ and $\|y_{\pi(\lceil 1.5 \cdot r \rceil)}\|_2 \geq (1 - 1/\log n)\|y_{\pi(r)}\|_2$ **do**
14:             $r \leftarrow \min(\lceil 1.5 \cdot r \rceil, n)$
15:         **end while** ▷ Finding a smooth cut
16:         $v_{\pi(i)}^{\text{new}} \leftarrow \begin{cases} w_{\pi(i)}^{\text{new}} & i \in \{1, 2, \cdots, r\} \\ v_{\pi(i)} & i \in \{r+1, \cdots, n\} \end{cases}$
17:         LSH.UPDATE $\pi([r])$
18:     **end if**
19:     $w \leftarrow w^{\text{new}}, v \leftarrow v^{\text{new}}$,
20:     $S = \{i \in [n] : \|w_i - v_i\|_2 \geq \epsilon_{\text{mp}}/2\}$
21: **end procedure**
22: **procedure** QUERY(h) ▷ Lemma B.4
23:     LSH.QUERY and check S
24: **end procedure**

We maintain two copies of the NN weights $w, v \in \mathbb{R}^{n \times d}$, where w are the actual weights that are updated via gradient descent and

v approximately equals w except for a few coordinates. We set an empirical threshold of ϵ_{mds}. Due to the robustness of the NNS problem, we can tolerate this small error ϵ_{mds} such that only those coordinates with a difference greater than ϵ_{mds} matters. To exploit the benefit of batch updating, we perform lazy updates on the LSH hash table. In particular, we update the LSH hash table if and only if the difference between w, v exceeds some threshold number n^ρ (see line 9 to line 11). One key part of our update procedure is that we also update some low-error coordinates when there are *too many* of them (see line 13 to line 16). This procedure can be seen as forecasting future updates. The intuition is that when there are too many coordinates close to the decision boundary, they are likely to change within a short amount of time. Updating these all together could further take advantage of the batch updates. To answer an LSH query, we keep track of a short list S (see line 20), which records coordinates that differ significantly between w, v, the short list S can be seen as corrupted data to keep track of when performing an LSH query, since they are no longer the same. In the query procedure (see line 22 to line 24), besides performing the normal LSH query, we also check the shortlist S and pick up weights that are close to x. Hence, we balance the overhead of query time with update time, where update time is usually the bottleneck.

3.2.2 THEORETICAL ANALYSIS

Assumption 3.2 (batch speedup). *Denote T_r as the updating time for LSH when r weights change and $T_r = r \cdot t_r$. We assume $\{t_i\}_{i=1,\dots n}$ is non increasing, i.e., $t_1 \geq t_2 \geq \dots \geq t_n$. We further assume $T_r = n^\rho$ when $r \leq n^\alpha$ for some constant α.*

The batch speedup assumption is realistic, especially due to advances in support for massive parallelism on modern computation architectures.

Theorem 3.3 (LSH maintenance). *For any constant c_1, c_2 ($c_1 > c_2$) there is a dynamic data structure (Algorithm 1) that achieves (c_1, c_2)-accuracy. The data structure takes $\widetilde{O}(dn^{1+\rho})$ time to initialize and each call of $\text{QUERY}(h)$ takes time $\widetilde{O}(n^\rho d)$. By taking $a = \min\{\rho, \alpha\}$ and*

$$g_r = \begin{cases} n^{\rho-a}, & r \leq n^a; \\ t_r, & r. \end{cases}$$

The amortized expected time per call of $\text{UPDATE}(w)$ is at most

$$\widetilde{O}((C_1 + C_2) \cdot \|g\|_2). \tag{2}$$

Remark 3.4. *Depending on the exact form of batch updating time t_r, the (amortized) running time and the benefit of our scheduler could be different. We provide concrete examples in Appendix B.6, showing advantages of our smart scheduler under different scenarios. In general, we remark that (1) Our scheduler is* oblivious *to the exact form of the update time t_r and weight change C_1, C_2. Thus, its performance is robust and doesn't need fine tuning (2) Our scheduler is always better than the naive sequential updating strategy.*

3.3 HASH FUNCTION LEARNING

In this section, we provide a simple streaming algorithm to learn parameterized hash functions. Here, the learning objective is to track the weight distribution as the weights change to better separate the input data to the NNS problem. Recall that in last section, we show an algorithm for scheduling the LSH updates, which makes it possible to involve learning for LSH and improve the query efficiency. Therefore, the overall update overhead can be reduced even with learning overhead if scheduled well, since the update time is closely related to query time.

Algorithm 2 Learnable Hash Function

1: **Input: query set** $Q = \{q_i\}_{i \in [N]}$, **query size** N
2: **hash table** $\mathcal{G} = \{g_l\}_{l \in [L]}$
3: **hash function** $\forall l \in [L]$, $\mathcal{H}_l = \{h_{l,k}\}_{k \in [K]}$, $\mathcal{H} = \cup_{l \in [L]} \mathcal{H}_l$
4: **Retrieved Neurons Sets** $\{\mathcal{S}_i\}_{i \in [N]}$, $\mathcal{S}_i = \{v_r\}_{r \in [M]}$
5: **parameters** t_+, t_-
6: $\mathcal{P}_+ \leftarrow \emptyset, \mathcal{P}_- \leftarrow \emptyset$ $\triangleright \mathcal{P}_+, \mathcal{P}_- \in \mathbb{R}^{2d+2}$
7: **for** $i = 1 \rightarrow N$ **do**
8:     $\mathcal{P}_+ \leftarrow \mathcal{P}_+ \cup \{(q_i, v_r) \mid v_r \in S_i, \langle q_i, v_r \rangle > t_+\}$
9:     $\mathcal{P}_- \leftarrow \mathcal{P}_- \cup \{(q_i, v_r) \mid v_r \in S_i, \langle q_i, v_r \rangle < t_-\}$
10: **end for**
11: $\text{size}^{\text{new}} \leftarrow \min\{|\mathcal{P}_+|, |\mathcal{P}_-|\}$
12: $\text{RESIZE}(\mathcal{P}_+, \mathcal{P}_-, \text{size}^{\text{new}})$
13: $\mathcal{H}^{\text{new}} \leftarrow \text{REHASH}(\mathcal{P}_+, \mathcal{P}_-, \mathcal{L})$ $\triangleright \mathcal{L}$ is a loss function
14: $\mathcal{G}^{\text{new}} \leftarrow \text{REBUILD}(\mathcal{G}, \mathcal{H}^{\text{new}})$
15: **return** $\mathcal{G}^{\text{new}}, \mathcal{H}^{\text{new}}$

3.3.1 LEARNABLE LSH

We view the sequence of neural network weights throughout training as a matrix stream. In each training iteration, if our scheduler schedules an update, we compute a training signal with which we can train our LSH parameters. Specifically, we compute the classical triplet loss (Chechik et al., 2010) using positive and negative samples from the current model weights for each LSH query. Here, positive samples (denoted by $\mathcal{P}_+$) are neurons that have higher inner product within the input retrieved by LSH, while negative samples (denoted by $\mathcal{P}_-$) are neurons with lower inner product that are selected. Denote a set of neurons in a particular layer as $\mathcal{C} = \{v_r \mid 0 \leq r < m\}$ and the input embedding as q_i. Denote the set of neurons retrieved from the LSH hash tables using q_i as $\mathcal{S}_i$. We formally present the learning algorithm in Algorithm 2. The triplet loss is defined as follows:

$$\mathcal{L}(\mathcal{H}, \mathcal{P}_+, \mathcal{P}_-) = \max(0, \sum_{(q,v)\in\mathcal{P}_+} -\cos(\mathcal{H}(q), \mathcal{H}(v)) + \sum_{(q,v)\in\mathcal{P}_-} \cos(\mathcal{H}(q), \mathcal{H}(v)) + \alpha), \quad (3)$$

where $\mathcal{H}$ denotes the LSH hash function at the current iteration and α is a margin between positive and negative pairs. $\cos(\mathcal{H}(\cdot), \mathcal{H}(\cdot))$ represents the cosine similarity. We provide a detailed justification of this learning approach in Appendix C.1.

3.3.2 FURTHER SPEEDUP

We demonstrate how to optimize learnable LSH for further acceleration in NN training. Here, we provide the main insights; further details are in Appendix A.

Layer Selection: In previous LSH-NN methods such as SLIDE or Reformer, the designation of whether a layer uses LSH is treated as a tunable hyperparameter. For example, Reformer applies LSH in three out of twelve attention layers in their final model based on empirical performance. In MONGOOSE we make this designation in a more

Figure 4: Attention distribution examples in different layers: Y-axis is the least number of attentions summing to 90% of full attentions. The annotations represent the median. The total number of attentions (or sequence length) is 512.

principled manner. The intuition behind the design can be presented by visualizing the statistics of attention weights in different layers of the transformer model (Figure 4). The three plots represent the distribution of the average number of coordinates with "heavy" attention for each layer. We also calculate the size of the minimal set of attention weights that captures 90% of the total attention (Ramsauer et al. (2020) perform a similar experiment). The median for the left plot is 2, meaning that they are well-separated and LSH can perform well on such a distribution. On the other hand, learnable LSH can be very helpful for the right plot, because classical LSH is inefficient for this distribution. Therefore, we can use this observation when deciding between LSH or learnable LSH in each layer for later training stages or fine-tuning on downstream tasks.

From the system design view, MONGOOSE improves the flexibility of LSH's usage on NN training. We provide a smart scheduler to decide the time stamp for LSH update and visualization on when to use LSH or learnable LSH. Therefore, the training process has the following tunable parameters for LSH: (i) the layers which we apply random LSH to, (ii) the layers for which we can use learning to improve LSH's random hash functions, (iii) the runtime that LSH or learnable LSH should perform the update in. Setting these parameters appropriately will enable much more efficient NN training or fine-tuning, as supported by our theory and observations.

4 EXPERIMENTS

In Section 4.1 we present the results of experiments that demonstrate the higher performance of MONGOOSE over other LSH-NN frameworks at training time. Then we further study the effectiveness of the two components separately: (i) smart scheduler in Section 4.2, (ii) learnable LSH in Section 4.3.

Table 1: This table summarizes the performance of MONGOOSE, SLIDE and Full-Computation implemented with PyTorch (Paszke et al., 2019). P@1 is the top-1 accuracy and P@5 is the top-5 accuracy. Time represents convergence time.

Tasks	Datasets	Full-Computation			SLIDE			MONGOOSE		
		P@1	P@5	Time (s)	P@1	P@5	Time (s)	P@1	P@5	Time (s)
Extreme Classification	Wiki10-31K	**0.824**	0.578	63	0.824	0.556	47 (1.3 ×)	**0.824**	**0.618**	**35 (1.8×)**
	Delicious-200K	0.446	0.356	483	0.465	**0.372**	318 (1.5×)	**0.469**	0.371	**162 (3×)**
	Wiki-325K	0.501	0.235	5702	0.438	0.205	4680 (1.4×)	**0.519**	**0.255**	**1906 (3×)**

4.1 MAIN RESULTS: MONGOOSE IN NN TRAINING

We present the results of main experiments that demonstrate MONGOOSE's advantage in fast NN training over two different LSH-NN baselines on recommendation and language modeling tasks.

4.1.1 TASK1: EXTREME MULTI-LABEL CLASSIFICATION

Settings: We compare the performance of MONGOOSE against SLIDE and networks without LSH (Full-Computation) on 3 large-scale multi-label classification datasets: Wiki10-31k, Delicious-200k, and Wiki-325k. The datasets are obtained from the Extreme Classification Repository (Bhatia et al., 2016), which is a benchmark for various recommendation systems. The model is a fully-connected network with one hidden-layer. The statistics of each dataset are included in Appendix D. MONGOOSE, SLIDE, and Full-Computation use the exact same architecture. We report the best results of each framework in $P@1$ and $P@5$ following evaluation metrics in (Bhatia et al., 2016).

Results: Table 1 shows test accuracy and wall-clock time to converge for MONGOOSE and other baselines. Figure 5 shows $P@1$ and $P@5$ for MONGOOSE and other baselines during the training process. MONGOOSE achieves $1.8\times$ faster convergence compared to Full-Computation on Wiki10-31K, and $3\times$ faster convergence on Delicious-200K and Wiki-325K. SLIDE has a large accuracy drop

Figure 5: $P@1$ versus training iteration. Left one is for Wiki325k and the right one is a synthetic copying task.

without a substantial speedup for Wiki-325K, but our method has a $3\times$ speedup with no accuracy loss. The benefits of MONGOOSE come from three aspects. First, matrix multiplication is only performed on a small subset of neurons. The average number of neurons sampled in the output layer for MONGOOSE on Delicious-200K is around 6k. Second, our adaptive scheduler further reduces updating costs. On Wiki-325K, we observe updating frequency drops significantly at the start of the second epoch. This is compatible with our observation of slow weight change in Figure 3. Finally, learnable LSH improves LSH query efficiency and quality. In addition, we observe that MONGOOSE obtains a slightly higher accuracy compared to Full-Computation, which may be a side benefit coming from activation sparsity (Ba & Frey, 2013).

4.1.2 TASK2: EFFICIENT TRANSFORMER

Settings: We run experiments on two tasks from Reformer (Kitaev et al., 2020a). The first task is a synthetic sequence duplication task where inputs are of the form $0w0w$ and $w \in \{0, ..., N\}^*$. This task is useful for demonstrating the effectiveness of LSH attention: it requires non-local attention lookups and therefore cannot be solved by any model relying on sparse attention with a limited range (*e.g.*, local attention). We compare MONGOOSE with a 1-layer Reformer by replacing the data-independent LSH in the attention layer with learnable LSH, updating the LSH parameters according to our smart scheduler. The second task is a standard language modeling task on the enwik8 dataset. For this second task, we use sequence length of 8192 and 6 LSH-attention layers.

Results: We compare the testing loss (training loss is similar) of MONGOOSE and Reformer on each task. The loss curve for the synthetic sequence duplication task is shown in Figure 5 (on the right).

On this task, MONGOOSE achieves a loss value of 0.75, which is 0.5 better than Reformer. Moreover, MONGOOSE only needs 20% time to reach the same loss as Reformer (5× speed-up). Similarly, on enwik8, Reformer only reaches 2.71 in perplexity, while MONGOOSE achieves 2.65, which is 0.06 better under the same time and setting. (More details and explanations are in Appendix D.3)

4.2 STUDY ON SMART SCHEDULER

In this section, we demonstrate the superiority of our smart scheduling algorithm over the two baselines we mentioned in Section 1 on Wiki-325K. The first approach ("Infrequent Scheduler") performs an update on a fixed schedule, every $1K$ iterations (6 times per epoch on Wiki-

Table 2: Speed with respect to accuracy

	P@1	P@5	Speed (batch/s)
Infrequent Scheduler	0.39	0.193	31.2
W/O Scheduler	0.521	0.254	0.4
MONGOOSE Scheduler	0.519	0.255	7.7

325K). The other baseline performs an update every iteration ("W/O Scheduler"). We compare speed (number of batches processed per second) and accuracy (P@1 and P@5) of these schedulers in Table 2. On average, MONGOOSE Scheduler reduces more than **97**% of the update overhead compared to W/O Scheduler, leading an end-to-end 20× speed-up. Meanwhile, although Infrequent Scheduler is faster in speed, it fails to reach the same task accuracy as the other approaches. In fact, MONGOOSE Scheduler achieves Infrequent Scheduler's final accuracy with **66**% less time. We can see that MONGOOSE substantially reduces LSH update overhead while maintaining performance.

4.3 STUDY ON LEARNABLE LSH

In this section, we compare MONGOOSE's learnable LSH scheme to the classical LSH on their NNS ability using the same number of hash functions. In Figure 6 (left), we plot 1) the average inner product computed using neurons retrieved by learnable LSH in MONGOOSE and random LSH in SLIDE (on the left) and 2) Reformer minus inner product computed using the same number of randomly chosen neurons (on the right).

Figure 6: The normalized inner product computed by NNS-ds neurons. In both Wiki-325k (left) and enwik8 (right), MONGOOSE has much higher average inner product than baselines.

MONGOOSE beats SLIDE by a large margin. In particular, a negative value indicates that LSH is performing worse than random sampling. We can see that at the beginning of training, when weights are initialized randomly, data-independent LSH is sufficient to partition the data. However, as training progresses, SimHash used in SLIDE fails to adapt to the evolving weight distribution, while our selection better approximates the full softmax. We conduct the same experiments for the language modeling task on enwik8. In Figure 6 (right), we can see that data-dependent hashing computes higher inner products within each bucket as training progresses. For attention layers in the Transformer models, random LSH fails to approximate attentions in certain layers due to the attention distribution. (This phenomenon was also explained in Section 3.3.2 and Figure 4.) In attention layers, our selection produces a better characterization of the full attention.

5 CONCLUSION

In this work, we make a novel observation on the slowly changing LSH hash codes during LSH-NN training. Based on the observation, we present MONGOOSE, a learnable LSH framework that outperforms original LSH methods in efficient neural network training. We demonstrate two key designs in the framework. One is a smart scheduling algorithm which reduces the LSH update overhead. The other one is a low cost learnable LSH which can improve the query efficiency and hashing quality. We empirically verify the effectiveness of our framework on both recommendation and language modeling tasks. In future work, we plan to extend our framework to more deep learning models.

REFERENCES

Amin Ahmad, Noah Constant, Yinfei Yang, and Daniel Cer. Reqa: An evaluation for end-to-end answer retrieval models. *arXiv preprint arXiv:1907.04780*, 2019.

Alexandr Andoni and Piotr Indyk. Near-optimal hashing algorithms for approximate nearest neighbor in high dimensions. In *2006 47th annual IEEE symposium on foundations of computer science (FOCS'06)*, pp. 459–468. IEEE, 2006.

Alexandr Andoni and Ilya Razenshteyn. Optimal data-dependent hashing for approximate near neighbors. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing (STOC)*, pp. 793–801, 2015.

Alexandr Andoni, Assaf Naor, Aleksandar Nikolov, Ilya Razenshteyn, and Erik Waingarten. Data-dependent hashing via nonlinear spectral gaps. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing (STOC)*, pp. 787–800, 2018.

Jimmy Ba and Brendan Frey. Adaptive dropout for training deep neural networks. In *Advances in neural information processing systems (NeurIPS)*, pp. 3084–3092, 2013.

Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Jauvin. A neural probabilistic language model. *Journal of machine learning research (JMLR)*, 3(Feb):1137–1155, 2003.

K. Bhatia, K. Dahiya, H. Jain, A. Mittal, Y. Prabhu, and M. Varma. The extreme classification repository: Multi-label datasets and code, 2016. URL http://manikvarma.org/downloads/XC/XMLRepository.html.

Leonid Boytsov, David Novak, Yury Malkov, and Eric Nyberg. Off the beaten path: Let's replace term-based retrieval with k-nn search. In *Proceedings of the 25th ACM international on conference on information and knowledge management (CIKM)*, pp. 1099–1108, 2016.

M. Burtscher, R. Nasre, and K. Pingali. A quantitative study of irregular programs on gpus. In *2012 IEEE International Symposium on Workload Characterization (IISWC)*, pp. 141–151, 2012.

Sarath Chandar, Sungjin Ahn, Hugo Larochelle, Pascal Vincent, Gerald Tesauro, and Yoshua Bengio. Hierarchical memory networks. *arXiv preprint arXiv:1605.07427*, 2016.

Wei-Cheng Chang, Felix X Yu, Yin-Wen Chang, Yiming Yang, and Sanjiv Kumar. Pre-training tasks for embedding-based large-scale retrieval. *arXiv preprint arXiv:2002.03932*, 2020.

Moses S Charikar. Similarity estimation techniques from rounding algorithms. In *Proceedings of the thiry-fourth annual ACM symposium on Theory of computing (STOC)*, pp. 380–388. ACM, 2002.

Gal Chechik, Varun Sharma, Uri Shalit, and Samy Bengio. Large scale online learning of image similarity through ranking. *Journal of Machine Learning Research*, 11(3), 2010.

Beidi Chen, Tharun Medini, James Farwell, Sameh Gobriel, Charlie Tai, and Anshumali Shrivastava. Slide: In defense of smart algorithms over hardware acceleration for large-scale deep learning systems. In *MLSys*. https://arxiv.org/pdf/1903.03129, 2020.

Wenlin Chen, James Wilson, Stephen Tyree, Kilian Weinberger, and Yixin Chen. Compressing neural networks with the hashing trick. In *International conference on machine learning*, pp. 2285–2294, 2015.

Michael B Cohen, Yin Tat Lee, and Zhao Song. Solving linear programs in the current matrix multiplication time. In *Proceedings of the 51st annual ACM SIGACT symposium on theory of computing (STOC)*, pp. 938–942, 2019.

Benjamin Coleman, Anshumali Shrivastava, and Richard G Baraniuk. Race: Sub-linear memory sketches for approximate near-neighbor search on streaming data. *arXiv preprint arXiv:1902.06687*, 2019.

Paul Covington, Jay Adams, and Emre Sargin. Deep neural networks for youtube recommendations. In *Proceedings of the 10th ACM Conference on Recommender Systems*, pp. 191–198. ACM, 2016.

Yihe Dong, Piotr Indyk, Ilya Razenshteyn, and Tal Wagner. Learning space partitions for nearest neighbor search. In *International Conference on Learning Representations (ICLR)*, 2019.

Bernhardsson Erik, Aumüller Martin, and Faithfull Alexander. ANN Benchmarks. `https://github.com/erikbern/ann-benchmarks`, 2018.

Miao Fan, Jiacheng Guo, Shuai Zhu, Shuo Miao, Mingming Sun, and Ping Li. Mobius: Towards the next generation of query-ad matching in baidu's sponsored search. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2509–2517. ACM, 2019.

Jianfeng Gao, Xiaodong He, Wen-tau Yih, and Li Deng. Learning continuous phrase representations for translation modeling. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (ACL)*, volume 1, pp. 699–709, 2014.

Ruiqi Guo et al. Quantization based fast inner product search. In *Artificial Intelligence and Statistics*, pp. 482–490, 2016.

Rob Hall and Josh Attenberg. Fast and accurate maximum inner product recommendations on mapreduce. In *Proceedings of the 24th International Conference on World Wide Web*, pp. 1263–1268. ACM, 2015.

Himanshu Jain, Yashoteja Prabhu, and Manik Varma. Extreme multi-label loss functions for recommendation, tagging, ranking & other missing label applications. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 935–944. ACM, 2016.

Herve Jegou, Matthijs Douze, and Cordelia Schmid. Product quantization for nearest neighbor search. *IEEE transactions on pattern analysis and machine intelligence*, 33(1):117–128, 2011.

Haotian Jiang, Tarun Kathuria, Yin Tat Lee, Swati Padmanabhan, and Zhao Song. A faster interior point method for semidefinite programming. In *FOCS*, 2020a.

Haotian Jiang, Yin Tat Lee, Zhao Song, and Sam Chiu-wai Wong. An improved cutting plane method for convex optimization, convex-concave games and its applications. In *STOC*. `https://arxiv.org/pdf/2004.04250.pdf`, 2020b.

Shunhua Jiang, Zhao Song, Omri Weinstein, and Hengjie Zhang. Faster dynamic matrix inverse for faster lps. *arXiv preprint arXiv:2004.07470*, 2020c.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. *arXiv preprint arXiv:2001.04451*, 2020a.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *ICLR*. `https://arxiv.org/pdf/2001.04451`, 2020b.

Tim Kraska, Alex Beutel, Ed H Chi, Jeffrey Dean, and Neoklis Polyzotis. The case for learned index structures. In *SIGMOD*, pp. 489–504, 2018.

Moontae Lee, Xiaodong He, Wen-tau Yih, Jianfeng Gao, Li Deng, and Paul Smolensky. Reasoning in vector space: An exploratory study of question answering. *arXiv preprint arXiv:1511.06426*, 2015.

Yury Malkov, Alexander Ponomarenko, Andrey Logvinov, and Vladimir Krylov. Scalable distributed algorithm for approximate nearest neighbor search problem in high dimensional general metric spaces. In *International Conference on Similarity Search and Applications*, pp. 132–147. Springer, 2012.

Yury Malkov, Alexander Ponomarenko, Andrey Logvinov, and Vladimir Krylov. Approximate nearest neighbor algorithm based on navigable small world graphs. *Information Systems*, 45:61–68, 2014.

Yury A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 2018.

Ioannis Partalas, Aris Kosmopoulos, Nicolas Baskiotis, Thierry Artieres, George Paliouras, Eric Gaussier, Ion Androutsopoulos, Massih-Reza Amini, and Patrick Galinari. Lshtc: A benchmark for large-scale text classification. *arXiv preprint arXiv:1503.08581*, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 1532–1543, 2014.

Jack Rae, Jonathan J Hunt, Ivo Danihelka, Timothy Harley, Andrew W Senior, Gregory Wayne, Alex Graves, and Timothy Lillicrap. Scaling memory-augmented neural networks with sparse reads and writes. In *Advances in Neural Information Processing Systems*, pp. 3621–3629, 2016.

Parikshit Ram and Alexander G Gray. Maximum inner-product search using cone trees. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining (KDD)*, pp. 931–939. ACM, 2012.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Lukas Gruber, Markus Holzleitner, Milena Pavlović, Geir Kjetil Sandve, Victor Greiff, et al. Hopfield networks is all you need. *arXiv preprint arXiv:2008.02217*, 2020.

Alexandre Sablayrolles, Matthijs Douze, Cordelia Schmid, and Hervé Jégou. Spreading vectors for similarity search. *arXiv preprint arXiv:1806.03198*, 2018.

Minjoon Seo, Jinhyuk Lee, Tom Kwiatkowski, Ankur P Parikh, Ali Farhadi, and Hannaneh Hajishirzi. Real-time open-domain question answering with dense-sparse phrase index. *arXiv preprint arXiv:1906.05807*, 2019.

Aliaksei Severyn and Alessandro Moschitti. Learning to rank short text pairs with convolutional deep neural networks. In *Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, pp. 373–382, Santiago, Chile, 2015.

Anshumali Shrivastava and Ping Li. Asymmetric lsh (alsh) for sublinear time maximum inner product search (mips). In *Advances in Neural Information Processing Systems*, pp. 2321–2329, 2014a.

Anshumali Shrivastava and Ping Li. Improved asymmetric locality sensitive hashing (alsh) for maximum inner product search (mips). *arXiv preprint arXiv:1410.5410*, 2014b.

Ryan Spring and Anshumali Shrivastava. Scalable and sustainable deep learning via randomized hashing. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 445–454, 2017.

Yukihiro Tagami. Annexml: Approximate nearest neighbor search for extreme multi-label classification. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 455–464. ACM, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems (NeurIPS)*, pp. 5998–6008, 2017.

Jingdong Wang, Ting Zhang, Nicu Sebe, Heng Tao Shen, et al. A survey on learning to hash. *IEEE transactions on pattern analysis and machine intelligence*, 40(4):769–790, 2017.

Donna Xu, Ivor W Tsang, and Ying Zhang. Online product quantization. *IEEE Transactions on Knowledge and Data Engineering*, 30(11):2185–2198, 2018.

Hong-Jian Xue, Xinyu Dai, Jianbing Zhang, Shujian Huang, and Jiajun Chen. Deep matrix factorization models for recommender systems. In *IJCAI*, pp. 3203–3209, 2017.

Appendix

Table of Contents

A   SLOW CHANGE OBSERVATIONS

In this section, we analyze the relative distance between iterates of model parameters and connect it with LSH updates throughout training. We target at making full use of our slowly change characterization for MONGOOSE.

Settings. We report ΔW throughout training on several benchmark models. We follow the standard training procedures of fully-connected networks on Wiki325k (Partalas et al., 2015) and Transformer (Vaswani et al., 2017) on enwik8. We choose W in the last linear layer for the fully-connected model and W in the projection layer before attention for the transformer model to correspond experiments in section 4. In Appendix A, we provide a detailed investigation on experimental results from different datasets.

Results. We plot our results in Figure 3. The left-two and right-most plots show that during the initial steps of the training, ΔW is relatively high, but quickly drops and flattens out afterwards. The middle and right-most plots exhibit the hash code change of W in the hamming distance along with the training. The pattern matches with ΔW but has a direct connection with the LSH update overhead. This is also consistent with LSH theory that the hash code collision probability of two vectors equals to the vectors' certain similarity, *e.g.*, angular. Note the above observations are made based on angular distance LSH. The above phenomenon suggests that if there exists an optimal scheduler to update the data structures adaptively based on the actual demand, the overhead by LSH updates can be largely reduced. Furthermore, this opens the door to make LSH learnable in order to improve query efficiency. Since the LSH update time is also closely related to the query time, the overall update overhead might still be reduced after considering learning costs, if the updates are well scheduled.

Figure 7: We show the average change of weight (left), cosine similarity (middle), weight's hash code (right). Top row is reformer and the bottom row is for Wiki-325k.

B DYNAMIC MAINTENANCE DATA STRUCTURE

The idea of dynamic maintenance have been successfully applied to matrix inversion problem, which served as a central component in linear program solvers (Cohen et al., 2019; Jiang et al., 2020c), cutting plane method (Jiang et al., 2020b), and semi-definite program solvers (Jiang et al., 2020a). In this work, we adopt it for dynamic LSH maintenance problem. The rest of this section is organized as follows

- In Section B.1, we state our main results.
- In Section B.2, we give a high-level overview on the correctness and the running time of the algorithm.
- In Section B.3, we give an analyze on the movement of w vector.
- In Section B.4 we give analyze on the movement of v vector.
- In Section B.5, we discussed over the choice of potential function and analysis its property.
- In Section B.6, we compare the performance our algorithm with sequential updating strategy/batch updating strategy.

B.1 MAIN RESULT

Theorem B.1 (Locality sensitive hashing maintenance, Formal statement of Theorem 3.3). *For any constant c_1, c_2 ($c_1 > c_2$) there is a dynamic data structure (Algorithm 1) that achieves (c_1, c_2)-accuracy. The data structure takes $\widetilde{O}(dn^{1+\rho})$ time to initialize and each call of $\mathrm{QUERY}(h)$ takes time $\widetilde{O}(n^\rho d)$. By taking $a = \min\{\rho, \alpha\}$ and*

$$g_r = \begin{cases} n^{\rho-a}, & r \le n^a; \\ t_r, & r. \end{cases}$$

The amortized expected time per call of $\mathrm{UPDATE}(w)$ is at most

$$\widetilde{O}((C_1 + C_2) \cdot \|g\|_2). \tag{4}$$

B.2 PROOF OF THEOREM B.1

We first give a rough explanation on the proof of Theorem 3.3. For intuition, we consider the case $C_1 = \Theta(1)$, $C_2 = \Theta(1)$, and $\epsilon_{\mathrm{mp}} = \Theta(1)$ in this explanation. The amortized time analysis is based on a potential function that measures the distance of the approximate vector v and the target vector w. We will show that

- The cost to update the LSH data structure is proportional to the decrease of the potential.
- Each call to query increase the potential by a fixed amount.

Combining both together gives the amortized running time bound of our data structure.

Now, we explain the definition of the potential. Consider the k-th round of the algorithm. For all $i \in [n]$, we define $x_i^{(k)} = w_i^{(k)} - v_i^{(k)}$. Note that $\|x_i^{(k)}\|_2$ measures the distance between $w_i^{(k)}$ and $v_i^{(k)}$. Our algorithm fixes the indices with largest error $\|x_i^{(k)}\|_2$. To capture the fact that updating in a larger batch is more efficient, we define the potential as a weighted combination of the error where we put more weight to higher $x_i^{(k)}$. Formally, we sort the coordinates of $x^{(k)}$ such that $\|x_i^{(k)}\|_2 \ge \|x_{i+1}^{(k)}\|_2$ and define the potential by

$$\Psi_k = \sum_{i=1}^{n} g_i \cdot \psi(x_i^{(k)}),$$

where g_i are positive decreasing numbers to be chosen and ψ is a symmetric ($\psi(x) = \psi(-x)$) positive function that increases on both sides. For intuition, one can think $\psi(x)$ behaves roughly like $|x|$.

B.2.1 Proof of correctness

We prove the correctness of Theorem 3.3, we will defer some simple calculations into later sections.

Definition of x and y. Consider the k-th round of the algorithm. For all $i \in [n]$, we define $x_i^{(k)} \in \mathbb{R}^d$, $x_i^{(k+1)} \in \mathbb{R}^d$ and $y_i^{(k)} \in \mathbb{R}^d$ as follows:

$$x_i^{(k)} = w_i^{(k)} - v_i^{(k)}, y_i^{(k)} = w_i^{(k+1)} - v_i^{(k)}, x_i^{(k+1)} = w_i^{(k+1)} - v_i^{(k+1)}.$$

Note that the difference between $x_i^{(k)}$ and $y_i^{(k)}$ is that w is changing. The difference between $y_i^{(k)}$ and $x_i^{(k+1)}$ is that v is changing.

Assume sorting. Assume the coordinates of vector $x^{(k)} \in \mathbb{R}^{n \times d}$ are sorted such that $\|x_i^{(k)}\|_2 \geq \|x_{i+1}^{(k)}\|_2$. Let τ and π are permutations such that $\|x_{\tau(i)}^{(k+1)}\|_2 \geq \|x_{\tau(i+1)}^{(k+1)}\|_2$ and $\|y_{\pi(i)}^{(k)}\|_2 \geq \|y_{\pi(i+1)}^{(k)}\|_2$.

Definition of Potential function. Let $\psi : \mathbb{R} \to \mathbb{R}$ be defined by

$$\psi(x) = \begin{cases} \frac{\|x\|_2^2}{2\epsilon_{\text{mds}}}, & \|x\|_2 \in [0, \epsilon_{\text{mds}}] \\ \epsilon_{\text{mds}} - \frac{(4\epsilon_{\text{mds}}^2 - \|x\|_2^2)^2}{18\epsilon_{\text{mds}}^3}, & \|x\|_2 \in (\epsilon_{\text{mds}}, 2\epsilon_{\text{mds}}] \\ \epsilon_{\text{mds}}, & \|x\|_2 \in (2\epsilon_{\text{mds}}, +\infty) \end{cases} \tag{5}$$

We define the potential at the k-th round by

$$\Psi_k = \sum_{i=1}^{n} g_i \cdot \psi(x_{\tau_k(i)}^{(k)}),$$

where $\tau_k(i)$ is the permutation such that $\|x_{\tau_k(i)}^{(k)}\|_2 \geq \|x_{\tau_k(i+1)}^{(k)}\|_2$.

Bounding the potential.

We can express $\Psi_{k+1} - \Psi_k$ as follows:

$$\Psi_{k+1} - \Psi_k = \sum_{i=1}^{n} g_i \cdot \left(\psi(x_{\tau(i)}^{(k+1)}) - \psi(x_i^{(k)}) \right)$$

$$= \sum_{i=1}^{n} g_i \cdot \underbrace{\left(\psi(y_{\pi(i)}^{(k)}) - \psi(x_i^{(k)}) \right)}_{w \text{ move}} - \sum_{i=1}^{n} g_i \cdot \underbrace{\left(\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\tau(i)}^{(k+1)}) \right)}_{v \text{ move}}. \tag{6}$$

Now, using Lemma B.5 and B.7, and the fact that $\Psi_0 = 0$ and $\Psi_T \geq 0$, with Eq. 6, we get

$$0 \leq \Psi_T - \Psi_0 = \sum_{k=0}^{T-1} (\Psi_{k+1} - \Psi_k)$$

$$\leq \sum_{k=0}^{T-1} \left(O(C_1 + C_2/\epsilon_{\text{mds}}) \cdot \|g\|_2 - \Omega(\epsilon_{\text{mds}} r_k g_{r_k} / \log n) \right)$$

$$= T \cdot O(C_1 + C_2/\epsilon_{\text{mds}}) \cdot \|g\|_2 - \sum_{k=1}^{T} \Omega(\epsilon_{\text{mds}} r_k g_{r_k} / \log n),$$

where the third step follows by Lemma B.5 and Lemma B.7 and r_k is the number of coordinates we update during that iteration.

Therefore, we get,

$$\sum_{k=1}^{T} r_k g_{r_k} = O\left(T \cdot (C_1/\epsilon_{\text{mds}} + C_2/\epsilon_{\text{mds}}^2) \cdot \log n \cdot \|g\|_2 \right).$$

B.2.2 INITIALIZATION TIME, UPDATE TIME, QUERY TIME

To formalize the amortized runtime proof, we first analyze the initialization time (Lemma B.2), update time (Lemma B.3), and query time (Lemma B.4) of our maintenance data-structure.

Lemma B.2 (Initialization time). *The initialization time of data-structure* MAINTAIN *(Algorithm 1) is $O(dn^{1+\rho})$.*

Lemma B.3 (Update time). *The update time of data-structure* MAINTAIN *(Algorithm 1) is $O(rg_r) + O(Sd + S\log n)$ where r is the number of indices we updated in v, S is the number of weights changed. The later two terms are dominated by the updating time of neural network.*

Proof. We change r ($r \geq n^a$) terms each time, and the running time for updating the LSH is rg_r. We need to update v and calculate its ℓ_2 norm every time, and the computational cost is Sd. We also need to maintain an order on the error $y_i^{(k)}$, using some standard data structure (like Fibonacci heap), this can be done in $S\log n$. Thus the total running time per update is $O(rg_r) + O(Sd + S\log n)$, the second term is bounded by the updating cost of neural network training, since calculate the gradient takes at least $O(Sd)$ and we usually have $d \gg \log n$. $\qquad\square$

Lemma B.4 (Query time). *The query time of data-structure* MAINTAIN *(Algorithm 1) is $O(n^\rho d + n^a d)$.*

B.3 BOUNDING w MOVE

Lemma B.5 (w move). *We have*

$$\sum_{i=1}^n g_i \cdot \mathbb{E}\left[\psi(y_{\pi(i)}^{(k)}) - \psi(x_i^{(k)})\right] \leq O(C_1 + C_2/\epsilon_{\mathrm{mds}}) \cdot \|g\|_2.$$

Proof. Observe that since the errors $\|x_i^{(k)}\|_2$ are sorted in descending order, and $\psi(x)$ is symmetric and non-decreasing function, thus $\psi(x_i^{(k)})$ is also in decreasing order. In addition, note that g is decreasing, we have

$$\sum_{i=1}^n g_i \psi(x_{\pi(i)}^{(k)}) \leq \sum_{i=1}^n g_i \psi(x_i^{(k)}). \tag{7}$$

Hence we have

$$\mathbb{E}\left[\sum_{i=1}^n g_i \cdot \left(\psi(y_{\pi(i)}^{(k)}) - \psi(x_i^{(k)})\right)\right] \leq \mathbb{E}\left[\sum_{i=1}^n g_i \cdot \left(\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\pi(i)}^{(k)})\right)\right] \qquad \text{by Eq. 7}$$

$$= \sum_{i=1}^n g_i \cdot \mathbb{E}[\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\pi(i)}^{(k)})]$$

$$= O(C_1 + C_2/\epsilon_{\mathrm{mds}}) \cdot \|g\|_2. \qquad \text{by Lemma B.6}$$

Thus, we complete the proof of w move Lemma. $\qquad\square$

It remains to prove the following Lemma,

Lemma B.6.

$$\sum_{i=1}^n g_i \cdot \mathbb{E}[\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\pi(i)}^{(k)})] = O(C_1 + C_2/\epsilon_{\mathrm{mds}}) \cdot \|g\|_2.$$

Proof. We separate the term into two:

$$\sum_{i=1}^n g_i \cdot \mathbb{E}[\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\pi(i)}^{(k)})] = \sum_{i=1}^n g_{\pi^{-1}(i)} \cdot \mathbb{E}[\psi(y_i^{(k)}) - \psi(\mathbb{E}[y_i^{(k)}])]$$

$$+ \sum_{i=1}^n g_{\pi^{-1}(i)} \cdot (\psi(\mathbb{E}[y_i^{(k)}]) - \psi(x_i^{(k)})). \tag{8}$$

For the first term, we have

$$
\begin{aligned}
&\psi(y_i^{(k)}) - \mathbb{E}[\psi(y_i^{(k)})]\\
&= \langle \psi'(\mathbb{E}[y_i^{(k)}]), y_i^{(k)} - \mathbb{E}[y_i^{(k)}]\rangle + \frac{1}{2}(y_i^{(k)} - \mathbb{E}[y_i^{(k)}])^\top \psi''(\zeta)(y_i^{(k)} - \mathbb{E}[y_i^{(k)}])\\
&\leq \langle \psi'(\mathbb{E}[y_i^{(k)}]), y_i^{(k)} - \mathbb{E}[y_i^{(k)}]\rangle + \frac{1}{2}L_2\|y_i^{(k)} - \mathbb{E}[y_i^{(k)}]\|_2^2\\
&= \langle \psi'(\mathbb{E}[y_i^{(k)}]), w_i^{(k+1)} - \mathbb{E}[w_i^{(k+1)}]\rangle + \frac{1}{2}L_2\|w_i^{(k+1)} - \mathbb{E}[w_i^{(k+1)}]\|_2^2 \qquad (9)
\end{aligned}
$$

where the first step follows from the Mean value theorem, the second step follows from the definition of L_2 (see Part 4 of potential lemma B.8), the last step follows from the definition of $y_i^{(k)}$.

Next, we denote $\gamma_i = \mathrm{Var}[w_i^{(k+1)}]$. Summing over i and taking conditional expectation given $w^{(k)}$ on both sides, we get

$$
\begin{aligned}
\sum_{i=1}^n g_{\pi^{-1}(i)} \cdot \mathbb{E}[\psi(y_i^{(k)}) - \psi(\mathbb{E}[y_i^{(k)}])] &\leq \sum_{i=1}^n g_{\pi^{-1}(i)} \cdot \mathbb{E}[\langle \psi'(\mathbb{E}[y_i^{(k)}]), w_i^{(k+1)} - \mathbb{E}[w_i^{(k+1)}]\rangle]\\
&\quad + \sum_{i=1}^n g_{\pi^{-1}(i)} \cdot \frac{1}{2}L_2\mathbb{E}[\|w_i^{(k+1)} - \mathbb{E}[w_i^{(k+1)}]\|_2^2]\\
&= 0 + \frac{1}{2}L_2\sum_{i=1}^n g_{\pi^{-1}(i)} \cdot \gamma_i\\
&\leq \frac{1}{2}L_2\|g\|_2(\sum_{i=1}^n \gamma_i^2)^{\frac{1}{2}}\\
&\leq \frac{1}{2}\cdot O(1/\epsilon_{\mathrm{mds}})\cdot\|g\|_2\cdot C_2\\
&= O(C_2/\epsilon_{\mathrm{mds}})\|g\|_2. \qquad (10)
\end{aligned}
$$

The first step follows from Eq. 9, the second step follows from the linearity of expectation and the definition of γ_i, the third step follows from Cauchy-Shwarz inequality, the fourth step follows from $L_2 = O(1/\epsilon_{\mathrm{mds}})$ (see Lemma B.8) and Eq. 1.

For the second term, conditioning on $w_i^{(k)}$, we have

$$
\psi(\mathbb{E}[y_i^{(k)}]) - \psi(x_i^{(k)}) \leq L_1 \cdot \|\mathbb{E}[y_i^{(k)}] - x_i^k\|_2 = L_1 \cdot \|\mathbb{E}[w_i^{(k+1)}] - w_i^k\|_2 \overset{\text{def}}{=} L_1 \cdot \beta_i. \qquad (11)
$$

The first inequality follows from the L_1-Lipschitz continuity of Ψ (see part 4 of Lemma B.8). The second step follows from the definition of $y_i^{(k)}$ and $x_i^{(k)}$.

Summing over i, we get

$$
\sum_{i=1}^n g_{\pi^{-1}(i)} \cdot (\psi(\mathbb{E}[y_i^{(k)}]) - \psi(x_i^{(k)})) \leq \sum_{i=1}^n g_{\pi^{-1}(i)} \cdot L_1\beta_i \leq L_1 \cdot \|g\|_2 \cdot (\sum_{i=1}^n \beta_i^2)^{\frac{1}{2}} \leq O(C_1) \cdot \|g\|_2. \qquad (12)
$$

The first step follows from Eq. 11, the second step follows from Cauchy Shwarz inequality, the last step follows from $L_1 \leq 2$ (see part 4 of Lemma B.8) and Eq. 1.

Combining Eq. 81012, we have

$$
\sum_{i=1}^n g_i \cdot \mathbb{E}[\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\pi(i)}^{(k)})] \leq O(C_1 + C_2/\epsilon_{\mathrm{mds}})\|g\|_2.
$$

Thus completing the proof. $\qquad\qquad\square$

B.4 BOUNDING v MOVE

The goal of this section is to prove Lemma B.7.

Lemma B.7 (v move). *We have,*

$$\sum_{i=1}^{n} g_i \cdot \left(\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\tau(i)}^{(k+1)}) \right) \geq \Omega(\epsilon_{\mathrm{mds}} r_k g_{r_k} / \log n).$$

Proof. We split the proof into two cases.

We first understand some simple facts which are useful in the later proof. Note that from definition of $x_i^{(k+1)}$, we know that $x^{(k+1)}$ has r_k coordinates are $\vec{0}$. Basically, $\|y^{(k)} - x^{(k+1)}\|_0 = r_k$. The difference between those vectors is, for the largest r_k coordinates in $y^{(k)}$, we erase them in $x^{(k+1)}$. Then for each $i \in [n - r_k]$, $x_{\tau(i)}^{(k+1)} = y_{\pi(i+r_k)}^{(k)}$. For convenience, we define $y_{\pi(n+i)}^{(k)} = \vec{0}, \forall i \in [r_k]$.

Case 1. We exit the while loop when $1.5 r_k \geq n$.

Let u^* denote the largest u satisfying $\|y_{\pi(u)}^{(k)}\|_2 \geq \epsilon_{\mathrm{mds}}/2$. If $u^* \geq r_k$, then we have that $\|y_{\pi(r_k)}^{(k)}\|_2 \geq \epsilon_{\mathrm{mds}}/2 \geq \epsilon_{\mathrm{mds}}/100$. Otherwise, the condition of the loop shows that

$$\begin{aligned}
\|y_{\pi(r_k)}^{(k)}\|_2 &\geq (1 - 1/\log n)^{\log_{1.5} r_k - \log_{1.5} u^*} \|y_{\pi(u^*)}^{(k)}\|_2 \\
&\geq (1 - 1/\log n)^{\log_{1.5} n} \epsilon_{\mathrm{mds}}/2 \\
&\geq \epsilon_{\mathrm{mds}}/100.
\end{aligned}$$

where we used that $n \geq 4$.

According to the definition of $x_{\tau(i)}^{(k+1)}$, we have

$$\begin{aligned}
\sum_{i=1}^{n} g_i(\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\tau(i)}^{(k+1)})) &= \sum_{i=1}^{n} g_i(\psi(y_{\pi(i)}^{(k)}) - \psi(y_{\pi(i+r_k)}^{(k)})) \\
&\geq \sum_{i=n/3+1}^{n} g_i(\psi(y_{\pi(i)}^{(k)}) - \psi(y_{\pi(i+r_k)}^{(k)})) \\
&\geq \sum_{i=n/3+1}^{n} g_i \psi(y_{\pi(i)}^{(k)}) \\
&\geq \sum_{i=n/3+1}^{2n/3} g_i f((\epsilon_{\mathrm{mds}}/100)^2) \geq \Omega(r_k g_{r_k} \epsilon_{\mathrm{mds}}),
\end{aligned}$$

where the first step follows from $x_{\tau(i)}^{(k+1)} = y_{\pi(i+r_k)}^{(k)}$, the second step follows from $\psi(x)$ is non-decreasing (see part 2 of Lemma B.8) and $\|y_{\pi(i)}^{(k)}\|_2$ is non-increasing, the third step follows from $1.5 r_k > n$ and hence $\psi(y_{\pi(i+r_k)}^{(k)}) = 0$ for $i \geq n/3+1$, the fourth step follows from $\psi(x) = f(\|x\|_2^2)$ is non-decreasing and $\|y_{\pi(i)}^{(k)}\|_2 \geq \|y_{\pi(r_k)}^{(k)}\|_2 \geq \epsilon_{\mathrm{mds}}/100$ for all $i < 2n/3$, and the last step follows by g is non-increasing and the part 3 of Lemma B.8.

Case 2. We exit the while loop when $1.5 r_k < n$ and $\|y_{\pi(1.5 r_k)}^{(k)}\|_2 < (1 - 1/\log n)\|y_{\pi(r_k)}^{(k)}\|_2$.

By the same argument as Case 1, we have that $\|y_{\pi(r_k)}^{(k)}\|_2 \geq \epsilon_{\mathrm{mds}}/100$. Part 3 of Lemma B.8 together with the fact

$$\|y_{\pi(1.5 r_k)}^{(k)}\|_2 < \min(\epsilon_{\mathrm{mds}}/2, \|y_{\pi(r_k)}^{(k)}\|_2 \cdot (1 - 1/\log n)),$$

indicates that

$$\psi(y_{\pi(1.5 r_k)}^{(k)}) - \psi(y_{\pi(r_k)}^{(k)}) = \Omega(\epsilon_{\mathrm{mds}}/\log n). \tag{13}$$

Putting things together, we have

$$
\sum_{i=1}^{n} g_i \cdot (\psi(y_{\pi(i)}^{(k)}) - \psi(x_{\tau(i)}^{(k+1)}))
$$

$$
= \sum_{i=1}^{n} g_i \cdot (\psi(y_{\pi(i)}^{(k)}) - \psi(y_{\pi(i+r_k)}^{(k)})) \qquad \text{by } x_{\tau(i)}^{(k+1)} = y_{\pi(i+r_k)}^{(k)}
$$

$$
\geq \sum_{i=r_k/2}^{r_k} g_i \cdot (\psi(y_{\pi(i)}^{(k)}) - \psi(y_{\pi(i+r_k)}^{(k)})) \qquad \text{by } \psi(y_{\pi(i)}^{(k)}) - \psi(y_{\pi(i+r_k)}^{(k)}) \geq 0
$$

$$
\geq \sum_{i=r_k/2}^{r_k} g_i \cdot (\psi(y_{\pi(r_k)}^{(k)}) - \psi(y_{\pi(1.5r_k)}^{(k)}))
$$

$$
\geq \sum_{i=r_k/2}^{r_k} g_i \cdot \Omega(\frac{\epsilon_{\mathrm{mds}}}{\log n}) \qquad \text{by } 13
$$

$$
\geq \sum_{i=r_k/2}^{r_k} g_{r_k} \cdot \Omega(\frac{\epsilon_{\mathrm{mds}}}{\log n}) \qquad \text{by } g_i \text{ is decreasing}
$$

$$
= \Omega\left(\epsilon_{\mathrm{mds}} r_k g_{r_k} / \log n\right),
$$

where the third step follows by $\|y_{\pi(i)}^{(k)}\|_2$ is non-increasing and ψ is non-decreasing (see part 2 of Lemma B.8). $\qquad\square$

B.5 POTENTIAL FUNCTION ψ

Here we proved a vector version ($\psi(x) = f(\|x\|_2^2)$):

Lemma B.8 (Properties of potential function ψ). *Let function $\psi : \mathbb{R}^d \to \mathbb{R}$ (defined in Eq. 5). Then function ψ satisfies the following properties:*
1. Symmetric ($\psi(-x) = \psi(x)$) and $\psi(0) = 0$;
2. If $\|x\|_2 \geq \|y\|_2$, then $\psi(x) \geq \psi(y)$;
3. $|f'(x)| = \Omega(1/\epsilon_{\mathrm{mds}}), \forall |x| \in [(0.01\epsilon_{\mathrm{mds}})^2, \epsilon_{\mathrm{mds}}^2]$;
4. $L_1 \stackrel{\text{def}}{=} \max_x \frac{D_x \psi[h]}{\|h\|_2} = 2$ and $L_2 \stackrel{\text{def}}{=} \max_x \frac{D_x^2 \psi[h,h]}{\|h\|_2^2} = 10/\epsilon_{\mathrm{mds}}$;
5. $\psi(x)$ is a constant for $\|x\|_2 \geq 2\epsilon_{\mathrm{mds}}$

Proof. Recall $f : \mathbb{R}_+ \to \mathbb{R}$ is defined as

$$
f(x) := \begin{cases} \frac{x^2}{2\epsilon_{\mathrm{mds}}^3}, & x \in [0, \epsilon_{\mathrm{mds}}^2]; \\ \epsilon_{\mathrm{mds}} - \frac{(4\epsilon_{\mathrm{mds}}^2 - x)^2}{18\epsilon_{\mathrm{mds}}^3}, & x \in (\epsilon_{\mathrm{mds}}^2, 4\epsilon_{\mathrm{mds}}^2]; \\ \epsilon_{\mathrm{mds}}, & x \in (4\epsilon_{\mathrm{mds}}^2, +\infty). \end{cases}
$$

We can see that

$$
f(x)' = \begin{cases} \frac{x}{\epsilon_{\mathrm{mds}}^3}, & x \in [0, \epsilon_{\mathrm{mds}}^2]; \\ \frac{4\epsilon_{\mathrm{mds}}^2 - x}{9\epsilon_{\mathrm{mds}}^3}, & x \in (\epsilon_{\mathrm{mds}}^2, 4\epsilon_{\mathrm{mds}}^2]; \\ 0, & x \in (4\epsilon_{\mathrm{mds}}^2, +\infty). \end{cases}
$$

and

$$
f(x)'' = \begin{cases} \frac{1}{\epsilon_{\mathrm{mds}}^3}, & x \in [0, \epsilon_{\mathrm{mds}}^2]; \\ -\frac{1}{9\epsilon_{\mathrm{mds}}^3}, & x \in (\epsilon_{\mathrm{mds}}^2, 4\epsilon_{\mathrm{mds}}^2]; \\ 0, & |x| \in (4\epsilon_{\mathrm{mds}}^2, +\infty) \end{cases}
$$

It implies that $\max_x |f(x)'| \leq \frac{1}{\epsilon_{\mathrm{mds}}}$ and $\max_x |f(x)''| \leq \frac{1}{\epsilon_{\mathrm{mds}}^3}$. Let $\psi(x) = f(\|x\|_2^2)$.

Proof of Part 1, 2 and 5. These proofs are pretty standard from definition of ψ.

Proof of Part 3. This is trivially following from definition of scalar function f.

Proof of Part 4. By chain rule, we have

$$D_x\psi[h] = 2f'(\|x\|_2^2) \cdot \langle x, h\rangle$$
$$D_x^2\psi[h,h] = 2f''(\|x\|_2^2) \cdot (\langle x, h\rangle)^2 + 2f'(\|x\|_2^2) \cdot \langle h, h\rangle$$

We can upper bound

$$|D_x\psi[h]| \leq 2|f'(\|x\|_2^2)| \cdot |\langle x, h\rangle| \leq 2|f'(\|x\|_2^2)| \cdot \|x\|_2 \cdot \|h\|_2.$$

Thus, we have

$$|f'(\|x\|_2^2)| \cdot \|x\|_2 = \begin{cases} \|x\|_2^3/\epsilon_{\mathrm{mds}}^3 \leq 1, & \|x\|_2 \in [0, \epsilon_{\mathrm{mds}}]; \\ (4\epsilon_{\mathrm{mds}}^2 - \|x\|_2^2)\|x\|_2/(9\epsilon_{\mathrm{mds}}^3) \leq 2/3, & \|x\|_2 \in (\epsilon_{\mathrm{mds}}, 2\epsilon_{\mathrm{mds}}); \\ 0, & \|x\|_2 \in (2\epsilon_{\mathrm{mds}}, +\infty). \end{cases}$$

It implies that $|D_x\psi[h]| \leq 2\|h\|_2, \forall x$.

By case analysis, we have

$$|f''(\|x\|_2^2)| \cdot \|x\|_2^2 \leq \begin{cases} \frac{1}{\epsilon_{\mathrm{mds}}^3}\|x\|_2^2 \leq 4/\epsilon_{\mathrm{mds}}, & \|x\|_2^2 \in [0, 4\epsilon_{\mathrm{mds}}^2]; \\ 0, & \|x\|_2^2 \in (4\epsilon_{\mathrm{mds}}, +\infty). \end{cases}$$

We can also upper bound

$$\begin{aligned} |D_x^2\psi[h,h]| &\leq 2|f''(\|x\|_2^2)| \cdot \langle x, h\rangle^2 + 2|f'(\|x\|_2^2)| \cdot \|h\|_2^2 \\ &\leq 2|f''(\|x\|_2^2)| \cdot (\|x\|_2 \cdot \|h\|_2)^2 + 2|f'(\|x\|_2^2)| \cdot \|h\|_2^2 \\ &\leq 2 \cdot \frac{4}{\epsilon_{\mathrm{mds}}}\|h\|_2^2 + 2 \cdot \frac{1}{\epsilon_{\mathrm{mds}}}\|h\|_2^2 \\ &= \frac{10}{\epsilon_{\mathrm{mds}}}\|h\|_2^2. \end{aligned}$$

$\square$

B.6 EXAMPLES

Comparing with sequential updating algorithm We present another version of our main result, which is particularly useful when we compare with the sequential updating algorithm.

Theorem B.9 (Locality sensitive hashing maintenance, worst case bound). *For any constant c_1, c_2 ($c_1 > c_2$) there is a dynamic data structure (Algorithm 1) that achieves (c_1, c_2)-accuracy. The data structure takes $\widetilde{O}(dn^{1+\rho})$ time to initialize and each call of $\mathrm{QUERY}(h)$ takes time $\widetilde{O}(n^\rho d)$. By taking $a = \min\{\rho, \alpha\}$ and $g_r = t_r$, after T iterations, the amortized expected time per call of $\mathrm{UPDATE}(w)$ is at most*

$$\widetilde{O}\left(\frac{n^\rho}{T} \sum_{k=0}^{T-1} \sum_{i=1}^{n} \left(\left|\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)}\right| + \mathrm{Var}[w_i^{k+1}]\right)\right) \tag{14}$$

The proof is almost indentical to Theorem B.1, we only need to replace Lemma B.5 by the following one.

Lemma B.10 (w move). *We have*

$$\sum_{i=1}^{n} g_i \cdot \mathbb{E}\left[\psi(y_{\pi(i)}^{(k)}) - \psi(x_i^{(k)})\right] \leq O\left(g_1 \sum_{i=1}^{n} \left|\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)}\right| + \mathrm{Var}[w_i^{k+1}]\right)$$

$$= O\left(n^\rho \sum_{i=1}^{n} \left|\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)}\right| + \mathrm{Var}[w_i^{k+1}]\right)$$

We omit the dependence on ϵ_{mds} since we assume it to be constant in the scheduler.

Proof. Again, the proof is almost identical to Lemma B.5, the only difference is that we use ℓ_∞/ℓ_1 form of Cauchy-Shwarz instead of the ℓ_2/ℓ_2 form in the previous proof. We only point out the difference here.

We replace Eq. 10 with

$$\sum_{i=1}^{n} g_{\pi^{-1}(i)} \cdot \mathbb{E}[\psi(y_i^{(k)}) - \psi(\mathbb{E}[y_i^{(k)}])] = 0 + \frac{1}{2} L_2 \sum_{i=1}^{n} g_{\pi^{-1}(i)} \cdot \gamma_i$$

$$\leq \frac{1}{2} L_2 g_1 \cdot \sum_{i=1}^{n} \gamma_i$$

$$\approx O\left(g_1 \sum_{i=1}^{n} \mathrm{Var}[w_i^{k+1}]\right).$$

The first step follows from Eq. 10, the second step follows from $\{g_i\}_{i=1,\cdots,n}$ are decreasing and the last step follows from the definition of γ_i.

Similarly, we replace Eq. 12 with

$$\sum_{i=1}^{n} g_{\pi^{-1}(i)} \cdot (\psi(\mathbb{E}[y_i^{(k)}]) - \psi(x_i^{(k)})) \leq \sum_{i=1}^{n} g_{\pi^{-1}(i)} \cdot L_1 \beta_i \lesssim O\left(g_1 \sum_{i=1}^{n} \left|\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)}\right|\right)$$

The first step follows from Eq. 12, the second step follows from the definition of β_i, $L_1 \leq 2$ and $\{g_i\}_{i=1,\cdots,n}$ are decreasing.

The rest of the proof are the same and we omit it here. $\qquad\square$

The sequential updating time for LSH is n^ρ. The total number of updating is (roughly) at least

$$O\left(\sum_{k=1}^{T} \sum_{i=1}^{n} \left(\left|\mathbb{E}[w_i^{(k+1)}] - w_i^{(k)}\right| + \mathrm{Var}[w_i^{k+1}]\right)\right)$$

It then easy to see that our scheduler always perform better than naive sequential update.

Comparing with naive batch updating algorithm   Below we give a concrete example to show the effectiveness of our algorithm. We take $\alpha = \rho$ for simplicity. Remember in Assumption 3.2, we already assume for any $r \leq n^a = n^\rho$, $T_r = n^\rho$, i.e., the average LSH updating time $t_r = n^\rho/r$ decays linearly in r when $r \leq n^\rho$. It remains to specify the rest t_r ($r \geq n^\rho$).

Example B.11. *Assuming the average running time decays faster than $1/\sqrt{r}$, i.e. $t_r = n^{-(1-\beta)\rho} r^{-\beta}$ for some $\beta \in [\frac{1}{2}, 1)$ when $r \geq n^\rho$. We then have*

$$\|g\|_2^2 = \sum_{r=1}^{n} g_r^2 \approx n^{-\rho/2}.$$

The running time of our scheduler is then at most

$$(C_1 + C_2)\|g\|_2 \approx (C_1 + C_2) n^{\rho/2}.$$

As long as the weight changes slowly, say $C_1 \approx C_2 \leq n^{\rho/2}$, we know the amortized updating time of our scheduler is strictly better than the naive approach that updates LSH every time, which has running time n^ρ each iteration.

C LEARNABLE LSH

C.1 LEARNING HASH FUNCTIONS

Denote a set of neurons in a particular layer as $\mathcal{C} = \{v_r \mid 0 \leq r < m\}$, where each neuron v_r has weight and bias. Given an input embedding q_i from the previous hidden layer, the output of a forward pass through neuron r is $\sigma(\langle q_i, v_r \rangle)$, where σ is some activation functions. For each input embedding q_i, both SLIDE and REFORMER select a set of neurons, denoted as $\mathcal{S}_i$, from the LSH hash tables for the forward pass. We collect the training samples from q_i and its $\mathcal{S}_i$ to improve the performance of LSH. Formally, The pairwise training samples (q, v) are collected according to the following criterion.

- positive pair $\mathcal{P}_+ = (q, v)$ if $v \in S$ and $\langle q, v \rangle > t_+$
- negative pair $\mathcal{P}_- = (q, v)$ if $v \in S$ and $\langle q, v \rangle < t_-$

And the loss is defined as:

$$\mathcal{L}(\mathcal{H}, \mathcal{P}_+, \mathcal{P}_-) = \max(0, \sum_{(q,v) \in \mathcal{P}_+} -\cos(\mathcal{H}(q), \mathcal{H}(v)) + \sum_{(q,v) \in \mathcal{P}_-} \cos(\mathcal{H}(q), \mathcal{H}(v)) + \alpha). \quad (15)$$

Here $\mathcal{H}$ is the hash functions of all L tables. $\mathcal{H}(x)$ generates a $K \cdot L$ vector containing the projection of x in each hash table. $\cos(\mathcal{H}(x), \mathcal{H}(y))$ represents the cosine similarity of two projected vectors. The major contribution of this learning approach is that it first optimize the hash function and the hash table index together. Our method targets at learning a useful indexing for retrieval efficiency while other learn to hash methods Wang et al. (2017) aim for a binary sketching that have higher precision.

C.2 OBSERVATIONS ON ATTENTION DISTRIBUTION

In this section, we present the visualization with analysis on the distribution of the minimal quantifies of neurons that sum up to have 0.9 softmax values in attention. On Figure 8, we present the distribution of each head of attention in each layer from a transformer model trained on Enwiki8 dataset. We classify the patternsRamsauer et al. (2020) of the distribution into 3 categories by their median values. With this observation, we are able to determine the layers that LSH or learnable LSH can apply in MONGOOSE framework.

Figure 8: The distribution of the minimal quantifies of neurons that sum up to have 0.9 softmax values in attention in each head of attention in each layer of transformer for Enwiki8

D EXPERIMENTS DETAILS

D.1 DATA STATISTICS

Table 3: Statistics for our benchmark dataset

Dataset	Wiki10-31k	Delicious-200K	Wiki-325K
Output Dimension	30938	205443	325056
Input Dimension	101938	782585	1617899
Training Samples	14146	6616	1778351
Testing Samples	196606	100095	587084

We present statistics on the 3 datasets we test on from the Extreme Classification Repository (Bhatia et al., 2016). While the number of datapoints in each dataset is not large (on the order of 200K at most), the key feature is the sheer size of the input and output dimensions. In particular, each dataset has over 10,000 output classes, which, using a conventional nueral network, requires a matrix multiplication involving over 10,000 neurons at the final layer.

D.2 ADDITIONAL RESULTS ON THE EXTREME-CLASSIFICATION TASK

Figure 9: Comparison of MONGOOSE against SLIDE and FULL during the training. The two metrics (P@1 in the top row and P@5 in the bottom row) are the same as in Bhatia et al. (2016).

We present the results of additional experiments comparing the classification performance of MON-GOOSE against SLIDE and FULL in Figure 9. The two metrics, P@1 and P@5, are presented in Bhatia et al. (2016) as follows:

$$\text{P@}k = \frac{1}{k} \sum_{l \in \text{rank}_k(\widehat{\mathbf{y}})} \mathbf{y}_l$$

where $\text{rank}_k(\cdot)$ extracts the top k indices from a vector, $\widehat{\mathbf{y}}$ refers to the predicted labels, and $\mathbf{y}$ refers to the ground truth label.

D.3 ADDITIONAL RESULTS ON THE LANGUAGE MODELING TASK

We present additional experiments comparing the training loss of MONGOOSE and Reformer on the synthetic copy task in Section 4. In Figure 10 we present additional experiments comparing the training loss of MONGOOSE and Reformer on the synthetic copy task in Section 4.1.2. The titles of each graph denote the hyperparameters of the Transformer model being tested: h1_s2048_t16 refers to a model with 1 round of hashing, a sequence length of 2048, and a token size of 16. Overall we can see that MONGOOSE makes a marked improvement in loss over Reformer in every case.

Figure 10: Comparison of MONGOOSE against Reformer during training on the synthetic copy task.

Figure 11: Comparison of MONGOOSE against Reformer during training on enwik8.

In Figure 11, we present further results comparing MONGOOSE to Reformer on the enwik8 character-level language modelling task. In particular, we train two sizes of Transformer (3 and 6 layers) with a maximum sequence length of 8192 and 4096 respectivelyh. In both settings mongoose achieves lower loss than Reformer.

Note that the goal of this experiments is to prove the superiority of learnable LSH over classical LSH in NN training (or MONGOOSE vs. naive LSH-NN framework) rather than improve the state-of-the-art perplexity.

E   RELATED WORK

E.1   DATA STRUCTURES FOR DYNAMIC SIMILARITY SEARCH

Similarity search is a well-studied problem with wide applications in recommendation system (Xue et al., 2017; Severyn & Moschitti, 2015; Hall & Attenberg, 2015), question answering (Boytsov et al., 2016; Seo et al., 2019; Ahmad et al., 2019; Chang et al., 2020), multi-label classification (Covington et al., 2016; Jain et al., 2016; Tagami, 2017) and natural language processing (Bengio et al., 2003; Gao et al., 2014; Lee et al., 2015). There are two major categories of similarity measures: (1) metric similarity (cosine similarity, euclidean distance), (2) non-metric similarity (inner product, KL divergence, neural network). The brute-force approach to solving similarity search is computationally expensive; in response, researchers have developed novel indexing structures to accelerate the search process, with trade-offs on search accuracy. Based on these indexing structures, similarity search algorithms can be broadly categorized as (1) hashing (Shrivastava & Li, 2014a;b), (2) quantization (Guo et al., 2016; Jegou et al., 2011), (3) tree-based (Ram & Gray, 2012), or (4) graph-based methods (Malkov et al., 2012; 2014; Malkov & Yashunin, 2018).

Most similarity search scenarios studied by these papers are static (search data does not change). In the experiments section, the developed similarity search methods are compared on a fixed dataset such as Sift (Jegou et al., 2011) or Glove (Pennington et al., 2014). However, in current similarity search applications such as the work of Fan et al. (2019), the search distribution (e.g. product vectors) changes over time due to the activation of new products and the expiration of old products. Therefore, some similarity search methods in metric space have been modified for online settings, such as hashing (Coleman et al., 2019) and quantization (Xu et al., 2018) methods; these methods sacrifice search speed for data-adaptiveness.

The training phase of Deep Learning models provides a natural setting for Dynamic LSH. During training, the weight matrices are slowly modified via gradients derived from objective functions. If we consider the weights as the search data and the training sample as queries, we can view DNN training as a Dynamic Similarity Search problem. Recent works take advantage of this view of DNN training by introducing LSH data structures to the NN training process. Chen et al. (2020) propose an algorithm (SLIDE) that retrieves neurons with maximum inner product in each step via an LSH based data structure. In this way, the backward pass of NN training is concentrated on the neurons with estimated large gradients. Their CPU implementation is able to outperform a traditional GPU implementation. Similar hashing based algorithms have also been used in Transformer models: Kitaev et al. (2020a) (Reformer) propose an LSH structure to reduce the memory bottleneck of self-attention modules especially over long sequences in Transformer.

Since DNN weights are the search data, the distribution of the weights among different hash buckets changes throughout the training. This necessitates constantly updating the LSH data structure: failing to update the LSH data structure as the search data changes degrades its nearest-neighbor search performance, which in turn worsens the quality of the DNN approximation. In our experiments, we found that failing to update the LSH data structure in SLIDE caused a 28% decrease in top-1 accuracy.

E.2   DATA DEPENDENT INDEXING

Data dependent hashing methods (DDH) focus on adapting hashing schemes to the data distribution. They often relate to indexing via an objective function. Most literature concentrates on hashing and quantization methods. Although previous works have achieved promising results in learning B-Trees (Kraska et al., 2018) or Lattice quantization (Sablayrolles et al., 2018), there are two major bottlenecks for DDH: (1) Theoretical insights are few applied in practice, (2) Complex index designs introduce computation overhead. In the theory of data dependent indexing, Andoni et al. (2018) present fruitful insights on hashing-based Approximate Nearest Neighbor search on metric space. However, there is not much literature that puts these insights into practice. Dong et al. (2019) propose a k-NN graph based algorithm for efficiently learning data dependent LSH in Euclidean space based on the insights given by Andoni et al. (2018). However, their method requires precomputing a k-NN graph, which is computationally expensive at scale. In the experiments, Dong et al. (2019) only compare their method with k-means; their performance compared to major ANN benchmarks (Erik et al., 2018) remains unknown.

Many practical applications of LSH eschew DDH methods for vanilla LSH due to the aforementioned computational bottlenecks. However, despite having sub-linear query time in theory, query complexity for even vanilla LSH is still high in practice Datar et al.(2004); Andoni et al. (2017).

When designing the dynamic data structure, we want to minimize the total running time and balance the overhead and benefit brought by the data structure. In general, the matrix multiplication and backpropagation procedures comes from neural network training, which we can not control, hence, we want to balance the accuracy-efficiency trade-offs by selecting neurons.

This is especially pronounced in the Dynamic LSH regime, when weights are evolving, besides query time, LSH updates incur a more significant overhead that harms the overall efficiency. Chen et al. (2020) introduce a method to control update frequency, but their method requires heavy hyper-parameter tuning and is not guaranteed to work for each benchmark. In contrast, our findings in the following section show that the update overhead can be significantly reduced while maintaining nearest-neighbor search quality during NN training. To our knowledge, this is the first time DDH techniques have been successfully applied to the Deep Learning setting.

E.3 EFFICIENT NEURAL NETWORK TRAINING

The weights of a neural network dynamically change during the training process, which brings great challenges to the LSH implementation. Since the data are no longer static, we need to constantly update the hash table, which incurs extra computation cost that could harm the overall performance. We present a *dynamic data structure* to handle this issue, and our data structure achieves significant speedup over naive implementation under mild assumptions, without compromising the worst case guarantee. The dynamic data structure (shown in Algorithm 1) borrows ideas from the work of Cohen et al. (2019); Jiang et al. (2020c) (which are originally designed for linear programming), and we adapt it to the LSH setting. Our data structure generalizes several practical insights and turns practical heuristics into rigorous theory, which guarantees significant speed up under natural assumptions for training neural networks and ensure the worst guarantee at the same time. In particular, we generalize and provide the following three practical heuristics (i) only update significantly changed coordinates, (ii) batch updating LSH instead of sequential updating, (iii) using "prediction" on those "marginal" coordinates.

In this work, we primarily study two LSH based efficient NN training methods: SLIDE and RE-FORMER. SLIDE introduces LSH to select neurons in the forward pass and then only do gradient descent on the chosen neurons. The major trade-off of SLIDE is the rebuild overhead versus the accurate neuron selection. To accurately retrieve the neurons with high inner products, the hash tables are required to be updated. This rehashing and rebuilding will be the major overhead caused by SLIDE. Therefore, the SLIDE's speed over full NN training is determined by the relative magnitude of rebuild overhead compared to the saved back-propagation time. The major goal of REFORMER is to reduce the memory consumption of the transformer so that GPU based hardware can support sequence to sequence tasks with longer sequence length. REFORMER also shares the trade-off when rebuilding the hash tables for better retrieval of attention weights. Besides, learning hash functions of REFORMER is more challenging than SLIDE. From an information retrieval's perspective, in attention settings, each data vector is also a query. This unique setting increases the hardness for learning better hash functions.

F   EFFICIENT GPU IMPLEMENTATION

As noted by Chen et al. (2020), each input in one batch samples a different set of weights(neurons). These irregular operations significantly reduce the benefits of using GPUs: they correspond to different sizes of rows for each input, which makes the forward pass much more difficult to parallelize and thus, more challenging to map to GPUs than regular programs (Burtscher et al., 2012). For this reason, Chen et al. (2020) build their SLIDE system in C++ from scratch on CPU. Even though their implementation achieved remarkable speed up, their impact is limited as they implemented their system from scratch in C++, making it difficult for the community to adopt SLIDE in practice. To verify that such randomized algorithm is not GPU friendly, we implement the exact same algorithm for GPUs. We show in Section 4.1.1 that it indeed fails to gain any speed up.

Figure 12: Visualization of how union selection within the batch instead of independent sets of neurons with variant length can avoid irregular memory access.

We design a variant of the algorithm to exploit fast matrix multiplications on GPUs. In the original SLIDE, each training example in a batch retrieves its own subset of weights. Here, we take a union of the retrieved subsets in each batch to avoid irregular and unbalanced memory access, shown in figure 12. Our implementation of this proposal is written in python under Pytorch framework with Cython compiled LSH and CUDA kernels for hashcode efficient computation. We believe this implementation would be more beneficial for the community as it can be easily plugged into any deep learning models.

Practical Implementation: In our design, we borrow insights from the theoretical guarantee from above and aim to find the sweet spot between theory limitations and practical challenges. First, instead of detecting weight changes at the cost of an extra copy, we reduce the problem to detect low quality of retrieved weights. In NN training setting, we measure quality as the inner product and low quality indicates a low inner product. We argue these two approaches are similar that they both signal the necessity of updating the data structure. Besides, rather than a soft margin for detecting data changes, which can be ambiguous under dynamic setting, inner product is a better measurement as it clearly indicates the performance of current data structure. More importantly from an efficiency perspective, quality detection comes almost for free because the inner product between the query embedding and retrieved neurons are necessary for the forward pass.

G   DISCUSSIONS

MONGOOSE shed lights on efficient NNS-ds for efficient training of deep neural networks. Especially, the slow change observation along with the smart scheduler demonstrate the possibility of applying NNS-ds with larger indexing overhead for dynamic similarity search where the distribution of data changes slowly. Equipped with both observation and algorithm, more NNS-ds could be involved in the deep learning community to tackle the efficiency issue.

REFERENCES

Amin Ahmad, Noah Constant, Yinfei Yang, and Daniel Cer. Reqa: An evaluation for end-to-end answer retrieval models. *arXiv preprint arXiv:1907.04780*, 2019.

Alexandr Andoni and Piotr Indyk. Near-optimal hashing algorithms for approximate nearest neighbor in high dimensions. In *2006 47th annual IEEE symposium on foundations of computer science (FOCS'06)*, pp. 459–468. IEEE, 2006.

Alexandr Andoni and Ilya Razenshteyn. Optimal data-dependent hashing for approximate near neighbors. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing (STOC)*, pp. 793–801, 2015.

Alexandr Andoni, Assaf Naor, Aleksandar Nikolov, Ilya Razenshteyn, and Erik Waingarten. Data-dependent hashing via nonlinear spectral gaps. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing (STOC)*, pp. 787–800, 2018.

Jimmy Ba and Brendan Frey. Adaptive dropout for training deep neural networks. In *Advances in neural information processing systems (NeurIPS)*, pp. 3084–3092, 2013.

Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Jauvin. A neural probabilistic language model. *Journal of machine learning research (JMLR)*, 3(Feb):1137–1155, 2003.

K. Bhatia, K. Dahiya, H. Jain, A. Mittal, Y. Prabhu, and M. Varma. The extreme classification repository: Multi-label datasets and code, 2016. URL http://manikvarma.org/downloads/XC/XMLRepository.html.

Leonid Boytsov, David Novak, Yury Malkov, and Eric Nyberg. Off the beaten path: Let's replace term-based retrieval with k-nn search. In *Proceedings of the 25th ACM international on conference on information and knowledge management (CIKM)*, pp. 1099–1108, 2016.

M. Burtscher, R. Nasre, and K. Pingali. A quantitative study of irregular programs on gpus. In *2012 IEEE International Symposium on Workload Characterization (IISWC)*, pp. 141–151, 2012.

Sarath Chandar, Sungjin Ahn, Hugo Larochelle, Pascal Vincent, Gerald Tesauro, and Yoshua Bengio. Hierarchical memory networks. *arXiv preprint arXiv:1605.07427*, 2016.

Wei-Cheng Chang, Felix X Yu, Yin-Wen Chang, Yiming Yang, and Sanjiv Kumar. Pre-training tasks for embedding-based large-scale retrieval. *arXiv preprint arXiv:2002.03932*, 2020.

Moses S Charikar. Similarity estimation techniques from rounding algorithms. In *Proceedings of the thiry-fourth annual ACM symposium on Theory of computing (STOC)*, pp. 380–388. ACM, 2002.

Gal Chechik, Varun Sharma, Uri Shalit, and Samy Bengio. Large scale online learning of image similarity through ranking. *Journal of Machine Learning Research*, 11(3), 2010.

Beidi Chen, Tharun Medini, James Farwell, Sameh Gobriel, Charlie Tai, and Anshumali Shrivastava. Slide: In defense of smart algorithms over hardware acceleration for large-scale deep learning systems. In *MLSys*. https://arxiv.org/pdf/1903.03129, 2020.

Wenlin Chen, James Wilson, Stephen Tyree, Kilian Weinberger, and Yixin Chen. Compressing neural networks with the hashing trick. In *International conference on machine learning*, pp. 2285–2294, 2015.

Michael B Cohen, Yin Tat Lee, and Zhao Song. Solving linear programs in the current matrix multiplication time. In *Proceedings of the 51st annual ACM SIGACT symposium on theory of computing (STOC)*, pp. 938–942, 2019.

Benjamin Coleman, Anshumali Shrivastava, and Richard G Baraniuk. Race: Sub-linear memory sketches for approximate near-neighbor search on streaming data. *arXiv preprint arXiv:1902.06687*, 2019.

Paul Covington, Jay Adams, and Emre Sargin. Deep neural networks for youtube recommendations. In *Proceedings of the 10th ACM Conference on Recommender Systems*, pp. 191–198. ACM, 2016.

Yihe Dong, Piotr Indyk, Ilya Razenshteyn, and Tal Wagner. Learning space partitions for nearest neighbor search. In *International Conference on Learning Representations (ICLR)*, 2019.

Bernhardsson Erik, Aumüller Martin, and Faithfull Alexander. ANN Benchmarks. https://github.com/erikbern/ann-benchmarks, 2018.

Miao Fan, Jiacheng Guo, Shuai Zhu, Shuo Miao, Mingming Sun, and Ping Li. Mobius: Towards the next generation of query-ad matching in baidu's sponsored search. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2509–2517. ACM, 2019.

Jianfeng Gao, Xiaodong He, Wen-tau Yih, and Li Deng. Learning continuous phrase representations for translation modeling. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (ACL)*, volume 1, pp. 699–709, 2014.

Ruiqi Guo et al. Quantization based fast inner product search. In *Artificial Intelligence and Statistics*, pp. 482–490, 2016.

Rob Hall and Josh Attenberg. Fast and accurate maximum inner product recommendations on map-reduce. In *Proceedings of the 24th International Conference on World Wide Web*, pp. 1263–1268. ACM, 2015.

Himanshu Jain, Yashoteja Prabhu, and Manik Varma. Extreme multi-label loss functions for recommendation, tagging, ranking & other missing label applications. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 935–944. ACM, 2016.

Herve Jegou, Matthijs Douze, and Cordelia Schmid. Product quantization for nearest neighbor search. *IEEE transactions on pattern analysis and machine intelligence*, 33(1):117–128, 2011.

Haotian Jiang, Tarun Kathuria, Yin Tat Lee, Swati Padmanabhan, and Zhao Song. A faster interior point method for semidefinite programming. In *FOCS*, 2020a.

Haotian Jiang, Yin Tat Lee, Zhao Song, and Sam Chiu-wai Wong. An improved cutting plane method for convex optimization, convex-concave games and its applications. In *STOC*. `https://arxiv.org/pdf/2004.04250.pdf`, 2020b.

Shunhua Jiang, Zhao Song, Omri Weinstein, and Hengjie Zhang. Faster dynamic matrix inverse for faster lps. *arXiv preprint arXiv:2004.07470*, 2020c.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. *arXiv preprint arXiv:2001.04451*, 2020a.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *ICLR*. `https://arxiv.org/pdf/2001.04451`, 2020b.

Tim Kraska, Alex Beutel, Ed H Chi, Jeffrey Dean, and Neoklis Polyzotis. The case for learned index structures. In *SIGMOD*, pp. 489–504, 2018.

Moontae Lee, Xiaodong He, Wen-tau Yih, Jianfeng Gao, Li Deng, and Paul Smolensky. Reasoning in vector space: An exploratory study of question answering. *arXiv preprint arXiv:1511.06426*, 2015.

Yury Malkov, Alexander Ponomarenko, Andrey Logvinov, and Vladimir Krylov. Scalable distributed algorithm for approximate nearest neighbor search problem in high dimensional general metric spaces. In *International Conference on Similarity Search and Applications*, pp. 132–147. Springer, 2012.

Yury Malkov, Alexander Ponomarenko, Andrey Logvinov, and Vladimir Krylov. Approximate nearest neighbor algorithm based on navigable small world graphs. *Information Systems*, 45:61–68, 2014.

Yury A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 2018.

Ioannis Partalas, Aris Kosmopoulos, Nicolas Baskiotis, Thierry Artieres, George Paliouras, Eric Gaussier, Ion Androutsopoulos, Massih-Reza Amini, and Patrick Galinari. Lshtc: A benchmark for large-scale text classification. *arXiv preprint arXiv:1503.08581*, 2015.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 1532–1543, 2014.

Jack Rae, Jonathan J Hunt, Ivo Danihelka, Timothy Harley, Andrew W Senior, Gregory Wayne, Alex Graves, and Timothy Lillicrap. Scaling memory-augmented neural networks with sparse reads and writes. In *Advances in Neural Information Processing Systems*, pp. 3621–3629, 2016.

Parikshit Ram and Alexander G Gray. Maximum inner-product search using cone trees. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining (KDD)*, pp. 931–939. ACM, 2012.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Lukas Gruber, Markus Holzleitner, Milena Pavlović, Geir Kjetil Sandve, Victor Greiff, et al. Hopfield networks is all you need. *arXiv preprint arXiv:2008.02217*, 2020.

Alexandre Sablayrolles, Matthijs Douze, Cordelia Schmid, and Hervé Jégou. Spreading vectors for similarity search. *arXiv preprint arXiv:1806.03198*, 2018.

Minjoon Seo, Jinhyuk Lee, Tom Kwiatkowski, Ankur P Parikh, Ali Farhadi, and Hannaneh Hajishirzi. Real-time open-domain question answering with dense-sparse phrase index. *arXiv preprint arXiv:1906.05807*, 2019.

Aliaksei Severyn and Alessandro Moschitti. Learning to rank short text pairs with convolutional deep neural networks. In *Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, pp. 373–382, Santiago, Chile, 2015.

Anshumali Shrivastava and Ping Li. Asymmetric lsh (alsh) for sublinear time maximum inner product search (mips). In *Advances in Neural Information Processing Systems*, pp. 2321–2329, 2014a.

Anshumali Shrivastava and Ping Li. Improved asymmetric locality sensitive hashing (alsh) for maximum inner product search (mips). *arXiv preprint arXiv:1410.5410*, 2014b.

Ryan Spring and Anshumali Shrivastava. Scalable and sustainable deep learning via randomized hashing. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 445–454, 2017.

Yukihiro Tagami. Annexml: Approximate nearest neighbor search for extreme multi-label classification. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 455–464. ACM, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems (NeurIPS)*, pp. 5998–6008, 2017.

Jingdong Wang, Ting Zhang, Nicu Sebe, Heng Tao Shen, et al. A survey on learning to hash. *IEEE transactions on pattern analysis and machine intelligence*, 40(4):769–790, 2017.

Donna Xu, Ivor W Tsang, and Ying Zhang. Online product quantization. *IEEE Transactions on Knowledge and Data Engineering*, 30(11):2185–2198, 2018.

Hong-Jian Xue, Xinyu Dai, Jianbing Zhang, Shujian Huang, and Jiajun Chen. Deep matrix factorization models for recommender systems. In *IJCAI*, pp. 3203–3209, 2017.