Context-Aware Kernel Search for Bayesian Optimization with Large Language Models

Abstract

The efficiency of Bayesian optimization (BO) relies on careful selection of the surrogate model to balance exploration and exploitation under limited budget. Traditional BO methods often struggle with sub-optimal kernel choices when using Gaussian processes (GPs) as the surrogate model. When the kernel is inadequately chosen, BO may converge slowly or even get stuck at an undesired local minimum. To address such drawback, we propose the novel Context-Aware Kernel Search (CAKES) to automate optimal kernel design in BO with large language models (LLMs). Concretely, CAKES exploits LLMs as crossover and mutation operators to adaptively generate and refine GP kernels based on the observed data. CAKES works entirely in-context and can be easily integrated into existing systems without requiring any fine-tuning. We further present a theoretical analysis demonstrating that our method achieves sub-linear regret relative to the budget for any input dimension. Experimental results demonstrate that CAKES outperforms various salient baseline methods in numerous synthetic and real-world optimization tasks. Notably, CAKES improves the overall performance on benchmark functions by roughly 36%. In hyperparameter tuning tasks, CAKES can effectively leverage fewer data samples to quickly identify high-performing configurations and consistently ranks first across various datasets. As an encouraging real application, we successfully applied CAKES to design photonic chips, achieving significant improvements in key performance indicators while speeding up the design cycle by a factor of ten compared to the baselines. Our code is accessible at https://github.com/cakes4bo/cakes.

1 Introduction

Many important scientific and engineering problems require optimizing objective functions that are noisy and expensive to evaluate. These objective functions often lack closed-form expressions, let alone gradient information, making optimization particularly difficult (Wang et al., 2023). Nonetheless, Bayesian optimization (BO) has shown remarkable success in optimizing such functions, due to its ability to operate on limited data and incorporate prior knowledge to guide the optimization process (Garnett, 2023). In the past couple of decades, BO has been used for diverse tasks ranging from tuning hyperparameters in machine learning (Snoek et al., 2012; Liu et al., 2024) to designing policies in robotics (Calandra et al., 2016; Martinez-Cantin, 2017) and recommending new molecules in drug discovery (Korovina et al., 2019; Tripp & Hernández-Lobato, 2024). The main idea behind BO is to first construct a *surrogate model*, typically using a Gaussian process (GP, Rasmussen & Williams, 2006), to represent the prior belief about the objective function. Then, by conditioning on the observations and the prior, the posterior is calculated using Bayes' rule to reflect the updated belief about the objective function. Based on this posterior, an *acquisition function* is further used to determine the next promising positions to query by balancing exploration (moving to regions with high uncertainty) and exploitation (moving to regions with high expected value).

Although the past decades have witnessed rapid development of BO, much of the focus has been on designing novel acquisition functions (Ament et al., 2023; Aglietti et al., 2024). In comparison, the challenge of appropriately choosing the surrogate model has received comparatively less attention (Shahriari et al., 2016). Many practitioners simply regard surrogate modeling as a "black art" and perceive it as less critical to the optimization outcome compared to the acquisition function design (Malkomes & Garnett, 2018). In the context of GPs, most off-the-shelf BO methods simply use

Figure 1: Overview of the proposed CAKES framework. Starting with an initial population of kernels, the LLM acts as crossover and mutation operators, proposing new kernels based on the given prompts. The proposed kernels are then evaluated using a fitness calculator, and the fittest ones advance to the next generation.

general-purpose kernels, such as the squared exponential kernel or Matérn-5/2 kernel (Snoek et al., 2012). While this seems reasonable at the first glance, the so-called *one-size-fits-all* approach has significant limitations. Since the kernel encodes our assumptions about the underlying objective function, the GP will be a poor fit if these assumptions do not match the reality (Roman et al., 2019). It has also been studied that with a poor choice of the kernel, BO may converge very slowly, especially when optimizing complex functions in moderate-to-high dimensional spaces (Gardner et al., 2017). These considerations underscore the need for a more sophisticated kernel design in BO.

While the pursuit for optimal kernel design is not new, existing approaches might not be straightforward in the setting of BO. In BO, the objective function is typically expensive to evaluate, resulting in limited observations for tuning the kernel. The lack of known functional structure and gradient information further complicates the kernel selection process, making it difficult to choose the most suitable kernel using traditional optimization-based methods (Bach, 2008; Gönen & Alpaydin, 2011). At its core, these challenges can be framed within the *few-shot learning* setting, where swift learning and generalization from limited data are required. Notably, these challenges align with the strengths of large language models (LLMs, Wei et al., 2022a), which excel at generalizing from few-shot samples (Brown et al., 2020), thus enabling efficient exploration with limited data. The *in-context learning* capability of LLMs also acts as implicit Bayesian inference (Xie et al., 2022; Han et al., 2023), allowing them to encode prior knowledge about the optimization task, search space, and other relevant information. LLMs' ability in performing complex reasoning further enhances their capacity to process contextual information and improve search performance (Yang et al., 2024). Moreover, LLMs are also pre-trained on massive internet data, which potentially contains transferable domain knowledge applicable to various optimization tasks. Given these insights, we aim to investigate the following question,

> "Can LLMs, with their encoded knowledge and few-shot prompting, help to enhance the kernel design in BO?"

Contributions. In this paper, we reveal the great potential of extending the capabilities of LLMs beyond standard natural language tasks to automated kernel design in BO. Our primary contributions are as follows:

- We conduct a thorough study to reveal the urgency for a more careful treatment of kernel design in BO, as the conventional setups, which often rely on fixed kernels or naive selection strategies, do not perform uniformly well across tasks.

- We propose CAKES, an adaptive kernel design method for BO that exploits LLMs as genetic operators to generate and refine kernels based on the observed data (see Figure 1). Our method can be applied entirely in-context and does not require any fine-tuning.

- We present a theoretical analysis based on regret and information gain, demonstrating that our method achieves sub-linear regret relative to the budget for any input dimension.

- We demonstrate that our method consistently outperforms other baselines across numerous optimization tasks, including globally optimizing benchmark functions, tuning hyperparameters of machine learning models, and optimizing photonic chip design.

2 PRELIMINARIES

We first review some key concepts in BO and the so-called *kernel grammar*, which serve as the bedrock for the method proposed in this paper.

2.1 BAYESIAN OPTIMIZATION

Consider optimizing an objective function $f : \mathcal{X} \subset \mathbb{R}^d \to \mathbb{R}$,

$$\mathbf{x}^* = \arg\max_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}). \tag{1}$$

Here, f is treated as a "black-box" function, meaning we can only obtain noisy evaluations of the form $y = f(\mathbf{x}) + \epsilon$, where $\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2)$ represents the Gaussian noise. The evaluations of f are also costly, limiting the number of queries we can make. In addition, the gradient of f is not directly accessible and must be estimated from the noisy evaluations, further complicating the optimization process. To address these challenges, Bayesian optimization (BO) employs a probabilistic surrogate model g to approximate f on the fly (Garnett, 2023). A popular choice for g is the family of Gaussian processes (GP, Rasmussen & Williams, 2006), where a GP can be fully defined by a mean function $m : \mathcal{X} \to \mathbb{R}$ and a positive semi-definite covariance (or kernel) function $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$. In practice, the mean function is often set to zero, allowing the GP to be solely characterized by the choice of the kernel function. At each iteration t, the calibration of the posterior distribution $p(g_t \mid \mathcal{D}_t)$ given the previous observations $\mathcal{D}_t = \{(\mathbf{x}_i, y_i)\}_{i=1}^{t-1}$ informs where to explore and exploit in $\mathcal{X}$. Then, based on $p(g_t \mid \mathcal{D}_t)$, an acquisition function $\alpha : \mathcal{X} \to \mathbb{R}$ defines a policy to choose the next best point to evaluate. Common choices of α include expected improvement (EI, Jones et al., 1998), upper confidence bound (UCB, Srinivas et al., 2012), and Thompson sampling (TS, Thompson, 1933). After each evaluation, the surrogate model g is refined to reflect the updated belief about f. We refer the readers to Appendix B.1 for a thorough treatment of BO with GPs.

2.2 KERNEL GRAMMAR

The kernel grammar introduced by Duvenaud et al. (2013) defines a comprehensive and flexible space of kernels. Such space exploits the closure properties of kernel functions under addition and multiplication, which ensures that: if $k_1(\mathbf{x}, \mathbf{x}')$ and $k_2(\mathbf{x}, \mathbf{x}')$ are valid kernels, then both $k_1(\mathbf{x}, \mathbf{x}') + k_2(\mathbf{x}, \mathbf{x}')$ and $k_1(\mathbf{x}, \mathbf{x}') \times k_2(\mathbf{x}, \mathbf{x}')$ are also valid kernels (Smola & Schölkopf, 1998). Starting from a set of base kernels, such as the squared exponential (SE), linear (LIN), periodic (PER), and rational quadratic (RQ), one can construct more expressive kernels by combining such base kernels via the addition and multiplication operators. For instance, LIN + PER kernel can capture periodic structure with a linear trend and SE × PER kernel can capture locally periodic components. Let $\mathcal{B}$ denote a base kernel and $\mathcal{S}$ denote a subexpression, the entire kernel space is described by all kernels that can be constructed using the following grammar rules:

1. Add a base kernel to a subexpression: $\mathcal{S} \to \mathcal{S} + \mathcal{B}$;

2. Multiply a subexpression with a base kernel: $\mathcal{S} \to \mathcal{S} \times \mathcal{B}$;

3. Replace a base kernel with another base kernel: $\mathcal{B} \to \mathcal{B}$.

Algorithm 1: Context-Aware Kernel Search (CAKES)

Input: Objective f, observations $\mathcal{D}$, budget T, number of crossovers n_c, probability of
       mutation p_m, population size n_p

Initialize the population $\mathbb{K}$

for $t = 1, \ldots, T$ **do**
    Feed $\mathcal{D}$ to the LLM with system prompt (see Fig. 4)
    Measure the fitness of each kernel $k \in \mathbb{K}$
    for $c = 1, \ldots, n_c$ **do**
        Sample two parent kernels k_1, k_2 from $\mathbb{K}$
        Generate kernel through crossover (see Fig. 5a): $k_c \sim \texttt{crossover}(k_1, k_2)$
        Add k_c to $\mathbb{K}$ and measure its fitness
    if $\texttt{rand()} < p_m$ **then**
        Select the fittest kernel k_f from $\mathbb{K}$
        Refine kernel through mutation (see Fig. 5b): $k_m \sim \texttt{mutation}(k_f)$
        Add k_m to $\mathbb{K}$ and measure its fitness
    Update population $\mathbb{K}$ by selecting the n_p fittest kernels
    Obtain candidate points: $\mathbf{x}_{t,k} = \arg\max_{\mathbf{x} \in \mathcal{X}} \alpha(\mathbf{x}; \mathcal{D}, k)$ for each $k \in \mathbb{K}$
    Set $k^* = \arg\max_{k \in \mathbb{K}} w_k \alpha(\mathbf{x}_{t,k}; \mathcal{D}, k)$ and let $\mathbf{x}_t = \mathbf{x}_{t,k^*}$
    Update observations: $\mathcal{D} \leftarrow \mathcal{D} \cup \{(\mathbf{x}_t, y_t)\}$

---

3 Context-Aware Kernel Search

We propose Context-Aware Kernel Search (CAKES) to automate GP surrogate modeling in BO with LLMs. CAKES uses LLMs as genetic operators to adaptively propose kernels based on the observed data. The main motivation is to refine the kernel choice at each iteration before determining the next query point. The complete procedure of CAKES is summarized in Algorithm 1 and the designed prompts are shown in Appendix D.1.

Conditioning the LLM. We begin by randomly sampling n points from the input space $\mathcal{X}$ to initialize the observations $\mathcal{D} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{n}$. These observations are then used as *few-shot samples* to prompt the LLM for analysis. The prompt is designed based on the concept of conditioning on high performance, as suggested by Zhou et al. (2023). Specifically, we start the prompt with a statement, *"You are an expert in machine learning, specializing in Gaussian processes",* to simulate the reasoning of a human expert in the field. It has also been shown that *chain-of-thought reasoning*, or generating intermediate reasoning steps, can improve the performance of LLMs (Wei et al., 2022b; Kojima et al., 2022). Motivated by this, we instruct the LLM to analyze the provided observations and identify patterns that can be represented by kernel functions, before proposing the kernels at each iteration. To enhance the LLM's understanding, we embed domain-specific knowledge by including examples of kernel functions along with their characteristics.

Initializing the population. We draw some inspiration from the genetic algorithm (Holland, 1992), where we maintain a population of candidates (kernels) throughout the optimization process. Our initial population consists of six base kernels: squared exponential (SE), periodic (PER), linear (LIN), rational quadratic (RQ), Matérn-3/2 (M3), and Matérn-5/2 (M5). We denote this initial set as $\mathbb{K} = \{\text{SE}, \text{PER}, \text{LIN}, \text{RQ}, \text{M3}, \text{M5}\}$. For each kernel $k \in \mathbb{K}$, we measure its *fitness* using the Bayesian Information Criterion (BIC, Schwarz, 1978), which balances model fit and complexity. BIC is commonly used for model selection and can be seen as an approximation to the Laplace approximation (Murphy, 2022). More detailed discussions on BIC and model selection for GPs can be found in Appendix B.3.

Proposing the kernels. We consider a generalized notion of the kernel grammar, which involves a set of base kernels $\{\mathcal{B}_1, \ldots, \mathcal{B}_r\}$ and a set of operators $\{\mathcal{T}_1, \ldots, \mathcal{T}_l\}$, where $r, l \in \mathbb{N}$. Each operator $\mathcal{T}_j : \mathcal{K} \times \mathcal{K} \to \mathcal{K}$, for $j = 1, \ldots, l$, is a closed operator (e.g., addition and multiplication) on the space of kernels $\mathcal{K}$. The grammar rules can be summarized in the following way:

1. Apply operator $\mathcal{T}_j$ on a subexpression and a base kernel: $\mathcal{S} \to \mathcal{T}_j(\mathcal{S}, \mathcal{B})$;

2. Replace a base kernel with another base kernel: $\mathcal{B} \to \mathcal{B}$.

Based on these grammar rules, we can formally define the kernel grammar space as follows:

Definition 1. *Let $\{k_1, \ldots, k_r\}$, where $r \in \mathbb{N}$, be a set of base kernels, and let $\{\mathcal{T}_1, \ldots, \mathcal{T}_l\}$, where $l \in \mathbb{N}$, be a set of operators defined by $\mathcal{T}_j : \mathcal{K} \times \mathcal{K} \to \mathcal{K}$ for $j = 1, \ldots, l$. For $i \in \mathbb{N}$, we can define the kernel grammar space recursively as follows:*

$$\mathbb{K}_0 := \{k_1, \ldots, k_r\},$$
$$\mathbb{K}_i := \{\mathcal{T}_j(k_1, k_2) \,|\, k_1, k_2 \in \mathbb{K}_{i-1}, j = 1, \ldots, l\} \cup \mathbb{K}_{i-1}.$$

When we refer to a kernel k from the kernel grammar space, we actually refer to the associated kernel family over its hyperparameters $\{k_{\boldsymbol{\theta}} \,|\, \boldsymbol{\theta} \in \Theta\}$. Hence, if we apply an operator $\mathcal{T}$ on two kernels k_1 and k_2, we obtain another kernel family $\{\mathcal{T}(k_{1,\boldsymbol{\theta}_1}, k_{2,\boldsymbol{\theta}_2}) \,|\, \boldsymbol{\theta}_1 \in \Theta_1, \boldsymbol{\theta}_2 \in \Theta_2\}$. By leveraging this kernel grammar space, we can use the LLM as *genetic operators* to propose kernels through the following steps:

- **Crossover:** We perform n_c crossover operations. For each crossover, we sample two parent kernels k_1, k_2 from $\mathbb{K}$ with probability proportional to their fitness. We then prompt the LLM to propose a new kernel k_c that has a lower BIC value, by applying an operator on the parent kernels.

- **Mutation:** With probability p_m, we perform a mutation operation. We select the fittest kernel k_f from $\mathbb{K}$ and prompt the LLM to suggest a new kernel k_m, by replacing one of the base kernels in k_f with another base kernel.

In the prompts, we also ask the LLM to report a brief analysis of its reasoning behind the proposed kernels. This serves as a sanity check, enabling us to verify and interpret the choices made by the LLM. The proposed kernels from both steps are added to $\mathbb{K}$, and their fitnesses are measured. Then, we select the top n_p fittest kernels to form the next generation of $\mathbb{K}$.

Choosing the next query point. In our experiments, we observed that some kernels may promise a good fit, but the actual improvement is not as substantial as expected when the proposed query points are evaluated. For this reason, we do not always rely on the fittest kernel to choose the next query point. Instead, we adopt the following weighting strategy,

$$k^* = \arg\max_{k \in \mathbb{K}} w_k \alpha(\mathbf{x}_{t,k}; \mathcal{D}, k), \tag{2}$$

where $w_k = \exp(-\mathrm{BIC}_k)/\sum_{j \in \mathbb{K}} \exp(-\mathrm{BIC}_j)$ and $\mathbf{x}_{t,k}$ denotes the proposed query point for that kernel. This strategy allows us to balance the kernel's ability to fit the data (as indicated by w_k) with the expected improvement at the proposed query point (as measured by α). After determining k^*, we set the next query point at $\mathbf{x}_t = \mathbf{x}_{t,k^*}$ and update the observations as $\mathcal{D} \leftarrow \mathcal{D} \cup \{(\mathbf{x}_t, y_t)\}$. This iterative process continues until a predefined budget T is exhausted.

4 THEORETICAL ANALYSIS

To establish the theoretical guarantee of our proposed method, we will use *regret* as a measure of convergence and *information gain* to assess the informativeness of the data samples. The instantaneous regret at iteration t is defined as $r_t = f(\mathbf{x}^*) - f(\mathbf{x}_t)$, and the corresponding cumulative regret after T iterations is $R_T = \sum_{t=1}^{T} r_t$. If we can show that the cumulative regret is *sub-linear* for a given algorithm, then the algorithm converges to a value arbitrarily close to the optimal (Berkenkamp et al., 2019). To measure the reduction in uncertainty about f from observing $\mathbf{y}_{\mathcal{A}}$ for a set of points $\mathcal{A} = \{\mathbf{x}_1, \ldots, \mathbf{x}_T\} \subset \mathcal{X}$, we use information gain, which is defined as the mutual information between f and $\mathbf{y}_{\mathcal{A}}$,

$$\mathcal{I}(\mathbf{y}_{\mathcal{A}}; f) = H(\mathbf{y}_{\mathcal{A}}) - H(\mathbf{y}_{\mathcal{A}} \,|\, f), \tag{3}$$

where $H(\cdot)$ denotes the entropy function. Following Wang & de Freitas (2014), we can define the *maximum information gain* after T iterations as,

$$\gamma_T = \max_{\mathcal{A} \subset \mathcal{X}:|\mathcal{A}|=T} \mathcal{I}(\mathbf{y}_{\mathcal{A}}; f) = \max_{\mathcal{A} \subset \mathcal{X}:|\mathcal{A}|=T} \frac{1}{2} \log |\mathbf{I} + \sigma_\epsilon^{-2} \mathbf{K}_{\mathcal{A};\boldsymbol{\theta}}|, \tag{4}$$

where $\mathbf{I}$ is the identity matrix and $\mathbf{K}_{\mathcal{A};\boldsymbol{\theta}}$ is the kernel matrix evaluated at the observed points. Before presenting our main result, we first make the following assumption:

Assumption 1 (Theorem 5 of (Ghosal & Roy, 2006)). *Let $\mathcal{X} \subset \mathbb{R}^d$ be compact and convex. There exist constants $a, b, L > 0$ such that for any $f(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, k(\mathbf{x}, \mathbf{x}'))$,*

$$\Pr\left\{\sup_{\mathbf{x} \in \mathcal{X}} \left|\frac{\partial f(\mathbf{x})}{\partial x_j}\right| > L\right\} \leq ae^{-(L/b)^2}, \ \ \forall j = 1, \ldots, d. \tag{5}$$

The cumulative regret can be bounded according to the following theorem:

Theorem 1. *Pick $\delta \in (0, 1)$. Under Assumption 1, with probability $1 - \delta$, the cumulative regret of CAKES over T iterations is bounded by,*

$$R_T \leq \sqrt{C_1 T \beta_T \gamma_T} + \frac{\pi^2}{6}, \ \ \forall T \geq 1,$$

where $C_1 = 8/(\log 1 + \sigma_\epsilon^{-2})$ and $\beta_t = 2\log(t^2 2\pi^2/(3\delta)) + 4d\log(dtbr\sqrt{\log(4da/\delta)})$.

The above theorem demonstrates that, with high probability, the cumulative regret of our method is bounded in terms of the maximum information gain γ_T. We can further bound γ_T using the following results from Srinivas et al. (2012):

Theorem 2 (Theorem 5 of (Srinivas et al., 2012)). *Let $\mathcal{X} \subset \mathbb{R}^d$ be compact and convex, $d \in \mathbb{N}$. Assume the kernel function satisfies $k(\mathbf{x}, \mathbf{x}') \leq 1$.*

1. *For the d-dimensional linear kernel: $\gamma_T = \mathcal{O}(d \log T)$.*

2. *For the squared exponential kernel: $\gamma_T = \mathcal{O}((\log T)^{d+1})$.*

3. *For Matérn kernels with $\nu > 1$: $\gamma_T = \mathcal{O}(T^{d(d+1)/(2\nu+d(d+1))}(\log T))$*

Combining these results with Theorem 1, our main result can be summarized as follows:

Theorem 3. *With high probability, the cumulative regret of CAKES is bounded by $\tilde{\mathcal{O}}(\sqrt{dT\gamma_T})$, where $\tilde{\mathcal{O}}$ suppresses the logarithmic factors. Applying the information gain bounds from Theorem 2, this yields sub-linear regret in T for any dimension d.*

We provide the detailed proof of our results in Appendix C. We also provide additional empirical analysis in Section F.

5 RELATED WORK

Kernel design. Traditionally, kernel design relied on visually inspecting patterns in the data and manually combining elementary kernels, such as squared exponential kernel and periodic kernel (Rasmussen & Williams, 2006). However, this approach is highly subjective and requires expert knowledge, making it impractical for complex data patterns. As a result, several methods have been developed to automate the kernel selection process. One such method involved multiple kernel learning techniques, which leverage data to identify the optimal kernel configuration by optimizing a linear or nonlinear combination of elementary kernels (Bach, 2008; Gönen & Alpaydin, 2011). Yet, these methods impose restrictions on the kernel space and require the hyperparameters to be specified in advance. Another line of research focused on designing flexible kernel families that can approximate arbitrary stationary kernels in the frequency domain (Lázaro-Gredilla et al., 2010; Wilson & Adams, 2013; Yin et al., 2020). While these methods can capture a wide range of kernels, they are limited by the stationarity assumption. Other works have also attempted to develop more expressive kernels by integrating GPs with deep neural networks (Damianou & Lawrence, 2013; Wilson et al., 2016). Unfortunately, these methods often require complex inference techniques that are computationally more expensive than traditional kernels. In contrast to these approaches, our method is based on the kernel grammar and in-context learning with pre-trained LLMs, which offers a flexible yet computationally feasible approach.

Surrogate modeling in BO. When using GPs as the surrogate model in BO, the kernel is typically selected *a priori* based on expert knowledge about the problem at hand. Unfortunately, when there is no prior knowledge available, most BO methods simply use default kernels such as squared exponential kernel or Matérn-5/2 kernel (Snoek et al., 2012). While this seems reasonable, it has

Table 1: Average normalized regret (↓) over 20 random seeds for different test functions and methods. The best value is highlighted in **bold** and the second best value is underlined.

Function	Fixed		Adaptive			DGP	EGP	CAKES
	SE	M5	Random	Utility	BIC			
Ackley-2	0.1773	0.1220	0.1358	0.1062	0.1863	0.2510	0.1878	**0.0783**
Ackley-5	0.3185	0.2369	**0.1722**	0.2278	0.3590	0.3110	0.2285	0.1732
Beale	0.3554	0.3522	0.2855	0.4410	0.3571	0.4775	0.3088	**0.2565**
Branin	0.0183	0.0055	0.0227	0.0372	0.0371	0.4810	0.2045	**0.0070**
Dropwave	0.5110	0.5411	0.5460	0.5265	0.5461	0.5560	0.6290	**0.4690**
Eggholder	0.4941	0.3545	0.4015	0.4855	0.5485	0.4535	0.4345	**0.1241**
Griewank-2	0.1196	0.1282	0.1295	0.1310	0.1272	0.1156	0.0935	**0.0267**
Griewank-5	0.0204	0.0223	0.0232	**0.0178**	0.0281	0.0815	0.0478	0.0185
Hartmann	0.0007	0.0019	0.0021	0.0358	0.6800	0.1305	0.1780	**0.0001**
Levy-2	0.1562	0.0418	0.0835	**0.0255**	0.1145	0.1965	0.0765	0.0353
Levy-3	0.1141	0.1422	0.1495	0.0880	0.1125	0.2265	0.0805	**0.0505**
Rastringin-2	0.4325	0.4251	0.5310	0.3455	0.4490	0.5405	0.3869	**0.3341**
Rastringin-4	0.5765	0.5461	0.4815	0.5905	0.5200	0.5340	0.3270	**0.3128**
Rosenbrock	0.1025	0.0898	0.1015	0.1405	0.1475	0.5340	0.6040	**0.0483**
Six-Hump Camel	0.2840	0.1507	0.3455	0.3310	0.3265	0.4940	0.5345	**0.1015**
Mean regret	0.2454	0.2111	0.2271	0.2355	0.3021	0.3585	0.2881	**0.1358**
Median regret	0.1773	0.1422	0.1495	0.1400	0.3265	0.4530	0.2285	**0.0783**

been studied that with poor or overly general choices of the kernel, BO can converge very slowly (Gardner et al., 2017). For this reason, deep GPs (DGPs) have been proposed as a promising alternative to traditional GPs in BO, particularly for capturing non-stationary behaviors (Hebbal et al., 2021). However, DGPs suffer from high computational complexity, which grows with the number of layers. Other prior works have explored adaptively changing the kernel during the optimization process. For example, Ginsbourger et al. (2008) used a discrete mixture of GPs, while Viana et al. (2013) and Roman et al. (2019) maintained multiple GPs with different kernels in parallel. More recently, Lu et al. (2023) proposed using an ensemble of GPs to adaptively select the surrogate model by adjusting the weights on the fly. We extend this line of research by using pre-trained LLMs to automatically generate and refine kernels during the optimization process, enabling a new-fashioned adaptive kernel design.

LLMs as genetic operators. As the model size and amount of training data increase, LLMs exhibit several emergent abilities that improve their performance across diverse tasks (Wei et al., 2022a). One such ability is few-shot learning, where the model can generalize from a few samples without adjusting its parameters (Brown et al., 2020). This generalization is achieved through in-context learning, in which the model identifies the patterns in the samples and extrapolates them via next-token prediction. Inspired by these abilities, recent works have explored the use of LLMs for optimization tasks, notably as genetic operators in evolutionary algorithms. For example, Meyerson et al. (2024) utilized LLMs to propose evolutionary crossovers on tasks such as image and code generation, while Lehman et al. (2023) trained an LLM on computer programs to act as a mutation operator for robot simulations. Chen et al. (2024) combined evolutionary search with soft prompt tuning to evolve neural network architectures using LLMs. To the best of our knowledge, the current work is the first to use LLMs as genetic operators for GP kernel design in BO. Compared to the state-of-the-art, our method can be applied entirely in-context and does not require any fine-tuning.

6 EXPERIMENTS

We evaluate the performance of our proposed method against several baselines across different tasks, including globally optimizing benchmark functions, tuning hyperparameters of machine learning models, and designing photonic chips with optimal configurations.

Figure 2: Average regret (↓) over 5 random seeds for different ML models on all datasets.

Setup. Our experiments are conducted using the software package BoTorch (Balandat et al., 2020), where we use the expected improvement (EI) as the acquisition function. For the LLM, we use OpenAI's `gpt-4o-mini` model, with the hyperparameters `temperature=0.7` and `top_p=0.95`. We give additional insights on the selection of these hyperparameters in Appendix D.1. To facilitate reproducibility, our code is publicly available at `https://github.com/cakes4bo/cakes`.

Baselines. We compare our proposed method against the following baselines:

- **Fixed:** This is the default method in BO, where we fix the kernel throughout the optimization process. We consider the two most commonly-used kernels in BO: squared exponential (SE) and Matérn-5/2 (M5).
- **Adaptive:** This is the adaptive kernel selection method proposed in (Roman et al., 2019). We employ the same six base kernels as in CAKES and use three selection criteria to adaptively change the kernel: *Random*, *Utility*, and *BIC*.
- **Deep GP:** This baseline uses a deep GP (DGP) as the surrogate model, implemeted through a functional composition of stationary GPs (Hebbal et al., 2021).
- **Ensemble GP:** This baseline uses an ensemble of GPs (EGP) to adaptively select the surrogate model (Lu et al., 2023). The kernel dictionary consists of the same six kernels used in CAKES.

In the interest of space, we provide more details of the chosen baselines in Appendix D.2.

6.1 OPTIMIZATION OF BENCHMARK FUNCTIONS

Setup. Our first set of tasks involve optimizing test functions commonly used as benchmark for optimization (Surjanovic & Bingham, 2013). The goal is to find the global minimum of each test function, where the maximum number of function evaluations is limited to 10 times the dimensionality of the function domain, i.e., $T = 10 \times d$. We provide more information about the chosen functions in Appendix E.1.

Evaluation. To evaluate the performance of each method, we consider the normalized regret (Arango et al., 2021):

$$\frac{f(\mathbf{x}_{\text{opt}}) - f(\mathbf{x}_{\text{best}})}{f(\mathbf{x}_{\text{opt}}) - f(\mathbf{x}_{\text{init}})}, \tag{6}$$

where $f(\mathbf{x}_{\text{init}})$ is the best function value among the initial points, $f(\mathbf{x}_{\text{best}})$ is the best value found by the method, and $f(\mathbf{x}_{\text{opt}})$ is the ground truth optimum. This metric is useful as it provides a normalized and task-agnostic measure to compare the optimization performance across different tasks.

Results. Table 1 shows the normalized regret averaged over 20 seeds for different functions and methods. Our results demonstrate that CAKES outperforms the baselines, achieving roughly a 36% improvement in the mean regret and a 44% improvement in the median regret compared to the runner-up method. Notably, CAKES ranks among the top two for all functions and achieves the best performance in 12 out of 15 functions. Our results also reveal that fixed kernels are not universally effective, underscoring the need for more adaptive and problem-specific methods. Specifically, the default kernels in BO like SE and M5, actually underperform on many test functions. Due to space limitations, we include additional results in Appendix G.1.

6.2 Hyperparameter Tuning Task

Setup. We consider the hyperparameter tuning tasks available in the HPOBench package (Eggensperger et al., 2021). We included a total of 60 tasks, comprising 12 OpenML datasets and 5 machine learning (ML) models: logistic regression (LR), support vector machine (SVM), random forest (RF), XGBoost (XGB), and multi-layer perceptron (MLP). We show more details on these tasks in Appendix E.2.

Evaluation. Our goal for each task is to maximize the accuracy of the ML model on the unseen test data. The performance of each method is measured by the simple regret, $f(\mathbf{x}^*) - \max_{1 \leq i \leq t} f(\mathbf{x}_i)$. We executed $T = 25$ trials using five different random seeds, where we ensure that all models share the same initialization for each seed.

Results. Figure 2 shows the regret for all tasks averaged over 5 random seeds. The results demonstrate that CAKES consistently achieves the lowest regret, and therefore the best tuning performance, compared to the other methods across all tasks. It is also worth noting that CAKES excels in the earlier stages of the optimization process, when fewer observations are available. This suggests that CAKES is able to effectively leverage fewer data samples to quickly converge to high-performing configurations. Table 7 further highlights the superior performance of CAKES, which achieves the best average rank at the end of each tuning task. Our results also reveal significant variations in performance for the fixed and adaptive kernel approaches. For instance, the SE kernel performs reasonably well in tuning XGB and MLP models, but struggles with tuning SVM and RF. In contrast, CAKES demonstrates more consistent performance across all tasks, exhibiting less sensitivity to the specific model being optimized. To provide a more comprehensive comparison, we report the individual task results for each ML model and dataset in Appendix G.2. We have also included two additional experiments that involve tuning a controller for the robot pushing task and the lunar lander problem in Appendix G.4 and G.5 respectively.

6.3 Photonic Chip Design

Motivation. To further evaluate our method in real-world optimization tasks, we consider optimizing the design parameters of photonic chips. This task has become a challenging problem in physics and engineering (Li et al., 2023; Zhang et al., 2024), as it is infeasible to try all the combinations (or even a few) of the parameters due to the high cost of the fabrication process. As a result, one has to rely on extensive computer simulations to assess the chip's performance without knowing any gradient information or explicit form of the objective function. This task can be formulated as an inverse design problem, where the goal is to optimize the chip to meet specific performance criteria.

Setup. In this problem, we consider five key indicators for assessing the chip's performance: Q-factor (f_1), wavelength (f_2), lasing area (f_3), power (f_4), and divergence angle (f_5). Based on these

Figure 3: Score ($\uparrow$) and hypervolume ($\uparrow$) of the designed chip over 250 trials.

performance indicators, we can calculate the overall score for a given set of parameters:

$$\alpha f_1 + \beta f_2 + \gamma f_3 + \delta f_4 + \epsilon f_5, \tag{7}$$

where we set $\alpha = \beta = 1$, $\gamma = \delta = 100$, and $\epsilon = 20$ to unify the dimensions between different objectives. We provide more details about the objectives and problem setup in Appendix E.3.

Baselines. For the baselines, we consider two widely-used BO-based methods in the literature. The first is the *Single-Task GP*, which serves as the default method, where a single Gaussian Process (GP) is employed to model each objective independently, typically utilizing the M5 kernel. The second method is the *Additive GP*, which models the overall objective as a sum of independent GPs, with each GP utilizing a squared exponential (SE) kernel. We provide more comparisons with additional baselines from the literature in Appendix G.3. For all methods, we set $T = 250$ with 6 different random initializations and use the expected hypervolume improvement (EHVI) as the acquisition function to identify the Pareto optimal solution (Couckuyt et al., 2014; Yang et al., 2019). We refer the reader to Appendix B.4 for more detailed definitions of the Pareto optimal solution and hypervolume.

Results. Figure 3 shows the score and hypervolume of the designed chip obtained by CAKES against competing baselines. Compared to the baselines, CAKES achieved the highest score and hypervolume, resulting in the best overall chip performance. The superiority of CAKES likely stems from its ability to utilize different kernels tailored to specific objectives, unlike competing methods that rely on a single kernel to model all objectives. Moreover, we can observe that the score of the chip was significantly improved by CAKES in less than 30 trials, which is equivalent to a tenfold speedup in the design cycle compared to the baselines. This could lead to significant reductions in both time and cost needed to design the chips, thus accelerating the research and development (R&D) process. We showcase the individual results on each objective in Appendix G.3.

7   CONCLUSION

We introduced CAKES, a novel kernel design method that integrates LLMs to automate surrogate modeling in BO. By leveraging LLMs as crossover and mutation operators, CAKES adaptively proposes kernels based on the observed data, bridging the gap between kernel selection and domain expertise. Our theoretical analysis demonstrates that CAKES achieves sub-linear regret relative to the budget for any input dimension. Experimental results strongly support our theoretical findings. In benchmark function optimization, CAKES consistently ranked among the top two for all test functions, achieving the best performance in 12 out of 15 cases. In hyperparameter tuning tasks, CAKES obtained the lowest regret across all models, particularly excelling in the early stage of optimization with fewer observations. In the photonic chip design problem, CAKES significantly enhanced chip performance in fewer than 30 trials, resulting in a tenfold speedup of the design cycle compared to baseline methods. We believe this work represents a solid step towards a fully automated BO system that can be used by non-experts on arbitrary objectives.

REFERENCES

Virginia Aglietti, Ira Ktena, Jessica Schrouff, Eleni Sgouritsa, Francisco J. R. Ruiz, Alan Malek, Alexis Bellot, and Silvia Chiappa. FunBO: Discovering acquisition functions for Bayesian optimization with FunSearch. *arXiv preprint arXiv:2406.04824*, 2024.

Sebastian Ament, Samuel Daulton, David Eriksson, Maximilian Balandat, and Eytan Bakshy. Unexpected improvements to expected improvement for Bayesian optimization. *Advances in Neural Information Processing Systems*, 36, 2023.

Sebastian P Arango, Hadi S Jomaa, Martin Wistuba, and Josif Grabocka. HPO-B: A large-scale reproducible benchmark for black-box HPO based on OpenML. In *Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

Francis Bach. Exploring large feature spaces with hierarchical multiple kernel learning. *arXiv preprint arXiv:0809.1493*, 2008.

Francis Bach. *Learning theory from first principles*. MIT press, 2024.

Maximilian Balandat, Brian Karrer, Daniel Jiang, Samuel Daulton, Ben Letham, Andrew G Wilson, and Eytan Bakshy. BoTorch: A framework for efficient Monte-Carlo Bayesian optimization. *Advances in Neural Information Processing Systems*, 33, 2020.

Felix Berkenkamp, Angela P Schoellig, and Andreas Krause. No-regret Bayesian optimization with unknown hyperparameters. *Journal of Machine Learning Research*, 20(50):1–24, 2019.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in Neural Information Processing Systems*, 33, 2020.

Roberto Calandra, André Seyfarth, Jan Peters, and Marc Peter Deisenroth. Bayesian optimization for learning gaits under uncertainty. *Annals of Mathematics and Artificial Intelligence*, 76(1): 5–23, 2016. ISSN 1573-7470.

Angelica Chen, David Dohan, and David So. EvoPrompting: Language models for code-level neural architecture search. *Advances in Neural Information Processing Systems*, 36, 2024.

Lih-Ren Chen, Kuo-Bin Hong, Kuan-Chih Huang, Hsu-Tung Yen, and Tien-Chang Lu. Improvement of output efficiency of p-face up photonic-crystal surface-emitting lasers. *Optics Express*, 29(7):11293–11300, 2021.

Ivo Couckuyt, Dirk Deschrijver, and Tom Dhaene. Fast calculation of multiobjective probability of improvement and expected improvement criteria for Pareto optimization. *Journal of Global Optimization*, 60:575–594, 2014.

Andreas Damianou and Neil D. Lawrence. Deep Gaussian processes. In *International Conference on Artificial Intelligence and Statistics*, volume 31, pp. 207–215, 2013.

Samuel Daulton, Maximilian Balandat, and Eytan Bakshy. Differentiable expected hypervolume improvement for parallel multi-objective Bayesian optimization. *Advances in Neural Information Processing Systems*, 33:9851–9864, 2020.

David Duvenaud, James Lloyd, Roger Grosse, Joshua Tenenbaum, and Ghahramani Zoubin. Structure discovery in nonparametric regression through compositional kernel search. In *International Conference on Machine Learning*, pp. 1166–1174. PMLR, 2013.

Katharina Eggensperger, Matthias Feurer, Frank Hutter, James Bergstra, Jasper Snoek, Holger Hoos, Kevin Leyton-Brown, et al. Towards an empirical foundation for assessing Bayesian optimization of hyperparameters. In *NIPS Workshop on Bayesian Optimization in Theory and Practice*, volume 10, pp. 1–5, 2013.

Katharina Eggensperger, Philipp Müller, Neeratyoy Mallik, Matthias Feurer, Rene Sass, Aaron Klein, Noor Awad, Marius Lindauer, and Frank Hutter. HPOBench: A collection of reproducible multi-fidelity benchmark problems for HPO. In *Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

Jacob Gardner, Chuan Guo, Kilian Weinberger, Roman Garnett, and Roger Grosse. Discovering and exploiting additive structure for Bayesian optimization. In *Artificial Intelligence and Statistics*, pp. 1311–1319. PMLR, 2017.

Roman Garnett. *Bayesian Optimization*. Cambridge University Press, 2023.

S Ghosal and A Roy. Posterior consistency of Gaussian process prior for nonparametric binary regression. *Annals of Statistics*, 34(5):2413–2429, 2006.

David Ginsbourger, Céline Helbert, and Laurent Carraro. Discrete mixtures of kernels for kriging-based optimization. *Quality and Reliability Engineering International*, 24(6):681–691, 2008.

Mehmet Gönen and Ethem Alpaydin. Multiple kernel learning algorithms. *Journal of Machine Learning Research*, 12(64):2211–2268, 2011.

Chi Han, Ziqi Wang, Han Zhao, and Heng Ji. Explaining emergent in-context learning as kernel regression. *arXiv preprint arXiv:2305.12766*, 2023.

Ali Hebbal, Loïc Brevault, Mathieu Balesdent, El-Ghazali Talbi, and Nouredine Melab. Bayesian optimization using deep Gaussian processes with applications to aerospace system design. *Optimization and Engineering*, 22:321–361, 2021.

John H Holland. *Adaptation in natural and artificial systems: An introductory analysis with applications to biology, control, and artificial intelligence*. MIT press, 1992.

Ming-Yang Hsu, Gray Lin, and Chien-Hung Pan. Electrically injected 1.3-μm quantum-dot photonic-crystal surface-emitting lasers. *Optics Express*, 25(26):32697–32704, 2017.

Donald R. Jones, Matthias Schonlau, and William J. Welch. Efficient global optimization of expensive black-box functions. *Journal of Global Optimization*, 13(4):455–492, 1998.

Kirthevasan Kandasamy, Jeff Schneider, and Barnabás Póczos. High dimensional Bayesian optimisation and bandits via additive models. In *International conference on machine learning*, pp. 295–304. PMLR, 2015.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. *Advances in Neural Information Processing Systems*, 35, 2022.

Ksenia Korovina, Sailun Xu, Kirthevasan Kandasamy, Willie Neiswanger, Barnabas Poczos, Jeff Schneider, and Eric P. Xing. ChemBO: Bayesian optimization of small organic molecules with synthesizable recommendations. *arXiv preprint arXiv:1908.01425*, 2019.

Miguel Lázaro-Gredilla, Joaquin Quinonero-Candela, Carl Edward Rasmussen, and Aníbal R Figueiras-Vidal. Sparse spectrum Gaussian process regression. *The Journal of Machine Learning Research*, 11:1865–1881, 2010.

Joel Lehman, Jonathan Gordon, Shawn Jain, Kamal Ndousse, Cathy Yeh, and Kenneth O Stanley. Evolution through large models. In *Handbook of Evolutionary Machine Learning*, pp. 331–366. Springer, 2023.

Renjie Li, Ceyao Zhang, Wentao Xie, Yuanhao Gong, Feilong Ding, Hui Dai, Zihan Chen, Feng Yin, and Zhaoyu Zhang. Deep reinforcement learning empowers automated inverse design and optimization of photonic crystals for nanoscale laser cavities. *Nanophotonics*, 12(2):319–334, 2023.

Xi Lin, Zhiyuan Yang, and Qingfu Zhang. Pareto set learning for neural multi-objective combinatorial optimization. In *International Conference on Learning Representations*, 2022.

Tennison Liu, Nicolás Astorga, Nabeel Seedat, and Mihaela van der Schaar. Large language models to enhance Bayesian optimization. In *International Conference on Learning Representations*, 2024.

Qin Lu, Konstantinos D Polyzos, Bingcong Li, and Georgios B Giannakis. Surrogate modeling for Bayesian optimization beyond a single Gaussian process. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(9):11283–11296, 2023.

Gustavo Malkomes and Roman Garnett. Automating Bayesian optimization with Bayesian optimization. *Advances in Neural Information Processing Systems*, 31, 2018.

Ruben Martinez-Cantin. Bayesian optimization with adaptive kernels for robot control. In *IEEE International Conference on Robotics and Automation*, pp. 3350–3356, 2017.

Elliot Meyerson, Mark J. Nelson, Herbie Bradley, Adam Gaier, Arash Moradi, Amy K. Hoover, and Joel Lehman. Language model crossover: Variation through few-shot prompting. *arXiv preprint arXiv:2302.12170*, 2024.

Kevin P. Murphy. *Probabilistic Machine Learning: An introduction*. MIT Press, 2022.

Dai Ohnishi, Takayuki Okano, Masahiro Imada, and Susumu Noda. Room temperature continuous wave operation of a surface-emitting two-dimensional photonic crystal diode laser. *Optics Express*, 12(8):1562–1568, 2004.

Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian processes for machine learning*. MIT Press, Cambridge, Mass, 2006.

Ibai Roman, Roberto Santana, Alexander Mendiburu, and Jose A. Lozano. An experimental study in adaptive kernel selection for Bayesian optimization. *IEEE Access*, 7:184294–184302, 2019. doi: 10.1109/ACCESS.2019.2960498.

Hugh Salimbeni and Marc Deisenroth. Doubly stochastic variational inference for deep Gaussian processes. *Advances in Neural Information Processing Systems*, 30, 2017.

Gideon Schwarz. Estimating the dimension of a model. *The Annals of Statistics*, 6(2):461–464, 1978.

Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando de Freitas. Taking the human out of the loop: A review of Bayesian optimization. *IEEE*, 104(1):148–175, 2016.

Alex J. Smola and Bernhard Schölkopf. *Learning with kernels*, volume 4. Citeseer, 1998.

Jasper Snoek, Hugo Larochelle, and Ryan P. Adams. Practical Bayesian optimization of machine learning algorithms. *arXiv preprint arXiv:1206.2944*, 2012.

Niranjan Srinivas, Andreas Krause, Sham M Kakade, and Matthias W Seeger. Information-theoretic regret bounds for Gaussian process optimization in the bandit setting. *IEEE Transactions on Information Theory*, 58(5):3250–3265, 2012.

Sonja Surjanovic and Derek Bingham. Virtual library of simulation experiments: Test functions and datasets. URL `http://www.sfu.ca/~ssurjano`, 2013.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.

Austin Tripp and José Miguel Hernández-Lobato. Diagnosing and fixing common problems in Bayesian optimization for molecule design. *arXiv preprint arXiv:2406.07709*, 2024.

Felipe AC Viana, Raphael T Haftka, and Layne T Watson. Efficient global optimization algorithm assisted by multiple surrogate techniques. *Journal of Global Optimization*, 56:669–689, 2013.

Xilu Wang, Yaochu Jin, Sebastian Schmitt, and Markus Olhofer. Recent advances in Bayesian optimization. *ACM Computing Surveys*, 55(13s), 2023.

Zi Wang, Clement Gehring, Pushmeet Kohli, and Stefanie Jegelka. Batched large-scale Bayesian optimization in high-dimensional spaces. In *International Conference on Artificial Intelligence and Statistics*, pp. 745–754. PMLR, 2018.

Ziyu Wang and Nando de Freitas. Theoretical analysis of Bayesian optimisation with unknown Gaussian process hyper-parameters. *arXiv preprint arXiv:1406.7758*, 2014.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682*, 2022a.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837, 2022b.

Andrew Gordon Wilson and Ryan Prescott Adams. Gaussian process kernels for pattern discovery and extrapolation. In *International Conference on Machine Learning*, pp. III–1067–III–1075, 2013.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P. Xing. Deep kernel learning. In *International Conference on Artificial Intelligence and Statistics*, volume 51, pp. 370–378, 2016.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An explanation of in-context learning as implicit Bayesian inference. *arXiv preprint arXiv:2111.02080*, 2022.

Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V Le, Denny Zhou, and Xinyun Chen. Large language models as optimizers. In *International Conference on Learning Representations*, 2024.

Kaifeng Yang, Michael Emmerich, André Deutz, and Thomas Bäck. Multi-objective Bayesian global optimization using expected hypervolume improvement gradient. *Swarm and evolutionary computation*, 44:945–956, 2019.

Feng Yin, Lishuo Pan, Tianshi Chen, Sergios Theodoridis, Zhi-Quan Tom Luo, and Abdelhak M. Zoubir. Linear multiple low-rank kernel based stationary Gaussian processes regression for time series. *IEEE Transactions on Signal Processing*, 68:5260–5275, 2020. ISSN 1941-0476.

Ceyao Zhang, Renjie Li, Cheng Zhang, Zhaoyu Zhang, and Feng Yin. Inverse design of photonic crystal surface emitting lasers is a sequence modeling problem. *arXiv preprint arXiv:2403.05149*, 2024.

Yongchao Zhou, Andrei Ioan Muresanu, Ziwen Han, Keiran Paster, Silviu Pitis, Harris Chan, and Jimmy Ba. Large language models are human-level prompt engineers. In *International Conference on Learning Representations*, 2023.

A ETHICS AND REPRODUCIBILITY STATEMENTS

Ethics. In this work, we follow the recommendations from Azure OpenAI service when using GPT models, where we ensure via the agreement that sensitive data is not sent for human review or stored, thereby respecting the guidelines given by the dataset providers.

Reproducibility. Experimental results are shown in Section 6 with further details of the implementations, baselines, and benchmarks, included in Appendix D and Appendix E. Additional results are also given in Appendix G. We provide the code to reproduce our results at `https://github.com/cakes4bo/cakes`.

B MATHEMATICAL DETAILS

B.1 BAYESIAN OPTIMIZATION WITH GAUSSIAN PROCESSES

A Gaussian process (GP) describes a collection of random variables, any finite number of which have a joint Gaussian distribution (Rasmussen & Williams, 2006). Mathematically, a GP can be expressed as, $\mathcal{GP}(m(\mathbf{x}), k_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta}))$, where $m(\mathbf{x})$ is the mean function and $k_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{x}'; \boldsymbol{\theta})$ is the covariance (kernel) function parameterized by some hyperparameters $\boldsymbol{\theta}$. Given any finite collection of inputs $\mathbf{X} = \mathbf{x}_{1:t}$, the outputs are jointly Gaussian,

$$f(\mathbf{X}) \sim \mathcal{N}(\boldsymbol{m}_{\mathbf{X}}, \mathbf{K}(\mathbf{X}, \mathbf{X}; \boldsymbol{\theta})), \tag{8}$$

where $\boldsymbol{m}_{\mathbf{X}} = m(\mathbf{X}) \in \mathbb{R}^t$ is the mean function vector evaluated at $\mathbf{X}$, often assumed to be $\mathbf{0}$ in practice, and $\mathbf{K}(\mathbf{X}, \mathbf{X}; \boldsymbol{\theta}) \in \mathbb{R}^{t \times t}$ is the covariance matrix with entries $[\mathbf{K}(\mathbf{X}, \mathbf{X}; \boldsymbol{\theta})]_{i,j} = k_{\boldsymbol{\theta}}(\mathbf{x}_i, \mathbf{x}_j)$. We assume that the evaluations of f at any point $\mathbf{x}_t$ are corrupted by a σ-sub-Gaussian noise,

$$y_t = f(\mathbf{x}_t) + \epsilon_t, \tag{9}$$

where $\epsilon_t \sim \mathcal{N}(0, \sigma_\epsilon^2)$. Given the observed data $\mathcal{D}_t = \{\mathbf{X}, \mathbf{y}\}$, where $\mathbf{y} = \mathbf{y}_{1:t}$, the joint Gaussian distribution of the observed data and an arbitrary query point $\mathbf{x}$ is:

$$\begin{bmatrix} \mathbf{y} \\ f(\mathbf{x}) \end{bmatrix} \sim \mathcal{N}\left(\mathbf{0}, \begin{bmatrix} \mathbf{K}_{t;\boldsymbol{\theta}} + \sigma_\epsilon^2 \mathbf{I} & \mathbf{k}_{t;\boldsymbol{\theta}}(\mathbf{x}) \\ \mathbf{k}_{t;\boldsymbol{\theta}}^\top(\mathbf{x}) & k_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{x}) \end{bmatrix}\right), \tag{10}$$

where $\mathbf{K}_{t;\boldsymbol{\theta}} = \mathbf{K}(\mathbf{X}, \mathbf{X}; \boldsymbol{\theta})$ and $\mathbf{k}_{t;\boldsymbol{\theta}}(\mathbf{x}) = \mathbf{k}_{\boldsymbol{\theta}}(\mathbf{X}, \mathbf{x})$. It follows that, the posterior distribution of any query point $\mathbf{x}$ is marginally Gaussian,

$$f(\mathbf{x})|\mathcal{D}_t; \boldsymbol{\theta} \sim \mathcal{N}(\mu_t(\mathbf{x}; \boldsymbol{\theta}), \sigma_t^2(\mathbf{x}; \boldsymbol{\theta})), \tag{11}$$

where

$$\mu_t(\mathbf{x}; \boldsymbol{\theta}) = \mathbb{E}[f(\mathbf{x})|\mathcal{D}_t] = \mathbf{k}_{t,\boldsymbol{\theta}}^\top(\mathbf{x})(\mathbf{K}_{t;\boldsymbol{\theta}} + \sigma_\epsilon^2 \mathbf{I})^{-1} \mathbf{y}, \tag{12a}$$

$$\sigma_t^2(\mathbf{x}; \boldsymbol{\theta}) = \mathbb{E}[f(\mathbf{x})f(\mathbf{x})|\mathcal{D}_t] = \mathbf{k}_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{x}) - \mathbf{k}_{t,\boldsymbol{\theta}}^\top(\mathbf{x})(\mathbf{K}_{t;\boldsymbol{\theta}} + \sigma_\epsilon^2 \mathbf{I})^{-1} \mathbf{k}_{t,\boldsymbol{\theta}}(\mathbf{x}). \tag{12b}$$

Based on the posterior distribution, the acquisition function must use its statistics to trade-off exploitation (where $\mu_t(\mathbf{x}; \boldsymbol{\theta})$ is high) and exploration (where $\sigma_t^2(\mathbf{x}; \boldsymbol{\theta})$ is high) effectively. Among the various acquisition functions proposed, expected improvement (EI) remains the default choice in many BO applications (Snoek et al., 2012). Let us define $\mu_{\boldsymbol{\theta}}^+ = \max_{\mathbf{x} \in \mathcal{X}} \mu_t(\mathbf{x}; \boldsymbol{\theta})$ as the best mean value. The EI acquisition function can then be expressed in closed form as:

$$\alpha(\mathbf{x}; \mathcal{D}_t) = \mathbb{E}[\max\{0, f(\mathbf{x}) - \mu_{\boldsymbol{\theta}}^+\}] = \sigma_t(\mathbf{x}; \boldsymbol{\theta})[u\Phi(u) + \phi(u)], \tag{13}$$

where $u = (\mu_t(\mathbf{x}; \boldsymbol{\theta}) - \mu_{\boldsymbol{\theta}}^+)/\sigma_t(\mathbf{x}; \boldsymbol{\theta})$, and $\phi(\cdot)$ and $\Phi(\cdot)$ are the standard normal density and cumulative distribution functions, respectively.

B.2 SUB-GAUSSIAN NOISE

We say ϵ is σ-sub-Gaussian if there exists $\sigma \geq 0$ such that,

$$\mathbb{E}[\exp(\rho\epsilon)] \leq \exp\left(\frac{\rho^2 \sigma^2}{2}\right), \quad \forall \rho \in \mathbb{R}. \tag{14}$$

It is easy to show that if ϵ is σ-sub-Gaussian, then $\mathbb{E}[\epsilon] = 0$ and $\text{Var}[\epsilon] \leq \sigma^2$. Examples of sub-Gaussian variables include, zero-mean Gaussian random variables with variance σ^2, symmetric Bernoulli random variables, and symmetric uniform distributions (Bach, 2024).

B.3 MODEL SELECTION

We conduct model selection over a discrete, infinite space of kernels $\mathcal{K} = \{k_1, k_2, \ldots\}$. As each kernel comes with its own hyperparameters, we are actually dealing with a space of kernel families. Thus, when referring to a kernel k, we actually associate it with its whole family over hyperparameters $\{k_{\boldsymbol{\theta}} \mid \boldsymbol{\theta} \in \Theta\}$. Given some model selection criteria $h : \mathcal{K} \to \mathbb{R}$, our goal is to identify the optimal kernel,

$$k^* = \arg\max_{k \in \mathcal{K}} h(k \mid \mathcal{D}). \tag{15}$$

A commonly-used criterion for probabilistic models, such as GPs, is the marginal log-likelihood (Murphy, 2022),

$$h(k \mid \mathcal{D}) = \log p(\mathbf{y} \mid \mathbf{X}, k) = \log \int p(\mathbf{y} \mid \mathbf{X}, \boldsymbol{\theta}, k) p(\boldsymbol{\theta}) d\boldsymbol{\theta}. \tag{16}$$

Unfortunately, the above likelihood is generally intractable for GPs (Rasmussen & Williams, 2006), so we resort to the Laplace approximation,

$$\log p(\mathbf{y} \mid \mathbf{X}, k) \approx \log p(\mathbf{y} \mid \mathbf{X}, \hat{\boldsymbol{\theta}}, k) + \log p(\hat{\boldsymbol{\theta}}) - \frac{1}{2} \log \det \boldsymbol{\Sigma}^{-1} + \frac{d_{\boldsymbol{\theta}}}{2} \log 2\pi \tag{17}$$

where $\hat{\boldsymbol{\theta}}$ denotes the maximum a posteriori (MAP) estimate of the hyperparameters with $d_{\boldsymbol{\theta}}$ being its dimension. The term $\boldsymbol{\Sigma}^{-1} = -\nabla^2 \log p(\boldsymbol{\theta} \mid \mathcal{D}, k)|_{\boldsymbol{\theta}=\hat{\boldsymbol{\theta}}}$ represents the Hessian matrix evaluated at the MAP estimate. Note that Eq. (17) can be interpreted as rewarding model fit while penalizing model complexity. In our experiments, we use the BIC (Schwarz, 1978), which was also employed by Duvenaud et al. (2013) and can be viewed as an approximation of the Laplace approximation.

B.4 MULTI-OBJECTIVE OPTIMIZATION

Setup. In our photonic chip inverse design problem, the solutions need to satisfy multiple, potentially competing objectives simultaneously. Multi-objective optimization aims to find the *Pareto optimal solution*, where no objective can be improved without degrading another (Lin et al., 2022). A simplistic approach to jointly optimize the given objectives $\{f_i(\cdot)\}_{i=1}^{M}$ is to consider an aggregate objective, such as the weighted sum of all individual objectives:

$$\mathbf{x}^* = \arg\max_{\mathbf{x} \in \mathcal{X}} \sum_i w_i f_i(\mathbf{x}) \tag{18}$$

where w_i is the weight of the i-th objective, considered as a hyperparameter. However, determining appropriate weights for each objective function is a nontrivial task.

Pareto optimal solution. A more rigorous approach to multi-objective optimization involves introducing partial order and considering solutions from the Pareto frontier (Yang et al., 2019). In this context, partial order is defined by comparing all objectives $\{f_i(\cdot)\}_{i=1}^{M}$ for the given solutions. We say a solution $\mathbf{x}'$ surpasses $\mathbf{x}$ if every objective evaluated on $\mathbf{x}'$ is greater than or equal to the same objective evaluated on $\mathbf{x}$ (assuming maximization of objectives):

$$\mathbf{x}' \succeq \mathbf{x} \Leftrightarrow \forall i, f_i(\mathbf{x}') \geq f_i(\mathbf{x}) \tag{19}$$

For a given set of solutions $S = \{\mathbf{x}_j\}_{j=1}^{m}$, the *Pareto frontier* $P(S)$ is defined as the set of non-dominated solutions. For every solution $\mathbf{x} \in P(S)$, there is no other solution in S surpassing $\mathbf{x}$:

$$P(S) = \{\mathbf{x} \in S : \{\mathbf{x}' \in S : \mathbf{x}' \succeq \mathbf{x}, \mathbf{x}' \neq \mathbf{x}\} = \emptyset\} \tag{20}$$

Hypervolume. Assuming bounded objectives, two Pareto frontiers can be compared by evaluating their hypervolume (Couckuyt et al., 2014):

$$\text{Volume}(P(S)) = \text{Volume}\left(\bigcup_{\mathbf{x} \in P(S)} H(\mathbf{x})\right) \tag{21}$$

where $H(\mathbf{x})$ is the hyperrectangle associated with the objectives evaluated on solution $\mathbf{x}$, and $\text{Volume}(\cdot)$ computes the Euclidean volume of the input set. In our experiments, we use EHVI as the acquisition function and adopt the implementation outlined in (Daulton et al., 2020) for efficient computation of EHVI.

C PROOF OF RESULTS

C.1 PROOF OF THEOREM 1

Key lemmas. In this section, we provide the detailed proof of Theorem 1. We first observe that we have confidence on all the decisions chosen according to the following lemma:

Lemma 1 (Lemma 5.5 of (Srinivas et al., 2012)). *Pick $\delta \in (0,1)$ and set $\beta_t = 2\log(\pi_t/\delta)$, where $\sum_{t \geq 1} \pi_t^{-1} = 1, \pi_t > 0$. Then,*

$$|f(\mathbf{x}_t) - \mu_{t-1}(\mathbf{x}_t)| \leq \beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t), \ \ \forall t \geq 1,$$

holds with probability $\geq 1 - \delta$.

Proof. Fix $t \geq 1$ and $\mathbf{x} \in \mathcal{X}$. Conditioned on $\mathbf{y}_{t-1} = [y_1, y_2, \ldots, y_{t-1}]^\top$, $\mathbf{x}_1, \ldots, \mathbf{x}_{t-1}$ are deterministic and $f(\mathbf{x}) \sim \mathcal{N}(\mu_{t-1}(\mathbf{x}), \sigma_{t-1}^2(\mathbf{x}))$. If $r \sim \mathcal{N}(0,1)$, then

$$\Pr\{r > c\} = e^{-c^2/2}(2\pi)^{-1/2}\int e^{-(r-c)^2/2 - c(r-c)} \leq e^{-c^2/2}\Pr\{r > 0\} = \frac{1}{2}e^{-c^2/2}.$$

Let $r = (f(\mathbf{x}) - \mu_{t-1}(\mathbf{x}))/\sigma_{t-1}(\mathbf{x})$, then $\Pr\{|f(\mathbf{x}) - \mu_{t-1}(\mathbf{x})| > \beta_t^{1/2}\sigma_{t-1}(\mathbf{x})\} \leq e^{-\beta_t/2}$. By using $e^{-\beta_t/2} = \delta/\pi_t$ and applying the union bound for $t \in \mathbb{N}$, the statement holds. $\square$

For the sake of analysis, we consider a set of discretizations $\mathcal{X}_t \subset \mathcal{X}$, where $\mathcal{X}_t$ will be used at iteration t in the analysis. The following lemma provides a confidence bound for these subsets.

Lemma 2 (Lemma 5.6 of (Srinivas et al., 2012)). *Pick $\delta \in (0,1)$ and set $\beta_t = 2\log(|\mathcal{X}_t|\pi_t/\delta)$, where $\sum_{t \geq 1} \pi_t^{-1} = 1, \pi_t > 0$. Then,*

$$|f(\mathbf{x}_t) - \mu_{t-1}(\mathbf{x}_t)| \leq \beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t), \ \ \forall \mathbf{x} \in \mathcal{X}_t, \forall t \geq 1,$$

holds with probability $\geq 1 - \delta$.

Proof. The proof is similar to that of Lemma 1, except now we use $\mathcal{X}_t$ at each iteration. $\square$

Now, by Assumption 1 and the union bound, we have

$$\Pr\left\{\left|\frac{\partial f}{\partial x_j}\right| < L\right\} \geq 1 - dae^{-L^2/b^2}, \ \ \forall \mathbf{x} \in \mathcal{X}, \forall j, \tag{22}$$

which implies that, with probability greater than $1 - dae^{-L^2/b^2}$,

$$|f(\mathbf{x}) - f(\mathbf{x}')| \leq L\|\mathbf{x} - \mathbf{x}'\|_1, \ \ \forall \mathbf{x} \in \mathcal{X}. \tag{23}$$

This allows us to obtain confidence on $\mathbf{x}^*$ as follows. Let us choose a discretization $\mathcal{X}_t$ of size $(\tau_t)^d$ such that for all $\mathbf{x} \in \mathcal{X}_t$,

$$\|\mathbf{x} - [\mathbf{x}]_t\|_1 \leq rd/\tau_t, \tag{24}$$

where $[\mathbf{x}]_t$ is the closest point in $\mathcal{X}_t$ to $\mathbf{x}$.

Lemma 3 (Lemma 5.7 of (Srinivas et al., 2012)). *Pick $\delta \in (0,1)$ and set $\beta_t = 2\log(2\pi_t/\beta_t) + 4d\log(dtbr\sqrt{\log(2da/\delta)})$, where $\sum_{t \geq 1} \pi_t^{-1} = 1, \pi_t > 0$. Let $\tau_t = dt^2br\sqrt{\log(2da/\delta)}$, then*

$$|f(\mathbf{x}^*) - \mu_{t-1}([\mathbf{x}^*]_t)| \leq \beta_t^{1/2}\sigma_{t-1}([\mathbf{x}^*]_t) + \frac{1}{t^2}, \ \ \forall t \geq 1,$$

holds with probability $\geq 1 - \delta$.

Proof. Using Eq. (23), we have,

$$|f(\mathbf{x}) - f(\mathbf{x}')| \leq b\sqrt{\log(2da/\delta)}\|\mathbf{x} - \mathbf{x}'\|_1, \ \ \forall \mathbf{x} \in \mathcal{X}.$$

with probability greater than $1 - \delta/2$. It follows that,

$$|f(\mathbf{x}) - f([\mathbf{x}]_t)| \leq rdb\sqrt{\log(2da/\delta)}/\tau_t, \ \ \forall \mathbf{x} \in \mathcal{X}.$$

By choosing $\tau_t = dt^2 br\sqrt{\log(2da/\delta)}$, we have

$$|f(\mathbf{x}) - f([\mathbf{x}]_t)| \leq \frac{1}{t^2},$$

which implies that $|\mathcal{X}_t| = (dt^2 br\sqrt{\log(2da/\delta)})^d$. Using $\delta/2$ in Lemma 2, we can apply the confidence bound to $[\mathbf{x}^*]_t$ to obtain the result. □

Next, we would like to bound the regret using the following lemma:

Lemma 4 (Lemma 5.8 of (Srinivas et al., 2012)). *Pick* $\delta \in (0, 1)$ *and set* $\beta_t = 2\log(4\pi_t/\beta_t) + 4d\log(dtbr\sqrt{\log(4da/\delta)})$, *where* $\sum_{t \geq 1} \pi_t^{-1} = 1, \pi_t > 0$. *Then,*

$$r_t \leq 2\beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) + \frac{1}{t^2}, \ \ \forall t \in \mathbb{N},$$

holds with probability $\geq 1 - \delta$.

Proof. We use $\delta/2$ in Lemma 1 and Lemma 2 such that the events hold with probability greater than $1 - \delta$. By using the definition of $\mathbf{x}_t$,

$$\mu_{t-1}(\mathbf{x}_t) + \beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) \geq \mu_{t-1}([\mathbf{x}^*]_t) + \beta_t^{1/2}\sigma_{t-1}([\mathbf{x}^*]_t).$$

By Lemma 3, we further have $\mu_{t-1}([\mathbf{x}^*]_t) + \beta_t^{1/2}\sigma_{t-1}([\mathbf{x}^*]_t) + \frac{1}{t^2} \geq f(\mathbf{x}^*)$, which implies

$$\mu_{t-1}(\mathbf{x}_t) + \beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) \geq f(\mathbf{x}^*) - \frac{1}{t^2}.$$

Therefore,

$$r_t = f(\mathbf{x}^*) - f(\mathbf{x}_t) \leq \mu_{t-1}(\mathbf{x}_t) + \beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) + \frac{1}{t^2} - f(\mathbf{x}_t) \leq 2\beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) + \frac{1}{t^2}.$$

□

Proof of Theorem 1. Now, we are ready to complete the proof of Theorem 1. Since β_t is non-decreasing,

$$4\beta_t\sigma_{t-1}^2(\mathbf{x}_t) \leq 4\beta_T\sigma_\epsilon^2(\sigma_\epsilon^{-2}\sigma_{t-1}^2(\mathbf{x}_t)) \leq 4\beta_T\sigma_\epsilon^2 C_2\log(1 + \sigma_\epsilon^{-2}\sigma_{t-1}^2(\mathbf{x}_t)),$$

with $C_2 = \sigma_\epsilon^2/\log(1 + \sigma_\epsilon^{-2}) \geq 1$, since $s^2 \leq C_2\log(1 + s^2)$ for $s \in [0, \sigma_\epsilon^{-2}]$ and $\sigma_\epsilon^{-2}\sigma_{t-1}^2(\mathbf{x}_t) \leq \sigma_\epsilon^{-2}k(\mathbf{x}_t, \mathbf{x}_t) \leq \sigma_\epsilon^{-2}$. By Lemma 5.3 of (Srinivas et al., 2012), for a finite set of observed points $\mathcal{A} = \{\mathbf{x}_1, \ldots, \mathbf{x}_T\} \subset \mathcal{X}$, the information gain can be expressed as,

$$\mathcal{I}(\mathbf{y}_\mathcal{A}; f) = \frac{1}{2}\sum_{t=1}^{T}\log\left(1 + \sigma^{-2}\sigma_{t-1}^2(\mathbf{x}_t)\right). \tag{25}$$

Thus, by substituting the above expression and setting $C_1 = 8\sigma_\epsilon^2 C_2$, we can obtain

$$\sum_{t=1}^{T} 4\beta_t\sigma_{t-1}^2(\mathbf{x}_t) \leq C_1\beta_T\mathcal{I}(\mathbf{y}_\mathcal{A}; f) \leq C_1\beta_T\gamma_T, \ \ \forall T \geq 1, \tag{26}$$

with probability greater than $1 - \delta$. By Cauchy-Schwarz,

$$\sum_{t=1}^{T} 2\beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) \leq \sqrt{C_1 T\beta_T\gamma_T}, \ \ \forall T \geq 1. \tag{27}$$

Finally, by choosing $\pi_t = \pi^2 t^2/6$ in Lemma 4, we have

$$R_T = \sum_{t=1}^{T} r_t \leq \sum_{t=1}^{T} 2\beta_t^{1/2}\sigma_{t-1}(\mathbf{x}_t) + \sum_{t=1}^{T} \frac{1}{t^2} \leq \sqrt{C_1 T\beta_T\gamma_T} + \frac{\pi^2}{6}, \ \ \forall T \geq 1.$$

This completes the proof of Theorem 1.

C.2 PROOF OF THEOREM 3

In this section, we provide the proof of our main result, which is summarized in Theorem 3. From Theorem 1, we have that with probability at least $1 - \delta$,

$$R_T \leq \sqrt{C_1 T \beta_T \gamma_T} + \frac{\pi^2}{6},$$

where $C_1 = 8/(\log(1 + \sigma_\epsilon^{-2}))$ and

$$\beta_T = 2 \log\left(\frac{T^2 2\pi^2}{3\delta}\right) + 4d \log\left(dtbr\sqrt{\log\left(\frac{4da}{\delta}\right)}\right).$$

Since β_T involves logarithmic terms and constants, we can express it using the $\tilde{\mathcal{O}}$ notation as $\beta_T = \tilde{\mathcal{O}}(d)$. Similarly, C_1 is a constant that can be absorbed into the $\tilde{\mathcal{O}}$ notation. Therefore, the cumulative regret bound simplifies to

$$R_T \leq \tilde{\mathcal{O}}\left(\sqrt{Td\gamma_T}\right).$$

We now combine this result with the bounds on γ_T from Theorem 2 for different kernels used in this work:

1. **Linear Kernel:** Substituting $\gamma_T = \mathcal{O}(d \log T)$ into the regret bound:
$$R_T \leq \tilde{\mathcal{O}}\left(\sqrt{Td \cdot d \log T}\right) = \tilde{\mathcal{O}}\left(d\sqrt{T \log T}\right).$$

2. **Squared Exponential Kernel:** Substituting $\gamma_T = \mathcal{O}((\log T)^{d+1})$ into the regret bound:
$$R_T \leq \tilde{\mathcal{O}}\left(\sqrt{Td(\log T)^{d+1}}\right) = \tilde{\mathcal{O}}\left(\sqrt{T(\log T)^{d+1}}\right).$$

3. **Matérn Kernel with $\nu > 1$:** Substituting $\gamma_T = \mathcal{O}\left(T^{\frac{d(d+1)}{2\nu+d(d+1)}} \log T\right)$ into the regret bound:
$$R_T \leq \tilde{\mathcal{O}}\left(\sqrt{Td \cdot T^{\frac{d(d+1)}{2\nu+d(d+1)}} \log T}\right) = \tilde{\mathcal{O}}\left(T^{\frac{1}{2} + \frac{d(d+1)}{4\nu+2d(d+1)}}\sqrt{\log T}\right).$$

In all cases, the cumulative regret R_T grows sub-linearly with T, ensuring that the regret per iteration diminishes as T increases. This completes the proof for Theorem 3.

D IMPLEMENTATION DETAILS

In this section, we outline the implementation details of our method and considered baselines.

D.1 CAKES SETUP

Choice of LLM. We chose the `gpt-4o-mini` model as it offers an excellent balance of affordability, fast inference, and intelligence for our implementation. We access the model through the OpenAI API, which provides two key hyperparameters that allow us to control the randomness and diversity of the generated output: `temperature` and `top_p`. Concretely, `temperature` adjusts the "sharpness" of the probability distribution used to select the next token. Lower values result in more deterministic outputs, while higher values yield more random results. Conversely, `top_p` (or nucleus sampling) filters the probability distribution to consider only the most likely tokens that cumulatively reach a specified threshold, typically between 0 and 1. In our experiments, we found that setting `temperature=0.7` and `top_p=0.95` strikes a good balance between generating relevant outputs and introducing diversity. For further details, we refer the interested reader to the official documentation: `https://platform.openai.com/docs/overview`. In our experiments, we set the number of crossovers $n_c = 5$, probability of mutation $p_m = 0.7$, and population size $n_p = 10$.

Prompt design. We show the designed system prompt in Figure 4 as well as the sample prompts for the mutation and crossover steps in Figures 5b and 5a, respectively. Note that in all figures, {} is used to indicate placeholders.

System Prompt

You are an expert in machine learning, specializing in Gaussian processes. Here are the observations we have collected so far: `{observations}`

Please analyze these observations to identify patterns in the data that can be captured by a kernel function. You can use squared exponential (SE) kernel to capture smoothness, periodic (PER) kernel to capture periodicity, linear (LIN) kernel to capture linear trends, and rational quadratic (RQ) kernel to capture varying data patterns. You can also combine these kernels using the $+$ and $*$ operators to capture more complex patterns. For example, LIN $+$ PER can capture a linear trend with periodic fluctuations and LIN $*$ PER can capture a periodic pattern with linearly increasing amplitude.

Figure 4: The designed system prompt for the LLM.

Crossover Prompt

You are given two parent kernels and their Bayesian Information Criterion (BIC) values: `{parent_kernel1}` (BIC: `{bic1}`), `{parent_kernel2}` (BIC: `{bic2}`).

Please recommend a kernel that has a lower BIC value. You can either combine the parent kernels with $+$ or $*$ operator. Your output should follow the following format:

Kernel: <your proposed kernel here, only use the kernel abbreviations and operators>
Analysis: <your analysis here, explaining your reason behind the proposed kernel>

Mutation Prompt

You are given a kernel and its Bayesian Information Criterion (BIC) value: `{kernel}` (BIC: `{bic}`).

Please recommend a kernel that has a lower BIC value. You can only replace one of the base kernels in the kernel with another base kernel. Your output should follow the following format:

Kernel: <your proposed kernel here, only use the kernel abbreviations and operators>
Analysis: <your analysis here, explaining your reason behind the proposed kernel>

(a) Crossover prompt.

(b) Mutation prompt.

Figure 5: Sample prompts for proposing the kernels.

D.2 BASELINES

To test our proposed method, we consider four categories of baselines: fixed kernel, adaptive kernel, deep GP, and ensemble GP.

Fixed. For the fixed kernel baseline, we consider the following widely-used kernels in BO:

1. **Squared exponential (SE):**

$$k(\mathbf{x}, \mathbf{x}') = \exp\left(-\frac{1}{2}(\mathbf{x} - \mathbf{x}')^\top \Theta^{-2}(\mathbf{x} - \mathbf{x}')\right), \tag{28}$$

where Θ is the lengthscale parameter.

2. **Periodic (PER):**

$$k(\mathbf{x}, \mathbf{x}') = \exp\left(-2\sum_i \frac{\sin^2\left(\pi(x_i - x'_i)/p\right)}{\lambda}\right), \tag{29}$$

where p is the period length parameter and λ is the lengthscale parameter.

3. **Linear (LIN):**

$$k(\mathbf{x}, \mathbf{x}') = v\mathbf{x}^\top \mathbf{x}', \tag{30}$$

where v is the variance parameter.

4. **Rational quadratic (RQ):**

$$k(\mathbf{x}, \mathbf{x}') = \left(1 + \frac{1}{2\alpha}(\mathbf{x} - \mathbf{x}')^\top \Theta^{-2}(\mathbf{x} - \mathbf{x}')\right)^{-\alpha}, \tag{31}$$

where Θ is the lengthscale parameter and α is the relative weighting parameter.

5. **Matérn:**

$$k(\mathbf{x}, \mathbf{x}') = \frac{2^{1-\nu}}{\Gamma(\nu)}\left(\sqrt{2\nu}D\right)^\nu K_\nu\left(\sqrt{2\nu}D\right), \tag{32}$$

where

$$D = (\mathbf{x} - \mathbf{x}')^\top \Theta^{-2}(\mathbf{x} - \mathbf{x}') \tag{33}$$

is the distance between $\mathbf{x}$ and $\mathbf{x}'$ scaled by the lengthscale parameter and K_ν is the modified Bessel function. In our experiments, the smoothness parameter ν is set to 1/2, 3/2, or 5/2, corresponding to Matérn-1/2 (M1), Matérn-3/2 (M3), or Matérn-5/2 (M5) kernels respectively.

Adaptive. For the adaptive kernel baseline, we adopt the implementation from Roman et al. (2019) and apply the following selection criteria:

1. **Random:** This criterion selects a kernel randomly from the set of available kernels.

2. **Utility:** Based on the proposed query points from each kernel, this criterion selects the kernel with the highest utility (acquisition) value:

$$k^* = \arg\max_{k \in \mathbb{K}} \alpha(\mathbf{x}_{t,k}; \mathcal{D}, k). \tag{34}$$

3. **BIC:** This criterion selects the kernel with the lowest BIC value:

$$k^* = \arg\min_{k \in \mathbb{K}} \text{BIC}(k; \mathcal{D}). \tag{35}$$

Deep GP. For the deep GP baseline, we use the `DeepGP` implementation from GPyTorch, where training and inference are conducted using the doubly stochastic variational inference method (Salimbeni & Deisenroth, 2017).

Ensemble GP. For the ensemble GP baseline, we follow the implementation suggested by Lu et al. (2023), using the six base kernels used in CAKES to form the kernel dictionary.

E   EXPERIMENTAL DETAILS

In this section, we provide additional details on the benchmarks employed in our experiments.

E.1   OPTIMIZATION OF BENCHMARK FUNCTIONS

Test functions. We provide additional details on test functions, including the function domain and dimensionality, in Table 2. The analytic expression as well as the global optimum of these functions can be found at `https://www.sfu.ca/~ssurjano/optimization.html`. We visualize the optimization landscapes of the two-dimensional test functions in Figure 6. From the figure, one can see the challenging nature of these functions, which is characterized by many local minima, multi-modality, and steep ridges.

E.2   HYPERPARAMETER TUNING TASK

Datasets. We include 12 OpenML datasets available in the HPOBench package (Eggensperger et al., 2021). The details of the selected datasets are given in Table 3.

Search space. We follow the search space designated in HPOBench, where we discretize the search space to facilitate efficient tabular lookup operations for various configurations (Eggensperger et al., 2013). The search space for each ML model is summarized below, i.e., {`type`: [`space`, `lower_bound`, `upper_bound`]}:

(a) Ackley-2 (b) Beale (c) Branin (d) Dropwave

(e) Eggholder (f) Griewank-2 (g) Levy-2 (h) Rosenbrock

(i) Rastrigin-2 (j) Six-Hump Camel

Figure 6: Visualization of the optimization landscapes of two-dimensional test functions.

Table 2: Details of the test functions used in the experiments.

Function	Domain	d
Ackley-d	$[-5, 5]^d$	2, 5
Beale	$[-1, 1]^2$	2
Branin	$[-5, 10]^2$	2
Dropwave	$[-5.12, 5.12]^2$	2
Eggholder	$[-512, 512]^2$	2
Griewank-d	$[-600, 600]^d$	2, 5
Hartmann	$[0, 1]^3$	3
Levy	$[-10, 10]^d$	2, 3
Rastringin-d	$[-5.12, 5.12]^d$	2, 4
Rosenbrock	$[-5, 10]^2$	2
Six-Hump Camel	$[-3, 3] \times [-2, 2]$	2

- **Logistic Regression** ($d = 2$): {`alpha`: [log, 0.001, 1.0], `eta0`: [log, 0.001, 1.0]}

- **Support Vector Machine** ($d = 2$): {`C`: [log, 0.01, 10.0], `gamma`: [log, 0.001, 1.0]}

- **Random Forest** ($d = 4$): {`max_depth`: [log, 1, 50], `max_features`: [linear, 0.0, 1.0], `min_samples_leaf`: [linear, 1, 2], `min_samples_split`: [log, 2, 128]}

- **XGBoost** ($d = 4$): {`colsample_bytree`: [linear, 0.1, 1.0], `eta`: [log, 0.001, 1.0], `max_depth`: [log, 1, 50], `reg_lambda`: [log, 0.1, 10.0]}

- **Multi-Layer Perceptron** ($d = 5$): {`alpha`: [log, 0.001, 1.0], `batch_size`: [log, 16, 128], `depth`: [linear, 1, 3], `learning_rate_init`: [log, 0.001, 1.0]}, `width`: [log, 16, 128]}

Table 3: Details of the OpenML datasets used in the experiments. More information can be found at `https://www.openml.org`.

Dataset	Task ID	Number of Instances	Number of Features
credit_g	31	1000	21
vehicle	53	846	19
kc1	2109	2109	22
phoneme	9952	5404	6
blood_transfusion	10101	748	5
australian	146818	690	15
car	146821	1728	7
segment	146822	2310	20
heart_h	50	294	14
tic_tac_toe	145804	958	10
kr_vs_kp	3	3196	37
qsar	9957	1055	42

Emission

Design Parameters

Length	Lattice constant
Width	Size of holes
Layer thickness	Filling factor
Shape of holes	Material properties

Indicator	Target
Q-factor (Q)	$Q^* = 2 \times 10^6$
Wavelength (λ)	$\lambda^* = 1310$
Lasing area (A)	$A^* = 3.6 \times 10^{-13}$
Power (P)	$P^* = 0.5$
Divergence angle (ω)	$\omega^* = 1.0$

Figure 7: Illustration of a photonic chip and its design parameters. The inverse design problem focuses on optimizing these parameters to satisfy certain performance indicators.

E.3 PHOTONIC CHIP DESIGN

Objective. The design parameters and indicators for optimizing the photonic chip are detailed in Figure 7. We established target values based on our experiments and a review of the literature to identify optimal standards for high-quality chip lasing (Li et al., 2023). For instance, a wavelength of 1310 nm is crucial for telecommunications and satellite applications, while high output power is essential for fields such as autonomous driving and medicine. Additionally, a small divergence angle is vital for ensuring high beam quality and effective long-distance light propagation. Based on these performance indicators, we can define the objectives as follows,

$$f_1 = 1 - \frac{Q^* - Q}{Q^*}, \tag{36}$$

$$f_2 = 1 - \frac{|\lambda^* - \lambda|}{\lambda^*}, \tag{37}$$

$$f_3 = 1 - \frac{A^* - A}{A^*}, \tag{38}$$

$$f_4 = 1 - \frac{P^* - P}{P^*}, \tag{39}$$

$$f_5 = 1 + \frac{\omega^* - \omega}{\omega^*}. \tag{40}$$

Q-factor (f_1) is related to the loss and threshold of the laser, wavelength (f_2) is the operation wavelength of the laser, lasing area (f_3) is the area of the laser beam at the laser's top surface, power

Figure 8: Comparison of the fitness distributions between an initial population of kernels before and after applying crossover and mutation operations.

(f_4) is the lasing power of the laser in watts, and divergence angle (f_5) is the angle between outer boundary and centerline of the laser beam.

F EMPIRICAL ANALYSIS

In this section, we provide additional empirical analysis on our proposed method in Section 3.

F.1 CROSSOVER AND MUTATION WITH LLMS

To demonstrate the benefits of using LLMs for kernel generation, we conduct an experiment to analyze the fitness distributions of an initial population of kernels before and after applying crossover and mutation operations. Specifically, we consider the hyper-parameter tuning tasks in Section 6.2 and evaluate the fitness values of the initial population. We then use the LLM to perform crossover and mutation on this population, and re-evaluate the fitness values. Figure 8 shows the comparison of fitness distributions across these three different stages. From the figure, we can observe that the initial population exhibits a wide distribution, with a noticeable peak at lower fitness values. After performing crossover, the distribution shifts slightly toward higher fitness values, indicating that the LLM can effectively combine the kernels and enhance the overall fitness of the population. Furthermore, we can see that applying mutation shifts the distribution toward even higher fitness values, suggesting that further refining the kernels can yield higher fitness values. Overall, these findings demonstrate that LLM can act as a good crossover and mutation operators.

F.2 CASE STUDY

We conduct a case study to analyze the output from the LLM and test whether or not the LLM can give helpful responses. Specifically, we show sample responses from the LLM for the crossover and mutation steps, which are depicted in Figure 9. In Figure 9a, given the parent kernels LIN and SE along with their BIC values, the LLM suggests combining them using the addition operator $(+)$ to minimize the BIC. The analysis explains the rationale behind this combination: the LIN kernel captures linear trends, while the SE kernel models smoothness. By combining these properties, the LIN + SE kernel effectively represents both linearity and smoothness in the data. In Figure 9b, given the LIN + SE kernel and its BIC, the LLM recommends replacing the SE kernel with the RQ kernel to achieve a lower BIC value. The analysis indicates that while the SE kernel assumes fixed smoothness, the RQ kernel introduces varying smoothness, allowing the model to adapt better to data with fluctuating noise levels. These examples illustrate that the LLM is familiar with kernel properties and their applications. Its responses demonstrate a strong understanding of the relationships between different kernels and their capacity to address specific data characteristics, enabling it to make informed suggestions for the kernel selection.

Crossover Response

Prompt:
You are given two parent kernels and their Bayesian Information Criterion (BIC) values: LIN (BIC: 93.42),
SE (BIC: 118.59).

Please recommend a kernel that has a lower BIC value. You can either combine the parent kernels with $+$ or $*$ operator. Your output should follow the following format:

Kernel: <your proposed kernel here, only use the kernel abbreviations and operators>
Analysis: <your analysis here, explaining your reason behind the proposed kernel>

- -

Response:
Kernel: LIN $+$ SE
Analysis: The LIN kernel captures linear trends in the data, which may be present given the varying function values across different inputs. The SE kernel, on the other hand, is effective in modeling smooth variations in the data, which could account for the fluctuations observed in the function values despite the overall linear trend. By combining these two kernels with the addition operator $(+)$, we can leverage the linear trend from the LIN kernel while also allowing for smooth deviations from this trend through the SE kernel.

(a) Sample response for the crossover step.

Mutation Response

Prompt:
You are given a kernel and its Bayesian Information Criterion (BIC) value:
LIN $+$ SE (BIC: 79.83).

Please recommend a kernel that has a lower BIC value. You can only replace one of the base kernels in the kernel with another base kernel. Your output should follow the following format:

Kernel: <your proposed kernel here, only use the kernel abbreviations and operators>
Analysis: <your analysis here, explaining your reason behind the proposed kernel>

- -

Response:
Kernel: LIN $+$ RQ
Analysis: The LIN $+$ SE kernel captures a linear trend with smooth variations. However, the SE kernel assumes a constant level of smoothness, which may not be appropriate for all data patterns. By replacing the SE kernel with the RQ kernel, we can introduce varying smoothness, allowing the model to adapt to different levels of noise in the data.

(b) Sample response for the mutation step.

Figure 9: Sample responses from the LLM for the kernel generation process.

G ADDITIONAL OPTIMIZATION RESULTS

In this section, we show additional experimental results on the optimization tasks considered in Section 6.

G.1 OPTIMIZATION OF BENCHMARK FUNCTIONS

Additional comparisons. We provide more comprehensive comparisons between our proposed method and fixed kernel approaches in Table 4. Specifically, we include three additional kernels: rational quadratic (RQ), Matérn-1/2 (M1), and Matérn-3/2 (M3). Overall, CAKES outperforms all fixed kernel approaches in terms of the mean and median regret. Our results indicate that fixed

Table 4: Average normalized regret ($\downarrow$) over 20 random seeds for different test functions and methods. The best value is highlighted in **bold** and the second best value is underlined.

Function	Fixed					CAKES
	SE	RQ	M1	M3	M5	
Ackley-2	0.1773	0.1605	0.1309	0.0878	0.1220	**0.0783**
Ackley-5	0.3185	0.2732	0.4949	0.2197	0.2369	**0.1732**
Beale	0.3554	0.2881	**0.2455**	0.2945	0.3522	0.2565
Branin	0.0183	**0.0055**	0.0323	0.0455	0.0117	0.0070
Dropwave	0.5110	0.5185	0.6669	0.5848	0.5411	**0.4690**
Eggholder	0.4941	0.5111	0.4195	0.4297	0.3545	**0.1241**
Griewank-2	0.1196	0.1365	0.0687	0.1362	0.1282	**0.0267**
Griewank-5	0.0204	0.0210	0.0419	0.0200	0.0223	**0.0185**
Hartmann	0.0007	0.0003	0.0915	0.0131	0.0019	**0.0001**
Levy-2	0.1562	0.0758	0.1190	0.0595	0.0418	**0.0353**
Levy-3	0.1141	0.1630	0.0873	0.1226	0.1422	**0.0505**
Rastringin-2	0.4325	0.4417	0.3573	0.4624	0.4251	**0.3341**
Rastringin-4	0.5765	0.5752	0.4009	0.4290	0.5461	**0.3128**
Rosenbrock	0.1030	0.1054	0.3375	0.2460	0.0898	**0.0483**
Six-Hump Camel	0.2840	0.3105	0.4410	0.1431	0.1507	**0.1015**
Mean regret	0.2454	0.2391	0.2623	0.2196	0.2111	**0.1358**
Median regret	0.1773	0.1630	0.2455	0.1431	0.1422	**0.0783**

Table 5: Average normalized regret ($\downarrow$) over 20 random seeds for different test functions and methods. The best value is highlighted in **bold** and the second best value is underlined.

Function	BOM	MCMC	ABO	CAKES
Ackley-2	0.1016	0.1012	0.1020	**0.0783**
Ackley-5	0.5907	**0.1312**	0.1910	0.1733
Beale	0.3559	0.4040	0.3118	**0.2570**
Branin	0.0499	0.0301	0.0101	**0.0071**
Dropwave	0.5040	0.5788	0.5529	**0.4693**
Eggholder	0.4709	0.4536	0.4210	**0.1242**
Griewank-2	0.0460	0.0589	0.0357	**0.0266**
Griewank-5	0.2437	0.0258	0.0320	**0.0189**
Hartmann	0.0299	**0.0001**	**0.0001**	**0.0001**
Levy-2	0.0626	0.0668	0.0519	**0.0352**
Levy-3	0.0867	0.0580	**0.0290**	0.0507
Rastringin-2	0.3618	0.3722	0.3420	**0.3342**
Rastringin-4	0.3177	0.3285	0.3179	**0.3125**
Rosenbrock	0.0901	0.0907	0.0901	**0.0484**
Six-Hump Camel	0.1102	0.1071	**0.1002**	0.1013
Mean regret	0.2281	0.1871	0.1725	**0.1358**
Median regret	0.1102	0.1012	0.1002	**0.0783**

kernels do not perform uniformly well across all tasks, which is consistent with our findings in Section 6.1.

Additional baselines. We compare our proposed method against the following baselines:

- **Bag-of-models (BOM):** This is a method proposed by Kandasamy et al. (2015) which maintains a collection of kernels, each capturing different structures, that best explains the observed data.

Table 6: Average normalized regret ($\downarrow$) over 20 random seeds for Ackley and Levy functions with varying dimensions. The best value is highlighted in **bold** and the second best value is underlined.

Function	Fixed		Adaptive			DGP	EGP	CAKES
	SE	M5	Random	Utility	BIC			
Ackley-2	0.1773	0.1220	0.1358	0.1062	0.1863	0.2510	0.1878	**0.0783**
Ackley-5	0.3185	0.2369	**0.1722**	0.2278	0.3590	0.3110	0.2285	0.1732
Ackley-10	0.3645	0.3225	0.2725	0.4122	0.3157	0.4557	0.3108	**0.2356**
Ackley-20	0.4523	0.4152	0.5103	0.5509	0.5021	0.5043	0.4237	**0.3281**
Ackley-30	0.5331	0.5114	0.6460	0.5966	0.5664	0.6056	0.6210	**0.4596**
Levy-2	0.1562	0.0418	0.0835	**0.0255**	0.1145	0.1965	0.0765	0.0353
Levy-3	0.1141	0.1422	0.1495	0.0880	0.1125	0.2265	0.0805	**0.0505**
Levy-10	0.3215	0.2514	0.2310	0.1545	0.1940	0.2845	0.1069	**0.0941**
Levy-20	0.3657	0.4061	0.3815	0.1905	0.2762	0.3450	0.1703	**0.1208**
Levy-30	0.4205	0.4598	0.4515	0.2405	0.3147	0.4534	0.2040	**0.1483**

- **Markov chain Monte Carlo (MCMC):** This is a method proposed by Gardner et al. (2017) which uses a Metropolis-Hastings algorithm to randomly sample kernels from the grammar based on a proposal distribution.

- **Automated BO (ABO)[1]:** This is a method proposed by Malkomes & Garnett (2018), which uses BO to dynamically select kernels that best explains the observed data.

For the above three baselines, we follow the setup suggested by the authors. We limited the number of models to 50 and use the L-BFGS algorithm to optimize each model's hyperparameters. As in Section 6.1, we set $T = 10 \times d$ and repeat each experiment using 20 different random seeds. The results in 5 shows that CAKES is superior compared to all the baselines in terms of the mean and median regret. Notably, CAKES ranked first in 12 out of 15 instances and ranked a top-two ranking in all instances.

Additional test functions. To further evaluate our method in higher-dimensional settings, we conducted additional experiments using the Ackley and Levy functions across various input dimensions d. Specifically, we tested with $d \in \{10, 20, 30\}$. As illustrated in Figure 6, both of these functions are highly non-convex and possess numerous local minima, making them particularly challenging to optimize. We set $T = 10 \times d$ and repeat each experiment using 20 different random seeds. The results, presented in Table 6, demonstrate that CAKES consistently outperforms the other methods, even as d increases. This suggests that our method can scale effectively in more complex search spaces. In addition, the results reveal that fixed kernel methods (SE and M5) perform poorly compared to the adaptive and multiple kernel approaches.

G.2 HYPERPARAMETER TUNING TASK

Individual task results. We present the individual task results from HPOBench for CAKES and other methods in Figures 14-23. Our findings reveal that there are significant variations in performance for fixed and adaptive kernel baselines, which align with the results presented in Section 6.2. Table 7 further highlights the superior performance of CAKES, which achieves the best average rank at the end of each tuning task.

Tuning accuracy. Figure 10 depicts the average accuracy in tuning different ML models over five random seeds. We further show the accuracy achieved by different methods on individual tasks in Figures 19-23 Overall, CAKES consistently achieves the highest accuracy in tuning all machine learning models compared to the other methods.

---

[1]We use the code provided by the authors in `https://github.com/gustavomalkomes/abo`.

Table 7: Average rank ($\downarrow$) $\pm$ standard deviation achieved by different methods over 5 random seeds.

Model		LR	SVM	RF	XGB	MLP
Fixed	SE	3.33 ± 2.09	4.58 ± 2.02	4.00 ± 2.35	3.42 ± 1.98	3.42 ± 1.93
	M5	4.25 ± 1.30	4.50 ± 2.63	4.08 ± 1.93	4.92 ± 1.98	5.58 ± 1.75
Adaptive	Random	5.17 ± 1.40	4.42 ± 1.71	5.08 ± 2.36	5.83 ± 1.57	6.08 ± 1.66
	Utility	6.17 ± 1.77	4.08 ± 2.14	3.92 ± 1.85	5.00 ± 2.38	4.42 ± 2.50
	BIC	7.33 ± 1.18	5.67 ± 2.01	5.25 ± 2.05	3.83 ± 2.03	4.83 ± 2.70
DGP		3.33 ± 2.36	5.92 ± 2.06	5.08 ± 2.63	5.17 ± 2.51	4.08 ± 2.18
EGP		4.17 ± 1.40	4.33 ± 2.32	5.17 ± 2.73	5.00 ± 2.12	4.92 ± 1.80
CAKES		2.25 ± 1.64	2.50 ± 1.50	3.42 ± 1.26	2.83 ± 1.95	2.67 ± 1.49

Figure 10: Average accuracy ($\uparrow$) over 5 random seeds for different ML models on all datasets.

G.3 PHOTONIC CHIP DESIGN

Individual objective results. We plot the individual performance on each objective in Figure 11. The results show that the CAKES algorithm outperforms the other baseline approaches across multiple performance indicators. Particularly for objectives f_3 and f_4, CAKES achieves higher objective values more quickly compared to the baselines. This is particularly desirable as the third and fourth objectives are much more important than the other ones, especially from an practical engineering (e.g., autonomous driving or military laser weapon) point of view. This is because we want the photonic chip to have large lasing area (f_3) to produce a large light field coverage and have higher power (f_4) to transmit signal/beam faster and farther. Besides, CAKES also maintains a competitive performance for the other objectives throughout the trials. These results demonstrate that CAKES is not only effective in the early stages of the optimization process, but also capable of achieving long-term performance improvements.

Figure 11: Comparison of individual objective results for photonic chip design across 250 trials.

Table 8: Comparison of optimized performance indicators obtained by our method and various baselines from the literature. NA denotes unreported values.

Method	Q-factor	Wavelength	Lasing area	Power	Divergence
Ohnishi et al. (2004)	NA	959.4	2.8×10^{-9}	NA	1.1
Hsu et al. (2017)	5.0×10^{3}	1299	1.8×10^{-8}	NA	2.0
Chen et al. (2021)	2.9×10^{3}	948	6.2×10^{-9}	NA	0.75
Ours	2.5×10^{7}	1309.3	1.3×10^{-13}	0.99	1.2

Additional baselines. To further validate our results, we compare the optimized performance indicators obtained by our method with some additional baselines in the literature. In Table 8, we compare the five objectives (f_1 through f_5) against three state-of-the-art photonic chips of the same category from existing literature. Notably, our work is the only one to report power (f_4), which are crucial for LiDAR and military applications. In addition, we achieved the highest Q-factor, indicating high efficiency and a low threshold. Our lasing area is smaller than the literature benchmarks due to our chip size of 4 square microns, which is several orders of magnitude smaller. This miniaturization is essential for integration into circuits and for enabling high-performance AI computing chips. It is worth mentioning that we could easily increase the lasing area by scaling up the chip size. Overall, these results demonstrate that the chip designed by CAKES remains competitive or even superior to these additional baselines.

G.4   ROBOT PUSHING

The robot pushing problem was initially considered by Wang et al. (2018). The objective is to develop a controller for two robotic hands tasked with pushing two objects to specified target positions. The robot controller is defined by $d = 14$ parameters that determine the position and orientation of the hands, the pushing speed, the direction of movement, and the duration of the push. The reward function is given by:

$$f(\mathbf{x}) = - \sum_{i=1}^{2} |\mathbf{x}_{gi} - \mathbf{x}_{si}| - |\mathbf{x}_{gi} - \mathbf{x}_{fi}| \tag{41}$$

where $\mathbf{x}_{si}$ represents the initial positions of the objects, $\mathbf{x}_{fi}$ denotes their final positions, and $\mathbf{x}_{gi}$ indicates the goal . The objective is to minimize the total distance from the initial and final positions of the objects to their respective goal positions, thus maximizing the reward. We run each method for a total of $T = 100$ iterations using 10 different random seeds. To evaluate the performance of each method, we conduct a series of simulations, running each method for a total of $T = 100$

Figure 12: Reward (↑) and regret (↓) for the robot pushing problem.

iterations, using 10 different initial positions. The results, illustrated in Figure 12, show that the CAKES method outperformed the other approaches in terms of achieving the highest reward and minimizing the regret.

G.5 LUNAR LANDER

We consider tuning a controller for a lunar lander implemented in OpenAI Gym[2]. The state space of the lunar lander consists of its position, angle, time derivatives, and indicators of whether either leg is in contact with the ground. This results in an 8-dimensional state vector, which is passed to a handcrafted parameterized controller that determines the appropriate action to take. There are four possible actions for each frame: firing the main engine, fire the left orientation engine, fire the right orientation engine, or doing nothing. The handcrafted control policy is defined by $d = 12$ parameters, which parameterize linear score functions based on the state vector and establish thresholds that dictate which action to prioritize. The reward system is defined as follows:

- Successful landing yields $+100$ points, while crashing incurs a penalty of -100 points.
- Each leg in contact with the ground yields $+10$ points.
- Firing the main engine incurs a penalty of -0.3 points per frame, and firing side engines incurs a penalty of -0.03 points per frame.

The benchmark for winning the game is 200 points, so we use it as the target objective. We run the simulation for $T = 250$ iterations and average the results over 50 randomly generated terrains, initial positions, and velocities. The results, illustrated in Figure 12, demonstrate that the controller optimized by CAKES significantly outperforms other methods, achieving both the highest rewards and the lowest regret. Specifically, CAKES consistently reached or exceeded the target objective of 200 points across various terrains, while the other methods struggled to maintain high scores and often incurred greater penalties due to crashes or inefficient landings. In our simulations, we also found that CAKES not only optimized the landing strategies but also minimized unnecessary engine usage, resulting in lower penalties over time.

H LIMITATIONS AND FUTURE WORK

Computational cost. While CAKES can be applied entirely in-context and does not require any fine-tuning, using LLMs for inference may result in a larger computational footprint compared to

---

[2]https://www.gymlibrary.dev/environments/box2d/lunar_lander/

Figure 13: Reward (↑) and regret (↓) for the lunar lander problem.

traditional BO methods. Despite this, our findings indicate that CAKES trades this off with improved sample efficiency, which is a particularly desirable property for black-box optimization tasks. This suggests the potential for integrating CAKES with more computationally efficient approaches, such as deploying it in the earlier stage of the optimization process.

Choice of LLM. We have demonstrated the potential of integrating LLMs to enhance kernel design in BO using the `gpt-4o-mini` model. We chose `gpt-4o-mini` as it offers an excellent balance of affordability, fast inference, and intelligence for our implementation. While we acknowledge that the choice of the LLM may influence the results, the overall methodology and key insights presented in this work are generally applicable, and extend beyond the specifics of any particular LLM. A promising direction for future research would be to benchmark various LLMs to better understand their strengths and limitations across different BO problem settings.

Generalized kernel grammar. While we focus on addition and multiplication as initial proof-of-concept operators, these operators are in fact good enough to form a rich and expressive space of kernels. For example, by only using these operations, we can construct polynomial kernels to capture non-linear patterns as well as multi-dimensional kernels to model interactions among input features (Duvenaud et al., 2013). However, we would like that to note that the kernel grammar can be extended using other operators that preserve the closure properties of kernel functions, such as convolution, composition, and affine transformations (Smola & Schölkopf, 1998). We aim to explore these possibilities further in future work.

Figure 14: Average regret (↓) over 5 random seeds for the LR model tuned with different methods on individual tasks.

Figure 15: Average regret (↓) over 5 random seeds for the SVM model tuned with different methods on individual tasks.

Figure 16: Average regret (↓) over 5 random seeds for the RF model tuned with different methods on individual tasks.

Figure 17: Average regret (↓) over 5 random seeds for the XGB model tuned with different methods on individual tasks.

Figure 18: Average regret (↓) over 5 random seeds for the MLP model tuned with different methods on individual tasks.

Figure 19: Average accuracy (↑) over 5 random seeds for the LR model tuned with different methods on individual tasks.

Figure 20: Average accuracy (↑) over 5 random seeds for the SVM model tuned with different methods on individual tasks.

Figure 21: Average accuracy (↑) over 5 random seeds for the RF model tuned with different methods on individual tasks.

Figure 22: Average accuracy (↑) over 5 random seeds for the XGB model tuned with different methods on individual tasks.

Figure 23: Average accuracy (↑) over 5 random seeds for the MLP model tuned with different methods on individual tasks.