DevFly: Bio-Inspired Development of Binary Connections for Locality Preserving Sparse Codes

Abstract

Neural circuits undergo developmental processes which can be influenced by experience. Here we explore a bio-inspired development process to form the connections in a network used for locality sensitive hashing. The network is a simplified model of the insect mushroom body, which has sparse connections from the input layer to a second layer of higher dimension, forming a sparse code. In previous versions of this model, connectivity between the layers is random. We investigate whether the performance of the hash, evaluated in nearest neighbour query tasks, can be improved by process of developing the connections, in which the strongest input dimensions in successive samples are wired to each successive coding dimension. Experiments show that, the accuracy of searching for nearest neighbours is improved, although performance is dependent on the parameter values and datasets used. Our approach is also much faster than alternative methods that have been proposed for training the connections in this model. Importantly, the development process does not impact connections built at an earlier stage, which should provide stable coding results for simultaneous learning in a downstream network.

1 Introduction

The insect mushroom body (MB) is a learning centre in the insect brain, and its function is of interest as a neural architecture for efficient association of arbitrary sensory patterns to actions. The MB is a shallow network, with an input layer of projection neurons (PNs) that sparsely connect to a larger number of Kenyon cells (KCs), which are fully connected to a small number of MB output neurons (MBONs). In this paper we focus on the PN to KC connectivity, and consider how the activity pattern in KCs could provide an efficient code for the input that enhances the appropriate generalisation from previously experienced patterns to new inputs. In the MB, only a small portion of KCs is activated at any time (Honegger et al., 2011), which is known as sparse coding (Olshausen & Field, 2004). Sparse coding facilitates learning by letting each KC represent a more specific pattern of sensory inputs, which reduces unintended association with a different pattern during learning (Treves & Rolls, 1991). Ideally, similarity in sensory input space should map to similarity in the space of sparse codes.

One way to interpret the function of the mapping from PN to KC is treating the mapping as a locality-sensitive hash (Dasgupta et al., 2017). Ideally, a locality-sensitive hash (LSH) function can preserve relative distances between data samples in the corresponding hash coding results (Hutchins, 1999), such that the codes can be used to efficiently locate close samples. Compared to a typical LSH, the MB-inspired hash algorithm (Figure 1) proposed by Dasgupta et al. (2017), called FlyLSH, maps inputs (with a dimension d) to a higher dimensional space (with a dimension m), using sparse binary connections, and then creates a sparse binary code by choosing the top k-values and setting them to 1. FlyLSH achieved better performance than a standard LSH algorithm (if the hash length of the latter

is scaled down so that the computational complexity to calculate each form of hash is similar). This in turn allows FlyLSH to attain higher precision than LSH algorithms that use a dense connectivity matrix. It has inspired some variations including deep nets that use FlyLSH as initial layers. For example, work by Chancan et al. (2020) combined a FlyLSH based network with a one-dimensional continuous attractor neural network and achieved a better performance than other methods in visual place recognition tasks.

Figure 1: Two steps to produce a hash using binary connections.

Figure 2: Summary of the mushroom body development (modified from (Lee et al., 1999)). NHL: newly hatched larvae, ALH: after larval hatching, APF: after puparium formation.

FlyLSH uses fixed random connections between the PN and KC layers, a feature inspired by previous accounts of this connectivity in the MB (Caron et al., 2013; Masuda-Nakagawa et al., 2005). However, more recent biological results suggest that the formation of connections between PNs and KCs can be experience-dependent, and when a KC connects to PNs depends on (1) when the KC is developmentally generated and (2) the existing connections (Eichler et al., 2017). Like other neural circuits, the MB develops during the animal's maturation from a few neurons to thousands of neurons, and new connections are built during this process. In the fly, this happens during embryo, larvae, pupae, and early adult stages (Figure 2) (Lee et al., 1999), with and without external stimulus. There is also evidence suggesting that the distribution of the connections cannot be simply explained as random, and this is supported by both experimental (Eichler et al., 2017; Elkahlah et al., 2020) and theoretical (Litwin-Kumar et al., 2017) studies.

In this paper, we propose a bio-inspired method that develops the binary connections between input PNs and the coding KCs. The connections to each coding dimension are built according to strongest dimensions of a selected sample, and once built, they will not be impacted by later development, so that reliable coding results are preserved during the development process. We then test this method against FlyLSH in a nearest neighbours search task using several datasets as inputs.

2 Related works

Models of the MB have been presented by several different groups mostly in the context of associative learning or classification tasks, such as (Huerta et al., 2004; Smith et al., 2008; Mosqueiro & Huerta, 2014; Bennett et al., 2021; Wessnitzer et al., 2012; Ardin et al., 2016; Zhu et al., 2021). Most of these studies make the assumption that the connections between PNs and KCs are randomised. The effect of non-random PN to KC connections has been explored for the biological task of odour discrimination in a model by Zavitz et al. (2021). They find the effective dimensionality of the KC layer is reduced, the response to odours potentially of ethological significance to the fly are heightened and the generalisation between odours is improved. There are also recent models that include plasticity between PNs and KCs, such as MothNet (Delahunt & Kutz, 2019) and a model by Peng & Chittka (2017) which adjusts the PN-KC synapses according to reward modulation and coactivation of connected PN and KC, showing that this alters the generalisation/discrimination tradeoff for KC encoding of sensory patterns.

A number of papers have explored the effects of altering the connection scheme from PN to KC from the FlyLSH default, which is for each KC to receive inputs from n randomly selected PNs where n is some fraction of the input dimension. Xu & Qiao (2018) explored the use of a variable n, centred on the same mean, and reported improved performance over FlyLSH for nearest neighbour search in CIFAR-10, as well as better performance than several data dependent (but unsupervised) standard hash methods including PCA-hash, Sperical Hash and ITQ. Data-dependent methods for

forming the sparse connections should be expected to do better than random connections for the same n. Ma et al. (2020) proposed an algorithm to iteratively construct the projection matrix to produce the winner-take-all (WTA) output that maximises the distance between codes for the whole dataset, subject to the limit n on the number of connections per KC. Ryali et al. (2020) proposed a method similar to self-organising mapping to train a modified version of FlyLSH, which uses continuous values instead of binary values for mapping, noting that this is equivalent to k-means clustering with some additional constraints. Both methods outperform FlyLSH, but are relatively data greedy because they use all images in the datasets for learning the connections. In Pehlevan et al. (2017) a neurally plausible method for online k-means clustering is proposed and related to known PN-KC connectivity properties, although the method is not explicitly tested as a hashing code.

Preissner & Herbelot (2019) took a contrasting approach when applying the FlyLSH method to a language corpora. In their work the PN layer is incrementally expanded, and the KC connections randomly redistributed, while preserving equal n, as words are encountered in new contexts. An interesting point made in this approach is that the resulting sparse KC code is interpretable, for example, the set of PNs connecting to one KC tend to refer to related or frequently co-occuring words in the input data. However, like the previous methods, it requires multiple updates for every KC during the training process.

There is relevant earlier research on growing ANNs (also described as resource allocation networks (Platt, 1991)) where neurons and/or connections are gradually added to the network (see review by Macleod & Maxwell (2001) and more recently (Mixter & Akoglu, 2020)). In this approach, new units are added when the existing network does not meet some criteria with respect to newly presented data, and then all the connection weights are retrained using gradient descent or similar standard methods. These methods might also include pruning, to remove units that are not contributing to successful performance, e.g., (Yingwei et al., 1998). In either case the aim is to produce a more compact network size. By contrast, our developmental algorithm assumes a target total number of neurons, and tries to connect each successive one to represent the data efficiently with respect to previous connections, but without changing any existing connections. Interestingly, our approach (and the MB structure) can be more closely compared to early work on 'prototype' learning in the form of RCE networks (Reilly et al., 1982), where input samples are used to set the weights of successive nodes in the first layer, with new connections to the next node formed if the existing node activations cannot support successful classification in the following layer, but no further changes made to existing weights. RCE networks have also been used in an unsupervised form (Marsland et al., 2002) where nodes are added when none of the current nodes are sufficiently activated, and this form of network can be related to radial basis functions.

3 Methods

The aim of the algorithm presented here is to produce a locality sensitive hash code such that the distance in the sample space is positively correlated to the distance in the code space. In the following, the distance in sample space is measured as Euclidean distance, and the distance in the code space is measured as Hamming distance for the binary coding (Sharma & Navlakha, 2018).

Hashing by FlyLSH or its variations consists of two steps (Figure 1), a linear mapping from the input (with dimension d) to the code space (with dimension m), and binarisation of the resulting activity pattern. Note that we assume the input data has been normalised, however, this has limited impact on the performance, because the connection building given a sample and binarisation is only determined by the top values. FlyLSH uses a "centering the mean" pre-processing step (Dasgupta et al., 2017), which shifts the samples so the sum of all the samples are zeros. However, we did not notice any difference in performance without the shift in FlyLSH, and our methods should not be sensitive to this again because they build the

---

Algorithm 1 Connection development for Method 1

Input: Data Samples $S = \{\mathbf{s}_1, \mathbf{s}_2, \ldots \mathbf{s}_q, \ldots \mathbf{s}_u\}$.
Parameter: code dimension m, number of connections per KC n.
Output: KC weights $R = \{\mathbf{r}_1, \mathbf{r}_2, \ldots \mathbf{r}_j, \ldots \mathbf{r}_m\}$.

1: $j := 1$
2: # Randomly choose m samples from S.
3: **for** $\mathbf{s}_q$ in m samples from S **do**
4:    # Set the weights of a KC according to a sample.
5:    Find the indexes $\mathbf{i}'$ of top n values in the sample.
6:    $r_{i' \in \mathbf{i}'} := 1$, where $r_i \in \mathbf{r}_j$.
7:    j++
8: **end for**
9: **return** R

---

connections according to the most intensive pixels, irrespective of the average intensity. Thus this step, which requires advance access to the dataset, is not critical and could be removed for online learning.

In FlyLSH, the linear mapping step uses a binary matrix R generated by randomly choosing $n = \lfloor \alpha d \rfloor$ indexes from the input dimensions for each code dimension, where $0 < \alpha < 1$, typically $\alpha \sim 0.1$, and $\lfloor \cdot \rfloor$ is the floor operation. Thus, for each row of R, n elements are randomly set to 1, and the remainder are 0. After all of the coding dimensions are computed, they are binarised by choosing the top k values and setting them to 1, with all remaining values set to 0.

Note that although in the fly, and in contrast to standard LSH, $m >> d$, in practice FlyLSH is often tested with high dimensional inputs resulting in $m <= d$. The key properties preserved from the fly are the use of a low sampling ratio α rather than full connectivity, and a sparse code $k << m$. For clarity, we have not followed Dasgupta et al. (2017) in referring to k as the hash length, as in practice the full code of length m is used to calculate Hamming distance, but see section 4.1 below.

The method we propose (which we call DevFLY) uses bioinspired development processes to replace the random choice that generates matrix R. They mimic the biological observation that in the MB, individual KCs mature at different times and each will make connections to PNs as they mature, that is, there is no single stage at which all PN-KC wiring occurs. We assume that, in the MB, when some criteria is triggered, synapses are built from those PNs that have strongest activities to an immature KC; subsequently the connections for this now mature KC remain fixed. Correspondingly, in DevFly, when some criteria is triggered, the connections are built from strongest input dimensions to a new code dimension. We propose three alternative criteria (from hereon referred to as Method 1,2 or 3).

Method 1: connection development according to randomly picked samples. The first method is designed to test the importance of connecting from the strongest input dimensions, by simply setting the criteria to be randomness: (1) Randomly choose data samples, as many as the number of code dimensions. (2) Given a sample, connect the strongest n input dimensions to a code dimension. (3) Repeat the previous step until all code dimensions are connected.

Method 2: connection development according to unfamiliar samples In the second method, we set the criteria so as to build new connections only when a sample input is not already well connected. That is, given a sample, an unconnected code dimension will be connected to the strongest input connections only if none of the previously connected code dimensions have an output stronger than a threshold. The threshold can be interpreted as a means of recognising "familiar" samples. (1) Set a threshold for when to connect. (2) Initialise the connections to the first code dimension with the first sample according to the strongest n input dimensions. (3) For the next sample, check the response of connected code dimensions. If all them are weaker than the threshold, connect an unconnected code dimension according to the strongest n input dimensions.(4) Repeat the previous step until all code dimensions are connected.

Algorithm 2 Connection development for Method 2 and 3

Input: Data Samples $S = \{\mathbf{s}_1, \mathbf{s}_2, \dots \mathbf{s}_q, \dots \mathbf{s}_u\}$.
Parameter: threshold θ, threshold increasing rate β, code dimension m, number of connections per KC n.
Output: KC weights $R = \{\mathbf{r}_1, \mathbf{r}_2, \dots \mathbf{r}_j, \dots \mathbf{r}_m\}$.

1: Let $R := \mathbf{0}$, $j := 1$, $q := 1$.
2: **while** $j \leq m$ **do**
3:     # Iterate for next unfamiliar sample $\mathbf{s}_q$.
4:     **while** $\mathbf{y}' > \theta \ \exists \ \mathbf{y}' \in \{\mathbf{y}'_j | \mathbf{y}'_j = \mathbf{r}_j \mathbf{s}_q\}, \ j' \in \{1, 2, \dots, j\}$ **do**
5:         $q + +$
6:         **if** $q > u$ **then**
7:             $\theta := \beta \theta$
8:             $q := 0$
9:         **end if**
10:    **end while**
11:    # Set the weights of a KC according to a sample.
12:    **if** Method 2 **then**
13:        Find the indexes $\mathbf{i}'$ of top n values in the sample.
14:    **else if** Method 3 **then**
15:        Randomly choose n indexes $\mathbf{i}'$ using the normalised sample as probability.
16:    **end if**
17:    $r_{i \in \mathbf{i}'} := 1$, where $r_i \in \mathbf{r}_j$.
18:    $j + +$.
19: **end while**
20: **return** R

If all samples have been examined but some code dimensions remain unconnected, increase the threshold, and then loop through the samples again.

Method 3: connection development randomly according to unfamiliar samples We propose an additional variation on Method 2 by introducing noise when building the connections. Instead of connecting the input dimensions and code dimensions strictly according to the strongest input dimensions, the connection is built by randomly selecting input dimensions according to the distribution of the input dimensions. This seems biologically more realistic, but we also believe that with this modification, the new connections could have better generalisation while capturing the features.

Method 1 is shown in Algorithm 1. Method 2 and 3 are shown in Algorithm 2. The code is available in the supplementary materials.

4 Experiments

We applied the three connection development methods to FlyLSH, and tested them on four different datasets for the precision in finding nearest neighbours. The datasets are MNIST (CC BY-SA 3.0), CIFAR-10 (MIT), SIFT10M and GloVe (Apache-2.0). MNIST (LeCun et al., 1998) is a dataset with images of handwriting digits from 0 to 9. Each of the images has a size of 28×28 and is in greyscale. CIFAR-10 (Krizhevsky, 2009) is a dataset with images from ten classes of objects. Each of the images has a size of 32×32 for each RGB channel. SIFT10M (Jegou et al., 2010) also contains vectors representing images but has a smaller dimension (128) and is specifically designed for nearest neighbours search. The GloVe dataset (Pennington et al., 2014) contains pre-trained vectors with a dimension of 300 for word representation, and the vectors have linear substructures in their space. These dataset do not include personally identifiable information or offensive content.

Following the protocol in the experiments by Dasgupta et al. (2017) and Sharma & Navlakha (2018), for each of the datasets, we chose 10,000 samples as an experiment dataset for the nearest neighbours search. In each experiment, m samples from a dataset were used to train the model, then 1000 samples were randomly chosen for querying. For each of the query sample, we listed the 200 samples with the smallest hamming distances to the query sample, then compared the list with the true neighbours list found according to their Euclidean distances. We report the results for the three DevFly methods with different hyperparameters, that is, varying k, m and α. Each of the tests with a specific combination of hyperparameters was repeated 10 times for statistical results. For comparison, we also run the random FlyLSH described by Dasgupta et al. (2017) on the same datasets. Because the original code by Dasgupta et al. (2017) is not available, we used code published by the same research group (Sharma & Navlakha, 2018) to implement these methods. We noticed that the performances reported for FlyLSH are not consistent in those two papers. Hence, comparisons are based on our experimental results only. For reference, both Fly methods consistently outperform a traditional LSH (Hutchins, 1999) if its hash length is set to k.

Note that in some cases, hashing methods include additional steps to increase performance. For example, multi-bin search by Kamel et al. (2015), a two-step evaluation is used to find the nearest neighbours: (1) the hash is used to find the bins that contain similar samples, (2) nearest neighbours are determined according to other information, which can be the raw data. The second step can significantly improve the accuracy. Other methods compute several hash tables and use them to compare across different results for the same query. The models used here only focus on the first step, and were trained only by learning some samples once, so the precision is expected to be lower than state-of-the-art hashing. Adding additional steps is still feasible to further improve the performance.

4.1 Query time

An LSH using a sparse binary code based on WTA has an advantage in query time. Because the number of activating coding dimensions is fixed, to carry out a nearest neighbour search query for a given sample it is not necessary to compare all of the coding dimensions. Instead, it is sufficient to just compare those coding dimensions which are activated (coded as 1) by the query sample. Hence, the query time will scale with k rather than with m. This provides a potential advantage over DenseFly (Sharma & Navlakha, 2018). DenseFly varies from FlyLSH by not using top-k WTA but instead using a threshold to set code elements to 1 or 0. As we show in figure 3 the mean average query time for Method 1 using a fixed sparseness, i.e., $k = m/20$ is significantly lower. The same

Figure 3: The search speed advantage of using a sparse code (Method 1) instead of a dense code (DenseFly). Tested on MNIST with 10000 samples. The search time is the time taken for 1000 queries. They were repeated for 10 times to compute the average and variance. Each query retrieves 200 nearest neighbours. Hash codes of all the samples, including the query samples, were computed before the queries; for Method 1, the sparse coding uses a fixed $k = m/20$. Please note the 10 repeats were executed at the same time in parallel to simulate concurrent queries, so a much shorter time is expected if the repeats are sequential. Tested on a computer running Ubuntu 20.04 with Intel®Core™i9-10940X CPU with 28 hyperthreading logical cores.

Figure 4: Performance on four datasets. 10000 samples were taken from each dataset for the tests. 1000 queries for 200 nearest neighbours were made for the means and variances. $m = 20k$, $\alpha = 0.1$.

advantage applies to our other developmental methods (and to the original FlyLSH) as they also use top-k WTA for binarisation.

4.2 Search accuracy

DevFly methods are tested on four datasets and the mean Average Precision (mAP) for nearest neighbour query is shown is Figure 4. In these experiments, $\alpha = 0.1$, sparseness $m/k = 20$, but k varies. We also tested the effects of reducing α or increasing sparseness by using setting $m/k = 40$. The results are shown in supplementary Figures S.1 to S.4.

All the developmental methods show a similar performance on MNIST, and perform better than FlyLSH for all k. For MNIST, the relative improvements range from 9% for $k = 32$ to 106% for $k = 2$, even with Method 1, in which the connections are made without any criteria for choosing the samples used to determine the connections.

For the other datasets, at least one developmental method outperforms FlyLSH, although which method performs best varies with the dataset. Notably for GloVe, the randomness introduced in Method 3 produces no improvement on performance over FlyLSH. For CIFAR-10, both the improvement with DevFLY methods and the overall performance are relatively low. This might be caused by the different complexity of this dataset compared to MNIST. CIFAR-10 has larger dimension, $d = 32 \times 32 \times 3 = 3072$, than MNIST, $d = 28 \times 28 = 784$. More crucially, for MNIST, the information for distinguishing the digits is clearly given by the highest intensity pixels, so our method which forms connections based on intensity will correspond to the key distinguishing features

Figure 5: (A) Cumulative sum of explained variances of the principal components of the four datasets, plus a randomly generated dataset with a uniform distribution. (B) Magnitude variances of the samples across the same datasets. The y-axis is plotted in log scale.

of the data. For illustration, we can visualise the weights for 100 KCs formed by Method 2 after 320 steps of development which clearly reflect the structure of the data (Figure S.6). Images in CIFAR-10 are photos of real objects, which have richer and more complex details than images in MNIST, and the pixels with the strongest intensities are not necessarily the most informative, e.g. they might be part of the background, corresponding to sky.

Higher performance of the models on MNIST and SIFT10M than on GloVe is due to the data being more clustered in MNIST and SIFT10M, making it easier to separate the nearest neighbours, where the separation is more arbitrary the more distributed the samples are in space. Indeed, none of the models were able to find more than 10% of the nearest neighbours when tested on a randomly generated dataset with an uniform distribution (see Section S.4). We analysed the principal components of these five datasets, and found that the datasets requiring fewer components to capture a high percentage of the the data generally resulted in better performances (Figure 5A). However, for CIFAR-10 the problem appears not to be lack of clustering but rather to a high variance in magnitudes across the samples (Figure 5B). This results in lower performance following the WTA operation, which is not sensitive to differences in magnitudes. This means that samples that vary only in magnitude will be mapped to the same hash, which will distort the original topology of the samples in the input space. Therefore, LSH methods would perform best on datasets that are clustered and samples that lie on a hypersphere.

4.3 Learning efficiency

There are many existing methods for tuning the projection matrix in LSH, and the methods can be categorised into three groups, unsupervised, supervised, and semisupervised. These methods can also be further categorised according to the levels of supervised information, linearity, one-shot/multiple-shot. For a comprehensive review, see the survey by Wang et al. (2016). Among them, we have not found a development based method.

Another alternative approach to optimising PN-KC connections for an MB inspired hashing model is BioHash (Ryali et al., 2020). BioHash proposed a method similar to self-organising mapping to train a modified version of FlyLSH, which uses a dense connection matrix and continuous values instead of binary values for mapping. We modified BioHash in order to have the same number of active KCs as DevFly and FlyLSH. We find that BioHash takes much more time to reach the same precision level as either Method 1 or Method 2 (Figure 6). Only 320 iterations were needed for DevFly versus 10,000 iterations for BioHash to reach the same performance level. In application, fast convergence of the model helps for timeliness. For huge multi-dimensional datasets, the bigger the dataset, the stricter the computational requirements are, and thus DevFly can be used in cases where BioHash is too costly. This also means that DevFly is more suitable for cases where the available training data is scarce.

Figure 6: Performance over training time for Method 1 and Method 2 versus BioHash. Note that the scale of the x-axis is semilog; it is linear from 0 to 10^{-2} and logarithmic for the rest of the range.

4.4 Insensitivity to sample order

We also tested DevFLY with ordered samples to check if training with non-random samples would impact performance. Because the original MNIST dataset is in a random order, we sorted 10000 samples according to their labels. Then, in Method 1, m samples are randomly chosen from the ordered data and used to form the successive connections to KCs while maintaining their labelling order. For Methods 2 and 3, in training, all samples labelled 0 were fed to the model, then all samples labelled 1 were fed, etc. The threshold for choosing if a sample is used to make new connections means that Methods 2 and 3 will typically pass through all samples several times before all KCs are connected. The results suggest that for all three methods, the order does not impact the performance (Figure S.5). Hence, training with a development-like approach, which only builds new connections and keeps the existing connections, helps to reduce the sensitivity to the order of samples. Note that FlyLSH results are not impacted by the order of samples simply because it does not use the dataset at all in initialising the matrix R.

5 Discussion

In this paper, we proposed a method to improve the performance of FlyLSH by developmental initialisation of its binary connections from input dimensions to code dimensions. This was inspired by biological data showing that in the insect mushroom body (the neural circuit that inspired FlyLSH) the connections are not random but there is a process of development in which PNs connect to KCs. We implement this as a simple wiring process driven by the highest values in data samples. We show this improves the performance of FlyLSH in a range of nearest neighbour search tasks. Essentially, FlyLSH detects features of the input space and represents them in a sparse high dimensional code. Using random connections can result in detectors for features that do not exist in the dataset, whereas DevFLY constructs the feature detectors from samples in the dataset, hence improves the efficiency of the coding for non-uniform dataset. The advantage provided by DevFLY diminish as the feature space gets larger (Table S.3, S.3, and S.4) as the random method covers more of the space.

There are many known methods for optimising the (sparse) connectivity between layers to preserve locality (or other desired) properties of the data. However most of these require multiple passes through a large and representative sample from the dataset and are significantly more costly to compute. The method we use here is aimed at scenarios - such as real brains - where 'rewiring' is costly, and a method that requires all weights to be adjusted for each new sample is expensive, as well as potentially disruptive as each new input changes the existing encoding.

The improvement in performance of DevFly over FlyLSH is due to an overlap between the regions with highest variance and those with highest intensity (Figure S.7). Essentially, our method assumes that the strongest signals in the input dimensions correspond to the most relevant signals for similarity (here defined as Euclidean distance in the input data). In CIFAR-10, the dimensions containing the highest intensity pixels don't overlap with the dimensions that vary the most (Figure S.7). By relying on the highest pixel activations to produce the hash, the most important dimensions in CIFAR-10 will be overlooked, leading to poor results. For the other datasets, where high intensity pixels coincide with high variance, DevFly has an advantage because it disregards those areas with low variance,

whereas FlyLSH sampling randomly will weight them equally. Hence a possible way to improve performance in this case would be to pre-process the data to extract the features relevant to similarity - in a sense this is what we see already for SIFT10M.

Our results also show this method is better suited to datasets that are clustered, have samples with a relatively constant norm, and in general have higher values in those input dimensions that are relevant to the similarity measure. For consistency with previous work we have used Euclidean distance in the input space as the 'ground truth' for similarity, but note this may not be the best measure for datasets such as CIFAR-10. Of interest is whether our method could be adapted to develop wiring from the input dimensions that show most correlated variability to the code dimensions. For example, wiring from the changing pixels of a security camera video.

The fact that a weight in DevFly methods only updates once for the entire life of the model facilitates the implementation of this model to hardware. For example, programmable ROM, which permits data to be written to memory only once, can be used to save the weights while learning. It is also easy to be implemented on an integrated circuit with minimum die size usage. The implementation of Method 3 on hardware does not necessarily need a random number generator. In fact, Method 3 suggests that for datasets like CIFAR-10, variation that naturally results from unreliable hardware can be an advantage for better generalisation, providing higher fault tolerance for hardware.

In the insect MB and the mammal cerebellum, sparse coding is used to extract and separate low-level features across different neurons (Olshausen & Field, 2004; Farris, 2011). Hence, DevFLY should also be suitable to improve the detection of low-level features in shallow layers of a deep net, such as the deep net used by Chancan et al. (2020) for place recognition. Error propagation-based approaches have difficulties to train shallow layers due to averaging of the gradient during propagation. Although there are some tricks like ResNet to convey more information by shortcut connections, it is worth considering the use of an unsupervised approach to update shallower layers directly according to data samples. Importantly, a developmental training approach provides more stable signals for deeper layers during training as it does not alter existing connections.

A particular application of this model of interest to us in future is reinforcement learning (RL). An approach to improve exploration efficiency in RL is to count visited states for computing the novelty. For continuous tasks or tasks with high-dimensional observations, using the raw observation as a state to count is not feasible. Tang et al. (2017) proposed a model that uses LSHs instead of the raw observation for state counting which achieved "surprisingly good results". They claimed that static hash methods such as SimHash perform worse than methods that can learn from data, such as autoencoders. However, they also argued that it is important to keep the mapping from states to codes relatively consistent over time, otherwise the same state could be mapped to different codes by training. DevFly suits this application because each weight only updates once so the learned coding dimension never changes, i.e., improving coding quality while minimising unnecessary change.

This work emphasises the development of connections and can belong to a special case of optimisation, which does not have a direct negative societal impact.

References

Ardin, P., Peng, F., Mangan, M., Lagogiannis, K., & Webb, B. (2016). Using an Insect Mushroom Body Circuit to Encode Route Memory in Complex Natural Environments. *PLoS Computational Biology*, *12*, 1–22. doi:doi: 10.1371/journal.pcbi.1004683.

Bennett, J. E., Philippides, A., & Nowotny, T. (2021). Learning with reinforcement prediction errors in a model of the Drosophila mushroom body. *Nature Communications 2021 12:1*, *12*, 1–14. URL: https://www.nature.com/articles/s41467-021-22592-4. doi:doi: 10.1038/s41467-021-22592-4.

Caron, S. J. C., Ruta, V., Abbott, L. F., & Axel, R. (2013). Random convergence of olfactory inputs in the Drosophila mushroom body. *Nature*, *497*, 113–7. URL: http://www.ncbi.nlm.nih.gov/pubmed/23615618. doi:doi: 10.1038/nature12063. arXiv:NIHMS150003.

Chancan, M., Hernandez-Nunez, L., Narendra, A., Barron, A. B., & Milford, M. (2020). A Hybrid compact neural architecture for visual place recognition. *IEEE Robotics and Automation Letters*, *5*, 993–1000. doi:doi: 10.1109/LRA.2020.2967324. arXiv:1910.06840.

Dasgupta, S., Stevens, C. F., & Navlakha, S. (2017). A neural algorithm for a fundamental computing problem. *Science*, *358*, 793–796. URL: http://science.sciencemag.org/https://www.sciencemag.org/lookup/doi/10.1126/science.aam9868. doi:doi: 10.1126/science.aam9868.

389 Delahunt, C. B., & Kutz, J. N. (2019). Putting a bug in ml: The moth olfactory network learns to read mnist.
390   *Neural Networks*, *118*, 54–64.

391 Eichler, K., Li, F., Litwin-Kumar, A., Park, Y., Andrade, I., Schneider-Mizell, C. M., Saumweber, T., Huser,
392   A., Eschbach, C., Gerber, B., Fetter, R. D., Truman, J. W., Priebe, C. E., Abbott, L. F., Thum, A. S., Zlatic,
393   M., & Cardona, A. (2017). The complete connectome of a learning and memory centre in an insect brain.
394   *Nature*, *548*, 175–182. URL: `http://www.nature.com/doifinder/10.1038/nature23455`. doi:doi:
395   10.1038/nature23455.

396 Elkahlah, N. A., Rogow, J. A., Ahmed, M., & Clowney, E. J. (2020). Presynaptic developmental plasticity allows
397   robust sparse wiring of the drosophila mushroom body. *eLife*, *9*, 1–32. doi:doi: 10.7554/eLife.52278.

398 Farris, S. M. (2011). Are mushroom bodies cerebellum-like structures? *Arthropod Structure and Development*,
399   *40*, 368–379. URL: `http://dx.doi.org/10.1016/j.asd.2011.02.004`. doi:doi: 10.1016/j.asd.2011.02.
400   004.

401 Honegger, K. S., Campbell, R. A., & Turner, G. C. (2011). Cellular-resolution population imaging reveals
402   robust sparse coding in the drosophila mushroom body. *Journal of Neuroscience*, *31*, 11772–11785. URL:
403   `http://www.r-project.org`. doi:doi: 10.1523/JNEUROSCI.1099-11.2011.

404 Huerta, R., Nowotny, T., García-Sanchez, M., Abarbanel, H. D., & Rabinovich, M. I. (2004). Learning
405   classification in the olfactory system of insects. *Neural computation*, *16*, 1601–1640.

406 Hutchins, C. J. (1999). Similarity Search in High Dimensions via Hashing. In *the 25th VLDB Conference* (pp.
407   311–312). volume 87.

408 Jegou, H., Douze, M., & Schmid, C. (2010). Product quantization for nearest neighbor search. *IEEE transactions
409   on pattern analysis and machine intelligence*, *33*, 117–128.

410 Kamel, A., Mahdy, Y. B., & Hussain, K. F. (2015). Multi-bin search: improved large-scale content-based image
411   retrieval. *International Journal of Multimedia information Retrieval*, *4*, 205–216.

412 Krizhevsky, A. (2009). *Learning Multiple Layers of Features from Tiny Images*. Technical Report.

413 LeCun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-based learning applied to document recognition.
414   *Proceedings of the IEEE*, *86*, 2278–2323. doi:doi: 10.1109/5.726791.

415 Lee, T., Lee, A., & Luo, L. (1999). Development of the Drosophila mushroom bodies: Sequential generation of
416   three distinct types of neurons from a neuroblast. *Development*, *126*, 4065–4076. doi:doi: 10.1242/dev.126.
417   18.4065.

418 Litwin-Kumar, A., Harris, K. D., Axel, R., Sompolinsky, H., & Abbott, L. F. (2017). Optimal Degrees of Synaptic
419   Connectivity. *Neuron*, *93*, 1153–1164.e7. URL: `http://dx.doi.org/10.1016/j.neuron.2017.01.030`.
420   doi:doi: 10.1016/j.neuron.2017.01.030.

421 Ma, C., Gu, C., Li, W., & Cui, S. (2020). Large-scale image retrieval with sparse binary projections. In
422   *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information
423   Retrieval* (pp. 1817–1820).

424 Macleod, C., & Maxwell, G. M. (2001). Incremental evolution in ANNs: Neural nets which grow. *Artificial
425   Intelligence Review*, *16*, 201–224. doi:doi: 10.1023/A:1011951731821.

426 Marsland, S., Shapiro, J., & Nehmzow, U. (2002). A self-organising network that grows when required.
427   *Neural Networks*, *15*, 1041–1058. URL: `https://www.sciencedirect.com/science/article/pii/`
428   `S0893608002000783`. doi:doi: https://doi.org/10.1016/S0893-6080(02)00078-3.

429 Masuda-Nakagawa, L. M., Tanaka, N. K., & O'Kane, C. J. (2005). Stereotypic and random patterns of
430   connectivity in the larval mushroom body calyx of Drosophila. *Proceedings of the National Academy of
431   Sciences of the United States of America*, *102*, 19027–19032. URL: `www.pnas.orgcgidoi10.1073pnas.`
432   `0509643102`. doi:doi: 10.1073/pnas.0509643102.

433 Mixter, J., & Akoglu, A. (2020). Growing Artificial Neural Networks, . URL: `http://arxiv.org/abs/2006.`
434   `06629`. arXiv:2006.06629.

435 Mosqueiro, T. S., & Huerta, R. (2014). Computational models to understand decision making and patternrecog-
436   nition in the insect brain. *Current Opinion in Insect Science*, *6*, 80–85. doi:doi: 10.1016/j.cois.2014.10.005.

437 Olshausen, B. A., & Field, D. J. (2004). Sparse coding of sensory inputs. *Current Opinion in Neurobiology*, *14*,
438   481–487. doi:doi: 10.1016/j.conb.2004.07.007.

Pehlevan, C., Genkin, A., & Chklovskii, D. B. (2017). A clustering neural network model of insect olfaction. In *2017 51st Asilomar Conference on Signals, Systems, and Computers* (pp. 593–600). IEEE.

Peng, F., & Chittka, L. (2017). A Simple Computational Model of the Bee Mushroom Body Can Explain Seemingly Complex Forms of Olfactory Learning and Memory. *Current Biology*, *27*, 224–230. URL: `http://dx.doi.org/10.1016/j.cub.2016.10.054`. doi:doi: 10.1016/j.cub.2016.10.054.

Pennington, J., Socher, R., & Manning, C. D. (2014). Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)* (pp. 1532–1543).

Platt, J. (1991). A resource-allocating network for function interpolation. *Neural computation*, *3*, 213–225.

Preissner, S., & Herbelot, A. (2019). To be fair: a case for cognitively-inspired models of meaning. In *CLiC-it*.

Reilly, D. L., Cooper, L. N., & Elbaum, C. (1982). A neural model for category learning. *Biological cybernetics*, *45*, 35–41.

Ryali, C. K., Hopfield, J. J., Grinberg, L., & Krotov, D. (2020). Bio-inspired hashing for unsupervised similarity search. *37th International Conference on Machine Learning, ICML 2020*, *PartF16814*, 8265–8276. `arXiv:2001.04907`.

Sharma, J., & Navlakha, S. (2018). Improving similarity search with high-dimensional locality-sensitive hashing. `arXiv:1812.01844`.

Smith, D., Wessnitzer, J., & Webb, B. (2008). A model of associative learning in the mushroom body. *Biological Cybernetics*, *99*, 89–103. doi:doi: 10.1007/s00422-008-0241-1.

Tang, H., Houthooft, R., Foote, D., Stooke, A., Chen, X., Duan, Y., Schulman, J., De Turck, F., & Abbeel, P. (2017). #Exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems* (pp. 2754–2763). volume 2017-Decem. `arXiv:1611.04717`.

Treves, A., & Rolls, E. T. (1991). What determines the capacity of autoassociative memories in the brain? *Network: Computation in Neural Systems*, *2*, 371–397. doi:doi: 10.1088/0954-898X_2_4_004.

Wang, J., Liu, W., Kumar, S., & Chang, S. F. (2016). Learning to hash for indexing big data - A survey. *Proceedings of the IEEE*, *104*, 34–57. doi:doi: 10.1109/JPROC.2015.2487976. `arXiv:1509.05472`.

Wessnitzer, J., Young, J. M., Armstrong, J. D., & Webb, B. (2012). A model of non-elemental olfactory learning in Drosophila. *Journal of Computational Neuroscience*, *32*, 197–212. doi:doi: 10.1007/s10827-011-0348-6.

Xu, K., & Qiao, Y. (2018). Randomized sampling-based fly local sensitive hashing. In *2018 25th IEEE International Conference on Image Processing (ICIP)* (pp. 1293–1297). IEEE.

Yingwei, L., Sundararajan, N., & Saratchandran, P. (1998). Performance evaluation of a sequential minimal radial basis function (rbf) neural network learning algorithm. *IEEE Transactions on neural networks*, *9*, 308–318.

Zavitz, D., Amematsro, E. A., Borisyuk, A., & Caron, S. J. (2021). Connectivity patterns that shape olfactory representation in a mushroom body network model. *bioRxiv*, . URL: `https://www.biorxiv.org/content/early/2021/08/16/2021.02.10.430647`. doi:doi: 10.1101/2021.02.10.430647. `arXiv:https://www.biorxiv.org/content/early/2021/08/16/2021.02.10.430647.full.pdf`.

Zhu, L., Mangan, M., & Webb, B. (2021). SPATIO-temporal memory for navigation in a mushroom body model. In *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)* (pp. 415–426). volume 12413 LNAI. URL: `https://doi.org/10.1101/2020.10.27.356535`. doi:doi: 10.1007/978-3-030-64313-3_39.