HyperQuery: A Framework for Higher Order Link Prediction

Abstract

Groups with complex set intersection relations are a natural way to model a wide array of data, from the formation of social groups to the complex protein interactions which form the basis of biological life. While graphs are a natural way to represent complex networks and are well studied, typical approaches to modeling group membership using graphs are lossy. Hypergraphs are a more natural way to represent such "higher order" relationships, but efforts to apply machine learning techniques to hypergraph structured datasets have been limited thus far. In this paper, we address the problem of link prediction in knowledge hypergraphs as well as simple hypergraphs and develop a novel, simple, and effective optimization architecture to solve this task. Additionally, we study how integrating data from node-level labels can improve the results of our system. Our self-supervised approach achieves significant improvement over state of the art results on several hyperedge prediction and knowledge hypergraph completion benchmarks.

1 Introduction

There is a significant demand for applying learning to graph structured data over the past couple of years. While graphs can accurately model binary relations between entities, they are not a natural representation of n-ary relations between entities. For example, a protein complex network cannot be represented by a graph since a protein complex might be created only in a presence of more than two proteins Giurgiu et al. (2019).

Hypergraphs are a generalization of graphs for representing such n-ary relations. Formally, a hypergraph H is a tuple (V, E) where V is a set of *nodes*; $E \subseteq 2^{|V|}$ is a set of nonempty subsets of V called *hyperedges*. Similarly, a *knowledge hypergraph* is a generalization of a knowledge graph where relations are between any number of entities. Recent research shows that hypergraph models produce more accurate results even in problems in which graphs are used to represent n-ary relations Zhou et al. (2006); Feng et al. (2020); Fatemi et al. (2019).

In this paper, we set out to study *Learning on Hypergraphs*. Specifically, we focus on the task of *hyperedge prediction* on both simple and knowledge hypergraphs. Hyperedge prediction in simple hypergraphs is analogous to link prediction in graphs, and can be formally defined as follows: *given a hypergraph $H = (V, E)$ and a k-tuple of nodes $(v_1, v_2, ..., v_k)$, predict whether this tuple forms a hyperedge or not*. While link prediction in graphs is a well-studied problem, hyperedge prediction has not received adequate attention in spite of its many applications. For example, it can be used to predict new protein complexes, drug-drug interactions, new collaborations in citation networks, discover new chemical reactions in metabolic networks, etc. Yadati et al. (2020); Giurgiu et al. (2019); Piñero et al. (2019). Hyperedge prediction is a more challenging problem than link prediction in graphs. Formulating this problem as a link prediction problem in graphs is a lossy operation, reducing the accuracy of predictions Kirkland (2017); Tu et al. (2018).

In knowledge hypergraphs, it is often necessary to not only predict new hyperedges but also their type. For example, in a protein-drug genomics knowledge hypergraph, it is important to predict not only drug-drug interactions but also the type of these interactions that describes the side effects Zitnik et al. (2018). This generalized hyperedge prediction problem can be described formally as follows: *given a knowledge hypergraph $KH = (\mathcal{E}, \mathcal{R})$ and a tuple of entities $(e_1, e_2, ..., e_k)$, we want to predict if this tuple forms a hyperedge and if so, what its type is*. This problem setting is illustrated in figure 1.

Figure 1: The HyperQuery Inference Problem: In this project, we prefer to work with the *star-expansion* representation of a hypergraph (*left*). In particular we are interested in studying hypergraphs as well as knowledge hypergraphs with categorical labels (types) stored on the edges (*center*). Our primary objective is to create a system that predicts the existence of a hyperedge and its type.

This paper makes the following contributions.

- **HyperQuery:** We describe *HyperQuery*, a neural message passing based framework that is designed to find embeddings of hyperedges in a semi-supervised fashion.
- **Novel feature extraction:** We use clustering to extract global features of nodes and hyperedges.
- **Higher order link prediction:** We solve hyperedge prediction on simple hypergraphs as well as knowledge hypergraphs.

The pipeline of our system is shown in figure 3.

2 RELATED WORK

Link prediction in graphs: There are two ways to address the link prediction problem in networks. One approach is to learn an embedding of the nodes of a graph and then apply a function on these embeddings to obtain the embedding of an edge. We call this approach an *indirect* approach to solve hyperedge prediction. For example, node2vec Grover & Leskovec (2016), and deepwalk Perozzi et al. (2014) are random-walk based approaches and Vashishth et al. (2019); Davidson et al. (2018) are GNN-based approaches for graphs that learn the embedding of the nodes and then use a binary operator such as average to compute the embedding of an edge i.e. given two nodes u, and v, they apply binary operator o to generate an embedding of $g(u, v)$ such that $g : V \times V \longrightarrow \mathcal{R}^d$ where d is the dimension of the embedding. *Direct* approaches in graphs learn the embedding of edges directly and apply that to the link prediction problem. Examples of this approach includes path-based approaches such as Zhu et al. (2021); Sadeghian et al. (2019). One popular task in knowledge graphs is to predict missing relations between entities. This task is called knowledge graph completion and one could think of it as a generalization of link prediction in graphs. The problem of knowledge graph completion has been studied extensively for example: Zhu et al. (2021); Wang et al. (2020); Rossi et al. (2022).

Hyperedge prediction: Link prediction in hypergraphs can also be done indirectly by first computing the embedding of the nodes of the hypergraph and then applying a function g to the tuple $(v_1, v_2, ..., v_k)$ to obtain the embedding of the tuple i.e. hyperedge. The difficulty with such models is that for hypergraphs, function g must be nonlinear to capture higher-order proximity of nodes in the hypergraph Tu et al. (2018). This means it is not a good design choice to use an operator such as average to obtain the embedding of a hyperedge from its nodes. Related works HyperSAGNN and NHP have used non-linear functions such graph neural networks Zhang et al. (2020); Yadati et al. (2020) to compute the embedding of a hyperedge from its nodes. Directly learning the embedding of a hyperedge and applying hyperedge prediction to that embedding has not been studied. To the best of our knowledge, we are the first to approach the problem in this manner.

Link prediction in knowledge hypergraphs is relatively under explored. Most approaches generalizes knowledge graph based methods to work with n-ary relations. More recent work on this area propose

Figure 2: Diffusion of Categorical Labels beats Random Walks: (*left*) In a high degree hypergraph, an individual random walk might mix very quickly. There have been a number of attempts to generalize node2vec features to hypergraphs, but one fundamental limitation is in the case of highly interconnected hypergraphs, even a biased random walk quickly begins to look like a random stream of nodes. (*right*) We propose a radically different approach to computing hyperedge embeddings. Instead of using a random walk based approach to approximate intrinsic distance, we learn to answer HyperQueries by first labeling highly correlated neighborhoods of hypergraph nodes and edges as distinct communities using an existing hierarchical clustering tool. (*In the paper*), we discuss how we then diffuse these categorical cluster labels and then invert this representation with an MLP to train a model to achieve state of the art performance in HyperQuery Inference.

novel methods that directly works with knowledge hypergraphs such as Fatemi et al. (2019); Wang et al. (2021).

Random Walk Based Feature Generation for hypergraphs: In problems in which nodes do not have features, the first step is to generate features for the nodes. The most common approach is to use node2vec. For example, HyperSAGNN Zhang et al. (2020) first generates features using node2vec and then passes these features through an attention layer. During inference, the embedding of a proposed tuple of nodes is computed using a one layer, position-wise feed-forward network. They can also use the corresponding row of the adjacency matrix to extract features. Similarly, NHP runs node2vec on the clique expansion of a hypergraph and then uses a GCN layer to improve these features. Finally, they pass these embeddings to a scoring layer Yadati et al. (2020).

Clustering Based Feature Generation: Random-walk based approaches are one way to generate features for a hypergraph, but they only exploit the local connectivity of nodes in the hypergraph. In this paper, we investigate the effectiveness of hypergraph clustering algorithms for feature extraction.

Clustering has been used to understand the structure of complex networks. A cluster in a hypergraph is a partition of nodes into sets that are similar to each other and dissimilar from the rest of the hypergraph. Intuitively, a cluster is a group where nodes are densely inter-connected and sparsely connected to other parts of the network. Placing the embedding of such nodes closely in the embedding space can be useful in many graph mining tasks such as clustering, node classification, network reconstruction and link prediction Bhowmick et al. (2020). A classic clustering algorithm in hypergraphs is the *FM* Fiduccia & Mattheyses (1982) algorithm: given an initial assignment of nodes to clusters, this algorithm moves a node to the cluster that results in the largest reduction in connectivity between clusters. Multi-level clustering approaches such as Karypis et al. (1999); Devine et al. (2006); Maleki et al. (2021) build on this algorithm and improve the performance of FM algorithm by successively coarsening the hypergraph, finding clusters in the smallest hypergraph, and then interpolating these to the coarser hypergraphs, applying the FM algorithm at each level. In this paper, we use a recent work called BiPart, Maleki et al. (2021), for clustering to generate initial features of the hyperedges as well as nodes of a hypergraph.

3   Defining Harmonic HyperQuery Statistics

We begin with the question of how one might build a system to "answer" HyperQueries. Ultimately our goal is to accurately predict a boolean existance bit for every set in the powerset of nodes, i.e. to create a system for hyperedge prediction. However, in this section we start by studying the question of inference in knowledge hypergraphs, where a vector of data is stored on labeled entities and relations. We present an approach for defining trainable convolutions on hyperedges which is well suited for performing inference for knowledge hypergraph completion. In the next section we will discuss the pre-processing approach that completes our framework for performing hyperedge prediction on unlabeled hypergraphs.

Figure 3: A HyperEdge Convolution Operator: (*left*) We first illustrate our process for calculating the *harmonic statistic* of a HyperEdge. Suppose we are given a "colored" hypergraph with vector-valued data encoded on nodes and hyperedges. A *HyperQuery HQ* can be passed as input by specifying a set of nodes q into the system (*left half*), or as an edge that is already in the system (*right half*). For each node $v_i \in q$, we aggregate over its "interests", computing $AGG(N(v_i))$. (*Left, Blue Circle*) After aggregation, our query has been transformed into a set of high dimensional vectors. This set of vectors is reduced by *summary function* Ω, (See Section 5.2 for more details)) to compute what we call the *harmonic statistic* of HQ. (*right*) By adding a fully connected layer W^k and a nonlinearity σ in series with this calculation, *we arrive* at our proposed HyperEdge convolution operator. Here we would like to highlight that our edge convolution operator convolves *relation level* data, requiring only local aggregation over a small effective neighborhood of node data which can be implemented efficiently with a GCN style message passing system.

Our basic approach for defining a HyperEdge (or HyperQuery) convolution operator proceeds in two steps. First, we set out to aggregate and summarize the known label data in the neighborhood of the edge e or query set of node q in question. Our approach here is to define a measure we call hs_q^1, the first *Harmonic Statistic* of a query set q, to be a vector in R^n, computed accordingly:

$$h_{v_i}^1 = AGG\left(h_e \forall e \in \mathcal{N}(v_i)\right) \tag{1}$$

$$hs_q^1 = hs(q) = \Omega(h_{v_i}^1 \forall v_i \in q) \tag{2}$$

The $h_{v_i}^1$ above amounts to a "mean-field" embedding of each node v_i as the average of a sampling of the data stored on the hyperedges it is connected to, notated as the neighborhood $\mathcal{N}(v_i)$. Correspondingly, we take AGG to be a component-wise mean operator. Ω is taken as differentiable *summarization* function, we test several choices of this measure in our work.

This concludes the first part of our approach to learning useful representations of HyperQueries. Our formulation is also illustrated in more detail in Figure 3, (*left*). Intuitively, this message passing based aggregation and summarization process can be thought of a *diffusion process* or a *flow*, which averages and symmetrizes the edge level data by effectively performing a step of Laplacian smoothing.

3.1 FROM STATISTICS TO LEARNED CONVOLUTIONS

Second, to fully unlock the power of modern machine learning, we set out to create a trainable system. To this end, we present an operator which can be directly used to attempt to invert from hs_q^1 to its training label in a supervised learning setting.

In fact we propose something more general. A flexible, composable, trainable, hyperedge message-passing based (i.e. scalable), operation for learning to answer HyperQueries:

$$h_v^k = AGG(h_e^{k-1}, \forall e \in \mathcal{N}(v)) \tag{3}$$

$$hs_e^k = \Omega(\{h_v^k \forall v \in \mathcal{N}(e)\}) \tag{4}$$

$$h_e^k = \sigma(W^k \cdot hs_e^k) \tag{5}$$

For each node v in an edge e, we aggregate along it's edge neighbor features to calculate h_v. Then, for each hyperedge e, we aggregate the messages from its nodes (*i.e.*, $h_v \forall v \in \mathcal{N}(e)$), using a *summarization* function $\Omega(.)$ as shown below. Finally, we have a hidden "deconvolution" layer and a non-linearity.

In a knowledge hypergraph, we can effectively learn the hidden weights W^k by choosing the initial feature h_e^0 of a hyperedge h_e to be the one hot vector of its type, and building up an autoencoder

style problem. By repeating this iteration twice, we already arrive at an effective tool for knowledge hypergraph classification which generalizes to unseen data far better than benchmark approaches. In Table 2, we outline our performance relative to other benchmarks. We achieve this performance with a straightforward model, we simply treat the output h_e^2 as a predicted class label $\mathcal{P}(e)$. From there we minimize the loss below as a function of hidden layer weights W^1 and W^2.

$$\mathcal{L} = \sum_{e \in \mathcal{D}} \mathcal{J}(\mathcal{P}(e), \mathcal{G}(e)) \tag{6}$$

In our objective function, we take $\mathcal{J}(.)$ to be the cross entropy loss, e to be a hyperedge in the training dataset $\mathcal{D}$, $\mathcal{P}(e)$ is the predicted type of hyperedge e, and $\mathcal{G}(e)$ is the actual ground truth type of hyperedge e in the dataset.

4 ANSWERING HYPERQUERIES ON SIMPLE HYPERGRAPHS

Our main focus in this paper is the task of *hyperedge prediction*, i.e. given an *unlabeled* hypergraph and set of nodes $(v_1, .., v_n)$, predict whether this tuple forms a hyperedge.

In this setting, there is no additional label data such as knowledge hypergraphs and thus inference must be computed entirely from the graph structure. Thus if we want to make use of a flow based approach, we need a way of computing a useful initialization. Our insight is that useful initial categorical embeddings can be found by existing clustering algorithms, which works by recursively finding balanced cuts of a hypergraph.

4.1 FEATURE EXTRACTION USING CLUSTERING

One way to learn an embedding that captures meaningful structural information about a hypergraph is to run random-walk based algorithms such as node2vec Grover & Leskovec (2016). Previous works on hyperedge prediction such as HyperSAGNN Zhang et al. (2020) and NHP Yadati et al. (2020) use node2vec to first learn feature vectors for nodes of a hypergraph represented in a variety of ways. Then, they improve these features using attention-based methods. However, such methods have a number of drawbacks:

1. They do not learn the correlation between nodes that do not appear in the same random walk, might require many samples to capture effects of weak correlations.

2. Random walks explore only the local properties of the hypergraph, optimization might get stuck in local minima.

3. As noted in Figure 2, random walks on hypergraphs mix very quickly and thus even if an algorithm converges to a good answer, will likely require many samples/computation to converge.

4. The published methods learn node based features and they do not learn feature vector of hyperedges directly, couldn't be directly applied to our architecture.

It occurred to us that instead, it is possible to use state-of-the-art hierarchical partitioning based clustering tools as an alternative approach to pre-computing features. While clustering is a well studied problem in ML, for instance it has been used in prediction as early as in 2015 Deylami & Asadpour (2015), it is not used by any of the state-of-the-art prediction tools today, and therefore, it merits revisiting, given the simplicity and effectiveness of the approach we evaluate in this paper.

In particular, for our HyperQuery flow, we want an initial label assignment that is "smooth" in a way that is well defined for the given hypergraph topology. To do this, we run a clustering algorithm that partitions the nodes of the hypergraph into clusters. Each cluster of nodes is given a unique integer id. To transfer these labels onto hyperedges, we perform a maxpooling step (described in more detail in Figure 4).

4.2 CUT-METRIC FOR HYPERGRAPHS

For our purpose, we can use any clustering algorithm. In our experiments, we use a multilevel clustering algorithm that partitions nodes into a given number of clusters while minimizing the

Figure 4: Generating Useful Labels with Hierarchical Clustering: Not all hypergraph data comes with labels (*left*), but so far our approach has depended on having categorical labels on the edges and nodes. One key novelty of our method relative to prior works is that we leverage existing approaches for clustering to first assign cluster id as labels to the nodes, obtaining an initial cluster assignment ℓ_v^0 (*center*), which we then propagate to the hyperedges via Max Pooling (*right*) in order to obtain the edge cluster assignment ℓ_e^0. We use ℓ_e^0 as the data in $\mathcal{L}(h)$.

hyperedge cut, defined below. While there is not a unique canonical way to define a hyper-edge cut, this approach worked well and exposes the number of clusters as a hyper-parameter to the system.

$$cut(H, C) = \sum_e (\lambda_e(H, C) - 1) \tag{7}$$

Here, H is the hypergraph, C is the partition of nodes into clusters, and $\lambda_e(H, C)$ is the number of clusters that hyperedge e spans. Intuitively, nodes that belong to the same cluster are considered similar. This is similar to approaches like node2vec in which nodes that appear in the same random walk are considered to be similar. Using clustering lets us exploit the global structure of the hypergraph, whereas random walk methods exploit only local information.

5   ADDITIONAL OPTIMIZATIONS

Here we outline two important technical details. The first is that we leverage the fact that we have label data on both nodes and hyperedges by concatenating node labels to aggregated hyperedge vectors. The second is that we find that for the hyperedge prediction task, variance performed better as a choice of Ω whereas in knowledge hypergraph completion, mean worked better.

5.1   MESSAGE PASSING FOR HYPEREDGE PREDICTION

In principle, we can just use the one hot vector of the cluster id of a hyperedge as its initial feature vector. However, this scheme does not capture correlations between different clusters. In particular, if a hyperedge has nodes in several clusters, only the cluster with the largest number of nodes of that hyperedge is represented in the one-hot vector.

To fix this problem, we include the cluster of a node in its feature vector as shown in Equation 8:

$$h_v^k = CONCAT\{AGG\{h_e^{k-1}, \forall e \in \mathcal{N}(v)\}, x_v\} \tag{8}$$

where $AGG(.)$ is an aggregation function, and x_v is the one-hot partition id of a node. If nodes of a hypergraph have features themselves, these features can also be concatenated with x_v.

5.2   CHOOSING THE RIGHT Ω

Broadly, we evaluated three different choices for Ω. A componentwise mean and varience, and a sort of "robust variance" estimator we call *minmax* similar to the one used in NHP. We also augment these aggregations to better capture the correlation between different labels/communities by implementing a bilinear aggregation layer Zhu & Koniusz (2021). Bilinear aggregation has significantly improved visual concepts recognition Koniusz et al. (2017), and in practice generally improves the accuracy of our results.

Our final scheme for hyperedge message passing with both optimizations turned on is the following:

$$h_v^k = CONCAT\{AGG\{h_e^{k-1}, \forall e \in \mathcal{N}(v)\}, x_v\} \tag{9}$$

$$\Omega_e^k = \Omega\{h_v^k, \forall v \in \mathcal{N}(e)\} \tag{10}$$

$$h_e^k = \sigma(W^k \cdot flat(\Omega_e^k \Omega_e^{k^T})) \tag{11}$$

where Ω is an aggregation function, $flat(.)$ flattens the correlation matrix and stores it in a column vector, $AGG(.)$ takes the element-wise mean of the hyperedge feature vector, x_v is the feature vector of node v, and W^k is the trainable weight matrix. The effect of different choices of summary functions Ω is experimentally evaluated in Section 6.

5.3 MODEL EXPLAINABILITY

The ideal initial feature vector for a hyperedge should include local and global properties of the hypergraph. In our model, clustering exposes global properties. Specifically, we keep track of the cluster id of hyperedges as well as the distribution of labels on the nodes in the neighborhood of a hyperedge. Intuitively, Hyperedges that are in the same cluster or have similar label distribution on their nodes are similar to each other and by assumption, they are related. Previous work Grover & Leskovec (2016); Perozzi et al. (2014) has shown that placing such similar nodes closely in the embedding space will facilitate tasks such as node classification and link prediction. We follow the same intuition.

The message-passing scheme of labels is conceptually similar to label propagation Raghavan et al. (2007). The objective of the label propagation algorithm is to assign each node into a cluster with the most number of its neighbouring nodes. Intuitively, this scheme also put hyperedges with the same label/cluster closer in the embedding space facilitating hyperedge prediction for both knowledge hypergraphs and simple hypergraphs.

6 EXPERIMENTS

We evaluate our framework HyperQuery on knowledge hypergraph completion task as well as hyperedge prediction and show that our architecture outperforms the sate of the arts for these tasks. Furthermore, we conduct an ablation study to understand the effectiveness of the major HyperQuery kernels. The details of our setting are in Appendix A.

6.1 KNOWLEDGE HYPERGRAPH COMPLETION

We first evaluate our system for the task of link prediction for knowledge hyperedges i.e. knowledge hypergraph completion. We evaluate our system on three datasets: FB-AUTO, M-FB15K, and JF17K. We used the same test, train, and validation sets as Fatemi et al. (2019). We use MRR (mean reciprocal rank) and Hit@1, 3 (hit ratio with cut-off values of 1 and 3) as our evaluation metrics.

Datasets: The datasets used in this section are standard knowledge hypergraph datasets from previous work Fatemi et al. (2019). The summary of the knowledge hypergraphs are in Table 1. FB-AUTO, M-FB15K Fatemi et al. (2019), and JF17K Wen et al. (2016) are knowledge hypergraphs with n-ary relations that is collected from Freebase dataset.

Table 1: Knowledge hypergraph dataset

DATA SET	$|\mathcal{E}|$	$|\mathcal{R}|$	#train	#valid	#test
FB-AUTO	3,410	8	6,778	2,255	2,180
M-FB15K	10,314	71	415,375	39,348	38,797
JF17K	29,177	327	77,733	15,822	24,915

We compare our results with the following baselines: **HSimplE, and HypE** two embedding based approaches for knowledge hypergraphs introduced by Fatemi et al. (2019). Both methods find the embedding of an entity based on its position in a relation. **M-DistMult** Yang et al. (2014) defines a scoring function for each tuple (e_1, r_1, e_2). We modify this so that each relation could have any number of entities. **M-TransH** is a modified standard knowledge graph scoring function (TranshH) that accepts beyond binary relations. Finally, **M-CP** Hitchcock (1927) is a tensor decomposition approach. We apply a similar approach as Fatemi et al. (2019) to extend it beyond binary relations.

We used HyperQuery to perform knowledge hypergraph completion. Table2 summarizes the result of our experiment. HyperQuery performs the best compared to all other baselines on all metrics.

Figure 5: Performance of HyperQuery for different numbers of clusters.

Specifically, on metric Hit@1 against the best baseline, it improves up to 5% on dataset FB-AUTO, 18% on M-FB15K, and more than 50% on JF17K.

Table 2: Knowledge Hyperedge Completion.

| | FB-AUTO | | | M-FB15K | | | JF17K | | |
	MRR	Hit@1	Hit@3	MRR	Hit@1	Hit@3	MRR	Hit@1	Hit@3
HYPERQUERY	**91.5**	**83.1**	**99.9**	**95.1**	**90.5**	**99.7**	**99.9**	**99.1**	**99.9**
HSIMPLE	79.8	76.6	82.1	73.0	66.4	76.3	47.2	37.8	52.0
HYPE	80.4	77.4	82.3	77.7	72.5	80.0	49.4	40.8	53.8
M-DISTMULT	78.4	74.5	81.5	70.5	63.3	74.0	46.3	37.2	51.0
M-TRANSH	72.8	72.7	72.8	62.3	53.1	66.9	44.4	37.0	47.5
M-CP	75.2	70.4	78.5	68.0	60.5	71.5	39.1	29.8	44.3

6.2 HYPEREDGE PREDICTION

The second task we study in this paper is hyperedge prediction. We evaluate our system on four datasets: iAF1260b, iJO1366, USPTO, and DBLP. We used 70% of the hyperedges in these for test, 10% for validation and 20% for training. The summary of these datasets are in Table 3.

Table 3: Hyperedge prediction dataset

DATA SET	NODES	HYPEREDGES	TYPE OF DATA
IAF1260B	1,668	2,084	METABOLIC REACTIONS
IJO1366	1,805	2,253	METABOLIC REACTIONS
USPTO	16,293	11,433	ORGANIC REACTIONS
DBLP	20,685	30,956	CO-AUTHORSHIP

iAF1260b[1] a metabolic reaction dataset for specie E. coli. We use this dataset for hyperedge prediction where our goal is to predict missing reactions i.e. hypereges. In this dataset each reaction is considered as a hyperedge connecting its participating metabolites (nodes). **iJO1366**[1] a metabolic reaction dataset similar to iAF1260b. **USPTO**[2] a organic reaction dataset. We used a subset of chemical substances that only contains carbon, hydrogen, nitrogen, oxygen, phosporous, and sulphur. **DBLP**[3] a co-authorship publication dataset. We used a subset of papers published in only AI conferences: AAAI, IJCAI, NeurIPS, ICML, CVPR, ICCV, ACL, NAACL, etc. Each author in this dataset is a node and papers represent hyperedges connecting authors of a paper.

We compare our results with previous works: NHP Yadati et al. (2020), HyperSAGNN Zhang et al. (2020), HyperGCN Yadati et al. (2019), and node2vec Grover & Leskovec (2016). The description of these methods are in 2. Motivated by NHP, we investigate another aggregation function Ω for our approach. We call this aggregation function *minmax* which is the element wise difference of max and min values of the embedding vectors in equation 9. Furthermore, we also experiment on using operator *variance* as an aggregation function. These results is summarized in Table 4. We use 16 communities for this experiment. In Section 6.3, we discuss the effect of different number of communities.

HyperQuery with minmax aggregation function performs the best on all datasets in this paper. Comparing with NHP, on their minmax operator, HyperQuery minmax outperform them by up to 7% on iAF1260b, 5% on iJO1366, 1.5% on USPTO, and 1.8% on DBLP; on mean aggregation operator, HyperQuery outperforms NHP by up to 6% on iAF1260b, 4.6% on iJO1366, 12% on USPTO, and 13.6% on DBLP. HyperQuery outperforms HyperSAGNN on all datasets by more than 6%, and HyperGCN by more than 4%. Finally, node2vec results show poor performance on hypergraph datasets showing that graph based approaches are not suitable for hypergraphs.

6.3 ABLATION STUDY

We study the behaviour of each component of HyperQuery. First, we study the effect of bilinear pooling on hyperedge prediction. Table 4, shows this effect. On the larger dataset, USPTO, the bilinear pooling improves the quality of our framework by 5.6% for minmax. Similarly, for DBLP, the improvement is about 2%. On the smaller datasets, bilinear pooling does not make a significant change.

Next, we study the effect of the number of clusters in our dataset. Figure 5 shows how the performance of our framework changes as we increase or decrease the number of clusters. For all datasets except iJO1366, the performance improves as we increase the number of clusters up to 16 clusters and then decreases. This behaviour is expected since as we increase the number of clusters, the quality of these clusters decreases (*i.e.*, the hyperedge cut increases). However, if the number of clusters is very small, we are not exploring the global structure of our hypergraph enough which again decreases the performance of our framework.

Table 4: Area Under Curve (AUC) scores for hyperedge prediction. NOPOOL refers to the model without bilinear pooling.

	IAF1260B AUC	IJO1366 AUC	USPTO AUC	DBLP AUC
HYPERQUERY-MINMAX	72.2	68.5	**75.7**	**72.0**
HYPERQUERY-MEAN	66.5	65.9	72.2	69.6
HYPERQUERY-VAR	71.1	68.1	75.0	71.3
HQ-MINMAX-NOPOOL	**72.7**	**68.9**	70.1	70.4
HQ-MEAN-NOPOOL	67.6	65.7	70.6	65.7
HQ-VAR-NOPOOL	72.3	67.5	74.1	71.6
NHP-MINMAX	64.3	63.2	74.2	69.2
NHP-MEAN	60.5	61.2	65.5	56.4
HYPER-SAGNN	60.1	56.3	67.1	65.2
HYPERGCN-MINMAX	64.0	62.2	70.5	67.4
NODE2VEC-MINMAX	66.0	62.0	71.0	67.0

---

[3] https://github.com/muhanzhang/HyperLinkPrediction
[4] https://github.com/wengong-jin/nips17-rexgen
[5] https://www.aminer.org/citation

REFERENCES

Ayan Kumar Bhowmick, Koushik Meneni, Maximilien Danisch, Jean-Loup Guillaume, and Bivas Mitra. LouvainNE: Hierarchical Louvain Method for High Quality and Scalable Network Embedding *. In *13th ACM International WSDM Conference*, WSDM '20: Proceedings of the 13th International Conference on Web Search and Data Mining, pp. 43–51, February 2020. doi: 10.114 5/3336191.3371800. URL https://hal.archives-ouvertes.fr/hal-02999888.

Tim R. Davidson, Luca Falorsi, Nicola De Cao, Thomas Kipf, and Jakub M. Tomczak. Hyperspherical variational auto-encoders. 2018. doi: 10.48550/ARXIV.1804.00891. URL https://arxiv.org/abs/1804.00891.

Karen D. Devine, Erik G. Boman, Robert T. Heaphy, Rob H. Bisseling, and Umit V. Catalyurek. Parallel hypergraph partitioning for scientific computing. In *Proceedings of the 20th International Conference on Parallel and Distributed Processing*, IPDPS'06, pp. 124–124, Washington, DC, USA, 2006. IEEE Computer Society. ISBN 1-4244-0054-6. URL http://dl.acm.org/citation.cfm?id=1898953.1899056.

Hasti Akbari Deylami and Masoud Asadpour. Link prediction in social networks using hierarchical community detection. In *2015 7th Conference on Information and Knowledge Technology (IKT)*, pp. 1–5, 2015. doi: 10.1109/IKT.2015.7288742.

Bahare Fatemi, Perouz Taslakian, David Vazquez, and David Poole. Knowledge hypergraphs: Prediction beyond binary relations, 2019. URL https://arxiv.org/abs/1906.00137.

Song Feng, Emily Heath, Brett Jefferson, Cliff Joslyn, Henry Kvinge, Hugh D. Mitchell, Brenda Praggastis, Amie J. Eisfeld, Amy C. Sims, Larissa B. Thackray, Shufang Fan, Kevin B. Walters, Peter J. Halfmann, Danielle Westhoff-Smith, Qing Tan, Vineet D. Menachery, Timothy P. Sheahan, Adam S. Cockrell, Jacob F. Kocher, Kelly G. Stratton, Natalie C. Heller, Lisa M. Bramer, Michael S. Diamond, Ralph S. Baric, Katrina M. Waters, Yoshihiro Kawaoka, Jason E. McDermott, and Emilie Purvine. Hypergraph models of biological networks to identify genes critical to pathogenic viral response, 2020. URL https://arxiv.org/abs/2010.03068.

C.M. Fiduccia and R.M. Mattheyses. A linear-time heuristic for improving network partitions. In *19th Design Automation Conference*, pp. 175–181, 1982. doi: 10.1109/DAC.1982.1585498.

M Giurgiu, J Reinhard, B Brauner, I Dunger-Kaltenbach, G Fobo, G Frishman, C Montrone, and A. Ruepp. CORUM: the comprehensive resource of mammalian protein complexes-2019. *Nucleic Acids Research*, 2019.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks, 2016.

Frank L. Hitchcock. The expression of a tensor or a polyadic as a sum of products. *Journal of Mathematics and Physics*, 6(1-4):164–189, 1927. doi: https://doi.org/10.1002/sapm192761164. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/sapm192761164.

George Karypis, Rajat Aggarwal, Vipin Kumar, and Shashi Shekhar. Multilevel hypergraph partitioning: Applications in vlsi domain. *IEEE Trans. Very Large Scale Integr. Syst.*, 7(1):69–79, March 1999. ISSN 1063-8210.

Steve Kirkland. Two-mode networks exhibiting data loss. *Journal of Complex Networks*, 6(2): 297–316, 08 2017. ISSN 2051-1329. doi: 10.1093/comnet/cnx039. URL https://doi.org/10.1093/comnet/cnx039.

Piotr Koniusz, Fei Yan, Philippe-Henri Gosselin, and Krystian Mikolajczyk. Higher-order occurrence pooling for bags-of-words: Visual concept detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(2):313–326, 2017. doi: 10.1109/TPAMI.2016.2545667.

Sepideh Maleki, Udit Agarwal, Martin Burtscher, and Keshav Pingali. Bipart: A parallel and deterministic hypergraph partitioner. *SIGPLAN Not.*, 2021. doi: 10.1145/3437801.3441611.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '14, pp. 701–710, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2956-9. doi: 10.1145/2623330.2623732. URL http://doi.acm.org/10.1145/2623330.2623732.

Janet Piñero, Juan Manuel Ramírez-Anguita, Josep Saüch-Pitarch, Francesco Ronzano, Emilio Centeno, Ferran Sanz, and Laura I Furlong. The DisGeNET knowledge platform for disease genomics: 2019 update. *Nucleic Acids Research*, 48(D1):D845–D855, 11 2019. ISSN 0305-1048. doi: 10.1093/nar/gkz1021. URL https://doi.org/10.1093/nar/gkz1021.

Usha Nandini Raghavan, Reka Albert, and Soundar Kumara. Near linear time algorithm to detect community structures in large-scale networks. *Physical Review E*, 76(3), sep 2007. doi: 10.1103/physreve.76.036106.

Andrea Rossi, Donatella Firmani, Paolo Merialdo, and Tommaso Teofili. Explaining link prediction systems based on knowledge graph embeddings. In *Proceedings of the 2022 International Conference on Management of Data*, SIGMOD '22, pp. 2062–2075, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450392495. doi: 10.1145/3514221.3517887. URL https://doi.org/10.1145/3514221.3517887.

Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. Drum: End-to-end differentiable rule mining on knowledge graphs, 2019. URL https://arxiv.org/abs/1911.00055.

Ke Tu, Peng Cui, Xiao Wang, Fei Wang, and Wenwu Zhu. Structural deep embedding for hyper-networks, 2018.

Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. Composition-based multi-relational graph convolutional networks, 2019. URL https://arxiv.org/abs/1911.03082.

Hongwei Wang, Hongyu Ren, and Jure Leskovec. Relational message passing for knowledge graph completion, 2020. URL https://arxiv.org/abs/2002.06757.

Quan Wang, Haifeng Wang, Yajuan Lyu, and Yong Zhu. Link prediction on n-ary relational facts: A graph-based approach, 2021. URL https://arxiv.org/abs/2105.08476.

Jianfeng Wen, Jianxin Li, Yongyi Mao, Shini Chen, and Richong Zhang. On the representation and embedding of knowledge bases beyond binary relations, 2016. URL https://arxiv.org/abs/1604.08642.

Naganand Yadati, Madhav Nimishakavi, Prateek Yadav, Vikram Nitin, Anand Louis, and Partha Talukdar. Hypergcn: A new method of training graph convolutional networks on hypergraphs, 2019.

Naganand Yadati, Vikram Nitin, Madhav Nimishakavi, Prateek Yadav, Anand Louis, and Partha Talukdar. Nhp: Neural hypergraph link prediction. In *Proceedings of the 29th ACM International Conference on Information and Knowledge Management*, CIKM '20, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450368599. doi: 10.1145/3340531.3411870. URL https://doi.org/10.1145/3340531.3411870.

Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases, 2014. URL https://arxiv.org/abs/1412.6575.

Ruochi Zhang, Yuesong Zou, and Jian Ma. Hyper-SAGNN: a self-attention based graph neural network for hypergraphs. In *International Conference on Learning Representations (ICLR)*, 2020.

Dengyong Zhou, Jiayuan Huang, and Bernhard Schölkopf. Learning with hypergraphs: Clustering, classification, and embedding. In B. Schölkopf, J. Platt, and T. Hoffman (eds.), *Advances in Neural Information Processing Systems*, volume 19. MIT Press, 2006. URL https://proceedings.neurips.cc/paper/2006/file/dff8e9c2ac33381546d96deea9922999-Paper.pdf.

Hao Zhu and Piotr Koniusz. Graph convolutional network with generalized factorized bilinear aggregation, 2021. URL `https://arxiv.org/abs/2107.11666`.

Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal Xhonneux, and Jian Tang. Neural bellman-ford networks: A general graph neural network framework for link prediction, 2021. URL `https://arxiv.org/abs/2106.06935`.

Marinka Zitnik, Monica Agrawal, and Jure Leskovec. Modeling polypharmacy side effects with graph convolutional networks. *Bioinformatics*, 34(13):457–466, 2018.

A   ADDITIONAL INFORMATION FOR HYPEREDGE PREDICTION

Table 5 shows the mean test auc and standard deviation over 10 different train-test splits. We compare *HyperQuery* with two other state of the art baseline methods. We find that our approach outperforms the other methods by a large margin, with high confidence.

Augmented HyperQuery Classifier (Baseline): As discussed in the main paper, we evaluate the baseline that treats hyperedge prediction problem as a classification task where we add an extra label in our dataset that represents the negative hyperedges (hyperedges that do not exist) and use our classification framework without community detection.

HyperQuery-minmax: The best performing hyperedge prediction formulation presented in this paper. We use operator *minmax* for the Ω aggregation function. We use 16 communities for our community detection step.

NHP-minmax: GCN based hyperedge prediction that can be used for directed and undirected hypergraphs. We used the minmax operator for this approach as well.

HyperSAGNN: A self attention approach for hyperedge prediction that can only be used for undirected hypergraphs. We used random-walk basd approach.

Comparing the performance of *HyperQuery* with the baselines clearly demonstrates the effectiveness of leveraging community detection algorithms to improve prediction accuracy. Our explanation for this is that community detection algorithms minimize global objectives, such as approximations of the NP-Hard multiway cut problem, whereas existing algorithms rely on purely local approaches like random walks and graph convolutions to learn salient features. Our results demonstrate that partitioning with community detection can be an extremely powerful tool when one sets out to learn useful representations of hypergraph structured data.

Table 5: Area Under Curve (AUC) scores for hyperedge prediction.

	IAF1260B AUC	IJO1366 AUC	USPTO AUC	DBLP AUC
BASELINE	62.4 ±.4	60.4±1.	65.5±.1	65.1±1.
HYPERQUERY-MINMAX	**72.2** ±.5	**68.5**±1.	**75.7**±.1	**72.0**±1.
NHP-MINMAX	64.3 ±3.	63.2 ±2.	74.2 ±2.	69.2 ±2.
HYPER-SAGNN	60.1 ±1.	56.3 ±2.	67.1 ±1.	65.2 ±1.

B   TIME COMPLEXITY

We analyze the time complexity of our pretext task (*i.e.*, Equations 9, 10,and 11) in terms of the size of the hypergraph, assuming the number of labels is independent of the size of the hypergraph. Let m denote the number of hyperedges and n denote the number of nodes. Let $deg(v_i)$ denote the degree of node v_i and let $\tilde{\Delta}$ denote $max_{1 \leq i \leq n} deg(v_i)$. For Equation 9, our framework takes $O(n \cdot \tilde{\Delta})$ time. For Equation10, let $deg(e_i)$ denote the degree of hyperedge e_i and let Δ denote $max_{1 \leq i \leq m} deg(e_i)$. Equation 10 takes $O(m \cdot \Delta)$ time. Finally, the time complexity of Equation11 is constant since the number of labels is independent of the size of the graph. Overall, our framework takes $O(m \cdot \Delta) + O(n \cdot \tilde{\Delta})$.

C   ILLUSTRATED ZOO OF STATISTICAL FEATURES OF Ω

In our paper we focused on evaluating each statistical feature separately in order to more clearly illustrate their relative effectiveness for our benchmark tasks. In future work, it would be interesting to explore more complex and potentially learned approaches to this aggregation step as well. An illustrated zoo of different choices of Ω that we tried can be found in Figure 6.

Figure 6: Zoo of Ω: We evaluate six different choices of Ω. We evaluate component wise mean, variance, and min/max, as well as the effect of performing an additional bilinear pooling operation after statistical aggregation in our experimental results section. Here we illustrate the full optimization pipeline when performing only one layer hyperedge convolutions. We do not evaluate the performance of more complex or learned choices of Ω.