THAT LABEL'S GOT STYLE: HANDLING LABEL STYLE BIAS FOR UNCERTAIN IMAGE SEGMENTATION

ABSTRACT

Segmentation uncertainty models predict a distribution over plausible segmentations for a given input, which they learn from the annotator variation in the training set. However, in practice these annotations can differ systematically in the way they are generated, for example through the use of different labeling tools. This results in datasets that contain both data variability and differing label styles. In this paper, we demonstrate that applying state-of-the-art segmentation uncertainty models on such datasets can lead to model bias caused by the different label styles. We present an updated modelling objective conditioning on labeling style for aleatoric uncertainty estimation, and modify two state-of-the-art-architectures for segmentation uncertainty accordingly. We show with extensive experiments that this method reduces label style bias, while improving segmentation performance, increasing the applicability of segmentation uncertainty models in the wild. We curate two datasets, with annotations in different label styles, which we will make publicly available along with our code upon publication.

1 INTRODUCTION

Image segmentation is a fundamental task in computer vision and biomedical image processing. As part of the effort to create safe and interpretable ML systems, the quantification of segmentation *uncertainty* has thus become a crucial task as well. While different sources and therefore different types of uncertainties can be distinguished (Kiureghian & Ditlevsen, 2009; Gawlikowski et al., 2021), research has mainly focused on modelling two types: aleatoric and epistemic uncertainty. While epistemic uncertainty mainly refers to model uncertainty due to missing training data, aleatoric uncertainty arises through variability inherent to the data, caused for example by different opinions of the annotators about the presence, position and boundary of an object. Since aleatoric uncertainty estimates are directly inferred from the training data it is important that the variability in the available ground-truth annotations represents the experts' disagreement. However, in practice the annotations might vary in systematic ways, caused by differing labeling tools or different labeling instructions. Especially in settings where opinions in form of annotations are sourced from experts in different institutions, datasets can be heterogeneous in the way the labels are generated.

Even in the best of cases, in which manual annotators are given detailed instructions on how to segment objects, they will still have to make choices on how to annotate in ambiguous parts of the image. Moreover, annotators are not always carefully trained, and may not have access to the same

Figure 1: Sample image the from PhC-U373 dataset with annotations (red). The first three annotators were instructed to delineate the boundary in detail, whereas the last three annotators were instructed to provide a coarser and faster annotation.

labeling tools. As a result, individual choices and external factors affect how annotations are made; we term this *label style*. Figure 1 shows an example of how annotations may vary in label style.

Label style can also depend on label cost: While detailed annotations are desirable, they also take more time, and one might desire to train models on cheaper, less detailed annotations. In the example of Fig. 1, we have access to both detailed and coarse, or *weak*, annotations. It is not clear that adding the weaker annotations will necessarily improve performance; removing them to train on fewer but higher quality annotations could also be beneficial.

While weak annotations carry less precise information about the segmentation boundary, they *do* carry information about the annotator's beliefs concerning the presence and rough location of an object. Exploiting this information could improve the annotator distribution learned by the model, even tough the target might not be delineated in a detailed way. In practice, however, neither datasets nor models distinguish between variations in label style and variations in the data. As a result, current methods for segmentation uncertainty run the risk of being biased by this difference in label style.

1.1 CONTRIBUTION

In this paper, we demonstrate that applying state-of-the-art models on datasets that contain differing label styles can lead to systematic over-segmentation. We show how this bias can be reduced by stating an updated modelling objective for aleatoric uncertainty estimation conditioned on label style. We adjust two state-of-the-art uncertainty segmentation architectures accordingly, presenting conditioned versions of the Probabilistic U-net (Kohl et al., 2018) and the Stochastic Segmentation Networks (Monteiro et al., 2020) that fit to the updated modelling objective and can be trained on datasets containing differing label styles. We the proposed strategy against the common strategy of removing the annotations of a weaker label style from the dataset.

We curate two datasets, both with annotations in different label styles, ranging from detailed, close crops to over-segmented outlines. In a series of experiments, we show that the conditioned models outperform standard models, trained on either all or a single label style. The conditioning reduces label style bias, improves overall segmentation accuracy and enables more precise flagging of probable segmentation errors. Our results stress that including all label styles using a conditioned model enables fully leveraging all labels in a dataset, as opposed to naively excluding weaker label styles. As such, our model contributes to increasing the applicability of uncertainty segmentation models in practice. Our code and curated datasets will be made publicly available, to enable the community to further assess models for segmentation uncertainty in the scenario with differing label styles.

2 BACKGROUND AND RELATED WORK

Uncertainties in deep learning in general, and image segmentation in particular, can be studied under the Bayesian framework (Bishop, 2006; Kendall & Gal, 2017). Let $D = (X, A)$ be a dataset of N images $x_n \in X$ with S pixels each, where each image x_n is associated with k ground-truth annotations $a_n^k \in A$, drawn from the unknown annotator distribution $p(a|x_n)$. Furthermore, let $f(x, \theta)$ denote a model of $p(a|x)$ defined by parameters θ. Formulating the segmentation task in a Bayesian way, we seek to model the probability distribution $p(y|x)$ over model predictions y given an image x to be as similar as possible to the annotator distribution $p(a|x)$. This predictive distribution can be decomposed into the two types of uncertainty (Kiureghian & Ditlevsen, 2009) as follows:

$$p(y|x, D) = \int \underbrace{p(y|x, \theta)}_{\text{aleatoric uncertainty}} \underbrace{p(\theta|D)}_{\text{epistemic uncertainty}} \, \mathrm{d}\theta. \tag{1}$$

After observing the data D during training, the posterior distribution $p(\theta|D)$ describes a density over the parameter space of the model, capturing epistemic uncertainty. The distribution $p(y|x, \theta)$, on the other hand, captures the variation in the data and possible model predictions, i.e., aleatoric uncertainty. Due to the typically intractable epistemic uncertainty distribution, the integral on the right hand side of equation 1 is usually not accessible. Therefore, it is of particular interest to develop suitable approximations of the predictive distribution or parts of the integral in 1, and various image segmentation approaches and models have been proposed for this purpose (Kohl et al., 2018; Monteiro et al., 2020; Kohl et al., 2019; Baumgartner et al., 2019).

In this context, the standard cross-entropy minimization approach pursued in most current deep learning research can be understood as approximating the posterior distribution $p(\theta|D)$ by a Dirac distribution $\delta(\theta - \theta_1)$ and assuming that there is no spatial correlation between the pixels in an image. Under these assumptions, one obtains

$$-\log p(a|x, D) = -\log p(a|x, \theta_1) = -\log \prod_{i=1}^{S} p(a_i|x_i, \theta_1) = -\sum_{i=1}^{S} \log p(a_i|x_i, \theta_1), \quad (2)$$

which is precisely the standard negative log likelihood (or cross-entropy) loss.

Variational Bayesian methods approximate the intractable integrals arising in Bayesian inference directly through optimization. A special case that uses Bernoulli distributions to approximate the posterior distribution of the parameters as well as the predictive distribution is the Monte Carlo Dropout method (Gal & Ghahramani, 2016a; 2015). Pixel-wise uncertainty values can be retrieved by averaging multiple forward passes, while applying dropout during inference time before each weight layer of a neural network. The resulting approximation of the predictive distribution is always multi-modal and not necessarily expressive (Folgoc et al., 2021), and drawn samples can lack coherence (Czolbe et al., 2021; Gal & Ghahramani, 2016b).

Ensemble methods (Lakshminarayanan et al., 2017) also yield pixel-wise uncertainty estimates by averaging over the predictions of different models which are independently trained on the same dataset. Contrary to Monte Carlo Dropout, which implicitly averages multiple models during inference time, those models do not share the same weights but can be seen as a frequentist approach to estimating $p(\theta|D)$. On the other hand, ensembles and multi-head models (Rupprecht et al., 2017; Lee et al., 2016) independently trained on one expert's annotation each return – in expectation – a distribution over annotations, therefore also modelling the variability and disagreement between the annotators $p(a|x)$ (Czolbe et al., 2021).

Models that mainly focus on modelling the annotator distribution $p(a|x)$ have been introduced based on combinations of deterministic segmentation networks and generative modelling techniques such as conditional variational autoencoders and normalizing flows (Baumgartner et al., 2019; Kohl et al., 2019; Selvan et al., 2020). Moreover, a Gaussian-Process based convolutional architecture was recently suggested to distinguish between annotator variability and estimator uncertainty (Popescu et al., 2021). Other approaches model the distribution over annotations with probabilistic graphical models and combinations of those with neural networks (Batra et al., 2012; Kirillov et al., 2015a;b; 2016; Arnab et al., 2018; Kamnitsas et al., 2017). However, the computational expense of inference in those models usually prohibits more than a maximum a posteriori estimate of the targeted distribution.

In the following, we will describe in detail two state-of-the-art methods for quantifying aleatoric segmentation uncertainty: the probabilistic U-net (Kohl et al., 2018) and the Stochastic Segmentation Networks (Monteiro et al., 2020). We propose a new modelling objective for the annotator distribution $p(a|x)$ including label styles, and we show how both models can be modified to fit it, increasing their applicability to datasets with varying label styles.

3 SEGMENTATION UNCERTAINTY MODELS CONDITIONED ON LABEL STYLE

Segmentation uncertainty models fit a predictive distribution $p(y|x, \theta)$ to the annotator distribution $p(a|x)$. We argue that, in practice, the targeted distribution of annotations should also be conditioned on label style. Therefore, we propose to model $p(a|x, l)$ instead, where $l \in \{0, \ldots, i > 0\}$ denotes a discrete variable representing the label style, and i denotes the number of available label styles. In this setting, the segmentation model is to be learned from a dataset $D = (X, A, L)$ containing tuples (x_n, a_n^k, l_n^k) of images $x_n \in X$, annotations $a_n^k \in A$, and corresponding label styles $l_n^k \in L$. In the following, we present modified versions of the probabilistic U-net and Stochastic Segmentation Networks that incorporate label styles directly into training and inference by conditioning the models on a discrete variable (Mirza & Osindero, 2014), therefore fitting the new modelling objective.

3.1 CONDITIONED PROBABILISTIC U-NET

The probabilistic U-net (Kohl et al., 2018) combines a U-net with a conditional variational auto-encoder. During training, the probabilistic U-net learns the encoding of plausible segmentation

variants given an image X, by learning the parameters ω of an encoder, called the prior net. The prior net is trained to minimize the Kullback-Leibler divergence between its predicted latent space distribution in $\mathbb{R}^6$ and the one estimated by the posterior net encoder, only used during training time, that is receiving both the image and annotation as inputs. During inference, samples z from the latent distribution are decoded and concatenated with the deterministic output of the U-net, leading to spatially coherent samples of predictions.

We adjust this model by adding a discrete label style variable l to the input of the prior net encoder, which is tiled and concatenated as one-hot encodings to the channel axis of the input image. The latent variable z is then modelled as the normal distribution

$$z|x,l \sim \mathcal{N}(\mu(x,l), \Sigma(x,l)) \tag{3}$$

where the covariance matrix Σ is assumed to be diagonal and both Σ and the mean vector $\mu \in \mathbb{R}^6$ are estimated by the prior net encoder. The architecture is trained by minimizing the variational lower bound as described by Kohl et al. (2018), consisting of a binary cross-entropy reconstruction loss added to the Kullback-Leibler divergence. During training, the posterior net receives the style variable l_n^k in addition to the training image x_n and annotation a_n^k. The style label is, again, tiled and concatenated as a one-hot-encoded vector to the channel dimension of the images.

3.2 Conditioned Stochastic Segmentation Networks

Stochastic Segmentation Networks (SSN) (Monteiro et al., 2020) are a recently suggested model class for quantifying aleatoric segmentation uncertainty. They relax the spatial independence assumption made for deriving the standard cross-entropy loss (compare equation 2), aiming to learn an expressive normal distribution over logits. These logits can be calculated by means of any deterministic model suitable for the segmentation task. The last layers of such a model are substituted by three separate convolutional layers that estimate the parameters of a low-rank multivariate normal distribution over the predicted logits. The resulting loss function can be approximated by Monte-Carlo sampling and backpropagated using the reparameterization trick.

We adjust this model by adding a discrete label style variable l to the output of the deterministic segmentation network, before the parameters of the logit distribution are estimated. The style variable is again tiled and concatenated as one-hot encodings to the channel axis of the feature maps. The distribution over the logits η is then modelled as

$$\eta|x,l \sim \mathcal{N}(\mu(x,l), \Sigma(x,l)) \tag{4}$$

where μ and Σ are estimated by the neural networks of the chosen model as a function of the input image x and the discrete label style variable l. During inference time, samples are drawn from the estimated distribution, directly resulting in logit maps that can be passed through a softmax layer to receive class-wise probabilities.

Given an image during test time, it is now possible with both models to condition their predictions on any label style $l \in \{0, \ldots, i > 0\}$ that has been used for training.

4 Experiments

To train and evaluate segmentation uncertainty models fitting the updated modelling objective $p(a|x,l)$, we need datasets with multiple annotations per image in differing label styles. We consider two such datasets: a subset of the ISIC19 dataset and a new version of the PhC-U373 dataset.

4.1 Data

For our first evaluation, we consider a subset of the ISIC19 skin lesion segmentation challenge (Combalia et al., 2019; Codella et al., 2018; Tschandl et al., 2018), where each image has exactly three annotations available. A distinctive feature of this dataset is the clear difference between label styles, exemplified in Fig. 2: Some annotations follow the skin lesion boundary as exactly as possible; this is important as the size and boundary features can be used to clinically classify lesions as malignant or benign (Abbasi et al., 2004). Other annotations, conversely, consist of loosely defined regions containing the lesion. This type of weak labeling is more consistent with the task of detecting lesions than segmenting them.

Figure 2: Two sample images from the ISIC dataset with annotations in different label styles (red): fine-grained delineations (style 0), smooth, close borders (style 1) and coarse crops (style 2). An image might have multiple annotations of a certain label style (as in the right example).

The ISIC dataset contains ground-truth segmentations generated by three different methods, each of which we consider as one label style. Label style 0 corresponds to tight annotations with a detailed boundary, generated by a semi-automated flood-fill algorithm supervised by an expert. Label style 1 annotations stem from a fully-automated algorithm, reviewed and accepted by experts, while label style 2 are polygonal annotations traced manually by specialists. Note that not every image has exactly one annotation of each label style, so different combinations can occur such as in Fig. 2 – we include such images on purpose to illustrate our models' ability to make the most of the available data when the choice of annotations is beyond our control. We consider the fine-grained annotations of label style 0 the ground truth in the downstream analysis of annotator bias. For our experiments, the images and annotations are rescaled to 256×256 pixels.

Our second dataset is based on a cell-tracking video from the PhC-U373 dataset of the ISBI cell tracing challenge (Ulrich et al., 2009; Ulman et al., 2017). We use the first video sequence, containing 115 2D images of multiple cells, annotated with two classes (Cell, Background). To obtain images of single cells, we find the smallest bounding boxes around the ground-truth masks and extend those by 20px on all sites. We then crop these bounding boxes out of the original images and use only those patches where the expanded bounding box lies completely within the full-sized image. This results in a dataset containing 651 images of single cells, which are resized to 128×128 pixels. In addition to the ground-truth labels, all images were annotated by three researchers independently, of which two labeled the dataset twice (in different styles), resulting in five additional annotations. Labelers were instructed to perform either detailed annotation (label style 0) or wider annotations (label style 1). In total, we end up with three annotations labeled in style 0 and three annotations labeled in style 1 for each image in the dataset. Label style 0 is, again, considered the ground truth in the downstream task analysis of annotator bias later on.

Table 1: Datasets and number of image-annotation pairs contained in the different splits.

	ISIC			
	Train	Val	Test	Total
Style 0	62	20	22	
Style 1	54	18	19	
Style 2	63	21	21	
All	179	59	62	**300**
	PhC-U373			
	Train	Val	Test	Total
Style 0	1170	390	393	
Style 1	1170	390	393	
All	2340	780	786	**3906**

Both datasets are divided into subsets containing only one label style and randomly split for training, validation and testing with a ratio of 60%, 20% and 20% respectively. Table 1 gives an overview over the resulting datasets and splits. Since all models are trained on pairs of images and annotations, we report this number for a fair comparison of the dataset sizes.

4.2 Models

The following models are compared in our experiments: (1) The proposed conditioned models, namely the style-conditioned probabilistic U-net (c-prob. U-net) and the style-conditioned Stochastic Segmentation Network (c-SSN), which are trained on annotations of all label styles. During inference, we condition on the style that the model will be evaluated on. (2) Probabilistic U-nets (prob. U-net) (Kohl et al., 2018) and Stochastic Segmentation Networks (SSN) (Monteiro et al., 2020) trained on subsets that only contain one specific label style. These models are indicated by a *(subset)* tag. (3) Probabilistic U-nets and Stochastic Segmentation Networks trained on the complete dataset, containing annotations of all label styles, but not conditioned on label style. These models are indicated by an *(all)* tag. Note that this would be the most common way to use the data.

All models are implemented in PyTorch and share a U-net backbone with four encoder and decoder blocks for comparability. Each block contains three convolution layers and bilinear interpolation was used for upsampling. Dropout ($p = 0.5$) is used in the lowest-level feature map of all architectures. For the probabilistic U-nets, we chose a latent space dimension of 6 as in Kohl et al. (2018). Encoder networks in the probabilistic U-net are identical to the contraction path of the backbone U-net. For the stochastic segmentation networks, the output of the last decoder block of the backbone U-net is passed into three different 1×1 convolutional layers to estimate the low-rank approximation of the normal distribution. Refer to appendix A.1 for further details on the training procedure.

5 RESULTS

Both datasets considered in this paper contain annotations of high quality that closely outline the object of interest and ones of lower quality that generally over-segment the object of interest. In Figure 3 and Table 2, we show the distribution of area differences (measured in number of pixels) between the different models' predictions and the high-quality annotations of a fixed label style 0 test set. Intuitively, training the prob. U-net and the SSNs on all annotations leads to predictions that are biased towards too large annotations compared to the high-quality segmentations of label style 0 on both datasets. To evaluate whether it is possible to reduce this bias while maintaining the prediction quality as well as the ability of the those models to fit the annotator distribution, we compare the prob. U-

Table 2: Average area difference with standard deviation in pixels between model predictions and respective label style 0 ground-truth annotations achieved on both datasets.

	Dataset	
Model	ISIC	PhC-U373
Prob. U-net (all)	6019 (13648)	370 (402)
Prob. U-net (subset 0)	4879 (15106)	584 (534)
c-prob. U-net	**311 (8332)**	**43 (417)**
SSNs (all)	5176 (15629)	716 (1022)
SSNs (subset 0)	**3142 (19438)**	1534 (2131)
c-SSNs	3199 (12987)	**262 (558)**

net and SSNs in all experiments below against the two alternatives described above in section 4.2: Firstly, against both models trained on subsets and, secondly, against the conditioned versions that we proposed to fit the new objective for the annotator distribution $p(a|x, l)$.

5.1 VANILLA MODELS HAVE AN AREA BIAS; THIS DECREASES UNDER THE UPDATED MODELLING OBJECTIVE

Figure 3 and Table 2 show that the prob. U-net and SSNs, both trained on subsets of only label style 0 annotations, tend to over-segment the targets, despite removing the coarser label style annotations. Further, we find that the conditioned models show lower area bias compared to the standard models. For the ISIC dataset, the standard SSN model trained on the label style 0 subset shows a slightly lower area bias compared to the conditioned model. The same is true for the subset-trained prob. U-net in the PhC-U373 dataset, but in both cases, the model trained on the subset shows a higher variance.

5.2 INCREASED PREDICTIVE PERFORMANCE AND FIT TO THE ANNOTATOR DISTRIBUTION

We evaluated predictive performance to assess how well the different models can predict in a certain label style. To this end, we calculated the Intersection over Union (IoU) between the model's mean prediction against test sets that only contain annotations of the targeted label style, indicated by the column index in Table 3. Note that for column i, the prob. U-nets (subsets) or SSNs (subsets) were trained only on annotations of the targeted label style i. Across both datasets and all label styles, the best predictive performance in terms of IoU is achieved by the style-conditioned models, with the exception of the c-SSN conditioned on label style 1 on the ISIC dataset.

In addition, we computed the area under the receiver-operating characteristic curve (AUROC) with respect to pixel-wise model predictions compared to the ground-truth segmentation mask. Table 4 shows the values obtained by the different models; the conditioned models show higher AUROC values across all models and label styles.

Figure 3: We assess bias in lesion and cell area estimation for the two test datasets (ISIC, PhC-U373) by distribution of area difference (in pixels) between 100 model predictions per image and respective label style 0 ground-truth annotations. Markers indicate the mean.

Table 3: Average IoU and standard deviation for the models' mean prediction on subsets of the ISIC and the PhC-U373 datasets containing only one label style each.

| | IoU wrt. to a subset of label style | | | | |
| | ISIC | | | PhC-U373 | |
Model	0	1	2	0	1
Prob. U-net (all)	0.65 (0.09)	0.65 (0.10)	0.69 (0.21)	0.89 (0.01)	0.90 (0.02)
Prob. U-net (subsets)	0.66 (0.11)	0.55 (0.17)	0.71 (0.15)	0.85 (0.03)	0.86 (0.03)
c-prob. U-net	**0.77 (0.15)**	**0.78 (0.15)**	**0.76 (0.15)**	**0.92 (0.02)**	**0.92 (0.01)**
SSNs (all)	0.72 (0.01)	**0.77 (0.09)**	0.71 (0.19)	0.89 (0.02)	**0.93 (0.02)**
SSNs (subsets)	0.61 (0.13)	0.75 (0.13)	0.61 (0.11)	0.85 (0.04)	0.92 (0.02)
c-SSNs	**0.77 (0.10)**	0.71 (0.20)	**0.78 (0.19)**	**0.92 (0.01)**	**0.93 (0.01)**

Figure 5 and Figure 6 in Appendix A.3 show qualitative results of sample predictions on 5 images from the ISIC dataset for the different models as well as the respective annotations, illustrating that the conditioning on label style corrects for the overestimation bias.

The goal of quantifying aleatoric segmentation uncertainty is formulated as fitting a model's predictive distribution $p(y|x)$ to the unknown true distribution $p(a|x)$, represented by the available annotations of ground-truth segmentations in the dataset. To assess this fit, we calculated the generalized energy distance (GED) (Székely & Rizzo, 2013; Kohl et al., 2018) between segmentations sampled from the predictive distribution of the models and the set of ground-truth segmentations. In Table 5, we show mean GED values and their standard

Table 4: Pixel-wise AUROC on ISIC and PhC-U373 test sets that only contain annotations of the targeted label style, indicated by the column index.

| | ISIC | | | PhC-U373 | |
Label style	0	1	2	0	1
Prob. U-net (all)	0.9289	0.9102	0.8153	0.9960	0.9959
Prob. U-net (subsets)	0.9171	0.9516	0.8819	0.9925	0.9903
c-prob. U-net	**0.9444**	**0.9750**	**0.9407**	**0.9963**	**0.9968**
SSNs (all)	0.8873	0.9111	0.8633	0.9958	0.9950
SSNs (subsets)	0.7986	0.9351	0.8609	0.9893	0.9957
c-SSNs	**0.9249**	**0.9506**	**0.9255**	**0.9964**	**0.9963**

deviation for different pairs of predictive and annotator distributions. Annotator distributions $p(a|x, l = i)$ contain only the set of ground-truth segmentations of label style i of the test set, whereas $p(a|x)$ contains all available annotations across all label styles of the test set. Table rows contain the predictive distributions of the following models: the standard prob. U-nets and SSNs

Figure 4: Distributions and medians of pixel-wise uncertainty (as quantified by the entropy of pixel-wise model predictions) for true positive (TP), false positive (FP), true negative (TN), and false negative (FN) predictions.

trained on all annotation styles; the standard prob. U-nets and SSNs trained on subsets of only annotation style i for each column and the c-prob. U-net and c-SSN conditioned on label style i. We find that for the fine-grained predictions of style 0 on the ISIC dataset, the c-prob. U-net and the c-SSN exhibit lower GED values, indicating a better model fit. This also holds for the other label styles on the ISIC dataset, with the exception of the c-SSN conditioned on label style 1. On the PhC-U373 dataset, we find that the GED values are very similar across all models.

Table 5: Mean GED (with standard deviation) between models' predictive distributions and the targeted annotator distributions $p(a|x, l)$ of the available label styles as well as the full annotator distribution $p(a|x)$ of an ISIC and PhC-U373 test set.

Annotator distribution	ISIC				PhC-U373		
	$p(a|x, l=0)$	$p(a|x, l=1)$	$p(a|x, l=2)$	$p(a|x)$	$p(a|x, l=0)$	$p(a|x, l=1)$	$p(a|x)$
Prob. U-net (all)	0.58 (0.14)	0.57 (0.23)	0.54 (0.14)	0.57 (0.17)	0.69 (0.06)	**0.60 (0.07)**	**0.61 (0.06)**
Prob. U-net (subsets)	0.61 (0.14)	0.57 (0.23)	0.51 (0.17)	-	0.70 (0.06)	0.62 (0.07)	-
c-prob. U-net	**0.57 (0.13)**	**0.55 (0.24)**	**0.49 (0.19)**	**0.55 (0.18)**	**0.68 (0.06)**	0.61 (0.06)	**0.61 (0.06)**
SSNs (all)	0.59 (0.14)	**0.55 (0.23)**	0.51 (0.17)	**0.55 (0.17)**	0.69 (0.06)	**0.60 (0.07)**	0.61 (0.06)
SSNs (subsets)	0.61 (0.15)	**0.55 (0.25)**	0.55 (0.23)	-	0.70 (0.06)	0.62 (0.07)	-
c-SSNs	**0.58 (0.13)**	0.56 (0.28)	**0.48 (0.19)**	**0.55 (0.20)**	**0.68 (0.06)**	**0.60 (0.06)**	**0.60 (0.06)**

5.3 DOES HIGH SEGMENTATION UNCERTAINTY INDICATE PROBABLE SEGMENTATION ERROR?

To answer this question, we assessed the relationship between pixel-wise segmentation uncertainty and the likelihood of a segmentation error in that pixel (as compared to the ground-truth segmentation mask) on the label style 0 test set. The distribution of the pixel-wise entropy of the predictions (as a measure of segmentation uncertainty) was assessed for the cases of true positive (TP), false positive (FP), true negative (TN), and false negative (FN) pixel predictions. A default threshold of 0.5 was applied. The results are shown in Figure 4 for all models and both datasets. We find that the c-prob. U-net consistently assigns higher uncertainty to false positive and false negative predictions on both datasets compared to the standard prob. U-net variants. The c-SSN performs on par with the alternative models.

6   DISCUSSION AND CONCLUSION

Our paper took as starting point the hypothesis that probabilistic segmentation models could be biased by different label styles if these are not accounted for by the model. We find this supported by the results of Fig. 3, where we see that the prob. U-net and SSNs trained in the standard way on all label styles tend to over-segment the objects of interest. In contrast, the c-prob. U-net conditioned on the close-cropped label style 0 can reduce this bias considerably on both datasets. Even compared to prob. U-nets and SSNs trained only on the label style 0 annotations, the conditioned models give lower or on par bias.

However, the bias reduction in practice is only of value if the prediction performance does not decrease. Indeed, we find that the c-prob. U-net and the c-SSNs outperform the compared models across label styles in terms of IoU, except for the c-SSN on the label style 1 test set. On average, the mean prediction of the conditioned models is more similar to the targeted label style compared to the standard models trained on all data or on respective subsets This indicates that the proposed conditioning of the models allows the models to implicitly correct for confounding label styles while preserve the ability to segment in a meaningful way. The strong predictive performance is supported by consistently higher AUROC values for the conditioned models in Table 4. Additionally, the conditioned models fit the annotator distributions better, as the results in Table 5 suggest. We observe that the advantage in predictive performance of the conditioned models measured by IoU is larger compared to the advantage in fitting the annotator distribution measured by GED. This might be due to the fact that the IoU is calculated on the models' mean predictions while the GED is based on 100 samples drawn from the predictive distribution.

For any segmentation uncertainty model, it is of interest to which extent the uncertainty estimates can be used to flag a high-probability segmentation error. In the context of label styles, a second highly relevant question is whether we really need fine-grained annotations, or whether we can exploit coarse-grained annotations to obtain a more precise indication of potential segmentation errors. From our preliminary analysis of the relationship between uncertainty estimates and segmentation errors, it can be observed that, as desirable, entropy is higher in the case of segmentation errors across all models and datasets (Fig. 4). The c-prob. U-net gives a consistent advantage across both datasets, while the c-SSN either improves on or performs on par with the alternative models across datasets.

To summarize, our results support that the proposed method of conditioning on label style provides an advantage over, firstly, the standard way of training a segmentation uncertainty model on all available data, ignoring label style, and, secondly, the strategy of removing confounding labels from the training set. While we find that the standard models are biased by coarser annotations (styles 1 or 2) and the models trained on subsets might suffer from the missing training data, our proposed method enables the segmentation uncertainty model to incorporate all annotations regardless of label style in a meaningful way. This leads to the conditioned models performing best in predicting fine-grained label style 0 annotations. The modifications made to the architectures for conditioning based on the new modelling objective can be easily implemented and do not incur heavier models, while yielding better results. Finally, the ability to incorporate annotations of many different label styles into training allows for using real-world datasets as they are, thus increasing the applicability of segmentation uncertainty models to datasets as they occur in the wild.

6.1   LIMITATIONS AND FURTHER RESEARCH

Due to limited availability of labeled data, the correctness of the segmentation mask distributions learned by the different models can only be assessed cursorily (as done by means of the GED in Table 5). To perform a more comprehensive validation of the learned distribution, experiments with synthetic data could be performed, similar to the synthetic experiments reported by Kohl et al. (2018). More generally, an evaluation of the impact of different label styles, and the performance of the style-conditioned models, in more and larger datasets is of interest. While the conditioned models in this work require a discrete label style variable, an interesting direction for further research could be the conditioning on continuous label styles as well as considering settings in which different label styles are present but not labelled.

REFERENCES

Naheed R. Abbasi, Helen M. Shaw, Darrell S. Rigel, Robert J. Friedman, William H. McCarthy, Iman Osman, Alfred W. Kopf, and David Polsky. Early diagnosis of cutaneous melanoma revisiting the ABCD criteria. *JAMA*, 292(22):2771–2776, 12 2004. ISSN 0098-7484.

Anurag Arnab, Shuai Zheng, Sadeep Jayasumana, Bernardino Romera-Paredes, Måns Larsson, Alexander Kirillov, Bogdan Savchynskyy, Carsten Rother, Fredrik Kahl, and Philip H.S. Torr. Conditional random fields meet deep neural networks for semantic segmentation: Combining probabilistic graphical models with deep learning for structured prediction. *IEEE Signal Processing Magazine*, 35(1):37–52, 2018.

Dhruv Batra, Payman Yadollahpour, Abner Guzman-Rivera, and Gregory Shakhnarovich. Diverse M-Best solutions in Markov random fields. *Computer Vision (ECCV)*, pp. 1–16, 2012.

Christian F. Baumgartner, Kerem C. Tezcan, Krishna Chaitanya, Andreas M. Hötker, Urs J. Muehlematter, Khoschy Schawkat, Anton S. Becker, Olivio Donati, and Ender Konukoglu. PHiSeg: Capturing uncertainty in medical image segmentation. *Medical Image Computing and Computer Assisted Intervention (MICCAI)*, pp. 119–127, 2019.

Christopher M. Bishop. *Pattern Recognition and Machine Learning (Information Science and Statistics)*. Springer-Verlag, Berlin, Heidelberg, 2006. ISBN 0387310738.

Noel CF Codella, David Gutman, M Emre Celebi, Brian Helba, Michael A Marchetti, Stephen W Dusza, Aadi Kalloo, Konstantinos Liopyris, Nabin Mishra, Harald Kittler, et al. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (ISBI), hosted by the international skin imaging collaboration (ISIC). In *IEEE 15th International Symposium on Biomedical Imaging*, pp. 168–172. IEEE, 2018.

Marc Combalia, Noel CF Codella, Veronica Rotemberg, Brian Helba, Veronica Vilaplana, Ofer Reiter, Cristina Carrera, Alicia Barreiro, Allan C Halpern, Susana Puig, et al. BCN20000: Dermoscopic lesions in the wild. *arXiv preprint arXiv:1908.02288*, 2019.

Steffen Czolbe, Kasra Arnavaz, Oswin Krause, and Aasa Feragen. Is segmentation uncertainty useful? In *Information Processing in Medical Imaging*, pp. 715–726, Cham, 2021. Springer International Publishing. ISBN 978-3-030-78191-0.

Loic Le Folgoc, Vasileios Baltatzis, Sujal Desai, Anand Devaraj, Sam Ellis, Octavio E Martinez Manzanera, Arjun Nair, Huaqi Qiu, Julia Schnabel, and Ben Glocker. Is mc dropout Bayesian? *arXiv preprint arXiv:2110.04286*, 2021.

Yarin Gal and Zoubin Ghahramani. Bayesian convolutional neural networks with Bernoulli approximate variational inference. *arXiv preprint arXiv:1506.02158*, 2015.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. *International Conference on Machine Learning*, pp. 1050–1059, 2016a.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Appendix, 2016b.

Jakob Gawlikowski, Cedrique Rovile Njieutcheu Tassi, Mohsin Ali, Jongseok Lee, Matthias Humt, Jianxiang Feng, Anna Kruspe, Rudolph Triebel, Peter Jung, Ribana Roscher, et al. A survey of uncertainty in deep neural networks. *arXiv preprint arXiv:2107.03342*, 2021.

Konstantinos Kamnitsas, Christian Ledig, Virginia F.J. Newcombe, Joanna P. Simpson, Andrew D. Kane, David K. Menon, Daniel Rueckert, and Ben Glocker. Efficient multi-scale 3D CNN with fully connected CRF for accurate brain lesion segmentation. *Medical Image Analysis*, 36:61–78, 2017. ISSN 1361-8415.

Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? *Advances in Neural Information Processing Systems*, 30, 2017.

Alexander Kirillov, Bogdan Savchynskyy, Dmitrij Schlesinger, Dmitry Vetrov, and Carsten Rother. Inferring M-Best diverse labelings in a single one. *International Conference on Computer Vision (ICCV)*, pp. 1814–1822, 2015a.

Alexander Kirillov, Dmytro Shlezinger, Dmitry P Vetrov, Carsten Rother, and Bogdan Savchynskyy. M-Best-Diverse labelings for submodular energies and beyond. *Advances in Neural Information Processing Systems*, 28, 2015b.

Alexander Kirillov, Alexander Shekhovtsov, Carsten Rother, and Bogdan Savchynskyy. Joint M-best-diverse labelings as a parametric submodular minimization. *Advances in Neural Information Processing Systems*, 29, 2016.

Armen Der Kiureghian and Ove Ditlevsen. Aleatory or epistemic? Does it matter? *Structural Safety*, 31(2):105–112, 2009. ISSN 0167-4730.

Simon Kohl, Bernardino Romera-Paredes, Clemens Meyer, Jeffrey De Fauw, Joseph R Ledsam, Klaus Maier-Hein, SM Eslami, Danilo Jimenez Rezende, and Olaf Ronneberger. A probabilistic U-Net for segmentation of ambiguous images. *Advances in Neural Information Processing Systems*, 31, 2018.

Simon A. A. Kohl, Bernardino Romera-Paredes, Klaus H. Maier-Hein, Danilo Jimenez Rezende, S. M. Ali Eslami, Pushmeet Kohli, Andrew Zisserman, and Olaf Ronneberger. A hierarchical probabilistic U-Net for modeling multi-scale ambiguities. *arXiv preprint arXiv:1905.13077*, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in Neural Information Processing Systems*, 30, 2017.

Stefan Lee, Senthil Purushwalkam Shiva Prakash, Michael Cogswell, Viresh Ranjan, David Crandall, and Dhruv Batra. Stochastic multiple choice learning for training diverse deep ensembles. *Advances in Neural Information Processing Systems*, 29, 2016.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*, 2014.

Miguel Monteiro, Loïc Le Folgoc, Daniel Coelho de Castro, Nick Pawlowski, Bernardo Marques, Konstantinos Kamnitsas, Mark van der Wilk, and Ben Glocker. Stochastic segmentation networks: Modelling spatially correlated aleatoric uncertainty. *Advances in Neural Information Processing Systems*, 33:12756–12767, 2020.

Sebastian G Popescu, David J Sharp, James H Cole, Konstantinos Kamnitsas, and Ben Glocker. Distributional Gaussian process layers for outlier detection in image segmentation. In *International Conference on Information Processing in Medical Imaging*, pp. 415–427. Springer, 2021.

Christian Rupprecht, Iro Laina, Robert DiPietro, Maximilian Baust, Federico Tombari, Nassir Navab, and Gregory D Hager. Learning in an uncertain world: Representing ambiguity through multiple hypotheses. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3591–3600, 2017.

Raghavendra Selvan, Frederik Faye, Jon Middleton, and Akshay Pai. Uncertainty quantification in medical image segmentation with normalizing flows. In *Machine Learning in Medical Imaging*, Lecture Notes in Computer Science, Switzerland, 2020. Springer.

Gábor J. Székely and Maria L. Rizzo. Energy statistics: A class of statistics based on distances. 143 (8):1249–1272, 2013. doi: 10.1016/j.jspi.2013.03.018.

Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The HAM10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Scientific Data*, 5(1):1–9, 2018.

Vladimír Ulman, Martin Maška, Klas E G Magnusson, Olaf Ronneberger, Carsten Haubold, Nathalie Harder, Pavel Matula, Petr Matula, David Svoboda, Miroslav Radojevic, Ihor Smal, Karl Rohr, Joakim Jaldén, Helen M Blau, Oleh Dzyubachyk, Boudewijn Lelieveldt, Pengdong Xiao, Yuexiang Li, Siu-Yeung Cho, Alexandre C Dufour, Jean-Christophe Olivo-Marin, Constantino C Reyes-Aldasoro, Jose A Solis-Lemus, Robert Bensch, Thomas Brox, Johannes Stegmaier, Ralf Mikut, Steffen Wolf, Fred A Hamprecht, Tiago Esteves, Pedro Quelhas, Ömer Demirel, Lars Malmström, Florian Jug, Pavel Tomancak, Erik Meijering, Arrate Muñoz-Barrutia, Michal Kozubek, and Carlos Ortiz de Solorzano. An objective comparison of cell-tracking algorithms. 14(12):1141–1152, 2017. doi: 10.1038/nmeth.4473.

Theresa A. Ulrich, Elena M. de Juan Pardo, and Sanjay Kumar. The mechanical rigidity of the extracellular matrix regulates the structure, motility, and proliferation of glioma cells. 69(10): 4167–4174, 2009. doi: 10.1158/0008-5472.can-08-4859.

A APPENDIX

A.1 TRAINING PROCEDURE FOR THE ISIC AND PHC-U373 DATASETS

All models are trained using the Adam optimizer. For the probabilistic U-net, as well as the conditioned probabilistic U-net, we minimize the reconstruction term given by the binary cross-entropy loss, added with a weighted Kullback-Leibler divergence between the estimated normal distributions, as described by Kohl et al. (2018). The Stochastic Segmentation Networks are trained on the loss function described in Monteiro et al. (2020). Across all datasets we used a learning rate of 10^{-4} to train the models. For the skin lesion datasets, we trained for 600 epochs with batch size 16; for the PhC-U373 dataset, we trained for 200 epochs with a batch size of 32. The above hyperparameters were retrieved by grid search. All computations were performed on an internal GPU cluster.

A.2 GENERALIZED ENERGY DISTANCE

In section 5.2, we use the Generalized Energy Distance (Székely & Rizzo, 2013; Kohl et al., 2018) as a distance measure between distributions. It is defined as

$$D^2_{\text{GED}}(p, \hat{p}) = 2\mathbb{E}_{y\sim p, \hat{y}\sim\hat{p}}[d(y, \hat{y})] - \mathbb{E}_{y,y'\sim p}[d(y, y')] - \mathbb{E}_{\hat{y},\hat{y}'\sim\hat{p}}[d(\hat{y}, \hat{y}')],$$

where d is set to $1 - IoU(\cdot, \cdot)$. We set $d = 0$ if both segmentations are empty. Low GED values indicate high similarity between distributions. The expectations are approximated with 100 sample predictions from each model as done by Monteiro et al. (2020).

Note that when calculating the GED between the full annotator distribution $p(a|x)$ and the conditioned models' predictive distribution, we need to draw samples from $p(y|x, l)$. To this end, we sample l from a categorical distribution with density $p(l = k) = p_k$, where p_k could be set to $\frac{1}{i}$ for i different label styles or be estimated form the training dataset. We choose to set $p_k = \frac{1}{3}$ for the ISIC dataset and $p_k = \frac{1}{3}$ for the PhC-U373 dataset and predict a sample prediction with the respective model, conditioned on the drawn label style.

A.3 QUALITATIVE RESULTS ON THE ISIC DATASET

Figure 5 and 6 show sample images from the ISIC dataset with overlayed annotations. Fig. 5 shows predictions (threshold 0.5) of the probabilistic U-net trained on all data, the prob. U-nets trained on the label style subsets and the c-prob. U-net conditioned on the different label styles. Fig. 6 shows predictions (threshold 0.5) of the SSN trained on all data, the SSNs trained on the label style subsets and the c-SSN conditioned on the different label styles. In both figures, the last column shows an overlay of the conditioned models' prediction when conditioning on each of the three label styles for the given image. In both figures, it is visible that the conditioning on label style corrects for the overestimation bias.

Figure 5: Mean predictions of the different prob. U-net models for 5 images from the ISIC dataset. From left to right: Image; Overlayed annotations; prob. U-net (all); prob. U-net (subset 0); prob. U-net (subset 1); prob. U-net (subset 2); c-prob. U-net conditioned on style 0; c-prob. U-net conditioned on style 1; c-prob. U-net conditioned on style 2; Overlayed predictions from c-prob. U-net for each label style.

Figure 6: Mean predictions of the different SSN models for 5 images from the ISIC dataset. From left to right: Image; Overlayed annotations; SSN (all); SSN (subset 0); SSN (subset 1); SSN (subset 2); c-SSN conditioned on style 0; c-SSN conditioned on style 1; c-SSN conditioned on style 2; Overlayed predictions from c-SSN for each label style.