Lossy Compression for Lossless Prediction

Abstract

Most data is automatically collected and only ever "seen" by algorithms. Yet, data compressors preserve perceptual fidelity rather than just the information needed by algorithms performing downstream tasks. In this paper, we characterize the bit-rate required to ensure high performance on all predictive tasks that are invariant under a set of transformations, such as data augmentations. Based on our theory, we design unsupervised objectives for training neural compressors. Using these objectives, we train a generic image compressor that achieves substantial rate savings (more than $1000\times$ on ImageNet) compared to JPEG on 8 datasets, without decreasing downstream classification performance.

1 Introduction

Progress in important areas requires processing huge amounts of data. For climate prediction, models are still data-limited [1], despite the Natl. Center for Computational Sciences storing 32 million gigabytes (GB) of climate data [2]. For autonomous driving, capturing a realistic range of rare events with current methods requires around 3 trillion GB of data.[1] At these scales, data are only processed by task-specific algorithms, and storing data in human-readable formats can be prohibitive. We need compressors that retain only the information needed for algorithmic execution of downstream tasks.

Existing lossy compressors are not up to the challenge, because they aim to reconstruct the data for human perception [5–10]. However, much of perceptual information is not needed to perform the tasks that we care about. Consider classifying images, which can require about 1 MB to store. Classification is typically invariant under small image transformations, such as rescalings or rotations, and could instead be performed using a representation that discards such information (see Fig. 1). The amount of unnecessary perceptual information is likely substantial, as illustrated by the fact that typical image classification can be performed using a detailed caption, which requires only about 1 kB to store ($1000\times$ fewer bits).

Source   Standard rec.   Our rec.

Figure 1: Our unsupervised coder improves compression by only keeping information necessary for typical tasks. (left) source augmented MNIST digit; (center) a neural perceptual compressor achieves 130 bit-rate; (right) our invariant compressor achieves 48 bit-rate.

Our goal is to quantify the bit-rate needed to ensure high performance on a collection of prediction tasks. In the simple case of a *single* supervised task, the minimum bit-rate is achieved by compressing predicted labels, and essentially corresponds to the Information Bottleneck (IB; [11]). Our challenge, instead, is to ensure good performance on *any* future tasks of interest, which will rarely be completely known at compression time, or might be too large to enumerate.

---

[1] Kalra and Paddock [3] estimated that autonomous vehicles would have to drive hundreds of billions of miles to demonstrate reliability in rare events. At 1 TB / hour [4] and 30 miles / hour, this is 3e12 GB.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

We overcome this challenge by focusing on sets of tasks that are *invariant* under user-defined transformations (e.g., translation, brightness, cropping), as is the case for many tasks of interest to humans [12, 13]. This structure allows us to characterize a worst-case invariant task, which bounds the relative predictive performance on all invariant tasks. As a result, the bit-rate required to perform well on *all* invariant tasks is exactly the rate to compress the worst-case labels. At a high level, the worst-case task is to recognize which examples are transformed versions of one another, and rate savings come from discarding information from those transformations.

We also provide two unsupervised neural compressors to target the optimal rates. One is similar to a variational autoencoder [14] that reconstructs canonical examples (Fig. 1). Our second is a simple modification of contrastive self-supervised learning (SSL; [15]), which allows us to convert pre-trained SSL models into powerful, generic compressors. Our contributions are:

- We formalize the notion of compression for downstream predictive tasks.
- We characterize the bits needed for high performance on any task invariant to augmentations.
- We provide unsupervised objectives to train compressors that approximate the optimal rates.
- We show that our compressor outperforms JPEG by orders of magnitude on 8 datasets on which it was never trained (i.e., zero-shot). E.g., on ImageNet [16], it decreases the bit-rate by $1000\times$.

2 Rate-distortion theory background

The goal of compression theory is to find the number of bits (the *bit-rate*) required to store outcomes x of a random variable (r.v.) X, so that it can be reconstructed within a certain tolerance. This is accomplished in Shannon's [17] rate-distortion (RD) theory by mapping X into a low-information r.v. Z, and considering their mutual information $\mathrm{I}[X; Z]$. Specifically, given a distortion measure $\mathrm{D}[X, Z]$, the RD theory characterizes the minimal achievable bit-rate for a distortion threshold δ by

$$Rate(\delta) = \min_{p(Z|X)} \mathrm{I}[X; Z] \quad \text{such that} \quad \mathrm{D}[X, Z] \leq \delta. \tag{1}$$

In the RD theorem, Z is a reconstruction of X, i.e., it aims to faithfully approximate X. As a result, typical distortions, e.g., the mean squared error (MSE), assume that the sample spaces $\mathcal{X}, \mathcal{Z}$ of both r.v.s are the same. This assumption is not required. Indeed, any distortion of the form $\mathrm{D}[X, Z] = \mathrm{E}_{p(X,Z)}[d(X, Z)]$, where $d : \mathcal{X} \times \mathcal{Z} \to \mathbb{R}_{\geq 0}$ is bounded, is a valid choice [18]. This shows that RD theory can be used for tasks that are different than reconstruction. In the following we refer to Z as a compressed *representation* of X to distinguish it from a reconstruction.

3 Minimal bit-rate for high predictive performance

In this section, we characterize the bit-rate needed to represent X to ensure high performance on downstream tasks. Our argument has three high-level steps: (i) define a distortion that controls downstream performance when predicting from Z instead of X; (ii) simplify and validate this distortion when desired tasks satisfy an invariance condition; (iii) apply RD theory with the valid distortion. For simplicity, our presentation is relatively informal; formal proofs are in Apps. A and B.

3.1 A distortion for worst-case predictive performance

Suppose X is an image. Potential downstream tasks might include Y_{dog}, whether the image displays a dog; or Y_{hd}, whether the image is hand-drawn. Formally, these and other downstream tasks are expressed as $\mathcal{T} = \{Y_{\mathrm{dog}}, Y_{\mathrm{hd}}, \ldots\}$, a set of random variables that are jointly distributed with X. Let $\mathrm{R}[Y \mid X]$ denote the Bayes (best possible) risk when predicting Y from X. For ease of presentation in the main paper, we consider only classification tasks $\mathcal{T}$ and Bayes risk of the standard log loss $\mathrm{R}[Y \mid X] := \inf_q \mathrm{E}_{p(X,Y)}[-\log q(Y|X)]$. We deal with MSE and regression in Appx. B.6.

In this setting, a meaningful distortion $\mathrm{D}_{\mathcal{T}}[X, Z]$ quantifies the difference between predicting any $Y \in \mathcal{T}$ from the compressed Z, as opposed to using X. This is the worst-case excess risk,

$$\mathrm{D}_{\mathcal{T}}[X, Z] := \sup_{Y \in \mathcal{T}} \quad \mathrm{R}[Y \mid Z] - \mathrm{R}[Y \mid X]. \tag{2}$$

If $\mathrm{D}_{\mathcal{T}}[X, Z] = 0$, it is possible to achieve *lossless prediction*: performing as well using Z as using X. More generally, bounding $\mathrm{D}_{\mathcal{T}}$ by δ ensures that $\mathrm{R}[Y \mid Z] - \mathrm{R}[Y \mid X] \leq \delta$ for all tasks in $\mathcal{T}$. However, there are two issues that need to be addressed before Eq. (2) can be used. First, it is not

Figure 2: Maximal invariants $M(X)$ are representatives of equivalence classes. Example Ms include the: (a) Euclidean norm for rotations; (b) unit vector for scaling; (c) f when equivalence classes are pre-images by f; (d) empirical measure for permutations; (e) canonical graph for graph isomorphisms; (f) unaugmented input for data augmentations.

clear whether $D_\mathcal{T}$ is a valid distortion for RD theory. Second, the worst excess-risk $D_\mathcal{T}$ assumes access to all downstream tasks of interest $\mathcal{T}$ during compression, which is unrealistic in general.

3.2 Invariant tasks

The tasks that we care about are not arbitrary, and often share structure. One such structure is invariance to certain pre-specified transformations of input data. For example, computer vision tasks are often invariant to mild transformations such as brightness changes. Such invariance structure is common in realistic tasks, as seen by the wide-spread use of data augmentations [13] in machine learning (ML), which encourage predictions to be the same for an unaugmented x and an augmented x^+. Motivated by this we focus on sets of invariant tasks $\mathcal{T}$.

We consider a general notion of invariance, namely invariance specified by an equivalence relation $\sim$ on $\mathcal{X}$.[2] The equivalence induces a partition of $\mathcal{X}$ into disjoint *equivalence classes*, and we are interested in tasks whose conditional distributions are constant within these classes.

Definition 1. The set of *invariant tasks of interest* with respect to an equivalence $(\mathcal{X}, \sim)$, denoted $\mathcal{T}_\sim$, is all random variables Y such that $x \sim x^+ \implies p(Y \mid x) = p(Y \mid x^+)$ for any $x, x^+ \in \mathcal{X}$.

3.3 Rate-distortion theory for invariant task prediction

The key to simplifying $D_{\mathcal{T}_\sim}$ is the existence of a (non-unique) worst-case invariant task, denoted $M(X)$. Such task contains all and only information to which tasks $Y \in \mathcal{T}_\sim$ are not invariant; we call them *maximal invariants*. A maximal invariant $M(\bullet)$ with respect to $\sim$ is any function satisfying[3]

$$x \sim x^+ \iff M(x) = M(x^+) \quad \text{for any } x, x^+ \in \mathcal{X}. \tag{3}$$

A maximal invariant removes all information that tasks are invariant to, as it maps equivalent inputs to the same output, i.e., $M(x) = M(x^+)$. Yet, it retains the minimal information needed to perform invariant tasks, by mapping non-equivalent inputs $x \not\sim x^-$ to different outputs $M(x) \neq M(x^-)$. In other words, $M(x)$ indexes the equivalence classes. For example, the Euclidean norm is a maximal invariant for rotation invariance, as all vectors that are rotated versions of one another can be characterized by their radial coordinate. For data augmentations, the canonical (unaugmented) version of the input is a maximal invariant. Other examples are shown in Fig. 2.

---

[2]As a reminder, $\sim$ is an equivalence relation iff for all $x, x', x'' \in \mathcal{X}$: (reflexivity) $x \sim x$, (symmetry) $x \sim x' \iff x' \sim x$, and (transitivity) $x \sim x'$ and $x' \sim x'' \implies x \sim x''$.

[3]This extends the definition of maximal invariants [19] beyond invariances to group actions.

107 We prove in Appx. B.2 that under weak regularity conditions, maximal invariant tasks exist in $\mathcal{T}_\sim$,
108 and that they achieve the supremum in Eq. (2). This allows us to show that $D_{\mathcal{T}_\sim}$ reduces to the Bayes
109 risk of predicting $M(X)$ from Z and that it is a valid distortion measure. Crucially, this allows us to
110 quantify downstream performance without enumerating invariant tasks.

111 **Proposition 1.** Let $(\mathcal{X}, \sim)$ be an equivalence relation and M a maximal invariant that takes at most
112 countably many values, with $H[M(X)] < \infty$. Then $D_{\mathcal{T}_\sim}$ (2) with log loss is a valid distortion and

$$D_{\mathcal{T}_\sim}[X, Z] = R[M(X) \mid Z] . \tag{4}$$

113 Here we used $R[M(X) \mid X] = 0$, as M is a deterministic function. Also, note that the countable
114 requirement holds when tasks are invariant to some rounding of the input, as is typically the case due
115 to floating-point storage. We accommodate the uncountable case for squared-error loss in Appx. B.6.

116 With a valid distortion in hand, we invoke the RD theorem with $D_{\mathcal{T}_\sim}$ to obtain our "Rate-Invariance"
117 (RI) theorem. The RI theorem characterizes the bit-rate needed to store X while ensuring small
118 log-loss on invariant tasks. We obtain analogous results for squared-error loss.

119 **Theorem 2** (Rate-Invariance). Assume the conditions of Prop. 1. Let $\delta \geq 0$, and $Rate(\delta)$ denote
120 the minimum achievable bit-rate for transmitting Z such that for any $Y \in \mathcal{T}_\sim$ we have $R[Y \mid Z] -$
121 $R[Y \mid X] \leq \delta$. Then $Rate(\delta) = 0$ if $\delta \geq H[M(X)]$ and otherwise it is finite and

$$Rate(\delta) = \underbrace{H[M(X)]}_{\substack{\text{information needed} \\ \text{to predict } \mathcal{T}_\sim}} \underbrace{- \delta}_{\substack{\text{acceptable decrease} \\ \text{in predictive loss}}} = \underbrace{H[X]}_{\substack{\text{standard} \\ \text{compression}}} \underbrace{- H[X \mid M(X)]}_{\substack{\text{gains due to} \\ \text{invariances}}} - \delta. \tag{5}$$

122 To ensure lossless prediction, i.e., $Rate(0)$, our theorem
123 states that we require a bit-rate of $H[M(X)]$. Intuitively,
124 this is because $M(X)$ contains the minimal information
125 needed to predict losslessly any $Y \in \mathcal{T}_\sim$.[4] Furthermore,
126 the theorem relates compression and prediction by show-
127 ing that allowing a δ decrease in log-loss performance on
128 all tasks can save *exactly* δ bits. Intuitively, this is a linear
129 relationship, because expected log-loss is measured in bits.
130 On the right of Eq. (5) we further decompose $H[M(X)]$
131 into two terms to provide another interpretation: (i) $H[X]$,
132 which, for discrete X, is the bit-rate required to losslessly
133 compress X, and (ii) $H[X \mid M(X)]$, which quantifies the
134 information removed due to the invariance structure of
135 desired tasks. Importantly, removing this information does
136 not impact the best possible predictive performance. A
137 schematic is provided in Fig. 3.

Figure 3: Rate-Invariance function.

138 The bit-rate gains can be substantial, depending on the invariances. Consider compressing a sequence
139 of n i.i.d. fair coin flips. Suppose one is only interested in predicting permutation invariant labels.
140 Then instead of compressing the entire sequence in $H[X^n] = n H[X] = n$ bits, one could compress
141 the number of heads, which is a maximal invariant for permutation invariance, in $\mathcal{O}(\log n)$ bits.[5] As
142 more interesting examples, we recover in Appx. B.4 results from (i) unlabeled graph compression
143 [20]; (ii) multiset compression [21]; (iii) single task compression (IB; [11]). The equivalence $\sim$ can
144 be induced by any transformations, such as transforming an image to its caption. We use this idea in
145 Sec. 5.3 to obtain $>1000\times$ compression on ImageNet without sacrificing predictive performance.

4 Unsupervised training of invariant neural compressors

147 In this section, we design practical, invariant neural compressors that bound optimal rates. Derivations
148 are in Appx. C. In particular, we are interested in the $\arg\min$ encoders $p(Z|X)$ of the RD function

---

[4]We prove in Appx. B.5 that $Rate(0) = H[M(X)]$ for any losses used in ML.

[5]The number of heads K follow a binomial distribution so $H[K] \in \mathcal{O}(\log n)$. Here K is also a minimal
sufficient statistic for X^n. More generally, if $P(X')$ is invariant to $\sim$ and $\sim$ is the coarsest such relation, then
minimal sufficiency coincides with maximal invariance. In practice, however, $P(X')$ will rarely be $\sim$ invariant.

Figure 4: Our unsupervised objectives for invariant image compression under data augmentation use the same encoder, but differ in their approximation to the invariance distortion. Both models encode the augmented data, pass the representation through an entropy bottleneck which ensures that they are compressed, and use a distortion to retain the information about the identity of the original data. The models differ in how they retain that information: (VIC) by reconstructing unaugmented inputs; (BINCE) by recognizing which inputs come from the same original data.

(Eq. (1)) under the invariance distortion $D_{\mathcal{T}_\sim}$. To accomplish this, we can optimize the following equivalent (i.e., it induces the same RI function) Lagrangian, where β takes the role of δ,[6]

$$\underset{p(Z|X)}{\arg\min} \quad I[X;Z] + \beta \cdot R[M(X)\,|\,Z]. \tag{6}$$

In ML, the maximal invariant M is often not available. Instead, invariances are implicitly specified by sampling a random augmentation from A, applying it to a datapoint X, and asking that the model's prediction be invariant between X and $A(X)$. For example, invariance to cropping can be enforced by randomly cropping images while retaining the original label. We show in Appx. C, that in such case, we can treat the augmented $A(X)$ as the new source, Z as the representation of $A(X)$, and the unaugmented X as the maximal invariant task $M(A(X))$. Indeed, $R[M(A(X))\,|\,Z]$ is equal to $R[X\,|\,Z]$ up to a constant, so we can rewrite Eq. (6) as the following equivalent objective,

$$\underset{p(Z|A(X))}{\arg\min} \quad I[A(X);Z] + \beta \cdot R[X\,|\,Z]. \tag{7}$$

Such reformulation is possible if random augmentations retain the invariance structure $X \sim A(X)$ but "erase" enough information about equivalent inputs. Specifically, if for all $x \sim x'$ in the dataset $\mathcal{D}$, we cannot say which input was augmented, i.e., $p(X|A(x)) = p(X|A(x'))$. This is likely the case if the dataset is small compared to the support $|\mathcal{D}| \ll |\mathcal{X}|$. With this, we have an objective whose r.v.s are easy to sample from. However, both terms in Eq. (7) are still challenging to estimate.

In the following, we develop two practical variational bounds to Eq. (7), which can be optimized by stochastic gradient descent [23] over the encoder's parameters. Both approximations use the standard lossy neural compression bound $I[Z;A(X)] \leq H[Z] \leq \min_\theta E_{p(Z)}[-\log q_\theta(Z)]$ where $q_\theta(Z)$ is called an entropy model (or a prior) [24, 25]. This has the advantage that the learned q_θ can be used for entropy coding Z [26, 27]. See Ballé et al. [28] for possible entropy models. Our two approximations differ in how they upper bound $R[X\,|\,Z]$. The first uses a reconstruction loss, which attempts to reconstruct the unaugmented input $x \in \mathcal{D}$ from $A(x)$. The second uses a discrimination loss, which attempts to recognize which examples are augmented versions of the input.

4.1 Variational Invariant Compressor (VIC)

Our first model is a modified neural compressor in which inputs are augmented but target reconstructions are not. We refer to it as a *variational invariant compressor* (VIC). See Fig. 4 for an illustration. VIC has an encoder $p_\varphi(Z|A(X))$, an entropy model $q_\theta(Z)$, and a decoder $q_\phi(X|Z)$. Given a data sample $x \in \mathcal{D}$, we apply an augmentation $A(x)$, and encode it to get a representation Z. The decoder then attempts to reconstruct the unaugmented x from Z. This leads to the objective,

$$\mathcal{L}_{\text{VIC}}(\phi,\theta,\varphi) := - \sum_{x \in \mathcal{D}} E_{p(A)p_\varphi(Z|A(x))}[\log q_\theta(Z) + \beta \cdot \log q_\phi(x\,|\,Z)]. \tag{8}$$

The term $\log q_\theta(Z)$ is an entropy bottleneck, which bounds the rate $I[A(X);Z]$ and ensures that unnecessary information is removed. The term $\log q_\phi(x\,|\,Z)$ bounds the distortion $R[X\,|\,Z] \leq E_{p(X,Z)}[-\log q_\phi(X\,|\,Z)]$ and ensures that VIC preserves the information needed for invariant tasks.

---

[6]As the RI function is not strictly convex (Fig. 3), it should be beneficial to use $R[M(X)\,|\,Z]^2$ to ensure that sweeping over β is equivalent to sweeping over δ [22]. We did not see any difference in practice.

4.2 Bottleneck InfoNCE (BINCE)

Our second compressor retains all predictive information without reconstructing the data. It has two components: an entropy bottleneck and an InfoNCE [15] objective, which is the standard in contrastive SSL. We refer to this as the *bottleneck InfoNCE* (BINCE), see Fig. 4. BINCE has an advantage over VIC in that it avoids the problem of reconstructing possibly high dimensional data.

A detailed algorithm for training BINCE is given in Algorithm 1. As with VIC, for every datapoint $x \in \mathcal{D}$, we obtain a representation Z by applying an augmentation $A(x)$ and passing it through the encoder $p_\varphi(Z \,|\, A(X))$. We then sample a "positive" example Z^+ by encoding a different augmented version of the same underlying datapoint x. Finally, we sample n "negative" examples Z_i^- by encoding augmentations $A(x_i^-)$ of datapoints $x_i^- \in \mathcal{D}$ that are different from x. This results in a sequence $\mathbf{Z} = (Z^+, Z_1^-, \dots, Z_n^-)$. For conciseness we will denote the above sampling procedure as $p_\varphi(Z, \mathbf{Z} \,|\, A, \mathcal{D}, x)$. The final loss uses a discriminator f_ψ that is optimized to score the equivalence of two representation,

---

Algorithm 1 BINCE's forward pass for x

Require: $p_\varphi, q_\theta, f_\psi, \mathcal{D}, A, \beta, n, x$
1: $\tilde{x} \leftarrow A(x)$ ▷ Augment
2: $z \leftarrow \text{sample}(p_\varphi(Z|\tilde{x}))$
3: $\text{rate\_loss} \leftarrow -\log q_\theta(z)$
4: $\{x_i^-\}_{i=1}^n \leftarrow \text{select}(\mathcal{D} \setminus \{x\})$ n times
5: $\tilde{\mathbf{x}} \leftarrow [A(x), A(x_1^-), \dots, A(x_n^-)]$
6: $\mathbf{z} \leftarrow \text{sample}(p_\varphi(Z|\mathbf{x}))$
7: $\text{softmax} \leftarrow \frac{\exp f_\psi(z^+, z)}{(\sum_{z' \in \mathbf{z}} \exp f_\psi(z', z))}$
8: $\text{distortion\_loss} \leftarrow -\log(\text{softmax})$
9: **return** $\text{rate\_loss} + \beta \cdot \text{distortion\_loss}$

$$\mathcal{L}_{\text{BINCE}}(\varphi, \theta, \psi) := -\sum_{x \in \mathcal{D}} \mathrm{E}_{p(A)p_\varphi(Z, \mathbf{Z}|A, \mathcal{D}, x)} \left[\log q_\theta(Z) + \beta \cdot \log \frac{\exp f_\psi(Z^+, Z)}{\sum_{Z' \in \mathbf{Z}} \exp f_\psi(Z', Z)} \right]. \quad (9)$$

BINCE retains the necessary information by classifying (as seen by the softmax) which Z is associated with an equivalent example. Both VIC and BINCE give rise to efficient compressors by passing X through $p_\varphi(Z|X)$ and entropy coding using $q_\theta(Z)$. In theory they can both recover the optimal rate for lossless predictions, i.e., $\mathrm{H}[M(X)]$, in the limit of infinite samples ($|\mathcal{D}|$,n) and unconstrained variational families. In practice, BINCE has the advantage of not requiring a high dimensional decoder but has a high bias, unless the number of negative samples n is large [29, 30].

5 Experiments

We evaluated our framework in practical settings, focusing on two questions: (i) What compression rates can our framework achieve at what cost? (ii) Can we train a general purpose predictive image compressor? For all experiments, we train the compressors, freeze them, train the downstream predictors, and finally evaluate both on a test set. For classical compressors, standard neural compressors (VC) and our VIC, we used reconstructions as inputs to the predictors. As BINCE does not provide reconstructions, we predicted from the compressed Z using a multi-layer perceptron (MLP). We used ResNet18 [31] for encoders and image predictors. For entropy models we used Ballé et al.'s [28] hyperprior. We optimized hyper-parameters on validation using random search. For classification tasks, we report the standard classification error instead of the log-loss. We provide the latter in appendices, but note that observed trends were similar. For experimental details see Appx. E. For additional results, including all RD curves, see Appx. F. Code is available at anonymous.

5.1 Building visual intuition with synthetic toy experiments

To build an intuition, we compressed samples from a 2D banana source distribution [32], assuming rotation invariant tasks, e.g., classifying whether points are in the unit circle. We compared our VIC to a standard neural compressors (VC). Both models optimize squared-error loss.

Where do our rate gains come from? For rotation invariant tasks, our method (VIC) discards unnecessary angular information by learning disk-shaped quantizations (Fig. 5, bottom right). Specifically, VIC retains only radial information by mapping all randomly rotated points (disks) back to maximal invariants (pink dots). In contrast, standard VCs attempt to reconstruct all information, which requires a finer partition (Fig. 5, top right). As a result (Fig. 5a), VIC needs a smaller bit-rate (y-axis) for the same desired performance ($\mathrm{D}_{\mathcal{T}_\sim}$, x-axis). The area under the RD curve (AURD) for VIC is 35.8 ± 4.2 against 48.1 ± 0.3 for VC, i.e., expected bit-rate gains are around 70%. Similar gains are achieved for MNIST in Fig. 1 by reconstructing canonical digits (see Appx. F.2).

(a) Rate-Invariance curves

(b) VC high rate   (c) VC   (d) VC low rate

(e) VIC high rate   (f) VIC   (g) VIC low rate

Figure 5: Compression rates of a Banana source [32] can be decreased when downstream tasks are rotation invariant. (Left) Our invariant compressor (VIC, blue) outperforms neural compressors (VC, orange). 5 runs with standard errors in gray. (Right) VIC quantizes the space using disks to remove unnecessary angular information. Pink lines are quantization boundaries, dots are code vectors with size proportional to learned probabilities. Low rates correspond to low β in Eq. (7).

5.2 Evaluating our methods with controlled experiments

To investigate our methods, we compressed the STL10 dataset [33]. We augment (flipping, color jittering, cropping) the train *and* test set, to ensure that the task invariance assumptions are satisfied. We focus on more realistic settings in the next section. In each experiment, we sampled 100 combinations of hyper-parameters to ensure equal computational budget across models and baselines.

Table 1: Invariant compressors (BINCE, VIC) outperform classical (PNG, JPEG, WebP) and neural (VC) compressors on STL10. BINCE achieves lossless prediction but compresses $121\times$ better.

	PNG [34]	JPEG [35]	WebP [36]	VC	**VIC**	**BINCE**
Decrease in test acc. [%]	0	0.7	1.1	21.0	25.1	0.0
Compression gains	$1\times$	$3\times$	$13\times$	$63\times$	$269\times$	$121\times$

How do our BINCE and VIC compare to standard compressors? In Table 1 we compare compressors at the lowest downstream error that they achieved. As benchmark, we use PNG's lossless compression. Predicting from PNG corresponds to standard image classification, and it obtains a bit-rate of 1.42e4 for 80.8% accuracy. Classical lossy methods (JPEG, WebP) achieved up to $13\times$ bit-rate gains with little drop in performance. In comparison, our BINCE method achieved $121\times$ compression gains with no impact on predictions. Both our invariant (VIC) and standard (VC) neural compressors significantly decreased classification accuracy, which we believe can be explained by the encoders architecture (ResNet18) that we use for consistency (see Appx. F.3.1).

Should we predict from representations or reconstructions? We analyzed the impact of predicting from representations instead of reconstructions for VIC and VC, and found that this increased accuracy by 9% for VIC (see Appx. F.3.1). This suggests that, contrary to standard reconstructions, invariant reconstructions might not be easy to predict from with standard image predictors.

How important is the distribution over augmentations? We investigated the choice of augmentations on RD curves. To ensure that our invariance assumption still holds we augment both train and test but used a different distributions over augmentations. In particular, we train our VIC by applying the augmentations 50% of the time but varying that probability p at test time. We hypothesize that this should not influence RD curves since our representations should be invariant to augmentation. We confirm this in **??** by showing negligible difference across test distribution shift.

5.3 A zero-shot compressor using pre-trained self-supervised models

BINCE includes a standard contrastive SSL loss. So, we investigated whether existing pre-trained SSL models [37, 38] can be used to build generic compressors. In particular, we investigated whether CLIP [38] could be quickly turned into a powerful task-centric compressor for computer vision. In the introduction, we motivated large compression gains by noting that typical image classification

tasks can be predicted from detailed captions instead of images (around $1000\times$ more bits). CLIP is a vision transformer [39] pre-trained on 400M pairs of images and text (x_{image}, x_{text}^+) using a contrastive loss. Specifically, pairs are treated as equivalent, i.e., $x_{image} \sim x_{text}^+$, by a contrastive loss that ensures that image representations Z_{image} can be used to predict text representations Z_{text}^+ and vice versa. This suggests that CLIP is retaining the information about an image that corresponds to a detailed caption, and may be turned into a generic compressor for image classification.

BINCE also has an entropy bottleneck. Thus, we constructed our desired BINCE compressor by two simple steps. First, we downloaded and froze CLIP parameters. Second, we trained, on the small MSCOCO dataset [40], an entropy bottleneck to compress CLIP's representation. We evaluated our resulting compressor on 8 datasets (various classification tasks and image shapes) that were never seen during training (zero-shot), by training an MLP for downstream predictions on each dataset. One can see this as a multi-task setting (each dataset is a distinct task). We investigate the standard case of multiple labels per images in Appx. F.5 using the GalaxyZoo dataset [41] and its 37 tasks.

Table 2: Converting a pretrained SSL model into a zero-shot compressor achieves substantial bit-rate gains while allowing test accuracies similar to supervised models predicting from raw images.

	ImageNet	STL	PCam	Cars	CIFAR10	Food	Pets	Caltech
Rate gains vs JPEG	$1104\times$	$35\times$	$64\times$	$131\times$	$7\times$	$109\times$	$150\times$	$126\times$
Our Acc. [%]	76.3	98.7	80.9	79.6	95.2	88.3	89.5	93.4
Supervised Acc. [%]	76.1	99.0	82.6	49.1	96.7	81.8	90.4	94.5

Can we use pretrained SSL to obtain a generic compressor? Table 2 shows that we can exploit existing state-of-the-art (SOTA) SSL models to get to a powerful image compressor, which achieves $1000\times$ bit-rate gains on ImageNet compared to JPEG (at the default quality level used for storing ImageNet). The bit-rate gains (1^{st} row) are significant across all zero-shot datasets, even for biological tissues (PCam; [42]). Importantly, these gains come at little to no cost in test performance. Indeed, the test accuracies of MLPs from our representations (2^{nd} row) is similar to a near SOTA model trained on the uncompressed images (3^{rd} row taken from Radford et al. [38]). We note the large variance in bit-rate gains come from varying JPEG rates due to different images shapes (see Table 3).

Our CLIP compressor retains all the information needed to get 0 error on those tasks. Table 2 provides the test performance for MLPs, while our theory discusses Bayes risk, which is independent of specific predictors and generalization. We estimated the excess Bayes risk for our datasets (a lower bound on δ) by counting the images (in train and test) that get compressed to the same Z but have different labels. We found that we are in the lossless prediction regime for those datasets.

Table 3: Adding our entropy bottleneck (EB) on CLIP increases compression of representation up to $17\times$ with little impact on predictions. The same compressor is used across datasets.

		ImageNet	STL	PCam	Cars	CIFAR10	Food	Pets	Caltech
Bit-rate	JPEG	1.49e6	4.71e4	9.60e4	1.92e5	1.05e4	1.54e5	1.81e5	1.69e5
	CLIP	1.52e4	1.52e4	1.52e4	1.52e4	1.52e4	1.52e4	1.52e4	1.52e4
	+EB low β	2.47e3	2.46e3	2.61e3	2.59e3	2.53e3	2.39e3	2.33e3	2.46e3
	+EB β	1.35e3	1.34e3	1.49e3	1.47e3	1.41e3	1.27e3	1.21e3	1.34e3
	+EB high β	9.63e2	9.52e2	1.09e3	1.07e3	1.02e3	8.89e2	8.35e2	9.53e2
Test Acc.	CLIP	76.5	98.6	84.5	80.8	95.3	88.5	89.7	93.2
	+EB low β	76.6	98.7	82.7	80.4	95.3	88.5	89.6	93.5
	+EB β	76.3	98.7	80.9	79.6	95.2	88.3	89.5	93.4
	+EB high β	76.0	98.7	80.1	78.9	94.8	87.6	88.6	92.9

What is the effect of the entropy bottleneck? In Table 3 we compare the pretrained CLIP, to our CLIP compressor with an entropy bottleneck (EB) trained at different values for β. We see that when trained with a low β, our EB improves bit-rates by an average of $6\times$ without impacting predictions. For our compressor from Table 2 (CLIP+EB β) the gains increase to $11\times$ with still little negative impact. The sacrifice in predictions starts to be more clear for compressors that achieve $16\times$ bit-rate

gains (high β). We suspect that compression gains without sacrificing predictions can be much larger by end-to-end training of our BINCE loss, which would require access to the original dataset.[7]

Our CLIP compressor is simple to use. In Appx. E.6, we provide a minimal script (150 lines) to train a generic compressor in less than five minutes on a single GPU. The script contains an efficient entropy coder for our model (200 images/second), which shows its practicality. As usual in SSL, the compressed representations are also more computationally efficient to work with than standard compressors. In our minimal script we achieve the desired performance (98.7% on STL) using a linear model that is trained in one second, which is $1000\times$ faster than the baseline in Table 2. This shows that our pipeline can improve computational efficiency in addition to storage efficiency.

6   Related work

In Appx. D we discuss more related work, including the link between our objectives and others in SSL, and how maximal invariants are related to sufficient statistics.

Task-centric compression. To our knowledge, our paper is the first to formalize compression only for predictions. IB [11] uses a task-centric distortion, but is not used for compression as it requires supervised training, so there are no advantages compared to compressing predicted labels. Other authors have incorporated predictive errors to perceptual distortions [43, 44], but removing the perceptual distortion essentially recovers IB. In practice, most related is Singh et al.'s [45] work on compressing pretrained features for transfer learning. Their work does not provide theoretical justifications, and is constrained to tasks that are similar to those used for pretraining.

Invariances and symmetries. Invariances are ubiquitous in ML, as seen by the use of data augmentations [13] and invariant models [46–52]. These force models not to rely on nuisances to improve generalization [53–55]. We directly discard such nuisances from the data to improve compression. Others have used symmetries in X for lossless compression of multisets [21], graphs [56–58], or structured images [59–63]. We, instead, use invariance of the tasks Y for lossless prediction.

7   Discussion and Outlook

Given the ever increasing amount of data that is processed by task-specific algorithms, it is necessary to rethink the current task-agnostic compression paradigm. We formalized the first compression framework for retaining only the information necessary for high performance on desired tasks. Using our theory, we provide two unsupervised objectives for training neural compressors. Experimentally, we show that these compressors can achieve bit-rates that are orders of magnitude ($1000\times$ on ImageNet) smaller than standard image compressors without losing predictive performance.

There are a number of caveats that should be addressed. First, to achieve better rates, our theory requires an irrecoverable loss of information. This can be an issue if the set of desired tasks changes. For example, if one uses text-image invariances then it may be impossible to perform image segmentation from the compressed representations. One solution would be to keep an original copy and use invariant compression for duplicated data, e.g., for the thousands copies of ImageNet. A second issue is the interpretability of the compressed representations. This can be partially addressed by reconstructing prototypical data as in Fig. 1 (post-hoc decoders could be trained for BINCE). Finally, the compressed representations may be harder to learn from, e.g., neural networks may struggle to predict from representations. Although our experiments actually showed the opposite, this should be addressed theoretically, e.g., by incorporating the decodability of information [64, 65].

Nevertheless, we achieved orders of magnitude improvements in compression for predictions, and we believe that our improvements are just the beginning. For example, many tasks can be answered by referencing a detailed natural language description of the data. In these cases, the improvements can be very large, potentially $1M\times$ for videos.[8] In the long-term, we hope that abandoning perceptual reconstructions will enable individuals to process data at scales that are currently only possible at large institutions, and our society to take advantage of large data sources in a more sustainable way.

---

[7]We investigated finetuning CLIP on MSCOCO but it suffered from catastrophic forgetting.

[8]A movie takes around 10GB to store, but the information relevant to humans (e.g., "what happened to the house?", "how did the movie end?") can likely be stored in a detailed movie script and would require 100KB.

References

[1] D. Rolnick, P. L. Donti, L. H. Kaack, K. Kochanski, A. Lacoste, K. Sankaran, A. S. Ross, N. Milojevic-Dupont, N. Jaques11, A. Waldman-Brown11 *et al.*, "Tackling climate change with machine learning," *Transportation*, vol. 2, no. 2.2, pp. 2–4.

[2] M. Z. Zgurovsky and Y. P. Zaychenko, *Big Data: Conceptual Analysis and Applications*. Springer, 2020.

[3] N. Kalra and S. M. Paddock, "Driving to safety: How many miles of driving would it take to demonstrate autonomous vehicle reliability?" *Transportation Research Part A: Policy and Practice*, vol. 94, pp. 182–193, 2016.

[4] D. J. Yeong, G. Velasco-Hernandez, J. Barry, J. Walsh *et al.*, "Sensor and sensor fusion technology in autonomous vehicles: a review," *Sensors*, vol. 21, no. 6, p. 2140, 2021.

[5] J. Johnston, "Transform coding of audio signals using perceptual noise criteria," *IEEE Journal on Selected Areas in Communications*, vol. 6, no. 2, pp. 314–323, Feb. 1988, conference Name: IEEE Journal on Selected Areas in Communications.

[6] D. J. Heeger and P. C. Teo, "A model of perceptual image fidelity," in *Proceedings 1995 International Conference on Image Processing, Washington, DC, USA, October 23-26, 1995*. IEEE Computer Society, 1995, pp. 343–345. [Online]. Available: https://doi.org/10.1109/ICIP.1995.537485

[7] J.-S. Lee and T. Ebrahimi, "Perceptual Video Compression: A Survey," *Ieee Journal Of Selected Topics In Signal Processing*, vol. 6, no. 6, p. 684, 2012, number: ARTICLE Publisher: Ieee-Inst Electrical Electronics Engineers Inc. [Online]. Available: https://infoscience.epfl.ch/record/184275

[8] Y. Blau and T. Michaeli, "Rethinking Lossy Compression: The Rate-Distortion-Perception Tradeoff," in *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, ser. Proceedings of Machine Learning Research, K. Chaudhuri and R. Salakhutdinov, Eds., vol. 97. PMLR, 2019, pp. 675–685. [Online]. Available: http://proceedings.mlr.press/v97/blau19a.html

[9] Y. Pan, "Digital Audio Compression," *Digital Technical Journal*, 1993.

[10] F. Mentzer, G. Toderici, M. Tschannen, and E. Agustsson, "High-Fidelity Generative Image Compression," in *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, H. Larochelle, M. Ranzato, R. Hadsell, M.-F. Balcan, and H.-T. Lin, Eds., 2020. [Online]. Available: https://proceedings.neurips.cc/paper/2020/hash/8a50bae297807da9e97722a0b3fd8f27-Abstract.html

[11] N. Tishby, F. C. N. Pereira, and W. Bialek, "The information bottleneck method," *CoRR*, vol. physics/0004057, 2000. [Online]. Available: http://arxiv.org/abs/physics/0004057

[12] J. Heaton, "Ian Goodfellow, Yoshua Bengio, and Aaron Courville: Deep learning - The MIT Press, 2016, 800 pp, ISBN: 0262035618," *Genet. Program. Evolvable Mach.*, vol. 19, no. 1-2, pp. 305–307, 2018. [Online]. Available: https://doi.org/10.1007/s10710-017-9314-z

[13] C. Shorten and T. M. Khoshgoftaar, "A survey on Image Data Augmentation for Deep Learning," *Journal of Big Data*, vol. 6, no. 1, p. 60, Jul. 2019. [Online]. Available: https://doi.org/10.1186/s40537-019-0197-0

[14] D. P. Kingma and M. Welling, "Auto-Encoding Variational Bayes," in *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, Y. Bengio and Y. LeCun, Eds., 2014. [Online]. Available: http://arxiv.org/abs/1312.6114

[15] A. v. d. Oord, Y. Li, and O. Vinyals, "Representation Learning with Contrastive Predictive Coding," *arXiv:1807.03748 [cs, stat]*, Jan. 2019, arXiv: 1807.03748. [Online]. Available: http://arxiv.org/abs/1807.03748

[16] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei, "ImageNet: A large-scale hierarchical image database," in *2009 IEEE Conference on Computer Vision and Pattern Recognition*, Jun. 2009, pp. 248–255, iSSN: 1063-6919.

[17] C. E. Shannon, "Coding theorems for a discrete source with a fidelity criterion," *IRE Nat. Conv. Rec*, vol. 4, no. 142-163, p. 1, 1959.

[18] T. M. Cover and J. A. Thomas, *Elements of information theory (2. ed.)*. Wiley, 2006.

[19] M. L. Eaton, "Group Invariance Applications in Statistics," *Regional Conference Series in Probability and Statistics*, vol. 1, pp. i–133, 1989, publisher: Institute of Mathematical Statistics. [Online]. Available: https://www.jstor.org/stable/4153172

[20] N. Rashevsky, "Life, information theory, and topology," *The bulletin of mathematical biophysics*, vol. 17, no. 3, pp. 229–235, Sep. 1955. [Online]. Available: https://doi.org/10.1007/BF02477860

[21] L. R. Varshney and V. K. Goyal, "Benefiting from Disorder: Source Coding for Unordered Data," *arXiv:0708.2310 [cs, math]*, Aug. 2007, arXiv: 0708.2310. [Online]. Available: http://arxiv.org/abs/0708.2310

[22] A. Kolchinsky, B. D. Tracey, and S. V. Kuyk, "Caveats for information bottleneck in deterministic scenarios," in *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. [Online]. Available: https://openreview.net/forum?id=rke4HiAcY7

[23] L. Bottou, "Large-Scale Machine Learning with Stochastic Gradient Descent," in *19th International Conference on Computational Statistics, COMPSTAT 2010, Paris, France, August 22-27, 2010 - Keynote, Invited and Contributed Papers*, Y. Lechevallier and G. Saporta, Eds. Physica-Verlag, 2010, pp. 177–186. [Online]. Available: https://doi.org/10.1007/978-3-7908-2604-3_16

[24] J. Ballé, V. Laparra, and E. P. Simoncelli, "End-to-end Optimized Image Compression," in *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. [Online]. Available: https://openreview.net/forum?id=rJxdQ3jeg

[25] L. Theis, W. Shi, A. Cunningham, and F. Huszár, "Lossy Image Compression with Compressive Autoencoders," in *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. [Online]. Available: https://openreview.net/forum?id=rJiNwv9gg

[26] J. J. Rissanen, "Generalized Kraft Inequality and Arithmetic Coding," *IBM Journal of Research and Development*, vol. 20, no. 3, pp. 198–203, May 1976, conference Name: IBM Journal of Research and Development.

[27] J. Duda, "Asymmetric numeral systems," *CoRR*, vol. abs/0902.0271, 2009, _eprint: 0902.0271. [Online]. Available: http://arxiv.org/abs/0902.0271

[28] J. Ballé, D. Minnen, S. Singh, S. J. Hwang, and N. Johnston, "Variational image compression with a scale hyperprior," in *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. [Online]. Available: https://openreview.net/forum?id=rkcQFMZRb

[29] B. Poole, S. Ozair, A. v. d. Oord, A. Alemi, and G. Tucker, "On Variational Bounds of Mutual Information," in *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, ser. Proceedings of Machine Learning Research, K. Chaudhuri and R. Salakhutdinov, Eds., vol. 97. PMLR, 2019, pp. 5171–5180. [Online]. Available: http://proceedings.mlr.press/v97/poole19a.html

[30] J. Song and S. Ermon, "Multi-label Contrastive Predictive Coding," *arXiv:2007.09852 [cs, stat]*, Jul. 2020, arXiv: 2007.09852. [Online]. Available: http://arxiv.org/abs/2007.09852

[31] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," in *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. Las Vegas, NV, USA: IEEE, Jun. 2016, pp. 770–778. [Online]. Available: http://ieeexplore.ieee.org/document/7780459/

[32] J. Ballé, P. A. Chou, D. Minnen, S. Singh, N. Johnston, E. Agustsson, S. J. Hwang, and G. Toderici, "Nonlinear Transform Coding," *CoRR*, vol. abs/2007.03034, 2020, _eprint: 2007.03034. [Online]. Available: https://arxiv.org/abs/2007.03034

[33] A. Coates, A. Ng, and H. Lee, "An Analysis of Single Layer Networks in Unsupervised Feature Learning," in *AISTATS*, 2011.

[34] P. N. G. (PNG), "Iso/iec 15948," hhttp://www.libpng.org/pub/png/spec/iso/index-object.html, 2003.

[35] J. P. E. G. (JPEG), "Itu-t t.81, itu-t t.83, itu-t t.84, itu-t t.86, iso/iec 10918," www.jpeg.org/jpeg/, 1992.

[36] WebP, "Google," developers.google.com/speed/webp, 2018.

[37] T. Chen, S. Kornblith, M. Norouzi, and G. E. Hinton, "A Simple Framework for Contrastive Learning of Visual Representations," in *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, ser. Proceedings of Machine Learning Research, vol. 119. PMLR, 2020, pp. 1597–1607. [Online]. Available: http://proceedings.mlr.press/v119/chen20j.html

[38] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, "Learning Transferable Visual Models From Natural Language Supervision," *arXiv:2103.00020 [cs]*, Feb. 2021, arXiv: 2103.00020. [Online]. Available: http://arxiv.org/abs/2103.00020

[39] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby, "An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale," *CoRR*, vol. abs/2010.11929, 2020, _eprint: 2010.11929. [Online]. Available: https://arxiv.org/abs/2010.11929

[40] T.-Y. Lin, M. Maire, S. Belongie, L. Bourdev, R. Girshick, J. Hays, P. Perona, D. Ramanan, C. L. Zitnick, and P. Dollár, "Microsoft COCO: Common Objects in Context," *arXiv:1405.0312 [cs]*, Feb. 2015, arXiv: 1405.0312. [Online]. Available: http://arxiv.org/abs/1405.0312

[41] C. J. Lintott, K. Schawinski, A. Slosar, K. Land, S. Bamford, D. Thomas, M. J. Raddick, R. C. Nichol, A. Szalay, D. Andreescu, P. Murray, and J. Vandenberg, "Galaxy Zoo: morphologies derived from visual inspection of galaxies from the Sloan Digital Sky Survey," *Monthly Notices of the Royal Astronomical Society*, vol. 389, pp. 1179–1189, Sep. 2008. [Online]. Available: http://adsabs.harvard.edu/abs/2008MNRAS.389.1179L

[42] B. S. Veeling, J. Linmans, J. Winkens, T. Cohen, and M. Welling, "Rotation Equivariant CNNs for Digital Pathology," Jun. 2018, _eprint: 1806.03962.

[43] D. Liu, D. Wang, and H. Li, "Recognizable or Not: Towards Image Semantic Quality Assessment for Compression," *Sensing and Imaging*, vol. 18, no. 1, p. 1, Dec. 2016. [Online]. Available: https://doi.org/10.1007/s11220-016-0152-5

[44] D. Liu, H. Zhang, and Z. Xiong, "On The Classification-Distortion-Perception Tradeoff," in *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, H. M. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché Buc, E. B. Fox, and R. Garnett, Eds., 2019, pp. 1204–1213. [Online]. Available: https://proceedings.neurips.cc/paper/2019/hash/6c29793a140a811d0c45ce03c1c93a28-Abstract.html

[45] S. Singh, S. Abu-El-Haija, N. Johnston, J. Ballé, A. Shrivastava, and G. Toderici, "End-to-End Learning of Compressible Features," in *IEEE International Conference on Image Processing, ICIP 2020, Abu Dhabi, United Arab Emirates, October 25-28, 2020*. IEEE, 2020, pp. 3349–3353. [Online]. Available: https://doi.org/10.1109/ICIP40778.2020.9190860

[46] J. Shawe-Taylor, "Building symmetries into feedforward networks," in *1989 First IEE International Conference on Artificial Neural Networks, (Conf. Publ. No. 313)*, Oct. 1989, pp. 158–162.

[47] J. Wood and J. Shawe-Taylor, "Representation Theory and Invariant Neural Networks," *Discret. Appl. Math.*, vol. 69, no. 1-2, pp. 33–60, 1996. [Online]. Available: https://doi.org/10.1016/0166-218X(95)00075-3

[48] J. Bruna and S. Mallat, "Invariant Scattering Convolution Networks," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 35, no. 8, pp. 1872–1886, 2013. [Online]. Available: https://doi.org/10.1109/TPAMI.2012.230

[49] T. Cohen and M. Welling, "Group Equivariant Convolutional Networks," in *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, ser. JMLR Workshop and Conference Proceedings, M.-F. Balcan and K. Q. Weinberger, Eds., vol. 48. JMLR.org, 2016, pp. 2990–2999. [Online]. Available: http://proceedings.mlr.press/v48/cohenc16.html

[50] M. Zaheer, S. Kottur, S. Ravanbakhsh, B. Póczos, R. Salakhutdinov, and A. J. Smola, "Deep Sets," in *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, I. Guyon, U. v. Luxburg, S. Bengio, H. M. Wallach, R. Fergus, S. V. N. Vishwanathan, and R. Garnett, Eds., 2017, pp. 3391–3401. [Online]. Available: https://proceedings.neurips.cc/paper/2017/hash/f22e4747da1aa27e363d86d40ff442fe-Abstract.html

[51] R. Kondor and S. Trivedi, "On the Generalization of Equivariance and Convolution in Neural Networks to the Action of Compact Groups," in *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, ser. Proceedings of Machine Learning Research, J. G. Dy and A. Krause, Eds., vol. 80. PMLR, 2018, pp. 2752–2760. [Online]. Available: http://proceedings.mlr.press/v80/kondor18a.html

[52] B. Bloem-Reddy and Y. W. Teh, "Probabilistic Symmetries and Invariant Neural Networks," *J. Mach. Learn. Res.*, vol. 21, pp. 90:1–90:61, 2020. [Online]. Available: http://jmlr.org/papers/v21/19-322.html

[53] T. Dao, A. Gu, A. J. Ratner, V. Smith, C. D. Sa, and C. Re, "A Kernel Theory of Modern Data Augmentation," p. 10, 2019.

[54] S. Chen, E. Dobriban, and J. H. Lee, "A Group-Theoretic Framework for Data Augmentation," *arXiv:1907.10905 [cs, math, stat]*, Feb. 2020, arXiv: 1907.10905. [Online]. Available: http://arxiv.org/abs/1907.10905

[55] C. Lyle, M. v. d. Wilk, M. Kwiatkowska, Y. Gal, and B. Bloem-Reddy, "On the Benefits of Invariance in Neural Networks," *CoRR*, vol. abs/2005.00178, 2020, _eprint: 2005.00178. [Online]. Available: https://arxiv.org/abs/2005.00178

[56] Y. Choi and W. Szpankowski, "Compression of Graphical Structures: Fundamental Limits, Algorithms, and Experiments," *IEEE Transactions on Information Theory*, vol. 58, no. 2, pp. 620–638, Feb. 2012. [Online]. Available: http://ieeexplore.ieee.org/document/6145505/

[57] M. Dehmer and A. Mowshowitz, "A history of graph entropy measures," *Information Sciences*, vol. 181, no. 1, pp. 57–78, Jan. 2011. [Online]. Available: https://linkinghub.elsevier.com/retrieve/pii/S0020025510004147

[58] I. Kontoyiannis, Y. H. Lim, K. Papakonstantinopoulou, and W. Szpankowski, "Compression and Symmetry of Small-World Graphs and Structures," *arXiv:2007.15981 [cs, math]*, Jul. 2020, arXiv: 2007.15981. [Online]. Available: http://arxiv.org/abs/2007.15981

[59] V. Sanchez, R. Abugharbieh, and P. Nasiopoulos, "Symmetry-Based Scalable Lossless Compression of 3D Medical Image Data," *IEEE Transactions on Medical Imaging*, vol. 28, no. 7, pp. 1062–1072, Jul. 2009, conference Name: IEEE Transactions on Medical Imaging.

[60] S. Amraee, N. Karimi, S. Samavi, and S. Shirani, "Compression of 3D MRI images based on symmetry in prediction-error field," in *Proceedings of the 2011 IEEE International Conference on Multimedia and Expo, ICME 2011, 11-15 July, 2011, Barcelona, Catalonia, Spain*. IEEE Computer Society, 2011, pp. 1–6. [Online]. Available: https://doi.org/10.1109/ICME.2011.6011897

[61] N. J. Mitra, M. Pauly, M. Wand, and D. Ceylan, "Symmetry in 3D Geometry: Extraction and Applications," *Comput. Graph. Forum*, vol. 32, no. 6, pp. 1–23, 2013. [Online]. Available: https://doi.org/10.1111/cgf.12010

[62] A. Gnutti, F. Guerrini, and R. Leonardi, "Representation of signals by local symmetry decomposition," in *2015 23rd European Signal Processing Conference (EUSIPCO)*. IEEE, 2015, pp. 983–987.

[63] V. K. Bairagi, "Symmetry-Based Biomedical Image Compression," *Journal of Digital Imaging*, vol. 28, no. 6, pp. 718–726, Dec. 2015. [Online]. Available: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4636716/

[64] Y. Xu, S. Zhao, J. Song, R. Stewart, and S. Ermon, "A Theory of Usable Information under Computational Constraints," in *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. [Online]. Available: https://openreview.net/forum?id=r1eBeyHFDH

[65] Y. Dubois, D. Kiela, D. J. Schwab, and R. Vedantam, "Learning Optimal Representations with the Decodable Information Bottleneck," in *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, H. Larochelle, M. Ranzato, R. Hadsell, M.-F. Balcan, and H.-T. Lin, Eds., 2020. [Online]. Available: https://proceedings.neurips.cc/paper/2020/hash/d8ea5f53c1b1eb087ac2e356253395d8-Abstract.html