*Proceedings of the 90th Annual International Meeting of the Psychometric Society, Minneapolis, United States* (2025).

# The Use of AI Tools to Develop and Validate Q-Matrices

Kevin Fan[††] 🆔, Jacquelyn A. Bialo[†] 🆔, and Hongli Li[†*] 🆔

†† Johns Creek High School, Johns Creek, GA. USA.

† Department of Educational Policy Studies, Georgia State University, Atlanta, GA. USA.

*Corresponding author. Email: hli24@gsu.edu

## Abstract

Constructing a Q-matrix is a critical but labor-intensive step in cognitive diagnostic modeling (CDM). This study investigates whether AI tools (i.e., general language models) can support Q-matrix development by comparing AI-generated Q-matrices with a validated Q-matrix from Li and Suen (2013) for a reading comprehension test. In May 2025, multiple AI models were provided with the same training materials as human experts. Agreement among AI-generated Q-matrices, the validated Q-matrix, and human raters' Q-matrices was assessed using Cohen's kappa. Results showed substantial variation across AI models, with Google Gemini 2.5 Pro achieving the highest agreement ($\kappa = 0.63$) with the validated Q-matrix. A follow-up analysis in January 2026 using newer AI versions, however, revealed lower agreement with the validated Q-matrix. Implications, limitations, and directions for future research are discussed.

**Keywords:** AI tools, Q-matrices, Validation

## 1.    Background

Cognitive diagnostic modeling (CDM) is a valuable approach that allows assessments to provide rich diagnostic information to inform instruction and learning (Rupp & Templin, 2008). To enable the use of CDM, a critical first step is to map test items onto an item-by-skill table, known as a Q-matrix (Tatsuoka, 1983). A Q-matrix represents a particular hypothesis about which skills (or attributes) are required to successfully answer each item in a test. A correct answer to the item may depend on one or more skills. Developing a Q-matrix is an iterative process that requires both theoretical guidance and content knowledge about the construct being tested. After an initial set of attributes has been specified, the Q-matrix needs to be refined to ensure that there are sufficient high-quality items for each attribute to produce stable results. Therefore, developing a Q-matrix, particularly for existing assessments, can be both challenging and time-consuming (Hunter et al., 2022).

While generative AI is increasingly recognized for assisting with different stages of educational measurement, such as test development, automatic scoring, and feedback giving (Bulut et al., 2024), its capacity to facilitate building a Q-matrix remains understudied. Aşiret and Sünbül (2025) evaluated ChatGPT 4o's performance in building a Q-matrix for a short math test consisting of 12 fraction subtraction items. The Q-matrix for this dataset included four skills: (a) performing basic fraction subtraction operations, (b) simplified/reduced fractions, (c) separating whole numbers from fractions, and (d) borrowing from whole numbers to fractions. The authors found that the Q-matrix generated by ChatGPT 4o had a high overlap with those constructed by researchers and human experts. Although these findings are encouraging, the subtraction items examined were relatively straightforward. In contrast, constructing a Q-matrix for a reading comprehension assessment involves more complex and abstract cognitive processes, making it substantially more challenging for automated approaches.

The purpose of this study is, therefore, to examine the application of a series of AI tools in Q-matrix development and validation of a reading comprehension test across time. Specifically, it compares the performance of several AI tools in generating Q-matrices for a reading comprehension test originally used in Li and Suen (2013). It is important to note that the validated Q-matrix used in Li and Suen is not a definitive

ground truth, but rather one empirically supported specification derived under certain assumptions. Q-matrix development is inherently iterative, and multiple plausible representations of the underlying skill structure may exist (Lee & Sawaki, 2009; Liu et al., 2012). Therefore, agreement with the validated Q-matrix should be interpreted as alignment with a reference specification, rather than as evidence of correctness.

## 2.    Methods

### 2.1 Original Q-Matrix in Li and Suen (2013)

The reading test examined in Li and Suen (2013) includes four passages, each followed by five multiple-choice items. The underlying reading comprehension construct consists of two broad categories: linguistic skills and comprehension skills. Linguistic skills include vocabulary (Skill 1) and syntax (Skill 2), whereas comprehension skills include extracting explicit information (Skill 3), connecting and synthesizing (Skill 4), and making inferences (Skill 5). A Q-matrix was developed based on student think-aloud protocols and expert judgment, then validated with empirical data. Their validated Q-matrix is presented in Table 1.

Four experts were invited to identify the skills required by each of the 20 items in the reading comprehension test. All experts were advanced doctoral students in education or applied linguistics with extensive experience teaching English reading to English as a Second Language learners. To familiarize the experts with the rating task, a training session was conducted prior to formal coding. During this session, the reading test, the cognitive model of reading, and the associated coding scheme were introduced. Following training, each expert independently read the passages and completed the rating task in a library study room. Experts identified the skills required for each item and documented annotations describing the evidence supporting their judgments.

**Table 1.** Validated Q-Matrix in Li and Suen (2013)

| Item | Skill 1 (Vocabulary) | Skill 2 (Syntax) | Skill 3 (Extracting explicit information) | Skill 4 (Connecting and synthesizing) | Skill 5 (Making inferences) |
|------|------|------|------|------|------|
| 1 | 1 | 0 | 0 | 1 | 0 |
| 2 | 1 | 0 | 0 | 0 | 0 |
| 3 | 0 | 0 | 0 | 1 | 0 |
| 4 | 0 | 0 | 1 | 0 | 0 |
| 5 | 1 | 0 | 0 | 0 | 1 |
| 6 | 1 | 0 | 1 | 0 | 0 |
| 7 | 0 | 0 | 1 | 0 | 0 |
| 8 | 1 | 0 | 0 | 1 | 0 |
| 9 | 0 | 0 | 1 | 0 | 0 |
| 10 | 1 | 0 | 0 | 0 | 1 |
| 11 | 0 | 0 | 1 | 0 | 0 |
| 12 | 1 | 1 | 0 | 0 | 0 |
| 13 | 0 | 0 | 0 | 1 | 0 |
| 14 | 1 | 0 | 0 | 1 | 0 |
| 15 | 1 | 1 | 0 | 0 | 1 |
| 16 | 1 | 1 | 1 | 0 | 0 |
| 17 | 0 | 1 | 0 | 1 | 0 |
| 18 | 0 | 1 | 1 | 0 | 0 |
| 19 | 1 | 0 | 0 | 1 | 0 |
| 20 | 0 | 0 | 1 | 0 | 0 |

### *2.2 The Use of AI Tools to Build Q-matrix*

In the present study, AI models were asked to follow the same procedures as the human experts and were provided with identical training materials. In May 2025, the training materials were supplied to several AI models, including ChatGPT (versions 4o and 4.5), Google Gemini 2.5 Pro, Claude 4 Sonnet, and DeepSeek V3. The AI-generated Q-matrices were compared with the validated Q-matrix reported in Li and Suen (2013) using Cohen's kappa. For benchmarking purposes, the Q-matrices produced by human experts were also compared with the validated matrix. The results of the first round were presented at the Psychometric Society Conference in July 2025 (Fan et al., 2025).

Because the AI models had been updated since the original results were presented, in January 2026, the same training materials were provided to newer versions of these models, including ChatGPT 5.2, Google Gemini 3 Pro, Claude 4.5 Sonnet, and DeepSeek V3.2. It is generally understood that the newer AI models incorporate advances in general reasoning, semantic abstraction, and long-context processing relative to earlier versions. The results from the second round of analyses were also briefly summarized.

The prompt used for both rounds was: *"For the rating task, you will be provided with 4 short reading passages, each followed by 5 multiple-choice items. You will be asked to identify what reading skills are required to answer each item correctly. If you believe the skill is required by the item, please put a 1 in the table below, otherwise, please put a zero. Please also provide justifications for your decisions."*

## 3.     Results and Discussion

### *3.1 Primary Analysis from May 2025*

Figure 1 shows the pairwise Cohen's Kappa value comparing AI-Generated and Human Raters' Q-Matrices with the Validated Q-Matrix. Cohen's Kappa was computed by treating all item–skill entries in the Q-matrix as binary observations. That is, the matrices were vectorized, and agreement was calculated across all entries jointly. Following the guidelines of Altman (1991), adapted from Landis and Koch (1977), values below 0.20 indicate poor agreement; 0.21–0.40, fair; 0.41–0.60, moderate; 0.61–0.80, good; and 0.81–1.00, very good agreement.

Gemini 2.5 Pro showed the highest agreement with the validated Q-matrix ($k$ = 0.63), followed by Claude 4 Sonnet ($k$ = 0.33), DeepSeek V3 ($k$ = 0.26), ChatGPT 4.5 ($k$ = 0.24), and ChatGPT 4o ($k$ = 0.12). Human experts generally showed slightly higher agreement with the validated Q-matrix than most AI tools. However, it is important to note that Gemini 2.5 Pro outperformed all human experts particularly in identifying comprehension skills (extracting explicit information, connecting and synthesizing, and making inferences). In addition, ChatGPT 4.5 and DeepSeek V3 demonstrated very high agreement with each other ($k$ = 0.97), suggesting strong internal consistency between these two, but lower alignment with the validated Q-matrix.

Figure 2 further illustrates Cohen's Kappa values across skill categories. Cohen's Kappa was computed separately for each skill to examine whether agreement varies across different skills. Both human experts and AI tools showed better performance in coding comprehension skills (extracting explicit information, connecting and synthesizing, and making inferences) than linguistic skills (vocabulary and syntax). This pattern was likely due to the complexity involved in understanding the linguistic skills and limitations in the original coding framework. Furthermore, Gemini 2.5 Pro showed higher agreement with the validated Q-matrix than the four human experts in identifying comprehension skills (extracting explicit information, connecting and synthesizing, and making inferences). However, this pattern was not observed for linguistic skills.

**Figure 1.** Cohen's Kappa Comparing AI-Generated Q-matrices, Human Raters' Q-Matrices, and the Validated Q-Matrix (May 2025).

**Figure 2.** Cohen's Kappa Comparing AI-Generated and Human Raters' Q-Matrices with the Validated Q-Matrix Across Skills (May 2025).

### 3.2 Additional Analysis from January 2026

As shown in Figure 3, among the newer AI models, Google Gemini 3 Pro still showed the highest agreement with the validated Q-matrix ($\kappa$ = 0.42), followed by Claude 4.5 Sonnet ($\kappa$ = 0.26), DeepSeek V3.2 ($\kappa$ = 0.21), and ChatGPT 5.2 ($\kappa$ = 0.16). Although Gemini 3 Pro is still the best performing model, its agreement was much lower than that of the earlier Gemini 2.5 Pro ($k$ = 0.63). Overall, agreement levels for the newer AI models were lower than those observed for earlier versions in May 2025, and all the newer models showed worse performance than all four human raters.

Upon close examination, we found that ChatGPT 5.2 did not code linguistic skills (vocabulary and syntax) for any items. The model justified this decision by stating that "vocabulary and syntax were not coded because no item hinges on decoding infrequent words or complex sentence structures." In contrast, earlier versions (ChatGPT 4.5 and ChatGPT 4o) coded linguistic skills for a subset of items. This discrepancy suggests that, although the newer model demonstrates enhanced reasoning capability, it may reinterpret task requirements and deviate from the provided coding rules. This pattern is consistent with prior literature indicating that instruction-tuned large language models are encouraged to reason about and reinterpret rules rather than adhere to them rigidly (Bai et al., 2022). Therefore, the findings from this study suggest that improvements in AI models' general reasoning ability do not necessarily translate into closer alignment with the validated Q-matrix structure.

**Figure 3.** Cohen's Kappa Between Newer AI-Generated Q-Matrices and the Validated Q-Matrix (January 2026).

## 4.    Conclusion

Constructing a Q-matrix is a critical but labor-intensive step in CDM, requiring substantial theoretical grounding and expert judgment. Recent advances in generative AI suggest potential for supporting this process, yet empirical evidence remains limited. This study examines the extent to which AI tools can generate Q-matrices that align with a validated Q-matrix for a reading comprehension test originally reported in Li and Suen (2013). Results from the primary analysis conducted in May 2025 indicate that AI tools can produce Q-matrices that show meaningful agreement with the validated Q-matrix, although performance varies substantially across models. Among the AI tools examined, Google Gemini 2.5 Pro demonstrated the highest level of agreement with the validated Q-matrix. It especially showed higher agreement than the four human experts in identifying comprehension-related skills. However, when newer versions of AI models were evaluated in January 2026 for the same task, AI generated Q-matrices showed lower agreement with the validated Q-matrix, though Google Gemini 3 Pro was still the best performing one.

These findings should be interpreted with caution for several reasons. First, we did not conduct statistical tests to compare agreement levels across AI tools and human experts. The observed differences were descriptive rather than inferential. Second, AI-generated outputs may vary across runs due to the probabilistic nature of large language models, yet this study relied on single-run outputs from each AI model. We did not systematically vary model parameters (e.g., temperature) or conduct repeated runs to formally assess the stability of agreement indices. Future research should examine the robustness of AI-generated Q-matrices across multiple runs and parameter settings to understand the consistency of these results. Third, this study focused on a single reading comprehension assessment. Given that the reading comprehension construct itself is complex and multifaceted, any single reading cognitive framework may provide an incomplete representation of the underlying skills. Future research should examine different reading assessments and cognitive frameworks, as well as explore alternative prompting strategies and training approaches to improve the consistency and accuracy of AI-assisted Q-matrix construction.

In summary, AI models show some potential to facilitate the Q-matrix construction process, but we observed substantial variability across different AI tools and time points. These findings suggest that AI tools may be best used as a supplementary source of evidence to support Q-matrix development, rather than as a replacement for expert judgment. As such, human expert judgment remains a critical component of Q-matrix construction for CDM analyses.

## References

Aşiret, S., & Sünbül, S. Ö. (2025). *Evaluating ChatGPT-4o's performance in construction of Q-matrix for a cognitive diagnostic assessment* (Version 1) [Preprint]. Research Square. https://doi.org/10.21203/rs.3.rs-6235063/v1

Altman, D. G. (1991). *Practical statistics for medical research.* Chapman & Hall.

Bai, Y., et al. (2022). Constitutional AI: Harmlessness from AI feedback. *ArXiv.* https://doi.org/10.48550/arXiv.2212.08073

Bulut, O., Beiting-Parrish, M., Casabianca, J. M., Slater, S. C., Jiao, H., Song, D., Ormerod, C., Fabiyi, D. G., Ivan, R., Walsh, C., Rios, O., Wilson, J., Yildirim-Erbasli, S. N., Wongvorachan, T., Liu, J. X., Tan, B., & Morilova, P. (2024). *The rise of artificial intelligence in educational measurement: Opportunities and ethical challenges. Chinese/English Journal of Educational Measurement and Evaluation | 教育测量与评估双语期刊, 5*(3), Article 3. https://doi.org/10.59863/MIQL7785

Fan, K., Bialo, J., & Li, H. (2025, July). *The use of AI tools to develop and validate Q-matrices.* Poster presented at the Psychometric Society Meeting (IMPS) Annual Meeting, Minneapolis, MN.

Hunter, C. V., Li, H., Liu, R. (2022). Methods to retrofit and validate Q-matrices for cognitive diagnostic modeling. In M. Wiberg, D. Molenaar, J. González, & J.-S. Kim (Eds.), *Quantitative Psychology: IMPS 2021. Springer Proceedings in Mathematics & Statistics, 393,* 217–225, Springer, Cham. https://link.springer.com/chapter/10.1007/978-3-031-04572-1_16

Landis, J. R., & Koch, G. G. (1977). The measurement of observer agreement for categorical data. *Biometrics, 33*(1), 159–174. https://doi.org/10.2307/2529310

Lee, Y-W., & Sawaki, Y. (2009). Cognitive diagnosis approaches to language assessment: An overview. *Language Assessment Quarterly, 6*(3), 172–189. https://doi.org/10.1080/15434300902985108

Li, H., & Suen, H. K. (2013). Constructing and validating a Q-matrix for cognitive diagnostic analyses of a reading test. *Educational Assessment, 18*(1), 1–25. https://doi.org/10.1080/10627197.2013.761522

Liu, J., Xu, G., & Ying, Z. (2012). Data-driven learning of Q-matrix. *Applied Psychological Measurement, 36*(7), 548–564. https://doi.org/10.1177/0146621612456

Rupp, A. A. & Templin, J. L. (2008). Unique characteristics of diagnostic classification models: A comprehensive review of the current state-of-the-art. *Measurement: Interdisciplinary Research and Perspectives, 6*(4), 219–262. https://doi.org/10.1080/15366360802490866

Tatsuoka, K. K. (1983). Rule-space: An approach for dealing with misconceptions based on item response theory. *Journal of Educational Measurement, 20,* 345–354. https://doi.org/10.1111/j.1745-3984.1983.tb00212.x