FINE-TUNING OFFLINE REINFORCEMENT LEARNING WITH MODEL-BASED POLICY OPTIMIZATION

ABSTRACT

In offline reinforcement learning (RL), we attempt to learn a control policy from a fixed dataset of environment interactions. This setting has the potential benefit of allowing us to learn effective policies without needing to collect additional interactive data, which can be expensive or dangerous in real-world systems. However, traditional off-policy RL methods tend to perform poorly in this setting due to the distributional shift between the fixed data set and the learned policy. In particular, they tend to extrapolate optimistically and overestimate the action-values outside of the dataset distribution. Recently, two major avenues have been explored to address this issue. First, behavior-regularized methods that penalize actions that deviate from the demonstrated action distribution. Second, uncertainty-aware model-based (MB) methods that discourage state-actions where the dynamics are uncertain. In this work, we propose an algorithmic framework that consists of two stages. In the first stage, we train a policy using behavior-regularized model-free RL on the offline dataset. Then, we can optionally enter a second stage where we fine-tune the policy using our novel Model-Based Behavior-Regularized Policy Optimization (MB2PO) algorithm. We demonstrate that for certain tasks and dataset distributions our conservative model-based fine tuning can greatly increase performance and allow the agent to generalize and outperform the demonstrated behavior. We evaluate our method on a variety of the Gym-MuJoCo tasks in the D4RL benchmark and demonstrate that our method is competitive and in some cases superior to the state of the art for most of the evaluated tasks.

1 INTRODUCTION

Deep reinforcement learning has recently been able to achieve impressive results in a variety of video games (Badia et al., 2020) and board games (Schrittwieser et al., 2020). However, it has had limited success in complicated real-world tasks. In contrast, deep supervised learning algorithms have been achieving extraordinary success in scaling to difficult real-world datasets and tasks, especially in computer vision (Deng et al., 2009) and NLP (Rajpurkar et al., 2016). The success of supervised learning algorithms can be attributed to the combination of deep neural networks and methods that can effectively scale with large corpora of varied data. The previous successes of deep RL (Levine, 2016; Schrittwieser et al., 2020) seem to indicate that reinforcement learning can potentially scale with large active data exploration to solve specific tasks. However, the ability to collect such large datasets online seems infeasible in many real-world applications such as automated driving or robot-assisted surgery, due to the difficulty and inherent risks in collecting online exploratory data with an imperfect agent.

Existing off-policy RL algorithms can potentially leverage large, previously collected datasets, but they often struggle to learn effective policies without collecting their own online exploratory data (Agarwal et al., 2020). These failures are often attributed to the Q-function poorly extrapolating to out-of-distribution actions, which leads to overly optimistic agents that largely over-estimate the values of unseen actions. Because we train Q-functions using bootstrapping, these errors will often compound and lead to divergent Q-functions and unstable policy learning (Kumar et al., 2019).

Recently, there have been a variety of offline RL approaches that have attempted to address these issues. Broadly, we group these approaches into two main categories based on how they address the extrapolation issue.

The first set of approaches (Wu et al., 2019; Kumar et al., 2019) rely on behavior-regularization to limit the learned policy's divergence from the perceived behavioral policy that collected the data. These approaches discourage the agent from considering out-of-distribution actions in order to avoid erroneous extrapolation. While these methods can often be effective when given some amount of expert demonstrations, they often seem too conservative and rarely outperform the best demonstrated behavior.

The second set of approaches (Yu et al., 2020; Kidambi et al., 2020) leverage uncertainty-aware MB RL to learn a policy that is discouraged from taking state-action transitions where the learned model has low confidence. Thus, these methods allow a certain degree of extrapolation where the models are confident. Because these methods tend to be less restrictive, they can generalize better than behavior-regularization methods and sometimes outperform the behavioral dataset. However, this flexibility also seems to make it harder for these methods to recover the expert policy when it is present in the dataset, and reduce their effectiveness when trained with a narrow distribution.

In this work, we develop an algorithmic framework that combines ideas from behavior-regularization and uncertainty-aware model-based learning. Specifically, we first train a policy using behavior-regularized model-free RL. Then, if we have sufficient data to learn an effective uncertainty-aware dynamics model, we fine-tune our results with our novel algorithm Model-Based Behavior-Regularized Policy Optimization (MB2PO). We find that our approach is able to combine the upside of these approaches and achieve competitive or superior results on most of the Gym-MuJoCo (Todorov et al., 2012) tasks in the D4RL (Fu et al., 2020) benchmark.

2 RELATED WORK

While there exists many off-policy RL methods that can learn to solve a large variety of complex control tasks and can scale with large amounts of online data collection, these methods often perform quite poorly when run completely offline without any online data collection. Recently, there have been several methods that made progress in improving the capabilities of offline RL. For a general overview of the field of offline RL, we refer the reader to Levine et al. (2020). Here we will discuss some recent works that are particularly relevant to our approach.

2.1 IMPROVING OFF-POLICY Q-LEARNING

Many of the recent advances in both discrete and continuous action off-policy deep RL can be attributed to improvements in stabilizing off-policy Q-learning and reducing overestimation due to erroneous extrapolation. Some notable methods include target networks (Mnih et al., 2013), double Q-learning (DDQN) (van Hasselt et al., 2015), distributional RL (Bellemare et al., 2017; Dabney et al., 2017), and variance reduction through invertible transforms (Pohlen et al., 2018). In learning for continuous control, (Fujimoto et al., 2018) introduced a conservative method that uses the minimum estimate of an ensemble of q-networks as the target, which is often referred to as clipped double-Q-learning. Agarwal et al. (2020) demonstrated that Quantile Regression DDQN (Dabney et al., 2017) and other ensemble methods can be effective in certain discrete action offline RL problems. However, (Agarwal et al., 2020) showed that when used naively, these methods do not perform well on complex continuous control tasks. In our work, we incorporate the mentioned advances in off-policy Q-learning into our approach to stabilize performance and prevent potential divergence.

Additionally, the offline RL algorithm Conservative Q-learning (CQL) (Kumar et al., 2020) has attempted to address Q-learning's overestimation issue on offline data directly, by including a constraint term that discourages the agent from valuing an out-of-distribution action more than a demonstrated action. We believe that this constraint acts as an implicit policy constraint and thus would be redundant to use in combination with AWAC.

2.2 BEHAVIOR-REGULARIZED MODEL-FREE RL

A variety of offline RL approaches have incorporated constraints or penalties on the learned policy's divergence from the empirical behavioral policy. Normally, KL Divergence is used (Wu et al., 2019), but mean measure of divergence (MMD) (Kumar et al., 2019) has also been used. This is

because it approximately constrains the learned policy to be in the support of the behavioral policy, which is less restricting than KL Divergence. However, most of these methods require the behavioral policy to be represented explicitly in order to estimate these divergences. In contrast, AWAC (Nair et al., 2020) or CRR (Wang et al., 2020) is able to incorporate a KL divergence constraint without explicitly representing the behavioral policy. They do this by reformulating the policy constrained RL optimization equations into a form that resembles behavioral cloning re-weighted by the exponential of the advantage. Wang et al. (2020) demonstrates that this method can effectively learn complex control tasks purely from offline data, and Nair et al. (2020) demonstrates that performance can even be improved with further online data collection. In this work, we demonstrate that these properties make AWAC work exceptionally well when used for initialization as well as when used for fine-tuning with Model-Based Policy Optimization (MBPO) (Janner et al., 2019).

2.3 Uncertainty-Aware Model-Based RL

MB RL algorithms have several natural advantages for offline RL compared to model-free RL algorithms. First, MB RL algorithms rely on supervised learning which provide more robust gradient signals compared to bootstrapped learning and policy gradients. Second, learning a dynamics model often provides strong task-independent supervision, which allows MB RL algorithms to learn from sub-optimal trajectories. These benefits makes generalization easier, and can allow MB RL algorithms to surpass the performance of the demonstrated data. In fact, in many environments, MB RL methods have already been effective in learning with offline or randomly collected datasets. Recently, incorporating uncertainty estimation techniques from supervised learning in MB RL has demonstrated further improvement in both online (Chua et al., 2018) and offline RL. In particular, two recent works Model-Based Offline Policy Optimization (MOPO) (Yu et al., 2020) and Model-Based Offline Reinforcement Learning (MoREL) (Kidambi et al., 2020) have demonstrated impressive results by incorporating uncertainty-aware MB RL with the Dyna (Sutton, 1991) style algorithm MBPO (Janner et al., 2019). Both methods use these models to create conservative MDPs that have a lower potential expected sum of rewards compared to the true MDP. By performing policy optimization in the conservative MDP through MBPO they are able to learn a conservative policy that can outperform the demonstrated trajectories. However, these methods can often fail to recover the expert policy even though it was demonstrated in the dataset. We believe that this is largely due to a lack of effective methods for estimating epistemic uncertainty for neural network regression.

3 Preliminaries

In RL, we assume our agent operates within a standard Markov decision process (MDP) $M = (\mathcal{S}, \mathcal{A}, T, r, \rho_0, \gamma)$, where $\mathcal{S}$ denotes the state space, $\mathcal{A}$ denotes the action space, $T(s'|s, a)$ represents the probabilistic transition dynamics, r is the reward function, ρ_0 is the initial state distribution, and $\gamma \in (0, 1)$ is the discount factor. The objective in RL is to learn a policy $\pi(a|s)$ that optimizes the expected discounted sum of rewards $R^\pi = \mathbb{E}_{\pi, T, \rho_0}[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t)]$.

In offline RL, we assume that during training we only have access to a fixed dataset $\mathcal{D}_\beta$ containing a set of tuples (s, a, s', r) of environment transitions and associated rewards. We assume that the data was collected by a policy π_b, which we call the behavioral policy. Typically, when training with data not collected by your current policy π, we either use off-policy model-free algorithms or model-based algorithms. The most common off-policy model-free algorithms are actor-critic algorithms that alternate between policy evaluation and policy improvement in order to learn an effective policy. In policy evaluation, these methods train a parametric Q-function by iteratively minimizing the temporal difference equation

$$Q_{k+1}^\pi = \arg\min_Q \mathbb{E}_{s,a,s'\sim\mathcal{D}} \left[((r(s,a) + \gamma\mathbb{E}_{a'\sim\pi(\cdot|s')}[Q_k^\pi(s',a')]) - Q^\pi(s,a))^2 \right] \qquad (1)$$

In policy improvement, we update our parametric policy π to maximize our current Q-function

$$\pi_{k+1} = \arg\max_\pi \mathbb{E}_{s\sim\mathcal{D},a\sim\pi(\cdot|s)}[Q^{\pi_k}(s,a)] \qquad (2)$$

In MB RL, we attempt to learn a model $\hat{T}$ of the transition dynamics and a model $\hat{r}$ of the reward function. With this learned model of the dynamics and reward function we can create a model MDP $\hat{M} = (\mathcal{S}, \mathcal{A}, \hat{T}, \hat{r}, \rho_0, \gamma)$ to estimate the true underlying MDP M. These methods tend to use either trajectory optimization or policy optimization in the model MDP to produce their policy.

4 MODEL-BASED BEHAVIOR-REGULARIZED POLICY OPTIMIZATION FOR OFFLINE FINE-TUNING

For many offline datasets, it could be much harder to learn an effective model of the MDP than to learn a reasonable policy. This is especially the case when there is low variability or insufficient coverage of the state and action space in the collected dataset, or in environments with complex observations, like images, or long horizons. To overcome these issues, recent works (Yu et al., 2020; Kidambi et al., 2020) have leveraged uncertainty estimation methods in order to construct conservative MDPs that use soft penalties or hard thresholds on model uncertainty to discourage deviating from the confident regions. However, these methods rely on the efficacy of ensemble-based neural network uncertainty estimation methods which currently are not particularly effective at estimating epistemic uncertainty in regression settings. Therefore, we propose Model-Based Behavior-Regularized Policy Optimization (MB2PO). In MB2PO, we likewise use uncertainty-aware models to perform offline MBPO, but use the behavior-regularized model-free algorithm AWAC (also known as CRR-exp) instead of SAC (Haarnoja et al., 2018) for policy optimization.

4.1 CONSERVATIVE MBPO

In this work, we use MOPO (Yu et al., 2020) as a basis for our conservative MBPO, due to its simplicity and prior effective results on the D4RL benchmarks. In MOPO, they construct a conservative MDP by augmenting the reward function as follows

$$\tilde{r}(s,a) = \hat{r}(s,a) - \lambda u(s,a) \tag{3}$$

Where, $\hat{r}$ is the learned estimate of the reward and u is the estimated uncertainty for the model transition. Specifically, we follow MOPO in using the maximum standard deviation across an ensemble of probabilistic dynamics models as our measure of uncertainty. Therefore, we can decompose our Q-function in this conservative MDP as

$$Q^\pi(s,a) = \hat{Q}_r^\pi(s,a) - \lambda Q_u^\pi(s,a) \tag{4}$$

Where $\hat{Q}_r^\pi$ represents our estimate of the expected discounted sum of rewards in the real MDP and Q_u^π represents our expected discounted sum of uncertainty penalties. Now at convergence if our policy π deviates from the behavioral policy π_β that collected the data, then we expect for all states in the conservative MDP that

$$\mathbb{E}[Q^\pi] \geq \mathbb{E}[Q^{\pi_\beta}] \tag{5}$$

Thus, by plugging in our decomposition we get

$$\mathbb{E}[\hat{Q}_r^\pi(s,a)] \geq \mathbb{E}[\hat{Q}_r^{\pi_\beta}(s,a)] + \lambda(\mathbb{E}[Q_u^\pi(s,a)] - \mathbb{E}[Q_u^{\pi_\beta}(s,a)]) \tag{6}$$

While in theory, with well calibrated uncertainty estimates and a proper tuning of λ, this should lead to only safe policy improvements over the behavioral policy, in practice it seems that MOPO is often unable to recover expert-level performance when it is provided in the offline dataset. This is unsurprising given that it is hard to generate well calibrated epistemic uncertainty estimates in regression settings, and there will inevitably be model errors that will lead to overestimated Q-values.

To address these issues, we use policy constrained model-free RL in MB2PO. In policy constrained model-free RL, we attempt to optimize the following policy objective

$$\pi = \arg\max_\pi E_{a \sim \pi(\cdot|s)}[Q^\pi(s,a)] \tag{7}$$

$$\text{s.t. } D_{\text{KL}}(\pi(\cdot|s)\|\pi_\beta(\cdot|s)) \leq \epsilon$$

If we estimate both π and π_β to be roughly univariate Gaussians with similar variances, then the KL constraint becomes an ℓ_2 constraint on the policy mean. Because we expect our models to be locally accurate around the data, this constraint can help ensure that we stay in the effective region of the estimated MDP even if we have poorly calibrated uncertainty estimation. Additionally, Janner et al. (2019) demonstrated that the difference between the true expected returns $J(\pi)$ and the expected returns $\hat{J}(\pi)$ of an MDP induced by an approximate model can be bounded by

$$J(\pi) \geq \hat{J}(\pi) - \left[\frac{2\gamma r_{\max}(\epsilon_m + 2\epsilon_\pi)}{(1-\gamma)^2} + \frac{4r_{\max}\epsilon_\pi}{1-\gamma} \right] \tag{8}$$

Where $r_{\max}$ is the maximum reward, γ is the discount factor, ϵ_m is a bound on the total variation distance (TVD) between the learned model and the true model, and ϵ_π is a bound on the TVD between π and π_β on the demonstrated states. By Pinker's inequality, bounding the KL divergence also bounds the TVD. Therefore, by leveraging policy constraints in the policy optimization in MBPO, we can reduce the gap in expected returns and improve the algorithm's robustness to model errors.

4.2 Behavior-Regularized Model-Free RL with AWAC

For performing behavior-regularized policy optimization, we use AWAC (Nair et al., 2020) also known as CRR-exp (Wang et al., 2020) due to its impressive results in offline RL and its ability to be fine-tuned with additional online data.

By enforcing the KKT conditions (Peng et al., 2019; Peters & Schaal, 2007; Gómez et al., 2014), we can derive an analytic solution to Equation 7, where the Lagrangian is

$$\mathcal{L}(\pi, \alpha) = \mathbb{E}_{a \sim \pi(\cdot|s)}\left[Q^\pi(s,a)\right] + \alpha(\epsilon - D_{\mathrm{KL}}(\pi(\cdot|s)\|\pi_\beta(\cdot|s)))$$

We can substitute $A^\pi(s,a)$ for $Q^\pi(s,a)$ because it does not effect the optimum and get the closed form solution

$$\pi^*(a|s) = \frac{1}{Z(s)}\pi_\beta(a|s)\exp\left(\frac{A^\pi(s,a)}{\alpha}\right)$$

Where $Z(s)$ is the normalizing partition function. In order to project this solution into our policy space, we update our parameters by minimizing $D_{\mathrm{KL}}(\pi^*\|\pi_\theta)$. This leads to following iterative update

$$\theta_{k+1} = \arg\min_\theta \mathbb{E}_{s,a \sim D}\left[-\log \pi_\theta(a|s)\frac{1}{Z(s)}\exp\left(\frac{A^{\pi_k}(s,a)}{\alpha}\right)\right] \tag{9}$$

We follow Wang et al. (2020) and Peng et al. (2019) and avoid estimating $Z(s)$ and instead clamp the exponential term to be at most 20. Additionally, one could adaptively learn α using dual gradient descent, but this would require us to explicitly model the behavioral policy π_β. Instead, we use a constant $\alpha = 1$ for all of our results. Additionally, the Q-function is updated off-policy using the bellman equations as described in Equation 2 and the improvements from section 2.1.

One of the major benefits of using AWAC with a fixed α is that we can leverage behavior regularization in a principled manner without needing to explicitly represent the behavioral policy. This is particularly important in 3 major cases: 1. when there is not enough data to learn the behavioral policy; 2. when the data was collected by a variety of different policies or sources; 3. when the data was collected by a policy outside of your policy class such as a human expert or a controller that leverages hidden state information.

Additionally, we can view AWAC as a reweighted behavioral cloning algorithm. Unlike SAC (Haarnoja et al., 2018) and DDPG (Lillicrap et al., 2015), it does not rely on the reparametrization trick or gradients of your learned Q-function to perform policy updates. This allows us to use a wider ranger of policy classes, which in this work we take advantage of and use a tanh squashed GMM with 5 components. We suspect that there are also some additional benefits to not depending on the gradients of the learned Q-function, which might be particularly bad in offline settings, but leave further investigation to future work.

An important thing to note with AWAC is that we can influence the implicit behavioral penalty by controlling the source of the data we train with. For example, if we perform a series of policy updates only using data collected by the previous policy iterate. Then, we are implicitly performing a trust-region policy update like TRPO (Schulman et al., 2015) and PPO (Schulman et al., 2017) of the form

$$\pi_{k+1} = \arg\max_\pi E_{a \sim \pi(\cdot|s)}[Q^{\pi_k}(s,a)] \tag{10}$$

$$\text{s.t. } D_{\mathrm{KL}}(\pi(\cdot|s)\|\pi_k(\cdot|s)) \leq \epsilon$$

In fact, if we train on data collected by the last n policy iterates, then we are approximately constraining our policy to a weighted sum of the previous n policies $\pi_k^{(n)} = \frac{1}{n}\sum_{i=0}^{n-1}\pi_{k-i}$ and damping our learning process in the policy space.

In our work, we train with a $\omega \in [0, 1]$ portion of the data from offline data collected by π_β and $(1 - \omega)$ portion of the data collected online from the last n policy iterates in the conservative MDP defined by our learned models. Therefore, we are approximately optimizing the following objective

$$\mathbb{E}_{a \sim \pi(\cdot|s)} \left[\hat{Q}^\pi(s, a) \right] - \alpha \left(\omega D_{\text{KL}}(\pi(\cdot|s)\|\pi_\beta(\cdot|s)) + (1 - \omega)D_{\text{KL}}(\pi(\cdot|s)\|\pi_k^{(n)}) \right) \qquad (11)$$

Therefore, by using AWAC as the policy optimization algorithm in MB2PO, we can easily perform behavior-regularized policy optimization with soft damped trust region updates in the conservative MDP to reduce the effects of model errors and poor uncertainty estimation.

4.3 Model-Based Behavior-Regularized Policy Optimization

Train π_θ, Q_ϕ with AWAC with samples from $\mathcal{D}_\beta$

if *model-based fine-tuning* **then**

    Train an ensemble of N probabilistic dynamics

    $\{\hat{T}_\theta^i(s_{t+1}, r|s_t, a_t) = \mathcal{N}(\mu_\theta^i(s_t, a_t), \Sigma_\theta^i(s_t, a_t))\}_{i=1}^N$ on the data in $\mathcal{D}_\beta$

    for *epoch k= 1, 2, …* **do**

        Initialize empty replay buffer $\mathcal{D}_k$

        for *1, 2, …, batchsize* **do**

            Sample state s_1 from $\mathcal{D}_\beta$

            for *j = 1, 2, …, h* **do**

                $a_j \sim \pi(s_j)$

                Uniformly sample $\hat{T}$ from $\{\hat{T}^i\}_{i=1}^N$

                $s_{j+1}, r_j \sim \hat{T}(s_j, a_j)$

                $r_j = r_j - \lambda \max_{i=1}^N \|\Sigma^i(s_j, a_j)\|_F$

                Add sample $(s_j, a_j, \tilde{r}_j, s_{j=1})$ to $\mathcal{D}_k$

            end

        end

        Drawing 5% samples from D_β and the rest uniformly from $\{\mathcal{D}_{k-i}\}_{i=0}^9$ train π_θ and Q_ϕ

          with AWAC

    end

end

We first initialize our policy by training with AWAC solely on the offline data. If this initial policy is able to recover expert-level performance, then we perform no additional fine-tuning with MB2PO as this will often lead to a degradation in final performance. We suspect that the degredation in performance is due to the model errors and miscalibration issues we discussed earlier.

If our initial policy does not achieve expert level performance, and we are confident that we can learn an effective model with the available data then we do additional fine-tuning using MB2PO. Specifically, we train an ensemble of probabilistic dynamics models represented by neural networks that output a Gaussian distribution over the next state and reward: $\{\hat{T}_\theta^i(s_{t+1}, r|s_t, a_t) = \mathcal{N}(\mu_\theta^i(s_t, a_t), \Sigma_\theta^i(s_t, a_t))\}_{i=1}^N$. We construct a conservative MDP that at every time step uses a randomly drawn dynamics model from $\{\hat{T}_\theta^i\}_{i=1}^M$ to determine the next state transition. Additionally, we incorporate an penalty on the largest predicted standard deviation among the dynamics models as a practical means of penalizing both epistemic and aleatoric uncertainty.

Then, we iterate between collecting data with our current policy in the conservative MDP and updating our policy and Q-network using Equation 9 and Equation 2 respectively. When collecting data in the conservative MDP, we collect h-length truncated trajectories starting from states in the original offline dataset. When performing training updates, we sample 5% of the data from the original dataset and the remaining 95% uniformly from the last 10 policy iterates. Our full algorithm is outlined in Algorithm 1.

Task and Dataset	Ours	AWAC	AWAC + MB2PO	MOPO	BEAR	BRAC-v	CQL($\mathcal{H}$)
halfcheetah-random	**31.2**	16.2	**31.2**	31.9	25.5	28.1	**35.4**
hopper-random	**10.8**	**10.8**	7.4	**13.3**	9.5	**12.0**	**10.8**
walker2d-random	5.0	5.0	0.0	**13.0**	6.7	0.5	7.0
halfcheetah-medium	**45.5**	**41.2**	**45.5**	40.2	38.6	**45.5**	**44.4**
hopper-medium	31.1	31.1	16.8	26.5	47.6	32.3	**58.0**
walker2d-medium	59.4	59.4	61.7	14.0	33.2	**81.3**	**79.2**
halfcheetah-expert	**106.5**	**106.5**	-1.1		**108.2**	-1.1	**104.8**
hopper-expert	**112.3**	**112.3**	12.8		**110.3**	3.7	**109.9**
walker2d-expert	104.5	104.5	0.0		106.1	0.0	**153.9**
halfcheetah-medium-expert	**104.5**	**104.5**	50.7	57.9	51.7	45.3	62.4
hopper-medium-expert	52.4	52.4	27.1	51.7	4.0	0.8	**111.0**
walker2d-medium-expert	**93.2**	**93.2**	0.0	55.0	26.0	66.6	**98.7**
halfcheetah-mixed	**52.9**	41.5	**52.9**	**54.0**	36.2	45.9	46.2
hopper-mixed	82.0	29.0	82.0	**92.5**	25.3	0.8	48.6
walker2d-mixed	**66.6**	16.6	**66.6**	42.7	10.8	0.9	26.7

Table 1: Here we compare our method averaged over 3 seeds to recent offline model-free and model-based RL algorithms. We report the normalized score where 100 is the performance of a fully trained SAC policy and 0 is the performance of a uniform random policy. For the other methods, we report the results from their own papers or the original D4RL paper. "-expert" results for MOPO were not included in the original paper and thus are omitted here.

5 EXPERIMENTS

In our experiments, we aim to address two questions: (1) Is AWAC an effective initialization algorithm? (2) When can we further improve performance by fine-tuning with MB2PO?

We evaluate (1) by comparing AWAC to other state-of-the-art model-free offline RL algorithms. In particular, we compare our results to BRAC-v (Wu et al., 2019), BEAR (Kumar et al., 2019), and CQL (Kumar et al., 2020) on the Gym-MuJoCo tasks in the D4RL benchmark.

We evaluate (2) by fine-tuning the policy and Q-function, after running AWAC for 100000 gradient steps, with MB2PO. In addition to the model-free offline RL algoirthm above, we also compare these results to MOPO, which to the best of our knowledge is the state-of-the-art MB offline RL algorithm on the Gym-MuJoCo tasks in the D4RL benchmark.

The Gym-MuJoCo tasks are a standard in evaluating modern deep RL algorithms. The goal in these tasks is to learn to travel as far forward as possible within a set horizon on a variety of different robots. The D4RL benchmark contains a variety of precollected datasets for the halfcheetah, walker2d, and hopper tasks. For each robot task, there are 5 different provided datasets. The "-random" datasets contain 1 million samples collected from a randomly initialized policy. The "-medium" datasets contain 1 million samples collected from a partially trained RL policy. The "-expert" datasets contain 1 million samples collected from a fully trained RL policy. The "-mixed" datasets contain all the data in the replay buffer from a partially trained policy. Finally, the "-medium-expert" datasets are a combination of the "-medium" and "-expert" datasets. An important thing to note is that all datasets besides the "-mixed" datasets were collected with only 1 or 2 policies, and thus probably only cover a narrow part of the state-action distribution. While the "-mixed" dataset contains the data collected by all of the policy iterates during an incomplete RL training run, and thus represents a much wider part of the state-action distribution.

Results in Table 1 demonstrate that AWAC on its own can get reasonable results on all the datasets and can approach state-of-the-art results on "-expert" and "-medium-expert" datasets. Unlike the other behavior-regularized model-free methods, AWAC and CQL are able to get near or fully recover expert-level performance when trained on the "medium-expert-" datasets. This indicates that AWAC and CQL are more robust as there is less of a drop in performance compared to other methods when incorporating additional sub-optimal trajectories.

Next, for completeness we fine-tune the AWAC trained policy and Q-function with MB2PO. For each task and dataset, we pretrain an ensemble of 5 probabilistic dynamics models for 500000 gradient steps on the behavioral dataset. We then perform MB2PO for 500 iterations. Each iteration consists of collecting 100000 steps in the conservative MDP, which should run in a few seconds on modern GPU hardware, followed by 1000 gradient steps.

Results in Table 1 demonstrate that our method can be quite effective in certain tasks and datasets. We find that MB2PO improves the performance on all of the "-mixed" and even achieves state-of-the-art on "walker2d-mixed" by a large margin. These strong results in the "-mixed" datasets demonstrate that our model-based fine-tuning method can be especially beneficial when there is sufficient variation in the behavioral dataset. Additionally, the noticeable improvement in "halfcheetah-random" and "halfcheetah-medium" demonstrate that our method can sometimes be effective even when the data was collected by a single policy.

In contrast, we did find that MB2PO fine-tuning always degraded the performance on the "-expert" and "-medium-expert" datasets and sometimes degrades the performance on the "-random" and "medium" datasets for our given parameters. We believe that with enough hyperparameter tuning we could potentially get more stable results for these datasets, but we did not want to overly rely on parameter tuning in the offline setting. We believe that our results demonstrate the difficulty in performing effective uncertainty-aware model-based learning from narrowly distributed datasets collected by only 1 or 2 policies.

Therefore, we suggest that when multiple deployments are possible, AWAC's performance should be compared to AWAC + MB2PO to select the superior policy. Otherwise, we suggest that AWAC + MB2PO should only be deployed in instances where there is sufficient coverage in the behavioral data to learn a helpful model. Following this, we only decide to use MB2PO fine-tuning on the "-mixed" datasets and the non-expert halfcheetah datasets. We include the "mixed-" datasets because there is enough variation to learn an effective model and we include the non-expert halfcheetah datasets because it seems easier to learn an effective model in this task. Otherwise, we use the fully trained AWAC policy. These results are reported in the column **Ours** in Table 1. Note that with this criterion, we are able to achieve results that are competitive or superior to the state-of-the-art on 9 of the 15 tasks.

6 CONCLUSION

We proposed an algorithmic framework that leverages the benefits of both behavior-regularized model-free methods and uncertainty-aware model-based methods. We do this by first training an initial policy with the offline model-free AWAC algorithm. Then, if we believe that we can learn an effective uncertainty-aware dynamics model from the behavioral dataset, we perform fine-tuning with MB2PO. We perform this by learning uncertainty-aware models that are used to create a conservative MDP. Then, we continue to use AWAC to further update our policy and Q-function in this conservative MDP. By using AWAC, we are able to perform policy optimization while implicitly constraining the learned policy's KL divergence to the behavioral policy. We demonstrate that this two stage process allows us to get the best of both worlds between behavior-regularized model-free methods and uncertainty-aware model-based methods. Specifically, the initial AWAC training allows us to often recover the best performing behavior in the dataset, and, when possible, MB2PO fine-tuning can allow us to generalize and outperform the demonstrated behavior.

We see three important directions of future work in order to extended the effectiveness and applicability of MB2PO: 1. developing a rigorous means of determining for what datasets MB2PO fine-tuning can be effective; 2. improving MB RL and neural network uncertain-estimation to increase the number of datasets where MB2PO can be effective; 3. better leveraging behavior-regularization in the policy optimization or the conservative MDP to improve MB2PO stability in narrow datasets.

REFERENCES

Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning*, 2020.

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark, 2020.

Marc G. Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. *CoRR*, abs/1707.06887, 2017. URL http://arxiv.org/abs/1707.06887.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *CoRR*, abs/1805.12114, 2018. URL http://arxiv.org/abs/1805.12114.

Will Dabney, Mark Rowland, Marc G. Bellemare, and Rémi Munos. Distributional reinforcement learning with quantile regression. *CoRR*, abs/1710.10044, 2017. URL http://arxiv.org/abs/1710.10044.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. *CoRR*, abs/1802.09477, 2018. URL http://arxiv.org/abs/1802.09477.

Vicenç Gómez, Hilbert J Kappen, Jan Peters, and Gerhard Neumann. Policy search for path integral control. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 482–497. Springer, 2014.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *CoRR*, abs/1801.01290, 2018. URL http://arxiv.org/abs/1801.01290.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, pp. 12519–12530, 2019.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. Morel : Model-based offline reinforcement learning, 2020.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, pp. 11784–11794, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning, 2020.

Sergey Levine. Deep learning for robots: Learning from large-scale interaction. *Google Research Blog, Março*, 2016.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin A. Riedmiller. Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602, 2013. URL http://arxiv.org/abs/1312.5602.

Ashvin Nair, Murtaza Dalal, Abhishek Gupta, and Sergey Levine. Accelerating online reinforcement learning with offline datasets, 2020.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

Jan Peters and Stefan Schaal. Reinforcement learning by reward-weighted regression for operational space control. In *Proceedings of the 24th international conference on Machine learning*, pp. 745–750, 2007.

Tobias Pohlen, Bilal Piot, Todd Hester, Mohammad Gheshlaghi Azar, Dan Horgan, David Budden, Gabriel Barth-Maron, Hado van Hasselt, John Quan, Mel Vecerík, Matteo Hessel, Rémi Munos, and Olivier Pietquin. Observe and look further: Achieving consistent performance on atari. *CoRR*, abs/1805.11593, 2018. URL http://arxiv.org/abs/1805.11593.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text. *arXiv preprint arXiv:1606.05250*, 2016.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model, 2020.

John Schulman, Sergey Levine, Philipp Moritz, Michael I. Jordan, and Pieter Abbeel. Trust region policy optimization. *CoRR*, abs/1502.05477, 2015. URL http://arxiv.org/abs/1502.05477.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017. URL http://arxiv.org/abs/1707.06347.

Richard S Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *ACM Sigart Bulletin*, 2(4):160–163, 1991.

E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. *CoRR*, abs/1509.06461, 2015. URL http://arxiv.org/abs/1509.06461.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Jost Tobias Springenberg, Scott Reed, Bobak Shahriari, Noah Siegel, Josh Merel, Caglar Gulcehre, Nicolas Heess, and Nando de Freitas. Critic regularized regression, 2020.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning, 2019.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization, 2020.