Synergy-of-Thoughts: Eliciting Efficient Reasoning in Hybrid Language Models

Abstract

Large language models (LLMs) have shown impressive emergent abilities in a wide range of tasks, but the associated expensive API cost greatly limits the real application. Previous works like chain-of-thought (CoT) and tree-of-thoughts (ToT) have predominately focused on enhancing accuracy, but overlook the rapidly increasing API cost, which could be particularly problematic for open-ended real-world tasks with huge solution spaces. Motivated by the dual process theory of human cognition, we propose "Synergy of Thoughts" (SoT) to unleash the synergistic potential of hybrid LLMs with different scales for efficient reasoning. By default, SoT uses smaller-scale language models to generate multiple low-cost intuitive thoughts, which resembles the parallel intuitions produced by *System 1*. We then design a confidence evaluator where the intuitive thoughts are cross-evaluated and introduce a controllable threshold mechanism to decide their mutual conflict. If these intuitive thoughts exhibit conflicts, SoT will invoke the reflective reasoning of scaled-up language models to emulate the intervention of *System 2*, which will override the intuitive thoughts and rectify the reasoning results. This framework is model-agnostic and training-free, which can be flexibly implemented with various off-the-shelf LLMs. Experiments on six representative reasoning tasks show that SoT substantially reduces the API cost by 38.3%∼75.1%, and simultaneously achieves state-of-the-art reasoning accuracy and solution diversity. Notably, the average token cost reduction on open-ended tasks reaches up to 69.1%. Code repo is available at: https://github.com/SoT-lab/SoT.

1 Introduction

Initially conceived for autoregressive text generation, large language models (LLMs), such as GPT (Brown et al., 2020; Radford et al., 2018, 2019) and PaLM (Chowdhery et al., 2023), have been shown to exhibit emergent abilities for reasoning tasks as they scale up (Wei et al., 2022a). A recent landmark study reveals LLMs can unlock their reasoning capability by employing "Chain of Thought" (CoT) (Wei et al., 2022a) prompts to produce intermediate steps for reasoning. The later "Tree of Thoughts" (ToT) framework (Yao et al., 2023) further allows LLMs to deliberate on multiple reasoning paths and make high-quality global decisions via tree search. Search methods like ToT are believed to resemble the reflective reasoning mode found in human cognition, offering greater accuracy but at the expense of significantly high token costs paid for API services. For example, finding a solution for "Game of 24" with ToT consumes approximately 100 times more tokens compared to CoT (Yao et al., 2023). Besides, many open-ended real-world problems (Zheng et al., 2023) with considerably larger solution spaces can also lead to high API costs. Consequently, a critical research problem arises for practical LLM reasoning: Can we strike a more effective balance between reasoning accuracy and costs? This is significant for addressing reasoning problems in low-resource scenarios and facilitating the democratization of LLM reasoning. Some previous works (Chen et al., 2023c; Yue et al., 2023) propose to strategically choose a weaker or stronger LLM for solving the reasoning problem. Despite the cost reduction, these methods are unpromising to obtain higher performance than stronger LLMs, thus only achieving a discounted accuracy-cost trade-off. For better accuracy-cost balance, it's challenging but promising to break down the reasoning process and design a more fine-grained and compact synergy mechanism for hybrid LLMs.

Our study is motivated by human's cognition ability to efficiently tackle complex problems. The prevalent "dual process" theory suggests (Evans, 2010) there are two distinct systems in human reasoning: *System 1*, capable of rapid, preconscious

Figure 1: An illustration of dual process theory (a) and the main differences between SoT (b) and prior works (c) (d) (e). SoT is designed following the synergy paradigm of dual processes in human reasoning.

and intuitive responses; and *System 2*, adept at high-effort, reflective reasoning. Research indicates that everyday decision-making is predominantly governed by *System 1* (Evans, 2010), providing fast responses with minimum resources through the intuition of associative experiences. Although *System 1* makes accurate decisions most of the time, it is also identified as the source of various cognitive biases (Kahneman, 2011), rendering it prone to errors if not properly monitored. On the contrary, *System 2* can avoid intuitive biases through effortful reflection, which is widely encouraged in critical decision-making (Croskerry, 2009).

Human reasoning has been observed to adopt a *default-interventionist* mechanism, which reconciles these two competing systems by firstly using *System 1* to generate low-effort *default* responses, which may be *intervened* upon with the reflection of high-effort *System 2* if the confidence is low. Such mechanisms contribute to simultaneously enhancing both the reasoning accuracy and efficiency of humans. Inspired by this, we propose "Synergy of Thoughts" (SoT) for efficient problem-solving with the synergy of hybrid LLMs (see Figure 1). There are mainly three components in the framework of SoT: *System 1*, *System 2* and a confidence evaluator monitoring the synergy of the two systems. Firstly, to mimic the fast, low-effort *System 1*, SoT employs several hybrid smaller-scale language models to emulate the intuitions derived from different associative experiences of humans. Secondly, SoT implements the reflective *System 2*

with a scaled-up LLM which is considered to possess superior reasoning abilities. Thirdly, we design a confidence evaluator to monitor the synergy of the two systems. Specifically, it conducts a cross-evaluation of the intuitive thoughts from *System 1*, generating a confidence score for each thought. We then introduce a progressively increasing threshold and compare it with the highest confidence score to determine whether there are conflicts between intuitive thoughts. Such a threshold control can also help flexibly adjust the workload of dual systems, delicately modulating the accuracy-cost balance in SoT. Regarding the whole workflow, for each reasoning step, SoT uses *System 1* to generate multiple intuitive thoughts at low costs by default. Next, the confidence evaluator receives these intuitive thoughts and produces an intervention signal based on their conflicts. If the intuitive thoughts are accepted, the final reasoning thought is selected as the best intuitive thought, otherwise, the reflective *System 2* will be invoked to rectify and override the intuitive thoughts, ensuring faithfulness of the reasoning results. With the above designs, SoT is expected to harness the synergistic potential of different-scale LLMs and deliver both efficient and accurate reasoning.

Empirically, we conduct extensive experiments on six complex reasoning tasks, including both close-ended (Game of 24 (Yao et al., 2023), Logic Grid Puzzle (Srivastava et al., 2022), GSM8K (Cobbe et al., 2021)) and open-ended problems (Trivia Creative Writing (Chen et al., 2023a),

Open-ended QA (Chen et al., 2023a), Constrained Generation (Madaan et al., 2023)). The results show that SoT achieves state-of-the-art reasoning accuracy on all six tasks. More importantly, it substantially reduces the API cost by 38.3%~75.1% compared to the second accurate baselines. Particularly, the token cost reduction in open-ended tasks (69.1% on average) is higher than the close-ended tasks (42.6% on average). Besides, we find SoT can also improve the solution diversity, probably because the *default* module implemented by hybrid smaller-scale LLMs can access more diverse information sources. Our further analysis investigates the impact of intervention rate on the accuracy-cost balance, showing wide feasible implementations that could lead to a beneficial synergistic effect by using SoT. Our contributions are as follows:

- We propose SoT, a novel "dual process" theory-inspired framework that unleashes the synergistic potential of hybrid LLMs for cost-efficient reasoning. The framework is model-agnostic and can be implemented with various LLMs flexibly.

- We present a novel confidence evaluation mechanism for hybrid LLMs via cross-evaluation and threshold control, which can effectively monitor the faithfulness of the reasoning process.

- We conduct extensive experiments on six representative reasoning tasks. Empirical results demonstrate that SoT achieves state-of-the-art reasoning accuracy and solution diversity on all tasks. At the same time, SoT substantially reduces the API cost by $38.3\% \sim 75.1\%$ compared to the second accurate baseline.

2 SoT: An Efficient Reasoning Framework with the Synergy of Hybrid LLMs

The evidence suggests that intuition is the dominant basis for real-world decision-making and is often effective; however, it also shows that reliance on intuition can be dangerous and that intervention with high-effort and explicit reasoning is often required, especially when problems have novel features. — Evans et al. (Evans, 2010)

Motivated by the above default-interventionist theory, we introduce SoT, a framework that adaptively integrates two systems for both cost-efficient and accurate LLM reasoning. The whole framework of SoT is illustrated in Figure 2, taking an open-ended QA problem as an example. The complete SoT algorithm is shown in Algorithm 2. Given a complex reasoning task, SoT utilizes problem characteristics to design and decompose intermediate reasoning steps, then adaptively addresses each step through the synergy of two systems monitored by a confidence evaluator. The framework provides a high-level design paradigm that can be implemented with various model architectures in practice. Next, we detail three key components in SoT, including System 1 and System 2, and the designed confidence evaluator for effective synergy of dual systems.

2.1 Efficient Intuitive Thought Generation with System 1

System 1 is fast, intuitive, and largely dependent on relevant experiences, which is suitable to be implemented with smaller-scale language models that have not exhibited emergent reasoning abilities. System 1 aims to efficiently draft intuitive thoughts and advance the reasoning process forward. To mimic the diverse intuitions for humans, here we introduce K distinct smaller-scale LLMs to generate diverse intuitive thoughts, denoted as $\{f_{Ii}(\cdot)|i \in \{1, 2, ..., K\}\}$.

In the current reasoning step t, each LLM independently generates an initial thought based on the previous reasoning thought a_{t-1}. Subsequently, we reconcile the competition among these diverse intuitive thoughts by implementing a cross-model refinement among the K LLMs. The detailed workflow of System 1 is shown in Algorithm 1 and reasoning with System 1 at step t is formulated as follows:

$$\mathcal{H}_t = System\ 1(a_{t-1}) \qquad (1)$$

where $\mathcal{H}_t = \{z_t^i|i \in \{1, 2, ..., K\}\}$ is the set of proposed intuitive thoughts.

2.2 Reflective Thought Intervention with System 2

System 2 is slow, reflective, and high-effort, which is expected to provide high-quality reasoning. In the framework of SoT, System 2 is introduced to correct the biased intuitive thoughts from System 1 to ensure the quality of reasoning results. To achieve this goal, we implement System 2 with a scaled-up LLM, because larger-scale LLMs exhibit more powerful reasoning capabilities than smaller-scale LLMs, which are promising to rectify the unfaithful intuitive thoughts.

Figure 2: Overview of SoT illustrated with a two-step reasoning problem from the Open-ended QA task (making an outline in the first step and giving the answer in the second step). SoT prioritizes reasoning with default intuitions (System 1). When multiple intuitions are evaluated to be conflictual and low-confidence, SoT will intervene with reflective reasoning (invoking System 2) to override them.

Specifically, when intuitive thoughts are considered low-confidence, System 2 will be invoked for thought intervention. The scaled-up LLM takes (1) the last-step thought a_{t-1} and (2) the highest-confidence intuitive thoughts z_t^* at the current reasoning step as inputs and produces a rectified thought a_t overriding previous intuitive thoughts, which is formulated as follows:

$$a_t = System\ 2(a_{t-1}; z_t^*). \qquad (2)$$

2.3 Confidence Evaluation-based Thought Synergy

Motivated by the synergy paradigm of dual processes of human reasoning (Evans, 2006; Kahneman et al., 2002; Stanovich, 2011), we follow a *default-interventionist mechanism* to design the synergy framework of two competing systems. It hypothesizes the two competing systems are reconciled by utilizing System 1 to obtain low-effort intuitive responses by default, which may be intervened upon with the reflection of high-effort System 2 when the confidence of intuitions is low. Following this idea, given a N-step reasoning problem, in each reasoning step $t \in \{1, 2, ..., N\}$, SoT prioritizes utilizing System 1 to propose multiple intuitive thoughts $\mathcal{H}_t$. However, these thoughts might be biased or hallucinated when facing novel and complex problems. When these intuitive thoughts show apparent conflicts, System 2 will be automatically invoked for intervention to rectify the reasoning process. To provide high-quality signals, we propose a novel confidence evaluator for hybrid LLMs via cross-evaluation and threshold control.

2.3.1 Confidence scoring with cross-evaluation

We firstly leverage the diverse knowledge of hybrid LLMs to comprehensively measure the confidence of intuitive thoughts. In each reasoning step, once System 1 provides K intuitive thoughts $\mathcal{H}_t = \{z_t^i | i \in \{1, 2, ..., K\}\}$, the K LLMs in System 1 will conduct a cross-evaluation, where each intuitive thought is scored in turn by each LLM. Denote p_{eval} as the prompt for confidence evaluation, the score of the i-th intuitive thought z_t^i is formulated as:

$$V(z_t^i) = \frac{\sum_{j \in \{1,2,...,K\}} f_{Ij}(p_{eval}; z_t^i)}{K}, \qquad (3)$$

where a larger value of $V(z_t^i)$ indicates higher quality and confidence of the intuitive thought z_t^i.

2.3.2 Intervention signal generation with threshold control

To dynamically adjust the workload of System 1 and System 2, we then introduce an adjustable threshold value ε. The confidence evaluator will accept the highest-confidence intuitive thought $z_t^* = argmax_{z \in \mathcal{H}_t} V(z)$ when $V(z_t^*) > \varepsilon$, otherwise it will reject intuitive thoughts and invoke System 2 to overwrite the thoughts. The intervention signal p is generated according to the following rule:

$$p = \begin{cases} True & V(z_t^*) > \varepsilon, \\ False & \text{otherwise.} \end{cases} \qquad (4)$$

When the signal is $True$, System 2 will intervene and override the intuitive thoughts. The working

frequency of System 1 and 2 can be easily controlled with varying threshold values. To further enhance the faithfulness of the reasoning pipeline, we progressively uplift the confidence threshold with the accumulated number of System 1-based reasoning steps. This is because the reasoning process with more intuitive thoughts is more likely to be biased, where the accepted threshold of intuitive thoughts should be raised.

Conceptually, SoT has several benefits via the harmonious synergy of two systems: (1) *Cost efficiency.* Compared with existing advanced reasoning methods purely relying on high-cost System 2, SoT can significantly save token cost by using cost-efficient System 1 to propose intuitive thoughts. (2) *Solution diversity.* SoT introduces diverse intuitions in System 1 to boost solution diversity, which is especially important for open-ended reasoning problems with huge solution space. (3) *Competitive performance.* Although SoT introduces intuitive thoughts for reasoning, the default-interventionist mechanism can timely prevent the spread of bias and ensure the quality of reasoning results.

2.4 Theoretical Computation Cost Analysis

To highlight the cost efficiency of SoT, we conduct a theoretical token cost analysis. For a more concise analysis, we assume that the output token cost of LLMs is proportional to the input token cost, thus do not distinguish input and output token prices. Denote the average API cost of every few-shot example in System 1 and System 2 as C_I and C_R.

In SoT, the API cost for System 1 with K LLMs consists of three parts. Firstly, the cost of initial thought generation of K LLMs is MKC_I. Secondly, the API cost of interaction within K LLMs consumes $(K-1)KC_I$. Thirdly, each LLM will update their own thought based on feedback from other $K-1$ LLMs and the cost is $(K-1)KC_I$. Therefore, the total cost of System 1 in SoT is:

$$C_{system1} = (M + 2K - 2)KC_I, \qquad (5)$$

where M denotes the number of few-shot examples in the prompt. The cost of the confidence evaluation in SoT comes from the cross-evaluation of K LLMs in System 1, and the total of this part is:

$$C_{eval} = (K-1)KC_I, \qquad (6)$$

If the confidence of intuitions is low, System 2 will be invoked with only the highest confidential intuitive thought as input, thus the cost is:

$$C_{system2} = C_R. \qquad (7)$$

By comparison, the cost of reasoning with only reflective System 2 is:

$$C' = MC_R. \qquad (8)$$

Denote the intervention rate as r, when $(1 - r)(C_{system1} + C_{eval}) + r(C_{system1} + C_{eval} + C_{system2}) < C'$ is satisfied, SoT is expected to effectively save API costs and the corresponding condition of r is (taking $M = 1$ in most cases):

$$r < 1 - \frac{(3K - 2)KC_I}{C_R}. \qquad (9)$$

In the experiment part, we present a detailed analysis combined with specific cost statistics of used LLMs.

3 Experiments

3.1 Experimental Settings

Task setup. We evaluate SoT and compared methods on six representative reasoning tasks including three close-ended tasks (Game of 24 (Yao et al., 2023), Logic Grid Puzzle (Srivastava et al., 2022), GSM8K (Cobbe et al., 2021)) and three open-ended tasks (Trivia Creative Writing (Chen et al., 2023a), Open-ended QA (Chen et al., 2023a), Constrained Generation (Madaan et al., 2023)). Details of task setup are presented in Appendix A.2.

Baselines. We compare SoT with 6 competitive baselines of LLM reasoning (all methods are implemented with GPT-4 unless otherwise stated, for a more fair performance comparison). More implementation details of baselines are presented in Appendix A.3.

Metrics. We evaluate the methods for reasoning tasks from four perspectives including Accuracy (Acc), Diversity (Div), API cost (Cost) and TFLOPS. More details are listed in Appendix A.4.

SoT setup. SoT provides a model-agnostic framework, which is flexible and has various implementations. In our experiments, we try two representative implementations, named SoT_O and SoT_C. In SoT_O, we implement System 1 with three popular open-source and small-scale LLMs including Mistral-7B (Jiang et al., 2023), LLaMA-13B (Touvron et al., 2023) and Yi-34B (Young et al., 2024). GPT-4 (Achiam et al., 2023) is chosen to implement the intervention with System 2. In SoT_C,

Method	Game of 24				Trivia Creative Writing				Logic Grid Puzzle			GSM8K		
	Acc	Div	Cost	TFLOPS	Acc	Div	Cost	TFLOPS	Acc	Cost	TFLOPS	Acc	Cost	TFLOPS
CoT(best of 1)	4%	1.0	0.87	5.22E4	67.1%	3.8	3.37	2.02E5	65.8%	6.72	4.03E5	87.8%	9.58	5.75E5
CoT(best of 5)	14%	1.1	1.73	1.04E5	73.4%	3.9	13.09	7.86E5	67.1%	27.26	1.64E6	91.3%	35.78	2.15E6
LLM-cascade	8%	1.0	1.24	7.86E4	65.7%	5.1	3.21	1.90E5	62.1%	7.98	5.11E5	89.1%	7.75	4.39E5
Self-refine	20%	1.2	24.83	1.51E6	78.2%	4.9	17.79	1.07E6	60.6%	33.37	2.00E6	91.1%	23.45	1.41E6
ToT	64%	2.1	23.37	1.40E6	76.8%	4.4	27.32	1.64E6	66.1%	38.66	2.32E6	91.8%	25.53	1.53E6
SPP	12%	1.2	29.97	1.80E6	79.9%	5.8	10.94	6.56E5	68.3%	20.68	1.24E6	84.6%	63.72	3.82E6
MAD+judge	22%	1.3	28.09	1.69E6	77.4%	6.1	17.00	1.02E6	66.8%	45.00	2.70E6	89.3%	43.68	2.62E6
SoT$_O$	73%	2.3	13.14	1.07E6	82.2%	6.5	2.96	1.82E5	69.9%	11.58	7.91E5	93.4%	12.91	8.74E5
SoT$_C$	76%	2.4	14.42	1.28E6	83.1%	6.3	3.41	2.38E5	71.5%	12.23	8.93E5	94.0%	13.14	8.98E5

Table 1: Results on Game of 24, Trivia Creative Writing, Logic Grid Puzzle and GSM8K tasks.

Methods	FairEval	Div	Cost	TFLOPS
SoT$_O$		**6.1**	7.94	5.01E5
v.s. CoT(best of 1)	71.4%	4.2	4.84	2.91E5
v.s. CoT(best of 5)	63.7%	4.2	20.11	1.21E6
v.s. LLM-cascade	73.9%	5.4	4.39	2.60E5
v.s. Self-refine	58.4%	5.3	31.86	1.91E6
v.s. ToT	65.2%	4.7	58.52	3.51E6
v.s. SPP	68.6%	4.6	26.69	1.60E6
v.s. MAD+judge	59.9%	5.6	36.59	2.20E6

Table 2: Results on Constrained Generation task (FairEval value larger than 50% means results from SoT_O are better).

Methods	FairEval	Div	Cost	TFLOPS
SoT$_O$		**5.5**	6.23	4.48E5
v.s. CoT(best of 1)	67.2%	3.1	2.27	1.36E5
v.s. CoT(best of 5)	63.9%	3.3	8.72	5.23E5
v.s. LLM-cascade	71.1%	4.5	2.49	1.50E5
v.s. Self-refine	58.6%	4.2	15.27	9.16E5
v.s. ToT	60.8%	3.3	19.44	1.17E6
v.s. SPP	66.1%	3.8	8.33	5.00E5
v.s. MAD+judge	55.2%	4.7	17.00	1.02E6

Table 3: Results on Open-ended Question Answer task (FairEval value larger than 50% means results from SoT_O are better).

Methods	Acc	Div	Cost	TFLOPS
SoT (default)	**73%**	**2.4**	13.14	1.07E6
SoT (3 LLaMA-13B)	61%	1.8	14.45	1.19E6
SoT (3 Mistral-7B)	64%	2.0	13.86	1.12E6
SoT (3 Yi-34B)	67%	2.0	14.20	1.18E6
SoT (1 LLaMA-13B)	55%	1.5	14.92	1.26E6
SoT (1 Mistral-7B)	60%	1.8	13.98	1.19E6
SoT (1 Yi-34B)	58%	1.7	14.71	1.21E6

Table 4: Performance of different model choices for SoT_O on Game of 24.

Methods	Acc	Div	Cost	TFLOPS
SoT (default)	**76%**	**2.4**	14.42	1.28E6
SoT (3 GPT-3.5)	70%	2.2	15.65	1.35E6
SoT (3 PaLM2)	67%	2.0	16.93	1.50E6
SoT (3 Gemini1pro)	69%	2.1	15.34	1.28E6
SoT (1 GPT-3.5)	67%	2.1	13.73	1.12E5
SoT (1 PaLM2)	59%	1.9	12.88	1.02E6
SoT (1 Gemini1pro)	62%	1.9	12.12	9.63E5

Table 5: Performance of different model choices for SoT_C on Game of 24.

we implement System 1 with three closed-source and relatively smaller-scale LLMs including GPT-3.5 (Achiam et al., 2023), PaLM2 (Anil et al., 2023) and Gemini1pro (Team et al., 2023). GPT-4 is chosen to implement the intervention with System 2 as before. Besides, it's practicable to implement SoT with other LLMs. We set the threshold value ε as 3.5 and the progressive increasing rate as 10% in the confidence evaluation for all tasks (more choices are analyzed in the experiment part). All LLMs are accessed via APIs and we run all experiments on a CPU machine with 16GB memory. The results of SoT are reported to be the average performance of three runs.

3.2 Main Results

We present the performance comparison of SoT and baselines on six representative reasoning tasks in Table 1, 2 and 3. From the results, we have the following observations:

(1) SoT achieves the best reasoning accuracy with significantly reduced computation cost across different tasks. Broadly, SoT outperforms

Methods	Acc	Div	Cost	TFLOPS
SoT (default)	**82.2%**	**6.5**	2.96	1.82E5
SoT (3 LLaMA-13B)	77.1%	5.8	3.31	2.01E5
SoT (3 Mistral-7B)	79.6%	5.6	3.22	1.97E5
SoT (3 Yi-34B)	80.3%	5.7	3.56	2.13E5
SoT (1 LLaMA-13B)	75.3%	4.4	3.69	2.16E6
SoT (1 Mistral-7B)	76.2%	4.5	2.88	1.71E6
SoT (1 Yi-34B)	77.8%	4.2	3.27	1.96E6

Table 6: Performance of different model choices for SoT_O on Trivia Creative Writing.

Methods	Acc	Div	Cost	TFLOPS
SoT (default)	**83.1%**	**6.3**	3.41	2.38E5
SoT (3 GPT-3.5)	80.9%	5.7	3.94	2.60E5
SoT (3 PaLM2)	78.6%	6.0	3.77	2.51E5
SoT (3 Gemini1pro)	80.1%	5.8	3.38	2.32E5
SoT (1 GPT-3.5)	78.4%	4.2	3.11	2.11E5
SoT (1 PaLM2)	75.9%	4.5	3.32	2.20E5
SoT (1 Gemini1pro)	77.3%	4.5	3.02	2.03E5

Table 7: Performance of different model choices for SoT_C on Trivia Creative Writing.

all compared methods in terms of reasoning accuracy (or quality evaluation with FairEval). For three close-ended reasoning tasks, compared with the best baseline, on average SoT improves 8.6% reasoning accuracy, simultaneously saving 42.6% token costs and 30.0% TFLOPS. For three open-ended reasoning tasks, compared with the best baseline, on average SoT improves 5.9% reasoning accuracy, simultaneously saving 69.1% token costs and 64.5% TFLOPS. We also provide intuitive comparisons of reasoning accuracy and solution diversity versus token costs/TFLOPS on Game of 24 and Trivia Creative Writing in the appendix. Overall, SoT achieves the best trade-off between reasoning performance and cost efficiency.

(2) SoT benefits solution diversity. Except for reasoning accuracy, we also pay attention to the solution diversity of reasoning tasks, which is especially vital for some open-ended problems. It can be found that solutions generated by SoT possess the highest diversity among all methods on four tested tasks. Specifically, for close-ended and open-ended tasks, SoT achieves 14.3% and 12.7% solution diversity improvement on average compared with the best baseline. This might be attributed to the integration of diverse intuitions in System 1 and the further synergy of dual systems.

(3) SoT achieves superior performance under various implementations. We implement SoT with two versions including both open-source and closed-source LLMs for System 1. From the results, SoT consistently outperforms baselines in terms of the trade-off between reasoning performance and costs. This demonstrates the superiority of our designed framework itself and verifies the flexibility of implementations for SoT.

3.3 In-depth Analysis of SoT

Study of model choices. In this part, we explore the impact of choosing different LLMs for the implementation of SoT including both open-source and closed-source LLMs. Here we show the results on Game of 24 and Trivia Creative Writing in Table 4, 5, 6, 7. For each version of SoT, we have tried implementations with each single LLM and hybrid LLMs. From the results, it can be found that utilizing hybrid LLMs to propose intuitions can benefit both accuracy and solution diversity. This might be attributed to hybrid LLMs' ability to access more diverse information sources. Besides, utilizing more LLMs in System 1 can also harvest performance gain.

Study of the threshold value in confidence evaluation. A key design of SoT is the confidential threshold ε to adjust the workload of System 1 and System 2. In our experiments, we regulate that the confidence score ranges from 0 to 5. We then try 7 different threshold values within this interval for SoT_O and present the cost-accuracy trade-off on three tasks in Figure 3. Specifically, $\varepsilon = 0$ means intuitive thoughts from System 1 will always be accepted and SoT degrades to pure System 1, which is cost-efficient but inaccurate. $\varepsilon = 5$ means intuitive thoughts from System 1 will always be overwritten by System 2 and SoT becomes a pure System 2, which is accurate but costly. Observing that the incremental accuracy gain becomes much weaker after $\varepsilon > 3.5$, for simplicity, we set $\varepsilon = 3.5$ in all experiments. Besides, we introduce a progressive threshold-rising strategy where ε increases 10% each time from 3.5 with the accumulation of intuition-based reasoning steps. This further enhances reasoning performance (shown as red dots in Figure 3) and mitigates bias propagation in the reasoning process.

Feasible intervention rate for efficient LLM synergy. Here we conduct a further study combined with empirical statistics to show the practical options of efficient LLM synergy. In terms of

Figure 3: Reasoning cost-accuracy trade-off under different threshold value choices in SoT_O on (a) Game of 24 and (b) Trivia creative writing. The number in the figure means the chosen threshold value.

SoT_C, the most diverse LLM combination (GPT-3.5/PaLM2/Gemini1pro + GPT-4) obtains the lowest intervention rate on the whole. We calculate the upper bound of the required intervention rate of SoT_C according to Eq.(9) and token costs shown in the appendix. The required condition is $r < 57.2\%$, which is higher than the empirical value. By comparison, some more homogeneous synergy groups such as 3 PaLM2 + GPT-4 come with higher intervention rates. Similarly, for SoT_O implemented with LLaMA-13B/Mistrial-7B/Yi-34B + GPT-4, it's expected to save token costs only if $r < 86.3\%$. Such estimation can be easily generalized to any LLM combination and provides a quick assessment of the feasibility of efficient LLM synergy.

4 Related Work

Reasoning with LLMs. With the blooming of LLMs, there has been plenty of work utilizing LLMs to address reasoning problems (Wei et al., 2022b; Yao et al., 2023; Wang et al., 2022; Zhou et al., 2022; Zhang et al., 2023; Besta et al., 2024). The early method is to add few-shot examples in the prompt and let LLMs answer the target question, *i.e.,* standard IO prompting (Brown et al., 2020). However, the resultant performance is very limited, then some more advanced prompting methods are proposed to facilitate the reasoning ability of LLMs. For example, CoT encourages LLMs to think step-by-step, which can activate their inherent reasoning abilities (Wei et al., 2022b). ToT further explores multiple different thought paths and searching in the thought tree with heuristics methods (Yao et al., 2023). Besides, there are other advanced mechanisms introduced to improve LLM reasoning abilities such as reflection (Shinn et al., 2023) and refinement (Madaan et al., 2023). An-

other line of work to enhance the reasoning ability of LLMs is to develop a multi-LLM collaboration system (Du et al., 2023; Liang et al., 2023; Wang et al., 2023b; Chen et al., 2023b; Sun et al., 2023b; Yin et al., 2023). Although these methods facilitate LLM reasoning performance, they all improve reasoning performance along with higher API costs. Differently, our method explores the effective synergy of the dual systems for a better balance between reasoning performance and cost efficiency.

Cost-efficient reasoning with LLMs. Efficiency and cost are critical challenges for LLM reasoning due to the involved complex computations. To improve the speed and cost-effectiveness of LLM reasoning, there have been several approaches, such as quantization (Tao et al., 2022) and model pruning (Sun et al., 2023a). Besides, some works focused on how to utilize the paid API efficiently (Chen et al., 2023c; Šakota et al., 2023). For example, Chen et al. (Chen et al., 2023c) proposed a framework that sends the query to a series of LLMs sequentially if the answers given by the prior model are considered unacceptable. However, all the above methods need to transform the model itself or introduce external fine-tuned verifiers, bringing additional computation costs. Different from the previous model-side modification, we explore a novel path for reducing reasoning cost via diverse LLM synergy, which is training-free and general purpose.

5 Conclusion

We introduce SoT, an effective hybrid LLM synergy framework for efficient reasoning without any additional training or fine-tuning. Following the default-interventionist mechanism of human decision-making, SoT can adaptively switch between intuitive and reflective thoughts, thus facilitating a better balance between reasoning performance and computation costs. Extensive experiments on broad reasoning tasks emphasize the superiority and generalizability of our method. Compared with the best baseline, SoT can further enhance reasoning accuracy and solution diversity, simultaneously reducing the API cost by 38.3% $\sim$ 75.1%. We hope that this work can provide a novel perspective for efficient LLM reasoning with model synergy.

6 Limitations

Currently, there are still some limitations of our method. Firstly, we have not run all baseline methods several times on every task to obtain the error bars due to the huge experimental design space and we will supplement that in the later version of the paper. Secondly, our method can be combined with efficient token-level decoding techniques such as deferral rules on open-source LLMs to further save computational costs. Thirdly, we would like to conduct experiments on more LLM combinations and consider more reasoning tasks such as MATH.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Rohan Anil, Andrew M Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, et al. 2023. Palm 2 technical report. *arXiv preprint arXiv:2305.10403*.

Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, et al. 2024. Graph of thoughts: Solving elaborate problems with large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17682–17690.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. 2023. Chateval: Towards better llm-based evaluators through multi-agent debate. *arXiv preprint arXiv:2308.07201*.

Guangyao Chen, Siwei Dong, Yu Shu, Ge Zhang, Jaward Sesay, Börje F Karlsson, Jie Fu, and Yemin Shi. 2023a. Autoagents: A framework for automatic agent generation. *arXiv preprint arXiv:2309.17288*.

Justin Chih-Yao Chen, Swarnadeep Saha, and Mohit Bansal. 2023b. Reconcile: Round-table conference improves reasoning via consensus among diverse llms. *arXiv preprint arXiv:2309.13007*.

Lingjiao Chen, Matei Zaharia, and James Zou. 2023c. Frugalgpt: How to use large language models while reducing cost and improving performance. *arXiv preprint arXiv:2305.05176*.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Pat Croskerry. 2009. Clinical cognition and diagnostic error: applications of a dual process model of reasoning. *Advances in health sciences education*, 14:27–35.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. 2023. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*.

Jonathan St BT Evans. 2006. The heuristic-analytic theory of reasoning: Extension and evaluation. *Psychonomic bulletin & review*, 13(3):378–395.

Jonathan St BT Evans. 2010. Intuition and reasoning: A dual-process perspective. *Psychological Inquiry*, 21(4):313–326.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.

Daniel Kahneman. 2011. *Thinking, fast and slow*. macmillan.

Daniel Kahneman, Shane Frederick, et al. 2002. Representativeness revisited: Attribute substitution in intuitive judgment. *Heuristics and biases: The psychology of intuitive judgment*, 49(49-81):74.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. 2023. Understanding the effects of rlhf on llm generalisation and diversity. *arXiv preprint arXiv:2310.06452*.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Zhaopeng Tu, and Shuming Shi. 2023. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang,

et al. 2023. Self-refine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*.

Vishakh Padmakumar and He He. 2023. Does writing with language models reduce content diversity? *arXiv preprint arXiv:2309.05196*.

Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. 2018. Improving language understanding by generative pre-training.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Marija Šakota, Maxime Peyrard, and Robert West. 2023. Fly-swat or cannon? cost-effective language model choice via meta-modeling. *arXiv preprint arXiv:2308.06077*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. 2022. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*.

Keith Stanovich. 2011. *Rationality and the reflective mind*. Oxford University Press, USA.

Mingjie Sun, Zhuang Liu, Anna Bair, and J Zico Kolter. 2023a. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*.

Qiushi Sun, Zhangyue Yin, Xiang Li, Zhiyong Wu, Xipeng Qiu, and Lingpeng Kong. 2023b. Corex: Pushing the boundaries of complex reasoning through multi-model collaboration. *arXiv preprint arXiv:2310.00280*.

Chaofan Tao, Lu Hou, Wei Zhang, Lifeng Shang, Xin Jiang, Qun Liu, Ping Luo, and Ngai Wong. 2022. Compression of generative pre-trained language models via quantization. *arXiv preprint arXiv:2203.10705*.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro,

Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Peiyi Wang, Lei Li, Liang Chen, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu, Tianyu Liu, and Zhifang Sui. 2023a. Large language models are not fair evaluators. *arXiv preprint arXiv:2305.17926*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Zhenhailong Wang, Shaoguang Mao, Wenshan Wu, Tao Ge, Furu Wei, and Heng Ji. 2023b. Unleashing the emergent cognitive synergy in large language models: A task-solving agent through multi-persona self-collaboration. *arXiv preprint arXiv:2307.05300*.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. 2022a. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022b. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *arXiv preprint arXiv:2305.10601*.

Zhangyue Yin, Qiushi Sun, Cheng Chang, Qipeng Guo, Junqi Dai, Xuan-Jing Huang, and Xipeng Qiu. 2023. Exchange-of-thought: Enhancing large language model capabilities through cross-model communication. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15135–15153.

Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, et al. 2024. Yi: Open foundation models by 01. ai. *arXiv preprint arXiv:2403.04652*.

Murong Yue, Jie Zhao, Min Zhang, Liang Du, and Ziyu Yao. 2023. Large language model cascades with mixture of thoughts representations for cost-efficient reasoning. *arXiv preprint arXiv:2310.03094*.

Yifan Zhang, Jingqin Yang, Yang Yuan, and Andrew Chi-Chih Yao. 2023. Cumulative reasoning with large language models. *arXiv preprint arXiv:2308.04371*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. 2023.

Judging llm-as-a-judge with mt-bench and chatbot arena. *arXiv preprint arXiv:2306.05685*.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc V Le, et al. 2022. Least-to-most prompting enables complex reasoning in large language models. In *The Eleventh International Conference on Learning Representations*.

A Appendix

A.1 Reproducibility Statements

Our method is convenient to implement and reproducible. We have provided an anonymous version of code repo in the following link: https://github.com/SoT-lab/SoT.

A.2 Details of task setup

For Game of 24, we evaluate performance using the first 50 problems out of the total 100 problems in the original work (Yao et al., 2023). For other tasks, we use the entire dataset to test performance. For each task, we use the same number of few-shot examples with original papers (one-shot in Game of 24 and zero-shot in others). The detail of decomposed intermediate reasoning steps of 6 six tasks according to problem characteristics is presented in Table 8 and Table 9. All of the used datasets are in English.

A.3 Baselines

We compare SoT with the following competitive baselines of LLM reasoning (all methods are implemented with GPT-4 unless otherwise stated, for a more fair performance comparison):

- **Chain-of-thought (CoT)** (Wei et al., 2022b): It firstly proposes to guide LLMs to think step-by-step for reasoning. For a fair comparison, we conduct multiple trials until reaching a similar token cost of our method. For example, the result of CoT (best of 5) is reported as the best performance among five independent trials of CoT.

- **Self-refine** (Madaan et al., 2023): It iteratively produces self-feedback and refines the results. The maximum refinement round is set as 4.

- **Tree-of-thoughts (ToT)** (Yao et al., 2023): It generates multiple thought paths and searches the best solution with the heuristics method. We set the candidate number at each step as 3.

- **LLM-cascade** (Yue et al., 2023): It designs a dynamic reasoning framework with weaker and stronger LLMs controlled by checking the answer consistency of the weak LLM. Different from our method, it only utilizes weaker LLMs from a single source and disentangles the thoughts of weaker and stronger LLMs, limiting the performance upper bound. We follow the implementation of CoT-2D-Vote in the original

paper, setting the number of sampling paths as 20 for GPT-3.5 and 3 for GPT-4.

- **SPP** (Wang et al., 2023b): It transforms a single LLM into different personas and lets them collaborate to solve reasoning problems. We use GPT-4 for the implementation.

- **Multi-agent debate with judgment (MAD+judge)** (Liang et al., 2023): It designs a multi-agent debate pipeline with judgment for reasoning problems. We set three agents implemented with GPT-4 and three rounds of debate.

A.4 Metrics

- **Accuracy (Acc)**: For three close-ended tasks, accuracy is measured directly by the generated answer and ground truths. For Trivia Creative Writing task, accuracy is calculated by # correct answer mentions/# trivia questions. For other open-ended tasks, we utilize FairEval (Wang et al., 2023a) to test the answer quality, following prior works (Chen et al., 2023a; Chan et al., 2023).

- **Diversity (Div)**: Solution diversity of content generated by LLMs has long been an important concern (Kirk et al., 2023; Padmakumar and He, 2023), which is also important for reasoning tasks, especially open-ended problems with huge solution spaces. For Game of 24, we use the number of generated correct answers to measure solution diversity. For Logic Grid Puzzle and GSM8K, there's no concept of diversity. For three open-ended tasks, we modify the prompt of FairEval to let it give a diversity score (from 1 to 10) of two answers from the same model.

- **API cost (Cost)**: It records the dollar cost of running the method once using API services, with great attention in prior works (Yue et al., 2023; Yao et al., 2023).

- **TFLOPS**: It reflects the computational complexity, which is estimated according to the number of parameters following (Kaplan et al., 2020).

A.5 Impact Statements

Our work provides a both cost-efficient and high-performance framework for solving reasoning problems with LLMs, which is expected to benefit broad organizations, such as the NLP research community and industrial companies. By designing such a cost-efficient framework, we empower these

	Trivia Creative Writing	**Logic Grid Puzzle**	**Constrained Generation**
Input	5 random questions	Several characteristics and clues and a question	20-30 random concepts
Output	A passage containing answers to five questions	An answer to the question	A coherent passage containing all concepts
Thoughts	Answers to five questions	Clues that contribute to solving the question	Several groups of concepts categorized by relevance
SoT steps	2	2	2

Table 8: Task Overview of Trivia Creative Writing, Logic Grid Puzzle and Constrained Generation including input, output, intermediate thoughts and the number of reasoning steps.

	Game of 24	**GSM8K**	**Open-ended QA**
Input	4 numbers	A grade school math problem	An open-ended question
Output	An equation to reach 24	An answer to the question	A response to an open-ended question
Thoughts	3 intermediate equations	Steps for solving the math problem	An outline for writing the response
SoT steps	4	2	2

Table 9: Task Overview of Game of 24, GSM8K and Open-ended QA including input, output, intermediate thoughts and the number of reasoning steps.

organizations to harness the reasoning ability of LLMs conveniently, especially for reasoning problems with high complexity. Our work not only makes financial savings but also benefits sustainability development by reducing the carbon emissions brought by extensive computation of running LLMs. There's no identified potential risk.

A.6 Comparison with existing works

In this section, we review some existing frameworks of LLM reasoning to clarify their difference with our method. We use p, s, and $f(\cdot)$ to denote the reasoning problem, solution and the used LLM respectively.

Chain-of-Thought (CoT) CoT enhances LLM reasoning abilities by instructing the model to conduct step-by-step thinking: $p \rightarrow z_1, \cdots, z_t \rightarrow s$, where $z_1, \cdots, z_t$ are intermediate thoughts during reasoning. In each reasoning step, thoughts are generated from a single LLM, which is formulated as follows:

$$z_n = f(p; \{z_m | m < n\}). \tag{10}$$

Tree-of-Thoughts (ToT) ToT uses the LLM to deliberate on multiple reasoning paths and make high-quality global decisions via tree search. Formally, at the n-th reasoning step, ToT generates N thought candidates from a single LLM:

$$\{z_n^k | k = 1, 2, \cdots, N\} = f(p; \{z_m | m < n\}). \tag{11}$$

Then it evaluates all candidate thoughts and selects the best one as the final thought z_n at step n.

The above two well-known methods can enhance LLM reasoning abilities but are limited to using a single LLM (either small-scale or large-scale), suffering from either low performance or high token cost issues. As for most multi-agent debate methods (Liang et al., 2023; Du et al., 2023; Wang et al., 2023b), they are also focusing on reasoning with larger-scale LLMs, resulting in challenges on complex reasoning tasks due to the expensive API costs. To address this issue, we propose an adaptive synergy framework composed of hybrid LLMs, fully exploiting the unique strengths of different-scale LLMs.

A.7 Token Prices of Used LLMs

Here we show the token prices of different LLMs we use in this work in Table 10. The statistics of GPT-3.5 and GPT-4 are from the official report of OpenAI[1]. The statistics of Yi-34B are from the official report of 01.AI[2]. The statistics of Gemini1pro are from the official report of Google[3]. The statistics of Mistral-7B are from the official report of Mistral AI[4]. The statistics of LLaMA-13B are

[1]https://openai.com/pricing
[2]https://platform.lingyiwanwu.com/
[3]https://ai.google.dev/pricing
[4]https://mistral.ai/technology

from Baidu online service platform[5]. PaLM2 is cost-free when the work is done.

Model	Input /1M tokens	Output /1M tokens
GPT-3.5	$1.5	$2
GPT-4	$30	$60
Yi-34B	$0.35	$0.35
Gemini1pro	$0.5	$1.5
Mistrial-7B	$0.25	$0.25
LLaMA-13B	$0.28	$0.28
PaLM2	0	0

Table 10: Input and output token prices of used LLMs.

A.8 Specific Algorithm of System 1

We show the specific algorithm for implementing System 1 in Algorithm 1.

Algorithm 1: Algorithm of System 1

Input: Last-step thought a_{t-1}, the number of hybrid LLMs K

for $k \in \{1, 2, ..., K\}$ **do**
$\quad z_t^k = f_{Ik}(a_{t-1})$ // Generate
$\qquad$ initial thoughts
end
for $j \in \{1, 2, ..., K\}$ **do**
$\quad$ **for** $k \in \{1, 2, ..., K\} \setminus \{j\}$ **do**
$\qquad h_{j \to k} = f_{Ij}(p_{inter}; z_t^k)$ // Mutual
$\qquad\qquad$ refinement between LLMs
$\quad$ **end**
end
for $k \in \{1, 2, ..., K\}$ **do**
$\quad z_t^k = f_{Ik}(p_{update}; \sum_{j \in \{1,2,...,K\} \setminus \{k\}} h_{j \to k})$
$\qquad$ // Update intuitions
end
$\mathcal{H}_t = \{z_t^1, z_t^2, ..., z_t^K\}$
return $\mathcal{H}_t$

A.9 Specific Algorithm of SoT

We show the specific algorithm of the whole framework of SoT in Algorithm 2.

A.10 Empirical Average Intervention Rates

Here we show the empirical average intervention rates of different LLM combinations in System 1 on six tasks in Table 11, for measuring the practicability to maintain cost-saving by using SoT.

A.11 Supplement of Main Results

Here we supplement the main results about SoT_C on Constrained Generation and Open-ended QA tasks in Table 12 and Table 13. The results show that SoT_C outperforms all baselines, consistent with the conclusion in the main text.

A.12 Statistical Tests of Results

Here we report the reasoning accuracy of SoT with standard error in five independent trials in Table 14. It can be seen that SoT achieves significant performance improvement compared with baselines.

A.13 Performance-cost Trade-off Analysis on More Reasoning Tasks

We conduct performance-cost visualization analysis on all reasoning tasks. The results are shown in Figure 4, 5, 6, 7, 8, 9 and 10. Consistent with the results in the main text, SoT achieves the best performance-cost trade-off among all methods.

A.14 Illustrations of SoT on More Reasoning Tasks

In the main paper, we illustrate SoT with an example from Open-ended QA tasks. For a better understanding of the scheme of SoT, here we present more cases from some other reasoning tasks in Figure 11, 12, 13 and 14.

A.15 Prompts used in SoT

We present the designed prompt templates for implementing System 1, System 2 and the confidence evaluator of SoT, taking Trivia Creative Writing (see Figure 15 and 17) and Game of 24 (see Figure 16 and 18) tasks as examples.

---

[5]https://console.bce.baidu.com/qianfan

Algorithm 2: Algorithm of SoT

Input: Required reasoning steps N, input task description x
$t = 0$ // Current reasoning step
$a_t = x$ // Intialize current thoughts
while $t \leq N$ **do**
    $t = t + 1$
    $\mathcal{H}_t = System\ 1(a_{t-1})$ // Propose intuitions by System 1
    $p, z_t^* = Confidence\ Evaluator(\mathcal{H}_t)$ // Confidence evaluation
    if p **then**
        $a_t = System\ 2(a_{t-1}; z_t^*)$ // Intervention with reflective System 2
    end
    else
        $a_t = z_t^*$ // Output the highest-confidence intuitive thought
    end
end
return a_t

LLM combinations	Game of 24	Puzzle	GSM8K	Creative Writing	OpenQA	CommonGen
3 GPT-3.5	28%	49%	24%	51%	55%	56%
3 PaLM2	33%	55%	27%	57%	57%	61%
3 Gemini1pro	30%	53%	26%	50%	54%	58%
GPT-3.5/PaLM2/Gemini1pro	26%	44%	23%	42%	52%	53%
3 LLaMA-13B	39%	68%	41%	65%	67%	65%
3 Mistral-7B	36%	61%	39%	60%	61%	63%
3 Yi-34B	36%	59%	36%	61%	59%	59%
LLaMA-13B/Mistral-7B/Yi-34B	33%	54%	35%	49%	54%	57%

Table 11: Empirical average intervention rate on six reasoning tasks.

Methods	FairEval	Diversity	Cost ($)	TFLOPS
SoT_C		**6.2**	8.32	5.44E5
v.s. CoT(best of 1)	73.0%	4.2	4.84	2.91E5
v.s. CoT(best of 5)	66.4%	4.2	20.11	1.21E6
v.s. Self-refine	59.2%	5.3	31.86	1.91E6
v.s. ToT	62.9%	4.7	58.52	3.51E6
v.s. SPP	70.7%	4.6	26.69	1.60E6
v.s. MAD+judge	57.6%	5.6	36.59	2.20E6

Table 12: Results on Constrained Generation task of SoT_C (FairEval value larger than 50% means results from SoT_C are better).

Methods	FairEval	Diversity	Cost ($)	TFLOPS
SoT_C		**5.2**	6.77	4.72E5
v.s. CoT(best of 1)	68.4%	3.1	2.27	1.36E5
v.s. CoT(best of 5)	62.8%	3.3	8.72	5.23E5
v.s. Self-refine	60.5%	4.2	15.27	9.16E5
v.s. ToT	62.3%	3.3	19.44	1.17E6
v.s. SPP	64.5%	3.8	8.33	5.00E5
v.s. MAD+judge	58.1%	4.7	17.00	1.02E6

Table 13: Results on Open-ended Question Answer task (FairEval value larger than 50% means results from SoT_C are better).

Method	Game of 24	Trivia Creative Writing	Logic Grid Puzzle	GSM8K
CoT(best of 1)	4%	67.1%	65.8%	87.8%
CoT(best of 5)	14%	73.4%	67.1%	91.3%
LLM-cascade	8%	65.7%	62.1%	89.1%
Self-refine	20%	78.2%	60.6%	91.1%
ToT	64%	76.8%	66.1%	91.8%
SPP	12%	79.9%	68.3%	84.6%
MAD+judge	22%	77.4%	66.8%	89.3%
SoT$_O$	73±2%	82.2±0.7%	69.9±0.8%	93.4±0.3%
SoT$_C$	**76±1%**	**83.1±0.9%**	**71.5±0.5%**	**94.0±0.5%**

Table 14: Performance comparison with standard error on Game of 24, Trivia Creative Writing, Logic Grid Puzzle and GSM8K tasks.

Figure 4: The reasoning accuracy, solution diversity versus token costs/TFLOPS on Game of 24 (a) (b) and Trivia Creative Writing (c) (d). SoT achieves a better performance-cost trade-off than all compared methods.

Figure 5: The reasoning accuracy versus token costs/TFLOPS on Logic Grid Puzzle task. SoT achieves a better performance-cost trade-off than all compared methods.

Figure 6: The reasoning accuracy versus token costs/TFLOPS on GSM8K task. SoT achieves a better performance-cost trade-off than all compared methods.

Figure 7: The reasoning accuracy, solution diversity versus token costs/TFLOPS of SoT_O and baselines on Open-ended QA task. SoT_O achieves a better performance-cost trade-off than all compared methods.

Figure 8: The reasoning accuracy, solution diversity versus token costs/TFLOPS of SoT_O and baselines on Constrained Generation task. SoT_O achieves a better performance-cost trade-off than all compared methods.

Figure 9: The reasoning accuracy, solution diversity versus token costs/TFLOPS of SoT_C and baselines on Open-ended QA task. SoT_C achieves a better performance-cost trade-off than all compared methods.

Figure 10: The reasoning accuracy, solution diversity versus token costs/TFLOPS of SoT_C and baselines on Constrained Generation task. SoT_C achieves a better performance-cost trade-off than all compared methods.

Figure 11: An illustrative example of SoT from Game of 24 Task.

Figure 12: An illustrative example of SoT from Logic Grid Puzzle Task.

Figure 13: An illustrative example of SoT from Trivia Creative Writing Task.

Figure 14: An illustrative example of SoT from Constrained Generation Task.

Prompts used for LLMs in System 1 of SoT on Trivia Creative Writing Task

Prompt_Template_For_the_Intuition:
Please answer the following {n} questions.
How confident are you in your answer on a scale of 0 to 5.
Please give the reasons for your answer.
Here are some examples:
questions:1.Who was the man behind The Chipmunks?2.Which Lloyd Webber musical
    premiered in the US on 10th December 1993?3.Who was the next British Prime
    Minister after Arthur Balfour?4.Who had a 70s No 1 hit with Kiss You All
    Over?5.What claimed the life of singer Kathleen Ferrier?
response_gpt_iterate: Answer:
1. Ross Bagdasarian Sr.
2. Sunset Boulevard
3. Henry Campbell-Bannerman
4. Exile
5. Breast cancer
Reason:
1. Ross Bagdasarian Sr., also known by his stage name David Seville, created Alvin and
    the Chipmunks, a popular music group of animated chipmunks, in 1958. He was
    responsible for writing and recording songs in which he pitched up the speed of
    the voice recordings to create distinctive high-pitched voices, which became the
    hallmark of The Chipmunks.
2. "Sunset Boulevard," a musical composed by Andrew Lloyd Webber, premiered in the
    United States on December 10, 1993. This musical is based on the 1950 film of the
    same name and features a score by Lloyd Webber with lyrics by Don Black and
    Christopher Hampton.
3. Henry Campbell-Bannerman succeeded Arthur Balfour as the Prime Minister of the
    United Kingdom. Balfour resigned in December 1905, and Campbell-Bannerman took
    office shortly thereafter, serving from 1905 to 1908.
4. The band Exile had a number one hit in the 1970s with the song "Kiss You All Over."
    Released in 1978, the song became very popular and topped the Billboard Hot 100
    chart.
5. Kathleen Ferrier, a renowned British contralto, died from breast cancer in 1953.
    Her battle with the disease was well-documented, and it ultimately claimed her
    life at the age of 41.
I'm not sure about the answer to question one, but I'm pretty sure about the rest.
Confidence score:4
questions:1.\"Who was the target of the failed \"\"Bomb Plot\"\" of 1944?\"2.Who had
    an 80s No 1 hit with Hold On To The Nights?3.Which musical featured the song The
    Street Where You Live?4.In what year's Olympics were electric timing devices and
    a public-address system used for the first time?5.Who was the director of the CIA
    from 1976-81?
Answer:
1. Adolf Hitler
2. Richard Marx
3. My Fair Lady
4. 1912
5. Stansfield Turner
Reason:
1. The "Bomb Plot" of 1944, also known as the July 20 Plot, targeted Adolf Hitler. It
    was an assassination attempt by German military officers who opposed Hitler's
    regime and sought to kill him with a bomb during a meeting at his Wolf's Lair
    headquarters.
2. Richard Marx had a number one hit in the 1980s with the song "Hold On to the
    Nights." This song reached the top of the Billboard Hot 100 chart in 1988,
    marking one of his several top hits during that era.
3. "The Street Where You Live" is a well-known song from the musical "My Fair Lady."
    This musical, based on George Bernard Shaw's play "Pygmalion," features this song
    as a romantic ballad sung by the character Freddy Eynsford-Hill.
4. The 1912 Olympics, held in Stockholm, Sweden, were the first to use electric timing
    devices and a public-address system. These technological advancements helped in
    improving the accuracy of timing results and facilitating communication during
    the events.
5. Stansfield Turner served as the Director of the Central Intelligence Agency (CIA)
    from 1976 to 1981. He was appointed by President Jimmy Carter and served during a
    period of significant reform and restructuring within the agency.
I'm not sure about the answers to questions four and five, I'm pretty sure about the
    rest
Confidence score:3
questions:{questions}
Write a short and coherent passage about {topic} that incorporates the following:
    {answers}
Please rate the reasonability, relevance, accuracy, coherence of your passage on a
    scale of 0 to 5.
Remember each words should be mentioned.
Your output should be of the following format:

Passage:
Confidence score:

Figure 15: Prompts used for LLMs in System 1 of SoT on Trivia Creative Writing Task.

Prompts used for LLMs in System 1 of SoT on Game of 24 Task.

```
Prompt_Template_For_the_Intuition:
Input: 2 8 7 14
Possible next steps:
14 + 2 = 16 (left: 16 8 7)
8 - 2 = 6 (left: 6 7 14)
2 * 8 = 16 (left: 16 7 14)
8 / 2 = 4 (left: 4 7 14)
7 + 8 = 15 (left: 15 2 14)
8 - 7 = 1 (left: 1 2 14)
7 * 8 = 56 (left: 56 2 14)
14 / 7 = 2 (left: 2 2 8)
14 - 8 = 6 (left: 6 2 7)
14 / 2 = 7 (left: 7 8 7)
2 * 14 = 28 (left: 28 8 7)
2 + 7 = 9 (left: 9 8 14)
14 - 2 = 12 (left: 12 8 7)
Input: {input}
Possible next steps

Use numbers and basic arithmetic operations (+ - * /) to obtain 24. Each step, you are
    only allowed to choose two of the remaining numbers to obtain a new number.
Input: 4 4 6 8
Steps:
4 + 8 = 12 (left: 4 6 12)
6 - 4 = 2 (left: 2 12)
2 * 12 = 24 (left: 24)
Answer: (6 - 4) * (4 + 8) = 24
Input: 1 4 8 8
Steps:
8 / 4 = 2 (left: 1 2 8)
1 + 2 = 3 (left: 3 8)
3 * 8 = 24 (left: 24)
Answer: (1 + 8 / 4) * 8 = 24
Input: 5 5 5 9
Steps:
5 + 5 = 10 (left: 5 9 10)
10 + 5 = 15 (left: 9 15)
15 + 9 = 24 (left: 24)
Answer: ((5 + 5) + 5) + 9 = 24
Input: 2 9 10 12
Steps:
12 * 2 = 24 (left: 9 10 24)
10 - 9 = 1 (left: 1 24)
24 * 1 = 24 (left: 24)
Answer: (12 * 2) * (10 - 9) = 24
Input: 4 9 10 13
Steps:
13 - 10 = 3 (left: 3 4 9)
9 - 3 = 6 (left: 4 6)
4 * 6 = 24 (left: 24)
Answer: 4 * (9 - (13 - 10)) = 24
Input: {input}
```

Figure 16: Prompts used for LLMs in System 1 of SoT on Game of 24 Task.

Prompts of the confidence evaluator and intervention with System 2 in SoT on Trivia Creative Writing Task

Prompt_Template_For_Confidence_Evaluator:
Other model has answered several questions.
You need to determine whether these answers are correct and then give a score on a scale of 0 to 5. If you think all the
answers are correct, give them 5 points. If you think some answers are wrong, reduce the score accordingly.
You can't be overconfident, and If you're not sure about the answer, You shouldn't give it a score.
You must format the output as in the example, including analysis and score.
Hera is an example:
questions:1.\"Who was the target of the failed \"\"Bomb Plot\"\" of 1944?\"2.Who had an 80s No 1 hit with Hold On To The
Nights?3.Which musical featured the song The Street Where You Live?4.In what year's Olympics were electric timing
devices and a public-address system used for the first time?5.Who was the director of the CIA from 1976-81?
Answer:
1. Adolf Hitler
2. Richard Marx
3. My Fair Lady
4. 1912
5. Stansfield Turner
Analysis: I think the answer to question five is George Bush. I'm not sure answer to question three is correct. So there are
three answers that I think are correct.
Score: 3
------------------New questions-----------------------
questions:{questions}
Answers:{answers}

Other model has written a short and coherent passage about {topic} that incorporates the following: {answers}
passage:{passage}
Please rate the reasonability, relevance, accuracy, coherence of the passage on a scale of 0 to 5.
Please write a score directly without explanation.
Your output should be of the following format:
Score:
Give a score

Prompt_Template_For_the_Intervention_with_System_2:
{previous answers}
Please modify the answer if you think the possible answer is wrong.
Please write your answer to the question directly without explanation.
Your output should be of the following format:
Answer:
Your answer here

{previous answers}
Write a short and coherent passage about {topic} that incorporates the following: {answers}
Remember each words should be mentioned.
Your output should be of the following format:
Passage:
Your passage here.

Figure 17: Prompts of the confidence evaluator and intervention with System 2 in SoT on Trivia Creative Writing Task.

Prompt_Template_For_Confidence_Evaluator:
Evaluate if given numbers can reach 24 and then give a score on a scale of 0 to 5
10 14
10 + 14 = 24
sure, score: 5
4 4 10
4 + 4 + 10 = 8 + 10 = 18
4 * 10 - 4 = 40 - 4 = 36
(10 - 4) * 4 = 6 * 4 = 24
sure, score: 5
5 7 8
5 + 7 + 8 = 12 + 8 = 20
(8 - 5) * 7 = 3 * 7 = 21
I cannot obtain 24 now, but numbers are within a reasonable range
likely, score: 2
10 10 11
10 + 10 + 11 = 31
(11 - 10) * 10 = 10
10 10 10 are all too big
impossible, score: 0
1 3 3
1 * 3 * 3 = 9
(1 + 3) * 3 = 12
1 3 3 are all too small
impossible, score: 0
{input}

Use numbers and basic arithmetic operations (+ - * /) to obtain 24. Given an input and
    an answer, evaluate if the answer is correct and then give a score on a scale of
    0 to 5, i.e. it uses each input exactly once and no other numbers, and reach 24.
Input: 4 4 6 8
Answer: (4 + 8) * (6 - 4) = 24
Judge:
sure, score: 5
Input: 4 4 6 8
Answer: (4 + 8) * (6 - 4) + 1 = 25
Judge:
impossible, score: 0
Input: 2 9 10 12
Answer: 2 * (12 - 10) = 24
Judge:
impossible, score: 0
Input: 4 9 10 13
Answer: (13 - 4) * (10 - 9) = 24
Judge:
impossible, score: 0
Input: {input}
Answer: {answer}
Judge:

Prompt_Template_For_the_Intervention_with_System_2:
Input: 2 8 8 14
Possible next steps:
2 + 8 = 10 (left: 8 10 14)
8 / 2 = 4 (left: 4 8 14)
14 + 2 = 16 (left: 8 8 16)
2 * 8 = 16 (left: 8 14 16)
8 - 2 = 6 (left: 6 8 14)
14 - 8 = 6 (left: 2 6 8)
14 / 2 = 7 (left: 7 8 8)
14 - 2 = 12 (left: 8 8 12)
{previous answers}
Input: {input}
Possible next steps:

Use numbers and basic arithmetic operations (+ - * /) to obtain 24. Each step, you are
    only allowed to choose two of the remaining numbers to obtain a new number.
Input: 4 4 6 8
Steps:
4 + 8 = 12 (left: 4 6 12)
6 - 4 = 2 (left: 2 12)
2 * 12 = 24 (left: 24)
Answer: (6 - 4) * (4 + 8) = 24
{previous answers}
Input: {input}

Figure 18: Prompts of the confidence evaluator and intervention with System 2 in SoT on Game of 24 Task.