A framework for bilevel optimization that enables stochastic and global variance reduction algorithms

Abstract

Bilevel optimization, the problem of minimizing a *value function* which involves the arg-minimum of another function, appears in many areas of machine learning. In a large scale empirical risk minimization setting where the number of samples is huge, it is crucial to develop stochastic methods, which only use a few samples at a time to progress. However, computing the gradient of the value function involves solving a linear system, which makes it difficult to derive unbiased stochastic estimates. To overcome this problem we introduce a novel framework, in which the solution of the inner problem, the solution of the linear system, and the main variable evolve at the same time. These directions are written as a sum, making it straightforward to derive unbiased estimates. The simplicity of our approach allows us to develop global variance reduction algorithms, where the dynamics of all variables is subject to variance reduction. We demonstrate that SABA, an adaptation of the celebrated SAGA algorithm in our framework, has $O(\frac{1}{T})$ convergence rate, and that it achieves linear convergence under Polyak-Łojasciewicz assumption. This is the first stochastic algorithm for bilevel optimization that verifies either of these properties. Numerical experiments validate the usefulness of our method.

1 Introduction

Bilevel optimization is attracting more and more attention in the machine learning community thanks to its wide range of applications. Typical examples are hyperparameters selection [5, 35, 16, 6], data augmentation [11, 39], implicit deep learning [3] or neural architecture search [31]. Bilevel optimization aims at minimizing a function whose value depends on the result of another optimization problem:

$$\min_{x \in \mathbb{R}^d} h(x) = F(z^*(x), x), \quad \text{such that } z^*(x) \in \arg\min_{z \in \mathbb{R}^p} G(z, x) \ , \tag{1}$$

where F and G are two real valued functions defined on $\mathbb{R}^p \times \mathbb{R}^d$. G is called the *inner function*, F is the *outer function* and h is the *value function*. Similarly, z is the *inner variable* and x is the *outer variable*. In most cases, the function z^* can only be approximated by an optimization algorithm, which makes bilevel optimization problems challenging. Under appropriate hypotheses, the function h is differentiable, and the chain rule and implicit function theorem give for any $x \in \mathbb{R}^d$

$$\nabla h(x) = \nabla_2 F(z^*(x), x) + \nabla_{21}^2 G(z^*(x), x) v^*(x) \ , \tag{2}$$

where $v^*(x) \in \mathbb{R}^p$ is the solution of a linear system

$$v^*(x) = - \left[\nabla_{11}^2 G(z^*(x), x) \right]^{-1} \nabla_1 F(z^*(x), x) \ . \tag{3}$$

In the light of (2) and (3), it turns out that the derivation of the gradient of h at each iteration is cumbersome because it involves two subproblems: the resolution of the inner problem to find an

approximation of $z^*(x)$ and the resolution of a linear system to find an approximation of $v^*(x)$. It makes the practical implementation of first order methods like gradient descent for (1) challenging.

As is the case in many machine learning problems, we suppose in this paper that F and G are empirical means:

$$F(z,x) = \frac{1}{m} \sum_{j=1}^{m} F_j(z,x), \quad G(z,x) = \frac{1}{n} \sum_{i=1}^{n} G_i(z,x) \ .$$

This structure suggests the use of stochastic methods to solve (1). For single-level problems (that is, classical optimization problems where one function should be minimized), using Stochastic Gradient Descent (SGD; [38, 7]) and variants is natural because individual gradients are straightforward unbiased estimators of the gradient. In the bilevel framework, we want to develop algorithms that make progress on problem (1) by using only a few functions F_j and G_i at a time. However, since ∇h involves

Figure 1: Convergence curves of the two proposed methods on a toy problem. SABA is a stochastic method that achieves fast convergence on the value function.

the inverse of the Hessian of G, building such stochastic algorithms is quite challenging, one of the difficulties being that there is no straightforward unbiased estimator of ∇h. Still, in settings where m or n are large, where computing even a single evaluation of F or G is extremely expensive, stochastic methods are the only scalable algorithms.

Variance reduction [25, 13, 40, 12] is a popular technique to obtain fast stochastic algorithms. In a single-level setting, these methods build an approximation of the gradient of the objective function using only stochastic gradients. Contrary to SGD, the variance of the approximation goes to 0 as the algorithm progresses, allowing for faster convergence. For instance, the SAGA method [13] achieves linear convergence if the objective function satisfies a Polyak-Łojasciewicz inequality, and $O(\frac{1}{T})$ convergence rate on smooth non-convex functions [37]. The extension of these methods to bilevel optimization is a natural idea to develop faster algorithms. However, this idea is hard to implement because it is hard to derive unbiased estimators of ∇h, let alone variance reduction ones.

Contributions. We introduce a **novel framework for bilevel optimization** in Section 2, where the inner variable, the solution of the linear system (3) and the outer variable evolve jointly. The evolution directions are written as sums of derivatives of F_j and G_i, which allows us to derive simple unbiased stochastic estimators. In this framework, we propose SOBA, an extension of SGD (Section 2.1), and SABA (Section 2.2), an extension of the variance reduction algorithm SAGA [13]. In Section 3 we analyse the convergence of our methods. SOBA is shown to achieve $\inf_{t \leq T} \mathbb{E}[\|\nabla h(x^t)\|^2] = O(\log(T)T^{-\frac{1}{2}})$ with decreasing step sizes. We prove that SABA with fixed step sizes achieves $\frac{1}{T} \sum_{t=1}^{T} \mathbb{E}[\|\nabla h(x^t)\|^2] = O(\frac{1}{T})$. SABA is therefore, to the best of our knowledge, the first **stochastic bilevel algorithm that matches the convergence rate of gradient descent** on h. We also prove that SABA achieves **linear convergence** under the assumption that h satisfies a Polyak-Łojasciewicz inequality. To the best of our knowledge, SABA is also the first stochastic bilevel algorithm to feature such a property. Importantly, **these rates match the rates of the single level counterparts of each algorithm in non-convex setting** (SGD for SOBA and SAGA for SABA). Finally, in Section 4, we provide an **extensive benchmark** of many stochastic bilevel methods on hyperparameters selection and data hyper-cleaning, and illustrate the usefulness of our approach.

Related work. The bilevel optimization problem has a strong history in the optimization community, taking root in game theory [42]. Gradient-based algorithms to solve (1) can be mainly classified in two different categories depending on how ∇h is computed, by *automatic* or *implicit differentiation*. Since the solution of the inner problem $z^*(x)$ is approximated by the output of an iterative algorithm, it is possible to use automatic differentiation [43, 29] to approximate $\nabla h(x)$. It consists in differentiating the different steps of the inner optimization algorithm – see [4] for a review – and has been applied successfully to several bilevel problems arising in machine learning [14, 15]. One of the main drawbacks of this approach is that it requires to store in memory each iterate of the

78 inner optimization algorithm, although this problem can sometimes be overcome using invertible
79 optimization algorithms [32] or truncated backpropagation [41].

80 The use of the implicit function theorem to obtain (2) and (3) is known as implicit differentiation [5].
81 While the cost of computing exactly (2) can be prohibitive for large scale problems, Pedregosa [35]
82 showed that we can still converge to a stationary point of the problem by using approximate solutions
83 of the inner problem and linear system (3), if the approximation error goes to 0 sufficiently quickly.
84 The complexity of approximate implicit differentiation has been studied in [18]. Ramzi et al. [36]
85 propose to reuse the computations done in the forward pass to approximate the solution of the linear
86 system (3) when the inner problem is solved thanks to a quasi-Newton method.

87 In the last few years, several works have proposed different strategies to solve (1) in a stochastic
88 fashion. A first set of methods relies on *two nested loops*: one inner loop to solve the inner problem
89 with a stochastic method, and one outer loop to update the outer variable with an approximate gradient
90 direction. In [17, 24, 9] the authors use several SGD iterations for the inner problem and then use
91 stochastic Neumann approximations to get an estimate solution of the linear system, which provides
92 them with an approximation of ∇h used to update x. The analysis of this kind of method was
93 refined by Chen et al. [9], allowing to achieve the same convergence rates as those of SGD. The
94 convergence of the hypergradient when using stochastic solvers for the inner problem and the linear
95 system has been studied in [19]. Arbel and Mairal [2] replace the Neumann approximation by SGD
96 steps to estimate (3). Other authors have proposed *single loop* algorithms, alternating steps in the
97 inner and the outer problem. Hong et al. [22] propose to perform Neumann approximations of the
98 inverse Hessian and use a single SGD step for the inner problem. It was refined in [21] and [44]
99 where the optimization procedure uses a momentum acceleration. Other variations around this idea
100 include [23, 26, 10, 20, 28]. We refer to Table 1 in appendix for a detailed comparison of these
101 methods.

102 **Notation.** The set of integers between 1 and n (included) is denoted $[n]$. For $f : \mathbb{R}^p \times \mathbb{R}^d \to \mathbb{R}$,
103 we denote $\nabla_i f(z, x)$ its gradient w.r.t. the i^{th} variable. The Hessian of f with respect to the first
104 variable is denoted $\nabla_{11}^2 f(z, x) \in \mathbb{R}^{p \times p}$, and the cross-derivatives matrix is $\nabla_{21}^2 f(z, x) \in \mathbb{R}^{d \times p}$. If v
105 is a vector, $\|v\|$ is its Euclidean norm. If M is a matrix, $\|M\|$ is its spectral norm. A function is said
106 to be L-smooth, for $L > 0$, if it is differentiable, and its gradient is L-Lipschitz.

2 Proposed framework

108 In this section, we introduce our framework in which
109 the solution of the inner problem, the solution of the
110 linear system (3) and the outer variable all evolve at
111 the same time, following directions that are written
112 as a sum of derivatives of F_j and G_i. We define

$$D_z(z, v, x) = \nabla_1 G(z, x) \ , \tag{4}$$

$$D_v(z, v, x) = \nabla_{11}^2 G(z, x)v + \nabla_1 F(z, x) \ , \tag{5}$$

$$D_x(z, v, x) = \nabla_{21}^2 G(z, x)v + \nabla_2 F(z, x) \ . \tag{6}$$

Algorithm 1 General framework

Input: initializations $z_0 \in \mathbb{R}^p$, $x_0 \in \mathbb{R}^d$,
$v_0 \in \mathbb{R}^p$, number of iterations T, step size
sequences $(\rho^t)_{t<T}$ and $(\gamma^t)_{t<T}$.
for $t = 0, \ldots, T - 1$ **do**
    Update z: $z^{t+1} = z^t - \rho^t D_z^t$,
    Update v: $v^{t+1} = v^t - \rho^t D_v^t$,
    Update x: $x^{t+1} = x^t - \gamma^t D_x^t$,
    where D_z^t, D_v^t and D_x^t are unbiased esti-
    mators of $D_z(z^t, v^t, x^t), D_v(z^t, v^t, v^t)$
    and $D_x(z^t, v^t, x^t)$.
end for

---

113 These directions are motivated by the fact that we
114 have $\nabla h(x) = D_x(z^*(x), v^*(x), x)$, with $z^*(x)$
115 the minimizer of $G(\cdot, x)$ and $v^*(x)$ the solution of
116 $\nabla_{11}^2 G(z^*(x), x)v = -\nabla_1 F(z^*(x), x)$. When x is fixed, we approximate z^* by doing a gradi-
117 ent descent on G, following the direction $-D_z(z, v, x)$. Finally, when z and x are fixed, we
118 find v^* by following the direction $-D_v(z, v, x)$, which corresponds to a gradient descent on
119 $v \mapsto \frac{1}{2} \langle \nabla_{11}^2 G(z, x)v, v \rangle + \langle \nabla_1 F(z, x), v \rangle$. The rest of the paper is devoted to the study of the
120 global dynamics where the three variables z, v and x evolve at the same time, following stochastic
121 approximations of D_z, D_v and D_x. The next proposition motivates the choice of these directions.

122 **Proposition 2.1.** *Assume that for all* $x \in \mathbb{R}^d$, $G(\cdot, x)$ *is strongly convex. If* (z, v, x) *is a zero of*
123 (D_z, D_v, D_x), *then* $z = z^*(x)$, $v = v^*(x)$ *and* $\nabla h(x) = 0$.

124 We also note that the computation of these directions does *not* require to compute the matrices
125 $\nabla^2_{11}G(z,x)$ and $\nabla^2_{21}G(z,x)$: we only need to compute their product with a vector, which can be
126 computed at a cost similar to that of computing a gradient.

127 The framework we propose is summarized in Algorithm 1. It consists in following a joint update
128 rule in (z,v,x) that follows directions D^t_z, D^t_v and D^t_x that are unbiased estimators of D_z, D_v, D_x.
129 The first and most important remark is that whereas ∇h cannot be written as a sum over samples, the
130 directions D_z, D_v and D_x involve only simple sums, since their expressions are "linear" in F and G:

$$D_z(z,v,x)= \frac{1}{n}\sum_{i=1}^n \nabla_1 G_i(z,x) \ , \tag{7}$$

$$D_v(z,v,x)= \frac{1}{n}\sum_{i=1}^n \nabla^2_{11} G_i(z,x)v + \frac{1}{m}\sum_{j=1}^m \nabla_1 F_j(z,x) \ , \tag{8}$$

$$D_x(z,v,x)= \frac{1}{n}\sum_{i=1}^n \nabla^2_{21} G_i(z,x)v + \frac{1}{m}\sum_{j=1}^m \nabla_2 F_j(z,x) \ . \tag{9}$$

131 It is therefore straightforward to derive unbiased estimators of these directions. In [28], the authors
132 considered one particular case of our framework, where each direction is estimated by using the
133 STORM variance reduction technique (see [12]). Taking a step back by proposing the framework sum-
134 marized in Algorithm 1 opens the way to potential new algorithms that implement other techniques
135 that exist in stochastic single level optimization. In what follows, we study two of them.

2.1 First example: the SOBA algorithm

137 The simplest unbiased estimator is obtained by replacing each mean by one of its terms chosen
138 uniformly at random, akin to what is done in classical single-level SGD. We call the resulting
139 algorithm SOBA (StOchastic Bilevel Algorithm). To do so, we choose two independent random
140 indices $i \in [n]$ and $j \in [m]$ uniformly and estimate each term coming from G using G_i and each
141 term coming from F using F_j. This gives the unbiased **SOBA directions**

$$D^t_z = \nabla_1 G_i(z^t,x^t) \ , \tag{10a}$$

$$D^t_v = \nabla^2_{11} G_i(z^t,x^t)v^t + \nabla_1 F_j(z^t,x^t) \ , \tag{10b}$$

$$D^t_x = \nabla^2_{21} G_i(z^t,x^t)v^t + \nabla_2 F_j(z^t,x^t) \ . \tag{10c}$$

142 This provides us with a first algorithm, SOBA, where we plug Equations (10a) to (10c) in Algorithm 1.
143 We defer its analysis to the next section. Importantly, we use different step sizes for the update in
144 (z,v) and for the update in x. We use the same step size in z and in v since the inner problem and the
145 linear system have similar conditioning, which is that of $\nabla^2_{11} G(z^t,x^t)$. The need for a different step
146 size for the outer and inner problem is clear: both problems can have a different conditioning.

147 An important remark for SOBA is that all the stochastic directions used are computed at the same
148 point z^t, v^t and x^t with the same indices (i,j). The update of z, v and x can thus be performed
149 in parallel instead of sequentially, benefiting from hardware parallelism. Moreover, this enables
150 to share the computations between the different directions. This is the case in hyperparameters
151 selection where $G_i(z,x) = \ell_i(\langle z, d_i\rangle) + \frac{x}{2}\|z\|^2$, with d_i a training sample, and ℓ_i that measures
152 how good is the prediction $\langle z, d_i\rangle$. In this setting, we have $\nabla_1 G_i(z,x) = \ell'_i(\langle z, d_i\rangle)d_i + xz$ and
153 $\nabla^2_{11} G_i(z,x)v = \ell''_i(\langle z, d_i\rangle)\langle v, d_i\rangle d_i$. The prediction $\langle z, d_i\rangle$ can thus be computed only once to
154 obtain both quantities. For more complicated models, where automatic differentiation is used to
155 compute the different derivatives and Jacobian-vector products, we can store the computational graph
156 only once to compute at the same time $\nabla_1 G_i(z,x), \nabla^2_{11} G_i(z,x)v$ and $\nabla^2_{21} G_i(z,x)v$, requiring only
157 one backward pass, thanks to the $\mathcal{R}$ technique [34].

158 Finally, like all single loop bilevel algorithms, our method updates at the same time the inner and outer
159 variable, avoiding unnecessary optimization of the inner problem when x is far from the optimum.

2.2 Global variance reduction with the SABA algorithm

161 In classical optimization, SGD fails to reach optimal rates because of the variance of the gradient
162 estimator. Variance reduction algorithms aim at reducing this variance, in order to follow directions
163 that are closer to the true gradient, and to achieve superior practical and theoretical convergence.

164 In our framework, since the directions D_z, D_v and D_x are all written as sums of derivatives of F_j and
165 G_i, it is easy to adapt most classical variance reduction algorithms. We focus on the celebrated SAGA

algorithm [13]. The extension we propose is called SABA (Stochastic Average Bilevel Algorithm).
The general idea is to replace each sum in the directions D by a sum over a memory, updating only
one term at each iteration. To help the exposition, we denote $y = (z, x, v)$ the vector of joint variables.
Since we have sums over i and over j, we have two memories for each variable: w_i^t for $i \in [n]$ and
$\tilde{w}_j^t$ for $j \in [m]$, which keep track of the previous values of the variable y.

At each iteration t, we draw two random independent indices $i \in [n]$ and $j \in [m]$ uniformly and
update the memories. To do so, we put $w_i^{t+1} = y^t$ and $w_{i'}^{t+1} = w_{i'}^t$ for $i' \neq i$, and $\tilde{w}_j^{t+1} = y^t$ and
$\tilde{w}_{j'}^{t+1} = \tilde{w}_{j'}^t$ for $j' \neq j$. Each sum in the directions D is then approximated using SAGA-like rules:
given n functions $\phi_{i'}$ for $i' \in [n]$, we define $S[\phi, w]_i^t = \phi_i(w_i^{t+1}) - \phi_i(w_i^t) + \frac{1}{n} \sum_{i'=1}^n \phi_{i'}(w_{i'}^t)$.
This is an unbiased estimators of the average of the ϕ's since $\mathbb{E}_i\left[S[\phi, w]_i^t\right] = \frac{1}{n} \sum_{i=1}^n \phi_i(y^t)$.

With a slight abuse of notation, we call $\nabla_{11}^2 Gv$ the sequence of functions $(y \mapsto \nabla_{11}^2 G_i(z, x)v)_{i \in [n]}$
and $\nabla_{21}^2 Gv$ the sequence of functions $(y \mapsto \nabla_{21}^2 G_i(z, x)v)_{i \in [n]}$. We define the **SABA directions** as

$$D_z^t = S[\nabla_1 G, w]_i^t \ , \tag{11a}$$

$$D_v^t = S[\nabla_{11}^2 Gv, w]_i^t + S[\nabla_1 F, \tilde{w}]_j^t \ , \tag{11b}$$

$$D_x^t = S[\nabla_{21}^2 Gv, w]_i^t + S[\nabla_2 F, \tilde{w}]_j^t \ . \tag{11c}$$

These estimators are unbiased estimators of the directions D_z, D_v and D_x. The SABA algorithm
corresponds to Algorithm 1 where we use Equations (11a) to (11c) as update directions. When taking
a step size $\gamma^t = 0$ in the outer problem, hereby stopping progress in x, we recover the iterations
of the SAGA algorithm on the inner problem. In practice, the sum in S is computed by doing a
rolling average (see Appendix B for precision), and the quantities $\phi_i(w_i^t)$ are stored rather than
recomputed: the cost of computing the SABA directions is the same as that of SGD. It requires an
additional memory for the five quantities, of total size $n \times p + (n + m) \times (p + d)$ floats that can be
reduced by using larger batch sizes. Indeed, if b_{in} and b_{out} are respectively the inner and the outer
batch sizes, the memory load is reduced to $n_b \times p + (n_b + m_b) \times (p \times d)$ with $n_b = \lceil \frac{n}{b_{\text{inn}}} \rceil$ and
$m_b = \lceil \frac{m}{b_{\text{out}}} \rceil$ which are smaller than the number of samples. This memory load can also be reduced
in specific cases, for instance when G and F correspond to linear models, where the individual
gradients and Hessian-vector products are proportional to the samples. In this case, we only store the
proportionality ratio, reducing the memory load to $3n + 2m$ floats. Like for SOBA, the computations
of the new quantities $\phi_i(w_i^{t+1})$ are done in parallel, thus benefiting from hardware acceleration and
shared computations. Despite this memory load, using SAGA-like variance reduction instead of
STORM as done in [28, 44, 26] has the advantage to bring the variance of the estimate directions to
zero, enabling faster $O(\frac{1}{T})$ convergence.

In the next section, we show that SABA is fast. It essentially has the same properties as SAGA:
despite being stochastic, it converges with fixed step sizes, and reaches the same rate of convergence
as gradient descent on h.

3 Theoretical analysis

In this section, we provide convergence rates of SOBA and SABA under some classical assumptions.
Note that, unlike most of the stochastic bilevel optimization papers, we work in finite sample setting
rather than the more general expectation setting. Actually, SABA does not make any sense for
functions that don't have a finite sum structure. However, we stress that SOBA could be studied in a
more general setting to obtain the same bounds as here. Also, the finite sum setting is still interesting
since doing empirical risk minimization is very common in practice in machine learning. The proofs
and the constants in big-O are deferred in Appendix C.

3.1 Background and assumptions

We start by stating some regularity assumptions on the functions F and G.

Assumption 3.1. The function F is twice differentiable. The derivatives ∇F and $\nabla^2 F$ are Lipschitz
continuous in (z, x) with respective Lipschitz constants L_1^F and L_2^F.

Note that the above assumption is typically verified in the machine learning context, *e.g.,* when F is the ordinary least squares (OLS) loss or the logistic loss.

Assumption 3.2. The function G is three times continuously differentiable on $\mathbb{R}^p \times \mathbb{R}^d$. For any $x \in \mathbb{R}^d$, $G(\,\cdot\,, x)$ is μ_G-strongly convex. The derivatives ∇G, $\nabla^2 G$ and $\nabla^3 G$ are Lipschitz continuous in (z, x) with respective Lipschitz constants L_1^G, L_2^G and L_3^G. We denote by $\kappa = \frac{L_1^G}{\mu_G}$ the condition number of G.

Strong convexity and smoothness with respect to z of G are verified when G is a regularized least-squares/logistic regression with a full rank design matrix, when the data is not separable for the logistic regression. Moreover, the strong convexity ensures the existence and uniqueness of the inner optimization problem for any $x \in \mathbb{R}^d$.

Assumption 3.3. There exists $C_F > 0$ such that for any x we have $\|\nabla_1 F(z^*(x), x)\| \leq C_F$.

This assumption, combined with the strong convexity of $G(\,\cdot\,, x)$, shows boundedness of v^*. This assumption holds, for instance, in the case of hyperparameters selection for a Ridge regression problem. Note that in Assumptions 3.1 and 3.2, we assume more regularity of F and G than in stochastic bilevel optimization literature (see for instance [17, 22, 24, 2]). It is necessary to get the smoothness of v^* which will allow to adapt the proof of Chen et al. [9] and get tight convergence rates. The following lemma gives us some smoothness properties of the considered directions that will be useful to derive convergence rates of our methods.

Lemma 3.4. *Under the Assumptions 3.1 to 3.3, there exist constants L_z, L_v and L_x such that* $\|D_z(z, v, x)\|^2 \leq L_z^2 \|z - z^*(x)\|^2$, $\|D_v(z, v, x)\|^2 \leq L_v^2(\|z - z^*(x)\|^2 + \|v - v^*(x)\|^2)$ *and* $\|D_x(z, v, x) - \nabla h(x)\|^2 \leq L_x^2(\|z - z^*(x)\|^2 + \|v - v^*(x)\|^2)$.

In first order optimization, a fundamental assumption on the objective function is the smoothness assumption. In the case of vanilla gradient descent applied to a function f, it allows to get a convergence rate of $\|\nabla f(x^t)\|^2$ in $O(1/T)$, i.e. convergence to a stationary point [33]. The following lemma proved by Ghadimi and Wang [17, Lemma 2.2] ensures the smoothness of h.

Lemma 3.5. *Under the Assumptions 3.1 to 3.3, the function h is L^h-smooth for some $L^h > 0$.*

The constant L^h is specified in Appendix C.3. As usual with the analysis of stochastic methods, we define the expected norms of the directions $V_z^t = \mathbb{E}[\|D_z^t\|^2]$, $V_v^t = \mathbb{E}[\|D_v^t\|^2]$ and $V_x^t = \mathbb{E}[\|D_x^t\|^2]$, where the expectation is taken over the past. Thanks to variance-bias decomposition, they are the sum of the variance of the stochastic direction and the squared-norm of the unbiased direction. For SOBA, we use classical bounds on variances like those found for instance in [22]:

Assumption 3.6. There exists B_z, B_v and B_x such that for all t, $\mathbb{E}_t[\|D_z^t\|^2] \leq B_z^2(1 + \|D_z(z^t, v^t, x^t)\|^2)$ and $\mathbb{E}_t[\|D_v^t\|^2] \leq B_v^2(1 + \|D_v(z^t, v^t, x^t)\|^2)$ where $\mathbb{E}_t$ denotes the expectation conditionally to (z^t, v^t, x^t).

For SOBA and SABA, we need to bound the expected norm of D_x^t. For SABA, this assumption allows to get a the same sample complexity as SAGA for single level problems.

Assumption 3.7. There exists B_x such that for all t, $\mathbb{E}_t[\|D_x^t\|^2] \leq B_x^2$.

Assumptions 3.6 and 3.7 are verified for instance, if all the G_i and $\nabla_1 G_i$ have at most quadratic growth, and if F has bounded gradients. They are also verified if the iterates remain in a compact set. Note that we do not assume that G has bounded gradients, as this would contradict its strong-convexity. Finally, for the analysis of SABA, we need regularity on each G_i and F_j:

Assumption 3.8. For all $i \in [n]$ and $j \in [m]$, the functions ∇G_i, ∇F_j, $\nabla_{11}^2 G_i$ and $\nabla_{21}^2 G_i$ are Lipschitz continuous in (z, x).

3.2 Fundamental descent lemmas

Our analysis for SOBA and SABA is based on the control of both $\delta_z^t = \mathbb{E}[\|z^t - z^*(x^t)\|^2]$ and $\delta_v^t = \mathbb{E}[\|v^t - v^*(x^t)\|^2]$, Strong convexity of G and smoothness of $z^*(x)$ and $v^*(x)$ allow to obtain the following lemma by adapting the proof of Chen et al. [9]. In what follows, we drop the dependency of the step sizes ρ and γ in t for clarity.

Lemma 3.9. *Assume that* $\gamma^2 \leq \min\left(\frac{\mu_G L_*^2}{4B_x^2 L_{zx}^2}, \frac{\mu_G L_*^2}{8B_x^2 L_{vx}^2}\right)\rho$. *We have:*

$$\delta_z^{t+1} \leq \left(1 - \frac{\rho\mu_G}{4}\right)\delta_z^t + 2\rho^2 V_z^t + \beta_{zx}\gamma^2 V_x^t + \overline{\beta}_{zx}\frac{\gamma^2}{\rho}\mathbb{E}[\|D_x(z^t, v^t, x^t)\|^2]$$

$$\delta_v^{t+1} \leq \left(1 - \frac{\rho\mu_G}{8}\right)\delta_v^t + \beta_{vz}\rho\delta_z^t + 2\rho^2 V_v^t + \beta_{vx}\gamma^2 V_x^t + \overline{\beta}_{zx}\frac{\gamma^2}{\rho}\mathbb{E}[\|D_x(z^t, v^t, x^t)\|^2]$$

where $\beta_{zx} = \beta_{vx} = 3L_*^2$, $\overline{\beta}_{zx} = \frac{8L_*^2}{\mu_G}$, $\overline{\beta}_{vx} = \frac{16L_*^2}{\mu_G}$, L_* *is the maximum between the Lipschitz constants of* z^* *and* v^* *(see Lemma C.1),* $\beta_{vz} = \frac{1}{\mu_G^3}(L_1^F\mu_G + L_2^G)^2$, L_{zx} *and* L_{vx} *are respectively the smoothness constants of* z^* *and* v^*.

We insist that this result is obtained in general for Algorithm 1 with arbitrary unbiased directions. We can therefore invoke this lemma for the analysis of both SOBA and SABA. We use the smoothness of h to get the following lemma, which is similar to [9, Lemma 1].

Lemma 3.10. *Let* $h^t = \mathbb{E}[h(x^t)]$ *and* $g^t = \mathbb{E}[\|\nabla h(x^t)\|^2]$. *We have*

$$h^{t+1} \leq h^t - \frac{\gamma}{2}g^t - \frac{\gamma}{2}\mathbb{E}[\|D_x(z^t, v^t, x^t)\|^2] + \frac{\gamma}{2}L_x^2(\delta_z^t + \delta_v^t) + \frac{L^h}{2}\gamma^2 V_x^t .$$

If $z^t = z^*(x^t)$, $v^t = v^*(x^t)$, that is δ_z, δ_v both cancel and $D_x(z^t, v^t, x^t) = \nabla h(x^t)$, we get an inequality reminiscent of the smoothness inequality for SGD on h.

3.3 Analysis of SOBA

The analysis of SOBA is based on Lemmas 3.5 and 3.9. We have the following theorem, with fixed step sizes depending on the number of iterations:

Theorem 1 (Convergence of SOBA, fixed step size)**.** Fix an iteration $T > 1$ and assume that Assumptions 3.1 to 3.7 hold. We consider fixed steps $\rho^t = \frac{\overline{\rho}}{\sqrt{T}}$ and $\gamma^t = \xi\rho^t$ with $\overline{\rho}$ and ξ are precised in the appendix. Let $(x^t)_{t\geq 1}$ the sequence of outer iterates for SOBA. Then, $\frac{1}{T}\sum_{t=1}^{T}\mathbb{E}[\|\nabla h(x^t)\|^2] = O(T^{-\frac{1}{2}})$.

As opposed to [22], we do not need that the ratio $\frac{\gamma}{\rho}$ goes to 0, which allows to get a complexity (that is, the number of call to oracles to have an ϵ-stationary soluion) in $O(\epsilon^{-2})$ better than the $\tilde{O}(\epsilon^{-\frac{5}{2}})$ they have. Also, note that this rate is the same as the one of SGD for non-convex and smooth objective [8]. We obtain a similar rate using decreasing step sizes:

Theorem 2 (Convergence of SOBA, decreasing step size)**.** Assume that Assumptions 3.1 to 3.7 hold. We consider steps $\rho^t = \overline{\rho}t^{-\frac{1}{2}}$ and $\gamma^t = \xi\rho$. Let x^t the sequence of outer iterates for SOBA. Then, $\inf_{t\leq T}\mathbb{E}[\|\nabla h(x^t)\|^2] = O(\log(T)T^{-\frac{1}{2}})$.

As for SGD, SOBA suffers from the need of decreasing step sizes to get actual convergence because of the variance of the estimation on each directions. On the other hand, the analysis of SABA leverages the dynamic of all three variables, resulting in fast convergence with fixed step sizes.

3.4 SABA: a stochastic method with optimal rates

In what follows, we denote $N = n + m$ the total number of samples. The following theorem shows $O(N^{\frac{2}{3}}T^{-1})$ convergence for the SABA algorithm in the general case where we only assume smoothness of h. Our analysis of SABA is inspired by the analysis of single-level SAGA by Reddi et al. [37].

Theorem 3 (Convergence of SABA, smooth case)**.** Assume that Assumptions 3.1 to 3.3 and 3.7 to 3.8 hold. We suppose $\rho = \rho'N^{-\frac{2}{3}}$ and $\gamma = \xi\rho$, where ρ' and ξ depend only on F and G and are specified in appendix. Let x^t the iterates of SABA. Then, $\frac{1}{T}\sum_{t=1}^{T}\mathbb{E}[\|\nabla h(x^t)\|^2] = O\left(N^{\frac{2}{3}}T^{-1}\right)$.

To prove the theorem, the idea is to control the distance from the memory to the current variables. We define $S^t = \frac{1}{n}\sum_{i=1}^{n}\|y^t - w_i^t\|^2 + \frac{1}{m}\sum_{j=1}^{m}\|y^t - \tilde{w}_j^t\|^2$. In appendix, we show that we can find

scalars $\phi_s, \phi_z, \phi_v > 0$ such that the quantity $\mathcal{L}^t = h^t + \phi_s S^t + \phi_z \delta_z^t + \phi_v \delta_v^t$ satisfies $\mathcal{L}^{t+1} \leq \mathcal{L}^t - \frac{\gamma}{2} g^t$. Summing these inequalities for $t = 1 \ldots T$ and using the fact that $\mathcal{L}^t$ is lower bounded demonstrates the theorem.

Note that the step sizes are constant with respect to the time, but they scale with $N^{-\frac{2}{3}}$. As a consequence, the sample complexity is $O(N^{\frac{2}{3}} \epsilon^{-1})$ which is analogous of the one of SAGA for non-convex single level problems [37]. This is better than the sample complexity of Algorithm 1 with full batch directions, which is $O(N \epsilon^{-1})$. Hence, with SABA, we get the best of both worlds: the stochasticity makes the scaling in N of the sample complexity goes from N in full batch mode to $N^{\frac{2}{3}}$ for SABA, and the variance reduction makes the scaling in ϵ goes from ϵ^{-2} for SOBA to ϵ^{-1} for SABA. Our experiments in Section 4 confirm this gain.

Furthermore, if we assume that h satisfies a Polyak-Łojasiewicz (PL) inequality, we recover linear convergence. Recall that h has the PL property if there exists $\mu_h > 0$ such that for all $x \in \mathbb{R}^d$, $\frac{1}{2} \|\nabla h(x)\|^2 \geq \mu_h(h(x) - h^*)$ with h^* the minimum of h.

Theorem 4 (Convergence of SABA, PL case)**.** Assume that h satisfies the PL inequality and that Assumptions 3.1 to 3.3 and 3.7 to 3.8 hold. We suppose $\rho = \rho' N^{-\frac{2}{3}}$ and $\gamma = \xi \rho' N^{-1}$, where ρ' and ξ depend only on F and G and are specified in appendix. Let x^t the iterates of SABA and $c' \triangleq \min\left(\mu_h, \frac{1}{16 P'}\right)$ with P' specified in the appendix. Then, $\mathbb{E}[h^T] - h^* = (1 - c'\gamma)^T (h^0 - h^* + C^0)$ where C^0 is a constant specified in appendix that depends on the initialization of z, v, x and memory.

The proof is similar to that of the previous theorem: we find coefficients ϕ_s, ϕ_z, ϕ_v such that $\mathcal{L}^t = h^t + \phi_s S^t + \phi_z \delta_z^t + \phi_v \delta_v^t$ satisfies the inequality $\mathcal{L}^{t+1} \leq (1 - c'\gamma)\mathcal{L}^t$, which is then unrolled. Note that in the case where we initialize z and v with $z^0 = z^*(x^0)$, $v^0 = v^*(x^0)$, and the memories $w_i^0 = w^0$, $\tilde{w}_j^0 = w^0$ for all i, j, the constant C^0 cancels and the bound simplifies to $\mathbb{E}[h(x^T)] - h^* \leq (1 - \frac{\gamma \mu_h}{4})^T (h(x^0) - h^*)$.

Just like classical variance reduction methods in single-level optimization, this theorem shows that our method achieves linear convergence under PL assumption on the value function. To the best of our knowledge, our method is the first stochastic bilevel optimization method that enjoys such property. We note that the PL hypothesis is more general than μ_h-strong convexity of h – it is a necessary condition for strong convexity.

We see here the importance of *global* variance reduction. Indeed, using variance reduction only on z and SGD on x would lead to sub-linear convergence in x. This would be the case even with a perfect estimation of $z^*(x)$. Similarly, using variance reduction only on x and SGD on z would lead to sub-linear convergence in z, and hence in x. Using global variance reduction with respect to each variable as we propose here is the only way to achieve linear convergence. We now turn to experiments, where we find that our method is also promising from a practical point of view.

4 Experiments

Here we compare the performances of SOBA and SABA with competitor methods on different tasks. The different methods being compared are stocBiO [24], AmiGO [2], FSLA [28], MRBO [44], TTSA [22], BSA [17] and SUSTAIN [26]. A detailed account of the experiments is provided in Appendix B.

4.1 Hyperparameters selection

The first task we perform is hyperparameters selection to choose regularization parameters on ℓ^2 logistic regression. Let us denote $((d_i^{\text{train}}, y_i^{\text{train}}))_{1 \leq i \leq n}$ and $((d_i^{\text{val}}, y_i^{\text{val}}))_{1 \leq i \leq m}$ the training and the validation sets. In this case, the inner variable θ corresponds to the parameters of the model, and the outer variable λ to the regularization. The functions F and G of the problem (1) are the logistic loss, with ℓ^2 penalty for G, that is to say $F(\theta, \lambda) = \frac{1}{m} \sum_{i=1}^{m} \varphi(y_i^{\text{val}} \langle d_i^{\text{val}}, \theta \rangle)$ and $G(\theta, \lambda) = \frac{1}{n} \sum_{i=1}^{n} \varphi(y_i^{\text{train}} \langle d_i^{\text{train}}, \theta \rangle) + \frac{1}{2} \sum_{k=1}^{p} e^{\lambda_k} \theta_k^2$ where $\varphi(u) = \log(1 + e^{-u})$. We fit a binary classification model on the IJCNN1[1] dataset. Here, $n = 49\,990$, $m = 91\,701$ and $p = 22$.

The suboptimality gap is plotted in Figure 2a for each method. The lowest values are reached by AmIGO and SABA, but much quicker for SABA. Moreover, SABA is the only single-loop method

---

[1] https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/binary.html

(a) Logistic regression   (b) Datacleaning

Figure 2: Comparison of SOBA and SABA with other stochastic bilevel optimization methods. For each algorithm, we plot the median performance over 10 runs. In both experiments, SABA achieves the best performance. The dashed lines are for one loop competitor methods, the dotted lines are for two loops methods and the solid lines are the proposed methods. **Left**: hyperparameter selection for ℓ^2 penalized logistic regression on IJCNN1 dataset , **Right**: data hyper-cleaning on MNIST with $p = 0.5$ corruption rate.

that reaches a suboptimality below 10^{-3}. Among all methods, SOBA is the first to reach it best value, but this value is also the highest. The gap between SOBA and SABA highlights the benefits of variance reduction: it gives us a lower plateau and the fixed step sizes enable faster convergence.

4.2 Data hyper-cleaning

The second task we perform is data hyper-cleaning introduced in [15] on the MNIST[2] dataset. The data is patitioned into a training set $(d_i^{\text{train}}, y_i^{\text{train}})$, a validation set $(d_i^{\text{val}}, y_i^{\text{val}})$, and a test set. The training set contains 20000 samples, the validation set 5000 samples and the test set 10000 samples. The targets y take values in $\{0, \ldots, 9\}$ and the samples x are in dimension 784. Each sample in the training set is *corrupted* with probability p: a sample is corrupted when we replace its label y_i by a random label in $\{0, \ldots, 9\}$. Samples in the validation and test sets are not corrupted. The goal of datacleaning is to train a multinomial logistic regression on the train set and learn a weight per training sample, that should go to 0 for corrupted samples. This is formalized by the bilevel optimization problem (1) with $F(\theta, \lambda) = \frac{1}{m} \sum_{i=1}^{m} \ell(\theta d_i^{\text{val}}, y_i^{\text{val}})$ and $G(\theta, \lambda) = \frac{1}{n} \sum_{i=1}^{n} \sigma(\lambda_i) \ell(\theta d_i^{\text{train}}, y_i^{\text{train}}) + C_r \|\theta\|^2$ where ℓ is the cross entropy loss and σ is the sigmoid function. The inner variable θ is a matrix of size 10×784, and the outer variable λ is a vector in dimension $n_{\text{train}} = 20000$.

For the estimated parameters θ during optimization, we report in Figure 2b the test error, *i.e.*, the percent of wrong predictions on the testing data. We use for this experiment a corruption probability $p = 0.5$. In general, the error decreases quickly until it reaches a final value. We observe that our method SABA outperforms all the other methods by reaching faster its smallest error, which is smaller than the ones of the other methods. For SOBA, it reaches a lower final error than stocBiO and BSA. In appendix, we provide other convergence curves, and find that for higher values of p, SABA is still the fastest algorithm to reach its final accuracy, but the algorithm MRBO can reach a lower test accuracy. Overall, we find that among all methods, even those that implement variance reduction (that is FSLA, MRBO, SUSTAIN, SABA), SABA is the one that demonstrates the best empirical performance.

5 Conclusion

In this paper, we have presented a framework for bilevel optimization that enables the straightforward development of stochastic algorithms. The gist of our framework is that the directions in Equations (4) to (6) are all written as simple sums of samples derivatives. We leveraged this fact to propose SOBA, an extension of SGD to our framework, and SABA, an extension of SAGA to our framework, which achieves similar convergence rates as gradient descent on the value function. Finally, we think that our framework opens a large panel of potential methods for stochastic bilevel optimization involving techniques of extrapolation, variance reduction, momentum and so on.

---

[2]http://yann.lecun.com/exdb/mnist/

References

[1] Zeeshan Akhtar, Amrit Singh Bedi, Srujan Teja Thomdapu, and Ketan Rajawat. Projection-Free Algorithm for Stochastic Bi-level Optimization. *preprint ArXiv 2110.11721*, 2021.

[2] Michael Arbel and Julien Mairal. Amortized Implicit Differentiation for Stochastic Bilevel Optimization. In *International Conference on Learning Representations (ICLR)*, 2022.

[3] Shaojie Bai, J. Zico Kolter, and Vladlen Koltun. Deep Equilibrium Models. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2019.

[4] Atilim Gunes Baydin, Barak A. Pearlmutter, Alexey Andreyevich Radul, and Jeffrey Mark Siskind. Automatic differentiation in Machine Learning: A survey. *Journal of Machine Learning Research*, 18(153):1–43, 2018.

[5] Yoshua Bengio. Gradient-Based Optimization of Hyperparameters. *Neural Computation*, 12(8): 1889–1900, 2000.

[6] Quentin Bertrand, Quentin Klopfenstein, Mathieu Blondel, Samuel Vaiter, Alexandre Gramfort, and Joseph Salmon. Implicit differentiation of lasso-type models for hyperparameter optimization. In *International Conference on Machine Learning (ICML)*, pages 810–821. PMLR, 2020.

[7] Léon Bottou. Large-Scale Machine Learning with Stochastic Gradient Descent. In *Proceedings of COMPSTAT*, pages 177–186. Physica-Verlag HD, Heidelberg, 2010.

[8] Léon Bottou, Frank E. Curtis, and Jorge Nocedal. Optimization methods for large-scale Machine Learning. *Siam Reviews*, 60(2):223–311, 2018.

[9] Tianyi Chen, Yuejiao Sun, and Wotao Yin. Closing the Gap: Tighter Analysis of Alternating Stochastic Gradient Methods for Bilevel Problems. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2021.

[10] Tianyi Chen, Yuejiao Sun, and Wotao Yin. A Single-Timescale Stochastic Bilevel Optimization Method. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2022.

[11] Ekin D. Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V. Le. AutoAugment: Learning Augmentation Strategies From Data. In *CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 113–123. IEEE, 2019.

[12] Ashok Cutkosky and Francesco Orabona. Momentum-based variance reduction in non-convex SGD. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2019.

[13] Aaron Defazio, Francis Bach, and Simon Lacoste-Julien. SAGA: A Fast Incremental Gradient Method With Support for Non-Strongly Convex Composite Objectives. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 28, pages 1646–1654, Montreal, QC, Canada, December 2014. Curran Associates, Inc.

[14] Justin Domke. Generic methods for optimization-based modeling. In *International Conference on Artificial Intelligence and Statistics (AISTAT)*, volume 22, pages 318–326. PMLR, 2012.

[15] Luca Franceschi, Michele Donini, Paolo Frasconi, and Massimiliano Pontil. Forward and reverse gradient-based hyperparameter optimization. In *International Conference on Machine Learning (ICML)*, pages 1165–1173. PMLR, 2017.

[16] Luca Franceschi, Paolo Frasconi, Saverio Salzo, Riccardo Grazzi, and Massimiliano Pontil. Bilevel programming for hyperparameter optimization and meta-learning. In *International Conference on Machine Learning (ICML)*, pages 1568–1577. PMLR, 2018.

[17] Saeed Ghadimi and Mengdi Wang. Approximation Methods for Bilevel Programming. *preprint ArXiv 1802.02246*, 2018.

[18] Riccardo Grazzi, Luca Franceschi, Massimiliano Pontil, and Saverio Salzo. On the iteration complexity of hypergradient computation. In *International Conference on Machine Learning (ICML)*, pages 3748–3758. PMLR, 2020.

[19] Riccardo Grazzi, Massimiliano Pontil, and Saverio Salzo. Convergence properties of stochastic hypergradients. In *International Conference on Artificial Intelligence and Statistics (AISTAT)*, pages 3826–3834. PMLR, 2021.

[20] Zhishuai Guo, Quanqi Hu, Lijun Zhang, and Tianbao Yang. Randomized Stochastic Variance-Reduced Methods for Multi-Task Stochastic Bilevel Optimization. *preprint ArXiv 2105.02266*, 2021.

[21] Zhishuai Guo, Yi Xu, Wotao Yin, Rong Jin, and Tianbao Yang. On Stochastic Moving-Average Estimators for Non-Convex Optimization. *preprint ArXiv 2104.14840*, 2021.

[22] Mingyi Hong, Hoi-To Wai, Zhaoran Wang, and Zhuoran Yang. A Two-Timescale Framework for Bilevel Optimization: Complexity Analysis and Application to Actor-Critic. *preprint ArXiv 2007.05170*, 2021.

[23] Feihu Huang and Heng Huang. BiAdam: Fast Adaptive Bilevel Optimization Methods. *preprint ArXiv 2106.11396*, 2021.

[24] Kaiyi Ji, Junjie Yang, and Yingbin Liang. Bilevel optimization: Convergence analysis and enhanced design. In *International Conference on Machine Learning (ICML)*, pages 4882–4892. PMLR, 2021.

[25] Rie Johnson and Tong Zhang. Accelerating stochastic gradient descent using predictive variance reduction. pages 315–323. Curran Associates, Inc., 2013.

[26] Prashant Khanduri, Siliang Zeng, Mingyi Hong, Hoi-To Wai, Zhaoran Wang, and Zhuoran Yang. A Near-Optimal Algorithm for Stochastic Bilevel Optimization via Double-Momentum. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2021.

[27] Siu Kwan Lam, Antoine Pitrou, and Stanley Seibert. Numba: A llvm-based python jit compiler. In *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC*, pages 1–6, 2015.

[28] Junyi Li, Bin Gu, and Heng Huang. A Fully Single Loop Algorithm for Bilevel Optimization without Hessian Inverse. In *Proceedings of the Thirty-sixth AAAI Conference on Artificial Intelligence, AAAI'22*, 2022.

[29] Seppo Linnainmaa. Taylor expansion of the accumulated rounding error. *BIT Numerical Mathematics*, 16(2):146–160, 1976.

[30] Dong C. Liu and Jorge Nocedal. On the limited memory BFGS method for large scale optimization. *Mathematical Programming*, 45(1-3):503–528, 1989.

[31] Hanxiao Liu, Karen Simonyan, and Yiming Yang. Darts: Differentiable architecture search. In *International Conference on Learning Representations (ICLR)*, 2018.

[32] Dougal Maclaurin, David Duvenaud, and Ryan Adams. Gradient-based hyperparameter optimization through reversible learning. In *International Conference on machine learning (ICML)*, pages 2113–2122. PMLR, 2015.

[33] IU E. Nesterov. *Introductory Lectures on Convex Optimization: A Basic Course*. Number v. 87 in Applied Optimization. Kluwer Academic Publishers, Boston, 2004.

[34] Barak A Pearlmutter. Fast exact multiplication by the hessian. *Neural computation*, 6(1): 147–160, 1994.

[35] Fabian Pedregosa. Hyperparameter optimization with approximate gradient. In *International Conference on Machine Learning (ICML)*, pages 737–746. PMLR, 2016.

[36] Zaccharie Ramzi, Florian Mannel, Shaojie Bai, Jean-Luc Starck, Philippe Ciuciu, and Thomas Moreau. SHINE: SHaring the INverse Estimate from the forward pass for bi-level optimization and implicit models. In *International Conference on Learning Representations (ICLR)*, 2022.

[37] Sashank J. Reddi, Suvrit Sra, Barnabas Poczos, and Alex Smola. Fast Incremental Method for Nonconvex Optimization. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, IEEE, pages 1971–1977, 2016.

[38] Herbert Robbins and Sutton Monro. A stochastic approximation method. *The Annals of Mathematical Statistics*, 22(3):400–407, 1951.

[39] Cédric Rommel, Thomas Moreau, Joseph Paillard, and Alexandre Gramfort. CADDA: Class-wise Automatic Differentiable Data Augmentation for EEG Signals. In *International Conference on Learning Representations (ICLR)*, 2022.

[40] Mark Schmidt, Nicolas Le Roux, and Francis Bach. Minimizing finite sums with the stochastic average gradient. *Mathematical Programming*, 162(1-2):83–112, 2017.

[41] Amirreza Shaban, Ching-An Cheng, Nathan Hatch, and Byron Boots. Truncated Back-propagation for Bilevel Optimization. In *Artificial Intelligence and Statistics (AISTAT)*, pages 1723–1732, Okinawa, Japan, 2019.

[42] Heinrich von Stackelberg. *Theory of the market economy*. Oxford University Press, 1952.

[43] R. Wengert. A simple automatic derivative evaluation program. *Communications of the ACM*, 7 (8):463–464, 1964.

[44] Junjie Yang, Kaiyi Ji, and Yingbin Liang. Provably Faster Algorithms for Bilevel Optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2021.