WHICH LAYER IS LEARNING FASTER?
A SYSTEMATIC EXPLORATION OF LAYER-WISE
CONVERGENCE RATE FOR DEEP NEURAL NETWORKS

ABSTRACT

The deeply hierarchical structures enable deep neural networks (DNNs) to fit extremely complex target functions. However, the complex interaction between layers also makes the learning process of a particular layer poorly understood. This work demonstrates that the shallower layers of DNNs tend to converge faster than the deeper layers. We call this phenomenon *Layer Convergence Bias*. We also uncover the fundamental reason behind this phenomenon: Flatter local minima of shallower layers make their gradients more stable and predictive, allowing for faster training. Another surprising result is that the shallower layers tend to learn the low-frequency components of the target function, while the deeper layers usually learn the high-frequency components. It is consistent with the recent discovery that DNNs learn lower frequency objects faster.

1 INTRODUCTION

Over the last decade, breakthrough progress has been made by deep neural networks (DNNs) on a wide range of complicated tasks in computer vision (Krizhevsky et al., 2017), natural language processing (Sutskever et al., 2014), speech recognition (Graves et al., 2013), game playing (Silver et al., 2016), and biomedical prediction (Jumper et al., 2021). Such progress hinged on a number of advances in hardware technology, dataset construction, and model architectural designs. Among them, the invention and application of very-deep network architectures play a decisive role.

Deepening the network is an effective way to empower its fitting ability. Extensive studies (Delalleau & Bengio, 2011; Eldan & Shamir, 2016; Lu et al., 2017) compared the power between deeper and wider neural networks and showed that the polynomial growth of depth has a similar effect to the exponential growth of width. Therefore, modern DNNs (Simonyan & Zisserman, 2014; He et al., 2016) usually contain tens of layers to ensure their modeling abilities for real-world applications.

Although the practical success of deep architectures is indisputable, they make the learning hardly predictable since complex interaction happens between layers when co-adapting to the target (Yosinski et al., 2014). By now, we still have a poor understanding of how different layers learn differently. Currently, a widely accepted view relates to the vanishing gradient problem Hochreiter (1991); Hochreiter et al. (2001). The gradients are getting weaker and weaker as they move back through the hidden layers, making the shallower layers converge more slowly (Nielsen, 2015). Informally, it is reasonable that larger gradient values bring higher learning speed.

Even though this view somewhat makes sense, we seem to have little concrete evidence supporting it. In particular, it is dubious how higher-level features can be built based on the unstable features extracted by the unconverged shallower layers. This paper aims to find a credible answer for the parameters of which layer are learning faster towards the convergence point (defined as the convergence rate in this work) with a systematic exploration. Our results lead to somewhat startling discoveries.

Our Contributions. Our point of start is illustrating that there does not seem to be a reliable positive correlation between the gradient magnitude and the convergence rate of a particular layer. Instead, we find that shallower layers tend to converge faster than the higher ones, even with smaller gradients. The phenomenon is called *layer convergence bias* in this paper.

We then turn our attention to excavating the underlying mechanism for the faster convergence of shallower layers. Specifically, we find out that the depth of a layer has a fundamental effect on its training: the parameters of shallower layers are usually optimized on flatter landscapes than deeper layers. This finding reveals that the gradients of shallower layers may be more predictive and thus have the potential to allow the larger learning rates (LRs) to be performed, making the convergence faster.

Finally, we find that the layer convergence bias is also tied to the frequency of the function they are modeling. When fitting a complex target function, the shallower layers tend to fit the low-frequency (usually simpler) components. On the contrary, the deeper layers struggle to fit the remaining high-frequency components. It is a consistent result of the recent discovery that DNNs prioritize learning low-frequency components of the modeling function, while having very low learning speed on high-frequency components that tend to be more complex (Rahaman et al., 2019). This finding provides us with another perspective to understand why deeper layers learn more slowly.

We believe that understanding the roots of such a fundamental convergence bias can give us a better grasp of the complicated learning process of DNNs. In turn, it can motivate more in-depth algorithmic progress for the deep learning community.

This paper is organized as follows. In Section 2, we introduce our method for measuring convergence speed for different layers, and formally define the layer convergence bias. In Section 3, we examine the relationship between gradient magnitude and convergence rate, and show that the shallower layers tend to converge faster even with smaller gradients. Then in Section 4, we analyze the mechanism behind the layer convergence bias in DNN training. The layer-frequency correspondence is demonstrated in Section 5. The practical significance of layer convergence bias is presented in Section 6. We further discuss the related work in Section 7 and conclude in Section 8.

2 LAYER CONVERGENCE BIAS

The deep architecture of DNNs is arguably one of the most important factors for their powerful fitting abilities. With the benefit brought by the deep structures, there are also extra complexities in the training process coming into being. So far, we do not have a firm conclusion about whether some layers are learning faster than others.

For examining the convergence progress for a DNN, a common practice is checking its loss curve. However, this is not applicable for comparing the convergence between different layers. In this work, we define a measurement for layer-wise convergence in the following.

Definition 2.1 (Layer-wise convergence rate) *At the training time t, let the deep neural network with L layers $\{T_l^{(t)}\}_{l=1}^L$ be $f(\boldsymbol{x}) = (T_L^{(t)} \circ T_{L-1}^{(t)} \circ \cdots \circ T_1^{(t)})(\boldsymbol{x}) : \mathbb{R}^i \to \mathbb{R}^o$, where i, o are the dimension of its inputs and outputs. We use $\theta_l^{(t)}$ to denote the parameters of the l-th layer $T_l^{(t)}$. Assuming that $\theta_l^{(t)}$ can finally converge to its optimal point θ_l^* when $t \to \infty$, we define the convergence rate of θ_l during the time interval $[t_1, t_2]$ to be*

$$C_l^{(t_1, t_2)} = \frac{1}{(t_2 - t_1)} \cdot \frac{\|\theta_l^{(t_1)} - \theta_l^*\|_2 - \|\theta_l^{(t_2)} - \theta_l^*\|_2}{\|\theta_l^{(t_0)} - \theta_l^*\|_2},$$

where t_0 denotes the time point when the training starts.

In this definition, $\|\theta_l^{(t_1)} - \theta_l^*\|_2 - \|\theta_l^{(t_2)} - \theta_l^*\|_2$ denotes how much the distance of the parameter θ_l to the optimal point is shortened in the period $[t_1, t_2]$. $\|\theta_l^{(t_0)} - \theta_l^*\|_2$ represents the distance between the initial point to the convergence point. Its primary function is to normalize the speed, allowing the convergence of different layers to compare with each other. Thus the convergence rate of θ_l can be understood as the ratio of normalized distance to time [1].

---

[1] Common optimization works (Yi et al., 1999; Nesterov, 2003) defined the rate of convergence for θ as $C = \lim_{k \to \infty} \frac{\|\theta^{(k+1)} - \theta^*\|_2}{\|\theta^{(k)} - \theta^*\|_2}$. Since for DNNs, $C = 1$ (sub-linear convergence) with SGD optimizer (Nemirovski et al., 2009), we care more about the subtle convergence difference between layers.

Observation 2.1 (Layer convergence bias). *For $l_1 < l_2$, $\exists \tilde{t} > 0$, such that $C_{l_1}^{(t_1,t_2)} > C_{l_2}^{(t_1,t_2)}$ when $t_1 < t_2 < \tilde{t}$.*

Layer convergence bias indicates that at an early training phase $t < \tilde{t}$, the parameters θ_{l_1} of a shallower layer l_1 tend to move to $\theta_{l_1}^*$ faster than a deeper layer θ_{l_2} moving to $\theta_{l_2}^*$. In the following, we use both synthetic and real datasets to show that the layer convergence bias appears for both fully-connected neural networks (FCNNs) and convolutional neural networks (CNNs).

3 VERIFICATION OF LAYER CONVERGENCE BIAS

In this section, we try to substantiate the central claim of this work. First, we use the FCNNs to show that the shallower layers tend to converge faster than the deeper layers on the regression task, even when the gradient values for shallower layers are smaller. We then use CNNs with modern architectures to verify that layer convergence bias is a common phenomenon in practical applications. All experimental settings in this work can be found in Appendix A.1.

3.1 LAYER CONVERGENCE BIAS IN FULLY-CONNECTED NETWORKS

For FCNNs, we construct a simple regression task to demonstrate that layers with smaller gradients do not necessarily learn more slowly than layers with larger gradients. The fitting target is $f(x) = sin(x) + \frac{1}{3}sin(3x) + \frac{1}{10}sin(10x) + \frac{1}{30}sin(30x)$, with mean square error loss for training.

First, we use the FCNN [1-32-32-32-1] with the Sigmoid activations as a simple example. In the following analysis, the first layer (1-32) is named *Layer 1*, and the subsequent two layers (32-32) are called *Hidden layer 1, Hidden layer 2* respectively. The gradient values and the convergence processes for these layers are shown in Fig. 1 (a). Two observations can be obtained from the plots: 1) The gradient of *Hidden layer 1* is nearly always smaller than the gradient of *Hidden layer 2*. 2) Although shallower layers have smaller gradients, they seem to converge faster. For the first 50 epochs, the shallower layers are moving faster to their convergence point (*e.g.*, $C_{Layer\ 1}^{(t_0,t_{50})} \approx 0.012$, $C_{Hidden\ layer\ 1}^{(t_0,t_{50})} \approx 0.009$, $C_{Hidden\ layer\ 2}^{(t_0,t_{50})} \approx 0.006$), which is inconsistent with the previous view that higher gradients lead to faster learning (Nielsen, 2015).

To further validate the above results with a deeper network, we adopt residual connections (He et al., 2016) for the FCNN (deep network fails to be trained in this task without residual connections) and use the ReLU activation function. The FCNN [1-(128-128)-(128-128)-(128-128)-(128-128)-1] with four residual blocks of width 128 shows similar results to the shallow FCNN without residual connection (see Fig. 1 (b)). In this case, the difference in layer-wise convergence rate can be observed even earlier (*i.e.*, $C_{Res-Block\ 1}^{(t_0,t_5)} \approx 2C_{Res-Block\ 4}^{(t_0,t_5)}$), which shows that the layer convergence bias also happens for deeper FCNNs with residual connections.

Clearly, these results cannot reconcile with the previous view that larger gradients bring a higher learning speed for deeper layers, at least for the DNNs used in this work. Instead, from the optimization point of view, the parameters of shallower layers are learning faster to converge.

(a) FCNN without residual connection   (b) FCNN with four residual blocks

Figure 1: Left (a,b): The absolute mean gradient values for different layers for FCNNs w/o residual connections in training. For both networks, deeper layers have larger gradients. Right (a,b): The convergence process of different layers for FCNNs. Shallower layers converge faster.

(a) ResNet-50   Val Acc 73.24%   (b) VGG-19   Val Acc 71.89%

Figure 2: The convergence process of ResNet-50 and VGG-19 on ImageNet. During the first 50 epochs, shallower layers converge much faster than deeper layers. After the learning rate decays at the 50th epoch, parameters of deeper layers accelerate to move to their convergence points.

3.2   LAYER CONVERGENCE BIAS IN CONVOLUTIONAL NETWORKS

Real-world datasets are very different from the synthetic data used in our previous experiments. In order to utilize the layer convergence bias to understand and better improve DNNs in real applications, it is important to verify whether the layer convergence bias holds for CNNs on images.

In the following experiments, we examine the layer-wise convergence process on ImageNet (Russakovsky et al., 2015) dataset with both ResNet-50 (He et al., 2016) and VGG-19 (Simonyan & Zisserman, 2014). Details of the network architectures can be found in Appendix A.1. We train the CNNs for 120 epochs with learning rate decay at the 50th epoch ($0.1 \rightarrow 0.01$) and the 100th epoch ($0.01 \rightarrow 0.001$). The training processes are shown in Fig. 2.

For ResNet-50, we visualize the learning process of the first convolutional layer and its subsequent four stages. One can easily observe that at the beginning of training, the shallower layers converge much faster than the deeper layers ($C_{Stage\ 1}^{(t_0, t_{20})} \approx 3 C_{Stage\ 4}^{(t_0, t_{20})}$). However, after the learning rate decays at the 50th epoch, deeper layers begin to learn effectively and achieve a higher convergence rate than the shallower layers ($C_{Stage\ 1}^{(t_{50}, t_{60})} \approx 0.5 C_{Stage\ 4}^{(t_{50}, t_{60})}$). We conjecture that the initial learning rate is too large for the deeper layers to learn.

For VGG-19, we visualize its 1st, 5th, 9th, 13th, and 17th layers. This network show a more significant convergence difference between layers than ResNet-50. At the first training stage with the initial learning rate, $\|\theta_l^{(t_5)} - \theta_l^*\| > \|\theta_l^{(t_0)} - \theta_l^*\|$ for $l \in \{5, 9, 13, 17\}$, which means that all layers but the first one even slightly diverge. Usually, the divergence appears when the learning rate is too large. This phenomenon confirms that the deeper layers cannot effectively learn with the large learning rate at the beginning.

The experiments on ImageNet verify that layer convergence bias is a common phenomenon for CNNs. Experiments on CIFAR datasets show similar results. We put the corresponding Fig. 8 in Section 5 since it reveals something more interesting and in-depth that is worth further discussion.

4   MECHANISM BEHIND LAYER CONVERGENCE BIAS

So far, our investigation shows that the seemingly-right perspective for linking the layer-wise gradient and convergence rate is tenuous, at best. Both FCNNs and CNNs demonstrate an evident bias that shallower layers learn faster. *Can we explain why this is the case?*

Gradient Predictiveness. Since gradient values cannot wholly determine the convergence rate, we wonder if the directions of the gradients play a more critical role. The more chaotic update directions make the convergence slower. Here we examine the gradient predictiveness (Santurkar et al., 2018) of different layers. If the gradient behavior is "predictive", less change in the gradient directions would appear when 1) the gradients are calculated with different batches of data; 2) the parameters of other layers update. Predictiveness can also be simply understood as the stability of gradient direction.

Definition 4.1 *Let $(x^{(t)}, y^{(t)})$ be a batch of input-label pairs for the DNN to train at time t, and $(x'^{(t)}, y'^{(t)})$ be another batch of data. We define the gradient predictiveness of the lth layer at time t*

(a) Gradient predictiveness *w.r.t.* data

(b) Gradient predictiveness *w.r.t.* parameters

Figure 3: The gradient predictiveness of shallower and deeper layers.

w.r.t. data be the cosine similarity $sim(G_{l,t}, G'_{l,t}) = \frac{\|G_{l,t}G'_{l,t}\|}{\|G_{l,t}\|\|G'_{l,t}\|} \in [-1, 1]$. *Likewise, the gradient predictiveness w.r.t. parameters is defined as* $sim(G_{l,t}, G''_{l,t})$, *where*

$$G_{l,t} = \nabla_{\theta_l^{(t)}} L(\theta_1^{(t)}, ..., \theta_L^{(t)}; x^{(t)}, y^{(t)})$$

$$G'_{l,t} = \nabla_{\theta_l^{(t)}} L(\theta_1^{(t)}, ..., \theta_L^{(t)}; x'^{(t)}, y'^{(t)})$$

$$G''_{l,t} = \nabla_{\theta_l^{(t)}} L(\theta_1^{(t+1)}, ..., \theta_{l-1}^{(t+1)}, \theta_l^{(t)}, \theta_{l+1}^{(t)}, ..., \theta_L^{(t+1)}; x^{(t)}, y^{(t)})$$

Here, $G_{l,t}$ corresponds to the gradient of $\theta_l^{(t)}$. $G'_{l,t}$ is the gradient of this layer with another batch of data, while $G''_{l,t}$ means the gradient after all the other layers have updated to new values. Therefore, $sim(G_{l,t}, G'_{l,t})$ indicates the stability of gradients with different data batches. $sim(G_{l,t}, G''_{l,t})$ reflects whether the currently estimated gradient is in a consistent decreasing direction when the loss landscape is affected by the updating of other layers' parameters. The gradient predictiveness during training is shown in Fig. 3, where Res-Block 1 has more predictive gradients than Res-Block 4.

Visualizing the Loss Landscapes. We are curious about why gradients for deeper layers have poorer predictiveness. A hypothesis is that the loss landscapes for deeper layers are more rugged, making the parameters fluctuate more. A straightforward method to validate this hypothesis is plotting the loss landscapes for the parameters. To do this for a particular layer l, one can choose a central point θ_l^* and two direction vectors $d_{l,1}$, $d_{l,2}$. Then the loss landscape can be drawn with

$$f(\beta_1, \beta_2) = L(\theta_l^* + \beta_1 d_{l,1} + \beta_2 d_{l,2})$$

in the 3D space with β_1, β_2 forming a simplified parameter space. In this work, we generate random Gaussian direction vectors for different layers, and normalize them to obtain the same norm of the corresponding layer. Specifically, we make the replacement $d_l \leftarrow \frac{d_l}{\|d_l\|}\|\theta_l^*\|$ for a fully connected layer. For a convolutional layer, we use filter-wise normalization $d_l^k \leftarrow \frac{d_l^k}{\|d_l^k\|}\|\theta_l^{k*}\|$ as in (Li et al., 2018), where d_l^k represents the kth filter of the lth layer. We set both β_1 and β_2 in the domain of $[-1, 1]$.

Landscapes for FCNN. The loss landscapes for four residual blocks of the FCNN are shown in Fig. 4. For the shallower blocks, the surfaces are flatter near the minimizer, meaning that the gradient magnitudes may be small. However, small gradients do not necessarily lead to slow learning speed in this case. Combined with the gradient predictiveness discussed above, a flatter loss landscape may lead to more consistent gradient directions, making the learning more smooth.

Landscapes for CNNs. The loss landscapes for ResNet-50 and VGG-19 on ImageNet are shown in Fig. 5. It is interesting that deep convolutional networks with/without residual connections present totally different loss landscapes. For ResNet-50, its landscapes near the convergence point θ_l^* are smooth and nearly convex, making the neural network easier to train. On the contrary, VGG-19 has much more shattered landscapes, the initial iterations probably lie in the chaotic regions, prohibiting its training (Balduzzi et al., 2017). This may explain the much less efficient convergence towards the optimal point for VGG than ResNet at the initial phase (Fig. 2).

Comparing different layers in these two CNNs, the answer for layer convergence bias becomes clearer. The key difference between different layers' loss landscapes of ResNet-50 is the sharpness

(a) Res-Block 1   (b) Res-Block 2   (c) Res-Block 3   (d) Res-Block 4

Figure 4: The loss landscapes of different layers of FCNN. Deeper layers are optimized on more rugged landscapes, slowing down the learning process.

(a) ResNet-50 Res-Block 1   (b) ResNet-50 Res-Block 4   (c) VGG-19 Layer 1   (d) VGG-19 Layer 13

Figure 5: The loss landscapes of different layers of ResNet-50 (a,b) and VGG-19 (c,d). The shallower layers for both networks have flatter minima, making them converge faster than the deeper layers. The plots for all layers can be found in Appendix A.4.

of the local minima (Fig. 5 (a,b)). The reason, we conjecture, is because of a well-known fact that the shallower layers of CNNs tend to learn general features which are applicable to various datasets and tasks, while the deeper layers usually learn task-specific features (Yosinski et al., 2014). Since the general features are more evenly distributed, they usually cause less fluctuation for training, leading to flatter optima. Theoretically, flatter minimizers are easier to be found by SGD optimizers (Pan et al., 2020). As for the VGG-19, its shallower and deeper layers also have a flatter and sharper minima (Fig. 5 (c,d)), respectively. The shattered loss landscape for its deeper layers may also explain its inefficient learning process with a large learning rate (Fig. 2 (b)).

Here we summarize the mechanism behind layer convergence bias: the parameters of shallower layers are easier to optimize due to their flatter loss landscapes. At a higher level, shallower layers learn general features, which are usually easier.

5   DEEPER LAYERS FIT THE HIGH-FREQUENCY COMPONENTS

Recent advances in the learning process of DNNs (Rahaman et al., 2019; Ronen et al., 2019; Xu & Zhou, 2021) revealed that the low-frequency components of the target function are fitted much faster than the high-frequency components. There is a natural question about whether there is some inherent link between layer convergence bias and this result. In this section, we investigate the answer, and surprisingly find that: the low-frequency parts are usually fitted by the shallower layers, while the remaining higher frequencies are mainly learned by the deeper layers. It provides us with an alternative perspective to understand the layer convergence bias.

The Correspondence for FCNN. With the residual structures, we can use a straightforward visualization to show what exactly each block of the FCNN learns. Considering the FCNN with one input layer $z_0 = T_0(x) : \mathbb{R}^1 \to \mathbb{R}^{128}$, four residual blocks $z_l = T'_l(z_{l-1}) = T_l(z_{l-1}) + z_{l-1} : \mathbb{R}^{128} \to \mathbb{R}^{128}$, $l \in \{1, 2, 3, 4\}$, and an output layer $y = T_5(z_4) : \mathbb{R}^{128} \to \mathbb{R}^1$. The whole network can be expressed as

$$y = T_5(z_1 + T_2(z_1) + T_3(z_2) + T_4(z_3)) = T_5(z_1) + T_5(T_2(z_1)) + T_5(T_3(z_2)) + T_5(T_4(z_3))$$

if the output layer T_5 is a linear transformation. The fitting results for each layer are shown in Fig. 6. It can be seen that the deeper layers tend to fit the more complex components of the target function $y = sin(x) + \frac{1}{3}sin(3x) + \frac{1}{10}sin(10x) + \frac{1}{30}sin(30x)$. Besides the curvature, the fitted functions are also consistent with the amplitudes of the components. Specifically, the ranges of the four fitted

y $\qquad$ $T_5(z_1)$ $\qquad$ $T_5(T_2(z_1))$ $\qquad$ $T_5(T_3(z_2))$ $\qquad$ $T_5(T_4(z_3))$

Figure 6: The visualization of what each residual block learns. From the first to the fourth block, the fitted function becomes more complex with smaller amplitude.

(a) ResNet-50 $\qquad\qquad\qquad\qquad$ (b) VGG-19

Figure 7: The visualization of response frequencies for CNNs. As the training goes on, deeper layers become more sensitive to perturbations, indicating that they have higher response frequencies.

functions are $2.3, 0.7, 0.5$, and 0.06, which are similar to the four components. This result further confirms the relationship between layers and frequencies.

The Correspondence for CNNs. For CNNs, we verify their layer-frequency correspondence through the response frequency (Xu et al., 2019). In a nutshell, if an input-output mapping f possesses significant high frequencies, then a small change in its input induces a large change in the output. We generate standard Gaussian-distributed input x for different residual blocks of ResNet-50 and different layers of VGG-19. At the same time, small Gaussian perturbation Δx is added to the input. A larger change Δy of the layer output means the layer handles higher frequencies. The response frequencies are shown in Fig. 7. At the first 5 epochs of training on ImageNet, different layers for both ResNet-50 and VGG-19 do not show significantly different response frequencies. But after about ten epochs, the response frequencies for deeper layers (*e.g.*, stage 4 for ResNet-50, layer 13 for VGG-19) increase while the shallower layers show lower response frequencies. Therefore, we conclude that the layer-frequency correspondence also holds for CNNs. In addition, it is not an innate nature of the layers, but a result of the training process.

How the target frequency affects layer convergence bias? To demonstrate the effect of layer-frequency correspondence on the layer convergence bias, we try fitting simpler targets with less high-frequency components, and see what would happen to the layer-wise convergence rate of FCNN. In Fig. 8 (a-d), we only keep several lowest frequencies of the target, *e.g.*, the target function $y = sin(x)$ is named "Complexity=1", and $y = sin(x) + \frac{1}{3}sin(3x)$ is named "Complexity=2", *etc*. After discarding more and more high-frequency components, the deeper layers converge faster and faster. In this case, the layer convergence bias does not strictly hold anymore. In Fig. 8 (b), the Res-Block 4 converges faster than Res-Block 3 after the 5th epoch. In Fig. 8 (c), the Res-Block 4 converges with a similar speed as Res-Block 2, while the Res-Block 3 even learns faster than Res-Block 2. It seems that removing the high-frequency component that corresponds to a high layer can effectively accelerate its training. For CNNs, we also observe similar phenomena (Fig. 8 (e-h)). On simpler targets (*e.g.*, CIFAR 10), the deeper layers converge faster than on more complex targets (*e.g.*, CIFAR100). An implication of this result is that the data complexity may be too low for the model. In practice, CIFAR datasets only need ResNet-18 to fit well (Wu et al., 2020).

In fact, (Rahaman et al., 2019) had shown that different layers have some links to different frequencies, but the authors did not provide further insight for this phenomenon. This work verifies the underlying relationship between layers and fitting frequencies, and establishes a connection for this relationship to the layer convergence bias.

(a) FCNN Complexity=4   (b) FCNN Complexity=3   (c) FCNN Complexity=2   (d) FCNN Complexity=1

(e) ResNet-50 CIFAR100   (f) ResNet-50 CIFAR10   (g) VGG-19 CIFAR100   (h) VGG-19 CIFAR10

Figure 8: The convergence curves when fitting target functions with different complexities. (a-d): Decreasing target complexities for FCNNs. The deeper layers accelerates more than the shallower ones when high-frequency components are removed. (e-h): For CNNs, the highest layers (*i.e.*, Stage 4 / Layer 17) learn faster on CIFAR10 than on CIFAR100 while the other layers do not change much.

6 PRACTICAL SIGNIFICANCE

Up to now, we have been analyzing the layer convergence bias from a theoretical perspective. This section discusses its practical use to drive the development of DNN architecture design, and a new explanation for the acceleration effect of transfer learning with the help of layer convergence bias.

6.1 DNN ARCHITECTURE DESIGN

Modern CNN architectures (He et al., 2016) usually contain layers from narrow to wide (*e.g.*, 64 channels of the first layer to 2048 channels of the last layer). From the perspective of computational complexity, the narrower shallower layers make the corresponding large feature maps less computation-consuming. Considering the layer convergence bias, deeper layers with larger capacities are also beneficial for the corresponding high-frequencies to be learned easier. Although this is a common design for CNNs, Transformers (Dosovitskiy et al., 2020) usually apply the same architecture for all encoders. For a vision Transformer with 12 encoders, we use encoders with width 2/4/8 to construct three variants. The variants only differ in the arrangement of different encoders, we use W to denote the widths, and N to denote the number of each kind of encoders. The configures are summarized below:

Figure 9: Performance of three variants of ViTs on ImageNet.

- deeper encoders wider: $W = (2, 4, 8)$, $N = (6, 3, 3)$

- vanilla architecture: $W = (4, 4, 4)$, $N = (4, 4, 4)$

- deeper encoders narrower: $W = (8, 4, 2)$, $N = (3, 3, 6)$

Fig. 9 shows their performances, with the best accuracy of 80.75%, 78.88%, and 75.75%, respectively. We find that with the same number of parameters, putting the wider layers deeper results in higher training performance. This finding may serve as an effective way to improve the model capacity.

6.2 ACCELERATION EFFECT OF TRANSFER LEARNING

Transfer learning (fine-tuning with the pre-trained models) is a widely-used technique that can accelerate the model convergence (Shao et al., 2018b;a; Liang & Zheng, 2020). With the result that DNNs usually take long to fit the high-frequency components with their deeper layers, we want to know whether pre-training mainly helps the deeper layers to learn faster. We show the effect of transfer learning on the Flowers dataset (Nilsback & Zisserman, 2006). When training from scratch (Fig. 10 (a)), the shallower layers converge first so that the deeper layers can extract semantic features based on basic features. However, under the setting of transfer learning (Fig. 10 (b)), deeper layers can directly be built on the pre-trained basic features. The *Stage 4* shows the highest convergence rate among all layers. According to the loss landscapes of *Stage 4* w/o pre-training, transfer learning accelerates the convergence by making the loss landscapes of the deeper layers flatter.

(a) Train from scratch   (b) Fine-tuning

Figure 10: The effect of transfer learning on the training process. Left (a,b): The convergence process of different layers in ResNet-50. Transfer learning leads to the highest *Stage 4* the fastest one to converge. Right (a,b): The loss landscapes of *Stage 4* w/o transfer learning. With pre-training, the deeper layers can be regarded to be optimized on much flatter landscapes.

7 RELATED WORK

DNNs with gradient-based training show great potential to fit targets with arbitrary complexities (Hornik et al., 1989; Leshno et al., 1993), given sufficient width. With the advances in the last decade to verify the capability of the depth of universal approximators (Delalleau & Bengio, 2011; Eldan & Shamir, 2016; Lu et al., 2017), practitioners tried to reduce the width of neural networks by adding more layers (Simonyan & Zisserman, 2014; He et al., 2016; Huang et al., 2017). We are also inspired by research on local properties (sharpness/flatness) of loss functions at minima (Keskar et al., 2017; Li et al., 2018), relationship between convergence rate and generalization (Hardt et al., 2016), and inductive bias (Arpit et al., 2017; Helmbold & Long, 2015; Xuhong et al., 2018).

Before our work, (Zeiler & Fergus, 2014) also revealed that shallower layers converge faster in a five-layer CNN. In practice, the idea of layer convergence bias had already been intuitively applied to accelerate DNN training (Huang et al., 2016; Brock et al., 2017). Besides, arrangement schemes of CNN/Transformer blocks with different widths were explored by (Liu et al., 2022b;a).

8 CONCLUSION

In this work, we empirically studied the phenomenon that the shallower layers of DNNs tend to converge faster than the deeper layers, called layer convergence bias. This phenomenon is a natural preference in the process of DNN training: the shallower layers are responsible for extracting low-level features which are more evenly distributed and easier to learn, while deeper layers refine these features to do specific tasks. This makes the loss landscapes for shallower layers flatter than the landscapes for deeper layers, making shallower layers converge faster. In addition, this work established a connection between layers and learned frequencies. By showing deeper layers tend to fit the high-frequency components in the target function, we can understand the layer convergence bias from another perspective. We finally took DNN architecture design and transfer learning as two examples to show how theoretical findings in this work can shed light on the practical applications of deep learning. For progress to continue, a more in-depth understanding of the properties of neural networks is needed. We also hope that the layer convergence bias can inspire more practical improvements in the DNNs' architecture design and training schemes.

REFERENCES

Devansh Arpit, Stanisław Jastrzebski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, et al. A closer look at memorization in deep networks. In *International conference on machine learning*, pp. 233–242. PMLR, 2017.

David Balduzzi, Marcus Frean, Lennox Leary, JP Lewis, Kurt Wan-Duo Ma, and Brian McWilliams. The shattered gradients problem: If resnets are the answer, then what is the question? In *International Conference on Machine Learning*, pp. 342–350. PMLR, 2017.

Andrew Brock, Theodore Lim, James Millar Ritchie, and Nicholas J Weston. Freezeout: Accelerate training by progressively freezing layers. In *NIPS 2017 Workshop on Optimization: 10th NIPS Workshop on Optimization for Machine Learning*, 2017.

Olivier Delalleau and Yoshua Bengio. Shallow vs. deep sum-product networks. *Advances in neural information processing systems*, 24, 2011.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Ronen Eldan and Ohad Shamir. The power of depth for feedforward neural networks. In *Conference on learning theory*, pp. 907–940. PMLR, 2016.

Alex Graves, Abdel-rahman Mohamed, and Geoffrey Hinton. Speech recognition with deep recurrent neural networks. In *2013 IEEE international conference on acoustics, speech and signal processing*, pp. 6645–6649. Ieee, 2013.

Moritz Hardt, Ben Recht, and Yoram Singer. Train faster, generalize better: Stability of stochastic gradient descent. In *International conference on machine learning*, pp. 1225–1234. PMLR, 2016.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

David P Helmbold and Philip M Long. On the inductive bias of dropout. *The Journal of Machine Learning Research*, 16(1):3403–3454, 2015.

Sepp Hochreiter. Untersuchungen zu dynamischen neuronalen netzen. *Diploma, Technische Universität München*, 91(1), 1991.

Sepp Hochreiter, Yoshua Bengio, Paolo Frasconi, Jürgen Schmidhuber, et al. Gradient flow in recurrent nets: the difficulty of learning long-term dependencies, 2001.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.

Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European conference on computer vision*, pp. 646–661. Springer, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

Nitish Shirish Keskar, Jorge Nocedal, Ping Tak Peter Tang, Dheevatsa Mudigere, and Mikhail Smelyanskiy. On large-batch training for deep learning: Generalization gap and sharp minima. In *5th International Conference on Learning Representations, ICLR 2017*, 2017.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.

Moshe Leshno, Vladimir Ya Lin, Allan Pinkus, and Shimon Schocken. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. *Neural networks*, 6(6):861–867, 1993.

Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. *Advances in neural information processing systems*, 31, 2018.

Gaobo Liang and Lixin Zheng. A transfer learning method with deep residual network for pediatric pneumonia diagnosis. *Computer methods and programs in biomedicine*, 187:104964, 2020.

Ze Liu, Jia Ning, Yue Cao, Yixuan Wei, Zheng Zhang, Stephen Lin, and Han Hu. Video swin transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3202–3211, 2022a.

Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A convnet for the 2020s. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11976–11986, 2022b.

Zhou Lu, Hongming Pu, Feicheng Wang, Zhiqiang Hu, and Liwei Wang. The expressive power of neural networks: A view from the width. *Advances in neural information processing systems*, 30, 2017.

Arkadi Nemirovski, Anatoli Juditsky, Guanghui Lan, and Alexander Shapiro. Robust stochastic approximation approach to stochastic programming. *SIAM Journal on optimization*, 19(4):1574–1609, 2009.

Yurii Nesterov. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2003.

Michael A Nielsen. *Neural networks and deep learning*, volume 25. Determination press San Francisco, CA, USA, 2015.

M-E Nilsback and Andrew Zisserman. A visual vocabulary for flower classification. In *CVPR*, volume 2, pp. 1447–1454. IEEE, 2006.

Zhou Pan, Feng Jiashi, Ma Chao, Xiong Caiming, Chu Hong Hoi Steven, and E Weinan. Towards theoretically understanding why sgd generalizes better than adam in deep learning. In *Advances in Neural Information Processing Systems*, pp. 21285–21296, 2020.

Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pp. 5301–5310. PMLR, 2019.

Basri Ronen, David Jacobs, Yoni Kasten, and Shira Kritchman. The convergence rate of neural networks for learned functions of different frequencies. *Advances in Neural Information Processing Systems*, 32, 2019.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 115(3):211–252, 2015.

Shibani Santurkar, Dimitris Tsipras, Andrew Ilyas, and Aleksander Madry. How does batch normalization help optimization? *Advances in neural information processing systems*, 31, 2018.

Kun Shao, Yuanheng Zhu, and Dongbin Zhao. Starcraft micromanagement with reinforcement learning and curriculum transfer learning. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 3(1):73–84, 2018a.

Siyu Shao, Stephen McAleer, Ruqiang Yan, and Pierre Baldi. Highly accurate machine fault diagnosis using deep transfer learning. *IEEE Transactions on Industrial Informatics*, 15(4):2446–2455, 2018b.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. *Advances in neural information processing systems*, 27, 2014.

Pengxiang Wu, Songzhu Zheng, Mayank Goswami, Dimitris Metaxas, and Chao Chen. A topological filter for learning with label noise. *Advances in neural information processing systems*, 33: 21382–21393, 2020.

Zhi-Qin John Xu, Yaoyu Zhang, Tao Luo, Yanyang Xiao, and Zheng Ma. Frequency principle: Fourier analysis sheds light on deep neural networks. *arXiv preprint arXiv:1901.06523*, 2019.

Zhiqin John Xu and Hanxu Zhou. Deep frequency principle towards understanding why deeper learning is faster. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 10541–10550, 2021.

LI Xuhong, Yves Grandvalet, and Franck Davoine. Explicit inductive bias for transfer learning with convolutional networks. In *International Conference on Machine Learning*, pp. 2825–2834. PMLR, 2018.

Zhang Yi, Pheng-Ann Heng, and Ada Wai-Chee Fu. Estimate of exponential convergence rate and exponential stability for neural networks. *IEEE Transactions on Neural Networks*, 10(6):1487–1493, 1999.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? *Advances in neural information processing systems*, 27, 2014.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

A APPENDIX

A.1 EXPERIMENTAL SETTINGS

Datasets. The synthetic and real datasets are summarized in the Tab. 1

Table 1: Descriptions and statistics of the datasets used in this work.

Dataset	Size (train/test)	Classes	Data description
Sine regression	5000/5000	n/a	Function with four sine components, domain [-2,2]
ImageNet	1,281,167/50,000	1000	Photos of common objects
CIFAR-10	50,000/10,000	10	Photos of common objects, image sizes 32×32
CIFAR-100	50,000/10,000	100	Photos of common objects, image sizes 32×32
Flowers	1,088/272	17	Find-grained photos of flowers
FGVC Aircraft	6,667/3,333	100	Find-grained photos of aircrafts
Caltech-101	3,060/6,084	102	Photos/paintings/sketches of common objects
CUB-200	5,994/5,794	200	Find-grained photos of birds
DomainNet painting	50,416/21,850	345	Oil Paintings, murals, drawings, tattoos

Network Architectures. The FCNNs, CNNs, and Vision Transformers are summarized in the Tab. 2.

Table 2: Complexities and architectures of DNNs used in this work.

Model	#Parameters	Mult-adds	Architecture description
FCNN (no res)	2k	10k	4 fc layers [1-32-32-32-1]
FCNN (res)	132k	390k	fc [1-128] $\to$ 4 res-blocks [128-128-128] $\to$ fc [128-1]
ResNet-50	25.6M	4.1G	conv $\to$ 4 stages with [3,4,6,3] res-blocks $\to$ fc
VGG-19	143.7M	19.8G	16 conv layers, 3 fc layers
ViT	9.9M	77.2M	12 Transformer encoder blocks (basic width 256), 1 fc layer

Training Hyper-parameters. For the regression task, we train FCNNs with SGD optimizers for 300 epochs. The initial learning rate is 0.1, with a learning rate decay (to 0.01) at the 150th epoch. The batch size is 128, no weight decay (L_2 regularization) is conducted.

For the ImageNet classification task with CNNs, we train ResNet-50 and VGG-19 for 120 epochs with SGD optimizers. The initial learning rate is 0.1, with learning rate decays at the 50th and 100th epoch to 0.01 and 0.001, respectively. The batch size is 256, the input image size is 224^2, and weight decay coefficient is 10^{-4}.

For Vision Transformers on ImageNet dataset, we train them for 200 epochs with Adam optimizers. The peak learning rate is set to 0.0003. We use linear learning rate warm-up for 10,000 iterations, and a subsequent cosine learning rate decay. The batch size is 256, the input image size is 224^2, and the weight decay coefficient is 10^{-4}.

For CNN image classification on other datasets, we train models for 100 epochs with SGD optimizers. Initial learning rate of 0.01 and cosine learning rate scheduler are applied. The batch size is 128, the input image sizes are 32^2 (for CIFAR) and 224^2 (for Flowers, Aircraft, Caltech, CUB, and DomainNet), and the weight decay coefficient is 10^{-4}.

A.2 FACTORS AFFECTING LAYER CONVERGENCE BIAS

In Section 5, we have shown that the complexity of the datasets is an important factor affecting layer convergence bias. When the fitting target function is complex enough with both low and high frequency components, the shallower layers learn the low low-frequency components while the deeper layers learn the high-frequency components. Here we use the FCNNs with residual connections to show whether some other important factors would affect the layer convergence bias.

First, we examine the FCNNs with different depths. Note that the default architecture is four res-blocks, but here we try adding more and see what change will happen. As shown in Fig. 11, all the

Figure 11: The convergence process of FCNNs with different number of res-blocks.

networks show layer convergence bias. With more and more res-blocks, the overall convergence of the network becomes slightly faster.

Figure 12: The convergence process of FCNNs with different learning rates.

In addition, we explore the effect of different learning rates. The results are shown in Fig. 12. When the learning rate gets smaller (*e.g.*, 0.01), layer convergence bias becomes weaker. This is because the gradient predictiveness *w.r.t.* parameters of all layers get close to 1 (see Fig. 3 (b,right) for the predictiveness with the learning rate of 0.01). In this case, only the gradient predictiveness *w.r.t.* data matters for the convergence rate.

Figure 13: The convergence process of FCNNs with different optimizers.

Last but not least, we try different optimizers for training FCNNs. In Section 4, we have discussed the mechanism behind layer convergence bias. The flatter/sharper minimizers of different layers make SGD learn at different speeds. This is because SGD is more good at finding flatter minimizers (Pan et al., 2020). In Fig. 13, we compare SGD with three adaptive optimizers: Adagrad, RMSprop, and Adam. It is evident that with adaptive optimizers, layer convergence bias does not hold anymore. We conjecture the reason behind this is that the adaptive optimizers heuristically assign different learning rates for different parameters, making their optimization hardly predictable.

A.3 RESULTS ON HARDER DATASETS

For verifying the layer convergence bias on more datasets, we show more convergence results on four harder image classification datasets (see Fig. 14). Most of the classes in these datasets only have < 100 samples, making them harder to learn. Note that the experiments are conducted with the learning rate of 0.01 (learning rate of 0.1 failed in some cases because these datasets have too many classes but not sufficient samples, leading to non-decreasing loss), some deeper layers have quite similar convergence rates because of the small learning rate. But roughly speaking, layer convergence bias still holds for these datasets.

(a) ResNet-50

(b) VGG-19

Figure 14: The convergence process of CNNs on four image classification tasks.

A.4 REPEATABILITY OF THE VISUALIZATIONS

Do different ImageNet trained models produce dramatically different loss landscapes? We plot the loss landscapes of different models with different random seeds in Fig. 15, 16. Quite similar patterns of the landscapes for different layers can be observed on both ResNet and VGG with different random seeds.

(a) Stage 1 Seed 1   (b) Stage 2 Seed 1   (c) Stage 3 Seed 1   (c) Stage 4 Seed 1

(d) Stage 1 Seed 2   (e) Stage 2 Seed 2   (f) Stage 3 Seed 2   (g) Stage 4 Seed 2

Figure 15: The loss landscapes of different layers of ResNet-50.

(a) Layer 1 Seed 1   (b) Layer 5 Seed 1   (c) Stage 9 Seed 1   (d) Stage 13 Seed 1

(e) Layer 1 Seed 2   (f) Layer 5 Seed 2   (g) Stage 9 Seed 2   (h) Stage 13 Seed 2

Figure 16: The loss landscapes of different layers of VGG-19.