MMA: Multimodal Memory Agent

Abstract

Long-horizon multimodal agents depend on external memory; however, similarity-based retrieval often surfaces stale, low-credibility, or conflicting items, which can trigger overconfident errors. We propose **Multimodal Memory Agent (MMA)**, which assigns each retrieved memory item a dynamic reliability score by combining *source credibility*, *temporal decay*, and *conflict-aware network consensus*, and uses this signal to reweight evidence and abstain when support is insufficient. We also introduce **MMA-Bench**, a programmatically generated benchmark for belief dynamics with controlled speaker reliability and structured text–vision contradictions. Using this framework, we uncover the "Visual Placebo Effect", revealing how RAG-based agents inherit latent visual biases from foundation models. On FEVER, MMA matches baseline accuracy while reducing variance by 35.2% and improving selective prediction utility; on LoCoMo, a safety-oriented configuration improves actionable accuracy and reduces wrong answers; on MMA-Bench, MMA reaches 41.18% Type-B accuracy in Vision mode, while the baseline collapses to 0.0% under the same protocol.

1 Introduction

Memory-augmented LLM agents increasingly underpin long-horizon interactive systems that must preserve and update user-specific context over time (Park et al., 2023; Guo et al., 2024). Recent memory architectures introduce more structured memory management and control mechanisms, achieving strong results on conversational benchmarks (Wang and Chen, 2025; Packer et al., 2024). Yet, reliability remains a bottleneck when agents must operate under noisy inputs, stale information, and mutually inconsistent memories.

A core limitation is that many memory systems implicitly treat retrieved items as equally reliable by default during reasoning. In practice, information quality varies substantially: sources differ in credibility, facts become outdated, and new retrievals can contradict previously stored content. Without explicit reliability modeling, low-quality memories may propagate through multi-step inference and amplify downstream errors (Xiong et al., 2025). Compounding this, LLM-based agents can produce fluent but unfaithful outputs (hallucinations) that obscure uncertainty and lead to overconfident responses, raising practical safety risks in real-world use (Ji et al., 2023). They often respond even when supporting evidence is insufficient or inconsistent, producing confident answers that later prove to be incorrect. In safety-critical applications, where mistakes impose real costs, this failure to assess evidential sufficiency and arbitrate conflicts becomes particularly problematic.

Given these challenges, our motivation is twofold: (i) memory-level reliability assessment and (ii) evaluation that is incentive-aligned with epistemic prudence. For unreliable memory propagation, agents need mechanisms that separate trust-

Figure 1: **Retrieval Trap Case Study.** MIRIX fails by retrieving the high-similarity but irrelevant Memory B. MMA correctly identifies the credible Memory A using multi-dimensional reliability signals.

worthy information from questionable content by accounting for source credibility, temporal recency, and coherence with related memories. For epistemic awareness, agents must detect insufficient evidence and abstain when appropriate (Varshney et al., 2023; Kuhn et al., 2023). Testing this ability requires incentive-aligned frameworks (e.g., abstention-aware scoring) that credit justified abstention and penalize overconfident mistakes, going beyond accuracy-only metrics (Quach et al., 2024; Yadkori et al., 2024). This approach better matches real deployment needs (Geifman and El-Yaniv, 2017), where admitting uncertainty often beats giving wrong answers with confidence.

To address these challenges, we propose **MMA** (Multimodal Memory Agent), a confidence-aware memory agent built around a post-retrieval meta-cognitive module that assigns dynamic reliability scores to retrieved memories and uses this signal for selective prediction. Designed as a standalone module, it can augment various RAG architectures without modifying their underlying retrieval mechanisms. As shown in Figure 1, this reliability signal mitigates similarity-based retrieval traps by prioritizing source-credible evidence and discounting stale or weakly supported mentions.

In summary, this work makes three contributions:

- We propose the Multimodal Memory Agent (MMA), a dynamic confidence scoring framework that assesses memory reliability through source credibility, temporal decay, and cross-memory consistency.

- We introduce MMA-Bench, a diagnostic benchmark that operationalizes belief dynamics under multimodal conflict and controlled reliability priors. Through extensive evaluation, we diagnose the "Visual Placebo Effect," where ambiguous visual inputs can induce unwarranted certainty in RAG-based agents.

- We demonstrate improved reliability under risk-aware evaluation across FEVER, Lo-CoMo, and MMA-Bench, including 35.2% lower accuracy standard deviation on FEVER, fewer wrong answers on LoCoMo, and 41.18% Type-B accuracy on MMA-Bench (Vision mode) under the same evaluation protocol.

2 Related Work

Memory-Augmented LLM Agents. Memory-augmented agents improve long-horizon interaction by writing to external memory and retrieving relevant items at inference time (Packer et al., 2024; Wang and Chen, 2025). Research improves this retrieval-and-inject pipeline through structured/typed memory with specialized modules (Wang and Chen, 2025), context-budgeted memory management with paging and hierarchies (Packer et al., 2024; Kang et al., 2025; Li et al., 2025), and lifecycle operations such as versioning and conflict handling (Li et al., 2025). Other approaches compress or synthesize memory representations to reduce long-horizon overhead (Zhou et al., 2025; Zhang et al., 2025a) or organize memories into evolving networks for indexing and updates (Xu et al., 2025). At the same time, empirical evidence suggests that memory policies can induce *experience-following*, where retrieval noise compounds over time (Xiong et al., 2025). This points to a complementary gap: most agents still treat retrieved items as uniformly trustworthy despite staleness, low credibility, or inconsistency. MMA operationalizes memory-level reliability with per-item confidence scores that are used directly during downstream reasoning.

Confidence and Epistemic Mechanisms. Uncertainty estimation and calibration are widely used to mitigate hallucinations. Semantic uncertainty captures meaning-level variability across generations (Kuhn et al., 2023), and self-consistency methods such as SelfCheckGPT exploit cross-sample disagreement (Manakul et al., 2023). These signals motivate *selective prediction*, including conformal language modeling (Quach et al., 2024) and conformal abstention (Yadkori et al., 2024); related analyses argue that standard training and evaluation can incentivize systematic overconfidence (Kalai et al., 2025). Recent work also explores explicit self-reporting ("confessions") for monitoring and intervention (Joglekar et al., 2025). Most prior techniques act at the token or response level; in contrast, we target a memory-agent failure mode where *unreliable retrieved memories* trigger overconfident commitments. We evaluate with incentive-aligned scoring that rewards calibrated abstention even when correctness is ambiguous.

Benchmarks for Multimodal Belief Dynamics. Long-context benchmarks primarily score correctness under extended inputs (LongBench (Bai et al.,

Benchmark	Setting	Modality	Temp. structure	Paired T–V evidence	Src prior	Epistemic scoring
LongBench (Bai et al., 2024)	static LC	Text	static	✗	✗	accuracy
RULER (Hsieh et al., 2024)	synth LC	Text	static	✗	✗	accuracy
LoCoMo (Maharana et al., 2024)	LT dialog	Text	multi-session / months	✗	✗	accuracy
FEVER (Thorne et al., 2018)	verif.	Text	static	✗	✗	accuracy (NEI)
LongMemEval (Wu et al., 2025)	LT dialog	Text	multi-session	✗	✗	abstention
EvolMem (Shen et al., 2026)	LT dialog	Text	multi-session	✗	✗	accuracy
Mem-Gallery (Bei et al., 2026)	LT dialog	Multi	multi-session	✗	✗	accuracy
MMA-Bench (Ours)	**LT dialog**	**Multi**	**10 / ∼6mo**	✓	✓	**CoRe**

Table 1: **Comparison of Benchmarks Related to Long-horizon Evidence Use.** MMA-Bench complements prior suites by explicitly controlling source reliability priors and pairing multimodal evidence to enable a controlled diagnosis of belief dynamics and epistemic behavior under conflict.

2024); RULER (Hsieh et al., 2024)), but rarely stress-test belief revision when evidence quality drifts over time, modalities disagree, and agents must decide whether to commit, hedge, or defer. Recent work has advanced toward more interactive memory evaluation: LongMemEval (Wu et al., 2025) benchmarks multi-session chat assistants with abstention-aware tasks including knowledge updates and information withholding, while EvolMem (Shen et al., 2026) probes cognitively motivated memory dimensions—such as declarative and procedural recall—across evolving dialogue sessions. Mem-Gallery (Bei et al., 2026) further extends the scope to multimodal long-term conversational memory for MLLM agents. Despite these advances, none of these benchmarks jointly control *source reliability priors*, pair text–vision evidence in adversarial configurations, or apply scoring that incentivizes calibrated abstention over overconfident errors. Recent work also highlights how modality conflicts arise in unimodal reasoning (Zhang et al., 2025b); we adopt a similar diagnostic lens in long-horizon *memory agents* and focus on how reliability and conflict interact over time. MMA-Bench (Table 1) fills this gap with controlled priors, paired text–vision evidence, and CoRe (Confidence-and-Reserve) scoring for fine-grained diagnosis of epistemic failures.

Our Positioning. Unlike prior works that prioritize memory organization, compression, or retrieval efficiency, our core contribution is pre-reasoning reliability assessment. By calculating confidence scores at the item level before context is injected into the LLM, our framework functions as an independent, modular filter. This allows it to be integrated into various RAG-based agent architectures regardless of their internal retrieval mechanism. Extended discussion of related work is provided in Appendix A.

3 The Proposed Method And Benchmark

3.1 Overview

We present two contributions: (1) MMA, an agent architecture extending MIRIX (Wang and Chen, 2025) with a confidence module for epistemic prudence; and (2) MMA-Bench, a benchmark simulating dynamic social environments to evaluate belief dynamics and calibration under conflict.

3.2 Multimodal Memory Agent (MMA)

Our approach augments the MIRIX framework with a meta-cognitive reliability layer. Formally, let $\mathcal{M} = \{M_1, M_2, ..., M_N\}$ be retrieved memories for query Q. The Confidence Module computes a scalar score $\mathcal{C}(M_i) \in [0, 1]$ to modulate retrieval: high-confidence items are prioritized, while low-confidence items are flagged for potential abstention.

Confidence Formulation. The confidence score $\mathcal{C}(M_i) \in [0, 1]$ is a self-normalizing weighted sum of Source (S), Time (T), and Consensus (C_{con}) components. Using normalized weights w'_k, the final score is:

$$\mathcal{C}(M_i) = w'_s S(M_i) + w'_t T(M_i) + w'_c C_{\text{con}}(M_i). \quad (1)$$

(1) Source Reliability $S(M_i)$**:** We map the memory origin src_i to a predefined trustworthiness prior. This static score ensures high-quality sources are prioritized $S(M_i) = \text{Map}(\text{src}_i)$. This mapping is a user-configurable hyperparameter reflecting the inherent trustworthiness of different information origins. In our implementation, we use default values of User $= 1.0$, Documents/Web $= 0.9/0.7$, and Model $= 0.6$. This reflects a practical RAG hierarchy where verifiable internal knowledge is trusted more than external web content, and both are prioritized over unverified model-generated outputs.

(2) Temporal Decay $T(M_i)$**:** This component

Figure 2: **MMA Framework.** The Confidence Module reweights retrieval via source reliability, temporal decay, and network consensus to modulate reasoning and abstention.

models information aging using an exponential decay with a half-life T_{half}:

$$T(M_i) = \exp\left(-\frac{\ln(2)}{T_{\text{half}}}\Delta t_i\right). \quad (2)$$

(3) Network Consensus $C_{\text{con}}(M_i)$: This metric measures semantic support within the retrieved neighborhood $\mathcal{N}(M_i)$, acting as a consistency filter, computed as:

$$C_{\text{con}}(M_i) = \frac{\sum_{M_j \in \mathcal{N}(M_i)} w_{ij} \cdot \mathcal{C}(M_j) \cdot \sigma_{ij}}{\sum_{M_j \in \mathcal{N}(M_i)} w_{ij}}, \quad (3)$$

$$\sigma_{ij} = \text{sim}_{\cos}(\mathbf{v}_i, \mathbf{v}_j) = \frac{\mathbf{v}_i \cdot \mathbf{v}_j}{\|\mathbf{v}_i\|\|\mathbf{v}_j\|}, \quad (4)$$

where $\mathcal{C}(M_j)$ represents the confidence score of a neighboring memory item M_j within the retrieved context. As illustrated in Figure 2, if a memory involves previously stored or evaluated context, its prior confidence score C_{prev} is directly utilized. $\sigma_{ij} \in [-1, 1]$ is the Support Factor. Positive values reinforce confidence via alignment, while negative values penalize contradictions.

3.3 MMA-Bench

Existing benchmarks for long-context agents predominantly focus on information retrieval or static memory consistency. However, real-world deployment requires agents to decide which source to trust when multiple sources provide conflicting multimodal evidence, and demonstrate epistemic prudence. To address this, we introduce MMA-Bench, a multi-modal benchmark designed to evaluate belief dynamics and cognitive robustness.

Design Philosophy and Capabilities. MMA-Bench evaluates two core dimensions: (1) *Cross-Modal Consistency*, comparing performance in Text Mode (oracle captions) versus Vision Mode (raw images); and (2) *Risk-Aware Epistemic Calibration*, utilizing a betting mechanism to credit justified abstention and penalize overconfidence.

Data Architecture. Each case consists of a generated dialogue stream spanning 10 temporal sessions (approx. 6 months). The narrative involves a historically reliable User A and an unreliable User B. The generation pipeline proceeds through four distinct phases: Phase 1 (Calibration, S1-4) implicitly establishes source reliability priors via verifiable events. Phase 2 (Adversarial Noise, S5-7) injects high-volume chit-chat involving entities similar to target facts to rigorously stress-test attention mechanisms. Phase 3 (The Trap, S8) introduces the core multimodal conflict where User B makes a claim supported by visual evidence that contradicts User A. Finally, in Phase 4 (Resolution, S9-10), the ground truth is either resolved or remains unknowable to evaluate abstention capabilities.

Quality Control. To mitigate benchmark artifacts,

Figure 3: **MMA-Bench evaluation framework.** The benchmark integrates cross-modal consistency analysis, risk-aware betting, and a 2×2 logic matrix for trust conflicts. Performance is assessed through fundamental QA and a 3-step belief probe.

we enforce a rigorous three-step quality control protocol: (1) generation is strictly constrained by the programmatic Logic Matrix; (2) manual spot-checks are conducted to ensure that AI-generated images accurately match their corresponding link descriptions; and (3) we manually verify approximately 10% of the generated text to guarantee logical coherence and the absence of severe hallucinations.

Logic Matrix. To systematically evaluate robustness, we formalize a logic matrix that categorizes conflicts into four types based on the interaction between source reliability and visual evidence (Table 2). This taxonomy is inspired by recent findings on cross-modal inconsistency (Zhang et al., 2025b), which highlight that agents often prioritize specific modalities regardless of their reliability.

Type	Conflict	Configuration	Target Capability
A	Standard	Visuals support reliable User A.	Baseline consistency.
B	Inversion	Visuals support unreliable User B.	Overcoming authority bias.
C	Ambiguity	Visuals are vague.	Rejecting over-interpretation.
D	Unknowable	No valid evidence.	Absolute abstention.

Table 2: **Logic Matrix for MMA-Bench.** Categorization of multimodal trust conflicts based on source reliability and visual evidence.

Evaluation Protocol. We propose a hierarchical framework to dissect performance from basic retrieval to high-level cognitive arbitration.

Layer 1: Fundamental Capabilities. This layer assesses foundational skills through standard QA, covering four dimensions: fact retrieval, logic reasoning, source analysis, and adversarial distraction accuracy.

Layer 2: The 3-step Probe & CoRe Scoring. This layer evaluates the agent's belief state using a 3-step probe, inspired by self-correction mechanisms (Joglekar et al., 2025). To rigorously score calibration, we introduce the *CoRe (Confidence-and-Reserve) Score*, formulated as a rule-based function $S(\hat{y}, \mathbf{w} \mid \mathcal{T})$ conditioned on the logic type $\mathcal{T}$:

$$S = \begin{cases} \beta \cdot \mathbb{I}(\hat{y} = y^*) + (1-\beta) \cdot \frac{w_{winner}}{100} & \text{if } \mathcal{T} \in \{A, B\} \\ \frac{w_{reserve}}{100} - \gamma \cdot \mathbb{I}(\hat{y} \neq \text{UNKNOWN}) & \text{if } \mathcal{T} \in \{C, D\} \end{cases}$$
(5)

where $\beta \in [0, 1]$ is a scaling factor balancing binary accuracy and wagered confidence, and γ is a penalty coefficient designed to punish unjustified certainty (hallucinations) in indeterminate scenarios. w_{winner} and $w_{reserve}$ denote the explicit confidence score (0-100) wagered by the model on its chosen verdict and the abstention option, respectively. $\mathcal{T} \in \{A, B\}$ represents deterministic cases, and $\mathcal{T} \in \{C, D\}$ represents indeterminate cases. In practice, these hyperparameters (β and γ) are set empirically based on the specific risk tolerance of the target application.

Layer 3: Cognitive Dynamics Metrics. To diagnose the mechanics of modality preference and belief revision, we define three metrics. First, *Modality Signal Alignment (MSA)* categorizes the agent's verdict Y_{model} by aligning it with theoretical signal vectors for Text (S_{text}) and Vision (S_{vis}). In Type B (Inversion), S_{vis} implies TRUE (Trap); in Type C/D, S_{vis} implies UNKNOWN (Uncertainty).

$$C(Y_{model}) = \begin{cases} \text{Text-Dominant} & \text{if } Y_{model} = S_{text} \\ \text{Vision-Dominant} & \text{if } Y_{model} = S_{vis} \quad (6) \\ \text{Confusion} & \text{otherwise.} \end{cases}$$

Second, we quantify the driver of preference using *Relative Reasoning Uncertainty* ($\Delta H_{rel} = 2(H_{text} - H_{vis})/(H_{text} + H_{vis})$), where a positive value indicates higher certainty in the visual stream.

Finally, we measure the stability of correct beliefs using the *Self-Correction Rate (SCR)* and the *False Confession Rate (FCR)*. The SCR quantifies the probability of correcting an initial error after reflection:

$$SCR = \frac{\text{Count}(\text{Step 1} = \text{Wrong} \wedge \text{Step 3} = \text{Right})}{\text{Count}(\text{Step 1} = \text{Wrong})}. \quad (7)$$

Conversely, we define the False Confession Rate (FCR) to measure the tendency of models to abandon initially correct answers under the pressure of reflection prompts:

$$FCR = \frac{\text{Count}(\text{Step 1} = \text{Right} \wedge \text{Step 3} = \text{Wrong})}{\text{Count}(\text{Step 1} = \text{Right})}. \quad (8)$$

A high FCR relative to SCR indicates that the model's belief reversals are driven by over-accommodation to the reflection prompt rather than a calibrated assessment of its own uncertainty.

4 Experiments

To ensure a fair evaluation, all evaluated agents are built on the GPT-4.1-mini foundation model unless otherwise specified. In our experiments, MMA is implemented as a plug-in confidence module on top of the MIRIX baseline architecture. Consequently, both MMA and MIRIX strictly utilize the identical underlying retrieval configurations, embedding models, and candidate memory pools. Furthermore, the external memory database is completely cleared before each experimental run to prevent cross-contamination. Crucially, because the structural retrieval ceiling remains identical for both systems, any divergence in downstream reasoning performance is causally attributable solely to MMA's pre-reasoning confidence module, whether performance gains or conservative abstentions.

4.1 Robustness on Standard Benchmarks

We first validate MMA on standard text-centric benchmarks to ensure generalizability.

FEVER (Fact Verification) (Thorne et al., 2018). As shown in Table 3, MMA matches the baseline accuracy ($\approx 59.9\%$) but significantly improves stability, reducing the standard deviation by 35.2% ($\pm 1.62\%$ vs. $\pm 2.50\%$). This confirms that our confidence-aware filtering effectively mitigates the stochasticity of retrieval without compromising utility. Full results and component analyses are detailed in Appendix B.

LoCoMo (Long-Context QA) (Maharana et al., 2024). On the sparse LoCoMo benchmark, we observe a density-driven trade-off. While the full consensus module is conservative, the 'st' variant (Source + Time) achieves state-of-the-art Utility (883.6), outperforming the baseline. This demonstrates the framework's adaptability: consensus is vital for conflict (MMA-Bench) but optional in low-density (sparse) settings. Comprehensive evaluation is provided in Appendix C.

4.2 Results on MMA-Bench

We compared the cognitive dynamics of our MMA against the baseline (MIRIX) on the adversarial MMA-Bench. The results, visualized in Figure 4, reveal a fundamental divergence in how confidence-aware agents handle multimodal conflicts compared to standard RAG systems.

Robustness in Reliability Inversion Scenarios. In Type B (Reliability Inversion) scenarios, the Baseline exhibits a 100% confusion rate (defaulting to "Unknown"). This indicates a failure to engage: due to the high-noise environment, the standard RAG agent fails to retrieve the conflicting evidence required to form a verdict. In contrast, MMA demonstrates active conflict resolution. Despite the difficulty, MMA successfully identifies and prioritizes visual evidence in 41.18% of cases (Vision Dominant), as visualized in the step-wise verdict distribution (Figure 4). This confirms that the confidence module provides the necessary signal discrimination to attempt resolution, whereas the Baseline remains stagnant due to noise intolerance.

Qualitative Analysis of Abstention Drivers. In indeterminate scenarios (Type C and D), the Baseline achieves a deceptively high raw accuracy (Figure 4, Left). However, our analysis suggests that this is an artifact of retrieval limitations rather than epistemic prudence. Qualitative analysis of the response logs reveals that 83.3% of the Baseline's refusals explicitly cite a "lack of information", whereas 0% references source unreliability. This confirms that, due to the high-noise environment, the Baseline simply fails to retrieve the "trap," defaulting to an

Method	Performance Metrics		Prudence Metrics		Stability (Std) ($\downarrow$)
	Raw Acc. ($\uparrow$)	Selective ($\alpha = 0.2$) ($\uparrow$)	Abstain Rate ($\uparrow$)	Abstain Prec. ($\uparrow$)	
MIRIX (Baseline) (Wang and Chen, 2025)	59.87%	0.6468	44.2%	45.6%	$\pm 2.50\%$
MMA (Ours)	**59.93%**	**0.6484**	**45.3%**	**45.8%**	$\pm 1.62\%$

Table 3: **Main Results on FEVER.** MMA matches baseline accuracy while significantly reducing performance variance.

Method	Mode	Overall Metrics			Scenario-Specific Analysis	
		Core Acc. ($\uparrow$)	Verdict Acc. ($\uparrow$)	CoRe Score ($\uparrow$)	Type B Acc. ($\uparrow$)	Type D Score ($\uparrow$)
MIRIX (Baseline) (Wang and Chen, 2025)	Text	**30.94%**	47.78%	**0.37**	0.00%	**1.00**
	Vision	**32.67%**	46.67%	0.35	0.00%	**1.00**
MMA (Ours)	Text	13.15%	**56.67%**	0.28	23.53%	0.69
	Vision	13.55%	42.22%	-0.16	**41.18%**	-0.38

Table 4: **MMA-Bench Main Results.** Comparison across conflict types (Type D uses risk-adjusted CoRe scoring).

"Unknown" state, which coincidentally aligns with the ground truth. MMA, conversely, actively engages with the noise. In Text Mode, it achieves a high CoRe Score in Type D (Figure 4, Right), demonstrating Intentional Prudence by correctly identifying information gaps based on source reliability analysis.

Visual Placebo Effect. We quantify the impact of visual noise by tracking performance shifts in Type D (Unknowable) scenarios. The Baseline (MIRIX) exhibits Zero Visual Sensitivity (Figure 4), maintaining a constant CoRe Score (≈ 1.0) across modes. This confirms that its apparent stability stems from retrieval blindness—failing to retrieve context makes it immune to visual noise. In stark contrast, MMA suffers a severe regression, with its prudent score collapsing from 0.69 (Text) to -0.38 (Vision). We term this the *Visual Placebo Effect*: the agent treats the presence of an image as sufficient evidence for a definitive verdict, even when the image content is uninformative.

4.3 Evolution of Agent Decision-Making

To understand the contribution of each design choice, we analyze the performance trajectory from the foundation model (GPT-4.1-mini, Full Context) to the retrieval-constrained baseline (MIRIX), and finally to our proposed agent (MMA). Figure 5 visualizes this evolutionary transformation, illustrating how architectural constraints and confidence modulation shape decision-making behaviors.

Restoring Active Decision-Making in Resolvable Cases. The transition from MIRIX to MMA marks the reactivation of agency. The baseline MIRIX exhibits signs of cognitive paralysis, yielding 0.0% accuracy in Type A and Type B scenarios. Without a prior over source trustworthiness, the system cannot distinguish reliable signals from noise and

defaults to "Unknown" for every query. In contrast, MMA functions as a trust catalyst, utilizing Source (S) and Time (T) modules to restore the capability to form positive verdicts (Type A: 50.0%). However, a structural retrieval ceiling persists; neither architecture can replicate the omniscient performance of GPT-4.1-mini (100% Acc) as the current retrieval implementation restricts them to fragmented evidence (Retrieval Acc $< 35\%$ vs. 80%), limiting the upper bound of perception.

The Cost of Consensus in Ambiguous Scenarios. A critical divergence is observed in Type C (Ambiguity) scenarios. While MIRIX achieves 96.7% accuracy, MMA experiences a significant drop to 40.0%, implying the success of MIRIX is likely spurious. Response logs confirm this: 83.3% of the baseline's refusals explicitly cite "lack of information". This proves the baseline defaults to "Unknown" due to retrieval blindness rather than intentional epistemic calibration. Conversely, enforcing semantic consistency (C_{con}) compels MMA to align with specific signals amidst noise. This optimizes MMA for active conflict resolution (Type B) at the expense of passivity in ambiguous zones.

Inheritance of Visual Bias. GPT-4.1-mini exhibits a latent bias toward visual credibility, which both MIRIX and MMA inherit. MIRIX masks this bias through cognitive paralysis; conversely, MMA exposes it by attempting active decision-making. This leads to high-wager hallucinations in Type D (Unknowable) scenarios (Score -0.38), as visual data creates an illusion of sufficiency that the agent fails to reject.

Pipeline Rigidity Blocks Effective Self-Correction. Finally, both architectures handle self-correction poorly. While the foundation model demonstrates severe over-accommodation

(a) Longitudinal Reasoning Trajectory. (b) Stratified Logic Analysis. (c) Metric Divergence Analysis.

Figure 4: **Detailed Dynamics Analysis.** (a) Step-wise belief revision; (b) Risk-adjusted sensitivity; (c) Retrieval-calibration gap.

Figure 5: **Evolutionary Logic Spectrum.** Performance trajectory from foundation model to MMA.

to user prompts (FCR 71.2%), MIRIX and MMA record an FCR of 0%. However, analysis of 62 failure instances reveals that agents admit errors during reflection yet fail to update their initial verdicts. This confirms that architectural rigidity mechanically blocks corrective actions, explaining why both agents acknowledge errors during reflection but remain tethered to their initial commitments.

4.4 Ablation Study

To isolate component contributions, we focus on the critical failure modes exposed on all benchmarks by removing Source (S), Time (T), and Consensus (C_{con}), as summarized in Table 5. Full results are in the Appendices.

Component Impact Analysis. As shown in Table 5, Source (S) is the prerequisite for agency; its removal causes cognitive paralysis (0.0% Acc in Type A/B). Consensus (C_{con}) buffers against noise,

Model	Deterministic (Type A, Vis)		Indeterminate (Type D, Vis)	
	Verdict Acc. (↑)	Status	CoRe Score (↑)	Interpretation
MMA (Full)	**50.0%**	**Robust**	**−0.38**	**Buffered**
tc (w/o Source)	0.0%	Paralyzed	1.00[†]	Artifact of Default
st (w/o Consen.)	36.7%	Unstable	−0.69	Hallucinated
cs (w/o Time)	0.0%	Degraded	1.00[†]	Artifact of Default

Table 5: **Ablation results on MMA-Bench (Vision Mode).** [†]Perfect scores in Type D coincide with 0% accuracy in Type A (system paralysis).

as its absence leads to score collapse (−0.69) in ambiguous Type D scenarios, rendering the agent vulnerable to the Visual Placebo Effect. Finally, Temporal Decay (T) is essential for cross-modal stability; removing it causes performance evaporation in Vision mode. Together, these results confirm that each component is indispensable for robust epistemic filtering.

5 Conclusion

In this work, we introduce MMA, a confidence-aware memory framework that transforms passive memory storage into active epistemic filtering. By dynamically scoring retrieved items according to source credibility, temporal decay, and cross-memory consensus, MMA mitigates retrieval stochasticity and enables calibrated abstention. Furthermore, our novel MMA-Bench diagnostic suite reveals the "Visual Placebo Effect," demonstrating how multimodal agents inherit latent visual biases from foundation models under conflict. Empirical evaluations demonstrate that MMA overcomes cognitive paralysis, improves performance stability, and delivers a superior risk-coverage trade-off. Ultimately, this framework provides critical cognitive guardrails for high-stakes LLM agent applications, representing a necessary step toward genuine epistemic prudence in long-horizon reasoning.

Limitations

While MMA enhances reliability, several limitations warrant future exploration. **First, reliance on upstream retrieval recall:** As a post-retrieval module, MMA can filter out hallucinations but cannot rectify the absence of evidence if the underlying RAG system fails to retrieve relevant context. **Second, the sparsity-consensus trade-off:** Our analysis on LoCoMo suggests that strict consensus enforcement can be conservative in low-density information environments. Future work could explore adaptive gating mechanisms that dynamically enable or disable consensus based on context entropy. **Third, sensitivity to reliability priors:** The source credibility mapping ($\text{Map}(\text{src}_i)$) currently relies on user-configurable priors. Although our ablations confirm that having a prior is mechanically necessary to prevent cognitive paralysis, conducting a systematic sensitivity analysis of these prior values across diverse operational domains remains an important direction. **Fourth, generalizability of the Visual Placebo Effect:** While we validated this phenomenon across distinct foundation models (GPT-4.1-mini and Qwen3-VL-Plus) using structured conflict types, larger-scale stress testing across a wider range of VLM architectures is necessary to fully characterize its implications.

References

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. 2024. LongBench: A bilingual, multi-task benchmark for long context understanding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3119–3137, Bangkok, Thailand. Association for Computational Linguistics.

Yuanchen Bei, Tianxin Wei, Xuying Ning, Yanjun Zhao, Zhining Liu, Xiao Lin, Yada Zhu, Hendrik Hamann, Jingrui He, and Hanghang Tong. 2026. Mem-gallery: Benchmarking multimodal long-term conversational memory for mllm agents. *Preprint*, arXiv:2601.03515.

Yonatan Geifman and Ran El-Yaniv. 2017. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.

Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V. Chawla, Olaf Wiest, and Xiangliang Zhang. 2024. Large language model based multi-agents: a survey of progress and challenges. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence*, IJCAI '24.

Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. 2024. Ruler: What's the real context size of your long-context language models? *Preprint*, arXiv:2404.06654.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM Comput. Surv.*, 55(12).

Manas Joglekar, Jeremy Chen, Gabriel Wu, Jason Yosinski, Jasmine Wang, Boaz Barak, and Amelia Glaese. 2025. Training llms for honesty via confessions. *Preprint*, arXiv:2512.08093.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. 2025. Why language models hallucinate. *Preprint*, arXiv:2509.04664.

Jiazheng Kang, Mingming Ji, Zhe Zhao, and Ting Bai. 2025. Memory OS of AI agent. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 25961–25970, Suzhou, China. Association for Computational Linguistics.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2023. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. *Preprint*, arXiv:2302.09664.

Zhiyu Li, Chenyang Xi, Chunyu Li, Ding Chen, Boyu Chen, Shichao Song, Simin Niu, Hanyu Wang, Jiawei Yang, Chen Tang, Qingchen Yu, Jihao Zhao, Yezhaohui Wang, Peng Liu, Zehao Lin, Pengyuan Wang, Jiahao Huo, Tianyi Chen, Kai Chen, and 20 others. 2025. Memos: A memory os for ai system. *Preprint*, arXiv:2507.03724.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. 2024. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13851–13870, Bangkok, Thailand. Association for Computational Linguistics.

Potsawee Manakul, Adian Liusie, and Mark Gales. 2023. SelfCheckGPT: Zero-resource black-box hallucination detection for generative large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9004–9017, Singapore. Association for Computational Linguistics.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. 2024. Memgpt: Towards llms as operating systems. *Preprint*, arXiv:2310.08560.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, UIST '23, New York, NY, USA. Association for Computing Machinery.

Victor Quach, Adam Fisch, Tal Schuster, Adam Yala, Jae Ho Sohn, Tommi S. Jaakkola, and Regina Barzilay. 2024. Conformal language modeling. *Preprint*, arXiv:2306.10193.

Ye Shen, Dun Pei, Yiqiu Guo, Junying Wang, Yijin Guo, Zicheng Zhang, Qi Jia, Jun Zhou, and Guangtao Zhai. 2026. Evolmem: A cognitive-driven benchmark for multi-session dialogue memory. *Preprint*, arXiv:2601.03543.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. FEVER: a large-scale dataset for fact extraction and VERification. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 809–819, New Orleans, Louisiana. Association for Computational Linguistics.

Neeraj Varshney, Wenlin Yao, Hongming Zhang, Jianshu Chen, and Dong Yu. 2023. A stitch in time saves nine: Detecting and mitigating hallucinations of llms by validating low-confidence generation. *Preprint*, arXiv:2307.03987.

Yu Wang and Xi Chen. 2025. Mirix: Multi-agent memory system for llm-based agents. *Preprint*, arXiv:2507.07957.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. 2025. Longmemeval: Benchmarking chat assistants on long-term interactive memory. *Preprint*, arXiv:2410.10813.

Zidi Xiong, Yuping Lin, Wenya Xie, Pengfei He, Zirui Liu, Jiliang Tang, Himabindu Lakkaraju, and Zhen Xiang. 2025. How memory management impacts llm agents: An empirical study of experience-following behavior. *Preprint*, arXiv:2505.16067.

Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. 2025. A-mem: Agentic memory for llm agents. *Preprint*, arXiv:2502.12110.

Yasin Abbasi Yadkori, Ilja Kuzborskij, David Stutz, András György, Adam Fisch, Arnaud Doucet, Iuliya Beloshapka, Wei-Hung Weng, Yao-Yuan Yang, Csaba Szepesvári, Ali Taylan Cemgil, and Nenad Tomasev. 2024. Mitigating llm hallucinations via conformal abstention. *Preprint*, arXiv:2405.01563.

Guibin Zhang, Muxin Fu, and Shuicheng Yan. 2025a. Memgen: Weaving generative latent memory for self-evolving agents. *Preprint*, arXiv:2509.24704.

Zhuoran Zhang, Tengyue Wang, Xilin Gong, Yang Shi, Haotian Wang, Di Wang, and Lijie Hu. 2025b. When modalities conflict: How unimodal reasoning uncertainty governs preference dynamics in mllms. *Preprint*, arXiv:2511.02243.

Zijian Zhou, Ao Qu, Zhaoxuan Wu, Sunghwan Kim, Alok Prakash, Daniela Rus, Jinhua Zhao, Bryan Kian Hsiang Low, and Paul Pu Liang. 2025. Mem1: Learning to synergize memory and reasoning for efficient long-horizon agents. *Preprint*, arXiv:2506.15841.

A Extended Related Work

This section expands on related research that is only briefly mentioned in the main paper due to space constraints. We provide additional background on (i) memory architectures and control policies for long-horizon agents, (ii) compressed or synthesized memory representations, (iii) uncertainty and selective-prediction mechanisms, and (iv) benchmark design for long-context and multimodal belief dynamics. These discussions offer supporting context for the reliability- and abstention-focused setting studied in this work.

Memory Architectures And Control Policies. Beyond basic retrieval-and-inject, recent systems emphasize *explicit control* over what is written, how it is indexed, and when it is surfaced to the model. MIRIX proposes typed memory with dedicated modules for writing, retrieval, and routing, enabling finer-grained control over what enters the reasoning context (Wang and Chen, 2025). MemGPT treats the context window as a managed resource and introduces paging between the prompt and external storage (Packer et al., 2024). Related "memory OS" lines of work propose multitier hierarchies and policy-driven memory operations to mitigate context growth and reduce retrieval noise (Kang et al., 2025; Li et al., 2025). These approaches primarily improve *organization* and *access*, but they typically do not provide an explicit epistemic signal that differentiates trustworthy from questionable retrieved content at the level of individual memory items.

Compressed And Synthesized Memory Representations. A complementary direction reduces long-horizon overhead by compressing interaction history or synthesizing latent memory. MEM1 compresses trajectories into compact states intended to support long-horizon reasoning under a constant-memory interface (Zhou et al., 2025). MemGen generates latent memory conditioned on agent state, aiming to preserve salient information while avoiding unbounded growth (Zhang et al., 2025a). A-MEM further organizes memories as evolving note-like networks to support dynamic indexing and updates (Xu et al., 2025). While these representations can improve scalability, they do not directly resolve the *reliability* issue when retrieved items are stale, low-credibility, or mutually inconsistent.

Error Accumulation in Long-horizon Memory Agents. Recent empirical evidence suggests that memory policies can induce *experience-following*, where retrieval noise compounds across turns and systematically steers future behavior (Xiong et al., 2025). This phenomenon motivates reliability-aware mechanisms that act *before* noisy memories enter downstream reasoning, rather than merely mitigating errors at the final response stage.

Uncertainty Signals, Selective Prediction, And Self-reporting. Uncertainty estimation for language generation has been studied from multiple angles. Semantic uncertainty estimates meaning-level variability across alternative generations (Kuhn et al., 2023). SelfCheckGPT uses cross-sample disagreement as a black-box signal for hallucination risk (Manakul et al., 2023). Such signals connect naturally to *selective prediction*, where a model answers only when sufficiently confident: conformal language modeling provides coverage-style guarantees for language outputs (Quach et al., 2024), and conformal abstention explicitly optimizes the decision to refrain under uncertainty (Yadkori et al., 2024). Complementary analyses argue that conventional training and evaluation can incentivize systematic overconfidence and guessing (Kalai et al., 2025). Recent work also explores explicit self-reporting mechanisms (e.g., "confessions") to surface potential mistakes for monitoring and intervention (Joglekar et al., 2025). Most of these approaches operate at the token or response level; our focus differs in that we attach uncertainty to *retrieved memory items* and use it to modulate reasoning and abstention when retrieval is unreliable.

Benchmarks for Long-context Reasoning And Interactive Memory. Long-context benchmarks primarily score correctness under extended inputs. LongBench provides a multilingual, multi-task suite for long-context understanding (Bai et al., 2024), and RULER uses configurable synthetic probes to study effective context use beyond naive retrieval (Hsieh et al., 2024). Memory-centric benchmarks move closer to interactive settings: LoCoMo evaluates very long-term conversational memory over extended dialogs (Maharana et al., 2024), while FEVER evaluates evidence-based verification with a dedicated insufficient-evidence label (Thorne et al., 2018). Recent work has advanced toward more interactive memory evaluation: LongMemEval (Wu et al., 2025) benchmarks multi-session chat assistants with abstention-aware tasks including knowledge updates and information with-

holding, while EvolMem (Shen et al., 2026) probes cognitively motivated memory dimensions—such as declarative and procedural recall—across evolving dialogue sessions. Mem-Gallery (Bei et al., 2026) further extends the scope to multimodal long-term conversational memory for MLLM agents. Despite these advances, none of these benchmarks jointly control (i) *source reliability priors*, (ii) *temporally evolving multi-session evidence*, and (iii) *structured cross-modal contradictions* under an abstention-aware utility.

Multimodal Conflict and Modality Preference Dynamics. Recent analysis suggests that when modalities conflict, the model's preference can be governed by relative unimodal reasoning uncertainty (Zhang et al., 2025b). We adopt a related diagnostic lens but place it in a long-horizon memory-agent setting where reliability evolves over time and conflicts arise from both source priors and multimodal evidence. MMA-Bench is designed to isolate these dynamics with paired text–vision evidence, controlled priors, and CoRe scoring, enabling fine-grained diagnosis of epistemic failures beyond accuracy-only metrics.

B   Results on FEVER Benchmark

Overall Performance and Stability. To rigorously evaluate the effectiveness of our proposed Multimodal Memory Agent framework, we conducted experiments on the FEVER benchmark using three random seeds (42, 922, 2025). For fair comparison, we align the evaluation scope to the first 500 samples for both the baseline and MMA across all seeds. Table 3 summarizes the aggregated performance metrics.

Statistical Robustness. While the baseline achieves a comparable raw accuracy average to MMA ($\approx 59.9\%$), it exhibits significant instability across different seeds. Specifically, the baseline's accuracy fluctuates widely with a high standard deviation ($\pm 2.50\%$). In contrast, MMA demonstrates superior robustness, maintaining a significantly lower variance ($\pm 1.62\%$). This indicates that our confidence-aware mechanism effectively mitigates the stochasticity inherent in retrieval-augmented generation.

Prudence and Calibration Analysis. A key contribution of our framework is enhancing the agent's ability to "know what it does not know." We analyze this through the lens of abstention behavior

(a) **Sensitivity Analysis of** (b) **Risk-Coverage Analysis.**
Abstention Reward (α).

Figure 6: **Selective Prediction Analysis on FEVER.** MMA consistently outperforms the Baseline under abstention-based risk control, achieving higher utility and lower risk across evaluation settings.

and selective scoring.

Improved Precision in Abstention. As shown in the detailed breakdown, MMA adopts a more prudent strategy, abstaining on average 226.3 times per 500 samples, compared to 221.0 for the baseline. Crucially, this conservatism is well-calibrated: MMA correctly identifies "Not Enough Info" (NEI) cases more frequently than the baseline (Average Correct Abstain: 103.7 vs. 100.7). This suggests that MMA is not merely silent, but selectively silent when information is truly insufficient.

Sensitivity to Abstention Reward (α). To further quantify the utility of our model in risk-sensitive scenarios, we evaluated the Selective Score with varying abstention reward parameters (α). As illustrated in Figure 6a, at the starting point ($\alpha = 0$) where no credit is given for abstention, both models exhibit nearly identical raw accuracy ($\approx 59.9\%$). However, as α increases—simulating scenarios where safety is prioritized—the MMA curve (red) consistently rises above the baseline (blue). Notably, the error band for MMA is visibly narrower than that of the baseline, confirming that our method consistently delivers higher utility with lower variance.

Risk-Coverage Trade-off. We further visualize the relationship between the model's willingness to answer (Coverage) and the error rate of those answers (Risk) in Figure 6b. The MMA data points (red) cluster towards the bottom-left quadrant relative to the baseline (blue), indicating lower coverage but simultaneously lower risk. By filtering out low-confidence retrieval results through our consensus mechanism, MMA sacrifices a small portion of coverage to ensure that the provided answers maintain a higher standard of correctness. This trade-off is highly desirable for trusted agents, where hallucinations are costly.

Performance on Long-Context Text Benchmarks. To validate robustness in non-adversarial settings, we also evaluated MMA on the LoCoMo benchmark. Results indicate a distinct trade-off driven by information sparsity: while the Full Model prioritizes prudence (lower coverage), the 'st' variant (Source + Time) effectively balances safety and retrieval, achieving the highest Actionable Accuracy (79.64%) and Utility (883.6), slightly surpassing the baseline. This demonstrates the framework's adaptability to varying density contexts. Comprehensive results are presented in Appendix C.

Ablation Analysis on FEVER. We evaluated the variants on the FEVER dataset ($N = 500$) across three random seeds. The comprehensive results are presented in Table 6 and Figure 7.

Mode	Components	Raw Acc. (%) (↑)	Act. Acc. (%) (↑)	Correct Abstain (↑)	Wrong Abstain (↓)
MMA (Ours)	$S + T + C_{\text{con}}$	59.93 ± 1.62	$71.61 \pm \mathbf{0.43}$	103.7 ± 4.7	122.6 ± 11.2
tc (w/o Source)	$T + C_{\text{con}}$	$\mathbf{60.47} \pm 1.33$	71.61 ± 2.54	102.3 ± 12.6	117.7 ± 20.6
cs (w/o Time)	$S + C_{\text{con}}$	59.00 ± 2.27	68.96 ± 2.35	95.0 ± 13.2	$\mathbf{114.0} \pm 32.1$
st (w/o Consen.)	$S + T$	58.93 ± 3.48	$\mathbf{72.05} \pm 2.34$	$\mathbf{105.7} \pm 16.1$	131.0 ± 36.4

Table 6: **Ablation results on FEVER ($N = 500$, Seeds = 3).** Act. Acc. (Actionable Accuracy) denotes the precision of non-abstained responses (Mean ± Std). Notably, while **MMA** shares a similar mean accuracy with other variants, it achieves significantly lower variance ($\sigma = 0.43$), demonstrating superior stability compared to **tc** (± 2.54) and **st** (± 2.34).

Impact of Temporal Decay (T): Enabling Prudence. The capability to "know what you don't know" is critical for reliable agents. As shown in Table 6, the removal of the temporal module (Model 'cs') results in the lowest number of *Correct Abstentions* (95.0) and the lowest *Actionable Accuracy* (68.96%). Figure 7b further illustrates that 'cs' underperforms significantly as the reward for safe abstention (α) increases. This suggests that without temporal awareness, the agent fails to identify outdated information, leading to overconfident hallucinations rather than prudent refusals.

Impact of Network Consensus (C_{con}): Ensuring Stability. While the 'st' variant (w/o Consensus) achieves a high mean Actionable Accuracy (72.05%), it suffers from severe instability ($\sigma \approx 2.34\%$) and excessive conservatism (highest Wrong Abstains: 131.0). In stark contrast, the Full Model (MMA) achieves a comparable Actionable Accuracy (71.61%) but with a remarkably low standard deviation of $\pm 0.43\%$. As visualized in Figure 7a, the inclusion of our conflict-aware consensus mechanism effectively smooths out retrieval noise, ensuring consistent and reproducible behavior across different initializations.

Impact of Source Reliability (S). Interestingly, Mode 'tc' (w/o Source) achieves the highest raw accuracy on FEVER. We attribute this to the homogeneity of the FEVER dataset (Wikipedia-based), where source credibility is uniformly high. However, the Source module becomes indispensable in adversarial scenarios with mixed reliability.

The Full Model (MMA) achieves the optimal trade-off. It avoids the "blind guessing" of 'cs' and the "erratic conservatism" of 'st', providing a stable, prudent, and trustworthy solution for fact verification.

C Results on LoCoMo Benchmark

We further evaluated our framework on the LoCoMo benchmark, which represents a distinct challenge: long-term conversational history with sparse information density and low adversarial conflict. We compare our Full Model (MMA) against the Baseline (MIRIX) across various reasoning dimensions. The comprehensive results are detailed in Table 7 and visualized in Figure 8.

Performance Overview. As shown in Table 7, the Baseline (MIRIX) achieves a higher Overall Accuracy (77.37%) and Utility Score (573.5) compared to MMA (72.31% / 488.0). This performance gap is primarily driven by the Baseline's aggressive retrieval strategy (Coverage 97.73%), which is advantageous in non-adversarial settings where "hallucinating" an answer often hits the correct target by chance. In contrast, MMA adopts a significantly more prudent strategy, triggering nearly $3\times$ more abstentions (98 vs. 35) due to its rigorous confidence filtering.

Category-wise Analysis. In the Temporal dimension, MMA achieves competitive performance (77.05%) compared to the Baseline (78.00%), validating the effectiveness of our Temporal Decay module in tracking timeline shifts. However, in Multi-Hop reasoning, MMA lags behind (62.31% vs. 76.01%). This suggests that the Conflict-Aware Consensus module, while robust against explicit contradictions (as seen in FEVER), may overly penalize weak but valid multi-hop links in sparse narrative contexts, leading to conservative "misses" rather than errors.

Safety and Robustness. Although MMA sacrifices some raw accuracy for prudence, its modular design offers flexibility. As shown in Figure 8a, the 'st' variant (a configuration of MMA without

| (a) **Stability Analysis.** | (b) **Prudence Analysis.** | (c) **Strategy Analysis.** |

Figure 7: **Ablation Study Results on FEVER.** We compare the Full Model (MMA) against variants without Consensus ('st'), without Time ('cs'), and without Source ('tc'). (a) Shows that removing Consensus drastically increases variance. (b) Shows that MMA maintains high utility under strict prudence requirements (high α). (c) Visualizes the trade-off between sensitivity and conservativeness.

Method	Reasoning Categories (LLM Score)				Overall Metrics		Reliability	Utility ($\uparrow$)
	Single-Hop ($\uparrow$)	Multi-Hop ($\uparrow$)	Open-Domain ($\uparrow$)	Temporal ($\uparrow$)	Accuracy ($\uparrow$)	Wrong Ans. ($\downarrow$)	Act. Acc. ($\uparrow$)	($\lambda = 1, r = 0.2$)
MIRIX (Baseline)	**80.14**	**76.01**	**67.71**	78.00	**77.37**	317	78.96%	880.0
MMA (Ours)	73.76	62.31	59.38	77.05	72.31	335	76.80%	793.6
Variant 'st'	79.08	67.91	61.46	**79.55**	75.94	**298**	**79.64%**	**883.6**

Table 7: **Main Results on LoCoMo.** Breakdowns of LLM Scores across reasoning dimensions ($N = 1542$). While the Baseline excels in raw accuracy, our 'st' variant achieves the highest **Actionable Accuracy (79.64%)** and **Utility**, demonstrating superior reliability in safety-critical retrieval tasks.

consensus) successfully suppresses hallucinations, achieving the lowest wrong answer count and surpassing the Baseline in Utility (609.0). This highlights that while the full consensus mechanism is conservative, the core Source and Time components are highly effective for safety-critical long-context retrieval.

Ablation Analysis on LoCoMo. Compared to the fact-centric nature of FEVER, the LoCoMo benchmark represents a distinct challenge: long-term conversational history with sparse information density. We evaluate how the removal of specific confidence components affects agent behavior in this non-adversarial but noise-heavy environment. The ablation results are summarized in Table 8 and the sensitivity trends are shown in Figure 9.

Mode	Components	Utility ($\uparrow$)	Wrong Ans. ($\downarrow$)	Abstain Count ($\uparrow$)	Act. Acc. ($\uparrow$)
MMA (Full)	$S + T + C_{con}$	488.0	335	98	76.80%
st (w/o Consen.)	$S + T$	**609.0**	**298**	78	**79.64%**
cs (w/o Time)	$S + C_{con}$	480.5	335	**113**	76.56%
tc (w/o Source)	$T + C_{con}$	471.5	344	77	76.52%

Table 8: Ablation results on LoCoMo ($N = 1542$). **Utility** is computed with $\lambda = 2.0, r = 0.5$. **Wrong Ans.** denotes hallucinations (Lower is Better). The 'st' variant achieves the best safety profile.

Impact of Network Consensus (C_{con}): Contrasting with the FEVER results, removing the consensus module (Mode 'st') significantly improves performance on LoCoMo, achieving the highest Utility (609.0) and the lowest hallucination rate (298 Wrong Answers). We attribute this to the "Sparsity Paradox": in long-term chit-chat, seman-

tic neighbors retrieved by RAG are often thematically related (e.g., discussing dinner) but factually irrelevant to the specific query. Including these neighbors in a consensus calculation introduces noise rather than signal, diluting the confidence of correct retrievals. Thus, for sparse, non-adversarial tasks, a streamlined $S + T$ architecture is more effective.

Impact of Source Reliability (S): The removal of the Source module (Mode 'tc') results in the highest number of Wrong Answers (344) and the lowest Utility (471.5). This underscores the critical role of $S(M_i)$. In multi-turn dialogues with fixed personas, identifying and trusting reliable speakers is a primary mechanism for filtering out noise. Without this prior, the agent becomes vulnerable to misleading context, increasing the risk of hallucination. This finding validates our hypothesis that source credibility acts as a critical filter in persona-driven dialogues.

Impact of Temporal Decay (T): The variant without time decay (Mode 'cs') exhibits the highest number of Abstentions (113) but fails to translate this prudence into higher utility. Without the temporal dimension, the agent cannot distinguish between outdated facts and current truths, leading to a state of "confused conservatism"—abstaining because it perceives valid updates as contradictions. This confirms that Time is essential for resolving longitudinal inconsistencies.

The ablation study reveals that while the Full

(a) **Utility vs. Safety.**   (b) **Penalty Sensitivity (λ).**   (c) **Reward Sensitivity (r).**

Figure 8: **Quantitative Analysis on LoCoMo.** While MMA focuses on prudence, its 'st' configuration demonstrates robust utility advantages over the Baseline in high-stakes settings.

(a) **Penalty Sensitivity (λ).**   (b) **Reward Sensitivity (r).**

Figure 9: **Ablation Sensitivity on LoCoMo.** Removing the Consensus module ('st') actually improves robustness in this specific domain, while removing Source ('tc') or Time ('cs') degrades performance.

MMA model is optimal for dense, adversarial verification (FEVER), the 'st' configuration is superior for sparse, long-context retrieval (LoCoMo). This demonstrates the adaptability of our framework: the components can be reconfigured to match the information density of the target domain.

D Results on MMA-bench

D.1 Analysis of Foundation Models

We evaluated two representative models, GPT-4.1-mini and Qwen3-VL-Plus, on MMA-Bench. These models were granted full context access (processing the entire dialog history at once) to isolate their reasoning capabilities from retrieval limitations. Despite this advantage, our multi-dimensional probes reveal significant deficits in their belief dynamics.

Gap Between Perception and Arbitration. As indicated in the breakdown of core metrics, both models demonstrate strong fundamental capabilities, achieving strong performance in fact retrieval and adversarial distraction tasks. This suggests that they effectively comprehend the long-context narrative and filter out irrelevant noise (Phase 2). However, their performance drops significantly in the 3-step probe, particularly in the verdict accuracy of conflict scenarios (ranging from 63% to 78%).

This discrepancy highlights a critical cognitive gap: while the models possess sufficient perception to identify the details, they lack the epistemic arbitration capability to resolve conflicts between reliable priors and contradictory visual evidence. They effectively "read" the text but fail to "judge" the truth.

Modality Preference and Visual Placebo Effect. We utilized the modality signal alignment metric to diagnose how visual inputs influence decision-making. The results expose divergent behaviors between the two models.

Type B (Inversion) scenarios reveal strong authority bias. Both models struggle to consistently prioritize objective visual evidence over textual statements from a historically reliable source (User A). Qwen3-VL-Plus exhibits a stronger tendency towards visual grounding (82.4% alignment with visual signals) compared to GPT-4.1-mini (64.7%), reflecting its architectural strength in vision. However, a significant portion of errors stems from the models hallucinating a justification to align the visual evidence with the textual prior.

In indeterminate scenarios (Type C and D), we observe a phenomenon we term the visual placebo effect. For GPT-4.1-mini, performance in Type D (Unknowable) scenarios degrades drastically when switching from text mode (oracle captions) to vi-

Model	Mode	Overall Metrics			Scenario-Specific Analysis	
		Core Acc. (↑)	Verdict Acc. (↑)	CoRe Score (↑)	Type B Acc. (↑)	Type D Score (↑)
GPT-4.1-mini	Text (Oracle)	85.26%	**77.78%**	**0.59**	76.47%	**0.85**
	Vision (Raw)	80.74%	73.33%	0.51	64.71%	0.23
Qwen3-VL-Plus	Text (Oracle)	88.05%	65.56%	0.32	**88.24%**	-0.69
	Vision (Raw)	**88.98%**	63.33%	0.28	82.35%	-0.69

Table 9: **Cognitive dynamics of foundation models on MMA-Bench. Core Acc.** measures basic reading comprehension. **CoRe Score** (Risk-Adjusted) reflects epistemic calibration. **Type B Acc.** indicates success in Reliability Inversion (overcoming authority bias). **Type D Score** reflects prudence in unknowable scenarios. Note the significant drop in Type D score for GPT-4.1-mini when switching to Vision mode, illustrating the *Visual Placebo Effect*.

(a) **The Visual Placebo Effect.**

(b) **The Confidence-Competence Gap.**

Figure 10: **Cognitive Dynamics of Foundation Models on MMA-Bench.** We compare GPT-4.1-mini and Qwen3-VL-Plus across Text (Oracle) and Vision (Raw) modes. (a) Reveals how visual modalities can act as distractors in noise scenarios. (b) Highlights the disconnect between reading comprehension (Core Acc) and epistemic prudence (CoRe Score).

sion mode (raw images), with the CoRe score dropping from 0.85 to 0.23. This suggests that the presence of an image, even if irrelevant or ambiguous, creates an illusion of information sufficiency, prompting the model to fabricate definitive answers rather than maintain prudence. Conversely, Qwen3-VL-Plus exhibits extreme overconfidence in these noise scenarios across both modes, frequently placing high wagers on hallucinated verdicts, indicating a fundamental lack of epistemic calibration.

Fragility of Self-Correction. Our analysis of the confession mechanism (Step 3) reveals pathological instability in reasoning. Although both models achieve high self-correction rates numerically, qualitative inspection shows that over 50 cases involved the models flipping from a correct verdict to an incorrect one during the reflection phase.

This suggests that verdict changes are not driven by genuine re-evaluation. Rather, models revise their answers because the reflection prompt implicitly signals doubt, regardless of whether a reasoning error has actually occurred. Furthermore, we observed a prevalence of logic collapse, where models would place a high wager on a verdict in Step 2, only to immediately confess it was wrong in Step 3. This disconnect between the acting sys-

tem (wagering) and the thinking system (reflecting) underscores the immaturity of current models in maintaining a coherent belief state.

D.2 Ablation on MMA-Bench

To dissect the specific mechanisms driving the cognitive behaviors observed in Subsection 4.2, we evaluated three ablated variants against the Full Model ($S + T + C_{con}$) on MMA-Bench. The results, summarized in Table 5 and visualized in Figure 11, isolate the distinct contributions of each component.

Impact of Source Reliability (S): Comparison with Mode 'tc' (w/o Source) reveals that source credibility is a prerequisite for agency. Without the source module, the agent exhibits symptoms of cognitive paralysis. We demonstrate this by contrasting performance across logic types: while Mode 'tc' achieves superficially perfect scores in indeterminate scenarios (Type D: 1.0, Type C: 96.7%), it paradoxically yields 0.0% accuracy in all deterministic scenarios (Type A and Type B) (Table 5). This distinct data pattern, visualized in Figure 11a, indicates that the agent is not exercising prudence but is mechanically incapable of forming positive verdicts. Lacking a prior trust distribution, it de-

(a) **Cognitive Paralysis (Accuracy Analysis).**   (b) **Visual Placebo Mitigation (CoRe Score Analysis).**

Figure 11: **Mechanism Ablation on MMA-Bench (Vision Mode).** We isolate the failure modes: (a) **Accuracy metrics** reveal that Source (S) and Time (T) are prerequisites for agency, as their absence leads to paralysis (0% accuracy in known facts); (b) **CoRe Scores** demonstrate that Consensus (C_{con}) is essential to buffer against the **Visual Placebo Effect** in indeterminate queries.

faults to "Unknown" for every query. Thus, unlike MMA which demonstrates functional discrimination (Vision Type A: 50.0%), the success of 'tc' in indeterminate cases is merely a statistical artifact of system inaction.

Impact of Network Consensus (C_{con}): Mode 'st' (w/o Consensus) highlights the role of consensus in mitigating the visual placebo effect. The results reveal an intriguing trade-off: without the consensus constraint, 'st' is more aggressive in accepting visual evidence, actually outperforming MMA in Type B Inversion scenarios (52.9% vs. 41.2%). However, this aggression proves fatal in indeterminate contexts. In Vision Mode, its Type D score collapses catastrophically to -0.69, indicating that isolated visual signals override textual caution (Figure 11b). In contrast, the Full Model employs C_{con} to validate visual inputs against the semantic neighborhood. While this conservatism slightly dampens Type B performance, it significantly buffers the Type D drop (Score: -0.38), providing a critical safety layer against hallucination.

Impact of Temporal Decay (T): Mode 'cs' (w/o Time) demonstrates a critical failure in stability when shifting modalities. We observe that while 'cs' performs comparably to MMA in Text Mode (Type A Acc: 40.0%), its capability degrades significantly in Vision Mode, dropping to 0.0% in Type A scenarios (see Table 5). This distinct drop suggests that, once temporal decay is removed, the historical noise that remains tolerable within the confines of textual input accumulates without bound; when such accumulated noise is further compounded by high-dimensional visual features, the signal-to-noise ratio is driven below the decision threshold. MMA utilizing T maintains con-

sistent performance across modes (Vision Type A: $\sim 50\%$), proving that temporal awareness is essential for robustness in high-entropy multimodal environments.