JustLogic: A Comprehensive Benchmark for Evaluating Deductive Reasoning in LLMs

Abstract

Logical reasoning is a critical component of Large Language Models (LLMs), and substantial research efforts in recent years have aimed to enhance their deductive reasoning abilities. However, existing deductive reasoning benchmarks suffer from significant constraints that restrict their utility, i.e., the lack of task complexity, the presence of prior knowledge as a confounder, and superficial error analysis. To address these deficiencies, we introduce JustLogic, a synthetically generated benchmark designed for rigorous evaluation of LLMs. JustLogic is (i) highly complex, capable of generating a diverse range of linguistic patterns, vocabulary, and argument structures; (ii) prior knowledge independent, eliminating the advantage of models possessing prior knowledge and ensuring that only deductive reasoning is used to answer questions; and (iii) capable of in-depth error analysis on the heterogeneous effects of reasoning depth and argument form on model accuracy. Our experimental results on JustLogic reveal that (i) state-of-the-art (SOTA) reasoning LLMs perform on par or better than the human average but significantly worse than the human ceiling, and (ii) SOTA non-reasoning models still underperform the human average. All code and data are available at https://anonymous.4open.science/r/JustLogic

1 Introduction

Deductive reasoning is a crucial capability for large language models (LLMs). It refers to the process of creating logically valid arguments, where conclusions necessarily follow from the premises, i.e., if an argument's premises are true, the conclusion must also be true. Recent state-of-the-art (SOTA) LLMs (Achiam et al., 2023; Dubey et al., 2024; Jiang et al., 2023) have exhibited outstanding performance and consistent improvement across various reasoning benchmarks, including HelloSwag (Zellers et al., 2019), ARC Challenge (Clark et al., 2018) and WinoGrande (Sakaguchi et al., 2021). However, we argue that the existing benchmarks are insufficient and often ineffective for evaluating LLMs' true deductive reasoning capabilities.

We identify three major problems with the existing benchmarks. **First**, they lack complexity, specifically (i) natural language complexity, i.e., how arguments are linguistically expressed, and (ii) argument complexity, i.e., the structure of the argument itself. Manually curated datasets, such as FOLIO (Han et al., 2022) and LogiQA 2.0 (Liu et al., 2020; 2023a) exhibit high natural language complexity but low argument complexity, while synthetic datasets like CLUTRR (Sinha et al., 2019) and ProofWriter (Tafjord et al., 2020) exhibit the opposite. Simplicity in either dimension makes these benchmarks prone to overfitting and memorization, thus allowing models to perform well despite underlying weaknesses in logical reasoning. A more detailed analysis can be found in Section 3.4. **Second**, existing benchmarks often fail to test deductive reasoning in isolation, as models can benefit from prior knowledge. To empirically validate this claim, we apply a prior knowledge independence test, which measures the influence of prior knowledge on reasoning benchmarks. Section 5.1 shows how prior knowledge can substantially increase accuracy, even in logical reasoning datasets, e.g., FOLIO and LogiQA 2.0. Thus, high accuracy may not reflect strong reasoning capabilities. **Third**, many existing benchmarks provide superficial error analysis, leaving key questions unanswered: At what reasoning depth does the model start to fail? How does the model compare to humans at different argument depths? Which argument forms is the model particularly weak at? These insights are essential for understanding

the depth and robustness of a model's deductive reasoning. Section 5.3 demonstrates the importance and usefulness of comprehensive error analysis.

Paragraph:

- It is a fact that either relics are artifacts or dogs are capable of barking. $[p \lor q]$
- If relics are artifacts, then fertilizers contain phosphorus. $[p \rightarrow r]$
- Assuming dogs are capable of barking, we know that fertilizers contain phosphorus. $[q \rightarrow r]$

Statement: Fertilizers contain phosphorus. $[r]$
Question: Is the statement true, false, or uncertain?
Answer: True

Figure 1: Example of a question adapted using JustLogic's dataset construction algorithm. Note that the statements are *intentionally* factually inaccurate, which we explain and justify in Section 3.2. Formal notations are included for illustrative purposes and are not provided to models.

Due to these issues, LLMs' deductive reasoning abilities remain ambiguous. In response to the critical need for a reliable benchmark to support ongoing research efforts, we present JustLogic, a novel natural language deductive reasoning benchmark. The task is to determine whether a given statement is true, false, or uncertain, using only the given premises, which are assumed to be true. An example is shown in Figure 1.

JustLogic's construction ensures it is (i) complex, (ii) prior knowledge independent, and (iii) capable of in-depth error analysis. **First**, to achieve high argument and natural language complexity, JustLogic is code-generated rather than manually curated. This allows the generation of a theoretically infinite number of unique argument structures. Natural language sentences are then drawn from GenericsKB-Best (Bhakthavatsalam et al., 2020), a database of 1M+ unique real-world sentences, and inserted into the argument structures, introducing high natural language complexity. **Second**, since sentences are randomly sampled from the entire GenericsKB-Best dataset, the generated arguments generally do not align with real-world knowledge, thereby eliminating prior knowledge as a confounder. **Finally**, in-depth error analysis is enabled by the programmatic generation process, which enables the inspection of each question's properties, such as reasoning depth and argument form, to investigate their impact on model performance. A comparison between JustLogic and four similar logical reasoning benchmarks (CLUTRR, ProofWriter, LogiQA 2.0, and FOLIO) is presented in Table 1, with further details on dataset construction provided in Section 3.

Using JustLogic, we conducted comprehensive experiments to evaluate the deductive reasoning capabilities of current LLMs. First, our novel prior knowledge independence test demonstrated that prior knowledge enables LLMs to bypass deductive reasoning on existing datasets, resulting in artificially high accuracies. This is not observed in JustLogic. Second, we benchmarked the performance of SOTA LLMs and human participants using JustLogic. Most SOTA LLMs performed significantly lower than the average human accuracy (73.0%). GPT-5.5 achieved the highest accuracy (88.8%), followed by Gemini 2.5 Flash (82.0%) and DeepSeek R1 (80.9%), with all three surpassing the human average but still falling short of the human ceiling (100.0%). Finally, enabled by JustLogic's code-generated nature, our thorough error analysis examined the heterogeneous impact of argument structure and reasoning depth on model performance. These experiments show that the JustLogic benchmark is a reliable test of deductive reasoning and reveals significant room for improvement in LLMs.

In summary, our contributions are threefold. First, we evaluate the limitations of existing benchmarks. Second, we introduce the JustLogic benchmark, a synthetic dataset to evaluate deductive reasoning, that addresses the aforementioned limitations. Third, our experiments using JustLogic demonstrate that most SOTA models perform significantly worse than humans. We posit that the deductive reasoning capabilities of LLMs still have significant room for improvement, and hope that the JustLogic benchmark will assist researchers in designing and evaluating LLMs.

Table 1: Comparison of JustLogic with other deductive reasoning datasets. The symbol $\sim$ suggests the feature is present but to a limited extent.

	High NL Complexity	High Arg. Complexity	Prior Knowledge Independence	In-Depth Error Analysis
CLUTRR	✗	✓	✓	✓
ProofWriter	✗	✓	✓	$\sim$
LogiQA 2.0	✓	✗	✗	$\sim$
FOLIO	✓	✗	✗	$\sim$
JustLogic	✓	✓	✓	✓

2 Related Work

2.1 Existing reasoning datasets for Large Language Models

Reasoning benchmarks are a vital part of LLM evaluation. Some benchmarks measure deductive reasoning in conjunction with natural language inference (NLI), inductive reasoning, and commonsense knowledge: HellaSwag (Zellers et al., 2019) tasks machines to select the most likely follow-up of an event description, WinoGrande (Sakaguchi et al., 2021) is a pronoun resolution task, and MuSR (Sprague et al., 2023) tasks machines to solve fictional problems, such as murder mysteries. Other benchmarks measure reasoning on domain knowledge: AI2 Reasoning Challenge (ARC) (Yadav et al., 2019) contains grade-school science questions, while Massive Multitask Language Understanding (MMLU) (Hendrycks et al., 2020) contains questions across 57 subjects in STEM, humanities, and more. Finally, math-specific benchmarks include GSM-8K (Cobbe et al., 2021) and DROP (Dua et al., 2019).

The aforementioned benchmarks explicitly evaluate skills beyond reasoning and do not specifically define the type of reasoning involved, e.g. inductive, deductive, and analogical. As such, benchmarks that solely test for deductive reasoning have seen a considerable increase in interest. They can be classified into two broad categories: synthetic and manually curated. Synthetically-generated datasets include (i) CLUTRR (Sinha et al., 2019), where a machine must infer the relationship of two family members based on stories, (ii) ProofWriter (Tafjord et al., 2020), where a machine must deduce a statement's truth value based on a set of facts and rules, and (iii) ProntoQA-OOD (Saparov et al., 2024), where a machine must prove a statement based on a set of facts. Manually curated datasets include (i) LogiQA 2.0 (Liu et al., 2023a), containing manually-translated logical reasoning questions from the Chinese Civil Service Exam, (ii) FOLIO (Han et al., 2022), containing questions with manually-annotated content using Wikipedia pages, and (iii) ReClor (Yu et al., 2020), containing reading comprehension questions from GMAT and LSAT.

As discussed earlier, synthetic datasets are prior knowledge independent and exhibit high argument and low natural language complexity; manually curated datasets are the opposite. JustLogic, being synthetic, contains all its advantages while offering the natural language complexity of manually curated datasets, which we further explained in Sections 3.4 and 5.1.

2.2 Reasoning in Large Language Models

As LLMs continue to increase in size, their performance on various reasoning-related benchmarks has improved dramatically. For example, in 2024, Gemini Ultra (Team et al., 2023) achieved 90.0% on MMLU when the SOTA model in 2020, UnifiedQA 11B (Khashabi et al., 2020), achieved a mere 48.9%. In 2023, GPT-4 achieved 96.4% on ARC when the SOTA model in 2020, GPT-3 (Brown, 2020), achieved 53.2%.

The advent of prompting techniques played an important role in developing LLMs' reasoning abilities. In-context learning (Dong et al., 2022) provides LLMs with instructions and examples in the input prompt to guide its response. Chain-of-thought prompting (Wei et al., 2022) prompts LLMs to generate a series of intermediate reasoning steps before arriving at the final answer. Self-consistency decoding (Wang et al., 2022) chooses the most consistent answer after sampling multiple chain-of-thought outputs. Least-to-most

prompting (Zhou et al., 2022) decomposes a complex problem into simpler subproblems, which are then solved sequentially.

As mentioned above, LLMs are conventionally tested on datasets that combine reasoning with other skills. Moreover, existing logical reasoning-specific datasets possess major limitations that call into question the reliability of their evaluations. In response, JustLogic aims to robustly and accurately evaluate the deductive reasoning abilities of LLMs.

3 Dataset Construction

JustLogic is a programmatically generated dataset designed to evaluate a model's ability of deductive reasoning, specifically its capability to form logically valid arguments. A logically valid argument is one where the conclusion necessarily follows from the premise(s); in other words, given the premises are true, the conclusion must also be true.

In order to test this, JustLogic presents a model with a paragraph consisting of premises, followed by a query statement. Based solely on the premises and assuming they are all true, the model needs to determine whether the query statement is true, false, or uncertain. In line with the open-world assumption, the "Uncertain" answer refers to cases where the premises neither support nor contradict the query statement.

Figure 2: A step-by-step example of how an instance with a reasoning depth of 2 is constructed.

The following outlines the process for generating each instance in the dataset, which is exemplified by Figure 2.

1. Step 1: Generate an argument structure.
2. Step 2: Add natural language statements to the argument structure.
3. Step 3: Generate a query statement.

3.1 Step 1: Generate argument structure

Argument structures are composed of one or more valid argument forms, derived from propositional logic; argument forms are made up of a series of logical forms, defined as symbolic representations of statements. Specifically, the argument forms in our dataset are constructed with the following four logical forms: basic (x), negation $(\neg x)$, conditional $(x \rightarrow y)$, and disjunction $(x \vee y)$. While there are theoretically infinitely many possible argument forms, they can be constructed with simpler ones. We therefore explicitly define the seven fundamental forms (Johnson, 2006): modus ponens (MP), modus tollens (MT), hypothetical syllogism

(HS), disjunctive syllogism (DS), reductio ad absurdum (RAA), constructive dilemma (CD), and disjunctive elimination (DE). Table 6 in Appendix A provides their formal notations and examples.

The generation process involves several random sampling steps with the following distributions: logical form conclusions are sampled with probabilities 0.8 (Statement), 0.1 (Conditional), and 0.1 (Disjunction); negation is applied to the conclusion with probability 0.3; and argument forms are sampled uniformly at random from the set of applicable forms for each conclusion type. The algorithm to create an argument structure (Appendix B) accepts the argument depth as input. It first generates a random conclusion and an argument form to support it, which in Figure 2 is c and disjunctive syllogism. If the intended depth has not been reached, one or more premises will become subconclusions, which are supported by new, randomly generated argument forms. In Figure 2, this is exemplified by $\neg b$ becoming a subconclusion, supported by a modus ponens argument. This process continues until the desired depth is achieved.

Specifically, reasoning depth is defined as the total number of argument forms in the proof structure, rather than the length of the longest inference chain. This definition captures the overall structural complexity of the argument, as each additional argument form introduces new premises and logical dependencies that the model must process. While a depth-d instance may contain inference chains of varying lengths, the total number of argument forms provides a comprehensive measure of the reasoning burden imposed on the model.

3.2 Step 2: Adding natural language

Next, the symbolic statements are converted into natural language. Each statement consists of one or more logical forms, *i.e.* variable, negation, conditional, and disjunction. In natural language, these forms can be expressed in a variety of ways. For example, a conditional can be expressed as both "If x, then y." and "Given that x, y is true.", where variables x and y are simple propositions. To emulate the diversity of natural language, a list of expressions for each logical form is created using human feedback, and potentially aided by LLMs. Table 2 shows the formal notation of each form, alongside a sample expression and the total number of unique expressions. The variable(s) within each expression are ultimately replaced by randomly selected generic, real-world sentences from GenericsKB-Best (Bhakthavatsalam et al., 2020). The open-source GenericsKB-Best dataset is chosen for its vast collection of simple propositions (1,020,868 sentences) without conditionals, disjunctions, etc. A complete example can be found in Step 2 of Figure 2.

Table 2: Expressions of logical forms.

	Formal Notation	Sample Expression	No. of Expr.
Basic	x	The claim that x holds true.	16
Negation	$\neg x$	The claim that x does not reflect reality.	15
Conditional	$x \rightarrow y$	Once we know that x, we also know that y.	11
Disjunction	$x \vee y$	It is a fact that either x or y.	8

Notably, as shown in Figure 2, the statements are generally factually inaccurate despite being drawn from real-world data. This is intentional. Real-world propositions allow us to generate sentences with diverse grammatical structures that closely emulate human-written arguments. However, factually accurate arguments enable models to bypass deductive reasoning with their prior real-world knowledge, which is experimentally demonstrated in Section 5.1. By using real-world yet factually inaccurate statements, we combine realism and prior knowledge independence.

There are potential concerns that factually inaccurate statements and "unnatural" synthetic language may confuse models and lead to artificially low performance. Appendix F.2 and F.3 empirically refute these concerns.

3.3 Step 3: Generate query statement

The LLM's task is to determine whether the given query statement is true, false, or uncertain based on the premises provided. Using Figure 2 as an example, if we assign the query statement to be the negation of

the conclusion, i.e. "It is not true that Japan is in Asia", then the answer is false. If the query statement is the same as the conclusion, then the answer is true. If the query statement is unrelated to the premises, then the answer is uncertain. To generate Uncertain instances, a sentence sharing the same topic term as the conclusion is sampled from GenericsKB-Best, while being distinct from the conclusion itself and all other sentences used in the argument structure. Since the sampled sentence introduces a new proposition not present in any premise, it is logically independent of the argument by construction. In cases where no same-term sentence is available, a sentence is sampled uniformly at random from the full GenericsKB-Best dataset, which similarly introduces a new proposition unrelated to the argument.

3.4 Dataset Complexity

In the context of deductive reasoning datasets, complexity is defined as the variety and comprehensiveness of instances. It can be further divided into two dimensions: natural language complexity and argument complexity. In this section, we highlight the significance of both aspects and how JustLogic compares against other logical reasoning datasets.

Table 3: Statistics of dataset complexity.

| | Natural Language | | Argument | |
	Reading Difficulty ↑	Vocab. (Domains)	Reasoning Depth	Arg. Structures
CLUTRR	6.67	1396 (1)	$1 - \infty$	∞
ProofWriter	0.96	101 ($\times$)	$1 - \infty$	∞
LogiQA 2.0	17.10	10004 (>10)	$\times$	$\times$
FOLIO	18.75	4351 (>10)	1 - 7	76
JustLogic	**20.55**	**10557 (>10)**	**$1 - \infty$**	**∞**

Natural language complexity. Human language is complex. Statements and arguments of similar meanings can be presented in a variety of ways. Therefore, it is insufficient for models to reason solely with symbols, *e.g.* x and y, and basic natural language sentences, *e.g.* "Some birds are yellow."; they must be capable of reasoning with real-world vocabulary and diverse sentence structures to be useful in practical contexts.

We measure natural language complexity with (i) reading difficulty, as measured by the Flesch-Kincaid Grade Level test (Kincaid, 1975), and (ii) lexical diversity, as measured by vocabulary & domain size. For (i), the score is presented as a U.S. grade level; the higher the score, the harder the text is to read. Scores greater than 12 should be used to compare the relative difficulty between benchmarks, with higher scores indicating relatively greater textual complexity. A domain is defined as any topic of interest, such as golf, computers, or traveling; the number of domains is quantified by counting the number of distinct topic categories present in the dataset. For JustLogic, domains are derived from the term 'categories' in GenericsKB-Best, which covers more than 10 broad topic areas. Vocabulary size refers to the number of unique words in the dataset. Given the difficulty of quantitatively capturing linguistic complexity, Appendix C also shows text samples of each benchmark, representative of their complexity.

As shown in Table 3, existing synthetic datasets have low natural language complexity, while human-written datasets, such as FOLIO and LogiQA 2.0, exhibit significantly higher complexity. This is expected since synthetic datasets translate symbols in formal logic into natural language using limited templates of sentence structures and vocabulary lists. For example, in ProofWriter, a typical sentence follows the format "All dogs are (not) red.". The linguistic patterns of human-written datasets, in contrast, are bound only by human creativity. Despite being synthetic, JustLogic, achieves natural language complexity on par with manually curated datasets, due to its comprehensive selection of expressions and the use of GenericsKB-Best as the source of sentences.

Argument complexity. Argument complexity refers to the diversity of argument structures used in the dataset. A sufficiently high argument complexity is important because humans use a range of argument forms to reason, beyond just conditionals and modus ponens. Moreover, a real-world argument is typically composed of multiple argument forms, due to their inherent complexity. A dataset's argument complexity is

evaluated based on (i) the range of reasoning depth and (ii) the number of unique argument structures. The upper limit of both metrics is calculated based on the theoretical maximum without any additional human input, rather than the highest depth used in existing experiments. For example, CLUTRR can generate any number of depths (or relation length in the original paper), despite its experiments only utilizing depths of up to 10; its upper limit of depth is infinite.

Table 3 shows that synthetic datasets, such as CLUTRR, ProofWriter, and JustLogic, excel in this area, as there is no upper limit to their reasoning depth and number of argument structures. Manually curated datasets, in contrast, either lack an explicit concept of reasoning depth and argument structures (e.g. LogiQA 2.0), or have a limited selection of both (e.g. FOLIO). While manual datasets require significant human efforts and investment to expand their complexity, synthetic ones can scale trivially. In summary, JustLogic combines the best of both worlds: the argument complexity of synthetic datasets and the natural language complexity of manually curated ones.

3.5 Future-proofing JustLogic

As the reasoning abilities of LLMs continue to improve, we expect LLMs to solve the existing JustLogic dataset eventually. To maintain JustLogic's relevance, we leverage its synthetic nature to increase complexity with minimal human input. Argument complexity can be adjusted by increasing the (i) range of argument depth (empirically validated in Appendix **??**) and (ii) number of distinct argument forms to >7. Natural language complexity can be adjusted by (i) increasing the number of expressions for each logical form and (ii) integrating more complex knowledge bases than GenericsKB. Importantly, these changes are programmatically achievable with minimal man-hours.

Importantly, JustLogic can also effectively tackle benchmark leakage (Xu et al., 2024), whereby test sets are unintentionally included in LLMs' pertaining data, thus artificially inflating their performance through memorization. Should JustLogic's test set be leaked, a new test set of similar difficulty can be trivially generated, thereby mitigating this problem.

4 Experimental Setup

We first investigate the influence of prior knowledge on evaluating deductive reasoning with JustLogic and other existing benchmarks using our prior knowledge independence test. Next, several SOTA LLMs of various sizes are evaluated using JustLogic. Finally, an in-depth error analysis of the LLMs' results is conducted.

JustLogic contains 7000 instances, equally split amongst reasoning depths ranging from 1 to 7. The test set (15% of all instances) is used for evaluation. Note that the number of instances and range of reasoning depths can be easily adjusted using JustLogic's open-source dataset generation program.

4.1 Prior Knowledge Independence Test

The task for deductive reasoning benchmarks is typically framed as $CQO \rightarrow A$: Given a context C, consisting of n premises ($P = \{p_1, p_2, ..., p_n\}$), a question Q, and m answer options ($O = \{o_1, o_2, ..., o_m\}$), determine the correct answer A. To assess the influence of prior knowledge on determining answer A, the prior knowledge independence test is framed as $QO \rightarrow A$. No context C is provided, and the prompt instructs the LLM to answer the question based on prior knowledge alone. A few-shot prompt with examples is provided to guide the model's response format, but no contextual premises are included. The full prompt is shown in Appendix D.

If prior knowledge is not useful, the LLM should be unable to answer question Q without C, and the accuracy for the prior knowledge independence test should approximate random probability $\frac{1}{m}$. Benchmarks exhibiting such accuracies are deemed prior knowledge independent.

While context ablation has been used in NLP to assess model reliance on input context, we systematically apply it across five deductive reasoning benchmarks to quantify the influence of prior knowledge on benchmark accuracy. While any LLM will be suitable, we use GPT-4 for its extensive prior knowledge. Similar results

are replicated using Llama3-70B in Appendix F.1. The test is conducted on JustLogic and other logical reasoning benchmarks, i.e. CLUTRR, ProofWriter, LogiQA 2.0, and FOLIO.

4.2 Evaluating LLMs' Deductive Reasoning

Our task, as illustrated in Figure 1, follows the conventional formulation: $CQO \rightarrow A$. Question Q is "Is the statement S true, false, or uncertain?"; there are 3 answer options, where $O = \{\text{true}, \text{false}, \text{uncertain}\}$. Prompts begin with a preamble, providing (i) the task instructions, (ii) a list of argument forms in propositional logic, and (iii) the available answer options.

We categorize models into reasoning and non-reasoning types based on their training methodology. Reasoning models are those explicitly trained with chain-of-thought reasoning via reinforcement learning, including DeepSeek R1, GPT-5.5, OpenAI o1, and Gemini 2.5 Flash, while non-reasoning models are standard instruction-tuned models without such training, including GPT-4o and Llama3. We evaluate reasoning and non-reasoning models of various sizes: Llama3-8B-Instruct (Dubey et al., 2024), Llama3-70B-Instruct, GPT-4o-mini-2024-07-18, GPT-4o-2024-05-13, DeepSeek R1 Distill Qwen 14B, DeepSeek R1 (Guo et al., 2025), OpenAI o1-mini-2024-07-18, OpenAI o1-2024-12-17 (Jaech et al., 2024), Gemini 2.5 Flash(Comanici et al., 2025), and GPT-5.5-2026-04-23, using zero-shot, few-shot, and CoT prompting methods (with more tested in Appendix H.1). Due to limited model access, 70 random samples are used for OpenAI o1 and 350 for DeepSeek R1, OpenAI o1-mini, and Qwen 14B (R1 Distill). GPT-5.5 and Gemini 2.5 Flash are evaluated on the full test set of 1,050 samples. Non-reasoning models are evaluated on the full test set of 1,050 samples. To ensure fairness, the selected subset has the same proportion of each reasoning depth as the entire test set. Further implementation details are provided in Appendix E. Human performance is also measured; the experiment settings are in Appendix G.

We perform an error analysis to examine the heterogeneous effects of argument form and reasoning depth on model accuracy. Accuracy for each argument form is only measured using questions with a reasoning depth of 1 because those with a depth of >1 typically have >1 argument forms. Lastly, a qualitative analysis of failure modes is conducted.

5 Results

5.1 Prior Knowledge Independence Test

The results of JustLogic and four other benchmarks are shown in Table 4; note that a benchmark is considered more prior knowledge independent when the absolute difference $|\Delta|$ between model accuracy and random probability is smaller, regardless of whether accuracy falls above or below random chance. A larger $|\Delta|$ in either direction indicates that prior knowledge is influencing model responses. Thus, the smaller the $|\Delta|$, the better. The $|\Delta|$s of CLUTRR and ProofWriter are relatively low, while those of LogiQA 2.0 and FOLIO are nontrivially higher. This is because the former are synthetic datasets, while the latter are manually curated. When a question is code-generated, it generally bears no correlation with reality, e.g. "Is it true, false, or uncertain that Gary is not red." from ProofWriter. Such questions are only answerable by reasoning over the context C. LogiQA 2.0 and FOLIO, on the other hand, often contain questions that are answerable purely using background knowledge, such as "Did the United States won the most medals in the last summer Olympic games?" from FOLIO. We posit that this is an unintentional consequence of the human bias to align the question's truth value with reality. While human curation enhances the question's realism, it compromises the test for deductive reasoning.

The JustLogic benchmark's $|\Delta|$ is 0.4%, which is much lower than other benchmarks, including synthetic ones. The reason for this is twofold: first, JustLogic is a synthetic dataset, thus eliminating the human bias. Second, while JustLogic uses real-world statements, their truth value is nonetheless randomly determined. For example, the statement "doors are solids" is factually true. However, by deducing from the paragraph, the correct answer is "False". Thus, using prior knowledge for many questions is not only unhelpful but also meaningfully decreases accuracy.

Table 4: Results of Prior Knowledge Independence Test. **The lower the |Δ|, the better.**

	|Δ| ↓	Accuracy (%)	Random (%)
CLUTRR	2.0	8.3	6.3
ProofWriter	3.7	37.0	33.3
LogiQA 2.0	27.1	52.1	25.0
FOLIO	6.7	40.0	33.3
JustLogic	**0.4**	33.7	33.3

5.2 Evaluating LLMs' Deductive Reasoning

As shown in Table 5, the best-performing model is GPT-5.5 (88.8%), followed by Gemini 2.5 Flash (82.0%) and DeepSeek R1 (80.9%). Surprisingly, OpenAI o1 (72.9%) performs substantially worse than GPT-5.5, Gemini 2.5 Flash, and DeepSeek R1; we provide deeper analysis on this in Appendix H.2. Several general observations can be made from these results: first, while larger models generally perform better, they offer diminishing returns, shown by the accuracy gain of just 1.0% from Llama3-70B to GPT-4o, with both using CoT prompting. Second, the improvements offered by increasing model size pale in comparison to those offered by better prompting methods. Llama3-8B using CoT achieved higher performance (57.8%) than zero-shot Llama3-70B (53.1%). Lastly, reasoning models generally perform better given similar model sizes: the best reasoning model (GPT-5.5) scored 23.2% higher than the best non-reasoning one (GPT-4o).

Table 5: Model and Human Evaluation Results.

	0-shot	Few-shot	CoT
Random Probability	33.3	33.3	33.3
Llama3-8B-Instruct	49.8	41.8	57.8
Llama3-70B-Instruct	53.1	57.8	64.6
GPT-4o-mini	53.0	54.7	51.8
GPT-4o	53.8	58.3	**65.6**
OpenAI o1-mini	-	-	62.0
OpenAI o1	-	-	72.9
Qwen 14B (R1 Distill)	-	-	61.7
DeepSeek R1	-	-	80.9
Gemini 2.5 Flash	-	-	82.0
GPT-5.5	-	-	**88.8**
Human Average	73.0	73.0	73.0
Human Ceiling	100.0	100.0	**100.0**

Human performance (73.0%) is higher than all non-reasoning models and most reasoning models, while the human ceiling (100.0%), representing the performance of the highest-scoring participant in our study, outperforms all models. The non-trivial gap between the human ceiling and the best-performing model (88.8%) shows that models still have significant room for improvement. Notably, the rapid improvement of LLMs on JustLogic, from 65.6% (GPT-4o) to 88.8% (GPT-5.5), raises the question of whether the benchmark is approaching saturation. However, since JustLogic is grounded in symbolic propositional logic with deterministic correct answers, we expect LLMs to eventually achieve 100% accuracy, much like how calculators perform arithmetic accurately every time. Rather than indicating saturation, this trajectory reflects genuine progress in deductive reasoning, and JustLogic's difficulty can be readily scaled as models improve (see Appendix **??**). Moreover, we believe actual human performance might be higher than 73.0%. Given the long paragraphs of questions with high reasoning depth, participants may have predicted answers by briefly scanning the paragraph, rather than carefully deducing based on all available premises. This is supported by the suspiciously short time taken to complete the questions of some participants.

5.3 Error Analysis

Figure 3 illustrates the model accuracy by argument form (left) and reasoning depth (right). The best models of their respective categories are presented: Llama3-8B (small, non-reasoning model), Llama3-70B (large, non-reasoning model), OpenAI o1-mini (small, reasoning model), and GPT-5.5 (large, reasoning model). To mitigate noise, depths are grouped into low (1–3), medium (4–5), and high (6–7) categories. The qualitative analysis of failure modes can be found in Appendix I.

Figure 3: How argument form and reasoning depth affect accuracy for various models.

While the relative accuracies of argument forms are heterogeneous across models, some forms perform distinctly better than others. For example, HS and CD achieve considerably higher performance than MT, DS, and RAA. Interestingly, the former argument forms are more commonly used by humans than the latter ones, which potentially hints at the cause of this observation.

As for reasoning depth, model accuracies generally decrease as depth increases, consistent with our intuition. Notably, GPT-5.5 achieves the highest accuracy across all depth levels, maintaining strong performance even at high depths (0.84), while OpenAI o1-mini sees a sharp decline in performance once depth increases. In fact, at medium and high depths, o1-mini no longer performs better than non-reasoning models, i.e. GPT-4o and Llama3-8B. These observations confirm that large reasoning models perform drastically better than smaller ones on reasoning problems, and that GPT-5.5 supports particularly deep and robust lines of reasoning.

6 Conclusion

In real-world reasoning scenarios, the most fundamental skill required is deductive reasoning; all other skills, such as background knowledge and instruction following, serve a supporting, albeit important, role. To advance SOTA LLM capabilities, researchers must diagnose whether their models are limited by their deductive reasoning ability, which must be evaluated in isolation. Against the backdrop of existing reasoning benchmarks that are confounded by the use of prior knowledge and other factors, JustLogic uniquely fulfills this crucial function by being (i) highly complex, (ii) prior knowledge independent, and (iii) capable of in-depth error analysis. Notably, GPT-5.5 achieved 88.8% accuracy, surpassing Gemini 2.5 Flash (82.0%), DeepSeek R1 (80.9%), and the human average (73.0%), yet still falling short of the human ceiling, highlighting the ongoing challenges in deductive reasoning for even the most capable models. We recommend that LLM researchers utilize JustLogic as a key pillar in a broader suite of benchmarks that encompasses the range of skills required for real-world reasoning.

7 Limitations

While JustLogic already achieves higher or similar natural language complexity to existing deductive reasoning benchmarks, as shown in Section 3.4, linguistic complexity can be further enhanced to emulate human-written prose, e.g., news articles and fiction stories. Notably, LLMs can be introduced in Step 2 of JustLogic's

dataset construction process, whereby instead of randomly selecting sentences from GenericsKB, an LLM can generate fictional statements and scenarios, e.g. "John's favorite food is hamburgers.". While LLM generation has been successful in datasets involving inductive reasoning and commonsense knowledge, e.g., MuSR (Sprague et al., 2023), it is currently too unreliable for deductive reasoning due to several common mistakes, e.g., ignoring instructions, hallucination, and invalid logic. Nonetheless, as LLMs become more reliable, LLM generation is a promising approach worthy of further exploration.

Error analysis using JustLogic can also be further explored. Interesting research questions include: Are models able to use argument forms appropriately? At which step of the argument chain does the model usually fail? What are the most common reasons for failure? These insights may be useful for fine-tuning models for logical reasoning tasks (Liu et al., 2023b) and model guidance (Beurer-Kellner et al., 2024).

Broader Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Amazon. Amazon Mechanical Turk, 2005. URL `https://www.mturk.com/`.

Luca Beurer-Kellner, Marc Fischer, and Martin Vechev. Guiding LLMs the right way: Fast, non-invasive constrained generation. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 3658–3673. PMLR, 21–27 Jul 2024. URL `https://proceedings.mlr.press/v235/beurer-kellner24a.html`.

Sumithra Bhakthavatsalam, Chloe Anastasiades, and Peter Clark. Genericskb: A knowledge base of generic statements. *arXiv preprint arXiv:2005.00660*, 2020.

Tom B Brown. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Gheorghe Comanici et al. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*, 2025.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, and Zhifang Sui. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*, 2022.

Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs. *arXiv preprint arXiv:1903.00161*, 2019.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Simeng Han, Hailey Schoelkopf, Yilun Zhao, Zhenting Qi, Martin Riddell, Luke Benson, Lucy Sun, Ekaterina Zubova, Yujie Qiao, Matthew Burtell, David Peng, Jonathan Fan, Yixin Liu, Brian Wong, Malcolm Sailor, Ansong Ni, Linyong Nan, Jungo Kasai, Tao Yu, Rui Zhang, Shafiq Joty, Alexander R. Fabbri, Wojciech Kryscinski, Xi Victoria Lin, Caiming Xiong, and Dragomir Radev. Folio: Natural language reasoning with first-order logic. *arXiv preprint arXiv:2209.00840*, 2022. URL https://arxiv.org/abs/2209.00840.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai o1 system card. *arXiv preprint arXiv:2412.16720*, 2024.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Robert Johnson. *A Logic Book: Fundamentals of Reasoning*. Cengage Learning, 5 edition, 2006.

Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. Unifiedqa: Crossing format boundaries with a single qa system. *arXiv preprint arXiv:2005.00700*, 2020.

JP Kincaid. Derivation of new readability formulas (automated readability index, fog count and flesch reading ease formula) for navy enlisted personnel. *Chief of Naval Technical Training*, 1975.

Hanmeng Liu, Jian Liu, Leyang Cui, Zhiyang Teng, Nan Duan, Ming Zhou, and Yue Zhang. Logiqa 2.0—an improved dataset for logical reasoning in natural language understanding. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2023a.

Hanmeng Liu, Zhiyang Teng, Leyang Cui, Chaoli Zhang, Qiji Zhou, and Yue Zhang. Logicot: Logical chain-of-thought instruction tuning. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 2908–2921, 2023b.

Jian Liu, Leyang Cui, Hanmeng Liu, Dandan Huang, Yile Wang, and Yue Zhang. Logiqa: A challenge dataset for machine reading comprehension with logical reasoning. *arXiv preprint arXiv:2007.08124*, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.

Abulhair Saparov, Richard Yuanzhe Pang, Vishakh Padmakumar, Nitish Joshi, Mehran Kazemi, Najoung Kim, and He He. Testing the general deductive reasoning capacity of large language models using ood examples. *Advances in Neural Information Processing Systems*, 36, 2024.

Koustuv Sinha, Shagun Sodhani, Jin Dong, Joelle Pineau, and William L Hamilton. Clutrr: A diagnostic benchmark for inductive reasoning from text. *arXiv preprint arXiv:1908.06177*, 2019.

Zayne Sprague, Xi Ye, Kaj Bostrom, Swarat Chaudhuri, and Greg Durrett. Musr: Testing the limits of chain-of-thought with multistep soft reasoning. *arXiv preprint arXiv:2310.16049*, 2023.

Oyvind Tafjord, Bhavana Dalvi Mishra, and Peter Clark. Proofwriter: Generating implications, proofs, and abductive statements over natural language. *arXiv preprint arXiv:2012.13048*, 2020.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Ruijie Xu, Zengzhi Wang, Run-Ze Fan, and Pengfei Liu. Benchmarking benchmark leakage in large language models. *arXiv preprint arXiv:2404.18824*, 2024.

Vikas Yadav, Steven Bethard, and Mihai Surdeanu. Quick and (not so) dirty: Unsupervised selection of justification sentences for multi-hop question answering. *arXiv preprint arXiv:1911.07176*, 2019.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822, 2023.

Weihao Yu, Zihang Jiang, Yanfei Dong, and Jiashi Feng. Reclor: A reading comprehension dataset requiring logical reasoning. *arXiv preprint arXiv:2002.04326*, 2020.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*, 2019.

Honghua Zhang, Liunian Harold Li, Tao Meng, Kai-Wei Chang, and Guy Van den Broeck. On the paradox of learning to reason from data. *arXiv preprint arXiv:2205.11502*, 2022.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, et al. Least-to-most prompting enables complex reasoning in large language models. *arXiv preprint arXiv:2205.10625*, 2022.

A Argument Forms

Table 6: An overview of the argument forms in the JustLogic dataset.

	Formal Notation	Example
Modus Ponens	$p \rightarrow q$	If the sky is blue, then the dog is happy.
	p	The sky is blue.
	$\vdash q$	Therefore, the dog is happy.
Modus Tollens	$p \rightarrow q$	If the sky is blue, then the dog is happy.
	$\neg q$	The dog is not happy.
	$\vdash \neg p$	Therefore, the sky is not blue.
Hypothetical Syllogism	$p \rightarrow q$	If the sky is blue, then the dog is happy.
	$q \rightarrow r$	If the dog is happy, the owner is happy.
	$\vdash p \rightarrow r$	Therefore, if the sky is blue, the owner is happy.
Disjunctive Syllogism	$p \vee q$	Either the dog is barking or the dog is asleep.
	$\neg p$	The dog is not barking.
	$\vdash q$	Therefore, the dog is asleep.
Reductio ad absurdum	$p \rightarrow q$	If the dog is calm, the owner is around.
	$p \rightarrow \neg q$	If the dog is calm, the owner is not around.
	$\vdash \neg p$	Therefore, the dog is not calm.
Constructive Dilemma	$p \vee q$	Either the sky is blue or it is raining.
	$p \rightarrow r$	If the sky is blue, the race can start.
	$q \rightarrow s$	If it is raining, the race is delayed.
	$\vdash r \vee s$	Therefore, either the race can start or it is delayed.
Disjunction Elimination	$p \vee q$	Either the sky is blue or it is raining.
	$p \rightarrow r$	If the sky is blue, the dog is cheerful.
	$q \rightarrow r$	If it is raining, the dog is cheerful.
	$\vdash r$	Therefore, the dog is cheerful.

B Algorithm for Step 1 of JustLogic's Dataset Construction

Algorithm 1 Pseudocode for Step 1 (Generate argument structure) of JustLogic's Dataset Construction Process. It generates the argument structure using level-order construction until the desired number of argument forms D is reached. Note that reasoning depth is defined as the total number of argument forms D (the size of the proof structure), not the length of the longest inference chain.

Require: D {Target number of argument forms}
1: $\phi_0 \leftarrow$ SAMPLELOGICALFORM() {Sample a random final conclusion}
2: $a_0 \leftarrow$ SAMPLEARGUMENTFORM(ϕ_0) {Samples a random argument form for the final conclusion}
3: $\mathcal{L} \leftarrow [a_0]$
4: $d \leftarrow 1$ {Tracks the no. of argument forms}
5: **while** $d < D$ **do**
6:   $P \leftarrow$ GETALLPREMISES($\mathcal{L}$) {Extract all premises of all a in $\mathcal{L}$}
7:   $k \leftarrow$ SAMPLEUNIFORM($1, \min(D - d, |P|)$) {Sample an integer from 1 to $\min(D - d, |P|)$}
8:   $P_{\text{sub}} \leftarrow$ SAMPLERANDOMSUBSET(P, k) {Select k premises to become subconclusions}
9:   $\mathcal{L}' \leftarrow [\,]$
10: **for all** $\phi \in P_{\text{sub}}$ **do**
11:    $a \leftarrow$ SAMPLEARGUMENTFORM(ϕ)
12:    Append a to $\mathcal{L}'$
13: **end for**
14: $\mathcal{L} \leftarrow \mathcal{L}'$
15: $d \leftarrow d + |P_{\text{sub}}|$
16: **end while**
17: **return** Argument structure rooted at ϕ_0

C   Sample texts from deductive reasoning benchmarks

Beyond metrics like vocabulary size and number of domains, the degree of natural language complexity can be straightforwardly determined by manually inspecting the linguistic patterns of a given benchmark. Table 7 shows sample texts from CLUTRR, ProofWriter, ProntoQA-OOD, SimpleLogic, LogiQA 2.0, FOLIO, and JustLogic.

Table 7: Sample texts from various deductive reasoning benchmarks.

Benchmark	Sample Text
CLUTRR (Sinha et al., 2019)	Lorraine and her brother Kevin went to see a movie. Clarence took his granddaughter Lorraine to the movies and they enjoyed themselves.
ProofWriter (Tafjord et al., 2020)	The bald eagle is not rough. The bear does not need the bald eagle. The dog needs the bear. If someone is rough then they chase the bald eagle. If someone needs the bear then they are not blue...
ProntoQA-OOD (Saparov et al., 2024)	Lempuses are bitter. Every lempus is a lorpus. Brimpuses are vumpuses. Tumpuses are impuses. Each impus is not hot. Every numpus is a sterpus. Each shumpus is brown. Sterpuses are fast. Every vumpus is not small...
SimpleLogic Zhang et al. (2022)	If messy and hypocritical and lonely, then shiny. If tame, then friendly. If plain and shiny and homely, then nervous. If tender, then hypocritical. If dull and impatient and plain, then tame. If spotless, then perfect. If elegant and tender, then homely...
LogiQA 2.0 (Liu et al., 2023a)	In the past 10 years, the sales of personal notebook computers of a computer company have continued to grow, but the growth rate is lower than the growth rate of the company's total sales of all products.
FOLIO (Han et al., 2022)	All people who regularly drink coffee are dependent on caffeine. People regularly drink coffee, or they don't want to be addicted to caffeine, or both. No one who doesn't want to be addicted to caffeine is unaware that caffeine is a drug...
JustLogic	Provided that sound travels through different kinds of matter, we know that every soul is a candidate for immortality. It is a common misconception that every soul is a candidate for immortality.

Evidently, JustLogic exhibits significantly greater natural language complexity than CLUTRR, ProofWriter, ProntoQA-OOD, and SimpleLogic, because the latter benchmarks programmatically generate every sentence, while JustLogic extracts its sentences from GenericsKB, a natural language text database. Thus, the former benchmarks rely on a limited number of grammar templates, reducing their linguistic complexity. JustLogic exhibits similar levels of complexity to FOLIO. LogiQA 2.0 is more complex because it is human-curated and not backed by a formal logic system (unlike how JustLogic is backed by propositional logic). Without a formal logic system, LogiQA 2.0's argument complexity suffers, as shown in Table 3, which compromises its ability to evaluate deductive reasoning in LLMs.

D   Prior Knowledge Independence Test

A sample prompt for the prior knowledge independence test, based on the example in Figure 1, is shown below in Figure 4. Note that the answer options vary depending on the benchmark. For example, the options for LogiQA are A, B, C, and D, while those of CLUTRR are 16 possible family relations.

Instructions:

- Use the knowledge you currently have to answer as accurately as possible.
- You have 3 answer options: True, False, and Uncertain.
- There should be roughly an equal proportion of each option.
- *Add 5-10 examples here*

Question: Is the following statement true, false, or uncertain?
Statement: Doors are solids.
Answer: True.

Figure 4: Example of a prior knowledge independence test prompt.

E   Experiment Implementation Details

The hyperparameters for the Llama3 models are decided largely based on the recommendations in the original paper Dubey et al. (2024), which are as follows: temperature of 0.6, top p of 0.9, presence penalty of 1.15, length penalty of 1. For DeepSeek R1 and Qwen-14B (R1 Distill), the recommended temperature of 0.6 is used. For OpenAI models (GPT-4o, GPT-4o-mini, OpenAI o1, OpenAI o1-mini, and GPT-5.5) and Gemini 2.5 Flash, the default temperature is used. All evaluations are conducted using the OpenAI, OpenRouter, and Google Generative Language APIs, with model costs ranging from $0.0003 per question for Llama3-8B-Instruct to approximately $0.26 for GPT-5.5.

With regards to prompting methods, 3-shot prompting is chosen for few-shot experiments because it produces the highest accuracies compared to 6 and 9-shot. Chain-of-thought prompts also contain three examples. In the interest of fairness, all prompting techniques contain similar general instructions, which are as follows:

You are given a paragraph of facts/premises, followed by a statement. Perform logical reasoning with propositional logic on the paragraph to determine the truth value of the statement.

Here is the list of argument forms:

- Modus Ponens
- Modus Tollens
- Hypothetical Syllogism
- Disjunctive Syllogism
- Reductio ad absurdum
- Constructive Dilemma
- Disjunction Elimination

You must answer with either one of the 3 options:

- TRUE: When the premises in the paragraph lead to the statement
- FALSE: When the premises in the paragraph directly contradict the statement
- UNCERTAIN: When the premises in the paragraph neither support nor contradict the statement

Do not use your prior knowledge; your answer must be solely determined by the information within the paragraph. Assume that all premises in the paragraph are true.

Question: Is the statement true, false, or uncertain?

As for the additional prompting techniques are explored in Appendix H.1, the tree-of-thought framework contains two prompts at each step: candidate generation and candidate evaluation. In addition to the general instructions above, the candidates generation prompt is shown below.

> Let's reason step by step. Generate 3 alternative possible next steps, based on the question and the answer so far. Each step consists of a single argument form, e.g. modus ponens. The question takes 1 or more steps to solve.
>
> Note that these 3 steps are NOT sequential. They must be alternatives to the same step.

As for candidate evaluation, the prompt is shown below. Note that the model may terminate the exploration prematurely by indicating a final answer. A practical consideration is that models tend to conclude *too early*; the prompt should be designed to emphasize exploration and instruct not to conclude unless sufficiently certain.

> Of the possible next steps, choose the one that **most directly advances the reasoning process** toward determining the truth value of the statement. Select the best next step to continue reasoning toward the answer. Do not conclude with TRUE, FALSE, or UNCERTAIN yet — unless:
>
> - All relevant reasoning paths have been explored, and
> - No further logical deduction is possible or necessary.
>
> Otherwise, output only the next reasoning step, using one valid argument form. Your goal is to build a full reasoning chain, not jump to conclusions.
>
> Only if this step logically completes the reasoning chain and no further analysis is needed, then conclude with one of: TRUE, FALSE, or UNCERTAIN.

F Additional Experimental Validations of the JustLogic Benchmark

F.1 Prior Knowledge Independence Test using Other Models

To ensure that the results of the prior knowledge independence test, conducted with GPT-4 in Section 5.1, are replicable, we conduct the same test using Llama3-70B-Instruct. The results are shown in Table 8. The results confirm that JustLogic maintains a high degree of prior knowledge independence compared to human-curated benchmarks such as FOLIO and LogiQA 2.0. However, we note that JustLogic's $|\Delta|$ differs between GPT-4 (0.4%) and Llama3-70B (5.7%). This discrepancy is likely attributable to differences in instruction-following ability between the two models: Llama3-70B may be more susceptible to leveraging prior knowledge despite explicit instructions not to do so, resulting in a higher $|\Delta|$. Nonetheless, JustLogic's $|\Delta|$ remains substantially lower than that of LogiQA 2.0 (23.3%) and FOLIO (10.0%) under Llama3-70B, confirming that JustLogic is more prior knowledge independent than manually curated benchmarks regardless of the model used for testing. Interestingly, ProofWriter's accuracy is significantly lower than random, which is potentially problematic since models may be biased *against* statements whose truth-value aligns with reality.

Table 8: Results of Prior Knowledge Independence Test using Llama3-70B-Instruct. **The lower the $|\Delta|$, the better.**

	$|\Delta| \downarrow$	Accuracy (%)	Random (%)
CLUTRR	5.4	11.7	6.3
ProofWriter	8.6	24.7	33.3
LogiQA 2.0	23.3	48.3	25.0
FOLIO	10.0	43.3	33.3
JustLogic	**5.7**	39.0	33.3

F.2 Impact of Factual Accuracy on Model Performance

Given that JustLogic randomly chooses sentences from GenericsKB to add to each instance's argument structure, the final conclusion may be factually accurate or inaccurate in the real world. For example, if the conclusion is "It is not true that Japan is in Asia.", then the conclusion is factually inaccurate. Thus, there is a concern that models underperform due to confusion arising from factually inaccurate conclusions. Moreover, since some conclusions are factually accurate, such instances may exhibit artificially high performance.

To study these concerns, we conducted the following empirical study. If the above concerns are true, we expect factually inaccurate conclusions to perform worse than factually accurate ones. Because all GenericsKB sentences are factually accurate, we can straightforwardly deduce each conclusion's factual accuracy. For example, $x \vee y$ is factually accurate while $\neg x$ is not.

Figure 5 shows the comparison of accuracies for five models: DeepSeek R1, OpenAI o1-mini, GPT-4o, Llama3-70B, and Llama3-8B; the left represents when reasoning depth is 1, while the right represents when depth is 7 or less.

Figure 5: How factual accuracy of conclusions affects model accuracy.

These results reject the hypothesis that factually inaccurate conclusions perform worse than factually accurate ones; there is no consistent trend between both conclusion types. In fact, when depth=1, factually inaccurate conclusions exhibit higher performance for some models! At depths of 7 or less, GPT-4o and Llama3-70B saw a decrease in *relative* accuracy of factually inaccurate statements, DeepSeek R1 and Llama3-8B maintained similar accuracies, while OpenAI o1-mini saw an improvement.

There are two reasons for these results. First, our prompt explicitly instructs models to answer the question only using the paragraph provided and without using prior knowledge. The full prompt is shown in Appendix E. Moreover, in few-shot prompts, the examples provided include conclusions where their factual accuracy does not match the correct answer. These measures encourage models to ignore prior knowledge and answer questions without considering the factual accuracy of conclusions in the real world.

Second, how LLMs treat factual accuracy when reasoning deductively depends on the LLM's training: specifically, the model's ability to follow prompt instructions to ignore prior knowledge. For example, DeepSeek R1 biases toward factually inaccurate conclusions when deductively reasoning, while OpenAI o1-mini exhibits little difference in performance. Should an LLM exhibit significant differences in performance between factually accurate and inaccurate conclusions, it suggests the LLM has room for improvement in instruction following.

Importantly, the ability to deduce whether premises lead to a conclusion without using prior knowledge is a fundamental human skill: we use it to evaluate whether a debater's speech or journalist's article supports their position. The inclusion of both factually accurate and inaccurate instances in JustLogic is a feature, not a bug.

F.3 Impact of Language "Unnaturalness" on Model Performance

Given that JustLogic is synthetically generated, there is a concern that its natural language may be highly unnatural to models, potentially hindering their ability to reason deductively. To study this concern, we compare the model perplexity of JustLogic, two other human-curated benchmarks (FOLIO and LogiQA), and two other synthetic benchmarks (CLUTRR and ProofWriter). Llama3-8B-Instruct (a non-reasoning model) and DeepSeek R1 Distill Qwen 14B (a reasoning model) are used. If JustLogic's language is indeed highly unnatural, we expect its model perplexity to be significantly higher than other benchmarks.

Figure 6: Model perplexities of various logical reasoning benchmarks.

The results, as shown in Figure 6, reject the aforementioned hypothesis. JustLogic's model perplexities are comparable to FOLIO and lower than the rest. This shows that despite JustLogic's higher linguistic complexity (Table 3), its syntactic patterns are well understood by models. CLUTRR's and ProofWriter's higher perplexities are likely due to their unnatural symbolic-like language; LogiQA's higher perplexities are likely because its questions are originally in Chinese and did not shed their foreign syntactic patterns when translated into English. Examples can be found in Appendix C.

Therefore, while JustLogic's natural language may seem unnatural to human readers, their syntactic patterns are highly intuitive to LLMs compared to other reasoning benchmarks. JustLogic's language likely does not hinder LLMs' understanding of the questions.

G   Details on Human Participants

18 anonymous participants are given a random subset of questions. This is because deductive reasoning questions, especially those at high reasoning depths, are cognitively demanding and time-consuming; it is impractical to expect humans to complete 1050 questions. To ensure fairness, both models and participants

are provided similar prompts and are given the same proportion of each reasoning depth. To ensure that participants understand the requirements of the task, a simple verification question is added. If they answer incorrectly, their subsequent responses are voided.

Participants are recruited from Amazon Mechanical Turk (Amazon, 2005) and are paid $24 per hour. Participation is entirely voluntary, and the survey posed no foreseeable risks to participants. As reflected in Figure 7, to create a sample representative of the human average, the participants possess a diverse range of educational qualifications and familiarity with propositional logic. The human ceiling (100.0%) represents the performance of the highest-scoring participant in our study. Since every JustLogic instance has a unique, logically determined correct answer, a sufficiently careful reasoner can in principle achieve perfect accuracy. The fact that a participant achieved 100.0% in our evaluation confirms this, and serves as a practical upper bound on human performance on the benchmark.

Figure 7: Participants' highest level of education and familiarity with proposition logic.

H Additional Model Evaluations

H.1 Additional Evaluations on Various Prompting Techniques

While reasoning models do not require specific prompting techniques due to their reasoning-specific training, non-reasoning models observe significant deltas in accuracy based on the choice of prompts. Thus, we evaluate the best small and large non-reasoning models, Llama3-8B-Instruct and GPT-4o, on additional prompting techniques: (i) the self-consistency decoding (SC) (Wang et al., 2022), where the answer is derived through majority voting over 5 sampled paths, and (ii) the tree-of-thought (ToT) framework (Yao et al., 2023), where each step generates 3 candidates and ultimately chooses 1; the maximum steps allowed is $depth + 2$, but the model may terminate the search earlier. Finally, we also test (iii) a CoT prompt that does not mention propositional logic. Explicit mentions of technical terms in propositional logic, e.g. reductio ad absurdum, may hinder the reasoning ability of models that are less familiar with them. This prompts tests the aforementioned hypothesis.

Table 9: Model and Human Evaluation Results.

	0-shot	Few-shot	CoT	SC-CoT	ToT	CoT (w/o prop. logic)
Llama3-8B-Instruct	49.8	41.8	**57.8**	54.6	38.6	54.0
Llama3-70B-Instruct	53.1	57.8	**64.6**	58.6	60.6	58.3
GPT-4o-mini	53.0	54.7	**51.8**	50.3	48.6	50.0
GPT-4o	53.8	58.3	65.6	67.1	**71.4**	67.4

The relative performance of the prompting techniques is heterogeneous across models. However, besides GPT-4o, we find that prompting techniques that are more expensive than vanilla CoT offer little to no performance advantage. Self-consistency CoT achieves similar performance to CoT; the former may require significantly higher sampled paths to reap its benefits. Tree-of-thought is too complex for most models to

utilize, often hallucinating across prompts and failing to break down the problem into coherent steps. Lastly, we find that the explicit mention of propositional logic in the prompt is generally helpful towards model performance.

H.2   Understanding the Performance of OpenAI o1 vs. GPT-5.5

OpenAI o1 (72.9%) performs substantially worse than GPT-5.5 (88.8%) on JustLogic, despite other benchmarks suggesting their performance should be comparable. To rule out any human errors during testing and to seek an explanation for these results, we performed a qualitative analysis of OpenAI o1's responses (all of which can be found in our GitHub repository). First, we find that o1's response to questions of depth $>= 5$ are significantly shorter than that of depth $= 3$ or 4, which is counterintuitive. Second, o1 prematurely answers "Uncertain" for 90% of questions of depth $= 7$ without faithfully engaging with the question. Figure 8, showing the accuracy of OpenAI o1 and GPT-5.5 over various difficulty levels based on argument depth, reinforces our analysis. Both models perform reasonably well at low and medium depths, though GPT-5.5 already outperforms o1 at these levels, but o1 struggles significantly at high difficulty problems (0.40), performing close to random probability, while GPT-5.5 maintains strong performance (0.84).

These observations suggest that OpenAI o1's test-time compute may have been artificially limited, reducing its ability to solve deep, challenging questions. In contrast, GPT-5.5 demonstrates robust reasoning across all depth levels, highlighting the significant advances in the latest generation of reasoning models. Importantly, this case study reflects JustLogic's ability to flexibly probe models at various levels of difficulty.

Figure 8: How reasoning depth affects accuracy for OpenAI o1 and GPT-5.5.

As LLMs improve, we expect their performance on JustLogic to rise, which necessitates increasing JustLogic's difficulty. One way is to increase the argument depth: specifically, we extended JustLogic to incorporate questions of very high depth (8 to 11), and evaluated them on the current SOTA reasoning and non-reasoning models, i.e. DeepSeek R1 and GPT-4o, using CoT prompt.

Additionally, two other benchmarks, LogiQA 2.0 and FOLIO, are also evaluated to compare their difficulty. The results, as shown in Table 10, suggest that (i) as JustLogic's question difficulty increases, model accuracy decreases, and (ii) hard JustLogic questions yield significantly lower accuracies than LogiQA 2.0 and FOLIO. This indicates that JustLogic is already more challenging than other benchmarks and is likely to remain so due to its reduced risk of performance saturation.

Table 10: SOTA Model Performance on various JustLogic difficulty levels and other benchmarks.

	JustLogic				LogiQA 2.0	FOLIO
	Easy	Medium	**Hard**	**Very Hard**		
GPT-4o	77.3	63.3	**57.3**	**53.0**	64.5	76.3
DeepSeek R1	90.0	83.3	**68.0**	**65.0**	87.6	86.2

I   Qualitative Analysis of Failure Modes

To identify exactly how JustLogic is challenging for existing LLMs, we conducted a qualitative analysis to identify the 4 major failure modes of various models' responses to JustLogic questions. We primarily rely on analyzing the chain-of-thought responses to investigate how they produced the wrong answers. High-level explanations and abbreviated examples are provided for the failure modes.

(1) Logical inconsistency. Models sometimes produce arguments that rely on premises, implicit or otherwise, that contradicts earlier parts of their chain-of-thought. This causes models to generate incoherent arguments, and ultimately arrive at the wrong conclusion. For example, the following is a truncated response from OpenAI o1:

```
While R implies that researchers are observing data, without specific information,
we cannot definitively state R → S.
...
Since M ∨ R is true and M ∨ S is the statement we are evaluating, and we have
established M is true if N is true, we can conclude:

  • M ∨ S is true.
```

This line of reasoning suggests that $M \vee R$ implies $M \vee S$. For this to be the case, $R \rightarrow S$ must be true. However, earlier in the reasoning chain, o1 says "we cannot definitively state $R \rightarrow S$". This argument is therefore logically inconsistent.

(2) Wrong application of argument forms. Models sometimes identify the correct argument form to solve the question. However, mistakes are made when applying the form to the specific question context. In the truncated response below by Llama3-70B, disjunctive syllogism is, in fact, the appropriate argument form, but the opposite conclusion should have been made: the statement, pain can be severe and make a person unable to perform normal activities, does not hold.

```
Premise 1:  Either condensation is water vapor changing to liquid water or the
statement, pain can be severe and make a person unable to perform normal activities,
does not hold.
Premise 2:  The claim that condensation is water vapor changing to liquid water does
not correspond with reality.

Using disjunctive syllogism with premises 1 and 2, we conclude that the statement,
pain can be severe and make a person unable to perform normal activities, holds.
```

(3) Using the wrong argument form. Sometimes, models attempt to use argument forms that logically cannot be applied to the context. Such mistakes often derail the response, making it entirely incoherent. In the following example of an output by Llama3-70B, modus tollens simply cannot be applied here; reductio ad absurdum should have been used instead.

```
Premise 1:  One may reasonably assume that if the statement that 'football is a
memory-making machine' is incorrect, then fairways are lawns.  Premise 2:  Assuming
the statement that 'football is a memory-making machine' is incorrect, we know that
it is not the case that fairways are lawns.

Using modus tollens with premise 1 and 2...
```

(4) False interpretation of facts. Models sometimes misinterpret the natural language facts entirely. This is most clearly seen when models translate sentences into the wrong logical form. While some of these translations seem trivially simple, especially for LLMs, such mistakes are as common as the other failure modes. In the example below, GPT-4o's interpretation of Premise 2 is incorrect: Premise 2 does in fact imply that the statement "most roses grow fairly rapidly" is false because of the word "mistakenly."

```
Premise 2:  Some people mistakenly believe that most roses grow fairly rapidly.

We cannot directly use Premise 2 to confirm or deny (¬Q), as it only mentions a
mistaken belief rather than the truth value.  Therefore, we do not have sufficient
information to directly negate (Q).
```

Nonetheless, some sentences are more complex and therefore more prone to false interpretations. In the example below, also by GPT-4o, Premise 2's logical form should be $\neg(A \rightarrow B) \rightarrow \neg C$ instead.

```
Premises:
...
2.  "Given that the claim that if police sergeants receive calls, then good
nutrition helps reduce low birth weight, miscarriage and anemia does not reflect
reality, it can be inferred that some people mistakenly believe that oil is simply a
liquid form of fat."

From Premise 2:  (¬(A→B))
```

J Future Works

JustLogic can be scaled to incorporate more question types related to logical reasoning, such as multiple-choice questions, identifying missing premises in arguments, identifying logical fallacies in arguments, and natural language sentence to formal logic translation. Liu et al. (2023b) provides a comprehensive taxonomy. JustLogic's program can be adapted to accommodate each question type while maintaining its key advantages. By measuring deductive reasoning across multiple modalities using a single dataset construction method, JustLogic can provide more comprehensive and controlled evaluations and error analysis.

JustLogic is currently an English, text-based dataset. However, importantly, it has enormous potential to be multilingual and multimodal. To make the dataset multilingual, researchers need only replace the natural language sentences used in Step 2 of the dataset construction process, i.e., replace the list of logical form expression templates and GenericsKB database. Otherwise, the dataset construction process is generalizable to any language. It is also entirely feasible to make the dataset multimodal. As a straightforward example, symbols can be used to reference other modalities, rather than just being replaced by text. For example, "If x, then y." can be replaced by "If the country in the map is shaded red, then it is currently in a recession.". JustLogic's extensibility and flexibility create immense, exciting opportunities for future research.