Incorporating Symmetry into Deep Dynamics Models for Improved Generalization

Abstract

Recent work has shown deep learning can accelerate the prediction of physical dynamics relative to numerical solvers. However, limited physical accuracy and an inability to generalize under distributional shift limits its applicability to the real world. We propose to improve accuracy and generalization by incorporating symmetries into convolutional neural networks. Specifically, we employ a variety of methods each tailored to enforce a different symmetry. Our models are both theoretically and experimentally robust to distributional shift by symmetry group transformations and enjoy favorable sample complexity. We demonstrate the advantage of our approach on a variety of physical dynamics including Rayleigh–Bénard convection and real-world ocean currents and temperatures. Compared with image or text applications, our work is a significant step towards applying equivariant neural networks to high-dimensional systems with complex dynamics.

1 Introduction

Modeling dynamical systems in order to forecast the future is of critical importance in a wide range of fields including, e.g., fluid dynamics, epidemiology, economics, and neuroscience [2; 20; 43; 21; 14]. Many dynamical systems are described by systems of non-linear differential equations that are difficult to simulate numerically. Accurate numerical computation thus requires long run times and manual engineering in each application.

Recently, there has been much work applying deep learning to accelerate solving differential equations [44; 6]. However, current approaches struggle with generalization. The underlying problem is that physical data has no canonical frame of reference to use for data normalization. For example, it is not clear how to rotate samples of fluid flow such that they share a common orientation. Thus real-world out-of-distribution test data is difficult to align with training data. Another limitation of current approaches is low physical accuracy. Even when mean error is low, errors are often spatially correlated, producing a different energy distribution from the ground truth.

We propose to improve the generalization and physical accuracy of deep learning models for physical dynamics by incorporating symmetries into the forecasting model. In physics, Noether's Law gives a correspondence between conserved quantities and groups of symmetries. By building a neural network which inherently respects a given symmetry, we thus make conservation of the associated quantity more likely and consequently the model's prediction more physically accurate.

A function f is equivariant if when its input x is transformed by a symmetry g, the output is transformed by the same symmetry,

$$f(g \cdot x) = g \cdot f(x).$$

In the setting of forecasting, f approximates the underlying dynamical system. The set of valid transformations g is called the symmetry group of the system.

By designing a model that is inherently equivariant to transformations of its input, we can guarantee that our model generalizes automatically across these transformations, making it robust to distributional shift. The symmetries we consider, translation, rotation, uniform motion, and scale, have different properties, and thus we tailor our methods for incorporating each symmetry.

Specifically, for scale equivariance, we replace the convolution operation with group correlation over the group G generated by translations *and* rescalings. Our method builds on that of Worrall and

Welling [49], with significant novel adaptations to the physics domain: scaling affecting time, space, and magnitude; both up and down scaling; and scaling by any real number. For rotational symmetries, we leverage the key insight of Cohen and Welling [9] that the input, output, and hidden layers of the network are all acted upon by the symmetry group and thus should be treated as representations of the symmetry group. Our rotation-equivariant model is built using the flexible `E(2)-CNN` framework developed by Weiler and Cesa [47]. In the case of a uniform motion, or Galilean transformation, we show the above methods are too constrained. We use the simple but effective technique of convolutions conjugated by averaging operations.

Research into equivariant neural networks has mostly been applied to tasks such as image classification and segmentation [26; 48; 47]. In contrast, we design equivariant networks in a completely different context, that of a time series representing a physical process. Forecasting high-dimensional turbulence is a significant step for equivariant neural networks compared to the low-dimensional physics examples and computer vision problems treated in other works.

We test on a simulated turbulent convection dataset and on real-world ocean current and temperature data. Ocean currents are difficult to predict using numerical methods due to unknown external forces and complex dynamics not fully captured by simplified mathematical models. These domains are chosen as examples, but since the symmetries we focus on are pervasive in almost all physics problems, we expect our techniques will be widely applicable. Our contributions include:

- We study the problem of improving the generalization capability and physical accuracy of deep learning models for learning complex physical dynamics such as turbulence and ocean currents.
- We design tailored methods with theoretical guarantees to incorporate various symmetries, including uniform motion, rotation, and scaling, into convolutional neural networks.
- When evaluated on turbulent convection and ocean current prediction, our models achieve significant improvement on generalization of both predictions and physical consistency.
- For different symmetries, our methods have an average 31% and maximum 78% reduction in energy error when evaluated on turbulent convection with no distributional shift.

2 MATHEMATICAL PRELIMINARIES

2.1 SYMMETRY GROUPS AND EQUIVARIANT FUNCTIONS

Formal discussion of symmetry relies on the concept of an abstract symmetry group. We give a brief overview, for a more formal treatment see Appendix A, or Lang [27].

A **group of symmetries** or simply **group** consists of a set G together with a composition map $\circ\colon G \times G \to G$. The composition map is required to be associative and have an identity $1 \in G$. Most importantly, composition with any element of G is required to be invertible.

Groups are abstract objects, but they become concrete when we let them act. A group G has an **action** on a set S if there is an action map $\cdot\colon G \times S \to S$ which is compatible with the composition law. We say further that S is a G-**representation** if the set S is a vector space and the group acts on S by linear transformations.

Definition 1 (invariant, equivariant). Let $f\colon X \to Y$ be a function and G be a group. Assume G acts on X and Y. The function f is G-**equivariant** if $f(gx) = gf(x)$ for all $x \in X$ and $g \in G$. The function f is G-**invariant** if $f(gx) = f(x)$ for all $x \in X$ and $g \in G$.

2.2 PHYSICAL DYNAMICAL SYSTEMS

We investigate two dynamical systems: Rayleigh–Bénard convection and real-world ocean current and temperature. These systems are governed by Navier-Stokes equations.

2D Navier-Stokes (NS) Equations. Let $\boldsymbol{w}(\boldsymbol{x}, t)$ be the velocity vector field of a flow. The field $\boldsymbol{w}$ has two components (u, v), velocities along the x and y directions. The governing equations for this physical system are the momentum equation, continuity equation, and temperature equation,

$$\frac{\partial \boldsymbol{w}}{\partial t} = -(\boldsymbol{w} \cdot \nabla)\boldsymbol{w} - \frac{1}{\rho_0}\nabla p + \nu\nabla^2\boldsymbol{w} + f; \quad \nabla \cdot \boldsymbol{w} = 0; \quad \frac{\partial H}{\partial t} = \kappa\Delta H - (\boldsymbol{w} \cdot \nabla)H, \ (\mathcal{D}_{\mathrm{NS}})$$

where $H(\boldsymbol{x}, t)$ is temperature, p is pressure, κ is the heat conductivity, ρ_0 is initial density, α is the coefficient of thermal expansion, ν is the kinematic viscosity, and f is the buoyant force.

2.3 Symmetries of Differential Equations

By classifying the symmetries of a system of differential equations, the task of finding solutions is made far simpler, since the space of solutions will exhibit those same symmetries. Let G be a group equipped with an action on 2-dimensional space $X = \mathbb{R}^2$ and 3-dimensional spacetime $\hat{X} = \mathbb{R}^3$. Let $V = \mathbb{R}^d$ be a G-representation. Denote the set of all V-**fields** on $\hat{X}$ as $\hat{\mathcal{F}}_V = \{\boldsymbol{w} \colon \hat{X} \to V : \boldsymbol{w} \text{ smooth}\}$. Define $\mathcal{F}_V$ similarly to be V-fields on X. Then G has an induced action on $\hat{\mathcal{F}}_V$ by $(g\boldsymbol{w})(x, t) = g(\boldsymbol{w}(g^{-1}x, g^{-1}t))$ and on $\mathcal{F}_V$ analogously.

Consider a system of differential operators $\mathcal{D}$ acting on $\hat{\mathcal{F}}_V$. Denote the set of solutions $\mathrm{Sol}(\mathcal{D}) \subseteq \hat{\mathcal{F}}_V$. We say G is **a symmetry group of** $\mathcal{D}$ if G preserves $\mathrm{Sol}(\mathcal{D})$. That is, if φ is a solution of $\mathcal{D}$, then for all $g \in G$, $g(\varphi)$ is also. In order to forecast the evolution of a system $\mathcal{D}$, we model the forward prediction function f. Let $\boldsymbol{w} \in \mathrm{Sol}(\mathcal{D})$. The input to f is a collection of k snapshots at times $t - k, \ldots, t - 1$ denoted $\boldsymbol{w}_{t-i} \in \mathcal{F}_d$. The prediction function $f \colon \mathcal{F}_d^k \to \mathcal{F}_d$ is defined $f(\boldsymbol{w}_{t-k}, \ldots, \boldsymbol{w}_{t-1}) = \boldsymbol{w}_t$. It predicts the solution at a time t based on the solution in the past. Let G be a symmetry group of $\mathcal{D}$. Then for $g \in G$, $g(\boldsymbol{w})$ is also a solution of $\mathcal{D}$. Thus $f(g\boldsymbol{w}_{t-k}, \ldots, g\boldsymbol{w}_{t-1}) = g\boldsymbol{w}_t$. Consequently, f is G-equivariant.

2.4 Symmetries of Navier-Stokes equations

The Navier-Stokes equations are invariant under the following five different transformations. Individually each of these types of transformations generates a group of symmetries of the system. The full list of symmetry groups of NS equations and Heat equations are shown in Appendix B.6.

- Space translation: $T_{\boldsymbol{c}}^{\mathrm{sp}} \boldsymbol{w}(\boldsymbol{x}, t) = \boldsymbol{w}(\boldsymbol{x} - \boldsymbol{c}, t), \;\; \boldsymbol{c} \in \mathbb{R}^2,$
- Time translation: $T_{\tau}^{\mathrm{time}} \boldsymbol{w}(\boldsymbol{x}, t) = \boldsymbol{w}(\boldsymbol{x}, t - \tau), \;\; \tau \in \mathbb{R},$
- Uniform motion: $T_{\boldsymbol{c}}^{\mathrm{um}} \boldsymbol{w}(\boldsymbol{x}, t) = \boldsymbol{w}(\boldsymbol{x}, t) + \boldsymbol{c}, \;\; \boldsymbol{c} \in \mathbb{R}^2,$
- Rotation/Reflection: $T_R^{\mathrm{rot}} \boldsymbol{w}(\boldsymbol{x}, t) = R\boldsymbol{w}(R^{-1}\boldsymbol{x}, t), \; R \in O(2),$
- Scaling: $T_{\lambda}^{sc} \boldsymbol{w}(\boldsymbol{x}, t) = \lambda \boldsymbol{w}(\lambda \boldsymbol{x}, \lambda^2 t), \;\; \lambda \in \mathbb{R}_{>0}.$

3 Methodology

We prescribe equivariance by training within function classes containing only equivariant functions. Our models can thus be theoretically guaranteed to be equivariant up to discretization error. We incorporate equivariance into two state-of-the-art architectures for dynamics prediction, `ResNet` and `U-net` [46]. Below, we describe how we modify the convolution operation in these models for different symmetries G to form four `Equ`$_G$`-ResNet` and four `Equ`$_G$`-Unet` models.

3.1 Equivariant Networks

The key to building equivariant networks is that the composition of equivariant functions is equivariant. Hence, if the maps between layers of a neural network are equivariant, then the whole network will be equivariant. Note that both the linear maps and activation functions must be equivariant. An important consequence of this principle is that the hidden layers must also carry a G-action. Thus, the hidden layers are not collections of scalar channels, but vector-valued G-representations.

Equivariant Convolutions. Consider a convolutional layer $\mathcal{F}_{\mathbb{R}^{d_{\mathrm{in}}}} \to \mathcal{F}_{\mathbb{R}^{d_{\mathrm{out}}}}$ with kernel K from a $\mathbb{R}^{d_{\mathrm{in}}}$-field to a $\mathbb{R}^{d_{\mathrm{out}}}$-field. Let $\mathbb{R}^{d_{\mathrm{in}}}$ and $\mathbb{R}^{d_{\mathrm{out}}}$ be G-representations with action maps ρ_{in} and ρ_{out} respectively. Cohen et al. [11, Theorem 3.3] prove the network is G-equivariant if and only if

$$K(gv) = \rho_{\mathrm{out}}^{-1}(g)K(v)\rho_{\mathrm{in}}(g) \qquad \text{for all } g \in G. \tag{1}$$

A network composed of such equivariant convolutions is called a *steerable CNN*.

Equivariant `ResNet` and `U-net`. Equivariant `ResNet` architectures appear in [9; 10], and equivariant transposed convolution, a feature of `U-net`, is implemented in [47]. We prove in general that

adding skip connections to a network does not affect its equivariance with respect to linear actions and also give a condition for `ResNet` or `Unet` to be equivariant in Appendix B.2.

Relation to Data Augmentation. To improve generalization, equivariant networks offer a better performing alternative to the popular technique of data augmentation [13]. Large symmetry groups normally require augmentation with many transformed examples. In contrast, for equivariant models, we have following proposition. (See Appendix B.1 for proof.)

Proposition 1. *G-equivariant models with equivariant loss learn equally (up to sample weight) from any transformation $g(s)$ of a sample s. Thus data augmentation does not help during training.*

3.2 TIME AND SPACE TRANSLATION EQUIVARIANCE

CNNs are time translation-equivariant as long as we predict in an autoregressive manner. Convolutional layers are also naturally space translation-equivariant (if cropping is ignored). Any activation function which acts identically pixel-by-pixel is equivariant.

3.3 ROTATIONAL EQUIVARIANCE

To incorporate rotational symmetry, we model f using $\mathrm{SO}(2)$-equivariant convolutions and activations within the `E(2)-CNN` framework of Weiler and Cesa [47]. In practice, we use the cyclic group $G = C_n$ instead of $G = \mathrm{SO}(2)$ as for large enough n the difference is practically indistinguishable due to space discretization. We use powers of the regular representation $\rho = \mathbb{R}[C_n]^m$ for hidden layers. The representation $\mathbb{R}[C_n]$ has basis given by elements of C_n and C_n-action by permutation matrices. It has good descriptivity since it contains all irreducible representations of C_n, and it is compatible with any activation function applied channel-wise.

3.4 UNIFORM MOTION EQUIVARIANCE

Uniform motion is part of Galilean invariance and is relevant to all non-relativistic physics modeling. For a vector field $X \colon \mathbb{R}^2 \to \mathbb{R}^2$ and vector $c \in \mathbb{R}^2$, uniform motion transformation is adding a constant vector field to the vector field $X(v)$, $T_{\boldsymbol{c}}^{\mathrm{um}}(X)(v) = X(v) + \boldsymbol{c}, \boldsymbol{c} \in \mathbb{R}^2$. By the following corollary, proved in Appendix B.3, enforcing uniform motion equivariance as above by requiring all layers of the `CNN` to be equivariant severely limits the model.

Corollary 2. *If f is a CNN alternating between convolutions f_i and channel-wise activations σ_i and the combined layers $\sigma_i \circ f_i$ are uniform motion equivariant, then f is affine.*

To overcome this limitation, we relax the requirement by conjugating the model with shifted input distribution. For each sliding local block in each convolutional layer, we shift the mean of input tensor to zero and shift the output back after convolution and activation function per sample. In other words, if the input is $\boldsymbol{\mathcal{P}}_{b \times d_{in} \times s \times s}$ and the output is $\boldsymbol{\mathcal{Q}}_{b \times d_{out}} = \sigma(\boldsymbol{\mathcal{P}} \cdot K)$ for one sliding local block, where b is batch size, d is number of channels, s is the kernel size, and K is the kernel, then

$$\boldsymbol{\mu}_i = \mathrm{Mean}_{jkl}\left(\boldsymbol{\mathcal{P}}_{ijkl}\right); \quad \boldsymbol{\mathcal{P}}_{ijkl} \mapsto \boldsymbol{\mathcal{P}}_{ijkl} - \boldsymbol{\mu}_i; \quad \boldsymbol{\mathcal{Q}}_{ij} \mapsto \boldsymbol{\mathcal{Q}}_{ij} + \boldsymbol{\mu}_i. \tag{2}$$

This will allow the convolution layer to be equivariant with respect to uniform motion. If the input is a vector field, we apply this operation to each element.

Proposition 3. *A residual block $f(\boldsymbol{x}) + \boldsymbol{x}$ is uniform motion equivariant if the residual connection f is uniform motion invariant.*

By the proposition 3 above that is proved in Appendix B.3, within `ResNet`, residual mappings should be *invariant*, not equivariant, to uniform motion. That is, the skip connection $f^{(i,i+2)} = I$ is equivariant and the residual function $f^{(i,i+1)}$ should be invariant. Hence, for the first layer in each residual block, we omit adding the mean back to the output $\boldsymbol{\mathcal{Q}}_{ij}$. In the case of `Unet`, when upscaling, we pad with the mean to preserve the overall mean.

3.5 SCALE EQUIVARIANCE

Scale equivariance in dynamics is unique as the physical law dictates the scaling of magnitude, space and time simultaneously. This is very different from scaling in images regarding resolutions [49]. For

example, the Navier-Stokes equations are preserved under a specific scaling ratio of time, space, and velocity given by the transformation

$$T_\lambda \colon \boldsymbol{w}(\boldsymbol{x},t) \mapsto \lambda\boldsymbol{w}(\lambda\boldsymbol{x},\lambda^2 t), \tag{3}$$

where $\lambda \in \mathbb{R}_{>0}$. We implement two different approaches for scale equivariance, depending on whether we tie the physical scale with the resolution of the data.

Resolution Independent Scaling. We fix the resolution and scale the magnitude of the input by varying the discretization step size. An input $\boldsymbol{w} \in \mathcal{F}_{\mathbb{R}^2}^k$ with step size $\Delta_x(\boldsymbol{w})$ and $\Delta_t(\boldsymbol{w})$ can be scaled $\boldsymbol{w}' = T_\lambda^{sc}(\boldsymbol{w}) = \lambda\boldsymbol{w}$ by scaling the magnitude of vector alone, provided the discretization constants are now assumed to be $\Delta_x(\boldsymbol{w}') = 1/\lambda\Delta_x(\boldsymbol{w})$ and $\Delta_t(\boldsymbol{w}') = 1/\lambda^2\Delta_t(\boldsymbol{w})$. We refer to this as *magnitude* equvariance hereafter.

To obtain magnitude equivariance, we divide the input tensor by the MinMax scaler (the maximum of the tensor minus the minimum) and scale the output back after convolution and activation per sliding block. We found that the standard deviation and mean L2 norm may work as well but are not as stable as the MinMax scaler. Specifically, using the same notation as in Section 3.4,

$$\boldsymbol{\sigma}_i = \text{MinMax}_{jkl}\left(\boldsymbol{\mathcal{P}}_{ijkl}\right); \quad \boldsymbol{\mathcal{P}}_{ijkl} \mapsto \boldsymbol{\mathcal{P}}_{ijkl}/\boldsymbol{\sigma}_i; \quad \boldsymbol{\mathcal{Q}}_{ij} \mapsto \boldsymbol{\mathcal{Q}}_{ij} \cdot \boldsymbol{\sigma}_i. \tag{4}$$

Resolution Dependent Scaling. If the physical scale of the data is fixed, then scaling corresponds to a change in resolution and time step size. To achieve this, we replace the convolution layers with group correlation layers over the group $G = (\mathbb{R}_{>0}, \cdot) \ltimes (\mathbb{R}^2, +)$ of scaling and translations. In convolution, we translate a kernel K across an input $\boldsymbol{w}$ as such $\boldsymbol{v}(\boldsymbol{p}) = \sum_{\boldsymbol{q}\in\mathbb{Z}^2} \boldsymbol{w}(\boldsymbol{p}+\boldsymbol{q})K(\boldsymbol{q})$. The G-correlation upgrades this operation by both translating *and* scaling the kernel relative to the input,

$$\boldsymbol{v}(\boldsymbol{p},s,\mu) = \sum_{\lambda\in\mathbb{R}_{>0}, t\in\mathbb{R}, \boldsymbol{q}\in\mathbb{Z}^2} \mu\boldsymbol{w}(\boldsymbol{p}+\mu\boldsymbol{q}, \mu^2 t, \lambda)K(\boldsymbol{q},s,t,\lambda), \tag{5}$$

where s and t denote the indices of output and input channels respectively. We add an axis to the tensors corresponding the scale factor μ. Note that we treat the channel as a time dimension both with respective to our input and scaling action. As a consequence, as the number of channels increases in the lower layers of `Unet` and `ResNet`, the temporal resolution increases, which is analogous to temporal refinement in numerical methods [23; 30]. For the input $\tilde{\boldsymbol{w}}$ of first layer where $\tilde{\boldsymbol{w}}$ has no levels originally, $\boldsymbol{w}(p,s,\lambda) = \lambda\tilde{\boldsymbol{w}}(\lambda p, \lambda^2 s)$.

Our model builds on the methods of Worrall and Welling [49], but with important adaptations for the physical domain. Our implementation of group correlation equation 5 directly incorporates the physical scaling law equation 3 of the system equation $\mathcal{D}_{\text{NS}}$. This affects time, space, and magnitude. (For heat, we drop the magnitude scaling.) The physical scaling law dictates our model should be equivariant to both up and down scaling and by any $\lambda \in \mathbb{R}_{>0}$. Practically, the sum is truncated to 7 different $1/3 \le \lambda \le 3$ and discrete data is continuously indexed using interpolation. Note equation 3 demands we scale *anisotropically*, i.e. differently across time and space. Our implementation uses antialiased rescaling as a composite of Gaussian blur and dilation. Dilation is the internal padding of conv kernels, $\sum_{a,b} I(x-ad, y-bd)K(a,b)$, where d is the dilation factor and I is the input tensor.

4 RELATED WORK

Equivariance and Invariance. Developing neural nets that preserve symmetries has been a fundamental task in image recognition [12; 47; 9; 7; 28; 26; 3; 50; 10; 19; 48; 16; 41]. But these models have never been applied to forecasting physical dynamics. Jaiswal et al. [22]; Moyer et al. [36] proposed approaches to find representations of data that are invariant to changes in specified factors, which is different from our physical symmetries. Ling et al. [29] and Fang et al. [17] studied tensor invariant neural networks to learn the Reynolds stress tensor while preserving Galilean invariance, and Mattheakis et al. [33] embedded even/odd symmetry of a function and energy conservation into neural networks to solve differential equations. But these two papers are limited to fully connected neural networks. Sosnovik et al. [42] extend Worrall and Welling [49] to group correlation convolution. But these two papers are limited to 2D images and are not magnitude equivariant, which is still inadequate for fluid dynamics. Bekkers [4] describes principles for endowing a neural architecture with invariance with respect to a Lie group.

Physics-informed Deep Learning.   Deep learning models have been used often to model physical dynamics. For example, Wang et al. [46] unified the CFD technique and U-net to generate predictions with higher accuracy and better physical consistency. Kim and Lee [24] studied unsupervised generative modeling of turbulent flows but the model is not able to make real time future predictions given the historic data. Anderson et al. [1] designed rotationally covariant neural network for learning molecular systems. Raissi et al. [39; 40] applied deep neural networks to solve PDEs automatically but these approaches require explicit input of boundary conditions during inference, which are generally not available in real-time. Mohan et al. [34] proposed a purely data-driven DL model for turbulence, but the model lacks physical constraints and interpretability. Wu et al. [51] and Beucler et al. [5] introduced statistical and physical constraints in the loss function to regularize the predictions of the model. However, their studies only focused on spatial modeling without temporal dynamics. Morton et al. [35] incorporated Koopman theory into a encoder-decoder architecture but did not study the symmetry of fluid dynamics.

Video Prediction.   Our work is also related to future video prediction. Conditioning on the observed frames, video prediction models are trained to predict future frames, e.g., [32; 18; 52; 45; 38; 18]. Many of these models are trained on natural videos with complex noisy data from unknown physical processes. Therefore, it is difficult to explicitly incorporate physical principles into these models. Our work is substantially different because we do not attempt to predict object or camera motions.

5 Experiments

We test our models on Rayleigh-Bénard convection and ocean dynamics. We also evaluate on diffusion systems with similar results, see Appendix C. Additional implementation details and a detailed description of energy spectrum error can be found in Appendices D and B.7.

Evaluation Metrics.   Our goal is to show that adding symmetry improves both the accuracy and physical consistency of predictions. For accuracy, we use Root Mean Square Error (RMSE) of forward predictions from the ground truth over all pixels. For physical consistency, we calculate the Energy Spectrum Error (ESE) which is the RMSE regarding the log of energy spectrum. ESE can indicate whether the predictions preserve the correct statistical distribution and obey the energy conservation law, which is a critical metric for physical consistency.

Experimental Setup.   `ResNet` and `U-net` are the best-performing models for our tasks [46] and well-suited for our equivariance techniques. Thus, we implemented these two convolutional architectures equipped with four different symmetries, which we name `Equ-ResNet(U-net)`. We use rolling windows to generate sequences with step size 1 for RBC data and step size 3 for ocean data. All models predict raw velocity/temperature fields up to 10 steps autoregressively using the MSE loss function that accumulates the forecasting errors. We use 60%-20%-20% training-validation-test split across time and report the averages of prediction errors over five runs.

5.1 Experiments on Simulated Rayleigh-Bénard Convection Dynamics

Data Description. Rayleigh-Bénard Convection occurs in a horizontal layer of fluid heated from below and is a major feature of the El Niño dynamics. The dataset comes from two-dimensional turbulent flow simulated using the Lattice Boltzmann Method [8] with Rayleigh number 2.5×10^8. We divide each 1792×256 image into 7 square subregions of size 256×256, then downsample to 64×64 pixels. To test the models' generalization ability, we generate additional four test sets : 1) *UM*: added random vectors drawn from $U(-1, 1)$; 2) *Mag*: multiplied by random values sampled from $U(0, 2)$; 3) *Rot*: randomly rotated by the multiples of $\pi/2$; 4) *Scale*: scaled by λ sampled from $U(1/5, 2)$. Due to lack of a fixed reference frame, real-world data would be transformed relative to training data. We use transformed data to mimic this scenario.

Prediction Performance. Table 1 shows the RMSE and ESE of predictions on the original and four transformed test sets by the non-equivariant `ResNet(Unet)` and four `Equ-ResNets(Unets)`. `Augm` is `ResNet(Unet)` trained on the augmented training set with additional samples with random transformations applied from the relevant symmetry group. Each column contains the prediction errors by the non-equivariant and equivariant models on each test set. On the original test set, all models have similar RMSE, yet the equivariant models have lower ESE. This demonstrates that incorporating symmetries into convolutional layers preserves the representation powers of CNNs and even improves models' physical consistency.

Table 1: The RMSE and ESE of the `ResNet(Unet)` and four `Equ-ResNets(Unets)` predictions on the original and four transformed test sets of Rayleigh-Bénard Convection. `Augm` is `ResNet(Unet)` trained on the augmented training set with additional samples applied with random transformations from the relevant symmetry group. Each column contains all models' prediction errors on the original test set and four different transformed test sets.

	Root Mean Square Error(10^3)					Energy Spectrum Errors				
	Orig	*UM*	*Mag*	*Rot*	*Scale*	*Orig*	*UM*	*Mag*	*Rot*	*Scale*
ResNet	0.67±0.24	2.94±0.84	4.30±1.27	3.46±0.39	1.96±0.16	0.46±0.19	0.56±0.29	0.26±0.14	1.59±0.42	4.32±2.33
Augm		1.10±0.20	1.54±0.12	0.92±0.09	1.01±0.11		1.37±0.02	1.14±0.32	1.92±0.21	1.55±0.14
Equ$_{UM}$	0.71±0.26	**0.71±0.26**				0.33±0.11	**0.33±0.11**			
Equ$_{Mag}$	0.69±0.24		**0.67±0.14**			0.34±0.09		**0.19±0.02**		
Equ$_{Rot}$	**0.65±0.26**			**0.76±0.02**		0.31±0.06			**1.23±0.04**	
Equ$_{Scal}$	0.70±0.02				**0.85±0.09**	0.44±0.22				**0.68±0.26**
U-net	0.64±0.24	2.27±0.82	3.59±1.04	2.78±0.83	1.65±0.17	0.50±0.04	0.34±0.10	0.55±0.05	0.91±0.27	4.25±0.57
Augm		0.75±0.28	1.33±0.33	0.86±0.04	1.11±0.07		0.96±0.23	0.44±0.21	1.24±0.04	1.47±0.11
Equ$_{UM}$	0.68±0.26	**0.71±0.24**				0.23±0.06	**0.14±0.05**			
Equ$_{Mag}$	0.67±0.11		**0.68±0.14**			0.42±0.04		**0.34±0.06**		
Equ$_{Rot}$	0.68±0.25			**0.74±0.01**		**0.11±0.02**			**1.16±0.05**	
Equ$_{Scal}$	0.69±0.13				**0.90±0.25**	0.45±0.32				**0.89±0.29**

Figure 1: The ground truth and the predicted velocity norm fields $\|w\|_2$ at time step 1, 5 and 10 by the `ResNet` and four `Equ-ResNets` on the four transformed test samples. The first column is the target, the second is `ResNet` predictions, and the third is predictions by `Equ-ResNets`.

On the transformed test sets, we can see that `ResNet(Unet)` fails, while `Equ-ResNets(Unets)` performs even much better than `Augm-ResNets(Unets)`. This demonstrates the value of equivariant models over data augmentation for improving generalization. Figure 1 shows the ground truth and the predicted velocity fields at time step 1, 5 and 10 by the `ResNet` and four `Equ-ResNets` on the four transformed test samples.

In order to evaluate models' generalization ability with respect to the extent of distributional shift, we created additional test sets with different scale factors from $\frac{1}{5}$ to 1. Figure 2 shows `ResNet` and Equ$_{Scal}$-`ResNet` prediction RMSEs (left) and ESEs (right) on the test sets upscaled by different factors. We observed that Equ$_{Scal}$-`ResNet` is very robust across various scaling factors while `ResNet` does not generalize. We also compare `ResNet` and `Equ-ResNet` when both train and test sets have random transformations from the relevant symmetry group applied to each sample. This mimics real-world data in which each sample has unknown reference frame. Table 2 shows `Equ-ResNet` outperforms `ResNet` on average by 34% RMSE and 40% ESE. `Equ-ResNet` is more sample efficient as it does not require data augmentation.

Table 2: Performance on transformed train and test sets.

	RMSE	ESE
ResNet	1.03±0.05	0.96±0.10
Equ$_{UM}$	**0.69±0.01**	**0.35±0.13**
ResNet	1.50±0.02	0.55±0.11
Equ$_{Mag}$	**0.75±0.04**	**0.39±0.02**
ResNet	1.18±0.05	1.21±0.04
Equ$_{Rot}$	**0.77±0.01**	**0.68±0.01**
ResNet	0.92±0.01	1.34±0.07
Equ$_{Scal}$	**0.74±0.03**	**1.02±0.02**

5.2 EXPERIMENTS ON REAL WORLD OCEAN DYNAMICS

Data Description. We use reanalysis ocean current velocity data generated by the NEMO ocean engine [31].[1] We selected an area from each of the Atlantic, Indian and North Pacific Oceans from

---

[1]The data are available at `https://resources.marine.copernicus.eu/?option=com_csw&view=details&product_id=GLOBAL_ANALYSIS_FORECAST_PHY_001_024`

Figure 2: Left: Prediction RMSE and ESE over five runs of `ResNet` and `Equ_Scal-ResNet` on the Rayleigh-Bénard Convection test set upscaled by different factors. Right: The ground truth and predicted ocean currents $\|\boldsymbol{w}\|_2$ by `ResNet` and four `Equ-ResNets` on the test set of future time.

01/01/2016 to 08/18/2017 and extracted 64×64 sub-regions for our experiments. The corresponding latitude and longitude ranges for the selected regions are (-44∼-23, 25∼46), (55∼76, -39∼-18) and (-174∼-153, 5∼26) respectively. We not only test all models on the future data but also on a different domain (-180∼-159, -40∼-59) in South Pacific Ocean from 01/01/2016 to 12/15/2016.

Prediction Performance. Table 3 shows the RMSE and ESE of ocean current predictions on test sets with different time range and domain from the training set. All the equivariant models outperform the non-equivariant baseline on RMSE, and `Equ_Scal-ResNet` achieves the lowest RMSE. For ESE, only the `Equ_Mag-ResNet(Unet)` is worse than the baseline. Also, it is remarkable that the `Equ_Rot` models have significantly lower ESE than others, suggesting they correctly learn the statistical distribution of ocean currents.

Figure 2 shows the ground truth and the predicted ocean currents at time step 5 and 10 by the non-equivariant `ResNet(Unet)` and `Equ-ResNets(Unets)`. We see that equivariant models' predictions are more accurate than the baselines. Thus, incorporating symmetry

Table 3: The prediction RMSEs and ESEs on two ocean currents test sets.

	RMSE		ESE	
	$Test_{time}$	$Test_{domain}$	$Test_{time}$	$Test_{domain}$
ResNet	0.71±0.07	0.72±0.04	0.83±0.06	0.75±0.11
Equ_UM	0.68±0.06	0.68±0.16	0.75±0.06	0.73±0.08
Equ_Mag	0.66±0.14	0.68±0.11	0.84±0.04	0.85±0.14
Equ_Rot	0.69±0.01	0.70±0.08	0.43±0.15	**0.28±0.20**
Equ_Scal	**0.63±0.02**	0.68±0.21	0.44±0.05	0.42±0.12
U-net	0.70±0.13	0.73±0.10	0.77±0.12	0.73±0.07
Equ_UM	0.66±0.10	0.67±0.03	0.73±0.03	0.82±0.13
Equ_Mag	0.63±0.08	**0.66±0.09**	0.74±0.05	0.79±0.04
Equ_Rot	0.68±0.05	0.69±0.02	**0.42±0.02**	0.47±0.07
Equ_Scal	0.65±0.09	0.69±0.05	0.45±0.13	0.43±0.05

into deep learning models can improve prediction accuracy of ocean currents. The most recent work on this dataset is de Bezenac et al. [15], which combines a warping scheme and a `U-net` to predict temperature. Since our models can also be applied to advection-diffusion systems, we investigate the task of ocean temperature field predictions. We observe that `Equ_UM-Unet` (RMSE: 0.37) performs slightly better than de Bezenac et al. [15] (RMSE: 0.38). A full results table is in Appendix E.

6 CONCLUSION AND FUTURE WORK

We develop methods to improve the generalization of deep sequence models for learning physical dynamics. We incorporate various symmetries by designing equivariant neural networks and demonstrate their superior performance on 2D time series prediction both theoretically and experimentally. Our designs obtain improved physical consistency for predictions. In the case of transformed test data, our models generalize significantly better than their non-equivariant counterparts. Importantly, all of our equivariant models can be combined and can be extended to 3D cases. The group G also acts on the boundary conditions and external forces of a system $\mathcal{D}$. If these are G-invariant, then the system $\mathcal{D}$ is strictly invariant as in Section 2.3. If not, one must consider a family of solutions $\cup_{g \in G} \mathrm{Sol}(g\mathcal{D})$ to retain equivariance. To the best of our best knowledge, there does not exist a single model with equivariance to the full symmetry group of the Navier-Stokes equations. It is possible but non-trivial, and we continue to work on combining different equivariances. Future work also includes speeding up the the scale-equivariant models and incorporating other symmetries into DL models.

REFERENCES

[1] Brandon Anderson, Truong-Son Hy, and Risi Kondor. Cormorant: Covariant molecular neural networks. In *Advances in neural information processing systems (NeurIPS)*, 2019.

[2] John David Anderson and J Wendt. *Computational fluid dynamics*, volume 206. Springer, 1995.

[3] Erkao Bao and Linqi Song. Equivariant neural networks and equivarification. *arXiv preprint arXiv:1906.07172*, 2019.

[4] Erik J Bekkers. B-spline cnns on lie groups. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1gBhkBFDH.

[5] Tom Beucler, Michael Pritchard, Stephan Rasp, Pierre Gentine, Jordan Ott, and Pierre Baldi. Enforcing analytic constraints in neural-networks emulating physical systems. *arXiv preprint arXiv:1909.00912*, 2019.

[6] Tian Qi Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *Advances in neural information processing systems*, pages 6571–6583, 2018.

[7] Benjamin Chidester, Minh N. Do, and Jian Ma. Rotation equivariance and invariance in convolutional neural networks. *arXiv preprint arXiv:1805.12301*, 2018.

[8] Dragos Bogdan Chirila. *Towards lattice Boltzmann models for climate sciences: The GeLB programming language with applications*. PhD thesis, University of Bremen, 2018.

[9] Taco S. Cohen and Max Welling. Group equivariant convolutional networks. In *International conference on machine learning (ICML)*, pages 2990–2999, 2016.

[10] Taco S. Cohen and Max Welling. Steerable CNNs. *arXiv preprint arXiv:1612.08498*, 2016.

[11] Taco S Cohen, Mario Geiger, and Maurice Weiler. A general theory of equivariant cnns on homogeneous spaces. In *Advances in Neural Information Processing Systems*, pages 9142–9153, 2019.

[12] Taco S. Cohen, Maurice Weiler, Berkay Kicanaoglu, and Max Welling. Gauge equivariant convolutional networks and the icosahedral CNN. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, volume 97, pages 1321–1330, 2019.

[13] Tri Dao, Albert Gu, Alexander J Ratner, Virginia Smith, Christopher De Sa, and Christopher Ré. A kernel theory of modern data augmentation. *Proceedings of machine learning research*, 97:1528, 2019.

[14] Richard H. Day. Complex economic dynamics-vol. 1: An introduction to dynamical systems and market mechanisms. *MIT Press Books*, 1, 1994.

[15] Emmanuel de Bezenac, Arthur Pajot, and Patrick Gallinari. Deep learning for physical processes: Incorporating prior scientific knowledge. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=By4HsfWAZ.

[16] Sander Dieleman, Jeffrey De Fauw, and Koray Kavukcuoglu. Exploiting cyclic symmetry in convolutional neural networks. In *International Conference on Machine Learning (ICML)*, 2016.

[17] Rui Fang, David Sondak, Pavlos Protopapas, and Sauro Succi. Deep learning for turbulent channel flow. *arXiv preprint arXiv:1812.02241*, 2018.

[18] Chelsea Finn, Ian Goodfellow, and Sergey Leine. Unsupervised learning for physical interaction through video prediction. In *Advances in neural information processing systems*, pages 64–72, 2016.

[19] Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data. *arXiv preprint arXiv:2002.12880*, 2020.

[20] Herbert W Hethcote. The mathematics of infectious diseases. *SIAM review*, 42(4):599–653, 2000.

[21] Eugene M. Izhikevich. *Dynamical systems in neuroscience*. MIT press, 2007.

[22] Ayush Jaiswal, Daniel Moyer, Greg Ver Steeg, Wael AbdAlmageed, and Premkumar Natarajan. Invariant representations through adversarial forgetting. *arXiv preprint arXiv:1911.04060*, 2019.

[23] Ihn S Kim and Wolfgang JR Hoefer. A local mesh refinement algorithm for the time domain-finite difference method using maxwell's curl equations. *IEEE Transactions on Microwave Theory and Techniques*, 38(6):812–815, 1990.

[24] Junhyuk Kim and Changhoon Lee. Deep unsupervised learning of turbulence for inflow generation at various Reynolds numbers. *Journal of Computational Physics*, page 109216, 2020.

[25] Anthony W. Knapp. *Lie Groups Beyond an Introduction*, volume 140 of *Progress in Mathematics*. Birkhäuser, Boston, 2nd edition, 2002.

[26] Risi Kondor and Shubhendu Trivedi. On the generalization of equivariance and convolution in neural networks to the action of compact groups. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, volume 80, pages 2747–2755, 2018.

[27] Serge Lang. *Algebra*. Springer, Berlin, 3rd edition, 2002.

[28] Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 991–999, 2015.

[29] Julia Ling, Andrew Kurzawskim, and Jeremy Templeton. Reynolds averaged turbulence modeling using deep neural networks with embedded invariance. *Journal of Fluid Mechanics*, 2017.

[30] Vadim Lisitsa, Galina Reshetova, and Vladimir Tcheverda. Finite-difference algorithm with local time-space grid refinement for simulation of waves. *Computational geosciences*, 16(1): 39–54, 2012.

[31] Gurvan Madec et al. NEMO ocean engine, 2015. Technical Note. Institut Pierre-Simon Laplace (IPSL), France. https://epic.awi.de/id/eprint/39698/1/NEMO_book_v6039.pdf.

[32] Michael Mathieu, Camille Couprie, and Yann LeCun. Deep multi-scale video prediction beyond mean square error. *arXiv preprint arXiv:1511.05440*, 2015.

[33] Marios Mattheakis, Pavlos Protopapas, D. Sondak, Marco Di Giovanni, and Efthimios Kaxiras. Physical symmetries embedded in neural networks. *arXiv preprint arXiv:1904.08991*, 2019.

[34] Arvind Mohan, Don Daniel, Michael Chertkov, and Daniel Livescu. Compressed convolutional LSTM: An efficient deep learning framework to model high fidelity 3D turbulence. *arXiv preprint arXiv:1903.00033*, 2019.

[35] Jeremy Morton, Antony Jameson, Mykel J. Kochenderfer, and Freddie Witherden. Deep dynamical modeling and control of unsteady fluid flows. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[36] Daniel Moyer, Shuyang Gao, Rob Brekelmans, Aram Galstyan, and Greg Ver Steeg. Invariant representations without adversarial training. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 9084–9093, 2018.

[37] Peter J. Olver. *Applications of Lie groups to differential equations*, volume 107. Springer Science & Business Media, 2000.

[38] Sergiu Oprea, P. Martinez-Gonzalez, A. Garcia-Garcia, John Alejandro Castro-Vargas, S. Orts-Escolano, J. Garcia-Rodriguez, and Antonis A. Argyros. A review on deep learning techniques for video prediction. *ArXiv*, abs/2004.05214, 2020.

[39] Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Physics informed deep learning (part I): Data-driven solutions of nonlinear partial differential equations. *arXiv preprint arXiv:1711.10561*, 2017.

[40] Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019.

[41] Anupam K. Gupta Rohan Ghosh. Scale steerable filters for locally scale-invariant convolutional neural networks. *arXiv preprint arXiv:1906.03861*, 2019.

[42] Ivan Sosnovik, Michał Szmaja, and Arnold Smeulders. Scale-equivariant steerable networks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=HJgpugrKPS.

[43] Steven H. Strogatz. *Nonlinear dynamics and chaos: with applications to physics, biology, chemistry, and engineering*. CRC press, 2018.

[44] Jonathan Tompson, Kristofer Schlachter, Pablo Sprechmann, and Ken Perlin. Accelerating Eulerian fluid simulation with convolutional networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, volume 70, pages 3424–3433, 2017.

[45] Ruben Villegas, Jimei Yang, Seunghoon Hong, Xunyu Lin, and Honglak Lee. Decomposing motion and content for natural video sequence prediction. In *International Conference on Learning Representations (ICLR)*, 2017.

[46] Rui Wang, Karthik Kashinath, Mustafa Mustafa, Adrian Albert, and Rose Yu. Towards physics-informed deep learning for turbulent flow prediction. *arXiv preprint arXiv:1911.08655*, 2019.

[47] Maurice Weiler and Gabriele Cesa. General E(2)-equivariant steerable CNNs. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 14334–14345, 2019.

[48] Maurice Weiler, Fred A. Hamprecht, and Martin Storath. Learning steerable filters for rotation equivariant CNNs. *Computer Vision and Pattern Recognition (CVPR)*, 2018.

[49] Daniel Worrall and Max Welling. Deep scale-spaces: Equivariance over scale. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 7364–7376, 2019.

[50] Daniel E Worrall, Stephan J Garbin, Daniyar Turmukhambetov, and Gabriel J Brostow. Harmonic networks: Deep translation and rotation equivariance. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5028–5037, 2017.

[51] Jin-Long Wu, Karthik Kashinath, Adrian Albert, Dragos Chirila, Prabhat, and Heng Xiao. Enforcing statistical constraints in generative adversarial networks for modeling chaotic dynamical systems. *Journal of Computational Physics*, page 109209, 2019.

[52] Tianfan Xue, Jiajun Wu, Katherine Bouman, and Bill Freeman. Visual dynamics: Probabilistic future frame synthesis via cross convolutional networks. In *Advances in neural information processing systems (NeurIPS)*, pages 91–99, 2016.