Tackling the Noisy Elephant in the Room: Label Noise-robust Out-of-Distribution Detection via Loss Correction and Low-rank Decomposition

Abstract

Robust out-of-distribution (OOD) detection is an indispensable component of modern artificial intelligence (AI) systems, especially in safety-critical applications where models must identify inputs from unfamiliar classes not seen during training. While OOD detection has been extensively studied—with both post hoc and training-based approaches—its effectiveness under noisy training labels remains underexplored. Recent studies suggest that label noise can significantly degrade OOD performance, yet principled solutions are lacking. In this work, we demonstrate that directly combining existing label noise-robust methods with OOD detection strategies is insufficient to address this critical challenge. To overcome this, we propose a *robust* OOD detection framework designed to *cleanse* feature embeddings, thereby mitigating the adverse effects of noisy labels on OOD performance. Towards this, we introduce an end-to-end training strategy that integrates loss correction methods from the noisy-label learning literature with low-rank and sparse decomposition techniques from signal processing. Building on this strategy, we derive a novel metric that quantifies the "OOD-ness" content within training data, which in turn leads to a label noise-robust OOD detection scoring technique. Extensive experiments on both synthetic and real-world datasets demonstrate that our method significantly outperforms the state-of-the-art OOD detection techniques, particularly under severe noisy label settings.

1 Introduction

Artificial intelligence (AI) models have achieved remarkable performance across a myriad of domains including computer vision and natural language processing. Yet, a persistent challenge arises in real-world deployment: these models often fail to recognize inputs from unfamiliar data distributions, leading to overly confident and potentially misleading predictions (Goodfellow et al., 2014). This limitation underscores the importance of out-of-distribution (OOD) detection for building trustworthy AI systems, particularly in high-stakes domains such as autonomous driving (Geiger et al., 2012) and medical diagnostics (Schlegl et al., 2017). The goal of OOD detection is not only to provide accurate prediction on seen data distributions but also to flag inputs from novel or unobserved distributions (Hendrycks & Gimpel, 2016).

OOD detection has been an active topic of research in the field of AI for many decades; a recent survey can be found in (Yang et al., 2024). A key focus in this field is detecting semantic shifts—scenarios where new, previously unseen classes appear in the test data, resulting in a mismatch between the label spaces of in-distribution (ID) and OOD samples. A wide range of methods have been proposed for OOD detection, including softmax/logit-based post-hoc techniques (Hendrycks & Gimpel, 2016; Liang et al., 2018; Hendrycks et al., 2022; Sun & Li, 2022; Sun et al., 2021; Dong et al., 2022) and feature distance-based strategies (Lee et al., 2018; Sun et al., 2022; Ming et al., 2023; Sehwag et al., 2021; Ghosal et al., 2024). As softmax/logit-based approaches are often susceptible to overconfidence, recent research has increasingly focused on distance-based methods—such as Mahalanobis distance (Lee et al., 2018) and k-nearest neighbors (kNN) (Sun et al., 2022)—due to their empirical success. These methods rely on the observation that feature representations extracted from OOD samples typically lie farther from the ID feature space. Since deep

neural networks naturally encode semantic similarity in their embeddings—forming well-structured clusters for similar samples—distance-based approaches leverage this structure to better separate ID and OOD samples. Nonetheless, most of these methods are developed under the assumption that models are trained on *clean, correctly* labeled data. However, in practice, training datasets often contain noisy labels, stemming from the scarcity of expert annotators and the high cost of accurate label acquisition (Buhrmester et al., 2016). Recent empirical studies have brought serious attention to this issue, revealing that label noise can significantly degrade the performance of state-of-the-art OOD detection methods (Humblot-Renaux et al., 2024). This highlights a critical gap in current research and underscores the need to develop robust OOD detection frameworks that remain reliable under real-world label noise.

The effect of label noise on training deep learning models has been extensively studied in recent years; see the survey (Song et al., 2022). It is now well-established that training deep neural network (DNN) models with noisy labels can severely degrade classification performance, leading to poor generalization and overfitting (Arpit et al., 2017; Zhang et al., 2016). To address this, a variety of label noise-robust methods have been proposed, including loss correction strategies such as probabilistic modeling techniques (Liu & Tao, 2016; Patrini et al., 2017; Li et al., 2021b; Xia et al., 2020; Yang et al., 2021; Cheng et al., 2020), robust loss function designs (Zhang & Sabuncu, 2018a; Lyu & Tsang, 2019; Wang et al., 2019a), and in-built sample selection strategies (Jiang et al., 2018; Yu et al., 2019; Nguyen et al., 2019; Han et al., 2018a; Li et al., 2020b). However, most of these methods are designed and evaluated primarily for ID classification, and their effectiveness in OOD detection when the training labels are noisy remains largely unclear. Recent works have begun to examine related aspects of the role of labels in OOD detection, including intentionally introducing label noise for OOD filtering (Geng et al., 2025) and analyzing the importance of label information for OOD detection (Yang et al., 2025). Nevertheless, a systematic understanding of how noisy ID training labels affect OOD detection performance, and how to design methods that are robust to this setting, remains largely underexplored. The key challenge lies in the misalignment of objectives: while label noise-robust methods aim to correct the prediction probabilities within the training distribution, OOD detection requires learning discriminative feature representations to detect samples that do not belong to the training distribution. Hence, most existing label-noise approaches exhibit poor OOD detection performance when applied directly, as we demonstrate in detail in subsequent sections.

Our Contributions. In this work, we investigate the critical challenge of robust OOD detection in the presence of noisy labels in the training set. Unlike existing studies that focus solely on the empirical limitations of current OOD detection methods (Humblot-Renaux et al., 2024), we identify a key gap: the label noise-robust methods improve generalization under noisy supervision for classification settings, yet they are largely ineffective when directly applied for OOD detection. To address this limitation, we make the following key contributions:

- *Robust OOD detection framework.* We propose a novel distance-based OOD detection framework that effectively cleanses feature embeddings, enhancing robustness under noisy training labels. Our framework is accompanied by an easy-to-implement, end-to-end learning criterion, leveraging loss correction techniques and low-rank and sparse decomposition strategies.
- *Novel OOD-detection scoring.* The framework allows us to quantify the "OOD-ness" content of each training sample, producing a score that reflects its difficulty in training the OOD detector. Leveraging this score, we introduce an enhanced distance-based scoring function that is more robust compared to existing metrics.
- *Promising empirical evidence for OOD detection.* We conduct extensive experiments using synthetic noise settings and several real-world noisy datasets, e.g., CIFAR-10N, CIFAR-100N (Wei et al., 2022), and Animal-10N (Song et al., 2019), and evaluate our approach across diverse OOD datasets. For large-scale settings, we consider synthetic noise on ImageNet-1k (Russakovsky et al., 2015) dataset. Additionally, we perform detailed ablation studies on key hyperparameters to demonstrate the robustness of our approach.

2 Problem Statement

Consider an input feature space $\mathcal{X} \subset \mathbb{R}^D$, where D denotes the dimensionality of the input features. Let the label space be defined as $\mathcal{Y} = \{1, \ldots, K\}$, corresponding to K distinct classes for the ID data. We define the

Figure 1: The upper row presents the UMAP representations of the latent feature vectors $\boldsymbol{h}(\boldsymbol{x})$ learned using the cross-entropy loss–based training on the noisily labeled dataset $\{\boldsymbol{x}_n, \widehat{y}_n\}$ for various synthetic noise rates. The clusters are more distorted for the training data, losing the ID-ness characteristics, resulting in degraded performance in OOD detection during test time. The lower row presents the corresponding kNN score histogram for the ID and OOD datasets. The false positive ratio (FPR) for OOD detection using the kNN score is also reported.

training dataset $\mathcal{D}$ as $\mathcal{D} = \{(\boldsymbol{x}_n, y_n)\}_{n=1}^N$, $\quad \boldsymbol{x}_n \in \mathcal{X}$, $\quad y_n \in \mathcal{Y}$, where $\boldsymbol{x}_n$ is the feature vector of the n-th training example, y_n is its associated *ground-truth* class label, and N denotes the total number of training samples. Each pair $(\boldsymbol{x}_n, y_n)$ is assumed to be drawn i.i.d. from an underlying joint distribution $\mathcal{P}_{\mathcal{X}\mathcal{Y}}$.

Let $\boldsymbol{h} : \mathbb{R}^D \to \mathbb{R}^L$ denote a DNN that maps each input $\boldsymbol{x}_n$ to an L-dimensional *latent feature* representation $\boldsymbol{h}(\boldsymbol{x}_n)$. For multi-class classification, we employ a projection head $\boldsymbol{c} : \mathbb{R}^L \to \mathbb{R}^K$ to produce pre-softmax logits. The overall label prediction function is $\boldsymbol{f}(\boldsymbol{x}_n) = \boldsymbol{\sigma}(\boldsymbol{c}(\boldsymbol{h}(\boldsymbol{x}_n)))$, where $\boldsymbol{\sigma}$ denotes the softmax function. We typically learn the parameters by minimizing cross-entropy (CE):

$$\text{minimize}_{\boldsymbol{\theta}} \ \mathcal{L}_{\text{CE}}(\boldsymbol{\theta}; \{\boldsymbol{x}_n, y_n\}) = -\sum_{n=1}^N \sum_{k=1}^K \mathbb{I}[y_n = k] \log(\boldsymbol{f}(\boldsymbol{x}_n)), \tag{1}$$

where $\boldsymbol{\theta}$ denotes the DNN parameters of both $\boldsymbol{h}$ and $\boldsymbol{c}$.

OOD Detection. AI systems are generally learned under the closed-world assumption, where test samples are drawn from the same distribution as the training data. However, this assumption often fails in practice, where models inevitably encounter samples outside the training distribution. These unfamiliar samples are known as OOD inputs (Hendrycks & Gimpel, 2016). In classification tasks, such distributional shift may manifest as a semantic shift, wherein some test instances originate from an *unknown* label space $\mathcal{Y}^o$, disjoint from the known label space, i.e., $\mathcal{Y} \cap \mathcal{Y}^o = \emptyset$. OOD detection can be formalized as a binary classification task:

$$\boldsymbol{g}_\tau(\boldsymbol{x}) = \begin{cases} \mathsf{ID} & \text{if } s(\boldsymbol{x}) \geq \tau, \\ \mathsf{OOD} & \text{if } s(\boldsymbol{x}) < \tau, \end{cases} \tag{2}$$

where $s(\boldsymbol{x})$ is a scoring function quantifying the likelihood of $\boldsymbol{x}$ belonging to the ID distribution, and τ is a predefined threshold. Early OOD detection methods used softmax outputs (Hendrycks & Gimpel,

2016; Liang et al., 2018) but suffered from overconfidence issues. Pre-softmax activation-based approaches (Hendrycks et al., 2022; Sun & Li, 2022; Sun et al., 2021; Dong et al., 2022) followed, though they remained sensitive to architecture. Recently, distance-based methods such as those based on Mahalanobis distance (Lee et al., 2018) and k-nearest neighbor (kNN) (Sun et al., 2022; Ming et al., 2023; Sehwag et al., 2021; Ghosal et al., 2024) have gained traction by leveraging the clusterability of latent feature representations $\boldsymbol{h}(\boldsymbol{x})$.

Learning under Label Noise. Most studies in OOD detection assume the DNN classifier $\boldsymbol{f}$ and scoring function $\boldsymbol{s}$ are learned using ground-truth labels y_n. However, the lack of access to reliable ground-truth annotations is a significant challenge—see Fig. 1, where the clusterability of latent representations $\boldsymbol{h}(\boldsymbol{x})$ is severely compromised under label noise, leading to significant degradation in ID-OOD separability for the kNN score. In scenarios where ground-truth labels y_n are difficult to obtain, we rely on their noisy counterparts $\widehat{y}_n \in \{1, \dots, K\}$. In noisy label settings, for many data items, the observed label does not match the true label, i.e., $\widehat{y}_n \neq y_n$.

> The goal of *label noise-robust OOD detection* is two-fold: *(i)* accurately classify ID samples through a well-generalized predictor $\boldsymbol{f}$, and *(ii)* reliably detect OOD instances using a robust decision function $\boldsymbol{g}_\tau$, despite learning them using the noisily labeled dataset $\widehat{\mathcal{D}} = \{(\boldsymbol{x}_n, \widehat{y}_n)\}_{n=1}^N$, $\boldsymbol{x}_n \in \mathcal{X}$, $\widehat{y}_n \in \mathcal{Y}$.

3 Proposed Approach

In this section, we present our label noise-robust OOD detection framework. Our strategy is based on *cleansing* the noise-corrupted latent feature space using an end-to-end training strategy, thereby making it robust for OOD detection at test time. Towards this goal, our framework encompasses three main components: *(i)* loss correction module, *(ii)* low-rank and sparse decomposition of the latent feature matrix, and *(iii)* robust OOD detector using distance-based metrics, e.g., kNN.

3.1 Loss Correction

As demonstrated in Fig. 1, training directly with noisy labels leads to a corrupted latent feature space. To address this, we first integrate a loss correction module to reduce the effect of label noise in the learned features. Loss correction strategies have attracted considerable attention in the noisy label learning literature. Among these, probabilistic noise modeling via *transition matrices* (Patrini et al., 2017; Tanno et al., 2019; Li et al., 2021b; Ibrahim et al., 2023) and robust loss function-based approaches (Zhang & Sabuncu, 2018a; Lyu & Tsang, 2019; Wang et al., 2019a) are particularly well-received, owing to their strong theoretical foundations and robust empirical performance in classification tasks.

In general, loss correction strategies design a modified cross-entropy loss to train the classifier $\boldsymbol{f}$ on the noisy dataset $\{\boldsymbol{x}_n, \widehat{y}_n\}$, while aiming to predict the ground-truth labels:

$$\underset{\boldsymbol{\theta}, \boldsymbol{\eta}}{\text{minimize}} \ \mathcal{L}_{\text{CE}}^{\text{mod}}(\boldsymbol{\theta}, \boldsymbol{\eta}; \{\boldsymbol{x}_n, \widehat{y}_n\}), \tag{3}$$

where $\boldsymbol{\eta}$ typically refers to additional model parameters according to specific loss designs. For instance, in transition matrix-based approaches (Patrini et al., 2017; Tanno et al., 2019; Li et al., 2021b; Ibrahim et al., 2023), $\boldsymbol{\eta}$ refers to the noise transition probabilities that learns the probabilistic label confusion matrix $\boldsymbol{T}$, whose (k, k')-th entry models the label corruption process via $[\boldsymbol{T}]_{k,k'} = \Pr(\widehat{y}_n = k | y_n = k')$. Intuitively, $\boldsymbol{T}$ describes how clean labels y_n are stochastically flipped into noisy labels $\widehat{y}_n$. The modified cross-entropy incorporates $\boldsymbol{T}$ by mapping the classifier's predicted clean-label distribution into the corresponding noisy-label distribution, so that training can directly account for and correct the effect of label noise. In sample selection approaches (Jiang et al., 2018; Yu et al., 2019; Nguyen et al., 2019; Han et al., 2018a; Li et al., 2020b), $\boldsymbol{\eta}$ instead represents sample-weighting terms that regulate the contributions of clean and noisy sample–label pairs.

Robust loss function-based methods (Zhang & Sabuncu, 2018a; Wang et al., 2019a), often do not introduce additional parameters—they directly design loss functions that are inherently less sensitive to incorrect labels. Popular approaches such as symmetric cross-entropy (SCE) (Wang et al., 2019a) and generalized

Table 1: OOD detection performance on CIFAR-10 with synthetic label noise across different OOD datasets. The top two performing algorithms (in terms of average FPR95) are highlighted in **bold**.

Method	SVHN		FashionMNIST		LSUN		iSUN		DTD/Texture		Places365		Average	
	FPR95↓	AUROC↑	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC
Noise rate = 10%														
OOD baselines														
KNN	34.23	93.92	38.51	93.57	17.71	96.66	21.72	95.93	28.58	94.04	62.26	84.62	33.84	93.12
MSP	73.54	84.82	54.92	88.64	32.84	94.49	55.18	89.70	77.02	75.86	69.01	80.33	60.42	85.64
ODIN	87.82	60.19	64.22	79.77	24.42	94.56	32.99	91.49	80.30	56.06	78.84	66.87	61.43	74.82
Energy	80.31	77.93	57.89	84.84	17.74	96.65	54.63	88.38	82.43	62.42	78.29	72.39	60.37	79.12
ReAct	96.77	53.22	63.00	87.87	49.38	90.45	72.98	81.08	92.89	44.08	75.21	75.29	75.04	72.00
Mahalanobis	31.71	91.10	72.56	74.47	28.29	93.87	52.77	81.81	49.11	80.53	94.74	44.55	54.86	77.72
CIDER	30.04	95.15	20.78	96.62	35.14	93.34	66.61	84.09	46.67	92.82	62.94	88.58	43.69	91.77
SSD+	52.65	87.82	80.75	85.52	90.05	77.82	65.24	84.64	21.60	95.72	16.22	96.88	54.42	88.07
SNN	49.71	91.73	29.72	95.06	20.96	96.25	25.36	95.23	34.26	92.53	56.29	86.46	36.05	92.88
Label noise-robust baselines														
SCE	5.97	98.96	12.60	97.80	2.93	99.44	15.62	97.01	27.16	94.28	59.64	85.79	20.66	95.55
GCE	7.81	98.50	16.20	97.33	5.88	98.96	12.03	97.92	31.63	93.56	47.83	89.35	20.23	95.94
Co-teaching	40.12	90.87	99.29	99.29	75.83	76.34	96.95	54.21	49.45	82.48	93.19	48.57	75.81	68.73
DivideMix	62.65	87.37	68.10	81.99	49.01	91.24	42.84	91.52	37.48	92.79	77.16	75.03	56.21	86.66
CM	6.14	98.90	15.80	97.05	6.03	98.91	10.40	98.12	19.08	96.47	53.54	87.17	18.50	96.10
VolMinNet	2.64	99.47	5.18	98.94	5.00	98.98	9.26	98.24	21.60	95.86	56.16	87.43	**16.64**	96.49
NOODLE (Ours)	3.51	99.28	5.03	98.97	3.31	99.33	3.05	99.22	16.61	96.78	48.02	89.62	**13.26**	**97.20**
Noise rate = 30%														
OOD baselines														
KNN	23.80	95.80	36.15	93.43	27.04	94.61	22.03	95.86	39.50	90.40	69.76	83.53	36.38	92.27
MSP	76.88	80.34	56.16	87.14	29.90	93.92	58.82	88.30	79.04	71.54	74.98	76.61	62.63	82.97
ODIN	83.79	61.60	50.70	83.57	22.26	94.83	35.64	89.98	79.68	54.97	83.19	60.62	59.21	74.26
Energy	76.67	76.82	51.45	86.81	19.38	95.65	66.77	84.97	80.89	62.95	77.32	72.32	62.08	79.92
ReAct	88.89	67.41	62.61	85.50	21.63	95.34	90.19	65.23	91.33	51.51	82.51	68.95	72.86	72.33
Mahalanobis	37.86	90.25	50.42	85.21	26.98	93.29	60.92	79.60	52.75	77.45	95.94	40.86	54.15	77.78
CIDER	90.69	65.27	60.75	79.74	96.69	48.38	90.98	66.91	75.66	76.81	70.11	79.49	78.16	69.43
SSD+	76.34	78.07	61.81	88.45	90.07	77.66	84.61	79.29	28.94	94.78	50.55	87.94	65.39	84.37
SNN	23.37	95.72	34.55	94.11	25.91	94.90	34.38	92.36	42.27	89.39	65.06	84.19	37.59	91.78
Label noise-robust baselines														
SCE	19.48	96.45	25.84	95.37	16.58	96.57	61.71	87.42	35.50	91.76	74.66	79.27	38.96	91.14
GCE	58.38	91.40	20.37	96.64	11.32	97.95	12.38	97.73	30.53	94.08	51.59	88.18	30.76	94.33
Co-teaching	50.10	83.16	99.99	20.37	96.73	64.14	97.86	41.70	53.71	79.45	93.84	48.63	82.04	56.24
DivideMix	58.39	90.07	31.17	94.93	27.86	95.59	16.38	96.64	36.28	92.76	59.28	84.34	38.22	92.44
CM	22.04	96.76	8.79	98.04	10.17	98.12	23.30	95.64	23.71	94.99	55.42	86.90	**23.90**	95.08
VolMinNet	4.99	99.04	14.01	97.09	9.48	98.33	51.23	89.68	27.84	93.44	59.25	85.42	27.80	93.84
NOODLE (Ours)	1.84	99.60	19.66	96.36	7.28	95.53	10.76	97.89	20.67	95.85	57.50	85.87	**19.62**	**95.68**
Noise rate = 50%														
OOD baselines														
KNN	65.53	85.64	37.84	93.71	30.61	93.38	45.41	89.21	43.81	89.06	74.98	79.58	49.70	88.43
MSP	96.92	53.68	80.68	77.70	47.78	89.67	67.84	83.23	82.50	68.45	81.12	73.63	76.14	74.40
ODIN	94.94	44.15	71.46	80.28	34.04	91.82	47.51	88.11	79.61	60.80	82.87	66.17	68.40	71.89
Energy	97.93	46.79	83.41	76.67	39.77	90.87	67.60	81.00	85.43	60.47	82.28	69.91	76.07	70.95
ReAct	99.19	24.75	90.11	64.20	50.47	85.45	78.12	67.79	93.79	39.56	86.40	62.25	83.02	57.33
Mahalanobis	55.77	83.12	59.93	85.98	31.23	93.54	45.17	88.63	48.90	81.70	93.28	51.47	55.71	80.74
CIDER	99.02	50.38	97.54	52.78	91.99	48.96	98.67	45.37	99.16	50.86	92.60	59.47	96.50	51.30
SSD+	83.54	77.49	76.76	76.56	83.89	76.28	86.10	73.24	62.31	81.41	42.27	88.67	72.48	78.94
SNN	71.41	83.96	68.22	87.66	53.56	89.27	63.49	80.99	56.95	85.48	82.28	77.12	65.99	84.08
Label noise-robust baselines														
SCE	14.10	97.40	42.30	90.96	25.18	94.09	67.17	80.81	51.51	84.65	70.67	77.75	45.15	87.61
GCE	19.19	96.43	29.10	95.06	22.98	95.40	53.92	86.31	48.35	87.54	65.83	83.58	39.89	90.72
Co-teaching	57.05	76.43	99.97	28.21	99.23	55.11	96.99	52.50	54.45	78.87	94.22	47.36	83.65	56.41
DivideMix	24.69	95.75	40.94	93.32	37.02	94.36	20.81	96.10	53.10	89.35	56.39	86.71	38.82	92.60
CM	17.37	96.91	21.93	95.56	17.16	96.58	39.52	92.86	30.23	93.36	61.88	84.82	**31.35**	93.35
VolMinNet	13.01	97.74	15.36	97.11	14.18	97.24	60.13	80.22	45.85	87.40	55.26	86.94	33.96	91.11
NOODLE (Ours)	6.35	98.43	17.83	96.58	7.09	98.50	32.28	93.92	30.09	92.47	70.41	81.24	**27.34**	**93.52**

cross-entropy (GCE) (Zhang & Sabuncu, 2018a) can be viewed as hybrids of CE and mean absolute error (MAE) losses, combining the favorable convergence properties of CE with the robustness of MAE against

Table 2: Average OOD detection performance on noisy real datasets. The top two performing algorithms (in terms of average FPR95) are highlighted in **bold**.

Method	CIFAR-10N												Animal-10N		CIFAR-100N	
	Clean		Worst		Agg		Rand1		Rand2		Rand3		FPR95	AUROC	FPR95	AUROC
	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC				
OOD baselines																
KNN	21.06	95.80	32.48	92.89	23.95	94.84	35.48	92.65	31.99	92.70	27.27	94.09	70.44	77.04	43.20	86.54
MSP	56.43	90.07	60.15	85.49	55.04	88.21	60.75	86.62	56.44	86.50	53.90	86.70	90.64	59.90	81.08	72.66
ODIN	33.10	92.47	45.31	86.69	43.83	89.03	49.12	86.56	46.71	84.24	41.91	87.37	76.97	62.55	71.72	76.64
Energy	39.15	92.03	47.30	87.75	56.03	87.90	54.89	87.24	50.31	86.11	42.74	88.90	75.60	74.52	78.93	51.74
ReAct	60.31	83.12	65.89	78.86	47.17	91.01	68.77	76.92	65.46	79.83	57.81	81.24	79.00	71.15	76.24	67.63
Mahalanobis	47.22	82.91	53.57	80.61	51.14	81.76	55.26	80.05	44.25	84.60	48.37	83.37	54.54	73.00	75.15	65.47
CIDER	39.33	92.49	98.35	58.92	83.54	62.71	98.32	57.88	97.59	57.59	96.48	50.41	82.64	75.09	54.01	82.50
SSD+	33.66	92.42	39.69	89.82	45.72	86.07	41.90	88.77	39.37	90.52	32.40	92.23	66.11	75.28	50.29	83.36
SNN	22.60	95.53	**30.87**	92.78	25.14	94.18	29.87	93.76	30.74	92.94	34.26	92.12	31.43	93.65	**43.15**	87.13
Label noise-robust baselines																
SCE	19.71	95.62	34.53	92.11	22.87	94.76	**22.90**	94.77	24.42	94.25	24.81	94.40	31.97	93.47	46.13	83.15
GCE	18.56	96.33	35.75	91.50	19.44	96.03	23.47	95.11	18.89	95.86	19.78	95.61	36.62	91.65	68.54	77.54
DivideMix	40.81	89.16	39.32	91.53	65.83	81.83	66.64	84.52	59.27	84.22	24.81	94.40	34.27	91.77	56.28	82.92
Co-teaching	81.94	58.15	82.14	60.68	77.98	63.71	53.42	74.23	77.59	62.76	81.94	58.15	68.47	61.72	81.68	59.61
CM	18.32	96.33	36.28	89.66	**21.22**	95.17	24.72	94.61	23.62	95.04	**20.70**	95.51	33.50	92.75	49.52	85.41
VolMinNet	**15.00**	96.89	37.52	91.60	23.37	94.96	**22.90**	95.15	**18.80**	96.15	22.19	95.02	**29.26**	94.09	56.65	81.39
NOODLE	**14.60**	96.81	**25.45**	94.71	**16.52**	96.46	**16.66**	96.42	**15.46**	96.70	**15.49**	96.50	**25.25**	95.13	**35.19**	89.52

outliers. For instance, the SCE loss function is defined as:

$$\ell_{\mathsf{SCE}}(\boldsymbol{g}, \boldsymbol{y}) = -\alpha \sum_{k=1}^{K} [\boldsymbol{y}]_k \log[\boldsymbol{g}]_k - \beta \sum_{k=1}^{K} [\boldsymbol{g}]_k \log[\boldsymbol{y}_\epsilon]_k,$$

where $\alpha, \beta > 0$ are scalars, $\boldsymbol{g} \in \mathbb{R}^K$ is a probability vector, $\boldsymbol{y} \in \{0,1\}^K$ is a one-hot label, and $\boldsymbol{y}_\epsilon$ handles the $\log 0$ cases using a small constant ϵ. The first term is the scaled CE loss, whereas the second term reduces to the MAE loss when $\epsilon = -2$ (Wang et al., 2019a).

Nonetheless, these loss correction strategies primarily operate by modifying the softmax prediction outputs of the ID samples rather than directly *correcting* their feature embeddings. However, feature embeddings are often more critical for OOD detection, particularly for distance-based OOD metrics such as kNN (Sun et al., 2022) and Mahalanobis (Lee et al., 2018). This misalignment of objectives results in suboptimal performance in mitigating the effect of label noise in OOD detection as observed in Fig. 1.

3.2 Low-rank Plus Sparse Decomposition

To overcome the limitation of loss correction modules in handling feature correction, we introduce the next key component of our framework. A critical observation underlying its design is that, in the absence of label noise, latent feature vectors naturally exhibit clustering patterns, reflecting their low-rank structure due to class-specific organization—see the first UMAP plot in Fig. 1. This intrinsic structural tendency can be explicitly leveraged during training to encourage low-rank properties in the feature representations. To this end, we adopt a low-rank and sparse decomposition strategy, drawing inspiration from classical signal processing techniques (Candès et al., 2011; Zhang et al., 2011).

Consider the latent feature matrix $\boldsymbol{H} = [\boldsymbol{h}(\boldsymbol{x}_1), \dots, \boldsymbol{h}(\boldsymbol{x}_N)] \in \mathbb{R}^{D \times N}$, where D is the feature dimension and N is the number of training samples. Our goal is to promote a low-rank structure in this feature matrix (as typically observed when labels are clean), while assuming that samples that deviate strongly from this structure are relatively few. Hence, we assume $\boldsymbol{H} \approx \boldsymbol{L} + \boldsymbol{S}$, where $\boldsymbol{L} \in \mathbb{R}^{D \times N}$ is the low-rank component and $\boldsymbol{S} \in \mathbb{R}^{D \times N}$ is a column sparse matrix. The low-rank term captures the underlying class structure information, whereas the sparse term handles outlier data items that do not strictly conform to the low-rank assumption.

Learning $\boldsymbol{L}$ and $\boldsymbol{S}$ generally involves solving an optimization problem of the form (Candes et al., 2009; Wang et al., 2008):

$$\min_{\boldsymbol{L},\boldsymbol{S}} \ \|\boldsymbol{L}\|_* + \lambda\|\boldsymbol{S}\|_{2,1} \quad \text{s.t.} \quad \boldsymbol{H} = \boldsymbol{L} + \boldsymbol{S},$$

where $\|\boldsymbol{L}\|_*$ denotes the nuclear norm of $\boldsymbol{L}$ to promote low-rankness and $\|\boldsymbol{S}\|_{2,1}$ promotes column sparsity in $\boldsymbol{S}$. Directly minimizing the nuclear norm can be computationally expensive, as it typically requires repeated singular value decompositions. To avoid this cost during training, we adopt an efficient power-iteration (PI)–based low-rank approximation strategy (Rokhlin et al., 2010; Gu, 2015). Specifically, the method estimates the top-K left singular vectors of $\boldsymbol{H}$ by iteratively refining a randomly initialized orthonormal basis $\boldsymbol{Q} \in \mathbb{R}^{D \times K}$ through alternating projections of $\boldsymbol{H}$ and orthonormalization via QR decomposition. The rank K can be selected according to the number of classes (or based on the number of coarse-grained classes for datasets with a very large label space). Using the learned $\boldsymbol{Q}$, we decompose the feature matrix as

$$\boldsymbol{H}_{\text{ID}} = (\boldsymbol{Q}\boldsymbol{Q}^\top)\boldsymbol{H}, \qquad \boldsymbol{H}_{\text{OOD}} = \boldsymbol{H} - \boldsymbol{H}_{\text{ID}}, \tag{4}$$

where $\boldsymbol{H}_{\text{ID}}$ represents the ID component and $\boldsymbol{H}_{\text{OOD}}$ contains residual features that may carry non-ID information. To enforce column sparsity in $\boldsymbol{H}_{\text{OOD}}$, we employ the following regularization term:

$$\mathcal{L}_{\text{sparse}} = \|\boldsymbol{H}_{\text{OOD}}\|_{2,1} = \sum_{j=1}^{N} \sqrt{\sum_{i=1}^{D} (\boldsymbol{H}_{\text{OOD}})_{ij}^2}. \tag{5}$$

Note that the outlier content captured in $\boldsymbol{H}_{\text{OOD}}$ can include both spurious features learned due to noisily labeled training examples and feature components within correctly labeled training samples that deviate from ID characteristics. We do not distinguish between these components explicitly; instead $\boldsymbol{H}_{\text{OOD}}$ is designed to capture anything that is non-ID, while the low-rank component $\boldsymbol{H}_{\text{ID}}$ focuses on learning the cleanest possible version of the ID feature space.

The proposed method is trained by minimizing a joint objective:

$$\mathcal{L}_{\mathcal{F}} = \mathcal{L}_{\text{CE}}^{\text{mod}} + \lambda \, \mathcal{L}_{\text{sparse}},$$

where $\lambda > 0$ controls the strength of the column-sparsity term. The detailed algorithm is presented in the supplementary section in Sec. B.

Remark 1. *The added regularization in (5) is implemented via the PI-based low-rank approximation of the batch-wise feature matrix $\boldsymbol{H}$ (see Algorithm 1 and 2 in the supplementary section in Sec. B). Since the PI method uses simple matrix–vector multiplications instead of a full SVD, the additional computational complexity is approximately $\mathcal{O}\big(T(DBK) + DK^2\big)$, where B is the batch size, K is the number of classes (or the chosen rank parameter), D is the feature embedding dimension, and T is the number of PI iterations, which is often a small number in practice. This overhead is moderate and substantially cheaper than exact nuclear-norm optimization.*

3.3 Robust OOD Detection with Refined Feature Representations

To detect OOD samples at test time, we propose a feature distance–based score with a robust selection strategy for reference embeddings. For each training sample $\boldsymbol{x}_n$, we assign an OOD-ness score:

$$o(\boldsymbol{x}_n) = \|\boldsymbol{h}(\boldsymbol{x}_n) - \boldsymbol{h}_{\text{ID}}(\boldsymbol{x}_n)\|_2,$$

where larger scores indicate greater deviation from ID characteristics (e.g., noisy or ambiguous samples), while smaller scores correspond to clean, representative ID examples—see also Fig. 3a in Sec. 4. Based on this score, we retain only the top $(1 - p)\%$ most challenging examples:

$$\mathcal{S} = \{n \in [N] \mid o(\boldsymbol{x}_n) \geq \alpha_p\}, \qquad \alpha_p = \text{Quantile}_{(1-p)}\big(\{o(\boldsymbol{x}_n)\}_{n=1}^{N}\big), \tag{6}$$

where $p \in [0, 1)$. The selected samples, which have large OOD-ness scores $o(\boldsymbol{x}_n)$, typically correspond to hard or boundary ID examples, and are chosen as a critical reference set for distance-based OOD detectors.

Intuitively, this design choice is similar in spirit to margin-based methods such as support vector machines (SVMs), where the decision boundary is determined by support vectors (the hardest points near the margin). This makes our OOD detector more robust to difficult ID samples and prevents it from becoming overly conservative.

For each selected sample $n \in \mathcal{S}$, we compute the ℓ_2-normalized feature vectors $\boldsymbol{u}_{\text{ID}}(\boldsymbol{x}_n) = \boldsymbol{h}_{\text{ID}}(\boldsymbol{x}_n)/\|\boldsymbol{h}_{\text{ID}}(\boldsymbol{x}_n)\|_2$. A test sample $\boldsymbol{x}^*$ is mapped to $\boldsymbol{u}(\boldsymbol{x}^*) = \boldsymbol{h}(\boldsymbol{x}^*)/\|\boldsymbol{h}(\boldsymbol{x}^*)\|_2$, and evaluated against the stored ID embeddings. Using kNN distance:

$$s_{\text{kNN}}(\boldsymbol{x}^*) = -\big\|\boldsymbol{u}(\boldsymbol{x}^*) - \boldsymbol{u}_{\text{ID}}^{(k)}\big\|_2,$$

where $\boldsymbol{u}_{\text{ID}}^{(k)}$ denotes the k-th nearest embedding in $\mathcal{S}$. A similar modified metric can be derived using Mahalanobis distance. A decision threshold τ is chosen based on a validation set to ensure a high ID recall (e.g., 95%).

4 Experiments

In this section, we evaluate the effectiveness of our label noise-robust OOD detection framework, named **N**oise-robust **O**ut-**O**f-**D**istribution **Le**arning (**NOODLE**).

Datasets. For synthetic label noise settings, we consider CIFAR-10 (Krizhevsky, 2009) as the ID dataset. We adopt class-independent symmetric noise, where every true label has the same probability of being corrupted, flipped uniformly at random to any of the other $K - 1$ classes. We vary the noise rate at 10%, 30%, and 50%. To test under realistic label noise, we also consider the human-annotated noisy label datasets CIFAR-10N, CIFAR-100N (Wei et al., 2022), and Animal-10N (Song et al., 2019). These are annotated by crowd workers from Amazon Mechanical Turk (AMT). CIFAR-10N provides five noisy label sets: *worst*, *aggregate*, *random1*, *random2*, and *random3*, with 40.21%, 9.03%, 17.23%, 18.12%, and 17.64% overall noise rates, respectively. Animal-10N has a noise rate of 8%, whereas CIFAR-100N has a noise rate of 40.20%. As OOD datasets during test time, we consider SVHN (Netzer et al., 2011), FashionMNIST (Xiao et al., 2017), LSUN (Yu et al., 2016), iSUN (Pan & Giró-i-Nieto, 2015), Texture (Cimpoi et al., 2013), and Places365 (Zhou et al., 2016). For larger dataset, we consider ImageNet-1k (Russakovsky et al., 2015) as the ID dataset. As ImageNet-1k does not include benchmark noisy-label variants with known noise rates, we consider synthetic noise rate with 30% and 50%. We consider iNaturalist (Horn et al., 2018), SUN50 (Xiao et al., 2010), Places50 (Zhou et al., 2016) and Texture (Cimpoi et al., 2013) as OOD dataset for this larger setting.

Baselines. We compare our method with several OOD detection baselines and label noise-robust techniques. For OOD detection, we consider MSP (Hendrycks & Gimpel, 2017), ODIN (Liang et al., 2018), Energy (Liu et al., 2020), ReAct (Sun et al., 2021), Mahalanobis (Lee et al., 2018), KNN (Sun et al., 2022), CIDER (Ming et al., 2023), SSD+ (Sehwag et al., 2021), and SNN (Ghosal et al., 2024). MSP, ODIN, and Energy are softmax-based approaches. MSP relies only on softmax output, while ODIN uses an additional temperature scaling hyperparameter. The Energy method computes an energy-based metric from the model outputs. ReAct is a logit-based approach. Mahalanobis, KNN, CIDER, SSD+, and SNN are distance-based approaches. Regarding label-noise-robust learning methods, we consider CM (Li et al., 2021a), VolMinNet (Li et al., 2021a), SCE (Wang et al., 2019b), GCE (Zhang & Sabuncu, 2018b), DivideMix (Li et al., 2020a), and Co-Teaching (Han et al., 2018b). CM and VolMinNet are probabilistic noise-modeling approaches that rely on transition matrices. GCE and SCE are robust loss function-based variants of the cross-entropy loss. DivideMix and Co-Teaching are sample-selection-based approaches. We also consider ViM (Wang et al., 2022) as a baseline, a post-hoc OOD detection method particularly well-suited for ViT and BiT architectures. For OOD performance evaluation, we use the kNN-based metric for all these methods, unless specified otherwise. For ViT-based architectures, we additionally report results using ViM, as it has been shown to be particularly effective for transformer-based representations.

Implementation Settings. We use DenseNet-101 (Huang et al., 2016) as the backbone model for all datasets, trained from scratch using the ID datasets. During training for CIFAR-10N and Animal-10N, we set the number of epochs to 100 with a batch size of 64. We extract penultimate layer features, apply global average pooling followed by ℓ_2-normalization, before performing the PI-based low-rank decomposition. We initialize transition matrices as identity matrices in CM-based approaches. We set the number of PI iterations

Figure 2: UMAP representations of the latent feature vectors $\boldsymbol{h}(\boldsymbol{x})$ learned using (a) CM approach (transition matrix-based label noise correction) with cross-entropy loss, and (b) NOODLE, our proposed approach, on the CIFAR-10 dataset with synthetic label noise.

Figure 3: (a) Learned "OOD-ness" score $o(\boldsymbol{x}_n)$ for CIFAR-10N training images. Top: top-10 samples with the highest $o(\boldsymbol{x}_n)$ scores. Bottom: bottom-10 samples with the lowest $o(\boldsymbol{x}_n)$ scores. Samples that are more ID-like has lower OOD score $o(\boldsymbol{x}_n)$. (b) OOD performance of NOODLE with $(p = 0.5)$ and without $(p = 0)$ robust selection strategy.

to $n_{\text{iter}} = 3$. For all datasets, we use SGD as the optimizer with momentum 0.9 and weight decay 1×10^{-4}. We tune λ from $\{0.0001, 0.0005, 0.001, 0.005, 0.1\}$ and p from $\{0, 0.3, 0.5\}$. We present the best performing variants of NOODLE in the main result tables and include detailed ablation studies in the supplementary material.

For the ViT-based experiments, we use ViT-B/16 pretrained on ImageNet-21K and fine-tuned on ImageNet-1K at a resolution of 384×384. For the clean setting, most of the compared OOD detectors require no additional retraining, except for SNN and NOODLE, which follow their respective fine-tuning procedures. To simulate label-noise conditions, we further fine-tune the pretrained model on a randomly selected subset of 200,000 ImageNet-1K training samples with symmetric label noise rates of 10%, 20% and 50%. The model is trained for 20 epochs using AdamW with a learning rate of 1×10^{-4}, weight decay of 1×10^{-4}, and a cosine annealing schedule. For the noisy-label setting, all baselines are evaluated using the checkpoints fine-tuned with the standard cross-entropy loss. We evaluate OOD detection performance on the ImageNet-1K validation set consisting of 50,000 images as the ID test set and on the standard OOD benchmarks introduced earlier. Following prior work (Wang et al., 2022), the ViM subspace dimension is set to 512. For NOODLE, we use a subspace rank of $K = 10$ and perform $n_{\text{iter}} = 3$ power-iteration steps. For KNN and SNN, we use $k{=}50$ and $k{=}20$ nearest neighbours, respectively, with SNN operating in the top-512 subspace of the training features, following (Ghosal et al., 2024). We evaluate OOD detection performance using the false positive rate at 95% true positive rate (FPR95) and the area under the receiver operating characteristic curve (AUROC).

Results. Table 1 presents the OOD detection performance under symmetric label noise across different noise rates for CIFAR-10. OOD detection baselines lacking label noise-robust training are significantly impacted by high levels of label noise. In contrast, label noise-robust approaches, especially those based

Table 3: Training time comparison on CIFAR-10N under the worst-case noise setting, conducted on a single NVIDIA V100 GPU. All methods are trained for 100 epochs.

Method	Total Time (100 Epochs)	Time / Epoch
GCE	1 hr 42 min	1.02 min
SCE	55 min	0.55 min
DivideMix	5 hr 30 min	3.30 min
Co-Teaching	2 hr 30 min	1.50 min
NOODLE	1 hr 30 min	0.90 min

on probabilistic modeling such as CM and VolMinNet, maintain relatively strong performance under noisy conditions. Notably, NOODLE consistently outperforms all other approaches in terms of both average FPR95 and AUROC. Our approach is particularly effective at higher noise rates. For example, at 50% noise rate, NOODLE achieves the best performance with an average FPR95 of 27.34%, representing a reduction of up to 12.5% compared to the best baseline method.

Table 2 presents results on real noisy label datasets. For CIFAR-10N "worst" noise (noise rate ≈40.21%), NOODLE achieves a 9.5% reduction in FPR95 and a 1.07% increase in AUROC compared to the best-performing baseline. Across other CIFAR-10N noise settings, NOODLE consistently outperforms all baselines. On Animal-10N, NOODLE achieves an additional ≈14% FPR95 reduction compared to the closest baseline. For CIFAR-100N, NOODLE substantially outperforms all baselines with an improvement of about 15% in FPR95.

Computational Cost. As discussed in Remark 1, NOODLE employs a power-iteration-based low-rank approximation that avoids the computational burden of full SVD. In practice, this introduces only a small overhead of approximately 5–8 ms per batch. As shown in Table 3, NOODLE maintains training efficiency comparable to GCE and SCE while remaining substantially faster than methods such as DivideMix. For example, NOODLE requires approximately 1.5 hours for 100 training epochs, compared to 5.5 hours for DivideMix, demonstrating that the proposed regularization improves robustness with minimal additional computational cost.

ID vs OOD Features. From Fig. 1, it is evident that higher noise levels distort the feature space, leading to less compact and more intermixed clusters. To illustrate how label noise-robust methods mitigate this issue, we examine UMAP visualizations in Fig. 2, where learned features $h(x)$ of the test data for both ID and OOD samples are presented. For CM, cluster distortions are mitigated compared to Fig. 1, showing that loss correction helps in feature cleaning to some extent. Nonetheless, ID and OOD sample mixups are still present, especially near boundaries. In contrast, NOODLE produces more compact and well-separated clusters even under high noise rates, with much reduced feature mix-up between ID and OOD samples.

We also observe the effectiveness of the proposed OOD-ness score in Fig. 3. The score $o(x_n)$ clearly differentiates samples that are more ID-like from those that are not (see Fig. 3a). As shown in Fig. 3b, the average FPR decreases across different real label noise settings when applying the sample selection strategy based on the learned scores $o(x_n)$.

Large-Scale ImageNet-1K Results. We further evaluate OOD detection methods on ImageNet-1K (Russakovsky et al., 2015) using a ViT-B/16 backbone pretrained on ImageNet-21K and fine-tuned on ImageNet-1K at a resolution of 384×384. Following the experimental setup described earlier, we randomly select 200,000 training samples to fit the detectors and use the ImageNet-1K validation set as the ID test set. We compare ViM (Wang et al., 2022), KNN (Sun et al., 2022), SNN (Ghosal et al., 2024), NOODLE+KNN, and NOODLE+ViM, where NOODLE+KNN combines the NOODLE residual with kNN scores and NOODLE+ViM replaces the SVD-based subspace in ViM (Wang et al., 2022) with the NOODLE subspace for virtual-logit scoring. The results under both clean and noisy-label settings are summarized in Table 4. On the clean pretrained model, NOODLE+ViM achieves the best overall performance, attaining an FPR95 of **26.60%** and an AUROC of **94.32%**, outperforming all competing methods. This suggests that the proposed subspace can effectively replace the computationally expensive SVD step used in ViM (Wang et al., 2022) while simultaneously improving OOD detection performance. More importantly, NOODLE+ViM remains

Table 4: OOD detection on ImageNet-1K with ViT-B/16 (384px), mean over iNaturalist, SUN50, Places50, and Texture. *Clean*: pretrained model with no noise. *Noise 10%*: model fine-tuned with 10% symmetric label noise; *Noise 20%*: model fine-tuned with 20% symmetric label noise; *Noise 50%*: model fine-tuned with 50% symmetric label noise. Details result is given in supplemntary Table10. Best performance per column is presented in **bold**.

Method	Clean (0%)		Noise (10%)		Noise (20%)		Noise (50%)	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
ViM	27.74	93.82	33.98	92.04	36.13	91.62	48.37	87.78
KNN	34.83	92.82	50.66	89.16	50.58	89.45	71.69	83.42
SNN	35.60	92.66	53.54	88.44	54.09	87.76	74.41	82.11
NOODLE+KNN	30.79	93.42	32.22	93.29	30.55	93.46	70.02	83.18
NOODLE+ViM	**26.60**	**94.24**	**26.48**	**94.03**	**26.23**	**94.32**	**47.76**	**87.37**

the most robust method under label corruption, achieving FPR95 values of **26.23%** and **47.76%** at 20% and 50% noise levels, respectively. By comparison, KNN and SNN suffer more performance degradation as the noise level increases, whereas the NOODLE-based methods remain relatively stable, highlighting the robustness of the proposed approach under noisy supervision.

Label-noise Robust OOD Detection with Vision-Language Model Prompt Tuning. A central motivation behind the proposed approach NOODLE is that, even under label noise, ID representations exhibit an underlying shared low-dimensional structure, whereas OOD samples tend to introduce irregular deviations from this structure. To examine whether this principle is useful beyond conventional OOD settings, we incorporate the low-rank promoting component of NOODLE into a large-scale vision-language prompt-learning framework. We adopt the context optimization method CoOp (Zhou et al., 2022) as the training framework, which has recently gained significant attention in large-scale zero-shot and few-shot OOD detection settings. Under this framework, we consider the vision-language model named contrastive language-image pre-training (CLIP) (Radford et al., 2021) with ViT-B/16 as the visual encoder and a transformer-based text encoder, and evaluate it on ImageNet-1K (Russakovsky et al., 2015) under a 16-shot setting with various synthetic label noise rates.

Given an input image $\boldsymbol{x}$, the pretrained CLIP visual encoder first extracts an image feature, which is then passed through a lightweight, trainable two-layer MLP head to obtain the adapted feature representations $\boldsymbol{h} \in \mathbb{R}^D$. The class probabilities are then computed from image-text similarities as follows:

$$\Pr(y = k|\boldsymbol{x}) = \frac{\exp(\mathrm{sim}(\boldsymbol{h}, \boldsymbol{g}_k)/\tau)}{\sum_{k'=1}^{K} \exp(\mathrm{sim}(\boldsymbol{h}, \boldsymbol{g}_{k'})/\tau)}, \quad k = 1, \dots, K,$$

where K denotes the number of classes, $\boldsymbol{g}_k = g(\boldsymbol{t}_k) \in \mathbb{R}^D$ is the textual feature obtained by passing the k-th class prompt $\boldsymbol{t}_k = \{\boldsymbol{\omega}_1, \boldsymbol{\omega}_2, \dots, \boldsymbol{\omega}_M, \boldsymbol{c}_k\}$ through the transformer-based CLIP text encoder $g(\cdot)$, $\boldsymbol{\omega}_m \in \mathbb{R}^D$ denotes the m-th learnable prompt vector, $\boldsymbol{c}_k$ is the fixed embedding of the k-th class name, and τ is the temperature parameter. To encourage the adapted image features to preserve the dominant low-dimensional ID structure, we impose a low-rank decomposition on the feature representations $\boldsymbol{h}(\boldsymbol{x})$. Specifically, we form the feature matrix $\boldsymbol{H} \in \mathbb{R}^{N \times D}$ by stacking the adapted image features $\boldsymbol{h}(\boldsymbol{x})$ of N training examples. Following the decomposition in our proposed approach as given by (4), we decompose $\boldsymbol{H}$ into low-rank ID component $\boldsymbol{H}_{\mathrm{ID}}$ and the residual component $\boldsymbol{H}_{\mathrm{OOD}}$, where the retained rank is fixed to 20 in our experiments. During training, we optimize the learnable prompt vectors and the parameters of the MLP adaptation head, while keeping the pretrained CLIP encoders frozen. We optimize the model using the cross-entropy loss ($\mathcal{L}_{\mathrm{CE}} = -\sum_{k=1}^{K} \mathbb{I}[y = k] \log \Pr(y = k|\boldsymbol{x})$) together with the proposed column sparse regularization loss $\mathcal{L}_{\mathrm{sparse}}$ defined in Eq. (5). We refer to this training framework as **CoOp+LR**. During inference, we use the global-local maximum concept matching (GL-MCM) score (Miyai et al., 2023; 2025) for OOD detection as advocated in recent prompt-learning-based OOD detection works. We evaluate **CoOp+LR** on iNaturalist (Horn et al., 2018), SUN50 (Xiao et al., 2010), Places50 (Zhou et al., 2016), and

Table 5: OOD detection performance on ImageNet-1K using CLIP ViT-B/16 under different symmetric label noise rates. CoOp+LR denotes CoOp augmented with the proposed low-rank decomposition module. Lower FPR95 and higher AUROC indicate better performance.

Noise	Method	iNaturalist		SUN50		Places50		Texture		Average	
		FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
30%	CoOp	**20.66**	**95.83**	27.88	92.84	36.64	89.94	52.84	84.67	34.51	90.82
	CoOp+LR	20.89	95.72	**26.81**	**93.22**	**36.48**	89.85	**50.39**	**85.26**	**33.64**	**91.01**
50%	CoOp	20.60	95.67	29.00	92.64	37.25	89.72	54.29	83.07	35.29	90.78
	CoOp+LR	**18.30**	**96.08**	**26.60**	**93.61**	**35.82**	**90.48**	**46.52**	**85.71**	**33.81**	**91.47**
75%	CoOp	**20.43**	**96.19**	33.89	92.17	40.16	89.77	52.32	85.27	36.70	90.85
	CoOp+LR	20.78	95.89	**28.13**	**92.88**	**38.63**	**90.87**	**52.19**	**85.74**	**34.93**	**91.35**

(a)   (b)

Figure 4: Comparison of OOD detection performance (FPR95↓) on CIFAR-10N. (a) Different KNN variants of NOODLE. (b) Different Mahalanobis variants of NOODLE. "NOODLE (X, Y)" refers to NOODLE with X as loss correction strategy and Y as OOD distance metric.

Texture (Cimpoi et al., 2013). As summarized in Table 5, **CoOp+LR** consistently improves the average OOD detection performance across different label noise rates. For example, under 50% symmetric label noise, **CoOp+LR** reduces the average FPR95 from 35.29% to 33.81% and improves the AUROC from 90.78% to 91.47%. Similar improvements are also observed under 30% and 75% noise, suggesting that the proposed low-rank structure transfers well to large-scale vision-language models and remains effective even in the presence of substantial label corruption.

Ablation Study. We provide a detailed breakdown of each component of the NOODLE framework by studying the effect of the low-rank and sparse decomposition module under different loss correction strategies and OOD detection metrics. We analyze CM and SCE strategies for loss correction, and kNN and Mahalanobis scores for feature distance-based OOD detection. Fig. 4a shows how the NOODLE variant with CM as loss correction and kNN as the distance metric substantially advances OOD detection performance for CIFAR-10N. The SCE variant is also reasonably good, yet the CM variant (NOODLE(CM, KNN)) performs much better in all CIFAR-10N scenarios. For CIFAR-100N, the SCE-Mahalanobis variant of NOODLE achieves the best performance, likely because estimating transition matrices for CM-based methods becomes increasingly difficult as the number of classes grows. Nevertheless, our key idea of feature cleaning via low-rank sparse decomposition consistently enhances performance across different settings. Additional ablation studies on the subspace rank K and sparsity parameter p are provided in the supplementary material, showing that NOODLE maintains competitive performance over a wide range of parameter values with only modest variations in OOD detection.

5 Conclusion

In this work, we introduce a novel framework for OOD detection under noisy labels that addresses the limitations of existing methods by correcting label noise and enhancing OOD performance. By leveraging low-rank ID feature representations, a carefully designed learning criterion, and robust OOD distance metrics, our approach provides greater flexibility and effectiveness in improving ID–OOD separability, even in highly noisy settings. Experimental results across multiple benchmarks and challenging OOD scenarios demonstrate the superiority of our method, highlighting its ability to tackle the challenging problem of OOD detection under noisy labels.

References

Devansh Arpit, Stanisław Jastrzundefinedbski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S. Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, and Simon Lacoste-Julien. A closer look at memorization in deep networks. In *Proceedings of International Conference on Machine Learning*, pp. 233–242, 2017.

Michael Buhrmester, Tracy Kwang, and Samuel D Gosling. Amazon's mechanical turk: A new source of inexpensive, yet high-quality data? 2016.

Emmanuel J. Candes, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis?, 2009. URL https://arxiv.org/abs/0912.3599.

Emmanuel J Candès, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis? *Journal of the ACM (JACM)*, 58(3):1–37, 2011.

Jiacheng Cheng, Tongliang Liu, Kotagiri Ramamohanarao, and Dacheng Tao. Learning with bounded instance and label-dependent label noise. In *Proceedings of International Conference on Machine Learning*, volume 119, pp. 1789–1799, 2020.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. *CoRR*, abs/1311.3618, 2013. URL http://arxiv.org/abs/1311.3618.

Xin Dong, Junfeng Guo, Ang Li, Wei-Te Ting, Cong Liu, and HT Kung. Neural mean discrepancy for efficient out-of-distribution detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 19217–19227, 2022.

Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *2012 IEEE conference on computer vision and pattern recognition*, pp. 3354–3361. IEEE, 2012.

Chuanxing Geng, Qifei Li, Xinrui Wang, Dong Liang, Songcan Chen, and Pong C. Yuen. Lod: Loss-difference ood detection by intentionally label-noisifying unlabeled wild data. In *Proceedings of the 34th International Joint Conference on Artificial Intelligence (IJCAI)*, 2025.

Soumya Suvra Ghosal, Yiyou Sun, and Yixuan Li. How to overcome curse-of-dimensionality for out-of-distribution detection? *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(18):19849–19857, Mar. 2024.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Ming Gu. Subspace iteration randomization and singular value problems. *SIAM Journal on Scientific Computing*, 37(3):A1139–A1173, 2015.

Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. *Advances in neural information processing systems*, 31, 2018a.

Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels, 2018b. URL https://arxiv.org/abs/1804.06872.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL https://openreview.net/forum?id=Hkg4TI9xl.

Dan Hendrycks, Steven Basart, Mantas Mazeika, Andy Zou, Joseph Kwon, Mohammadreza Mostajabi, Jacob Steinhardt, and Dawn Song. Scaling out-of-distribution detection for real-world settings. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, pp. 8759–8773. PMLR, 2022. URL https://proceedings.mlr.press/v162/hendrycks22a.html.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Yin Cui, Chen Sun, Alex Shepard, Hartwig Adam, Pietro Perona, and Serge Belongie. The inaturalist species classification and detection dataset, 2018. URL https://arxiv.org/abs/1707.06642.

Gao Huang, Zhuang Liu, and Kilian Q. Weinberger. Densely connected convolutional networks. *CoRR*, abs/1608.06993, 2016. URL http://arxiv.org/abs/1608.06993.

Galadrielle Humblot-Renaux, Sergio Escalera, and Thomas B Moeslund. A noisy elephant in the room: Is your out-of-distribution detector robust to label noise? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 22626–22636, 2024.

Shahana Ibrahim, Tri Nguyen, and Xiao Fu. Deep learning from crowdsourced labels: Coupled cross-entropy minimization, identifiability, and regularization. In *Proceedings of International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=_qVhsWyWB9.

Lu Jiang, Zhengyuan Zhou, Thomas Leung, Li-Jia Li, and Li Fei-Fei. Mentornet: Learning data-driven curriculum for very deep neural networks on corrupted labels. In *International conference on machine learning*, pp. 2304–2313. PMLR, 2018.

Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009. URL https://api.semanticscholar.org/CorpusID:18268744.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*. Curran Associates, Inc., 2018.

Junnan Li, Richard Socher, and Steven C. H. Hoi. Dividemix: Learning with noisy labels as semi-supervised learning, 2020a. URL https://arxiv.org/abs/2002.07394.

Junnan Li, Richard Socher, and Steven CH Hoi. Dividemix: Learning with noisy labels as semi-supervised learning. *arXiv preprint arXiv:2002.07394*, 2020b.

Xuefeng Li, Tongliang Liu, Bo Han, Gang Niu, and Masashi Sugiyama. Provably end-to-end label-noise learning without anchor points. In *International Conference on Machine Learning*, 2021a. URL https://api.semanticscholar.org/CorpusID:231802306.

Xuefeng Li, Tongliang Liu, Bo Han, Gang Niu, and Masashi Sugiyama. Provably end-to-end label-noise learning without anchor points. In *Proceedings of International Conference on Machine Learning*, pp. 6403–6413, 2021b.

Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations (ICLR)*, 2018. URL https://openreview.net/forum?id=H1VGkIxRZ.

Tongliang Liu and Dacheng Tao. Classification with noisy labels by importance reweighting. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 38:447–461, 2016.

Weitang Liu, Xiaoyun Wang, John Douglas Owens, and Yixuan Li. Energy-based out-of-distribution detection. *ArXiv*, abs/2010.03759, 2020. URL https://api.semanticscholar.org/CorpusID:222208700.

Yueming Lyu and Ivor W Tsang. Curriculum loss: Robust learning and generalization against label corruption. *arXiv preprint arXiv:1905.10045*, 2019.

Yifei Ming, Yiyou Sun, Ousmane Dia, and Yixuan Li. How to exploit hyperspherical embeddings for out-of-distribution detection?, 2023. URL https://arxiv.org/abs/2203.04450.

Atsuyuki Miyai, Qing Yu, Go Irie, and Kiyoharu Aizawa. Zero-shot in-distribution detection in multi-object settings using vision-language foundation models. *arXiv preprint arXiv:2304.04521*, 2023.

Atsuyuki Miyai, Qing Yu, Go Irie, and Kiyoharu Aizawa. GL-MCM: Global and local maximum concept matching for zero-shot out-of-distribution detection. *International Journal of Computer Vision*, pp. 1–11, 2025.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf.

Duc Tam Nguyen, Chaithanya Kumar Mummadi, Thi Phuong Nhung Ngo, Thi Hoai Phuong Nguyen, Laura Beggel, and Thomas Brox. Self: Learning to filter noisy labels with self-ensembling. *arXiv preprint arXiv:1910.01842*, 2019.

Junting Pan and Xavier Giró-i-Nieto. End-to-end convolutional network for saliency prediction. *CoRR*, abs/1507.01422, 2015. URL http://arxiv.org/abs/1507.01422.

Giorgio Patrini, Alessandro Rozza, Aditya Krishna Menon, Richard Nock, and Lizhen Qu. Making deep neural networks robust to label noise: A loss correction approach. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Vladimir Rokhlin, Arthur Szlam, and Mark Tygert. A randomized algorithm for principal component analysis. *SIAM Journal on Matrix Analysis and Applications*, 31(3):1100–1124, 2010.

Olga Russakovsky et al. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Thomas Schlegl, Philipp Seeböck, Sebastian M. Waldstein, Ursula Schmidt-Erfurth, and Georg Langs. Unsupervised anomaly detection with generative adversarial networks to guide marker discovery. In *Information Processing in Medical Imaging*, pp. 146–157. Springer International Publishing, 2017.

Vikash Sehwag, Mung Chiang, and Prateek Mittal. SSD: A unified framework for self-supervised outlier detection. *CoRR*, abs/2103.12051, 2021. URL https://arxiv.org/abs/2103.12051.

Hwanjun Song, Minseok Kim, and Jae-Gil Lee. SELFIE: Refurbishing unclean samples for robust deep learning. In *ICML*, 2019.

Hwanjun Song, Minseok Kim, Dongmin Park, Yooju Shin, and Jae-Gil Lee. Learning from noisy labels with deep neural networks: A survey. *IEEE transactions on neural networks and learning systems*, 34(11): 8135–8153, 2022.

Yiyou Sun and Yixuan Li. Dice: Leveraging sparsification for out-of-distribution detection. In *Computer Vision – ECCV 2022*, pp. 691–708. Springer Nature Switzerland, 2022.

Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 144–157. Curran Associates, Inc., 2021.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *Proceedings of the 39th International Conference on Machine Learning (ICML)*, pp. 20827–20840. PMLR, 2022.

Ryutaro Tanno, Ardavan Saeedi, Swami Sankaranarayanan, Daniel C Alexander, and Nathan Silberman. Learning from noisy labels by regularized estimation of annotator confusion. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 11244–11253, 2019.

Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. Vim: Out-of-distribution with virtual-logit matching, 2022. URL https://arxiv.org/abs/2203.10807.

Yilun Wang, Junfeng Yang, Wotao Yin, and Yin Zhang. A new alternating minimization algorithm for total variation image reconstruction. *SIAM J. Imaging Sciences*, 1:248–272, 01 2008. doi: 10.1137/080724265.

Yisen Wang, Xingjun Ma, Zaiyi Chen, Yuan Luo, Jinfeng Yi, and James Bailey. Symmetric cross entropy for robust learning with noisy labels. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 322–330, 2019a.

Yisen Wang, Xingjun Ma, Zaiyi Chen, Yuan Luo, Jinfeng Yi, and James Bailey. Symmetric cross entropy for robust learning with noisy labels, 2019b. URL https://arxiv.org/abs/1908.06112.

Jiaheng Wei, Zhaowei Zhu, Hao Cheng, Tongliang Liu, Gang Niu, and Yang Liu. Learning with noisy labels revisited: A study using real-world human annotations. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=TBWA6PLJZQm.

Xiaobo Xia, Tongliang Liu, Bo Han, Nannan Wang, Mingming Gong, Haifeng Liu, Gang Niu, Dacheng Tao, and Masashi Sugiyama. Part-dependent label noise: Towards instance-dependent label noise. In *Advances in Neural Information Processing Systems*, volume 33, pp. 7597–7610, 2020.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *CoRR*, abs/1708.07747, 2017. URL http://arxiv.org/abs/1708.07747.

Jianxiong Xiao, James Hays, Krista A Ehinger, Aude Oliva, and Antonio Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3485–3492, 2010.

Hong Yang, Qi Yu, and Travis Desell. Can we ignore labels in out-of-distribution detection? In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025.

Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *International Journal of Computer Vision*, 132(12):5635–5662, 2024.

Shuo Yang, Erkun Yang, Bo Han, Yang Liu, Min Xu, Gang Niu, and Tongliang Liu. Estimating instance-dependent Bayes-label transition matrix using a deep neural network. In *Proceedings of International Conference on Machine Learning*, 2021.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop, 2016. URL https://arxiv.org/abs/1506.03365.

Xingrui Yu, Bo Han, Jiangchao Yao, Gang Niu, Ivor Tsang, and Masashi Sugiyama. How does disagreement help generalization against label corruption? In *International conference on machine learning*, pp. 7164–7173. PMLR, 2019.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *Proceedings of International Conference on Learning Representations*, 2016.

Chunjie Zhang, Jing Liu, Qi Tian, Changsheng Xu, Hanqing Lu, and Songde Ma. Image classification by non-negative sparse coding, low-rank and sparse decomposition. In *CVPR 2011*, pp. 1673–1680. IEEE, 2011.

Zhilu Zhang and Mert Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels. *Advances in neural information processing systems*, 31, 2018a.

Zhilu Zhang and Mert R. Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels, 2018b. URL https://arxiv.org/abs/1805.07836.

Bolei Zhou, Aditya Khosla, Àgata Lapedriza, Antonio Torralba, and Aude Oliva. Places: An image database for deep scene understanding. *CoRR*, abs/1610.02055, 2016. URL http://arxiv.org/abs/1610.02055.

Kaiyang Zhou, Jingkang Yang, Chen Change Loy, and Ziwei Liu. Learning to prompt for vision-language models. *International Journal of Computer Vision (IJCV)*, 2022.

Algorithm 1 Proposed approach NOODLE

Input: Noisily labeled data $\{(\boldsymbol{x}_n, \widehat{y}_n)\}_{n=1}^N$, number of PI iterations n_{iter}, stopping criterion, number of classes K
Output: Estimated parameters $\boldsymbol{\theta}$ and $\boldsymbol{T}$
1: Initialize transition matrix $\boldsymbol{T} \leftarrow \boldsymbol{I}_K$
2: Initialize network parameters $\boldsymbol{\theta}$
3: **while** stopping criterion is not reached **do**
4:     Draw a random batch $\mathcal{B}$ of size B
5:     $\boldsymbol{H}_\mathcal{B} \leftarrow [\, \boldsymbol{h}(\boldsymbol{x}_1), \ldots, \boldsymbol{h}(\boldsymbol{x}_B) \,]$ *// penultimate layer features*
6:     $\boldsymbol{Q} \leftarrow \text{ApproxTopKSingularVectors}(\boldsymbol{H}_\mathcal{B}, K, n_{\text{iter}})$
7:     $\boldsymbol{H}_{\text{ID}} \leftarrow (\boldsymbol{Q}\boldsymbol{Q}^\top)\boldsymbol{H}_\mathcal{B}$
8:     $\boldsymbol{H}_{\text{OOD}} \leftarrow \boldsymbol{H}_\mathcal{B} - \boldsymbol{H}_{\text{ID}}$
9:     Compute $\nabla \mathcal{L}_\mathcal{F}(\boldsymbol{T}, \mathcal{B}, \boldsymbol{H}_{\text{OOD}})$
10:     $\boldsymbol{T}, \boldsymbol{\theta} \leftarrow \text{SGDOptimizer}(\boldsymbol{T}, \nabla \mathcal{L}_\mathcal{F}(\boldsymbol{T}, \mathcal{B}, \boldsymbol{H}_{\text{OOD}}))$
11: **end while**

Algorithm 2 ApproxTopKSingularVectors

Input: Feature matrix $\boldsymbol{H}_\mathcal{B} \in \mathbb{R}^{B \times D}$, target rank K, number of iterations n_{iter}
Output: Orthonormal matrix $\boldsymbol{Q} \in \mathbb{R}^{D \times K}$ spanning the approximate top-K right singular vectors of $\boldsymbol{H}_\mathcal{B}$
1: Randomly initialize $\boldsymbol{Q} \in \mathbb{R}^{D \times K}$
2: **for** $i = 1$ to n_{iter} **do**
3:     $\boldsymbol{Z} \leftarrow \boldsymbol{H}_\mathcal{B}^\top (\boldsymbol{H}_\mathcal{B} \boldsymbol{Q})$ *// project $\boldsymbol{Q}$ into column space of $\boldsymbol{H}_\mathcal{B}$*
4:     $\boldsymbol{Q} \leftarrow \text{QRDecomposition}(\boldsymbol{Z})$ *// orthonormalize*
5: **end for**
6: **return** $\boldsymbol{Q}$

A Notation

We use the following notation throughout the paper: x, $\boldsymbol{x}$, $\boldsymbol{X}$, and $\tilde{\boldsymbol{X}}$ represent a scalar, a vector, a matrix, and a tensor, respectively. Both x_i and $[\boldsymbol{x}]_i$ denote the i-th entry of the vector $\boldsymbol{x}$. $[\boldsymbol{X}]_{i,j}$ denotes the (i, j)-th entry of the matrix $\boldsymbol{X}$. $[I]$ means an integer set $\{1, 2, \ldots, I\}$. The superscript $^\top$ denotes transpose. $\boldsymbol{X} \geq \boldsymbol{0}$ implies that all entries of $\boldsymbol{X}$ are non-negative. $\mathbb{I}[A]$ denotes an indicator function for event A. $\boldsymbol{I}$ denotes an identity matrix of appropriate size. $\boldsymbol{1}_K$ denotes an all-one vector of size K. $|\mathcal{C}|$ denotes the cardinality of set $\mathcal{C}$. Δ^K denotes a $(K-1)$-dimensional probability simplex: $\Delta^K = \{\boldsymbol{u} \in \mathbb{R}^K \mid \boldsymbol{u} \geq \boldsymbol{0}, \boldsymbol{1}^\top \boldsymbol{u} = 1\}$.

B Algorithm Description

Algorithm 1 provides the complete step-by-step procedure of our approach using the transition matrix-based loss correction strategy. The decomposition routine is detailed in Algorithm 2.

C Additional Experimental Results

This section provides additional experimental results that complement the main paper. We include detailed per-dataset OOD detection performance under different label noise settings, additional evaluations on real-world noisy datasets, and ablation studies analyzing the sensitivity of NOODLE to different hyperparameters.

Tables 6 and 7 report the complete per-dataset OOD detection results on CIFAR-10N under all synthetic noise settings. In addition to FPR95 and AUROC for each OOD dataset, we also report the corresponding ID classification accuracy to illustrate the trade-off between robust classification and OOD detection.

Table 6: OOD detection performance (FPR95↓ / AUROC↑) on CIFAR-10 under clean, worst, and aggregate noise settings using a DenseNet-100 encoder.

Method	SVHN FPR95	SVHN AUROC	FashionMNIST FPR95	FashionMNIST AUROC	LSUN FPR95	LSUN AUROC	iSUN FPR95	iSUN AUROC	Texture FPR95	Texture AUROC	Places365 FPR95	Places365 AUROC	Average FPR95	Average AUROC	ID Acc.
Clean															
KNN	10.25	98.26	10.95	98.03	13.21	97.64	17.05	96.87	25.30	95.31	49.58	88.70	21.06	95.80	93.32
MSP	72.54	87.37	49.86	92.74	34.70	95.33	46.04	93.34	68.51	85.16	66.90	86.46	56.43	90.07	93.32
ODIN	55.88	89.16	16.01	97.23	3.01	99.12	8.47	98.20	60.46	82.84	54.77	88.30	33.10	92.47	93.32
Energy	73.05	87.23	15.64	97.18	4.44	98.86	23.22	96.16	67.02	83.48	51.52	89.30	39.15	92.03	93.32
ReAct	97.03	61.00	44.59	93.52	28.01	95.84	41.26	93.42	88.14	68.86	62.85	86.07	60.31	83.12	93.32
Mahalanobis	4.51	99.13	2.47	99.31	0.63	99.75	14.79	97.38	22.46	95.08	69.08	82.08	18.99	95.45	93.32
CIDER	18.61	96.78	27.17	95.35	31.63	94.34	42.00	93.82	56.65	89.58	59.95	85.06	39.33	92.49	90.51
SSD+	31.05	92.81	15.85	96.54	19.28	95.86	17.41	95.87	64.27	85.06	54.11	88.39	33.66	92.42	94.03
SNN	8.68	98.35	21.49	96.22	9.22	98.42	19.46	96.72	26.99	94.97	49.74	88.52	22.60	95.53	94.15
SCE	4.59	99.13	15.47	97.06	1.96	99.58	10.60	98.06	29.31	92.84	56.36	87.03	19.71	95.62	91.09
GCE	11.33	98.02	11.73	98.00	7.16	98.73	9.06	98.30	21.70	96.15	50.39	88.80	18.56	96.33	93.54
DivideMix	22.35	94.72	36.90	91.74	33.41	90.87	46.05	87.62	47.11	86.55	58.04	84.45	40.81	89.16	81.22
Co-teaching	56.55	74.88	99.90	36.86	95.18	58.31	96.28	61.89	55.83	78.99	94.03	48.08	81.94	58.15	86.22
CM	8.35	98.64	8.39	98.49	7.16	98.67	15.19	97.31	19.72	96.36	51.14	88.54	18.32	96.33	94.39
VolMinNet	2.45	99.48	13.06	97.57	5.96	98.93	6.25	98.85	15.96	97.07	46.30	89.42	15.00	96.89	94.56
NOODLE	3.06	99.35	5.44	98.86	4.92	99.06	9.73	98.03	15.48	96.80	48.96	88.72	14.60	96.81	98.37
Noise = Worst															
KNN	9.17	98.28	27.89	94.95	15.76	96.98	38.41	92.03	36.21	90.94	67.46	84.15	32.48	92.89	80.79
MSP	56.74	87.97	50.54	89.33	38.83	93.72	62.58	87.03	78.16	76.44	74.04	78.44	60.15	85.49	80.79
ODIN	45.45	90.96	33.09	93.31	13.41	97.43	32.36	92.03	71.68	72.39	75.89	73.02	45.31	86.69	80.79
Energy	37.62	93.17	35.78	93.28	14.57	97.00	47.39	90.98	76.06	74.61	72.39	77.45	47.30	87.75	80.79
ReAct	70.94	82.60	52.84	90.05	36.40	93.87	68.31	81.53	88.92	54.21	77.90	70.87	65.89	78.86	80.79
Mahalanobis	4.41	98.97	19.95	96.33	10.05	98.07	30.50	92.65	33.69	89.11	87.96	60.38	31.09	89.25	80.79
CIDER	99.75	58.13	98.68	66.64	99.94	52.42	99.25	61.61	93.60	65.80	98.86	48.94	98.35	58.92	80.26
SSD+	20.08	94.86	37.05	91.58	24.16	94.97	33.27	93.97	50.12	89.22	73.44	74.29	39.69	89.82	82.87
SNN	10.98	97.95	24.49	95.67	16.61	96.76	31.84	93.96	33.92	90.69	67.36	81.67	30.87	92.78	80.57
SCE	12.39	97.67	28.98	94.52	17.71	96.62	49.37	89.63	34.61	91.13	64.11	83.10	34.53	92.11	83.48
GCE	10.53	98.18	21.72	96.09	15.71	97.05	55.81	87.25	45.69	87.86	65.02	82.54	35.75	91.50	83.49
DivideMix	44.70	93.52	48.20	89.20	38.09	90.29	15.35	96.70	32.06	94.42	57.95	85.09	39.39	91.53	80.23
Co-teaching	50.04	85.37	99.95	29.04	99.61	58.63	96.88	58.36	52.15	82.65	94.22	50.03	82.14	60.68	86.34
CM	8.61	98.29	17.92	96.78	28.37	90.87	56.29	81.97	39.24	88.19	67.23	81.87	36.28	89.66	76.26
VolMinNet	7.58	98.33	42.88	90.42	19.70	95.50	43.71	89.08	40.90	87.46	70.64	77.54	37.57	89.72	76.30
NOODLE	3.17	99.47	21.57	96.21	7.57	98.03	28.09	97.28	30.52	92.53	61.75	84.71	25.45	94.71	83.72
Noise = Aggregate															
KNN	11.37	97.91	18.32	96.70	9.93	98.11	18.12	96.35	23.69	95.43	62.26	84.54	23.95	94.84	89.93
MSP	57.75	89.45	47.16	90.89	27.74	95.11	59.89	88.27	67.84	83.15	69.89	82.42	55.04	88.21	89.93
ODIN	49.75	91.54	30.78	94.69	9.29	98.25	33.50	92.13	65.18	82.01	74.50	75.54	43.83	89.03	89.93
Energy	66.66	88.00	40.23	93.66	18.07	97.10	64.95	88.41	71.46	81.96	74.80	78.26	56.03	87.90	89.93
ReAct	66.66	88.00	40.23	93.66	18.07	97.10	64.95	88.41	71.46	81.96	21.61	96.92	47.17	91.01	89.93
Mahalanobis	4.41	98.97	19.95	96.33	10.05	98.07	30.50	92.65	33.69	89.11	87.96	60.38	31.09	89.25	89.93
CIDER	82.88	71.63	99.61	32.85	48.08	84.89	94.50	65.86	79.66	70.30	96.50	50.70	83.54	62.71	89.06
SSD+	63.39	76.39	34.70	90.34	23.16	94.58	43.26	90.42	36.14	90.22	73.66	74.43	45.72	86.07	90.66
SNN	6.15	98.90	14.36	97.33	8.61	98.32	35.76	92.37	26.12	94.45	59.86	83.74	25.14	94.18	90.00
SCE	4.32	99.14	19.12	96.41	4.92	98.98	19.90	96.39	24.98	94.82	63.95	82.82	22.87	94.76	90.45
GCE	1.94	99.64	11.17	98.11	7.57	98.58	14.44	97.36	28.63	94.62	52.86	87.84	19.43	96.03	91.55
DivideMix	77.88	85.56	84.07	74.54	48.41	87.26	59.81	78.07	49.49	86.58	74.63	78.99	65.72	81.83	73.44
Co-teaching	48.52	80.16	99.49	39.54	94.18	58.15	86.59	72.57	45.46	84.21	93.64	47.65	77.98	63.71	86.15
CM	7.82	98.68	13.01	97.55	8.41	98.30	12.70	97.62	22.45	95.18	62.91	83.70	21.22	95.17	78.82
VolMinNet	3.88	99.17	10.28	98.08	8.46	98.32	31.84	93.84	29.41	93.06	56.36	87.27	23.37	94.96	91.86
NOODLE	1.34	99.75	17.07	97.21	2.26	98.95	8.42	98.21	17.15	96.21	52.88	88.41	16.52	96.46	91.57

Table 8 presents detailed results on the real-world noisy Animal-10N dataset. Performance is reported separately for each OOD benchmark together with the average metrics and the final ID classification accuracy.

Table 9 provides the complete per-dataset evaluation on CIFAR-100N with real noisy labels. These results demonstrate the effectiveness of NOODLE across a more challenging large-class benchmark under realistic annotation noise.

Table 7: OOD detection performance (FPR95↓ / AUROC↑) on CIFAR-10 under random1, random2, and random3 noise using a DenseNet-100 encoder.

Method	SVHN		FashionMNIST		LSUN		iSUN		Texture		Places365		Average		ID Acc.
	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	
Noise = random1															
KNN	26.55	95.11	32.22	94.66	19.98	96.43	36.27	92.58	30.12	93.01	67.75	84.12	35.48	92.65	88.03
MSP	63.91	89.44	56.80	88.35	33.35	94.64	70.25	83.87	70.71	81.70	69.47	81.73	60.75	86.62	88.03
ODIN	55.83	87.93	43.60	91.41	11.17	98.01	46.12	89.32	65.07	77.53	72.94	75.16	49.12	86.56	88.03
Energy	81.76	85.45	39.75	92.56	11.32	97.78	63.37	86.34	68.55	80.04	64.57	81.25	54.89	87.24	88.03
ReAct	97.67	60.00	57.46	89.81	28.41	95.32	72.90	78.42	86.65	62.40	69.53	75.58	68.77	76.92	88.03
Mahalanobis	16.86	96.22	48.89	88.49	13.62	97.36	50.63	82.90	36.24	87.86	92.57	50.57	43.14	83.90	88.03
CIDER	98.03	48.59	99.91	59.70	97.94	63.79	99.45	58.63	97.02	58.86	97.60	57.74	98.32	57.88	87.74
SSD+	18.54	93.66	51.21	87.56	20.28	95.63	36.77	91.92	51.22	89.03	73.38	74.79	41.90	88.77	90.33
SNN	16.25	97.07	35.63	93.93	15.74	97.05	23.81	95.32	26.77	93.92	61.03	85.28	29.87	93.76	87.13
SCE	17.45	97.24	10.51	97.91	5.81	98.81	14.95	97.11	25.83	93.70	62.82	83.86	22.90	94.77	89.81
GCE	6.38	98.87	11.85	97.92	11.48	97.93	23.18	96.11	31.91	93.27	56.04	86.58	23.47	95.11	90.46
DivideMix	89.21	84.82	62.24	86.97	56.76	88.52	68.00	80.74	50.85	86.88	72.78	79.19	66.64	84.52	77.14
Co-teaching	51.32	81.34	49.00	83.00	52.00	87.00	23.18	96.11	74.58	69.89	94.74	62.07	53.42	74.23	86.44
CM	3.13	99.35	18.50	96.55	15.74	97.22	21.04	96.18	25.85	94.65	64.08	83.69	24.72	94.61	90.31
VolMinNet	5.48	99.01	15.74	97.11	6.92	98.75	22.86	95.86	30.30	94.07	56.10	86.06	22.90	95.15	90.53
NOODLE	3.21	99.47	15.65	97.21	5.23	98.93	5.03	98.85	12.79	97.69	58.03	86.35	16.66	96.42	90.36
Noise = random2															
KNN	6.29	98.73	41.05	91.75	19.28	96.04	24.92	95.02	30.85	92.20	69.53	82.43	31.99	92.70	87.79
MSP	53.36	89.13	58.24	84.86	30.82	94.26	48.26	91.41	73.00	80.23	74.98	79.10	56.44	86.50	87.79
ODIN	44.99	87.97	56.14	83.96	13.74	97.24	19.78	94.78	68.03	73.23	77.58	68.27	46.71	84.24	87.79
Energy	60.00	87.44	50.75	87.08	17.62	96.63	29.00	93.97	71.31	76.10	73.20	75.42	50.31	86.11	87.79
ReAct	78.12	80.74	56.58	86.77	30.49	94.12	62.46	86.31	87.27	61.33	77.87	69.69	65.46	79.83	87.79
Mahalanobis	11.94	96.96	69.11	81.20	23.57	95.12	36.79	87.81	38.72	86.17	94.13	48.44	45.71	82.62	87.79
CIDER	96.75	67.67	99.94	45.22	99.59	46.57	99.68	67.00	91.21	60.02	98.38	59.07	97.59	57.59	87.53
SSD+	16.20	96.64	34.41	91.92	18.91	95.97	36.97	93.74	54.53	86.97	75.17	77.90	39.37	90.52	90.27
SNN	4.84	99.05	42.45	92.36	19.44	96.04	17.68	96.06	33.90	91.82	66.09	82.28	30.74	92.94	88.11
SCE	6.17	98.78	15.97	97.16	13.15	97.50	24.60	95.04	25.41	94.60	61.19	82.42	24.42	94.25	89.72
GCE	2.02	99.57	18.91	96.46	5.57	98.84	9.06	98.09	19.47	96.02	55.29	86.18	18.89	95.86	90.29
DivideMix	79.28	78.13	68.73	80.40	55.05	86.76	26.58	94.70	51.37	87.91	74.59	77.40	59.27	84.22	78.30
Co-teaching	51.32	81.34	99.87	32.07	74.58	69.89	94.74	62.07	52.39	81.73	92.63	49.46	77.59	62.76	85.99
CM	1.83	99.62	16.84	97.00	17.64	96.72	18.08	96.81	27.96	94.45	59.38	85.66	23.62	95.04	90.29
VolMinNet	3.95	99.25	15.59	97.29	8.74	98.36	8.31	98.42	22.82	95.84	53.37	87.74	18.80	96.15	94.35
NOODLE	2.14	99.49	12.51	97.82	3.98	99.05	5.02	98.87	17.78	95.74	52.42	87.89	15.46	96.70	90.25
Noise = random3															
KNN	8.79	98.41	29.45	93.81	12.45	97.66	28.16	94.63	25.80	94.26	58.99	85.76	27.27	94.09	87.77
MSP	50.92	90.23	44.39	89.13	25.79	95.34	69.78	81.85	67.02	81.86	65.51	81.76	53.90	86.70	87.77
ODIN	41.84	90.63	30.77	92.45	8.82	98.25	42.48	89.24	60.35	77.22	67.20	76.41	41.91	87.37	87.77
Energy	40.77	92.63	26.49	93.06	8.85	98.19	57.99	85.82	64.08	80.66	58.27	83.06	42.74	88.90	87.77
ReAct	77.62	77.76	34.33	92.52	16.16	96.96	67.01	79.29	85.32	62.89	66.42	77.99	57.81	81.24	87.77
Mahalanobis	7.87	98.31	26.49	94.43	7.01	98.64	54.91	82.04	28.95	90.66	87.15	57.60	35.40	86.95	87.77
CIDER	94.37	51.43	95.95	62.08	98.10	51.80	99.37	33.13	93.19	46.85	97.89	57.20	96.48	50.41	87.16
SSD+	31.92	93.43	29.40	93.66	12.15	97.74	25.35	93.66	36.34	91.72	59.22	83.18	32.40	92.23	90.23
SNN	12.97	97.67	34.27	91.84	16.04	96.81	53.01	89.46	29.40	92.96	59.90	83.95	34.26	92.12	87.94
SCE	6.08	98.81	16.65	96.94	13.47	96.64	24.29	95.55	23.32	95.23	65.06	83.22	24.81	94.40	89.39
GCE	7.30	98.63	17.23	96.88	5.28	98.96	10.88	97.86	20.04	95.84	57.98	85.49	19.78	95.61	90.71
DivideMix	26.15	95.47	57.09	89.78	38.77	92.91	46.40	89.32	49.93	87.99	74.53	80.78	48.81	89.38	69.20
Co-teaching	50.65	80.80	99.96	23.83	99.55	56.65	95.49	58.16	52.45	80.56	93.54	48.86	81.94	58.15	86.53
CM	2.56	99.48	12.00	97.75	6.82	98.60	23.46	95.99	23.74	94.94	55.65	86.32	20.70	95.51	90.79
VolMinNet	9.80	98.06	10.10	98.02	7.61	98.40	24.25	95.63	25.74	94.40	55.65	85.58	22.19	95.02	94.36
NOODLE	2.31	99.41	12.31	97.82	3.34	99.25	5.26	98.79	17.56	95.86	52.15	87.86	15.49	96.50	90.37

Table 10 reports detailed OOD detection performance on ImageNet-1K under different symmetric label noise rates. Results are presented separately for iNaturalist, SUN50, Places50, and DTD, allowing a dataset-wise comparison of the robustness of different post-hoc OOD detectors.

Tables 11, 12, and 13 investigate the sensitivity of NOODLE to the regularization weight λ, the retained subspace dimension K, and the residual ratio parameter p, respectively. These experiments demonstrate that NOODLE achieves stable performance over a broad range of hyperparameter choices.

Table 8: OOD detection performance (FPR95↓ / AUROC↑) on Animal-10N with real noisy labels using a DenseNet-100 encoder.

	SVHN		FashionMNIST		LSUN		iSUN		DTD		Places365		Average		
Method	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	ID Acc.
KNN	45.29	89.55	58.05	90.30	66.19	79.93	90.66	62.18	73.17	74.54	89.26	65.71	70.44	77.04	81.52
MSP	93.12	64.84	82.74	79.61	84.00	74.53	96.60	34.67	96.97	41.18	90.40	64.56	90.64	59.90	81.52
ODIN	79.29	64.67	51.20	88.26	48.52	87.84	96.52	34.97	95.43	36.66	90.85	62.89	76.97	62.55	81.52
Energy	81.91	74.54	66.32	88.64	31.94	94.83	96.32	45.16	89.02	69.24	88.09	74.71	75.60	74.52	81.52
ReAct	79.18	77.62	72.85	85.98	42.96	92.02	95.69	58.85	91.88	52.46	91.43	59.99	79.00	71.15	81.52
Mahalanobis	31.73	91.49	97.47	42.44	68.73	66.87	4.87	98.87	33.39	86.64	91.04	51.67	54.54	73.00	81.52
CIDER	78.00	82.28	74.75	83.81	51.20	87.60	99.00	36.84	95.13	78.33	74.75	81.70	82.64	75.09	81.85
SSD+	62.40	82.49	59.80	84.02	40.96	87.82	97.62	36.93	76.10	78.53	59.80	81.90	66.11	75.28	82.06
SNN	41.40	91.28	11.58	97.79	12.04	97.63	39.68	91.61	29.22	93.29	54.67	90.27	31.43	93.65	81.52
SCE	29.06	90.96	41.71	93.05	27.00	94.63	9.45	98.39	29.59	94.10	55.03	89.71	31.97	93.47	81.22
GCE	28.98	91.90	43.05	91.28	23.75	94.14	27.02	95.91	30.18	92.52	66.74	84.15	36.62	91.65	80.86
DivideMix	16.15	96.44	19.84	96.28	18.42	95.98	60.56	86.34	40.14	85.92	50.52	89.62	34.27	91.77	79.63
Co-teaching	68.04	83.45	99.90	8.68	84.54	55.97	11.71	97.11	49.72	82.39	96.92	42.70	68.47	61.72	74.08
CM	25.84	95.25	15.41	97.22	13.42	97.44	63.61	84.11	37.06	90.88	45.65	91.58	33.50	92.75	82.48
VolMinNet	15.08	96.79	29.22	94.51	11.80	97.73	40.62	90.67	25.20	94.64	53.63	90.21	29.26	94.09	81.78
NOODLE	26.49	94.77	24.41	95.75	11.36	97.86	17.29	96.70	18.21	96.33	53.76	89.37	25.25	95.13	82.98

Table 9: OOD detection performance (FPR95↓ / AUROC↑) on CIFAR-100N with real noisy labels using a DenseNet-100 encoder.

	SVHN		FashionMNIST		LSUN		iSUN		DTD		Places365		Average		
Method	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	ID Acc.
KNN	11.08	97.63	42.68	92.88	28.07	93.32	53.09	81.81	32.73	91.70	91.56	61.90	43.20	86.54	52.48
MSP	86.65	75.40	76.23	81.21	52.72	88.08	88.69	67.64	92.36	60.23	89.81	63.40	81.08	72.66	52.48
ODIN	93.41	68.56	58.06	87.70	26.85	95.10	70.69	83.42	92.78	59.70	88.51	65.36	71.72	76.64	52.48
Energy	97.07	47.12	53.27	91.52	35.35	93.49	90.27	68.41	99.29	3.46	98.31	6.41	78.93	51.74	52.48
ReAct	97.07	47.12	53.27	91.52	35.35	93.49	90.27	68.41	97.53	38.90	83.94	66.32	76.24	67.63	52.48
Mahalanobis	64.60	82.25	99.38	44.82	95.23	49.37	53.12	83.45	42.13	84.50	96.43	48.47	75.15	65.47	52.48
CIDER	28.62	94.78	14.64	97.02	66.68	77.38	73.73	72.75	57.96	80.94	82.41	72.13	54.01	82.50	57.70
SSD+	35.23	88.50	34.22	89.82	26.73	92.94	48.84	85.22	76.06	77.32	80.69	69.36	50.29	83.86	60.06
SNN	16.78	96.78	35.98	93.88	91.30	61.59	56.80	84.25	30.82	92.35	27.24	93.93	43.15	87.13	58.06
SCE	16.87	96.64	14.13	97.12	30.67	91.97	75.99	62.21	50.27	86.01	88.84	64.92	46.13	83.15	60.74
GCE	63.18	82.35	58.27	88.42	63.09	77.88	80.78	66.52	58.03	82.63	87.90	67.42	68.54	77.54	58.21
DivideMix	30.53	94.00	37.22	93.63	67.81	83.31	67.09	70.49	48.55	85.01	86.47	71.10	56.28	82.92	33.26
Co-teaching	51.77	83.17	99.96	27.69	85.42	66.48	98.34	47.85	59.41	79.01	95.20	53.47	81.68	59.61	46.18
CM	35.24	92.09	40.79	92.55	36.79	90.95	54.59	79.49	40.46	89.36	89.26	68.02	49.52	85.41	59.06
VolMinNet	36.03	91.87	50.23	91.22	45.13	88.00	74.76	61.76	43.26	88.84	90.49	66.66	56.65	81.39	60.10
NOODLE	21.12	95.97	20.44	96.46	5.24	98.76	39.20	91.36	37.45	89.97	87.67	64.59	35.19	89.52	60.89

Finally, Table 14 includes comparisons with additional OOD detection baselines on CIFAR-10N, further validating the effectiveness and competitiveness of the proposed method.

Table 10: Detailed per-dataset and average OOD detection performance (%) on ImageNet-1K under different symmetric label noise rates. Results are reported for each OOD dataset (iNaturalist, SUN50, Places50, and Texture). Lower FPR95 and higher AUROC indicate better performance.

Noise	Method	iNaturalist		SUN50		Places50		Texture		Average	
		FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
0%	ViM	**1.52**	99.46	30.69	93.75	42.13	90.46	36.61	91.59	27.74	93.82
	KNN	5.85	98.88	45.21	91.70	51.44	89.37	36.81	91.33	34.83	92.82
	SNN	5.15	98.96	47.67	91.28	52.67	89.14	36.90	91.26	35.60	92.66
	NOODLE+KNN	3.34	99.36	37.75	92.69	47.02	89.90	35.05	91.73	30.79	93.42
	NOODLE+ViM	1.55	**99.49**	**28.94**	**94.22**	**40.90**	**91.12**	**35.02**	**92.13**	**26.60**	**94.24**
10%	ViM	2.43	99.46	42.57	90.84	50.37	88.11	40.57	89.76	33.98	92.04
	KNN	10.77	97.85	72.14	85.79	71.20	84.73	48.55	88.26	50.66	89.16
	SNN	13.48	97.48	76.61	84.45	73.71	83.75	50.37	88.07	53.54	88.44
	NOODLE+KNN	0.98	99.82	60.33	87.96	24.38	95.73	43.21	89.65	32.22	93.29
	NOODLE+ViM	**0.84**	**99.77**	**42.24**	**91.09**	**23.99**	**94.85**	**38.87**	**90.41**	**26.48**	**94.03**
20%	ViM	3.60	99.19	45.35	90.82	57.01	85.91	38.55	90.57	36.13	91.62
	KNN	26.60	95.78	55.75	89.56	83.87	80.97	36.12	91.48	50.58	89.45
	SNN	11.34	97.88	87.55	79.94	55.46	88.20	62.02	85.01	54.09	87.76
	NOODLE+KNN	3.31	99.36	37.25	92.78	46.60	89.96	35.04	91.72	30.55	93.46
	NOODLE+ViM	**1.57**	**99.50**	**28.06**	**94.38**	**40.36**	**91.25**	**34.93**	**92.14**	**26.23**	**94.32**
50%	ViM	8.85	98.15	57.02	85.81	62.09	83.65	65.51	83.51	48.37	87.78
	KNN	46.05	93.04	90.94	77.22	87.85	76.98	**60.64**	**86.04**	71.37	83.32
	SNN	52.86	91.87	92.08	75.68	89.27	75.68	63.44	85.21	74.41	82.11
	NOODLE+KNN	41.40	93.66	88.45	77.79	86.42	77.12	63.79	84.15	70.02	83.18
	NOODLE+ViM	**9.13**	**98.19**	**53.05**	**86.90**	**60.18**	**84.05**	68.67	80.36	**47.76**	**87.37**

Table 11: OOD detection performance for different λ values on the CIFAR-10N "worst" noise case using a DenseNet-101 encoder.

	SVHN		FashionMNIST		LSUN		iSUN		Texture		Places365		Average	
λ	FPR↓	AUROC↑	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC
0.0001	3.23	99.31	23.67	95.81	8.08	98.40	36.55	93.57	32.98	91.67	63.14	83.91	27.94	93.78
0.0005	19.66	95.99	42.48	90.61	25.72	94.65	18.28	95.86	33.81	91.92	59.99	82.62	33.32	91.94
0.001	29.12	94.13	47.44	90.18	36.82	92.17	31.88	92.10	56.01	83.47	57.17	84.44	43.07	89.42

Table 12: OOD detection performance (FPR95↓ / AUROC↑) on CIFAR-100N with real noisy labels varying K.

	SVHN		FashionMNIST		LSUN		iSUN		Texture		Places365		Average	
K	FPR↓	AUROC↑	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC
10	21.28	95.95	31.66	94.16	6.70	98.51	35.01	91.50	31.77	91.58	90.59	63.49	36.17	89.20
15	17.14	96.42	38.31	92.93	6.02	98.68	47.71	90.76	28.14	92.57	89.62	64.97	37.82	89.39
20	21.12	95.97	20.44	96.46	5.24	98.76	39.20	91.36	37.45	89.97	87.67	64.59	35.19	89.52
30	26.45	94.70	29.85	95.10	6.50	98.50	35.50	93.20	42.20	90.00	86.30	65.00	37.80	89.40
40	25.10	94.81	20.04	96.67	6.50	98.73	39.08	93.04	33.51	90.82	90.72	65.42	35.83	89.92

Table 13: OOD detection under real noisy labels (worst case) on CIFAR-10N for various p values.

	SVHN		FashionMNIST		LSUN		iSUN		Texture		Places365		Average	
p (%)	FPR↓	AUROC↑	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC	FPR	AUROC
0	13.52	97.42	29.92	94.26	12.52	97.22	28.44	94.74	29.65	92.99	63.60	83.41	29.61	93.34
20	8.63	98.36	30.26	94.28	12.05	97.31	17.64	96.35	27.75	93.47	63.89	83.21	26.70	93.83
30	8.24	98.41	30.14	94.31	11.98	97.33	17.21	96.48	27.22	93.50	64.02	83.14	26.47	93.86
40	7.86	98.52	30.69	94.37	12.13	97.34	15.59	96.85	26.91	93.67	65.25	83.02	26.40	93.96
50	3.17	99.47	21.57	96.21	7.57	98.03	28.09	97.28	30.52	92.53	61.75	84.71	**25.45**	**94.71**
70	5.68	98.90	30.83	94.31	12.05	97.34	13.96	97.11	26.10	93.82	67.26	82.40	25.98	93.98

Table 14: OOD detection performance (FPR95↓ / AUROC↑) on CIFAR-10 with real noisy labels using a DenseNet-100 encoder.

Method	SVHN		FashionMNIST		LSUN		iSUN		DTD		Places365		Average	
	FPR95↓	AUROC↑	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC	FPR95	AUROC
Worst														
FDBD	48.40	91.34	70.39	75.34	60.75	81.90	69.90	73.77	74.72	72.60	95.00	38.63	69.86	72.26
RankFeat	60.41	85.53	61.81	84.44	25.66	93.74	65.47	76.22	68.28	65.89	96.40	36.73	63.00	73.76
NECO	78.06	60.65	70.85	70.22	58.76	75.76	83.83	62.01	74.05	71.28	74.15	73.12	73.28	68.84
NOODLE	3.17	99.47	21.57	96.21	7.57	98.03	28.09	97.28	30.52	92.53	61.75	84.71	**25.45**	**94.71**
Aggregate														
FDBD	71.83	83.66	46.31	87.52	47.19	89.26	79.11	74.58	78.30	69.04	88.81	61.12	68.59	77.53
RankFeat	24.32	94.38	48.27	91.09	14.21	97.55	70.29	77.94	61.72	74.77	92.18	57.91	51.83	82.27
NECO	81.73	66.91	66.42	72.13	65.12	67.84	46.48	82.13	76.79	67.93	61.95	79.76	66.42	72.79
NOODLE	1.34	99.75	17.07	97.21	2.26	98.95	8.42	98.21	17.15	96.21	52.88	88.41	**16.52**	**96.46**
Rand1														
FDBD	48.40	91.34	70.39	75.34	60.75	81.90	69.90	73.77	74.72	72.60	95.00	38.63	69.86	72.26
RankFeat	40.54	89.96	78.08	74.02	30.94	91.98	93.35	48.12	69.47	65.98	97.83	32.54	68.37	67.10
NECO	87.57	55.73	50.18	82.85	53.82	80.93	68.28	78.11	70.27	77.44	64.11	81.02	65.70	76.01
NOODLE	3.21	99.47	15.65	97.21	5.23	98.93	5.03	98.85	12.79	97.69	58.03	86.35	**16.66**	**96.42**