# Sharpness-Aware Training for Free

## Abstract

Modern deep neural networks (DNNs) have achieved state-of-the-art performances
but are typically over-parameterized. The over-parameterization may result in
undesirably large generalization error in the absence of other customized training
strategies. Recently, a line of research under the name of *Sharpness-Aware Mini-
mization* (SAM) has shown that minimizing a sharpness measure, which reflects
the geometry of the loss landscape, can significantly reduce the generalization error.
However, SAM-like methods incur a two-fold computational overhead of the given
base optimizer (e.g. SGD) for approximating the sharpness measure. In this paper,
we propose *Sharpness-Aware Training for Free*, or *SAF*, which mitigates the sharp
landscape at *almost zero additional computational cost* over the base optimizer.
Intuitively, SAF achieves this by avoiding sudden drops in the loss in the sharp
local minima throughout the trajectory of the updates of the weights. Specifically,
we suggest a novel trajectory loss, based on the KL-divergence between the outputs
of DNNs with the current weights and past weights, as a replacement of the SAM's
sharpness measure. This loss captures the rate of change of the training loss along
the model's update trajectory. By minimizing it, SAF ensures the convergence
to a flat minimum with improved generalization capabilities. Extensive empiri-
cal results show that SAF minimizes the sharpness in the same way that SAM
does, yielding better results on the ImageNet dataset with essentially the same
computational cost as the base optimizer. The code will be released.

## 1 Introduction

Despite achieving remarkable performances in many applications, powerful neural networks [5, 27, 28,
2, 22, 27, 36, 35] are typically over-parameterized. Such over-parameterized deep neural networks
require advanced training strategies to ensure that their generalization errors are appropriately
small [2, 33] and the adverse effects of the overfitting are alleviated. Understanding how deep neural
networks generalize is perhaps the most fundamental and yet perplexing topic in deep learning.

Numerous studies expend significant amounts of efforts to understand the generalization capabilities of
deep neural networks and mitigate this problem from a variety of perspectives, such as the information
perspective [19], the model compression perspective [1, 9], and the Bayesian perspective [23, 25], etc.
The loss surface geometry perspective, in particular, has attracted a lot of attention from researchers
recently [15, 4, 13, 14, 29]. These studies connect the generalization gap and the sharpness of the
minimum's loss landscape, which can be characterized by the largest eigenvalue of the Hessian
matrix $\nabla_\theta^2 f_\theta$ [15] where $f_\theta$ represents the input-output map of the neural network. In other words, a
(local) minimum that is located in a flatter region tends to generalize better than one that is located
in a sharper one [4, 14]. The recent work [8] proposes an effective and generic training algorithm,
named *Sharpness-Aware Minimization* (SAM), to encourage the training process to converge to a flat
minimum. SAM explicitly penalizes a sharpness measure to obtain flat minima, which has achieved
state-of-the-art results in several learning tasks [2, 37].

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Unfortunately, SAM's computational cost is twice that compared to the given base optimizer, which is typically stochastic gradient descent (SGD). This prohibits SAM from being deployed extensively in highly over-parameterized networks. Half of SAM's computational overhead is used to approximate the sharpness measure in its first update step. The other half is used by SAM to minimize the sharpness measure together with the vanilla loss in the second update step. As shown in Figure 1, SAM significantly reduces the generalization error at the expense of double computational overhead.

Figure 1: Accuracy vs training speed of SGD, SAM [8], ESAM [6], GSAM [37], and SAF. GSAM is the state-of-the-art among SAM's follow-up works. Every connected line represents a method that trains ResNet-50, ResNet-101, and ResNet-152 models on ImageNet-1k. SAF outperforms SAM and its variants yet requires *no additional computational overhead*.

Liu *et al.* [21] and Du *et al.* [6] recently addressed the computation issue of SAM and proposed LookSAM [21] and Efficient SAM (ESAM) [6], respectively. LookSAM only minimizes the sharpness measure *once* in the first of every five iterations. For the other four iterations, LookSAM reuses the gradients that minimizes the sharpness measure, which is obtained by decomposing the SAM's updated gradients in the first iteration into two orthogonal directions. As a result, LookSAM saves $40\%$ computations compared to SAM but unfortunately suffers from performance degradation. On the other hand, ESAM proposes two strategies to save the computational overhead in SAM's two updating steps. The first strategy approximates the sharpness by using fewer weights for computing; the other approximates the updated gradients by only using a subset containing the instances that contribute the most to the sharpness. ESAM is reported to save up to $30\%$ computations without degrading the performance. However, ESAM's efficiency degrades in large-scale datasets and architectures (from $30\%$ on CIFAR-10/100 to $22\%$ on ImageNet). LookSAM and ESAM both follow SAM's path to minimize SAM's sharpness measure, which limits the potential for further improvement of their efficiencies.

In this paper, we aim to perform sharpness-aware training with *zero additional computations and yet still retain superior generalization performance*. Specifically, we introduce a novel trajectory loss to replace SAM's sharpness measure loss. This trajectory loss measures the KL-divergence between the outputs of neural networks with the current weights and those with the past weights. We propose the *Sharpness-Aware training for Free* (SAF) algorithm to penalize the trajectory loss for sharpness-aware training. More importantly, SAF requires *almost zero extra computations* (SAF 0.7% v.s. SAM 100%). SAF memorizes the outputs of DNNs in the process of training as the targets of the trajectory loss. By minimizing it, SAF avoids the quick converging to a local sharp minimum. SAF has the potential to result in out-of-memory issue on extremely large scale datasets, such as ImageNet-21K [16] and JFT-300M [26]. We also introduce a memory-efficient variant of SAF, which is *Memory-Efficient Sharpness-Aware Training* (MESA). MESA adopts a DNN whose weights are the exponential moving averages (EMA) of the trained DNN to output the targets of the trajectory loss. As a result, MESA resolves the out-of-memory issue on extremely large scale datasets, at the cost of 15% additional computations (v.s. SAM 100%). As shown in Figure 2, SAF and MESA both encourage the training to converge to flat minima similarly as SAM. Besides visualizing the loss landscape, we conduct experiments on the CIFAR-10/100 [17] and the ImageNet [3] datasets to verify the effectiveness of SAF. The experimental results indicate that our proposed SAF and MESA outperform SAM and its variants with almost twice the training speed; this is illustrated on the ImageNet-1k dataset in Figure 1.

In a nutshell, we summarize our contributions as follows.

- We propose a novel trajectory loss to measure the sharpness to be used for sharpness-aware training. Requiring almost zero extra computational overhead, this trajectory loss is a better loss to quantify the sharpness compared to SAM's loss.

- We address the efficiency issue of current sharpness-aware training, which generally incurs twice the computational overhead compared to regular training. Based on our proposed trajectory loss, we propose the novel SAF algorithm for improved generalization ability in

Figure 2: Visualizations of loss landscapes [18, 2] of the Wide-28-10 model on the CIFAR-100 dataset trained with SGD, SAM, our proposed SAF, and MESA. SAF encourages the networks to converge to a flat minimum as SAM does with zero additional computational overhead.

this paper. SAF is demonstrated to outperform SAM on the ImageNet dataset, with the same computational cost as the base optimizer.

- We also propose the MESA algorithm as a memory-efficient variant of SAF. MESA reduces the extra memory-usage of SAF at the cost of 15% additional computations, which allows SAF/MESA to be deployed efficiently (both in terms of memory and computation) on extremely large-scale datasets (e.g. ImageNet-21K [16]).

## 2 Preliminaries

Throughout the paper, we use $f_\theta$ to denote a neural network with weight parameters $\theta$. We are given a training dataset $\mathbb{S}$ that contains i.i.d. samples drawn from a natural distribution $\mathcal{D}$. The training of the network is typically a non-convex optimization problem which aims to search for an optimal weight vector $\hat{\theta}$ that satisfies

$$\hat{\theta} = \arg\min_\theta L_\mathbb{S}(f_\theta) \quad \text{where} \quad L_\mathbb{S}(f_\theta) = \frac{1}{|\mathbb{S}|} \sum_{x_i \in \mathbb{S}} \ell(f_\theta(x_i)), \tag{1}$$

where $\ell$ can be an arbitrary loss function, and we use $x_i$ to denote the pair (inputs, targets) of the $i$-th element in the training set. In this paper, we take $\ell$ to be the cross entropy loss; We use $\|\cdot\|$ represents $\ell_2$ norm; *we assume that $L_\mathbb{S}(f_\theta)$ is continuous and differentiable, and its first-order derivation is bounded*. In each training iteration, optimizers randomly sample a mini-batch $\mathbb{B}_t \subset \mathbb{S}$ with a fixed batch size.

**Sharpness-Aware Minimization** The conventional optimization and training focuses on minimizing the empirical loss of a single weight vector $\hat{\theta}$ over the training set $\mathbb{S}$ as stated in Equation 1. This training paradigm is known as *empirical risk minimization*, and tends to overfit to the training set and converges to sharp minima. Sharpness-Aware Minimization (SAM) [8] aims to encourage the training to converge to a flatter region in which the training losses in the neighborhood around the minimizer $\hat{\theta}$ are lower. To achieve this, SAM proposes a training scheme that solves the following min-max optimization problem:

$$\min_\theta \max_{\epsilon: \|\epsilon\|_2 \leq \rho} L_\mathbb{S}(f_{\theta+\epsilon}). \tag{2}$$

where $\rho$ is a predefined constant that constrains the radius of the neighborhood; $\epsilon$ is the weight perturbation vector that maximizes the training loss within the $\rho$-constrained neighborhood. The objective loss function of SAM can be rewritten as the sum of the vanilla loss and the loss associated to the sharpness measure, which is the maximized change of the training loss within the $\rho$-constrained neighborhood, i.e.,

$$\hat{\theta} = \arg\min_\theta \left\{ R_\mathbb{S}(f_\theta) + L_\mathbb{S}(f_\theta) \right\} \quad \text{where} \quad R_\mathbb{S}(f_\theta) = \max_{\epsilon: \|\epsilon\|_2 \leq \rho} L_\mathbb{S}(f_{\theta+\epsilon}) - L_\mathbb{S}(f_\theta). \tag{3}$$

The sharpness measure is approximated as $R_\mathbb{S}(f_\theta) = L_\mathbb{S}(f_{\theta+\hat{\epsilon}}) - L_\mathbb{S}(f_\theta)$, where $\hat{\epsilon}$ is the solution to an approximated version of the maximization problem where the objective is the first-order Taylor approximation of $L_\mathbb{S}(f_{\theta+\epsilon})$ around $\theta$, i.e.,

$$\hat{\epsilon} = \arg\max_{\epsilon: \|\epsilon\|_2 < \rho} L_\mathbb{S}(f_{\theta+\epsilon}) \approx \rho \frac{\nabla_\theta L_\mathbb{S}(f_\theta)}{\|\nabla_\theta L_\mathbb{S}(f_\theta)\|}. \tag{4}$$

127 Intuitively, SAM seeks flat minima with low variation in their training losses when the optimal
128 weights are slightly perturbed.

# 3 Methodology

130 The fact that SAM's computational cost is twice that compared to the base optimizer is its main
131 limitation. The additional computational overhead is used to compute the sharpness term $R_{\mathbb{S}}(f_\theta)$
132 in Equation 3. We propose a new trajectory loss as a replacement of SAM's sharpness loss $R_{\mathbb{S}}(f_\theta)$
133 with essentially zero extra computational overhead over the base optimizer. Next, we introduce the
134 *Sharpness-Aware Training for Free* (SAF) algorithm whose pseudocode can be found in Algorithm 1.
135 We first start with recalling SAM's sharpness measure loss. Then we explain the intuition for the
136 trajectory loss as a substitute for SAM's sharpness measure loss in Section 3.1. Next, we present the
137 complete algorithm of SAF in Section 3.2 and a memory-efficient variant of it in Section 3.3.

---

**Algorithm 1** Training with SAF and MESA

**Input:** Training set $\mathbb{S}$; A network $f_\theta$ with weights $\theta$; Learning rate $\eta$; Epochs $E$; Iterations $T$ per
    epoch; SAF starting epoch $E_{\text{start}}$; SAF coefficients $\lambda$; Temperature $\tau$; SAF hyperparameter $\tilde{E}$;
    EMA decay factor $\beta$ for MESA.
1: **for** $e = 1$ to $E$ **do**                         ▷ $e$ represents the current epoch
2:     **for** $t = 1$ to $T$, Sample a mini-batch $\mathbb{B} \subset \mathbb{S}$ **do**
3:         **if** SAF **then**
4:             Record the outputs: $\hat{y}_i^e \leftarrow f_\theta(x_i)$, where $x_i \in \mathbb{B}$
5:             Load $\hat{y}_i^{(e-\tilde{E})}$ saved in $\tilde{E}$ epochs ago for each $x_i \in \mathbb{B}$
6:             Compute $L_{\mathbb{B}}^{\text{tra}}(f_\theta, \mathbb{Y}^{(e-\tilde{E})})$           ▷ Defined in Equation 8;
7:         **else if** MESA **then**
8:             Update EMA model weights: $v_t = \beta v_{t-1} + (1 - \beta)\theta$
9:             Compute $L_{\mathbb{B}}^{\text{tra}}(f_\theta, f_{v_t})$               ▷ Defined in Equation 12
10:         **if** $e > E_{\text{start}}$ **then**         ▷ Added the trajectory loss after $E_{\text{start}}$ epoch
11:             $\mathcal{L} = L_{\mathbb{B}}(f_\theta) + \lambda L_{\mathbb{B}}^{\text{tra}}$
12:         **else**
13:             $\mathcal{L} = L_{\mathbb{B}}(f_\theta)$
14:         Update the weights: $\theta \leftarrow \theta - \eta\nabla_\theta\mathcal{L}$
**Output:** A flat minimum solution $\tilde{\theta}$.

---

## 3.1 General Idea: Leverage the trajectory of weights to estimate the sharpness

139 We first rewrite the sharpness measure $R_{\mathbb{B}}(f_\theta)$ of SAM based on its first-order Taylor expansion.
140 Given a vector $\hat{\epsilon}$ (Equation 4) whose norm is small, we have

$$R_{\mathbb{B}}(f_\theta) = L_{\mathbb{B}}(f_{\theta+\hat{\epsilon}}) - L_{\mathbb{B}}(f_\theta) \approx L_{\mathbb{B}}(f_\theta) + \hat{\epsilon}\nabla_\theta L_{\mathbb{B}}(f_\theta) - L_{\mathbb{B}}(f_\theta)$$
$$= \rho \frac{\nabla_\theta L_{\mathbb{B}}(f_\theta)^\top}{\|\nabla_\theta L_{\mathbb{B}}(f_\theta)\|}\nabla_\theta L_{\mathbb{B}}(f_\theta) = \rho\|\nabla_\theta L_{\mathbb{B}}(f_\theta)\|. \tag{5}$$

141 We remark that minimizing the sharpness loss $R_{\mathbb{B}}(f_\theta)$ is equivalent to minimizing the $\ell_2$-norm of the
142 gradient $\nabla_\theta L_{\mathbb{B}}(f_\theta)$, which is the same gradient used to minimize the vanilla loss $L_{\mathbb{B}}(f_\theta)$.

143 The learning rate $\eta$ in the standard training (using SGD) is typically smaller than $\rho$ as suggested by
144 SAM [8]. Hence, if the mini-batch $\mathbb{B}$ is the same for the two consecutive iterations, the change of the
145 training loss after the weights have been updated can be approximated as follow,

$$L_{\mathbb{B}}(f_\theta) - L_{\mathbb{B}}(f_{\theta-\eta\nabla_\theta L_{\mathbb{B}}(f_\theta)}) \approx \eta\|\nabla_\theta L_{\mathbb{B}}(f_\theta)\|^2 \approx \frac{\eta}{\rho^2}R_{\mathbb{B}}(f_\theta)^2. \tag{6}$$

146 We also remark that the change of the training loss after the weights have been updated is proportional
147 to $R_{\mathbb{B}}(f_\theta)^2$. Hence, minimizing the loss difference is equal to minimizing the sharpness loss of SAM
148 in this case.

This inspires us to leverage the update of the weights in the standard training to approximate SAM's sharpness measure. Regrettably though, the samples in the mini-batches $\mathbb{B}_t$ and $\mathbb{B}_{t+1}$ in two consecutive iterations are different with high probability, which does not allow the sharpness to be computed as in Equation 6. This is precisely the reason why SAM uses an additional step to compute $\hat{\epsilon}$ for approximating the sharpness. To avoid these additional computations completely, we introduce a novel trajectory loss that makes use of the trajectory of the weights learned in the standard training procedure to measure sharpness.

Figure 3: For the vanilla training loss $L_{\mathbb{B}}(f_\theta)$ (dashed lines), the blue arrows represent the trajectory during training. **Left**: A sharp local minimum tends to have a large trajectory loss. **Right**: By minimizing the trajectory loss, SAF prevents the training from converging to a sharp local minimum.

We denote the trajectory of the weights as the iterations progress as $\Theta = \{\theta_1, \theta_2, \ldots, \theta_t\}$. Hence, $\theta_t$ represents the weights in the $t$-th iteration. We use SGD as the base optimizer to illustrate our ideas. Recall that standard SGD updates the weights as $\theta_{t+1} = \theta_t - \eta \nabla_{\theta_t} L_{\mathbb{B}_t}(f_{\theta_t})$. For iteration $t$, we observe that

$$\arg\min_{\theta_t} R_{\mathbb{B}_t}(f_{\theta_t}) = \arg\min_{\theta_t} \mathbb{E}_{\theta_i \sim \mathrm{Unif}(\{\theta_1, \theta_2, \ldots, \theta_t\})} [\gamma_i R_{\mathbb{B}_t}(f_{\theta_i}) R_{\mathbb{B}_i}(f_{\theta_i})],$$

where $\gamma_t = \frac{\eta_t}{\rho^2} \cos(\Phi_t)$ and $\Phi_t$ is the angle between the gradients that are computed using the mini-batches $\mathbb{B}_i$ and $\mathbb{B}_t$, respectively. The sharpness can therefore be alternatively estimated by

$$\mathbb{E}_{\theta_i \sim \mathrm{Unif}(\Theta)} [\gamma_i R_{\mathbb{B}_t}(f_{\theta_i}) R_{\mathbb{B}_i}(f_{\theta_i})] \approx \mathbb{E}_{\theta_i \sim \mathrm{Unif}(\Theta)} \left[ \eta_i \cos(\Phi_i) \|\nabla_{\theta_i} L_{\mathbb{B}_t}(f_{\theta_i})\| \, \|\nabla_{\theta_i} L_{\mathbb{B}_i}(f_{\theta_i})\| \right]$$

$$= \mathbb{E}_{\theta_i \sim \mathrm{Unif}(\Theta)} \left[ \eta_i \nabla_{\theta_i} L_{\mathbb{B}_t}(f_{\theta_i})^\top \nabla_{\theta_i} L_{\mathbb{B}_i}(f_{\theta_i}) \right] \approx \mathbb{E}_{\theta_i \sim \mathrm{Unif}(\Theta)} \left[ L_{\mathbb{B}_t}(f_{\theta_i}) - L_{\mathbb{B}_t}(f_{\theta_{i+1}}) \right]$$

$$= \frac{1}{t-1} \left[ L_{\mathbb{B}_t}(f_{\theta_1}) - L_{\mathbb{B}_t}(f_{\theta_t}) \right], \tag{7}$$

where $\theta_i$ is is uniformly distributed over the set $\Theta$. We remark that minimizing the loss difference $L_{\mathbb{B}_t}(f_{\theta_1}) - L_{\mathbb{B}_t}(f_{\theta_t})$ is equivalent to minimizing the SAM's loss $R_{\mathbb{B}_t}(f_{\theta_t})$. Accordingly, requiring no additional computational overhead, the training loss difference is a good replacement of SAM's loss $R_{\mathbb{B}_t}(f_{\theta_t})$ to quantify and penalize the sharpness.

### 3.2 Sharpness-Aware Training for Free (SAF)

We elaborate our proposed training algorithm SAF in this subsection. To estimate the sharpness precisely, SAF only takes the update trajectory in the past $\tilde{E}$ epochs into consideration. When simultaneously minimizing the vanilla loss and the training loss difference (as in Equation 7), the second term $-L_{\mathbb{B}_T}(f_{\theta_T})$ will cancel out the vanilla loss. Therefore, we replace the cross entropy loss with the KL divergence loss to decouple the vanilla loss. As inspired by Knowledge distillation [12], we also soften the targets of the KL divergence loss using a temperature $\tau$. Accordingly, the trajectory loss at $e$-th epoch is defined as follow

$$L_{\mathbb{B}}^{\mathrm{tra}}(f_\theta, \mathbb{Y}^{(e-\tilde{E})}) = \frac{\lambda}{|\mathbb{B}|} \sum_{x_i \in \mathbb{B}, \hat{y}_i^{(e-\tilde{E})} \in \mathbb{Y}^{(e-\tilde{E})}} \mathrm{KL}\left( \frac{1}{\tau} \hat{y}_i^{(e-\tilde{E})}, \frac{1}{\tau} f_\theta(x_i) \right), \tag{8}$$

where $\mathbb{Y}^{(e-\tilde{E})} = \left\{ \hat{y}_i^{(e-\tilde{E})} = f_\theta^{(e-\tilde{E})}(x_i) : x_i \in \mathbb{B} \right\}$. We remark that $\hat{y}_i^{(e-\tilde{E})}$ is the network output of the instance $x_i$ in $\tilde{E}$ epochs ago, as illustrated in Line 4 of Algorithm 1. The outputs of each instance $x_i$ will be recorded, and no additional computations are required during this procedure. The trajectory loss will be deployed after a predefined epoch $E_{\mathrm{start}}$ (Line 10 of Algorithm 1), because the outputs of the DNN are not stable and reliable at the beginning epochs. Intuitively, the trajectory loss slows down the rate of change of the training loss to avoid convergence to sharp local minima, which is illustrated in Figure 3.

### 3.3 Memory-Efficient Sharpness-Aware Training (MESA)

The memory usage for recording the outputs is negligible for standard datasets such as CIFAR [17] (57 MB). However, SAF's memory usage is proportional to the size of the training datasets, which

may result in an out-of-memory issue on extremely large-scale datasets such as ImageNet-21k [16] and JFT-300M [26]. Another limitation of SAF is that the coefficient $\gamma_t$ will decay at the same rate as the learning rate $\eta_t$ since $\gamma_t \propto \eta_t$ as shown in Equation 7. Hence, the sharpness at the current weights are quantified by smaller coefficients $\gamma_t$. For a SAF-like algorithm to be applicable on extremely large-scale datasets and to emphasize the sharpness of the *most current/recent* weights, we introduce *Memory-Efficient Sharpness-Aware Training* (MESA), which adopts an exponential moving average (EMA) weighting strategy on the weights to construct the trajectory loss. The *EMA weight* $v_t$ at the $t$-th iteration is updated as follows

$$v_t = \beta v_{t-1} + (1-\beta)\theta_t, \tag{9}$$

where $\beta \in (0.9, 1)$ is the decay coefficient of EMA. Given that $v_1 = \theta_1$, and $\theta_{t+1} = \theta_t - \eta\nabla_{\theta_t}L_{\mathbb{B}_t}(f_{\theta_t})$, the EMA weight in the $t$-th iteration, can be expressed as

$$v_t = \theta_1 - \sum_{i=1}^{t-1}(1-\beta^{t-i})\eta\nabla_{\theta_i}L_{\mathbb{B}_i}(f_{\theta_i}) = \theta_t + \sum_{i=1}^{t-1}\beta^{t-i}\eta\nabla_{\theta_i}L_{\mathbb{B}_i}(f_{\theta_i}). \tag{10}$$

More details can be found in Appendix. Therefore, the trajectory from $\theta_t$ to $v_t$ is collected in the vector $\mathbb{W}_{\text{EMA}} = \{w_1, w_2, \ldots, w_t\}$, where $w_i = w_{i-1} - \beta^{t-i}\eta\nabla_{\theta_i}L_{\mathbb{B}_i}(f_{\theta_i})$, $w_1 = v_t$, and $w_t = \theta_t$. If we regard the outputs of EMA model $f_{v_t}$ as the targets of the trajectory loss, and substitute it into Equation 7,

$$\frac{1}{t-1}\left[L_{\mathbb{B}_t}(f_{v_t}) - L_{\mathbb{B}_t}(f_{\theta_t})\right] = \mathop{\mathbb{E}}_{w_i \sim \text{Unif}(\mathbb{W}_{\text{EMA}})}\left[L_{\mathbb{B}_t}(f_{w_i}) - L_{\mathbb{B}_t}(f_{w_{i+1}})\right]$$
$$\approx \mathop{\mathbb{E}}_{w_i \sim \text{Unif}(\mathbb{W}_{\text{EMA}})}\left[\beta^{t-i}\gamma_i R_{\mathbb{B}_t}(f_{w_i}) R_{\mathbb{B}_t}(f_{\theta_i})\right]. \tag{11}$$

More details can be found in Appendix. Hence, the EMA coefficients $\beta^{t-i}$ will place more emphasis on the sharpness of the *current* and *more recent* weights since $0 < \beta < 1$. The trajectory loss of MESA is

$$L_{\mathbb{B}}^{\text{tra}}(f_\theta, f_{v_t}) = \frac{1}{|\mathbb{B}|}\sum_{x_i \in \mathbb{B}}\text{KL}\left(\frac{1}{\tau}f_{v_t}(x_i), \frac{1}{\tau}f_\theta(x_i)\right). \tag{12}$$

We see that the difference between this and the trajectory loss $L_{\mathbb{B}}^{\text{tra}}(f_\theta, \mathbb{Y}^{(e-\tilde{E})})$ discussed in Section 3.2 is that the target $\hat{y}_i^{(e-\tilde{E})}$ at the $t$-iteration has been replaced by $f_{v_t}(x_i)$ for $x_i \in \mathbb{B}$.

## 4 Experiments

We verify the effectiveness of our proposed SAF and MESA algorithms in this section. We first conduct experiments to demonstrate that our proposed SAF achieves better performance comparing to SAM with twice the training speed. SAF is demonstrated to outperform SAM and its variants in large-scale datasets and models. The main results are summarized into Tables 1 and 3. Next, we evaluate the sharpness of SAF using the measurement proposed by SAM. We demonstrate that SAF encourages the training to converge to a flat minimum. We also visualize the loss landscape of the minima converged by SGD, SAM, SAF, and MESA in Figures 2 and 5, which shows that both SAF's and MESA's loss landscape are as flat as SAM.

### 4.1 Experiment Setup

**Datasets** We conduct experiments on the following image classification benchmark datasets: CIFAR-10, CIFAR-100 [17], and ImageNet [3]. The 1000-class ImageNet dataset contains roughly 1.28 million training images, which is the popular benchmark for evaluating large-scale training.

**Models** We employ a variety of widely-used DNN architectures to evaluate the performance and training speed. We use ResNet-18 [11], Wide ResNet-28-10 [32], and PyramidNet-110 [10] for the training in CIFAR-10/100 datasets. We use ResNet and Vision Transformer [5] models with various sizes on the ImageNet dataset.

**Baselines** We take the vanilla (AdamW for ViT, SGD for the other models), SAM [8], ESAM [6], GSAM [37], and LookSAM [21] as the baselines. ESAM and LookSAM are SAM's follow-up works that improve efficiency. GSAM achieves the best performance among the SAM's variants.

**Implementation details** We set all the training hyperparameters to be the same for a fair comparison among the baselines and our proposed algorithms. The details of the training setting are displayed in Appendix. We follow the settings of [2, 21, 6, 37] on the ImageNet datasets which is different from the experimental setting of SAM [8]. The codes are implemented based on the TIMM framework [30]. The ResNets are trained with a batch size of 4096, 1.4 learning rate, 90 training epochs, and SGD optimizer (momentum=0.9) over 8 Nvidia V-100 GPU cards. The ViTs are trained with 300 training epochs and AdamW optimizer ($\beta_1 = 0.9, \beta_2 = 0.999$). We only conduct the basic data augmentation for the training on both CIFAR and ImageNet (Inception-style data augmentation). The hyperparameters of SAF and MESA are obtained via grid searches on the CIFAR datasets, which are consistent among various DNNs architectures and various datasets. We set $\tau = 5, \tilde{E} = 3, E_{\text{start}} = 5$ for all the experiments on CIFAR, $\lambda \in \{0.3, 0.8\}$ for SAF and MESA , respectively.

Table 1: Classification accuracies and training speeds on the ImageNet dataset. The numbers in parentheses (·) indicate the ratio of the training speed w.r.t. the vanilla base optimizer's (SGD's) speed. Green indicates improvement compared to SAM, whereas red suggests a degradation.

| ImageNet | ResNet-50 | | ResNet-101 | |
| --- | --- | --- | --- | --- |
| | Accuracy | images/s | Accuracy | images/s |
| Vanilla (SGD) | 76.0 | 1,627 (100%) | 77.8 | 1,042 (100%) |
| SAM [8] | 76.9 | 802 (49.3%) | 78.6 | 518 (49.7%) |
| ESAM [1] [6] | 77.1 | 1,037 (63.7%) | 79.1 | 650 (62.4%) |
| GSAM [2] [37] | 77.2 | 783 (48.1%) | 78.9 | 503 (48.3%) |
| SAF (Ours) | **77.8** | 1,612 (99.1%) | **79.3** | 1,031 (99.0%) |
| MESA (Ours) | 77.5 | 1,386 (85.2%) | 79.1 | 888 (85.4%) |

| ImageNet | ResNet-152 | | ViT-S/32 | |
| --- | --- | --- | --- | --- |
| | Accuracy | images/s | Accuracy | images/s |
| Vanilla[3] | 78.5 | 703 (100%) | 68.1 | 5,154 (100%) |
| SAM [8] | 79.3 | 351 (49.9%) | 68.9 | 2,566 (49.8%) |
| LookSAM[4] [21] | - | - | 68.8 | 4,273 (82.9%) |
| GSAM[2] [37] | **80.0** | 341 (48.5%) | **73.8** | 2,469 (47.9%) |
| SAF (Ours) | 79.9 | 694 (98.7%) | 69.5 | 5,108 (99.1%) |
| MESA (Ours) | **80.0** | 601 (85.5%) | 69.6 | 4,391 (85.2%) |

## 4.2 Experimental Results

**ImageNet** Our proposed SAF and MESA achieve better performance on the ImageNet dataset compared to the other competitors. We report the best test accuracies and the average training speeds in Table 1. The experiment results demonstrate that SAF incurs no additional computational overhead to ensure that the training speed is the same as the base optimizer—SGD. We observe that SAF and MESA perform better in the large-scale datasets. SAF trains DNN at a douled speed than SAM (SAF 99.2% vs SAM 50%). MESA achieves a training speed which is 84% to 85% that of SGD. Concerning the performance, both SAF and MESA outperform SAM up to (0.9%) on the ImageNet dataset. More importantly, SAF and MESA achieve a new state-of-the-art results of SAM's follow-up works on the ImageNet datasets trained with ResNets.

**CIFAR10 and CIFAR100** We ran all the experiments three times with different random seeds for fair comparisons. We summarize the results in Table 3, in the same way as we do for the experiments on the ImageNet dataset. The training speed is consistent with the results on ImageNet. Similarly, SAF and MESA outperform SAM on large-scale models—Wide Resnet and PyradmidNets.

## 4.3 Discussion

**Memory Usage** We evaluate the additional memory usage of SAF and MESA on the ImageNet dataset with the ResNet-50 model. We only present the results on the ImageNet in Table 2, because

---

[1]We report in [6], as ESAM only release their codes in Single-GPU environment.

[2]We report the results in [37], but failed to reproduce them using the officially released codes.

[3]We use base optimizers SGD for ResNet-152 and AdamW for ViT-S/32.

[4]The authors of LookSAM have not released their code for either Single- or Multi-GPU environments; hence we report the results in [21]. LookSAM only reports results for ViTs and there are no results for ResNet.

(a) Training loss vs Epochs of SAF.

(b) The SAM's sharpness measure vs epochs

Figure 4: **Left**: The change of the vanilla loss (exclude the trajectory loss) in each epoch. SAF does not affect the convergence of the training. **Right**: The change of sharpness, which is the measurement proposed by SAM with $\rho = 0.05$. SAF and MESA decrease the sharpness measure of SAM significantly.

the memory usage of SAF on the CIFAR dataset is negligible (57 Mb). MESA saves $99.3\%$ memory usage compared to SAF, which allows MESA to be deployed on extremely large-scale datasets.

**Convergence Rate** Intuitively, SAF minimizes the trajectory loss to control the rate of training loss change to obtain flat minima. A critical problem of SAF may be SAF's influence on the convergence rate. We empirically show that the change of the sharpness-inducing term in SAF and MESA (compared to SAM) will not affect the convergence rate during training. Figure 4a illustrates the change of the training loss in each epoch of SGD, SAM, SAF, and MESA . It shows that SAF and MESA converge at the same rate as SGD and SAM.

Table 2: The additional memory used by SAF and MESA on the ImageNet dataset.

| Algorithms | Extra Memory Usage |
| --- | --- |
| SAF | 14,643 MB |
| MESA | 98 MB |

**Sharpness** We empirically demonstrate that the trajectory loss can be a reliable substitute of the sharpness loss proposed by SAM. We plot the sharpness, which is the measurement of SAM in Equation 6, in each epoch of SAM, SGD, SAF, and MESA during training. As shown in Figure 4b, SAF and MESA minimize the sharpness as SAM does throughout the entire training procedure. Both SAF's and MESA's sharpnesses drop significantly at epoch 5, from which the trajectory loss start to be minimized. SAM's sharpness is lower than SAF's and MESA's in the second half of the training. A plausible reason is that SAM minimizes the sharpness directly. However, SAF and MESA outperform SAM in terms of the test accuracies, as demonstrated in Table 1.

Figure 5: Loss landscapes visualization of the PyramidNet-110 model on the CIFAR-100 dataset trained with SGD, SAM, our proposed SAF and MESA.

**Visualization of Loss Landscapes** We also demonstrate that minimizing the trajectory loss is an effective way to obtain flat minima. We visualize the loss landscape of converged minima trained by SGD, SAM, SAF, and MESA in Figures 2 and 5. We follow the method to do the plotting proposed by [18], which has also been used in [6, 2]. The $x$- and $y$-axes represent two random sampled orthogonal Gaussian perturbations. We sampled $100 \times 100$ points with random Gaussian perturbations for visualization. The visualized loss landscape clearly demonstrate that SAF can converge to a region as flat as SAM does.

## 5 Other Related Works

The first work that revealed the relation between the generalization ability and the geometry of the loss landscape (sharpness) can be traced back to [13]. Following that, many studies verified the relation between the flat minima and the generalization error [15, 4, 14, 20, 18, 7, 24] . Specifically, Keskar *et al.* [15] proposed a sharpness measure and indicated the negative correlation between the

Table 3: Classification accuracies and training speed on the CIFAR-10 and CIFAR-100 datasets. The numbers in parentheses (·) indicate the ratio of the training speed w.r.t. the vanilla base optimizer's (SGD's) speed. Green indicates improvement compared to SAM, whereas red suggests a degradation.

| | CIFAR-10 | | CIFAR-100 | |
|---|---|---|---|---|
| **ResNet-18** | Accuracy | images/s | Accuracy | images/s |
| Vanilla (SGD) | $95.61_{\pm 0.02}$ | 3,289 (100%) | $78.32_{\pm 0.02}$ | 3,314 (100%) |
| SAM [8] | $\mathbf{96.50}_{\pm 0.08}$ | 1,657 (50.4%) | $\mathbf{80.18}_{\pm 0.08}$ | 1,690 (51.0%) |
| SAF (Ours) | $96.37_{\pm 0.02}$ | 3,213 (97.6%) | $80.06_{\pm 0.05}$ | 3,248 (98.0%) |
| MESA (Ours) | $96.24_{\pm 0.02}$ | 2,780 (84.5%) | $79.79_{\pm 0.09}$ | 2,793 (84.3%) |
| **ResNet-101** | Accuracy | images/s | Accuracy | images/s |
| Vanilla (SGD) | $96.52_{\pm 0.04}$ | 501 (100%) | $80.68_{\pm 0.16}$ | 501 (100%) |
| SAM [8] | $\mathbf{97.01}_{\pm 0.32}$ | 246 (49.1%) | $\mathbf{82.99}_{\pm 0.04}$ | 249 (49.7%) |
| SAF (Ours) | $96.93_{\pm 0.05}$ | 497 (99.2%) | $82.84_{\pm 0.19}$ | 497 (99.2%) |
| MESA (Ours) | $96.90_{\pm 0.23}$ | 425 (84.8%) | $82.51_{\pm 0.27}$ | 426 (85.0%) |
| **Wide-28-10** | Accuracy | images/s | Accuracy | images/s |
| Vanilla (SGD) | $96.50_{\pm 0.05}$ | 732 (100%) | $81.67_{\pm 0.18}$ | 739 (100%) |
| SAM [8] | $97.07_{\pm 0.11}$ | 367 (50.1%) | $83.51_{\pm 0.04}$ | 370 (50.0%) |
| SAF (Ours) | $97.08_{\pm 0.15}$ | 727 (99.3%) | $\mathbf{83.81}_{\pm 0.04}$ | 729 (98.6%) |
| MESA (Ours) | $\mathbf{97.16}_{\pm 0.23}$ | 617 (84.3%) | $83.59_{\pm 0.24}$ | 625 (84.6%) |
| **PyramidNet-110** | Accuracy | images/s | Accuracy | images/s |
| Vanilla (SGD) | $96.66_{\pm 0.09}$ | 394 (100%) | $81.94_{\pm 0.06}$ | 401 (100%) |
| SAM [8] | $97.25_{\pm 0.15}$ | 194 (49.3%) | $84.61_{\pm 0.06}$ | 198 (49.4%) |
| SAF (Ours) | $97.34_{\pm 0.06}$ | 391 (99.2%) | $84.71_{\pm 0.01}$ | 397 (99.0%) |
| MESA (Ours) | $\mathbf{97.46}_{\pm 0.09}$ | 332 (84.3%) | $\mathbf{84.73}_{\pm 0.14}$ | 339 (84.5%) |

sharpness measure and the generalization abilities. Dinh *et al.* [4] further argued that the sharpness measure can be related to the spectrum of the Hessian, whose eigenvalues encode the curvature information of the loss landscape. Jiang *et al.* [14] demonstrated that one of the sharpness-based measures is the most correlated one among 40 complexity measures by a large-scale empirical study.

SAM [8] solved the sharp minima problem by modifying training schemes to approximate and minimize a certain sharpness measure. The concurrent works [31, 34] propose a model to adversarially perturb trained weights to bias the convergence. The aforementioned methods lead the way for sharpness-aware training despite the computational overhead being doubled over that of the base optimizer. Subsequently, LookSAM [21] and Efficient SAM (ESAM) [6] were proposed to alleviate the computational issue of SAM. Apart from efficiency issues, Surrogate Gap Guided Sharpness-Aware Minimization (GSAM) [37] was proposed to further improve SAM's performance. GSAM places more emphasis on the gradients that minimize the sharpness loss to achieve the best generalization performance among all the research that followed SAM.

## 6 Conclusion and Future Research

In this work, we introduce a novel trajectory loss as an equivalent measure of sharpness, which requires almost no additional computational overhead and preserves the superior performance of sharpness-aware training [8, 6, 37, 21]. In addition to deriving a novel trajectory loss that penalizes sharp and sudden drops in the objective function, we propose a novel sharpness-aware algorithm SAF, which achieves impressive performances in terms of its accuracies on the benchmark CIFAR and ImageNet datasets. More importantly, SAF trains DNNs *at the same speed* as non-sharpness-aware training (e.g., SGD). We also propose MESA as a memory-efficient variant of SAF to avail sharpness-aware training on extremely large-scale datasets. In future research, we will further enhance SAF to automatically sense the current state of training and alter the training dynamics accordingly. We will also evaluate SAF in more learning tasks (such as natural language processing) and enhance it to become a general-purpose training strategy.

# References

[1] Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In *International Conference on Machine Learning*, pages 254–263. PMLR, 2018.

[2] Xiangning Chen, Cho-Jui Hsieh, and Boqing Gong. When vision transformers outperform resnets without pretraining or strong data augmentations. *arXiv preprint arXiv:2106.01548*, 2021.

[3] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[4] Laurent Dinh, Razvan Pascanu, Samy Bengio, and Yoshua Bengio. Sharp minima can generalize for deep nets. In *International Conference on Machine Learning*, pages 1019–1028. PMLR, 2017.

[5] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[6] Jiawei Du, Hanshu Yan, Jiashi Feng, Joey Tianyi Zhou, Liangli Zhen, Rick Siow Mong Goh, and Vincent YF Tan. Efficient sharpness-aware minimization for improved training of neural networks. *arXiv preprint arXiv:2110.03141*, 2021.

[7] Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. *arXiv preprint arXiv:1703.11008*, 2017.

[8] Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. In *International Conference on Learning Representations*, 2020.

[9] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.

[10] Dongyoon Han, Jiwhan Kim, and Junmo Kim. Deep pyramidal residual networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5927–5935, 2017.

[11] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[12] Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

[13] Sepp Hochreiter and Jürgen Schmidhuber. Simplifying neural nets by discovering flat minima. In *Advances in neural information processing systems*, pages 529–536, 1995.

[14] Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. In *International Conference on Learning Representations*, 2019.

[15] Nitish Shirish Keskar, Jorge Nocedal, Ping Tak Peter Tang, Dheevatsa Mudigere, and Mikhail Smelyanskiy. On large-batch training for deep learning: Generalization gap and sharp minima. In *5th International Conference on Learning Representations, ICLR 2017*, 2017.

[16] Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In *European conference on computer vision*, pages 491–507. Springer, 2020.

[17] Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. CIFAR-10 and CIFAR-100 datasets. *URl: https://www. cs. toronto. edu/kriz/cifar. html*, 6(1):1, 2009.

[18] Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. *arXiv preprint arXiv:1712.09913*, 2017.

[19] Tengyuan Liang, Tomaso Poggio, Alexander Rakhlin, and James Stokes. Fisher-rao metric, geometry, and complexity of neural networks. In *The 22nd international conference on artificial intelligence and statistics*, pages 888–896. PMLR, 2019.

[20] Chen Liu, Mathieu Salzmann, Tao Lin, Ryota Tomioka, and Sabine Süsstrunk. On the loss landscape of adversarial training: Identifying challenges and how to overcome them. *Advances in Neural Information Processing Systems*, 33:21476–21487, 2020.

[21] Yong Liu, Siqi Mai, Xiangning Chen, Cho-Jui Hsieh, and Yang You. Towards efficient and scalable sharpness-aware minimization. *arXiv preprint arXiv:2203.02714*, 2022.

[22] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10012–10022, 2021.

[23] David A McAllester. Pac-bayesian model averaging. In *Proceedings of the twelfth annual conference on Computational learning theory*, pages 164–170, 1999.

[24] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Jonathan Uesato, and Pascal Frossard. Robustness via curvature regularization, and vice versa. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9078–9086, 2019.

[25] Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. *arXiv preprint arXiv:1707.09564*, 2017.

[26] Chen Sun, Abhinav Shrivastava, Saurabh Singh, and Abhinav Gupta. Revisiting unreasonable effectiveness of data in deep learning era. In *Proceedings of the IEEE international conference on computer vision*, pages 843–852, 2017.

[27] Ilya O Tolstikhin, Neil Houlsby, Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Thomas Unterthiner, Jessica Yung, Andreas Steiner, Daniel Keysers, Jakob Uszkoreit, et al. Mlp-mixer: An all-mlp architecture for vision. *Advances in Neural Information Processing Systems*, 34, 2021.

[28] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pages 10347–10357. PMLR, 2021.

[29] Yusuke Tsuzuku, Issei Sato, and Masashi Sugiyama. Normalized flat minima: Exploring scale invariant definition of flat minima for neural networks using pac-bayesian analysis. In *International Conference on Machine Learning*, pages 9636–9647. PMLR, 2020.

[30] Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

[31] Dongxian Wu, Shu-Tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization. *Advances in Neural Information Processing Systems*, 33:2958–2969, 2020.

[32] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *British Machine Vision Conference 2016*. British Machine Vision Association, 2016.

[33] Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3):107–115, 2021.

[34] Yaowei Zheng, Richong Zhang, and Yongyi Mao. Regularizing neural networks via adversarial model perturbation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8156–8165, 2021.

[35] Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.

[36] Daquan Zhou, Zhiding Yu, Enze Xie, Chaowei Xiao, Anima Anandkumar, Jiashi Feng, and Jose M Alvarez. Understanding the robustness in vision transformers. *arXiv preprint arXiv:2204.12451*, 2022.

[37] Juntang Zhuang, Boqing Gong, Liangzhe Yuan, Yin Cui, Hartwig Adam, Nicha Dvornek, Sekhar Tatikonda, James Duncan, and Ting Liu. Surrogate gap minimization improves sharpness-aware training. *arXiv preprint arXiv:2203.08065*, 2022.