HIERARCHICAL FEW-SHOT IMITATION WITH SKILL TRANSITION MODELS

ABSTRACT

A desirable property of autonomous agents is the ability to both solve long-horizon problems and generalize to unseen tasks. Recent advances in data-driven skill learning have shown that extracting behavioral priors from offline data can enable agents to solve challenging long-horizon tasks with reinforcement learning. However, generalization to tasks unseen during behavioral prior training remains an outstanding challenge. To this end, we present Few-shot Imitation with Skill Transition Models (FIST), an algorithm that extracts skills from offline data and utilizes them to generalize to unseen tasks given a few downstream demonstrations. FIST learns an inverse skill dynamics model, a distance function, and utilizes a semi-parametric approach for imitation. We show that FIST is capable of generalizing to new tasks and substantially outperforms prior baselines in navigation experiments requiring traversing unseen parts of a large maze and 7-DoF robotic arm experiments requiring manipulating previously unseen objects in a kitchen.

1 INTRODUCTION

We are interested in developing control algorithms that enable robots to solve complex and practical tasks such as operating kitchens or assisting humans with everyday chores at home. There are two general characteristics of real-world tasks – long-horizon planning and generalizability. Practical tasks are often long-horizon in the sense that they require a robot to complete a sequence of subtasks. For example, to cook a meal a robot might need to prepare ingredients, place them in a pot, and operate the stove before the full meal is ready. Additionally, in the real world many tasks we wish our robot to solve may differ from tasks the robot has completed in the past but require a similar skill set. For example, if a robot learned to open the top cabinet drawer it should be able to quickly adapt that skill to open the bottom cabinet drawer. These considerations motivate our research question: *how can we learn skills that enable robots to generalize to new long-horizon downstream tasks?*

Recently, learning data-driven behavioral priors has become a promising approach to solving long-horizon tasks. Given a large unlabeled offline dataset of robotic demonstrations solving a diverse set of tasks this family of approaches Singh et al. (2020); Pertsch et al. (2020); Ajay et al. (2021) extract behavioral priors by fitting maximum likelihood expectation latent variable models to the offline dataset. The behavioral priors are then used to guide a Reinforcement Learning (RL) algorithm to solve downstream tasks. By selecting skills from the behavioral prior, the RL algorithm is able to explore in a structured manner and can solve long-horizon navigation and manipulation tasks. However, the generalization capabilities of RL with behavioral priors are limited since a different RL agent needs to be trained for each downstream task and training each RL agent often requires millions of environment interactions.

On the other hand, few-shot imitation learning has been a promising paradigm for generalization. In the few-shot imitation learning setting, an imitation learning policy is trained on an offline dataset of demonstrations and is then adapted in few-shot to a downstream task Duan et al. (2017). Few-shot imitation learning has the

Figure 1: In this work we are interested in enabling autonomous robots to solve complex long-horizon tasks that were unseen during training. To do so, we assume access to a large multi-task dataset of demonstrations, extract skills from the offline dataset, and adapt those skills to new tasks that were unseen during training.

added advantage over RL in that it is often easier for a human to provide a handful of demonstrations than it is to engineer a new reward function for a downstream task. However, unlike RL with behavioral priors, few-shot imitation learning is most often limited to short-horizon problems. The reason is that imitation learning policies quickly drift away from the demonstrations due to error accumulation Ross et al. (2011b), and especially so in the few-shot setting when only a handful of demonstrations are provided.

While it is tempting to simply combine data-driven behavioral priors with few-shot imitation learning, it is not obvious how to do so since the two approaches are somewhat orthogonal. Behavioral priors are trained on highly multi-modal datasets such that a given state can correspond to multiple skills. Given a sufficiently large dataset of demonstrations for the downstream task the imitation learning algorithm will learn to select the correct mode. However, in the few-shot setting how do we ensure that during training on downstream data we choose the right skill? Additionally, due to the small sample size and long task horizon it is highly likely that a naive imitation learning policy will drift from the few-shot demonstrations. How do we prevent the imitation learning policy from drifting away from downstream demonstrations?

The focus of our work is the setup illustrated in Figure 1; we introduce Few-Shot Imitation Learning with Skill Transition Models (FIST), a new algorithm for few-shot imitation learning with skills that enables generalization to unseen but semantically similar long-horizon tasks to those seen during training. Our approach addresses the issues with skill selection and drifting in the few-shot setting with two main components. First, we introduce an inverse skill dynamics model that conditions the behavioral prior not only on the current state but also on a future state, which helps FIST learn uni-modal future conditioned skill distribution that can then be utilized in few-shot. The inverse skill model is then used as a policy to select skills that will take the agent to the desired future state. Second, we train a distance function to find the state for conditioning the inverse skill model during evaluation. By finding states along the downstream demonstrations that are closest to the current state, FIST prevents the imitation learning policy from drifting. We show that our method results in policies that are able to generalize to new long-horizon downstream tasks in navigation environments and multi-step robotic manipulation tasks in a kitchen environment. To summarize, we list our three main contributions:

1. We introduce FIST - an imitation learning algorithm that learns an inverse skill dynamics model and a distance function that is used for semi-parametric few-shot imitation.

2. We show that FIST can solve long-horizon tasks in both navigation and robotic manipulation settings that were unseen during training and outperforms previous behavioral prior and imitation learning baselines.

3. We provide insight into how different parts of the FIST algorithm contribute to final performance by ablating different components of our method such as future conditioning and fine-tuning on downstream data.

2 Related Work

Our approach combines ingredients from imitation learning and skill extraction to produce policies that can solve long-horizon tasks and generalize to tasks that are out of distribution but semantically similar to those encountered in the training set. We cover the most closely related work in imitation learning, skill extraction, and few-shot generalization.

Imitation Learning: Imitation learning is a supervised learning problem where an agent extracts a policy from a dataset of demonstrations. The two most common approaches to imitation are Behavior Cloning Pomerleau (1988); Ross et al. (2011a) and Inverse Reinforcement Learning (IRL) Ng & Russell (2000). BC approaches learn policies $\pi_\theta(a|s)$ that most closely match the state-conditioned action distribution of the demonstration data. IRL approaches learn a reward function from the demonstration data assuming that the demonstrations are near-optimal for a desired task and utilize Reinforcement Learning to produce policies that maximize the reward. For simplicity and to avoid learning a reward function, in this work we aim to learn generalizable skills and using the BC approach. However, two drawbacks of BC are that the imitation policies require a large number of demonstrations and are prone to drifting away from the demonstration distribution during evaluation due to error accumulation Ross et al. (2011b). For this reason, BC policies work best when the time-horizon of the task is short.

Skill Extraction with Behavioral Priors: Methods that leverage behavioral priors utilize offline datasets of demonstrations to bias a policy towards the most likely skills in the datasets. While related closely to imitation learning, behavioral priors have been mostly applied to improve Reinforcement Learning. Behavioral priors learned through maximum likelihood latent variable models have been used for structured exploration in RL Singh et al. (2020), to solve complex long-horizon tasks from sparse rewards Pertsch et al. (2020), and regularize offline RL policies Wu et al. (2019); Peng et al. (2019); Nair et al. (2020). While impressive, RL with data-driven behavioral priors does not generalize to new tasks efficiently, often requiring millions of environment interactions to converge to an optimal policy for a new task.

Few-Shot Learning: Few-shot learning Wang et al. (2020) has been studied in the context of image recognition Vinyals et al. (2016); Koch et al. (2015), reinforcement learning Duan et al. (2016), and imitation learning Duan et al. (2017). In the context of reinforcement and imitation learning, few-shot learning is often cast as a meta-learning problem Finn et al. (2017); Duan et al. (2016; 2017), with often specialized datasets of demonstrations that labeled by tasks. However, there are other means of attaining few-shot generalization that do not require such expensive sources of data. Recently, advances in unsupervised representation learning in natural language processing Radford et al. (2019); Brown et al. (2020) and vision He et al. (2020); Chen et al. (2020) have shown how a network pre-trained with a self-supervised objective can be finetuned or adjusted with a linear probe to generalize in few-shot or even zero-shot Radford et al. (2021) to a downstream task. Our approach to few-shot imitation learning is loosely inspired by the generalization capabilities of networks pre-trained with unsupervised objectives. Our approach first fits a behavioral prior to an *unlabeled* offline dataset of demonstrations to extract skills and then fits an imitation learning policy over the previously acquired skills to generalize in few-shot to new tasks.

3 Approach

3.1 Problem Formulation

Few-shot Imitation Learning: We denote a demonstration as a sequence of states and actions: $\tau = \{s_1, a_1, s_2, a_2, \ldots, s_T, a_T\}$. In a few-shot setting we assume access to a small dataset of M such expert demonstrations $\mathcal{D}^{\text{demo}} = \{\tau_i\}_{i=1}^{i=M}$ that fulfill a specific long horizon task in the environment. For instance a sequence of sub-tasks in a kitchen environment such as moving the kettle, turning on the burner and opening a cabinet door. The goal is to imitate this behavior using only a few available example trajectories.

Figure 2: Our algorithm – Few-Shot Imitation Learning with Skill Transition Models (FIST) – is composed of three parts: (a) *Skill Extraction:* we fit a skill encoder, decoder, inverse skill dynamics model, and a distance function to the offline dataset; (b) *Skill Adaptation:* For downstream task, we are given a few demonstrations and adapt the skills learned in (a), by fine-tuning the encoder, decoder, and the inverse model. (c) *Few-Shot Imitation:* finally, to imitate the downstream demonstrations, we utilize the distance function to perform a look ahead along the demonstration to condition the inverse model and decode an action.

Skill Extraction: In this work we assume access to an unlabeled offline dataset of prior agent interactions with the environment in the form of N reward-free trajectories $\{\tau_i = \{(s_t, a_t)\}_{t=1}^{t=T_i}\}_{i=1}^{i=N}$. We further assume that these trajectories include semantically meaningful skills that are composable to execute long horizon tasks in the environment. This data can be collected from past tasks that have been attempted, or be provided by human-experts through teleoperation Zhang et al. (2018).

Skill extraction refers to an unsupervised learning approach that utilizes this reward-free and task-agnostic dataset to learn a skill policy in form of $\pi_\theta(a|s, z)$ where a is action, s is the current state, and z is the skill. Our hypothesis is that by combining these skill primitives we can solve semantically similar long-horizon tasks that have not directly been seen during the training. In this work we propose a new architecture for skill extraction based on continuous latent variable models that enables a semi-parametric evaluation procedure for few-shot imitation learning.

3.2 Hierarchical Few-Shot Imitation with Skill Transition Models

Our method, shown in Fig. 2, has three components: (i) Skill extraction, (ii) Skill adaptation via fine-tuning on few-shot data, and (iii) Evaluating the skills using a semi-parametric approach to enable few-shot imitation.

(i) Skill Extraction from Offline Data: We define a continuous skill $z_i \in \mathcal{Z}$ as an embedding for a sequence of state-action pairs $\{s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1}\}$ with a fixed length H. This temporal abstraction of skills has proven to be useful in prior work Pertsch et al. (2020); Ajay et al. (2021), by allowing a hierarchical decomposition of skills to achieve long horizon downstream tasks. To learn the latent space $\mathcal{Z}$ we propose training a continuous latent variable model with the encoder as $q_\phi(z|s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1})$ and the decoder as $\pi_\theta(a|s, z)$. The encoder outputs a distribution over the latent variable z that best explains the variation in the state-action pairs in the sub-trajectory.

The encoder is an LSTM that takes in the sub-trajectory of length H and outputs the parameters of a Gaussian distribution as the variational approximation over the true posterior $p(z|s_t, a_t, \ldots, s_{t+H-1}, a_{t+H-1})$. The

decoder is a policy that maximizes the log-likelihood of actions of the sub-trajectory conditioned on the current state and the skill. We implement the decoder as a feed-forward network which takes in the current state s_t and the latent vector z and regresses the action vector directly. This architecture resembles prior works on skill extraction Pertsch et al. (2020).

To learn parameters ϕ and θ, we randomly sample batches of H-step continuous sub-trajectories from the training data $\mathcal{D}$ and maximize the evidence lower bound (ELBO):

$$\log p(a_t|s_t) \geq \mathbb{E}_{\tau \sim \mathcal{D}, z \sim q_\phi(z|\tau)}[\underbrace{\log \pi_\theta(a_t|s_t, z)}_{\mathcal{L}_{\text{rec}}} + \beta \underbrace{(\log p(z) - \log q_\phi(z|\tau))}_{\mathcal{L}_{\text{reg}}}] \tag{1}$$

where the posterior $q_\phi(z|\tau)$ is regularized by its Kullback-Leibler (KL) divergence from a unit Gaussian prior $p(z) = \mathcal{N}(0, I)$ and β is a parameter that tunes the regularization term Higgins et al. (2016).

To enable quick few-shot adaptation over skills we learn an inverse skill dynamics model $q_\psi(z|s_t, s_{t+H-1})$ that infers which skills should be used given the current state and a future state that is H steps away. To train the inverse skill dynamics model we minimize the KL divergence between the approximated skill posterior $q_\phi(z|\tau)$ and the output of the state conditioned skill prior. This will result in minimizing the following loss with respect to the parameters ψ:

$$\mathcal{L}_{\text{prior}}(\psi) = \mathbb{E}_{\tau \sim \mathcal{D}}\left[D_{KL}(q_\phi(z|\tau), q_\psi(z|s_t, s_{t+H-1}))\right]. \tag{2}$$

We use a reverse KL divergence to ensure that our inverse dynamics model has a broader distribution than the approximate posterior to ensure mode coverage Bishop (2006). In our implementation we use a feed-forward network that takes in the concatenation of the current and future state and outputs the parameters of a Gaussian distribution over z. Conditioning on the future enables us to make a more informative decision on what skills to execute which is a key enabler to few-shot imitation. We jointly optimize the skill extraction and inverse model with the following loss:

$$\mathcal{L}(\phi, \theta, \psi) = \mathcal{L}_{\text{rec}}(\phi, \theta) + \beta \mathcal{L}_{\text{reg}}(\phi) + \mathcal{L}_{\text{prior}}(\psi) \tag{3}$$

(ii) Skill Adaption via Fine-tuning on Downstream Data : To improve the consistency between the unseen downstream demonstrations and the prior over skills, we use the demonstrations to fine-tune the parameters of the architecture by taking gradient steps over the loss in Equation 3. In the experiments we ablate the performance of FIST with and without fine-tuning to highlight the differences.

(iii) Semi-parametric Evaluation for Few-shot Imitation Learning: To run the agent, we need to first sample a skill $z \sim q_\psi(z|s_t, s_t^*)$ based on the current state and the future state that it seeks to reach. Then, we can use the low-level decoder $\pi(a_t|z, s_t)$ to convert that sampled skill z and the current state s_t to the corresponding action a_t. During evaluation we use the demonstrations $\mathcal{D}^{\text{demo}}$ to decide which state to use as the future state to condition on. For this purpose we use a learned distance function $d(s, s')$ to measure the distance between the current state s_t and every other state in the demonstrated trajectories. Then, from the few-shot data we find the closest state s_t^* to the current state according to the distance metric:

$$s_t^* = \min_{s_{ij} \in \mathcal{D}^{\text{demo}}} d(s_t, s_{ij}) \tag{4}$$

where s_{ij} is the j^{th} state in the i^{th} trajectory in $\mathcal{D}^{\text{demo}}$. We then condition the inverse dynamics model on the current state s_t and the state s_{t+H}^*, H steps ahead of s_t^*, within the trajectory that s_t^* belongs to. If by adding H steps we reach the end of the trajectory, we use the end state within the trajectory as the target future state.

The reason for this look-ahead adjustment is to ensure that the sampled skill always makes progress towards the future states of the demonstration. After the execution of action a_t according to the low-level decoder, the process is repeated until the fulfillment of the task. The procedure is summarized in Algorithm 1.

Algorithm 1 FIST: Evaluation Algorithm

1: **Inputs:** Fine-tuned inverse skill dynamics model $q_\psi(z|s_t, s_{t+H-1})$, fine-tuned skill policy $\pi_\theta(a|s, z)$, learned distance function $d(s, s')$, downstream demonstration $\mathcal{D}^{\text{demo}}$
2: Initialize the environment to s_0
3: **for** each $t = [1 \dots T]$ **do**
4:     Pick $s_t^{*'} = \text{LookAhead}(\min_{s \in \mathcal{D}^{\text{demo}}} d(s_t, s))$
5:     Sample skill $z \sim q_\psi(z|s_t, s_t^{*'})$
6:     Sample action $a \sim \pi_\theta(a|s_t, z)$
7:     $s_t \leftarrow \text{env.step}(a)$

3.3 LEARNING THE DISTANCE FUNCTION

To enable few-shot imitation learning we use a learned distance function to search for a goal state that is "close" to the current state of the agent. Learning contrastive distance metrics has been successfully applied in prior work both in navigation and manipulation experiments. Both Liu et al. (2020) and Emmons et al. (2020) utilize contrastive distance functions to build semi-parametric topological graphs, and Savinov et al. (2018) and Shah et al. (2020) use a similar approach for visual navigation. Inspired by the same idea, we also use a contrastive loss such that states that are H steps in the future are close to the current state while all other states are far. We refer the reader to the Appendix A.1 for further details.

4 EXPERIMENTS

In the experiments we are interested in answering the following questions: (i) Can our method successfully imitate unseen long-horizon downstream demonstrations? (ii) What is the importance of semi-parametric approach vs. future conditioning? (iii) Is pre-training and fine-tuning the skill embedding model necessary for achieving high success rate?

4.1 ENVIRONMENTS

We evaluate the performance of FIST on two simulated navigation environments and a robotic manipulation task from the D4RL benchmark as shown in Figure 3. To ensure generalizability to out-of-distribution tasks we remove some category of trajectories from the offline data and at test-time, we see if the agent can generalize to those unseen trajectories. Specifically for Pointmass and Ant environments we block some regions of the maze and at test-time we provide demonstration that move into the excluded region; and for Kitchen we exclude interactions with a few selected objects and at test-time we provide demonstrations that involve manipulating the excluded object. Further details on the environment setup and data collection procedure is provided in appendix B.

4.2 RESULTS

We use the following approaches for comparison: **BC+FT**: Trains a behavioral cloning agent (i.e. $\pi_\theta(a|s)$) on the offline dataset $\mathcal{D}$ and fine-tunes to the downstream dataset $\mathcal{D}^{\text{demo}}$. **SPiRL**: This is an extension of the existing skill extraction methods to imitation learning over skill space Pertsch et al. (2020). The skill

Figure 3: **Top**: In each environment, we block some part of the environment and collect task-agnostic and reward-free trajectories for extracting skills. In the kitchen environment, red markers indicate the objects that are excluded. **Bottom**: For downstream demonstrations, we use 10 expert trajectories that involve unseen parts of the maze or manipulation of unseen objects.

extraction method in SPiRL Pertsch et al. (2020) is very similar to FIST, but instead of conditioning the skill prior on the future state it only uses the current state. To adapt SPiRL to imitation learning, after pre-training the skills module, we fine-tune it on the downstream demonstrations $\mathcal{D}^{\text{demo}}$ (instead of finetuning with RL as proposed in the original paper). After fine-tuning we execute the skill prior for execution. **FIST (ours)**: This runs our semi-parametric approach after learning the future conditioned skill prior. After extracting skills from $\mathcal{D}$ we fine-tune the parameters on the downstream demonstrations $\mathcal{D}^{\text{demo}}$ and perform the proposed semi-parametric approach for evaluation.

Figure 4 compares the normalized average score on each unseen task from each domain. Each tick on x-axis presents either an excluded region (for Maze) or an excluded object (for Kitchen). The un-normalized scores are included in tables 5 and 6 in Appendix C.1. Here, we provide a summary of our key findings [1]:

(i) In the PointMaze environment, FIST consistently succeeds in navigating the point mass into all three goal locations. The skills learned by SPiRL fail to generalize when the point mass falls outside of the training distribution, causing it to get stuck in corners. While BC+FT also solves the task frequently in the Left and Bottom goal location, the motion of the point mass is sub-optimal, resulting in longer episode lengths.

(ii) In the AntMaze environment, FIST achieves the best performance compared to the baselines. SPiRL and BC+FT make no progress in navigating the agent towards the goal while FIST is able to frequently reach the goals in the demonstrated trajectories. We believe that the low success rate numbers in this experiment is due to the low quality of trajectories that exist in the offline skill dataset $\mathcal{D}$. In the dataset, we see many episodes with ant falling over, and FIST's failure cases also demonstrate the same behavior, hence resulting in a low success rate. We hypothesize that with a better dataset FIST can achieve a higher success rate number.

(iii) In the kitchen environment, FIST significantly outperforms SPiRL and BC+FT. FIST can successfully complete **3 out of 4** long-horizon object manipulation tasks in the same order required by the task. In one of these long-horizon tasks all algorithms perform similarly poor. We believe that such behavior is due to the

---

[1]The video of some of our experiments are included in the supplementary material.

Figure 4: Normalized Reward on all of our environments, and their excluded regions / objects. For maze, the episode length is subtracted from the maximum episode length, which is then divided by the maximum episode length. For kitchen, the reward is the number of sub-tasks completed in order, and normalized by the maximum of 4.0

fact that the majority of the trajectories in the pre-training dataset start with a microwave task and removing this sub-task can substantially decrease the diversity and number of trajectories seen during pre-training.

4.3 ABLATION STUDIES

In this section we study different components of the FIST algorithm to provide insight on the contribution of each part. We provide further ablations in Appendix C.2.

Effect of the Semi-parameteric evaluation and future conditioning of the skill prior. We recognize two major differences between FIST and SPiRL: (1) future conditioning of the skill prior during skill extraction (2) the semi-paramteric approach for picking the future state to condition on. In order to separately investigate the contribution of each part we performed an ablation with the following modifications of FIST and SPiRL on the kitchen environment: **FIST (Euc.)** is similar to our FIST experiment, except that we use the Euclidean distance on the raw state space, rather than our learned contrastive distance for lookup. Comparison to this baseline measure the importance of our contrastive distance method, compared to a simpler alternative; **SPiRL (closest)** uses the contrastive distance function to look-up the closest state in the demonstrations to sample the skill via $p(z|s_{\text{closest}})$; and **SPiRL (H-step)** uses the same H-step-ahead look-up approach as FIST and samples a skill based on $p(z|s_{\text{closest}+H})$.

Table 1: Ablation on the impact of semi-parameteric appraoch nd the future conditioning of skill prior

Task (Unseen)	FIST (ours)	FIST (Euc.)	SPiRL	SPiRL (closest)	SPiRL (H-steps)
Microwave, Kettle, **Top Burner**, Light Switch	$\mathbf{3.6 \pm 0.16}$	3.3 ± 0.15	2.1 ± 0.48	0.0 ± 0.0	0.2 ± 0.13
Microwave, Bottom Burner, Light Switch, Slide Cabinet	2.3 ± 0.5	$\mathbf{2.8 \pm 0.42}$	2.3 ± 0.49	2.8 ± 0.44	0.0 ± 0.0
Microwave, **Kettle**, Slide Cabinet, Hinge Cabinet	$\mathbf{3.5 \pm 0.3}$	3.0 ± 0.32	1.9 ± 0.29	0.0 ± 0.0	0.0 ± 0.0
Microwave, Kettle, **Slide Cabinet**, Hinge Cabinet	$\mathbf{4.0 \pm 0.0}$	1.3 ± 0.14	3.3 ± 0.38	2.4 ± 0.51	1.5 ± 0.41

Comparison of SPiRL results suggests that the performance would degrade if the semi-parameteric lookup method is used to pick the conditioning state in SPiRL. This is not surprising since the model in SPiRL is trained to condition on the current state and is unable to pick a good skill z based on $p(z|s_{\text{closest}})$ in SPiRL (closest) or $p(z|s_{\text{closest}+H})$ in SPiRL (H-steps). Therefore, it is crucial to have the prior as $p(z|s_t, s_{t+H})$, so that we can condition on both the current and future goal state.

We also note that FIST (Euc.) results are slightly worse in 3 out of 4 cases. This suggests that (1) contrastive distance is better than Euclidean to some degree (2) the environment's state space is simple enough that Euclidean distance still works to a certain extent. It is worth noting that the Euclidean distance, even with comparable results to the contrastive distance in the kitchen environment, is not a general distance metric to use and would quickly lose advantage when state representation gets complex (e.g. pixel representation).

The effect of skill pre-training and fine-tuning on FIST: To adjust the pre-trained skill-set to OOD tasks (e.g. moving the kettle while it is excluded from the skill dataset) FIST requires fine-tuning on the downstream demonstrations. We hypothesize that without fine-tuning, the agent should be able to perfectly imitate the demonstrated sub-trajectories that it has seen during training, but should start drifting away when encountered with an OOD skill. We also hypothesise that pre-training on a large dataset, even if it does not include the downstream demonstration sub-trajectories, is crucial for better generalization. Intuitively, pre-training provides a behavioral prior that is easier to adapt to unseen tasks than a random initialization.

To examine the impact of fine-tuning, we compare FIST with *FIST-no-FT* which directly evaluates the semi-parameteric approach with the model parameters trained on the skill dataset without fine-tuning on the downstream trajectories. To understand the effect of pre-training, we compare FIST with *FIST-no-pretrain* which is not pre-trained on the skill dataset. Instead, we directly train the latent variable and inverse skill dynamics model on the downstream data and perform the semi-parametric evaluation of the FIST algorithm.

From the results in Table 2, we observe that fine-tuning is a critical component for adapting to OOD tasks. The scores on *FIST-no-FT* indicate that the agent is capable of fulfilling the sub-tasks seen during skill pre-training but cannot progress onto unseen tasks without fine-tuning. Based on the scores on *FIST-no-pretrain*, we also find that the pre-training on a rich dataset, even when the downstream task is directly excluded, provides sufficient prior knowledge about the dynamics of the environment and can immensely help with generalization to unseen tasks via fine-tuning.

Table 2: We ablate the use of pre-training on offline data, as well as fine-tuning on downstream demonstrations. FIST-no-FT removes the fine-tuning on downstream demonstration step in FIST, while FIST-no-pretrain trains the skills purely from the given downstream data. Without seeing the subtask, FIST-no-FT is unable to solve the downstream subtask. Trained on only downstream data, FIST-no-pretrain is unable to properly manipulate the robot.

Task (Unseen)	FIST (ours)	FIST-no-FT	FIST-no-pretrain
Microwave, Kettle, **Top Burner**, Light Switch	$\mathbf{3.6 \pm 0.16}$	2.0 ± 0.0	0.5 ± 0.16
Microwave, Bottom Burner, Light Switch, Slide Cabinet	$\mathbf{2.3 \pm 0.5}$	0.0 ± 0.0	0.7 ± 0.15
Microwave, **Kettle**, Slide Cabinet, Hinge Cabinet	$\mathbf{3.5 \pm 0.3}$	1.0 ± 0.0	0.0 ± 0.0
Microwave, Kettle, **Slide Cabinet**, Hinge Cabinet	$\mathbf{4.0 \pm 0.0}$	2.0 ± 0.0	0.8 ± 0.13

5 CONCLUSION

We present FIST, a semi-parametric algorithm for few-shot imitation learning for long-horizon tasks that are unseen during training. We use previously collected trajectories of the agent interacting with the environment to learn a set of skills along with an inverse dynamics model that is then combined with a non-parametric approach to keep the agent from drifting away from the downstream demonstrations. Our approach is able to solve long-horizon challenging tasks in the few-shot setting where other methods fail.

REFERENCES

Anurag Ajay, Aviral Kumar, Pulkit Agrawal, Sergey Levine, and Ofir Nachum. {OPAL}: Offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=V69LGwJ0lIN.

Christopher M Bishop. *Pattern recognition and machine learning*. springer, 2006.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, 2020.

Yan Duan, John Schulman, Xi Chen, Peter L. Bartlett, Ilya Sutskever, and Pieter Abbeel. Rl^2: Fast reinforcement learning via slow reinforcement learning. *arXiv:1611.02779*, 2016.

Yan Duan, Marcin Andrychowicz, Bradly C. Stadie, Jonathan Ho, Jonas Schneider, Ilya Sutskever, Pieter Abbeel, and Wojciech Zaremba. One-shot imitation learning. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 1087–1098, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/ba3866600c3540f67c1e9575e213be0a-Abstract.html.

Scott Emmons, Ajay Jain, Michael Laskin, Thanard Kurutach, Pieter Abbeel, and Deepak Pathak. Sparse graphical memory for robust planning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/385822e359afa26d52b5b286226f2cea-Abstract.html.

Chelsea Finn, Tianhe Yu, Tianhao Zhang, Pieter Abbeel, and Sergey Levine. One-shot visual imitation learning via meta-learning. In *1st Annual Conference on Robot Learning, CoRL 2017, Mountain View, California, USA, November 13-15, 2017, Proceedings*, volume 78 of *Proceedings of Machine Learning Research*, pp. 357–368. PMLR, 2017. URL http://proceedings.mlr.press/v78/finn17a.html.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

Abhishek Gupta, Vikash Kumar, Corey Lynch, Sergey Levine, and Karol Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. *arXiv preprint arXiv:1910.11956*, 2019.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Conference on Computer Vision and Pattern Recognition*, 2020.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

Gregory Koch, Richard Zemel, and Ruslan Salakhutdinov. Siamese neural networks for one-shot image recognition. 2015.

Kara Liu, Thanard Kurutach, Christine Tung, Pieter Abbeel, and Aviv Tamar. Hallucinative topological memory for zero-shot visual planning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6259–6270. PMLR, 2020. URL http://proceedings.mlr.press/v119/liu20h.html.

Ashvin Nair, Abhishek Gupta, Murtaza Dalal, and Sergey Levine. Awac: Accelerating online reinforcement learning with offline datasets, 2020.

Andrew Y. Ng and Stuart J. Russell. Algorithms for inverse reinforcement learning. In Pat Langley (ed.), *Proceedings of the Seventeenth International Conference on Machine Learning (ICML 2000), Stanford University, Stanford, CA, USA, June 29 - July 2, 2000*, pp. 663–670. Morgan Kaufmann, 2000.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *CoRR*, abs/1910.00177, 2019. URL http://arxiv.org/abs/1910.00177.

Karl Pertsch, Youngwoon Lee, and Joseph J. Lim. Accelerating reinforcement learning with learned skill priors. In *Conference on Robot Learning (CoRL)*, 2020.

Dean Pomerleau. ALVINN: an autonomous land vehicle in a neural network. In David S. Touretzky (ed.), *Advances in Neural Information Processing Systems 1, [NIPS Conference, Denver, Colorado, USA, 1988]*, pp. 305–313. Morgan Kaufmann, 1988. URL http://papers.nips.cc/paper/95-alvinn-an-autonomous-land-vehicle-in-a-neural-network.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision, 2021.

Stéphane Ross, Geoffrey J. Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In Geoffrey J. Gordon, David B. Dunson, and Miroslav Dudík (eds.), *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, volume 15 of *JMLR Proceedings*, pp. 627–635. JMLR.org, 2011a. URL http://proceedings.mlr.press/v15/ross11a/ross11a.pdf.

Stéphane Ross, Geoffrey J. Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In Geoffrey J. Gordon, David B. Dunson, and Miroslav Dudík (eds.), *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, volume 15 of *JMLR Proceedings*, pp. 627–635. JMLR.org, 2011b. URL http://proceedings.mlr.press/v15/ross11a/ross11a.pdf.

Nikolay Savinov, Alexey Dosovitskiy, and Vladlen Koltun. Semi-parametric topological memory for navigation. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=SygwwGbRW.

Dhruv Shah, Benjamin Eysenbach, Gregory Kahn, Nicholas Rhinehart, and Sergey Levine. Ving: Learning open-world navigation with visual goals. *arXiv preprint arXiv:2012.09812*, 2020.

Avi Singh, Huihan Liu, Gaoyue Zhou, Albert Yu, Nicholas Rhinehart, and Sergey Levine. Parrot: Data-driven behavioral priors for reinforcement learning. In *International Conference on Learning Representations*, 2020.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Oriol Vinyals, Charles Blundell, Tim Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 3630–3638, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/90e1357833654983612fb05e3ec9148c-Abstract.html.

Yaqing Wang, Quanming Yao, James T. Kwok, and Lionel M. Ni. Generalizing from a few examples: A survey on few-shot learning. *ACM Comput. Surv.*, 53(3):63:1–63:34, 2020. doi: 10.1145/3386252. URL https://doi.org/10.1145/3386252.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *CoRR*, abs/1911.11361, 2019. URL http://arxiv.org/abs/1911.11361.

Tianhao Zhang, Zoe McCarthy, Owen Jow, Dennis Lee, Xi Chen, Ken Goldberg, and Pieter Abbeel. Deep imitation learning for complex manipulation tasks from virtual reality teleoperation. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pp. 1–8. IEEE, 2018. doi: 10.1109/ICRA.2018.8461249. URL https://doi.org/10.1109/ICRA.2018.8461249.