Conservative Dual Policy Optimization for Efficient Model-Based Reinforcement Learning

Abstract

Provably efficient Model-Based Reinforcement Learning (MBRL) based on optimism or posterior sampling (PSRL) is ensured to attain the global optimality asymptotically by introducing complexity measure of model. However, the complexity might grow exponentially for the simplest nonlinear models, where global convergence is impossible within finite iterations. When the model suffers a large generalization error, which is quantitatively measured by the model complexity, the uncertainty can be large. The sampled model that current policy is greedily optimized upon will thus be unsettled, resulting in aggressive policy updates and over-exploration. In this work, we propose *Conservative Dual Policy Optimization* (CDPO) that involves a *Referential Update* and a *Conservative Update*. The policy is first optimized under a reference model, which imitates the mechanism of PSRL while offering more stability. A conservative range of randomness is guaranteed by maximizing the expectation of model value. Without harmful sampling procedures, CDPO can still achieve the same regret as PSRL. More importantly, CDPO enjoys monotonic policy improvement and global optimality simultaneously. Empirical results also validate the exploration efficiency of CDPO.

1 Introduction

Model-Based Reinforcement Learning (MBRL) involves acquiring a model by interacting with the environment and learning to make the optimal decision using the model [55, 32]. MBRL is appealing due to its significantly reduced sample complexity compared to its model-free counterparts. However, greedy model exploitation that assumes the model is sufficiently accurate lacks guarantees for global optimality. The policies can be suboptimal and get stuck at local maxima even in simple tasks [10].

As such, several provably-efficient MBRL algorithms have been proposed. Based on the principle of *optimism in the face of uncertainty* (OFU) [56, 49, 10], OFU-RL achieves the global optimality by ensuring that the optimistically biased value is close to the real value in the long run. Based on Thompson Sampling [62], Posterior Sampling RL (PSRL) [57, 42, 43] explores by greedily optimizing the policy in an MDP which is sampled from the posterior distribution over MDPs. Beyond finite MDPs, to obtain a general bound that permits sample efficiency in various cases, we need to introduce additional complexity measure. For example, [49, 43] provide an $\widetilde{O}(\sqrt{d_E T})$ regret for both OFU and PSRL with eluder dimension d_E capturing how effectively the model generalizes. However, it is recently shown [13, 33] that the eluder dimension for even the simplest nonlinear models cannot be polynomially bounded. The effectiveness of the algorithms will thus be crippled.

The underlying reasons for such ineffectiveness are the aggressive policy updates and the over-exploration issue. Specifically, when a nonlinear model is used to fit complex transition functions, its generalizability will be poor compared to simple linear problems. If a random model is selected from the large hypothesis, e.g., optimistically chosen or sampled from posterior, it is "unsettled".

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

In other words, the selected model can change dramatically between successive iterations. Policy updates under this model will also be aggressive and thus causing value degradation. What's worse, large epistemic uncertainty results in an unrealistically model, which drives agents for uninformative exploration. An exploration step can only eliminate an exponentially small portion of the hypothesis.

In this work, we present *Conservative Dual Policy Optimization* (CDPO), a simple yet provable MBRL algorithm. As the sampling process in PSRL harms policy updates due to the unsettled model during training, we propose the *Referential Update* that greedily optimizes an intermediate policy under a *reference model*. It mimics the sampling-optimization procedure in PSRL, but offers more stability since we are free to set a steady reference model. We show that even without a sampling procedure, CDPO can match the expected regret of PSRL up to constant factors for any proper reference model, e.g., the least squares estimate where the confidence set is centered at. The *Conservative Update* step then follows to encourage exploration within a reasonable range. Specifically, the objective of a reactive policy is to maximize the *expectation* of model value, instead of a single model's value. These two steps are performed in an iterative manner in CDPO.

Theoretically, we show the statistical equivalence between CDPO and PSRL with the same order of expected regret. Additionally, we give the iterative policy improvement bound of CDPO, which guarantees monotonic improvement under mild conditions. We also establish the sublinear regret of CDPO, which permits its global optimality equipped with any model function class that has bounded complexity measure. To our knowledge, the proposed framework is the first that *simultaneously* enjoys global optimality and iterative policy improvement. Experimental results verify the existence of the over-exploration issue, and demonstrate the practical benefit of CDPO.

2 Background

2.1 Model-Based Reinforcement Learning

We consider the problem of learning to optimize an infinite-horizon γ-discounted Markov Decision Process (MDP) over repeated episodes of interaction. Denote the state space and action space as $\mathcal{S}$ and $\mathcal{A}$, respectively. When taking action $a \in \mathcal{A}$ at state $s \in \mathcal{S}$, the agent receives reward $r(s, a)$ and the environment transits into a new state according to probability $s' \sim f^*(\cdot | s, a)$. Here, f^* is a dirac measure for deterministic dynamics and is a probability distribution for probabilistic dynamics.

In model-based RL, the true dynamical model f^* is unknown and needs to be learned using the collected data through episodic (or iterative) interaction. The history data up to iteration t then forms $\mathcal{H}_t = \{\{s_{h,i}, a_{h,i}, s_{h+1,i}\}_{h=0}^{H-1}\}_{i=1}^{t-1}$, where H is the actual timesteps agents run in an episode. The posterior distribution of the dynamics model is estimated as $\phi(\cdot | \mathcal{H}_t)$. Alternatively, the frequentist model of the mean and uncertainty can also be estimated. Specifically, consider the model function class $\mathcal{F} = \{f : \mathcal{S} \times \mathcal{A} \to \mathcal{S}\}$ with size $|\mathcal{F}|$, which contains the real model $f^* \in \mathcal{F}$. The confidence set (or model hypothesis set) $\mathcal{F}_t \subset \mathcal{F}$ is introduced to represent the range of dynamics that is statistically plausible [49, 43, 10]. To ensure that $f^* \in \mathcal{F}_t$ with high probability, one way is to construct the confidence set as $\mathcal{F}_t := \{f \in \mathcal{F} \mid \|f - \widehat{f}_t^{LS}\|_{2, E_t} \leq \sqrt{\beta_t}\}$. Here, β_t is an appropriately chosen confidence parameter (via concentration inequality), the cumulative empirical 2-norm is defined by $\|g\|_{2, E_t}^2 := \sum_{i=1}^{t-1} \|g(x_i)\|_2^2$. The least squares estimate is

$$\widehat{f}_t^{LS} := \operatorname*{argmin}_{f \in \mathcal{F}} \sum_{(s, a, s') \in \mathcal{H}_t} \|f(s, a) - s'\|_2^2. \tag{2.1}$$

Denote the state and state-action value function associated with π on model f by $V_\pi^f : \mathcal{S} \to \mathbb{R}$ and $Q_\pi^f : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$, respectively, which are defined as

$$V_\pi^f(s) = \mathbb{E}\left[\sum_{h=0}^{\infty} \gamma^h r(s_h, a_h) \,\middle|\, s_0 = s, \pi, f\right], \quad Q_\pi^f(s, a) = \mathbb{E}\left[\sum_{h=0}^{\infty} \gamma^h r(s_h, a_h) \,\middle|\, s_0 = s, a_0 = a, \pi, f\right].$$

The objective of RL is to learn a policy $\pi^* = \operatorname{argmax}_\pi J(\pi)$ that maximizes the expected return $J(\pi)$. Denote the initial state distribution as ζ. Under policy π, the state visitation measure $\nu_\pi(s)$ over $\mathcal{S}$ and the state-action visitation measure $\rho_\pi(s, a)$ over $\mathcal{S} \times \mathcal{A}$ in the true MDP are defined as

$$\nu_\pi(s) = (1 - \gamma) \cdot \sum_{h=0}^{\infty} \gamma^h \cdot \mathbb{P}(s_h = s), \quad \rho_\pi(s, a) = (1 - \gamma) \cdot \sum_{h=0}^{\infty} \gamma^h \cdot \mathbb{P}(s_h = s, a_h = a), \tag{2.2}$$

where $s_0 \sim \zeta$, $a_h \sim \pi(\cdot|s_h)$ and $s_{h+1} \sim f^*(\cdot|s_h, a_h)$. The objective $J(\pi)$ is then

$$J(\pi) = \mathbb{E}_{s_0 \sim \zeta}[V_\pi^{f^*}(s_0)] = \mathbb{E}_{(s,a) \sim \rho_\pi}[r(s,a)] \tag{2.3}$$

2.2 Cumulative Regret and Asymptotic Optimality

A common criterion to evaluate RL algorithms is the cumulative regret, defined as the cumulative performance discrepancy between policy π_t at each iteration t and the optimal policy π^* over the run of the algorithm. The (cumulative) regret up to iteration T is defined as:

$$\text{Regret}(T, \pi, f^*) := \sum_{t=1}^{T} \int_{s \in \mathcal{S}} \zeta(s)(V_{\pi^*}^{f^*}(s) - V_{\pi_t}^{f^*}(s)), \tag{2.4}$$

In the Bayesian view, the model f^*, the learning policy π and the regret are random variables that must be learned from the gathered data. The Bayesian expected regret is defined as:

$$\text{BayesRegret}(T, \pi, \phi) := \mathbb{E}\left[\text{Regret}(T, \pi, f^*) \mid f^* \sim \phi\right]. \tag{2.5}$$

One way to prove the asymptotic optimality is to show that the (expected) regret is sublinear in T, so that π_t converges to π^* within sufficient iterations. To obtain the regret bound, the *width of confidence set* $\omega_t(s, a)$ is introduced to represent the maximum deviation between any two members in $\mathcal{F}_t$:

$$\omega_t(s,a) = \sup_{\underline{f}, \overline{f} \sim \mathcal{F}_t} \|\overline{f}(s,a) - \underline{f}(s,a)\|_2. \tag{2.6}$$

3 Provable Model-Based Reinforcement Learning

In this section, we analyze the central ideas and limitations of greedy algorithms as well as two popular theoretically justified frameworks: optimistic algorithms and posterior sampling algorithms.

Greedy Model Exploitation. Before introducing provable algorithms, we first analyze greedy model-based algorithms. In this framework, the agent takes actions assuming that the fitted model sufficiently accurately resembles the real MDP. Algorithms that lie in this category can be roughly divided into two groups: model-based planning and model-augmented policy optimization. For instance, Dyna agents [61, 20, 17] optimize policies using model-free learners with model-generated data. The model can also be exploited in first-order gradient estimators [18, 12, 9] or value expansion [15, 6]. On the other hand, model-based planning, or model-predictive control (MPC) [40, 41], directly generates optimal action sequences under the model in a receding horizon fashion.

However, greedily exploiting the model without *deep exploration* [45] will lead to suboptimal performance. The resulting policy can suffer from premature convergence, leaving the potentially high-reward region unexplored. Since the transition data is generated by the agent taking actions in the real MDP, the dual effect [4, 27] that current action influences *both* the next state and the model uncertainty is not considered by greedy model-based algorithms.

Optimism in the Face of Uncertainty. A common provable exploration mechanism is to adopt the principle of *optimism in the face of uncertainty* (OFU) [56, 49, 10]. With OFU, the agent assigns to its policy an optimistically biased estimate of virtual value by *jointly* optimizing over the policies and models inside the confidence set $\mathcal{F}_t$. At iteration t, the OFU-RL policy π_t is defined as:

$$\pi_t = \underset{\pi}{\arg\max} \max_{f_t \in \mathcal{F}_t} V_\pi^{f_t}. \tag{3.1}$$

Most asymptotic analyses of optimistic RL algorithms can be abstracted as showing two properties: the virtual value V_π^f is sufficiently high, and it is close to the real value $V_\pi^{f^*}$ in the long run. However, in complex environments where the generalizability of nonlinear models is limited, large epistemic uncertainty will result in an unrealistically large optimistic return that drives agents for uninformative exploration. What's worse, such suboptimal exploration steps eliminate only a small portion of the model hypothesis [13], leading to a slow converging process and suboptimal practical performance.

Posterior Sampling Reinforcement Learning. An alternative exploration mechanism is based on *Thompson Sampling* (TS) [62, 52], which involves selecting the maximizing action from a statistically

plausibly set of action values. These values can be associated with the MDP sampled from its posterior distribution, thus giving its name *posterior sampling for reinforcement learning* (PSRL) [57, 42, 43]. The algorithm begins with a prior distribution of f^*. At each iteration t, a model f_t is sampled from the posterior $\phi(\cdot|\mathcal{H}_t)$, and π_t is updated to be optimal under f_t:

$$f_t \sim \phi(\cdot|\mathcal{H}_t), \ \pi_t = \operatorname*{argmax}_{\pi} V_\pi^{f_t}. \tag{3.2}$$

The insight is to keep away from actions that are unlikely to be optimal in the real MDP. Exploration is guaranteed by the randomness in the sampling procedure. Unfortunately, executing actions that are optimally associated with a single sampled model can cause similar over-exploration issues [52, 51]. Specifically, an imperfect model sampled from the large hypothesis can cause aggressive policy updates and value degradation between successive iterations. The suboptimality degree of the resulting policies depends on the epistemic model uncertainty. Besides, executing π_t is not intended to offer performance improvement for follow-up policy learning, but only to narrow down the model uncertainty. However, this elimination procedure will be slow when the model suffers a large generalization error, which is quantitatively formulated in the model complexity measure below.

Complexity Measure and Generalization Bounds. In RL, we seek to have the sample complexity for finding a near-optimal policy or estimating an accurate value function. When given access to a generative model (i.e., an abstract sampling model) in finite MDPs, it is known that the (minimax) number of transitions the agent needs to observe can be sublinear in the model size, i.e. smaller than $O(|\mathcal{S}|^2|\mathcal{A}|)$. Beyond finite MDPs where the number of states is large (or countably or uncountably infinite), we are interested in the learnability or generalization of RL. Unfortunately, it is impossible for agnostic reinforcement learning that finds the best hypothesis in some given policy, value, or model hypothesis class: the number of needed samples depends exponentially on the problem horizon [24]. Despite of the structural assumptions, e.g. linear MDPs [67, 22, 66] or low-rank MDPs [21, 38], we focus on the generalization bounds that can cover various cases. This can be done with additional complexity measure, e.g. eluder dimension [49], witness rank [60], or bilinear rank [14].

By introducing the eluder dimension d_E [49], previous work [43, 44] established regret $\widetilde{O}(\sqrt{d_E T})$ for both OFU-RL and PSRL. Intuitively, the eluder dimension captures how effectively the model learned from observed data can extrapolate to future data, and permits sample efficiency in various (linear) cases. Nevertheless, it is shown in [13, 33] that even the simplest nonlinear models do not have polynomially-bounded eluder dimension. The following result is from Thm. 5.2 in Dong et al. [13] and similar results are also established in [33].

Theorem 3.1 (Eluder Dimension of Nonlinear Models [13]). The eluder dimension $dim_E(\mathcal{F}, \varepsilon)$ (c.f. Definition 5.4) of one-layer ReLU neural networks is at least $\Omega(\varepsilon^{-(d-1)})$, where d is the state-action dimension, i.e. $(s, a) \in \mathbb{R}^d$. With more layers, the requirement of ReLU activation can be relaxed.

As a result, additional complexity is hidden in the eluder dimension, e.g. when we choose $\varepsilon = T^{-1}$, regret $\widetilde{O}(\sqrt{d_E T})$ contains $d_E = \Omega(T^{d-1})$ and is no longer sublinear in T. In this case, previous provable exploration mechanisms will lose the desired property of global optimality and sample efficiency, which is the underlying reason for the over-exploration issue.

4 Conservative Dual Policy Optimization

When using nonlinear models, e.g. neural networks, the over-exploration issue causes unfavorable performance in practice, in terms of slow convergence and suboptimal asymptotic values. To tackle this challenge, the key is to abandon the sampling process and have guarantees *during* training.

In this regard, we propose *Conservative Dual Policy Optimization* (CDPO) that is simple yet provably efficient. By optimizing the policy following two successive update procedures iteratively, CDPO simultaneously enjoys monotonic policy value improvement and global optimality properties.

4.1 CDPO Framework

To begin with, consider the problem of maximizing the expected value, $\pi_t = \operatorname{argmax}_\pi \mathbb{E}[V_\pi^{f^*} | \mathcal{H}_t]$, where $\mathbb{E}[V^{f^*} | \mathcal{H}_t]$ denotes the expected values over the posterior. Obviously, we have the expected value improvement guarantee $\mathbb{E}[V_{\pi_t}^{f^*} | \mathcal{H}_t] \geq \mathbb{E}[V_{\pi_{t-1}}^{f^*} | \mathcal{H}_t]$. We can also perform expected value

maximization in a trust-region to guarantee iterative improvement under any f^*. However, such updates will lose the desired global convergence guarantee and may get stuck at local maxima even with linear models. For this reason, we propose a dual procedure of policy optimization.

Referential Update. The first update step returns an intermediate policy, denoted as q_t. This step is a greedy one in the sense that q_t is optimal with respect to the value of a *single* model $\widetilde{f}_t$, which we call a *reference model*. Selecting a reference model and optimizing a policy w.r.t. it imitates the sampling-optimization procedure of PSRL. We will show in Section 5.1 that if we pose the constraint $\widetilde{f}_t \in \mathcal{F}_t$, then CDPO achieves the same expected regret as PSRL, which implies global optimality.

More importantly, policy optimization under $\widetilde{f}_t$ is more stable and can avoid the over-exploration issue in PSRL since we are free to set it as a steady reference between successive iterations. For example, we fix the reference model $\widetilde{f}_t$ as the least squares estimate $\widehat{f}_t^{LS}$ defined in (2.1), instead of a random model *sampled* from the large hypothesis that causes aggressive policy update. This gives us:

$$\text{Referential Update (with LS Reference):} \qquad q_t = \underset{q}{\arg\max}\, V_q^{\widehat{f}_t^{LS}}. \tag{4.1}$$

Constrained Conservative Update. The conservative update then follows as the second stage of CDPO, which takes input q_t and returns the reactive policy π_{t+1}:

$$\text{Conservative Update: } \pi_t = \underset{\pi}{\arg\max}\, \mathbb{E}\big[V_\pi^{f_t} \,\big|\, \mathcal{H}_t\big], \text{ s.t. } \mathbb{E}_{s\sim\nu_{q_t}}\Big[D_{\text{TV}}\big(\pi_t(\cdot|s), q_t(\cdot|s)\big)\Big] \leq \eta, \tag{4.2}$$

where $D_{\text{TV}}(\cdot, \cdot)$ stands for the total variation distance and η is the hyperparameter that characterizes the trust-region constraint and controls the degree of exploration.

Compared with OFU-RL and PSRL, the above exploration and policy updates are conservative since the policy maximizes the *expectation* of the model value, instead of a *single* model's value (i.e. the optimistic model in OFU-RL and the sampled model in PSRL). The conservative update (4.2) avoids the pitfalls when the optimistic model or the posterior sampled model suffers large bias, which leads to aggressive policy update and over-exploration during training. Notably, the term *conservative* in our work differs from previous use, e.g. Conservative Policy Iteration [23, 53]. While the latter refers to policy updates with constraints, ours is to emphasize the conservative range of randomness and the reduction of unnecessary over-exploration by shelving the sampling process.

In our analysis, we follow previous work [43, 59, 10, 35] and assume access to a policy optimization oracle. In practice, the problem of finding an optimal policy under a given model can be approximately solved by model-based solvers listed below. More fine-grained analysis can be obtained by applying off-the-shelf results established for policy gradient or MPC for specific policy or model function classes. This, however, is beyond the scope of this paper.

4.2 Practical Algorithm

The pseudocode of CDPO is in Alg. 1. The model-based solver MBPO$(\pi, f, \mathcal{J})$ outputs the policy (q_t or π_t) that optimizes the objective $\mathcal{J}$ with access to model f. Several different types of solvers can be leveraged, e.g., model-augmented model-free policy optimization such as Dyna [61], model-based reparameterization gradient [18, 9], or model-predictive control [64]. Details of different optimization choices can be found in Appendix E. In experiments, we use Dyna and MPC solvers .

With Pinsker's inequality, the total variation constraint in (4.2) is replaced by the KL divergence [53, 2] in experiments. We follow

---

Algorithm 1 Practical CDPO Algorithm
___
Input: Prior ϕ, model-based policy optimization solver MBPO$(\pi, f, \mathcal{J})$.
___
1: **for** iteration $t = 1, ..., T$ **do**
2: $\quad q_t \leftarrow$ MBPO$(\cdot, \widehat{f}_t^{LS}, (4.1))$
3: $\quad$ Sample N models $\{f_{t,n}\}_{n=1}^N$ from ϕ
4: $\quad \pi_t \leftarrow$ MBPO$(q_t, \{f_{t,n}\}_{n=1}^N, (4.2))$
5: $\quad$ Execute π_t in the real MDP
6: $\quad$ Update $\mathcal{H}_{t+1} = \mathcal{H}_t \cup \{s_{h,t}, a_{h,t}, s_{h+1,t}\}_h$
7: $\quad$ Update $\widehat{f}_{t+1}^{LS}$ and ϕ
8: **end for**
9: **return** policy π_T

---

previous work [34] to use neural network ensembles [10, 25] for model estimation and use calibrations [29, 10] for accurate uncertainty measure.

5 Analysis

In this section, we first show the statistical equivalence between CDPO and PSRL in terms of the same BayesRegret bound. Then we give the iterative policy value bound with monotonic improvement. Finally, we prove the global convergence of CDPO. The missing proofs can be found in the Appendix.

5.1 Statistical Equivalence between CDPO and PSRL

We begin our analysis by highlighting the connection between CDPO and PSRL with the following theorem, from which we also show the role of the dual update procedure and the reference model.

Theorem 5.1 (CDPO Matches PSRL in BayesRegret). *Let π^{PSRL} be the policy of any posterior sampling algorithm for reinforcement learning optimized by (3.2). If the BayesRegret bound of π^{PSRL} satisfies that for any $T > 0$, $\text{BayesRegret}(T, \pi^{\text{PSRL}}, \phi) \leq \mathcal{D}$, then for all $T > 0$, we have for the CDPO policy π^{CDPO} that $\text{BayesRegret}(T, \pi^{\text{CDPO}}, \phi) \leq 3\mathcal{D}$.*

Sketch proof. We first sketch the general strategy in the PSRL analysis. Recall the definition of the Bayesian expected regret $\text{BayesRegret}(T, \pi, \phi) := \mathbb{E}[\sum_{t=1}^{T} \mathfrak{R}_t]$, where $\mathfrak{R}_t = V_{\pi^*}^{f^*} - V_{\pi_t}^{f^*}$. PSRL breaks down $\mathfrak{R}_t$ by adding and subtracting value $V_{\pi_{f_t}}^{f_t}$ of the *imagined* optimal policy π_{f_t} under a sampled model f_t, i.e. $\pi_{f_t} = \text{argmax}_\pi V_\pi^{f_t}$.

$$\text{PSRL:} \qquad \mathfrak{R}_t = V_{\pi^*}^{f^*} - V_{\pi_t}^{f^*} = V_{\pi^*}^{f^*} - V_{\pi_{f_t}}^{f^*} = V_{\pi^*}^{f^*} - V_{\pi_{f_t}}^{f_t} + V_{\pi_{f_t}}^{f_t} - V_{\pi_{f_t}}^{f^*}, \qquad (5.1)$$

where the second equality follows from the definition of the PSRL policy. Following the law of total expectation and the Posterior Sampling Lemma (e.g. Lemma 1 in [42]), we have $\mathbb{E}[V_{\pi^*}^{f^*} - V_{\pi_{f_t}}^{f_t}] = 0$ by noting that f^* and f_t are identically distributed conditioned upon $\mathcal{H}_t$. Then we obtain

$$\text{BayesRegret}(T, \pi^{\text{PSRL}}, \phi) = \sum_{t=1}^{T} \mathbb{E}[V_{\pi_{f_t}}^{f_t} - V_{\pi_{f_t}}^{f^*}] \leq \gamma \sum_{t=1}^{T} \mathbb{E}\Big[\mathbb{E}_\rho\big[L\|f_t(s_h, a_h) - f^*(s_h, a_h)\|_2\big]\Big]$$

$$\leq \gamma \frac{L}{1 - 4\delta} \sum_{t=1}^{T} \mathbb{E}[\omega_t] + 4\gamma\delta T \leq \mathcal{D}, \qquad (5.2)$$

where the first inequality follows from the simulation lemma under the L-Lipschitz value assumption [43]. The second inequality follows from the definition of ω_t in (2.6) and the construction of confidence set such that $\mathbb{P}(f^* \in \bigcap \mathcal{F}_t) \geq 1 - 2\delta$ and $\mathbb{P}(f_t \in \bigcap \mathcal{F}_t, f^* \in \bigcap \mathcal{F}_t) \geq 1 - 4\delta$ via a union bound. As more data is collected, the model uncertainty is reduced and the sum of confidence set width ω_t will be sublinear in T (c.f. Lemma B.4 and B.5), indicating sublinear regret.

When it comes to CDPO, we decompose the regret as

$$\text{CDPO:} \qquad \mathfrak{R}_t = V_{\pi^*}^{f^*} - V_{\pi_t}^{f^*} = V_{\pi^*}^{f^*} - V_{\pi_{f_t}}^{f_t} + V_{\pi_{f_t}}^{f_t} - V_{\pi_t}^{f_t} + V_{\pi_t}^{f_t} - V_{\pi_t}^{f^*}, \qquad (5.3)$$

where the CDPO policy π_t is defined in (4.2). Since $\mathbb{E}[V_{\pi^*}^{f^*} - V_{\pi_{f_t}}^{f_t}] = 0$, we have

$$\text{BayesRegret}(T, \pi^{\text{CDPO}}, \phi) = \sum_{t=1}^{T} \mathbb{E}[V_{\pi_{f_t}}^{f_t} - V_{\pi_t}^{f_t} + V_{\pi_t}^{f_t} - V_{\pi_t}^{f^*}]$$

$$\leq \sum_{t=1}^{T} \mathbb{E}[V_{\pi_{f_t}}^{f_t} - V_{\pi_{f_t}}^{\widetilde{f}_t} + V_{q_t}^{\widetilde{f}_t} - V_{q_t}^{f_t} + V_{\pi_t}^{f_t} - V_{\pi_t}^{f^*}] \leq \frac{L}{1 - 4\delta} \sum_{t=1}^{T} 3\mathbb{E}[\omega_t] + 8\gamma\delta T \leq 3\mathcal{D}, \quad (5.4)$$

where the first inequality follows from the optimality of q_t and π_t, i.e., $V_{\pi_{f_t}}^{\widetilde{f}_t} \leq V_{q_t}^{\widetilde{f}_t}$ for any π_{f_t} and $V_{\pi_t}^{f_t} \geq V_{q_t}^{f_t}$. The $8\delta T$ term is introduced since $\widetilde{f}_t \in \mathcal{F}_t$ and $\mathbb{P}(f_t \in \bigcap \mathcal{F}_t, \widetilde{f}_t \in \bigcap \mathcal{F}_t) \geq 1 - 2\delta$. $\square$

Theorem 5.1 indicates that although CDPO performs conservative updates and abandons the sampling process, it matches the statistical efficiency of PSRL up to constant factors.

The importance of the reference model and the dual procedure is also reflected in the proof. The referential update builds the bridge between $V_{\pi_{f_t}}^{f_t}$ and $V_{\pi_t}^{f_t}$. Policy optimization under the reference model mimics the sampling-optimization of PSRL. However, more stability is offered when the reference is steady, e.g., the least squares estimate we use. We will formalize this idea below.

5.2 CDPO Policy Iterative Improvement

One motivation of the conservative update is that it maximizes (thus improves) the expected value over the posterior. In this section, we are interested in the policy value improvement under any unknown f^*. Namely, we seek to have the iterative improvement bound $J(\pi_t) - J(\pi_{t-1})$, where the true objective J is defined in (2.3).

We impose the following regularity condition on the underlying MDP transition.

Assumption 5.2 (Regularity Condition on MDP Transition). Assume that the MDP transition function $f^* : \mathcal{S} \times \mathcal{A} \to \mathcal{S}$ is with additive σ-sub-Gaussian noise and bounded norm, i.e., $\|s\|_2 \leq C$.

Theorem 5.3 (Policy Iterative Improvement). Suppose we have $\|\widetilde{f}(\cdot, \cdot)\| \leq C$ for $\widetilde{f} \in \mathcal{F}$ where the model class $\mathcal{F}$ is finite. Define $\iota := \max_{s,a} |A_\pi^{f^*}(s, a)|$, where $A_\pi^{f^*}$ is the advantage function defined as $A_\pi^{f^*}(s, a) := Q_\pi^{f^*}(s, a) - V_\pi^{f^*}(s)$. With probability at least $1 - \delta$, the policy improvement between successive iterations is bounded by

$$J(\pi_t) - J(\pi_{t-1}) \geq \Delta(t) - \frac{22\gamma C^2 \ln(|\mathcal{F}|/\delta)}{(1-\gamma)H} - \frac{4\eta\iota}{1-\gamma}, \tag{5.5}$$

where $\Delta(t) := \mathbb{E}_{s \sim \zeta}\big[V_{q_t}^{\widetilde{f}_t}(s) - V_{q_{t-1}}^{\widetilde{f}_t}(s)\big]$ is non-negative due to the greediness of q_t.

The above theorem provides the iterative improvement bound following the CDPO algorithm. When H is large enough, the policy value improvement is at least $\Delta(t)$ by choosing a properly small η.

In particular, the first term $\Delta(t)$ characterizes the policy improvement brought by the greedy exploitation in (4.1), and $\Delta(t) \geq 0$ since q_t is optimal under $\widetilde{f}_t$. The second term in (5.5) accounts for the generalization error of least square methods. Specifically, model $\widetilde{f}_t = \widehat{f}_t^{LS} \in \mathcal{F}_t$ is trained to fit the history samples. However, we seek to have the model error bound over the state-action visitation measure, which requires the deviation from the empirical mean to its expectation using Bernstein's inequality and union bound. This term will approach 0 with a long length H of the sampling path, which in the ideal case should be set to ∞ since the MDP is infinite-horizon. Finally, the trust-region constraint in (4.2) brings the $4\eta\alpha/(1-\gamma)$ term, which reduces to zero if η is small. It makes intuitive sense as η controls the degree of conservative exploration.

5.3 Global Optimality of CDPO

We now analyze the global optimality of CDPO by studying its expected regret. As discussed in Section 3, agnostic reinforcement learning is impossible. Without structural assumptions, additional complexity measure is required for a generalization bound beyond finite settings. For this reason, we adopt the notation of *eluder dimension* [49, 43], defined as follows.

Definition 5.4 (Eluder Dimension). The eluder dimension $dim_E(\mathcal{F}, \varepsilon)$ is the length of the longest possible sequence of elements in $\mathcal{S} \times \mathcal{A}$ such that for some $\varepsilon' \geq \varepsilon$, every element is $(\mathcal{F}, \varepsilon')$-independent of its predecessors, where we defer the definition of $(\mathcal{F}, \varepsilon)$-independence to Appendix C.

We make the regularity condition on the Lipschitz continuity of the value function.

Assumption 5.5 (Lipschitz Continuous Value). At iteration t, the value function $V_\pi^{f_t}$ is Lipschitz continuous in the sense that $|V_\pi^{f_t}(s_1) - V_\pi^{f_t}(s_2)| \leq L_t \|s_1 - s_2\|_2$.

Notably, Assumption 5.5 holds under certain regularity conditions of the MDP, e.g. when the transition and rewards are Lipschitz continuous [5, 47]. Under this assumption, many RL settings can be satisfied [13], e.g., nonlinear models with stochastic Lipschitz policies and Lipschitz reward models, and thus is adopted by various model-based RL work [35, 7, 13].

We now study the global optimality of CDPO by the following expected regret theorem.

Theorem 5.6 (Expected Regret of CDPO). Let $N(\mathcal{F}, \alpha, \|\cdot\|_2)$ be the α-covering number of $\mathcal{F}$. Denote $d_E := \dim_E(\mathcal{F}, T^{-1})$ for the eluder dimension of $\mathcal{F}$ at precision $1/T$. Under Assumption 5.2 and 5.5, the cumulative expected regret of CDPO in T iterations is bounded by

$$\text{BayesRegret}(T, \pi, \phi) \leq \frac{\gamma T(3T-5)L}{(T-1)(T-2)} \cdot \left(1 + \frac{1}{1-\gamma}Cd_E + 4\sqrt{Td_E\beta}\right) + 4\gamma C, \tag{5.6}$$

where $\beta := 8\sigma^2 \log\big(2N\big(\mathcal{F}, 1/(T^2), \|\cdot\|_2\big)T\big) + 2\big(8C + \sqrt{8\sigma^2 \log(8T^3)}\big)/T$ and $L := \mathbb{E}[L_t]$.

289 Here, the covering number is introduced since we are considering $\mathcal{F}$ that may contain infinitely many
290 functions, for which we cannot simply apply a union bound. Besides, β is the confidence parameter
291 that contains f^* with high probability (via concentration inequality).

292 To clarify the asymptotics of the expected regret bound, we introduce another measure of dimension-
293 ality that captures the sensitivity of $\mathcal{F}$ to statistical overfitting.

294 **Corollary 5.7** (Asymptotic Bound). Define the Kolmogorov dimension w.r.t. function class $\mathcal{F}$ as

$$d_K = \dim_K(\mathcal{F}) := \limsup_{\alpha \downarrow 0} \frac{\log(N(\mathcal{F}, \alpha, \|\cdot\|_2))}{\log(1/\alpha)}.$$

295 Under the assumptions of Theorem 5.6 and by omitting terms logarithmic in T, the regret of CDPO is

$$\text{BayesRegret}(T, \pi, \phi) = \widetilde{O}(L\sigma\sqrt{d_K d_E T}). \tag{5.7}$$

296 The sublinear regret result permits the global optimality and sample efficiency for any model class
297 with reasonable complexity measure. Meanwhile, the iterative improvement theorem guarantees
298 efficient exploration and good performance even when the model class is highly nonlinear.

6 Empirical Evaluation

6.1 Understanding Different Exploration Mechanisms

301 We first provide insights and evidence of why CDPO exploration can be more efficient in N-Chain
302 MDPs, which have optimal *right* actions and suboptimal *left* actions at each of the N states. Settings
303 and full results are provided in Appendix F.4. In Fig. 1, we compare the posterior of CDPO and PSRL
at the state furthest away from the initial state, i.e. the state that is the hardest for agents to explore.

Figure 1: CDPO and PSRL posterior on an 8-Chain MDP Figure 2: Regret curve of CDPO and and a 15-Chain MDP, where the *right* actions are optimal. PSRL when $N = 8$ and $N = 15$.

304
305 When training starts, both algorithms have a large variance of value estimation. However, as training
306 progresses, CDPO gives more accurate and certain estimates, but *only* for the optimal *right* actions not
307 for the suboptimal *left* actions, while PSRL agents explore *both* directions. This verifies the potential
308 over-exploration issue in PSRL: as long as the uncertainty contains unrealistically large values, PSRL
309 agents can perform uninformative exploration by acting suboptimally according to an inaccurate
310 *sampled* model. In contrast, CDPO replaces the sampled model with a stable mean estimate and cares
311 about the *expected* value, thus avoiding such pitfalls. We see in Fig. 2 that although CDPO has much
312 larger uncertainty for the suboptimal *left* actions, its regret is lower.

6.2 Exploration Efficiency with Nonlinear Model Class

314 In finite MDPs, PSRL-style agents can specify and try every action to finally obtain an accurate
315 high-confidence prediction. However, our discussion in Sec. 3 indicates that similar over-exploration
316 steps in more complex environments can only eliminate an exponentially small portion of the
317 uncertainty. We experimentally validate this phenomenon by plotting the average uncertainty scale
318 on the validation data in Appendix Section F.3. The slower uncertainty elimination rate of PSRL and
319 HUCRL [10] indicates less informative exploration steps.

320 To see its impact on the training performance, we report the results of provable algorithms with
321 nonlinear models on several MuJoCo tasks in Figure 3. We observe that all algorithms achieve
322 the asymptotic optimality in inverted pendulum. Since the dimension of the pendulum task is low,
323 learning an accurate (and thus generalizable) model poses no actual challenge. However, in higher
324 dimensional tasks such as half-cheetah and ant, CDPO achieves higher asymptotic value with faster
325 convergence. Implementation details and hyperparameters are provided in Appendix F.1.

(a) Inverted Pendulum.   (b) 7-DOF Pusher.   (c) Half-Cheetah.   (d) Ant.

Figure 3: Performance of CDPO, PSRL, and HUCRL equipped with nonlinear models.

6.3 Comparisons with Prior RL Algorithms

For other MBRL algorithms, we examine DPI [59], SLBO [35], ME-TRPO [30], MBPO [20], and VaGraM [63]. Despite the curves in Fig. 4, we report the sample efficiency and running time in Appendix F.2. The model-free baselines we compare with include SAC [16], PPO [54], and MPO [2].

(a) Inverted Pendulum.   (b) 7-DOF Pusher.   (c) Half-Cheetah.   (d) Ant.

Figure 4: Comparion between CDPO and model-free, model-based RL baseline algorithms.

6.4 Ablation Study

One can observe from Fig. 5 that the policies updated with only Referential Update or Conservative Update lag behind the dual framework. We also test the necessity and sensitivity of the constraint hyperparameter η. We see that constant η and time-decaying η achieve similar asymptotic value with similar convergence rate (around $7.5e5$ timesteps), showing the robustness of CDPO. However, removing the constraint will lose the policy improvement guarantee, thus causing degradation. Ablation on different choices of MBPO solver (Dyna and POPLIN-P [64]) shows the generalizability of CDPO.

(a) Inverted Pendulum.   (b) Half-Cheetah.   (c) Half-Cheetah.

Figure 5: Ablation studies. Here, $(0.2, 15\%)$ means initial $\eta = 0.2$ decayed by 15% every 100 iters.

7 Conclusions & Future Work

In this work, we present *Conservative Dual Policy Optimization* (CDPO), a simple yet provable model-based algorithm. By iterative execution of the *Referential Update* and *Conservative Update*, CDPO explores within a reasonable range while avoiding aggressive policy update. CDPO gets rid of the sampling procedure by optimizing under a reference model and maximizing the *expected* policy value. With the same order of regret as PSRL, the proposed algorithm can achieve global optimality while monotonically improving the policy. Considering our naive choice of the reference model, other more sophisticated designs should be a fruitful future direction. It will also be interesting to explore different choices of MBPO solvers, which we would like to leave as future work.

References

[1] Yasin Abbasi-Yadkori and Csaba Szepesvári. Regret bounds for the adaptive control of linear quadratic systems. In *Proceedings of the 24th Annual Conference on Learning Theory*, pages 1–26. JMLR Workshop and Conference Proceedings, 2011.

[2] Abbas Abdolmaleki, Jost Tobias Springenberg, Yuval Tassa, Remi Munos, Nicolas Heess, and Martin Riedmiller. Maximum a posteriori policy optimisation. *arXiv preprint arXiv:1806.06920*, 2018.

[3] Alekh Agarwal, Nan Jiang, Sham M Kakade, and Wen Sun. Reinforcement learning: Theory and algorithms. *CS Dept., UW Seattle, Seattle, WA, USA, Tech. Rep*, 2019.

[4] Yaakov Bar-Shalom and Edison Tse. Dual effect, certainty equivalence, and separation in stochastic control. *IEEE Transactions on Automatic Control*, 19(5):494–500, 1974.

[5] Osbert Bastani. Sample complexity of estimating the policy gradient for nearly deterministic dynamical systems. In *International Conference on Artificial Intelligence and Statistics*, pages 3858–3869. PMLR, 2020.

[6] Jacob Buckman, Danijar Hafner, George Tucker, Eugene Brevdo, and Honglak Lee. Sample-efficient reinforcement learning with stochastic ensemble value expansion. *arXiv preprint arXiv:1807.01675*, 2018.

[7] Sayak Ray Chowdhury and Aditya Gopalan. Online learning in kernelized markov decision processes. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 3197–3205. PMLR, 2019.

[8] Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *arXiv preprint arXiv:1805.12114*, 2018.

[9] Ignasi Clavera, Violet Fu, and Pieter Abbeel. Model-augmented actor-critic: Backpropagating through paths. *arXiv preprint arXiv:2005.08068*, 2020.

[10] Sebastian Curi, Felix Berkenkamp, and Andreas Krause. Efficient model-based reinforcement learning through optimistic policy search and planning. *arXiv preprint arXiv:2006.08684*, 2020.

[11] Richard Dearden, Nir Friedman, and Stuart Russell. Bayesian q-learning. In *Aaai/iaai*, pages 761–768, 1998.

[12] Marc Deisenroth and Carl E Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *Proceedings of the 28th International Conference on machine learning (ICML-11)*, pages 465–472. Citeseer, 2011.

[13] Kefan Dong, Jiaqi Yang, and Tengyu Ma. Provable model-based nonlinear bandit and reinforcement learning: Shelve optimism, embrace virtual curvature. *arXiv preprint arXiv:2102.04168*, 2021.

[14] Simon Du, Sham Kakade, Jason Lee, Shachar Lovett, Gaurav Mahajan, Wen Sun, and Ruosong Wang. Bilinear classes: A structural framework for provable generalization in rl. In *International Conference on Machine Learning*, pages 2826–2836. PMLR, 2021.

[15] Vladimir Feinberg, Alvin Wan, Ion Stoica, Michael I Jordan, Joseph E Gonzalez, and Sergey Levine. Model-based value estimation for efficient model-free reinforcement learning. *arXiv preprint arXiv:1803.00101*, 2018.

[16] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, pages 1861–1870. PMLR, 2018.

[17] Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.

[18] Nicolas Heess, Gregory Wayne, David Silver, Timothy Lillicrap, Tom Erez, and Yuval Tassa. Learning continuous control policies by stochastic value gradients. *Advances in neural information processing systems*, 28, 2015.

[19] Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(4), 2010.

[20] Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. *arXiv preprint arXiv:1906.08253*, 2019.

[21] Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E Schapire. Contextual decision processes with low bellman rank are pac-learnable. In *International Conference on Machine Learning*, pages 1704–1713. PMLR, 2017.

[22] Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pages 2137–2143. PMLR, 2020.

[23] Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *In Proc. 19th International Conference on Machine Learning*. Citeseer, 2002.

[24] Michael Kearns, Yishay Mansour, and Andrew Ng. Approximate planning in large pomdps via reusable trajectories. *Advances in Neural Information Processing Systems*, 12, 1999.

[25] Rahul Kidambi, Jonathan Chang, and Wen Sun. Optimism is all you need: Model-based imitation learning from observation alone. *arXiv preprint arXiv:2102.10769*, 2021.

[26] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[27] Edgar D Klenske and Philipp Hennig. Dual control for approximate bayesian reinforcement learning. *The Journal of Machine Learning Research*, 17(1):4354–4383, 2016.

[28] Vijay R Konda and John N Tsitsiklis. Actor-critic algorithms. In *Advances in neural information processing systems*, pages 1008–1014. Citeseer, 2000.

[29] Volodymyr Kuleshov, Nathan Fenner, and Stefano Ermon. Accurate uncertainties for deep learning using calibrated regression. In *International Conference on Machine Learning*, pages 2796–2804. PMLR, 2018.

[30] Thanard Kurutach, Ignasi Clavera, Yan Duan, Aviv Tamar, and Pieter Abbeel. Model-ensemble trust-region policy optimization. *arXiv preprint arXiv:1802.10592*, 2018.

[31] Sergey Levine and Pieter Abbeel. Learning neural network policies with guided policy search under unknown dynamics. In *NIPS*, volume 27, pages 1071–1079. Citeseer, 2014.

[32] Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

[33] Gene Li, Pritish Kamath, Dylan J Foster, and Nathan Srebro. Eluder dimension and generalized rank. *arXiv preprint arXiv:2104.06970*, 2021.

[34] Xiuyuan Lu and Benjamin Van Roy. Ensemble sampling. *Advances in neural information processing systems*, 30, 2017.

[35] Yuping Luo, Huazhe Xu, Yuanzhi Li, Yuandong Tian, Trevor Darrell, and Tengyu Ma. Algorithmic framework for model-based deep reinforcement learning with theoretical guarantees. *arXiv preprint arXiv:1807.03858*, 2018.

[36] Horia Mania, Stephen Tu, and Benjamin Recht. Certainty equivalence is efficient for linear quadratic control. *arXiv preprint arXiv:1902.07826*, 2019.

[37] Efstratios Markou and Carl E. Rasmussen. Bayesian methods for efficient reinforcement learning in tabular problems, 2019.

[38] Aditya Modi, Jinglin Chen, Akshay Krishnamurthy, Nan Jiang, and Alekh Agarwal. Model-free representation learning and exploration in low-rank mdps. *arXiv preprint arXiv:2102.07035*, 2021.

[39] William Montgomery and Sergey Levine. Guided policy search as approximate mirror descent. *arXiv preprint arXiv:1607.04614*, 2016.

[40] Manfred Morari and Jay H Lee. Model predictive control: past, present and future. *Computers & Chemical Engineering*, 23(4-5):667–682, 1999.

[41] Anusha Nagabandi, Gregory Kahn, Ronald S Fearing, and Sergey Levine. Neural network dynamics for model-based deep reinforcement learning with model-free fine-tuning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7559–7566. IEEE, 2018.

[42] Ian Osband, Daniel Russo, and Benjamin Van Roy. (more) efficient reinforcement learning via posterior sampling. *arXiv preprint arXiv:1306.0940*, 2013.

[43] Ian Osband and Benjamin Van Roy. Model-based reinforcement learning and the eluder dimension. *arXiv preprint arXiv:1406.1853*, 2014.

[44] Ian Osband and Benjamin Van Roy. Why is posterior sampling better than optimism for reinforcement learning? In *International Conference on Machine Learning*, pages 2701–2710. PMLR, 2017.

[45] Ian Osband, Benjamin Van Roy, Daniel J Russo, Zheng Wen, et al. Deep exploration via randomized value functions. *J. Mach. Learn. Res.*, 20(124):1–62, 2019.

[46] Brendan O'Donoghue, Ian Osband, Remi Munos, and Volodymyr Mnih. The uncertainty bellman equation and exploration. In *International Conference on Machine Learning*, pages 3836–3845, 2018.

[47] Matteo Pirotta, Marcello Restelli, and Luca Bascetta. Policy gradient in lipschitz markov decision processes. *Machine Learning*, 100(2):255–283, 2015.

[48] Stephane Ross and J Andrew Bagnell. Agnostic system identification for model-based reinforcement learning. *arXiv preprint arXiv:1203.1007*, 2012.

[49] Daniel Russo and Benjamin Van Roy. Eluder dimension and the sample complexity of optimistic exploration. In *NIPS*, pages 2256–2264. Citeseer, 2013.

[50] Daniel Russo and Benjamin Van Roy. Learning to optimize via posterior sampling. *Mathematics of Operations Research*, 39(4):1221–1243, 2014.

[51] Daniel Russo and Benjamin Van Roy. Satisficing in time-sensitive bandit learning. *arXiv preprint arXiv:1803.02855*, 2018.

[52] Daniel Russo, Benjamin Van Roy, Abbas Kazerouni, Ian Osband, and Zheng Wen. A tutorial on thompson sampling. *arXiv preprint arXiv:1707.02038*, 2017.

[53] John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pages 1889–1897. PMLR, 2015.

[54] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[55] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

[56] Alexander L Strehl and Michael L Littman. A theoretical analysis of model-based interval estimation. In *Proceedings of the 22nd international conference on Machine learning*, pages 856–863, 2005.

[57] Malcolm Strens. A bayesian framework for reinforcement learning. In *ICML*, volume 2000, pages 943–950, 2000.

[58] HJ Suh, Max Simchowitz, Kaiqing Zhang, and Russ Tedrake. Do differentiable simulators give better policy gradients? *arXiv preprint arXiv:2202.00817*, 2022.

[59] Wen Sun, Geoffrey J Gordon, Byron Boots, and J Andrew Bagnell. Dual policy iteration. *arXiv preprint arXiv:1805.10755*, 2018.

[60] Wen Sun, Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Model-based rl in contextual decision processes: Pac bounds and exponential improvements over model-free approaches. In *Conference on Learning Theory*, pages 2898–2933. PMLR, 2019.

[61] Richard S Sutton. Integrated architectures for learning, planning, and reacting based on approximating dynamic programming. In *Machine learning proceedings 1990*, pages 216–224. Elsevier, 1990.

[62] William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

[63] Claas Voelcker, Victor Liao, Animesh Garg, and Amir-massoud Farahmand. Value gradient weighted model-based reinforcement learning. *arXiv preprint arXiv:2204.01464*, 2022.

[64] Tingwu Wang and Jimmy Ba. Exploring model-based planning with policy networks. *arXiv preprint arXiv:1906.08649*, 2019.

[65] Jie Xu, Viktor Makoviychuk, Yashraj Narang, Fabio Ramos, Wojciech Matusik, Animesh Garg, and Miles Macklin. Accelerated policy learning with parallel differentiable simulation. *arXiv preprint arXiv:2204.07137*, 2022.

[66] Lin Yang and Mengdi Wang. Sample-optimal parametric q-learning using linearly additive features. In *International Conference on Machine Learning*, pages 6995–7004. PMLR, 2019.

[67] Lin Yang and Mengdi Wang. Reinforcement learning in feature space: Matrix bandit, kernels, and regret bound. In *International Conference on Machine Learning*, pages 10746–10756. PMLR, 2020.