ENERGY-BASED LEARNING FOR COOPERATIVE GAMES, WITH APPLICATIONS TO VALUATION PROBLEMS IN MACHINE LEARNING

ABSTRACT

Valuation problems, such as feature interpretation, data valuation and model valuation for ensembles, become increasingly more important in many machine learning applications. Such problems are commonly addressed via well-known game-theoretic criteria, such as the Shapley value or Banzhaf index. In this work, we present a novel energy-based treatment for cooperative games, with a theoretical justification by the maximum entropy framework. Surprisingly, by conducting variational inference of the energy-based model, we recover classical game-theoretic valuation criteria through conducting *one-step* gradient ascent for maximizing the mean-field ELBO objective. This observation also verifies the rationality of existing criteria, as they are all attempting to decouple the correlations among players through the mean-field approach. By running gradient ascent for *multiple* steps, we achieve a trajectory of the variational valuations, among which we define the valuation with the best conceivable decoupling error as the *Variational Index*. We empirically demonstrate that the proposed Variational Index enjoys intriguing properties on certain synthetic and real-world valuation problems.

1 INTRODUCTION

Valuation problems (Lundberg and Lee, 2017; Ghorbani and Zou, 2019; Sim et al., 2020; Rozember-czki and Sarkar, 2021) in machine learning are often formulated as an importance assignment problem in cooperative games. A cooperative game $(N, F(S))$ consists of a grand coalition $N = \{1, ..., n\}$ of n players and a value function (a.k.a. characteristic function) $F(S) : 2^N \to \mathbb{R}$ describing the collective payoff of a coalition/cooperation S. A fundamental problem in cooperative game theory is to assign an importance vector (solution concept) $\phi(F) \in \mathbb{R}^n$ to n players.

In this paper, we explore a *probabilistic treatment* of cooperative games $(N, F(S))$. Such a treatment makes it possible to conduct learning and uncertainty quantification in a unified Bayesian manner. Concretely, we seek a probability distribution over coalitions $p(\mathbf{S} = S)$[1], measuring the odds that a specific coalition S happens. Generally, we consider distributions where the probability of a coalition $p(S)$ grows monotonically with the payoff $F(S)$.

Among all the possible probability mass functions (pmfs), how should we construct the proper $p(S)$? We advocate to choose the pmf with the maximum entropy $\mathbb{H}(p) = -\sum_{S \subseteq N} p(S) \log p(S)$. This principle makes sense since maximizing the entropy minimizes the amount of prior information built into the distribution. In other words, it amounts to assume nothing about what is unknown, i.e., choosing the most "uniform" distribution. Now finding a proper $p(S)$ becomes the following constrained optimization problem: suppose each coalition S is associated with a payoff $F(S)$ with probability $p(S)$. We would like to maximize the entropy $\mathbb{H}(p) = -\sum_{S \subseteq N} p(S) \log p(S)$, subject to the constraints that $\sum_S p(S) = 1, p(S) \geq 0$ and $\sum_S p(S)F(S) = \mu$ (i.e., the average payoff is known as μ). Solving this optimization problem (detailed derivation in Appendix A), we reach the

---

[1]Note that distributions over subsets of N are equivalent to distributions of $|N| = n$ binary random variables $X_1, ..., X_n \in \{0, 1\}$: We use X_i as the indicator function of the event $i \in S$, or $X_i = [i \in S]$. With slight abuse of notation, we use $\mathbf{S}$ as a random variable represented as sets and often abbreviate $p(\mathbf{S} = S)$ as $p(S)$.

maximum entropy distribution:

$$p(S) = \frac{\exp(F(S)/T)}{\mathbf{Z}}, \quad \mathbf{Z} := \sum\nolimits_{S' \subseteq N} \exp(F(S')/T), \tag{1}$$

where $T > 0$ is the temperature. This is an energy-based model (EBM (LeCun et al., 2006)) with $-F(S)$ as the energy function.

The above energy-based treatment admits two benefits: i) Where supervision is available, it enables learnable value functions $F(S)$ through standard training techniques of energy-based learning, such as noise contrastive estimation (Gutmann and Hyvärinen, 2010) and score matching (Hyvärinen, 2005). ii) Approximate inference techniques such as variational inference or sampling can be adopted to solve the valuation problem.

Below, we explore variational inference for the energy-based formulation. Perhaps surprisingly, by conducting only *one-step* gradient ascent for maximizing the mean-field objective (the ELBO objective), we recover classical valuation criteria, such as the Shapley value (Shapley, 1953) and the Banzhaf index (Penrose, 1946; Banzhaf III, 1964). This observation also verifies the rationality of existing criteria, as they are all trying to decouple the correlations among players through the mean-field approach. By running gradient ascent for *multiple* steps, we achieve a trajectory of valuations, among which we define the valuation with the best conceivable decoupling error as the *Variational Index*. Our major contributions can be summarized as below:

i) We present a theoretically justified energy-based treatment for cooperative games. Through mean field inference in the energy-based model, we provide a unified perspective on popular game-theoretic criteria. This provides an alternative motivation of existing criteria via a *decoupling* perspective. ii) In pursuit of better decoupling performance, we propose to run gradient ascent for *multiple* steps, which generates a trajectory of valuations. We define the valuation with the best conceivable decoupling error as the Variational Index. iii) Synthetic and real-world experiments demonstrate intriguing properties of the proposed Variational Index.

2 PRELIMINARIES AND BACKGROUND

Notation. We assume $\mathbf{e}_i \in \mathbb{R}^n$ being the standard i^{th} basis vector and use boldface letters $\mathbf{x} \in \mathbb{R}^N$ and $\mathbf{x} \in \mathbb{R}^n$ interchangebly to indicate an n-dimensional vector, where x_i is the i^{th} entry of $\mathbf{x}$. By default, $f(\cdot)$ is used to denote a continuous function, and $F(\cdot)$ to represent a set function. For a differentiable function $f(\cdot)$, $\nabla f(\cdot)$ denotes its gradient. $\mathbf{x}|x_i \leftarrow k$ is the operation of setting the i^{th} element of $\mathbf{x}$ to k, while keeping all other elements unchanged, i.e., $\mathbf{x}|x_i \leftarrow k = \mathbf{x} - x_i \mathbf{e}_i + k \mathbf{e}_i$. For two sets S and T, $S + T$ and $S - T$ represent set union and set difference, respectively. $|S|$ is the cardinality of S. i is used to denote the singleton $\{i\}$ with a bit abuse of notation.

Existing valuation criteria. Various valuation criteria have been proposed from the area of cooperative games, amongst them the most famous ones are the Shapley value (Shapley, 1953) and the Banzhaf index (Penrose, 1946; Banzhaf III, 1964). For the Shapley value, the importance assigned to player i is:

$$\mathbf{Sh}_i = \sum\nolimits_{S \subseteq N-i} [F(S+i) - F(S)] \frac{|S|!(n-|S|-1)!}{n!}. \tag{2}$$

One can see that it gives less weight to $n/2$-sized coalitions. It satisfies several axioms: null player, symmetry, additivity and efficiency (Shapley, 1953). See Appendix B for details on common axioms in cooperative games. The Banzhaf index, actually proposed earlier than the Shapley value, assigns the following importance to player i:

$$\mathbf{Ba}_i = \sum\nolimits_{S \subseteq N-i} [F(S+i) - F(S)] \frac{1}{2^{n-1}}, \tag{3}$$

which uses uniform weights for all the coalitions. See Greco et al. (2015) for a comparison of Shapley value and Banzhaf index.

Valuation problems in machine learning. Currently most classes of valuation problems (Lundberg and Lee, 2017; Ghorbani and Zou, 2019; Sim et al., 2020; Rozemberczki and Sarkar, 2021) use Shapley value as the valuation criterion. Along with the rapid progress of model interpretation in the

past decades (Zeiler and Fergus, 2014; Ribeiro et al., 2016; Lundberg and Lee, 2017; Sundararajan et al., 2017; Petsiuk et al., 2018; Wang et al., 2021a), attribution-based interpretation aims to assign importance to the features for a specific data instance $(\mathbf{x} \in \mathbb{R}^N, y)$ given a black-box model $\mathcal{M}$. Here each feature maps to a player in the game $(N, F(S))$, and the value function $F(S)$ is usually the model response, such as the predicted probability for classification problems, when feeding a subset S of features to $\mathcal{M}$. The data valuation problem (Ghorbani and Zou, 2019) tries to assign values to the samples in the training dataset $N = \{(\mathbf{x}_i, y_i)\}_1^n$ for general supervised machine learning: one training sample corresponds to one player, and the value function $F(S)$ indicates the predictor performance on some test dataset given access to only a subset of the training samples in S. Model valuation in ensembles (Rozemberczki and Sarkar, 2021) measures importance of individual models in an ensemble in order to correctly label data points from a dataset, where each pre-trained model maps to a player and the value function measures the predictive performance of subsets of models.

3 RELATED WORK

Energy-based modeling. Energy based learning (LeCun et al., 2006) is a classical learning framework that uses an energy function $E(\mathbf{x})$ to measure the quality of a data point $\mathbf{x}$. Energy based models have been applied to different domains, such as data generation (Deng et al., 2020), out-of-distribution detection (Liu et al., 2020), reinforcement learning (Haarnoja et al., 2017), memory modeling (Bartunov et al., 2019), discriminative learning (Grathwohl et al., 2019; Gustafsson et al., 2020) and biologically-plausible training (Scellier and Bengio, 2017). Energy based learning admits principled training methods, such as contrastive divergence (Hinton, 2002), noise contrastive estimation (Gutmann and Hyvärinen, 2010) and score matching (Hyvärinen, 2005). For approximate inference, sampling based approaches are mainly MCMC-style algorithms, such as stochastic gradient Langevin dynamics (Welling and Teh, 2011). For a wide class of EBMs with submodular or supermodular energies (Djolonga and Krause, 2014), there exist provable mean field inference algorithms with constant factor approximation guarantees (Bian et al., 2019).

Shapley values in machine learning. Shapley values have been extensively used for valuation problems in machine learning, including attribution-based interpretation (Cohen et al., 2007; Datta et al., 2016; Lundberg and Lee, 2017; Chen et al., 2018; Lundberg et al., 2018; Kumar et al., 2020; Wang et al., 2021b), data valuation (Ghorbani and Zou, 2019; Jia et al., 2019b;a; Wang et al., 2020; Fan et al., 2021), collaborative machine learning (Sim et al., 2020) and recently, model valuation in ensembles (Rozemberczki and Sarkar, 2021). To alleviate the exponential computational cost of exact evaluation, various methods have been proposed to approximately calculate Shapley values in polynomial time (Ancona et al., 2017; 2019). It is worth noting that these approximation techniques can be seamlessly lifted to estimate the Variational Index proposed in this work. Owen (1972) proposes the multilinear extension purely as a representation of cooperative games and Okhrati and Lipani (2021) use it to develop sampling algorithms for Shapley values.

4 VALUATION FOR COOPERATIVE GAMES: A DECOUPLING PERSPECTIVE

In the introduction we have verified that under the setting of cooperative games, the Boltzmann distribution (see Eq. (1)) achieves the maximum entropy among all of the pmf functionals. One can naturally view the importance assignment problem of cooperative games as a *decoupling problem*: The n players in a game $(N, F(S))$ might be arbitrarily correlated in a very complicated manner. However, in order to assign each of them an *individual* importance value, we have to decouple their interactions, which can be viewed as a way to simplify their correlations.

We therefore consider a surrogate distribution $q(S; \mathbf{x})$ governed by parameters in $\mathbf{x}$. q has to be simple, given our intention to decouple the correlations among the n players. A natural choice is to restrain $q(S; \mathbf{x})$ to be fully factorizable, which leads to a mean-field approximation of $p(S)$. The simplest form of $q(S; \mathbf{x})$ would be a n independent Bernoulli distribution, i.e., $q(S; \mathbf{x}) := \prod_{i \in S} x_i \prod_{j \notin S} (1 - x_j), \mathbf{x} \in [0, 1]^n$. Given a divergence measure $D(\cdot \| \cdot)$ for probability distributions, we can define the *best conceivable decoupling error* to be the divergence between p and the best possible q.

Definition 1 (Best Conceivable Decoupling Error)**.** *Considering a cooperative game $(N, F(S))$, and given a divergence measure $D(\cdot \| \cdot)$ for probability distributions, the decoupling error is defined as the divergence between q and p: $D(q \| p)$, and the best conceivable decoupling error is defined as the*

divergence between the best possible q and p:

$$D^* := \min_q D(q\|p). \tag{4}$$

Note that the *best conceivable decoupling error* D^* is closely related to the intrinsic coupling amongst n players: if all the players are already independent with each other, then D^* could be zero.

4.1 MEAN FIELD OBJECTIVE FOR EBMS

If we consider the *decoupling error* $D(q\|p)$ to be the Kullback-Leibler divergence between q and p, then we recover the mean field approach[2]. Given the EBM formulation in Eq. (1), the classical mean-field inference approach aims to approximate $p(S)$ by a fully factorized product distribution $q(S; \mathbf{x}) := \prod_{i \in S} x_i \prod_{j \notin S}(1 - x_j), \mathbf{x} \in [0, 1]^n$, by minimizing the distance measured w.r.t. the Kullback-Leibler divergence between q and p. Since $\mathbb{KL}(q\|p)$ is non-negative, we have:

$$
\begin{aligned}
0 \le \mathbb{KL}(q\|p) &= \sum_{S \subseteq N} q(S; \mathbf{x}) \log \frac{q(S; \mathbf{x})}{p(S)} \\
&= -\mathbb{E}_{q(S;\mathbf{x})}[\log p(S)] - \mathbb{H}(q(S;\mathbf{x})) \tag{5} \\
&= -\mathbb{E}_{q(S;\mathbf{x})}\Big[\frac{F(S)}{T} - \log \mathbb{Z}\Big] - \mathbb{H}(q(S;\mathbf{x})) \tag{6} \\
&= -\sum_{S \subseteq N} \frac{F(S)}{T} \prod_{i \in S} x_i \prod_{j \notin S}(1 - x_j) + \sum_{i=1}^{n}[x_i \log x_i + (1 - x_i)\log(1 - x_i)] + \log \mathbb{Z}. \tag{7}
\end{aligned}
$$

In Eq. (6) we plug in the EBM formulation that $\log p(S) = \frac{F(S)}{T} - \log \mathbb{Z}$. Then one can get

$$
\begin{aligned}
\log \mathbb{Z} &\ge \sum_{S \subseteq N} \frac{F(S)}{T} \prod_{i \in S} x_i \prod_{j \notin S}(1 - x_j) - \sum_{i=1}^{n}[x_i \log x_i + (1 - x_i)\log(1 - x_i)] \\
&= \frac{f_{\mathrm{mt}}^F(\mathbf{x})}{T} + \mathbb{H}(q(S;\mathbf{x})) := \text{(ELBO)} \tag{8}
\end{aligned}
$$

where $\mathbb{H}(\cdot)$ is the entropy, ELBO stands for the *evidence lower bound*, and

$$f_{\mathrm{mt}}^F(\mathbf{x}) := \sum_{S \subseteq N} F(S) \prod_{i \in S} x_i \prod_{j \notin S}(1 - x_j), \mathbf{x} \in [0, 1]^n, \tag{9}$$

is the *multilinear extension* of $F(S)$ (Owen, 1972; Calinescu et al., 2007). Note that the multilinear extension plays a central role in modern combinatorial optimizaiton techniques (Feige et al., 2011), especially for guaranteed submodular maximization problems (Krause and Golovin, 2014; Bach, 2015).

Maximizing (ELBO) in Eq. (8) amounts to minimizing the Kullback-Leibler divergence between q and p. If one solves this optimization problem to optimality, one can obtain the $q(S; \mathbf{x}^*)$ with the best conceivable decoupling error. Here x_i^* describes the odds that player i shall participate in the game, so it can be naturally used to define the importance score of each player.

Definition 2 (Variational Index of Cooperative Games). *Consider a cooperative game $(N, F(S))$ and its mean field approximation. Let $\mathbf{x}^*$ be the variational marginals with the best conceivable decoupling error, we define $\mathbf{s}^* := T\sigma^{-1}(\mathbf{x}^*)$ to be the variational index of the game. Formally,*

$$\mathbf{x}^* = \arg\min_{\mathbf{x}} \mathbb{KL}(q(S; \mathbf{x})\|p(S)), \tag{10}$$

where $\mathbf{x}^*$ can be obtained by maximizing the ELBO objective in Eq. (8), and $\sigma^{-1}(\cdot)$ is the inverse of the sigmoid function, i.e. $\sigma^{-1}(x) = \log \frac{x}{1-x}$. For a vector it is applied element-wise.

4.2 ALGORITHMS FOR CALCULATING THE VARIATIONAL INDEX

Equilibrium condition. For coordinate i, the partial derivative of the multilinear extension is $\nabla_i f_{\mathrm{mt}}^F(\mathbf{x})$, and for the entropy term, it is $\nabla_i \mathbb{H}(q) = \log \frac{1-x_i}{x_i}$. By setting the partial derivative of ELBO in Eq. (8) to be 0, we have the equilibrium condition:

$$x_i^* = \sigma(\nabla_i f_{\mathrm{mt}}^F(\mathbf{x}^*)/T) = \big(1 + \exp(-\nabla_i f_{\mathrm{mt}}^F(\mathbf{x}^*)/T)\big)^{-1}, \quad \forall i \in N, \tag{11}$$

---

[2]Notably, one could also apply the reverse KL divergence $\mathbb{KL}(p\|q)$, which would lead to an expectation propagation (Minka, 2001) treatment of cooperative games.

where σ is the sigmoid function. This equilibrium condition implies that one cannot change the value assigned to any player in order to further improve the overall decoupling performance. It also implies the fixed point iteration $x_i \leftarrow \sigma(\nabla_i f_{\mathrm{mt}}^F(\mathbf{x})/T)$. When updating each coordinate sequentially, we recover the classic naive mean field algorithm as shown in Appendix C.

Instead, here we suggest to use the full-gradient method shown in Alg. 1 for maximizing the ELBO objective. As we will see later, the resultant valuations satisfy certain game-theoretic axioms. It needs an initial marginal vector $\mathbf{x}^0 \in [0, 1]^n$ and the number of epochs K. After K steps of gradient ascent, it returns the estimated marginal $\mathbf{x}^K$.

Algorithm 1: Mean Field Inference with Full Gradient: MFI($\mathbf{x}; K$)

Input: A cooperative game $(N, F(S))$ with n players. Initial marginals $\mathbf{x}^0 \leftarrow \mathbf{x} \in [0, 1]^n$;
    #epochs K.
Output: Marginals after K steps of gradient ascent: $\mathbf{x}^K$
1 **for** $k = 1 \rightarrow K$ **do**
2     $\mathbf{x}^k \leftarrow \sigma(\nabla f_{\mathrm{mt}}^F(\mathbf{x}^{k-1})/T) = \left(1 + \exp(-\nabla f_{\mathrm{mt}}^F(\mathbf{x}^{k-1})/T)\right)^{-1}$;

In case Alg. 1 solves the optimization problem to optimality, we obtain the Variational Index. However, maximizing ELBO is in general a non-convex/non-concave problem, and hence one can only ensure reaching a stationary solution. Below, when we say Variational Index, we therefore refer to its approximation obtained via gradient ascent by default.

Meanwhile, the MFI($\mathbf{x}; K$) subroutine also defines a series of marginals, which enjoy interesting properties as we show in the next part. So we define variational valuations through intermediate solutions of MFI($\mathbf{x}; K$).

Definition 3 (K-Step Variational Values). *Considering a cooperative game $(N, F(S))$ and its mean field approximation by Alg. 1, we define the K-Step Variational Value initialized at $\mathbf{x}$ as:*

$$T\sigma^{-1}(MFI(\mathbf{x}; K)), \tag{12}$$

where $\sigma^{-1}()$ is the inverse of the sigmoid function ($\sigma^{-1}(x) = \log \frac{x}{1-x}$).

Notice when running more steps, the K-Step variational value will be more close to the Variational Index. The gradient $\nabla f_{\mathrm{mt}}^F(\mathbf{x})$ itself is defined with respect to an exponential sum via the multilinear extension. Next we show how it can be approximated via principled sampling methods.

Sampling methods for estimating the partial derivative. The partial derivative follows,

$$
\begin{aligned}
\nabla_i f_{\mathrm{mt}}^F(\mathbf{x}) &= \mathbb{E}_{q(S;(\mathbf{x}|x_i \leftarrow 1))}[F(S)] - \mathbb{E}_{q(S;(\mathbf{x}|x_i \leftarrow 0))}[F(S)] \\
&= f_{\mathrm{mt}}^F(\mathbf{x}|x_i \leftarrow 1) - f_{\mathrm{mt}}^F(\mathbf{x}|x_i \leftarrow 0) \\
&= \sum_{S \subseteq N, S \ni i} F(S) \prod_{j \in S-i} x_j \prod_{j' \notin S}(1 - x_{j'}) \quad - \sum_{S \subseteq N-i} F(S) \prod_{j \in S} x_j \prod_{j' \notin S, j' \neq i}(1 - x_{j'}) \\
&= \sum_{S \subseteq N-i}[F(S + i) - F(S)] \prod_{j \in S} x_j \prod_{j' \in N-S-i}(1 - x_{j'}) \\
&= \sum_{S \subseteq N-i}[F(S + i) - F(S)]q(S; (\mathbf{x}|x_i \leftarrow 0)) = \mathbb{E}_{S \sim q(S;(\mathbf{x}|x_i \leftarrow 0))}[F(S + i) - F(S)].
\end{aligned}
\tag{13}
$$

All of the variational criteria are based on the calculation of the partial derivative $\nabla_i f_{\mathrm{mt}}^F(\mathbf{x})$, which can be approximated by Monte Carlo sampling since $\nabla_i f_{\mathrm{mt}}^F(\mathbf{x}) = \mathbb{E}_{S \sim q(S;(\mathbf{x}|x_i \leftarrow 0))}[F(S + i) - F(S)]$: we first sample m coalitions $S_k, k = 1, ..., m$ from the surrogate distribution $q(S; (\mathbf{x}|x_i \leftarrow 0))$, then approximate the expectation by the average $\frac{1}{m}\sum_{k=1}^{m}[F(S_k + i) - F(S_k)]$. According to the Chernoff-Hoeffding bound (Hoeffding, 1963), the approximation will be arbitrarily close to the true value with increasingly more samples: With probability at least $1 - \exp(-m\epsilon^2/2)$, it holds that $|\frac{1}{m}\sum_{k=1}^{m}[F(S_k + i) - F(S_k)] - \nabla_i f_{\mathrm{mt}}^F(\mathbf{x})| \leq \epsilon \max_S |F(S + i) - F(S)|$, for all $\epsilon > 0$.

Roles of the initializer $\mathbf{x}^0$ and the temperature T. This can be understood in the following respects: 1) The initializer $\mathbf{x}^0$ represents the initial credit assignments to the n players, so it denotes the prior

knowledge/initial belief of the contributions of the players; 2) If one just runs Alg. 1 for one step, $\mathbf{x}^0$ matters a lot to the output. However, if one runs Alg. 1 for many steps, it wouldn't affect too much on the final output: $\mathbf{x}^k$ will converge to the stationary points according to the classical mean field theory (see our results below on convergence of Alg. 1). Empirically, it will take around 5∼10 steps to converge. The temperature T controls the "spreading" of credits assigned to the players: A higher T leads to more flat assignments, and a lower T leads to more concentrated assignments.

Computational efficiency of calculating Variational Index and variational values. Alg. 1 calculates the K-step variational values, 1-step variatioinal value has the same computational cost as that of Shapley value and Banzhaf index, since they all need to evaluate the gradient of multilinear extension. Sampling methods could help with approximating all of the three criteria when there are a large number of players. Variational Index can be approximated by K-step variational value, the number K depends on when Alg. 1 will converge. One can easily show that, under the setting of maximizing ELBO, $\mathbf{x}^k$ will converge to some stationary point $\mathbf{x}^*$, based on the analysis of mean field approximation in Wainwright and Jordan (2008). We have also empirically verified the convergence rate of Alg. 1 in Sec. 5.3, and find that it always converges with 5 to 10 steps. So the computational cost is roughly similar as that of Shapley value and Banzhaf index.

4.3 RECOVERING CLASSICAL CRITERIA

Perhaps surprisingly, it is possible to recover classical valuation criteria via the K-step variational values as in Def. 3. Firstly, for Banzhaf index, by comparing with Eq. (13) it reads,

$$\text{Ba}_i = \sum_{S \subseteq N-i} [F(S+i) - F(S)] \frac{1}{2^{n-1}} = \nabla_i f_{\text{mt}}^F(0.5 * \mathbf{1}) = T\sigma^{-1}(\text{MFI}(0.5 * \mathbf{1}; 1)), \quad (14)$$

which is the 1-step variational value initialied at $0.5 * \mathbf{1}$. We can also recover the Shapley value through its connection to the multilinear extension (Owen, 1972; Grabisch et al., 2000):

$$\text{Sh}_i = \int_0^1 \nabla_i f_{\text{mt}}^F(x\mathbf{1})dx = \int_0^1 T\sigma^{-1}(\text{MFI}(x\mathbf{1}; 1))dx, \quad (15)$$

where the integration denotes integrating the partial-derivative of the multilinear extension along the main diagonal of the unit hypercube. A self-contained proof is given in Appendix D.

These insights offer a novel, unified interpretation of the two classical valuation indices: both the Shapley value and Banzhaf index can be viewed as approximating the variational index by running *one step* of gradient ascent for the decoupling (ELBO) objective. Specifically, for the Banzhaf index, it initializes $\mathbf{x}$ at $0.5 * \mathbf{1}$, and runs one step of gradient ascent. For the Shapley value, it also performs a one-step gradient-ascent approximation. However, instead of starting at a single initial point, it averages over all possible intialializations through the line integration in Eq. (15).

Relation to probabilistic values. Probabilistic values for games (Weber, 1988; Monderer and Samet, 2002) capture a class of solution concepts, where the value of each player is given by some averaging of the player's marginal contributions to coalitions, and the weights depend on the colitions only. According to (Monderer and Samet, 2002, Equation (3.1)), a solution ϕ is called a probabilistic value, if for each player i, there exists a probability $p^i \in \Delta(C^i)$, such that ϕ_i is the expected marginal contribution of i w.r.t. p^i. Namely, $\phi_i = \sum_{S \in C^i} p^i(S)[F(S+i) - F(S)]$, where C^i is the set of all subsets of $N - i$, and $\Delta(C^i)$ is the set of all probability measures on C^i. One can easily see that, for any fixed $\mathbf{x}$, 1-step variational value in Def. 3 is a probabilistic value with $p^i(S) = q(S; (\mathbf{x}|x_i \leftarrow 0))$, where $q(S; \mathbf{x})$ is the surrogate distribution in our EBM framework.

4.4 AXIOMATISATION OF VARIATIONAL VALUES

Our EBM framework introduces a series of variational values controlled by T and the running step number K. We now establish that the variational values $T\sigma^{-1}(\text{MFI}(0.5; K))$ in Def. 3 satisfy certain game-theoretic axioms (see Appendix B for definitions of five common axioms: Null player, Symmetry, Marginalism, Additivity and Efficiency). We prove that all the variational values in the trajectory satisfy three fundamental axioms: null player, marginalism and symmetry. Detailed proof is deferred to Appendix E. Note that it might be very difficult or even impossible to find equivalent axiomatisations of the series of variational values, which will be left for future work. Meanwhile, our methods incur a decoupling and fairness tradeoff by tuning the the two hyperparameters K and T.

Figure 1: Data removing results. Numbers in the legend are the *decoupling* errors. Columns: 1st: synthetic data; 2nd: breast cancer data with 569 samples; 3rd: digits data with 1797 samples. Specific configurations (e.g., temperature) are put inside the figure texts.

Theorem 1 (Axiomatisation of Variational Values of Def. 3). *If initialized uniformly, i.e., $\mathbf{x}^0 = x\mathbf{1}, x \in [0, 1]$, all the variational values in the trajectory $T\sigma^{-1}(MFI(\mathbf{x}; k)), k = 1, 2, 3...$ satisfy the null player, marginalism and symmetry axioms.*

Why additivity and efficiency do not make sense? We do not expect Variational Values to satisfy the additivity and efficiency axioms due to the following reasons: 1) Similar as what Ridaoui et al. (2018) argues, efficiency and additivity do not make sense for certain games. Let's consider feature valuation in the simple classification problem, which can be viewed as a voting game $(N, F(S))$: each feature participates in the coalition in order to vote for the result to be true or false. In this circumstance, what matters is the voting power of each feature. However, the voting power shall not be distributed to each of the players, which means the efficiency axiom does not make sense. Meanwhile, suppose one just duplicate the original classification game to get a second game $(N, F'(S))$. Being involved in two same games would not double the voting power of a feature, so additivity doesn't make sense either. 2) Efficiency can be viewed as imposing some "fairness" constraints on the valuations, which might not always be distributing the total payoff $F(N)$ to all players. Tuning the temperature T in our EBM formulation (Eq. (1)) is arguably a better way to control fairness since T affects the spreading of assignment. One can potentially tune T in the classical annealing manner.

5   EMPIRICAL STUDIES

Throughout the experiments, we are trying to understand the following: 1) Would the proposed Variational Index have lower decoupling error compared to others? 2) Could the proposed Variational Index gain benefits compared to the classical valuation criteria for valuation problems?

Since we are mainly comparing the quality of different criteria, it is necessary to rule out the influence of approximation errors when estimating their values. So we focus on small-sized problems where one can compute the exact values of these criteria in a reasonable time. Usually this requires the number of players to be no more than 25. Meanwhile, we have also conducted experiments with a larger number of players in Appendix F.5, in order to show the efficiency of sampling methods. We choose T empirically from the values of 0.1, 0.2, 0.5, 1.0. We choose K such that Alg. 1 would converge. Usually, it takes around 5 to 10 steps to converge. We give all players a fair start, so $\mathbf{x}^0$ was intialized to be $0.5 \times \mathbf{1}$. Code will be released soon.

We first conduct synthetic experiments on submodular games (details defered to Appendix F.1), in order to verify the quality of solutions in terms of the true marginals $p(i \in \mathbf{S})$. One can conclude that Variational Index obtains better performance in terms of MSE and Spearman's rank correlation compared to the one-point solutions (Shapley value and Banzhaf index) in all experiments. More experimental results on data point and feature valuations are deferred to Appendix F.

Figure 2: First column: Change of predicted probabilities when removing features. The *decoupling error* is included in the legend. Last three columns: waterfall plots of feature importance.

5.1 EXPERIMENTS ON DATA VALUATIONS

We follow the setting of Ghorbani and Zou (2019) and reuse the code of `https://github.com/amiratag/DataShapley`. We conduct data removal: training samples are sorted according to the valuations returned by different criteria, and then samples are removed in that order to check how much the test accuracy drops. Intuitively, the best criteria would induce the fastest drop of performance. We experiment with the following datasets: a) Synthetic datasets similar as that of Ghorbani and Zou (2019); b) The breast cancer dataset, which is a binary classification dataset with 569 samples; c) The digits dataset, that is a 10-class classification dataset with 1797 samples. The above two datasets are both from UCI Machine Learning repository (`https://archive.ics.uci.edu/ml/index.php`). Specifically, we cluster data points into groups and studied two settings: 1) Grouping the samples randomly; 2) Clustering the samples with the k-means algorithm. For simplicity, we always use equal group sizes. The data point removal corresponds to singleton groups. Fig. 1 shows the results. One can observe that in certain situations the Variational Index achieves the fastest drop rate. It always achieves the lowest decoupling error (as shown in the legends in each of the figures). Sometimes Variational Index and Banzhaf show similar performance. We expect that this is because the Bahzhaf index is a one-step approximation of Variational Index, and for the specific problem considered, the ranking of the solutions does not change after one-step of gradient ascent. There are also situations that the rankings of the three criteria are not very distinguible, however, the specific values are also very different since the decoupling error differs.

5.2 EXPERIMENTS ON FEATURE VALUATIONS/ATTRIBUTIONS

We follow the setting of Lundberg and Lee (2017) and reuse the code of `https://github.com/slundberg/shap` with an MIT License. We train classifiers on the Adult dataset[3], which predicts whether an adult's income exceeds 50k dollar per year based on census data. It has 48,842 instances and 14 features such as age, workclass, occupation, sex and capital gain (12 of them used).

Feature removal results. This experiment follows a similar fashion as the data removal experiment: we remove the features one by one according to the order defined by the returned criterion, then observe the change of predicted probabilities. Fig. 2 reports the behavior of the three criteria. The first row shows the results from an xgboost classifier (accuracy: 0.893), second row a logistic regression classifier (accuracy: 0.842), third row a multi-layer perceptron (accuracy: 0.861). For the probability dropping results, Variational Index usually induces the fastest drop, and it always enjoys the smallest decoupling error, as expected from its mean-field nature. From the waterfall plots, one can see that the three criteria indeed produce different rankings of the features. Take the first row for example.

---

[3]`https://archive.ics.uci.edu/ml/datasets/adult`

GT Labels: True	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Capital Gain	Relationship	Age	Education-Num	Occupation	Marital Status	Capital Loss	Hours per week	Sex	Race	Workclass	Country
Shapley	Capital Gain	Relationship	Education-Num	Age	Occupation	Marital Status	Hours per week	Capital Loss	Sex	Workclass	Race	Country
Banzhaf	Capital Gain	Relationship	Education-Num	Age	Occupation	Marital Status	Capital Loss	Hours per week	Sex	Race	Workclass	Country

Figure 3: Statistics on valuations with the *xgboost* classifier. First row: box plot of valuations. We always consider the predicted probability of the ground truth label. "True" means the samples with positive ground truth label and "False" means with the negative ground truth label. Second row: Average ranking of the 12 features. Colored texts denote different rankings among the three criteria.

All criteria put "Capital Loss" and "Relationship" as the first two features. However, the remaining features have different ranking: Variational Index and Banzhaf indicate that "Marital Status" should be ranked third, while Shapley ranks it in the fourth position. It is hard to tell which ranking is the best because: 1) There is no golden standard to determine the true ranking of features; 2) Even if there exists a ground truth ranking of some "perfect model", the trained xgboost model here might not be able to reproduce it, since it might not be aligned with the "perfect model". The feature removal experiments nevertheless demonstrate the intriguing behavior of Variational Index.

Average results. We further provide the bar plots and averaged ranking across the adult datasets in Fig. 3. From the bar plots one can see that different criterion has slightly different values for each feature on average. Average rankings in the table demonstrate the difference: The three methods do not agree on the colored features, for example, "Age", "Education-Num" and "Captical Loss".

5.3 EMPIRICAL CONVERGENCE RESULTS OF ALG. 1

Table 1 shows empirical convergence results of Alg. 1 on feature and data valuation experiments. The value in the cells are the stepwise difference of $\mathbf{x}^k$, $\frac{\|\mathbf{x}^k - \mathbf{x}^{k-1}\|^2}{n}$, which is a classical criterion to measure the convergence of iterative algorithms. One can clearly see that for all the experiments, Alg. 1 converges in 5 to 10 iterations.

Table 1: Stepwise difference $\frac{\|\mathbf{x}^k - \mathbf{x}^{k-1}\|^2}{n}$ of Alg. 1 for different experiments.

Step/Iteration Num	1	2	3	5	9	10
Data Val (breast cancer)	0.0023	3.61e-6	1.53e-7	2.77e-10	9.12e-16	0
Data Val (digits)	0.00099	5.93e-7	1.46e-8	8.92e-12	9.25e-18	0
Data Val (synthetic)	0.00059	2.49e-8	3.13e-10	6.06e-14	0	0
Feature Val (xgboost)	0.0066	1.68e-5	8.71e-7	2.35e-9	1.75e-14	9.25e-16
Feature Val (LR)	0.0092	2.63e-5	1.44e-6	4.31e-9	2.14e-15	1.28e-16
Feature Val (MLP)	0.0040	4.86e-6	1.86e-7	2.84e-10	6.82e-16	3.20e-17

DISCUSSIONS AND FUTURE WORK. We have presented an energy-based treatment of cooperative games, in order to improve the valuation problem. It is very worthwhile to explore more in the following directions: 1) Choosing the temperature T. The temperature controls the level of fairness since when $T \to \infty$, all players have equal importance, when $T \to 0$, a player has either 0 or 1 importance. Perhaps one can use an annealing-style algorithm in order to control the fairness level: starting with a high temperature and gradually decreasing it, one can obtain a series of importance values under different fairness levels. 2) Given the probabilistic treatment of cooperative games, one can naturally add priors over the players, in order to encode more domain knowledge. It may also make sense to consider conditioning and marginalization in light of practical applications. 3) It's very interesting to explore the interaction of a group of players in the energy-based framework, which would result in an "interactive" index among size-k coalitions. This can be potentially solved by some group-based variational inference methods.

ETHICS STATEMENT AND BROADER IMPACT

Besides the valuation problems explored in this work, cooperative game theory has already been applied to a wide range of disciplines, to name a few, economics, political science, sociology, biology, so this work could potentially contribute to broader domains as well.

Meanwhile, we have to be aware of possible negative societal impacts, including: 1) negative side effects of the technology itself, for example, possible unemployment issue due to the reduced amount of the need of valuations by human beings; 2) applications in negative downstream tasks, for instance, the data point valuation technique could make it easier to conduct underground transactions of private data.

REPRODUCIBILITY STATEMENT

All the datasets are publicly available as described in the main text. In order to ensure reproducibility, we have made the efforts in the following respects: 1) Provide a sampled code as the supplementary material. 2) Provide self-contained proofs of the main claims in Appendices D and E; 3) Provide more details on experimental configurations and experimental results in Appendix F.

REFERENCES

M. Ancona, E. Ceolini, C. Öztireli, and M. Gross. Towards better understanding of gradient-based attribution methods for deep neural networks. *arXiv preprint arXiv:1711.06104*, 2017.

M. Ancona, C. Öztireli, and M. Gross. Explaining deep neural networks with a polynomial time algorithm for shapley values approximation. *arXiv preprint arXiv:1903.10992*, 2019.

F. Bach. Submodular functions: from discrete to continuous domains. *arXiv preprint arXiv:1511.00394*, 2015.

J. F. Banzhaf III. Weighted voting doesn't work: A mathematical analysis. *Rutgers L. Rev.*, 19:317, 1964.

S. Bartunov, J. W. Rae, S. Osindero, and T. P. Lillicrap. Meta-learning deep energy-based memory models. *arXiv preprint arXiv:1910.02720*, 2019.

Y. A. Bian, J. M. Buhmann, and A. Krause. Optimal continuous dr-submodular maximization and applications to provable mean field inference. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 644–653, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

G. Calinescu, C. Chekuri, M. Pál, and J. Vondrák. Maximizing a submodular set function subject to a matroid constraint. In *International Conference on Integer Programming and Combinatorial Optimization*, pages 182–196. Springer, 2007.

J. Chen, L. Song, M. J. Wainwright, and M. I. Jordan. L-shapley and c-shapley: Efficient model interpretation for structured data. *arXiv preprint arXiv:1808.02610*, 2018.

Y. Chun. A new axiomatization of the shapley value. *Games and Economic Behavior*, 1(2):119–130, 1989.

S. Cohen, G. Dror, and E. Ruppin. Feature selection via coalitional game theory. *Neural Computation*, 19(7):1939–1961, 2007.

I. Covert, S. Lundberg, and S.-I. Lee. Explaining by removing: A unified framework for model explanation. *arXiv preprint arXiv:2011.14878*, 2020.

A. Datta, S. Sen, and Y. Zick. Algorithmic transparency via quantitative input influence: Theory and experiments with learning systems. In *2016 IEEE symposium on security and privacy (SP)*, pages 598–617. IEEE, 2016.

Y. Deng, A. Bakhtin, M. Ott, A. Szlam, and M. Ranzato. Residual energy-based models for text generation. *arXiv preprint arXiv:2004.11714*, 2020.

J. Djolonga and A. Krause. From map to marginals: Variational inference in bayesian submodular models. In *Neural Information Processing Systems (NIPS)*, 2014.

Z. Fan, H. Fang, Z. Zhou, J. Pei, M. P. Friedlander, C. Liu, and Y. Zhang. Improving fairness for data valuation in federated learning. *arXiv preprint arXiv:2109.09046*, 2021.

U. Feige, V. S. Mirrokni, and J. Vondrák. Maximizing non-monotone submodular functions. *SIAM Journal on Computing*, 40(4):1133–1153, 2011.

A. Ghorbani and J. Zou. Data shapley: Equitable valuation of data for machine learning. In *International Conference on Machine Learning*, pages 2242–2251. PMLR, 2019.

M. Grabisch. K-order additive discrete fuzzy measures and their representation. *Fuzzy sets and systems*, 92(2):167–189, 1997.

M. Grabisch, J.-L. Marichal, and M. Roubens. Equivalent representations of set functions. *Mathematics of Operations Research*, 25(2):157–178, 2000.

W. Grathwohl, K.-C. Wang, J.-H. Jacobsen, D. Duvenaud, M. Norouzi, and K. Swersky. Your classifier is secretly an energy based model and you should treat it like one. *arXiv preprint arXiv:1912.03263*, 2019.

G. Greco, F. Lupia, and F. Scarcello. Structural tractability of shapley and banzhaf values in allocation games. In *Twenty-Fourth International Joint Conference on Artificial Intelligence*, 2015.

F. K. Gustafsson, M. Danelljan, R. Timofte, and T. B. Schön. How to train your energy-based model for regression. *arXiv preprint arXiv:2005.01698*, 2020.

M. Gutmann and A. Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pages 297–304. JMLR Workshop and Conference Proceedings, 2010.

T. Haarnoja, H. Tang, P. Abbeel, and S. Levine. Reinforcement learning with deep energy-based policies. In *International Conference on Machine Learning*, pages 1352–1361. PMLR, 2017.

P. L. Hammer and S. Rudeanu. *Boolean methods in operations research and related areas*, volume 7. Springer Science & Business Media, 2012.

G. E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 14(8):1771–1800, 2002.

W. Hoeffding. Probability inequalities for sums of bounded random variables. *Journal of the American statistical association*, 58(301):13–30, 1963.

A. Hyvärinen. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6(4), 2005.

E. T. Jaynes. Information theory and statistical mechanics. *Physical review*, 106(4):620, 1957a.

E. T. Jaynes. Information theory and statistical mechanics. ii. *Physical review*, 108(2):171, 1957b.

R. Jia, D. Dao, B. Wang, F. A. Hubis, N. Hynes, N. M. Gürel, B. Li, C. Zhang, D. Song, and C. J. Spanos. Towards efficient data valuation based on the shapley value. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 1167–1176. PMLR, 2019a.

R. Jia, X. Sun, J. Xu, C. Zhang, B. Li, and D. Song. An empirical and comparative analysis of data valuation with scalable algorithms. *arXiv preprint arXiv:1911.07128*, 2019b.

A. Krause and D. Golovin. Submodular function maximization. *Tractability*, 3:71–104, 2014.

I. E. Kumar, C. Scheidegger, S. Venkatasubramanian, and S. Friedler. Shapley residuals: Quantifying the limits of the shapley value for explanations. In *ICML Workshop on Workshop on Human Interpretability in Machine Learning (WHI)*, 2020.

Y. LeCun, S. Chopra, R. Hadsell, M. Ranzato, and F. Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

W. Liu, X. Wang, J. D. Owens, and Y. Li. Energy-based out-of-distribution detection. *arXiv preprint arXiv:2010.03759*, 2020.

S. Lundberg and S.-I. Lee. A unified approach to interpreting model predictions. *arXiv preprint arXiv:1705.07874*, 2017.

S. M. Lundberg, G. G. Erion, and S.-I. Lee. Consistent individualized feature attribution for tree ensembles. *arXiv preprint arXiv:1802.03888*, 2018.

T. P. Minka. Expectation propagation for approximate bayesian inference. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pages 362–369, 2001.

D. Monderer and D. Samet. Variations on the shapley value. *Handbook of game theory with economic applications*, 3:2055–2076, 2002.

R. Okhrati and A. Lipani. A multilinear sampling algorithm to estimate shapley values. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pages 7992–7999. IEEE, 2021.

G. Owen. Multilinear extensions of games. *Management Science*, 18(5-part-2):64–79, 1972.

L. S. Penrose. The elementary statistics of majority voting. *Journal of the Royal Statistical Society*, 109(1):53–57, 1946.

V. Petsiuk, A. Das, and K. Saenko. Rise: Randomized input sampling for explanation of black-box models. *arXiv preprint arXiv:1806.07421*, 2018.

M. T. Ribeiro, S. Singh, and C. Guestrin. " why should i trust you?" explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1135–1144, 2016.

M. Ridaoui, M. Grabisch, and C. Labreuche. An axiomatisation of the banzhaf value and interaction index for multichoice games. In *International Conference on Modeling Decisions for Artificial Intelligence*, pages 143–155. Springer, 2018.

B. Rozemberczki and R. Sarkar. The shapley value of classifiers in ensemble games. *arXiv preprint arXiv:2101.02153*, 2021.

B. Scellier and Y. Bengio. Equilibrium propagation: Bridging the gap between energy-based models and backpropagation. *Frontiers in computational neuroscience*, 11:24, 2017.

L. S. Shapley. A value for n-person games. *Contributions to the Theory of Games*, 2(28):307–317, 1953.

R. H. L. Sim, Y. Zhang, M. C. Chan, and B. K. H. Low. Collaborative machine learning with incentive-aware model rewards. In *International Conference on Machine Learning*, pages 8927–8936. PMLR, 2020.

M. Sundararajan, A. Taly, and Q. Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pages 3319–3328. PMLR, 2017.

S. Tschiatschek, J. Djolonga, and A. Krause. Learning probabilistic submodular diversity models via noise contrastive estimation. In *Proc. International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2016.

M. J. Wainwright and M. I. Jordan. *Graphical models, exponential families, and variational inference*. Now Publishers Inc, 2008.

J. Wang, J. Wiens, and S. Lundberg. Shapley flow: A graph-based approach to interpreting model predictions. In *International Conference on Artificial Intelligence and Statistics*, pages 721–729. PMLR, 2021a.

R. Wang, X. Wang, and D. I. Inouye. Shapley explanation networks. *arXiv preprint arXiv:2104.02297*, 2021b.

T. Wang, J. Rausch, C. Zhang, R. Jia, and D. Song. A principled approach to data valuation for federated learning. In *Federated Learning*, pages 153–167. Springer, 2020.

R. J. Weber. Probabilistic values for games. *The Shapley Value. Essays in Honor of Lloyd S. Shapley*, pages 101–119, 1988.

M. Welling and Y. W. Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pages 681–688. Citeseer, 2011.

H. P. Young. Monotonic solutions of cooperative games. *International Journal of Game Theory*, 14 (2):65–72, 1985.

M. D. Zeiler and R. Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pages 818–833. Springer, 2014.

Appendix

CONTENTS

A DERIVATIONS OF THE MAXIMUM ENTROPY DISTRIBUTION

One may wonder why do we need energy-based treatment of valuation problems in machine learning? Specifically, under the setting of cooperative games $(N, F(S))$, why we have to take the exponential form of EBM $p(S) \propto \exp(F(S)/T)$? Because one may also formulate it as something else, say, $p(S) \propto (1 + |F(S)|)$?

In one word, because EBM is the maximum entropy distribution. Being a maximum entropy distribution means minimizing the amount of prior information built into the distribution. Meanwhile, many physical systems tend to move towards maximal entropy configurations over time (Jaynes, 1957a;b).

In the following we will give a derivation to show that $p(S) \propto \exp(F(S)/T)$ is indeed the maximum entropy distribution for a cooperative game. The derivation bellow is closely following Jaynes (1957a;b) for statistical mechanics. Suppose each coalition S is associated with a payoff $F(S)$ with probability $p(S)$. We would like to maximize the entropy $\mathbb{H}(p) = -\sum_{S \subseteq N} p(S) \log p(S)$, subject to the constraints that $\sum_S p(S) = 1, p(S) \geq 0$ and $\sum_S p(S)F(S) = \mu$ (i.e., the average payoff is known as μ).

Writing down the Lagrangian

$$L(p, \lambda_0, \lambda_1) := -\left[\sum_{S \subseteq N} p(S) \log p(S) + \lambda_0 (\sum_{S \subseteq N} p(S) - 1) + \lambda_1 (\mu - \sum_{S \subseteq N} p(S)F(S))\right] \quad (16)$$

Setting

$$\frac{\partial L(p, \lambda_0, \lambda_1)}{\partial p(S)} = -\left[\log p(S) + 1 + \lambda_0 - \lambda_1 F(S)\right] \quad (17)$$

$$= 0 \quad (18)$$

we get:

$$p(S) = \exp[-(\lambda_0 + 1 - \lambda_1 F(S))] \tag{19}$$

$$\lambda_0 + 1 = \log \sum_{S \subseteq N} \exp(\lambda_1 F(S)) =: \log Z \tag{20}$$

is the log-partition function. So,

$$p(S) = \frac{\exp[\lambda_1 F(S))]}{Z} \tag{21}$$

Note that the maximum value of the entropy is

$$H_{\max} = -\sum_{S \subseteq N} p(S) \log p(S) \tag{22}$$

$$= \lambda_0 + 1 - \lambda_1 \sum_{S \subseteq N} p(S) F(S) \tag{23}$$

$$= \lambda_0 + 1 - \lambda_1 \mu \tag{24}$$

So one can get,

$$\lambda_1 = -\frac{\partial H_{\max}}{\partial \mu} =: \frac{1}{T} \tag{25}$$

which defines the inverse temperature.

So we reach the exponential form of $p(S)$ as:

$$p(S) = \frac{\exp[F(S)/T]}{\sum_{S \subseteq N} \exp[F(S)/T]}. \tag{26}$$

B COMMON AXIOMS OF VALUATION CRITERIA

Following the definitions in Covert et al. (2020), the five common axioms are listed as bellow. $\phi_i(F)$ denotes the value assigned to player i in the game $(N, F(S))$. Note that the notions might be slightly different in classical literature of game theory.

Null player: For a player i in the cooperative game $(N, F(S))$, if $F(S + i) = F(S)$ holds for all $S \subseteq N - i$, then its value should be $\phi_i(F) = 0$.

Symmetry: For any two players i, j in the cooperative game $(N, F(S))$, if $F(S + i) = F(S + j)$ holds for all $S \subseteq N - i - j$, then it holds that $\phi_i(F) = \phi_j(F)$.

Marginalism: For two games $(N, F(S))$ and $(N, G(S))$ where all players have identical marginal contributions, the players obtain equal valuations: $F(S + i) - F(S) = G(S + i) - G(S)$ holds for all (i, S), then it holds that $\phi_i(F) = \phi_i(G)$.

Additivity: For two games $(N, F(S))$ and $(N, G(S))$, if they are combined, the total contribution of a player is equal to the sum of its individual contributions on each game: $\phi_i(F+G) = \phi_i(F) + \phi_i(G)$.

Efficiency: The values add up to the difference in value between the grand coalition and the empty coalition: $\sum_{i \in N} \phi_i(F) = F(N) - F(\emptyset)$.

Remark 1 (The notion of "marginalism"). *Specifically, the marginalism axiom was first mentioned by (Young, 1985, Equation 7 on page 70), where it was called the "independence" condition; Following (Chun, 1989, page 121), it was formally called the "marginality". This axiom requires a player's payoffs to depend only on his own marginal contributions – whenever they remain unchanged, his payoffs should be unaffected.*

Algorithm 2: NAIVE MEAN FIELD FOR CALCULATING THE VARIATIONAL INDEX

Input: A cooperative game $(N, F(S))$ with n players. Initial marginal $\mathbf{x}^0 \in [0, 1]^n$; #epochs K.
Output: The Variational Index $\mathbf{s}^* = \sigma^{-1}(\mathbf{x}^*)$

1 $\mathbf{x} \leftarrow \mathbf{x}^0$;
2 **for** *epoch from* 1 *to* K **do**
3   **for** $i = 1 \rightarrow n$ **do**
4   let v_i be the player being operated;
5        $x_{v_i} \leftarrow \sigma(\nabla_{v_i} f_{\mathrm{mt}}^F(\mathbf{x})/T) = \left(1 + \exp(-\nabla_{v_i} f_{\mathrm{mt}}^F(\mathbf{x})/T)\right)^{-1}$;

6 $\mathbf{x}^* \leftarrow \mathbf{x}$;

C THE NAIVE MEAN FIELD ALGORITHM

The naive mean field algorithm is one of the most classical algorithm for mean field inference. It is summarized in Alg. 2.

D PROOF OF RECOVERING CLASSICAL CRITERIA

For Banzhaf index, by comparing its definition in Eq. (2) with Eq. (13) it reads,

$$\mathrm{Ba}_i = \sum_{S \subseteq N - i} [F(S + i) - F(S)] \frac{1}{2^{n-1}} = \nabla_i f_{\mathrm{mt}}^F(0.5 * \mathbf{1}) = T\sigma^{-1}(\mathrm{MFI}(0.5 * \mathbf{1}; 1)), \quad (27)$$

which is the 1-step variational value initialied at $0.5 * \mathbf{1}$.

For Shapley value, according to Grabisch et al. (2000), here we prove a stronger conclusion regarding the generalization of Shapley value: Shapley interaction index, which is defined for any coalition S:

$$\mathrm{Sh}_S = \sum_{T \subseteq N - S} \frac{(n - |T| - |S|)!|T|!}{(n - |S| + 1)!} \sum_{L \subseteq S} (-1)^{|S| - |L|} F(L + T). \quad (28)$$

Given Hammer and Rudeanu (2012), we have a second form of the multilinear extension as:

$$f_{\mathrm{mt}}^F(\mathbf{x}) = \sum_{S \subseteq N} a(S) \prod_{i \in S} x_i, \mathbf{x} \in [0, 1]^n, \quad (29)$$

where $a(S) := \sum_{T \subseteq S} (-1)^{|S| - |T|} F(T)$ is the Mobius transform of $F(S)$.

Then, one can show the S-derivative of $f_{\mathrm{mt}}^F(\mathbf{x})$ is (suppose $S = \{i_1, ..., i_{|S|}\}$),

$$\Delta_S f_{\mathrm{mt}}^F(\mathbf{x}) := \frac{\partial^{|S|} f_{\mathrm{mt}}^F(\mathbf{x})}{\partial x_{i_1}, ..., \partial x_{i_{|S|}}} = \sum_{T \supseteq S} a(T) \prod_{i \in T - S} x_i. \quad (30)$$

So,

$$\Delta_S f_{\mathrm{mt}}^F(x\mathbf{1}) = \sum_{T \supseteq S} a(T) x^{|T| - |S|}. \quad (31)$$

Then it holds,

$$\int_0^1 \Delta_S f_{\mathrm{mt}}^F(x\mathbf{1}) dx = \int_0^1 \sum_{T \supseteq S} a(T) x^{|T| - |S|} dx \quad (32)$$

$$= \sum_{T \supseteq S} a(T) \int_0^1 x^{|T| - |S|} dx \quad (33)$$

$$= \sum_{T \supseteq S} a(T)(|T| - |S| + 1)^{-1} \quad (34)$$

According to Grabisch (1997), we have $\text{Sh}_S = \sum_{T \supseteq S} a(T)(|T| - |S| + 1)^{-1}$, then we reach the conclusion:

$$\text{Sh}_S = \int_0^1 \Delta_S f_{\text{mt}}^F(x\mathbf{1}) dx. \tag{35}$$

When $|S| = 1$, we recover the conclusion for Shapley value.

E PROOF OF THEOREM 1

Theorem 1 (Axiomatisation of Variational Values of Def. 3). *If initialized uniformly, i.e., $\mathbf{x}^0 = x\mathbf{1}, x \in [0, 1]$, all the variational values in the trajectory $T\sigma^{-1}(MFI(\mathbf{x}; k)), k = 1, 2, 3...$ satisfy the null player, marginalism and symmetry axioms.*

Proof of Theorem 1. In step k, we know that the value to player i is:

$$T\sigma^{-1}(MFI(\mathbf{x}; k))_i = \sum_{S \subseteq N-i} [F(S+i) - F(S)] \prod_{j \in S} x_j \prod_{j' \in N-S-i} (1 - x_{j'}) \tag{36}$$

For the **null player** property, since $F(S + i) = F(S)$ always holds, it is easy to see that $T\sigma^{-1}(MFI(\mathbf{x}; k))_i = 0$ holds for all $i \in N$.

Now we will show that the **symmetry** property holds. The value to player i' is:

$$T\sigma^{-1}(MFI(\mathbf{x}; k))_{i'} = \sum_{S' \subseteq N-i'} [F(S'+i') - F(S')] \prod_{j \in S'} x_j \prod_{j' \in N-S'-i} (1 - x_{j'}) \tag{37}$$

Now let us compare different terms in the summands of Eq. (36) and Eq. (37). We try to match the summands one by one. There are two situations:

Situation I: For any $S \subseteq N - i - i'$, we choose $S' = S$.

In this case we have $F(S + i) - F(S) = F(S' + i') - F(S')$. For the products of $\mathbf{x}$ we have:

$$\prod_{j \in S} x_j \prod_{j' \in N-S-i} (1 - x_{j'}) - \prod_{j \in S'} x_j \prod_{j' \in N-S'-i} (1 - x_{j'}) = \tag{38}$$

$$\prod_{j \in S} x_j \prod_{j' \in N-S-i-i'} (1 - x_{j'})[(1 - x_{i'}) - (1 - x_i)] \tag{39}$$

We know that $x_{i'} = x_i$ holds from step 0, by simple induction, we know that $x_{i'} = x_i$ holds for step k as well. So in this situation, the summands equal to each other.

Situation II: For any $S = A + i'$, we choose $S' = A + i$, where $A \subseteq N - i - i'$. In this case, it still holds that $F(S + i) - F(S) = F(S' + i') - F(S')$. For the products of $\mathbf{x}$ we have:

$$\prod_{j \in S} x_j \prod_{j' \in N-S-i} (1 - x_{j'}) - \prod_{j \in S'} x_j \prod_{j' \in N-S'-i'} (1 - x_{j'}) = \tag{40}$$

$$\prod_{j \in A} x_j \prod_{j' \in N-A-i-i'} (1 - x_{j'})[x_{i'} - x_i]. \tag{41}$$

Again, by the simple induction, we know that $x_{i'} = x_i$ holds for step k.

The above two situations finishes the proof of symmetry.

For the **marginalisim** axiom, one can see that the update step for the two games are identical, and it is easy to deduce that they produce exactly the same trajectories, given that they have the same initializations.

$\square$

Figure 4: Comparison of different importance measures for FLID games. Hidden dimensions: First column D=4, second column D=8. n denotes # of players. Vertical lines means (marginals - 0.5) since we would like to clearly show positive players (marginal > 0.5) and negative players (marginal < 0.5).

F   MORE CONFIGURATION DETAILS AND EXPERIMENTAL RESULTS

F.1   SYNTHETIC EXPERIMENTS ON SUBMODULAR (FLID) GAMES

Here we define a synthetic game with the value function as a FLID (Tschiatschek et al., 2016) objective $F(S)$, which is a diversity boosting model satisfying the submodularity property. We know that its multilinear extension admits polynomial time algorithms (Bian et al., 2019). Let $\mathbf{W} \in \mathbb{R}_{+}^{|N| \times D}$ be the weights, each row corresponds to the latent representation of an item, with D as the dimensionality. Then

$$F(S) := \sum_{i \in S} u_i + \sum_{d=1}^{D} (\max_{i \in S} W_{i,d} - \sum_{i \in S} W_{i,d}) = \sum_{i \in S} u_i' + \sum_{d=1}^{D} \max_{i \in S} W_{i,d}, \quad (42)$$

which models both coverage and diversity, and $u_i' = u_i - \sum_{d=1}^{D} W_{i,d}$. In order to test the performance of the proposed variational objectives, we consider small synthetic games with 6, 8 and 10 players such that the ground truth marginals can be computed exhaustively. We would like to compare with the true marginals $p(i \in \mathbf{S})$ since they represent the probability that player i participates in all coalitions, which is hard to compute in general. The distance to the true marginals is also a natural measure of the decoupling error as defined in Def. 1. We apply a sigmoid function to Shapley value and Banzhaf index in order to translate them to probabilities. We calculate the mean squared error (MSE) and Spearman's rank correlation (ρ) to the ground truth marginals $p(i \in \mathbf{S})$ and report them in the figure legend. Fig. 4 collects the figures, one can see that the Variational Index clearly obtains better performance in terms of MSE and Spearman's rank correlation compared to the one-point solutions (Shapley value and Banzhaf index) in all experiments.

F.2   DETAILS OF THE MODELS FOR FEATURE VALUATIONS

For xgboost, the train accuracy is 0.8934307914376094, the specific configuration with the xgboost package is:

```
XGBClassifier(base_score=0.5, booster='gbtree', colsample_bylevel=1,
            colsample_bynode=1, colsample_bytree=1, gamma=0, gpu_id=-1,
            importance_type='gain', interaction_constraints='',
            learning_rate=0.300000012, max_delta_step=0, max_depth=6,
            min_child_weight=1, missing=nan, monotone_constraints='()',
            n_estimators=100, n_jobs=56, num_parallel_tree=1,
            random_state=0, reg_alpha=0, reg_lambda=1,
            scale_pos_weight=1, subsample=1, tree_method='exact',
            validate_parameters=1, verbosity=None)
```

We used the sklearn package for the logistic regression and MLP classifiers. For logistic regression, the accuracy is 0.8418967476428857, the specific configuration is:

```
LogisticRegression(random_state=0, solver="liblinear", C=0.5)
```

For the MLP, its accuracy is 0.8614600288688923, and the configuration is:

```
MLPClassifier(random_state=0, max_iter=300,
            learning_rate_init=0.002,
            hidden_layer_sizes=(50,50))
```

F.3   MORE RESULTS ON FEATURE VALUATIONS

In this part we provide more results on feature removal in Figures 5 and 6. Fig. 5 shows similar behavior as that shown in the main text. Fig. 6 provides not very distinguishable results of the three criteria.

F.4   MORE AVERAGE RESULTS ON FEATURE VALUATIONS

We provide additional statistical results with the MLP model (Fig. 8) and logistic regression model (Fig. 9). Meanwhile, we also put the full statistics on the xgboost model in Fig. 7 since in the main

Figure 5: First column: Change of predicted probabilities when removing features. The *decoupling error* is included in the legend. Last three columns: waterfall plots of feature importance from Variational Index, Shapley and Banzhaf.

Figure 6: Not very distinguishable results. First column: Change of predicted probabilities when removing features. The *decoupling error* is included in the legend. Last three columns: waterfall plots of feature importance from Variational Index, Shapley and Banzhaf.

text the table of the samples with "False" grouthtruth label is skipped due to space limit. From Fig. 8 one can observe that Variational Index induces different rankings of the features compared to Shapley and Banzhaf: Variational Index ranks "Marital Status" the second, while Shapley and Banzhaf put it in the third location.

It is also very interesting to see that the logistic regression model (with the lowest training accuracy among the three models, shown in Fig. 9) provides different ranking for the first two features compared to MLP and xgboost. For the samples with "True" groundtruth labels, "Education-Num" is the first important feature for the logistic regression model, while "Captical Gain" was ranked first for the MLP and xgboost.

GT Labels: True	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Capital Gain	Relationship	Age	Education-Num	Occupation	Marital Status	Capital Loss	Hours per week	Sex	Race	Workclass	Country
Shapley	Capital Gain	Relationship	Education-Num	Age	Occupation	Marital Status	Hours per week	Capital Loss	Sex	Workclass	Race	Country
Banzhaf	Capital Gain	Relationship	Education-Num	Age	Occupation	Marital Status	Capital Loss	Hours per week	Sex	Race	Workclass	Country

GT Labels: False	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Capital Gain	Relationship	Age	Education-Num	Occupation	Marital Status	Capital Loss	Hours per week	Sex	Race	Workclass	Country
Shapley	Capital Gain	Relationship	Capital Loss	Age	Education-Num	Marital Status	Hours per week	Occupation	Work class	Country	Race	Sex
Banzhaf	Capital Gain	Relationship	Capital Loss	Age	Education-Num	Marital Status	Hours per week	Occupation	Work class	Country	Race	Sex

Figure 7: Full statistics on valuations with the *xgboost* classifier (in the main text the last row is skipped due to space limit). First row: box plot of valuations returned by the three criteria. We always consider the predicted probability of the ground truth label. "True" means the samples with positive ground truth label and "False" means with the negative ground truth label. Second and third rows: Average ranking of the 12 features. Colored texts denote different rankings among the three criteria.

F.5 EXPERIMENTS WITH MORE PLAYERS

Furthermore, we experiment with a bit larger number of players ($n = 80$) using MCMC sampling to approximate the partial derivative in Eq. (13). The sampling based approximation works pretty fast. Table 2 shows the top 15 ranked players returned by our method, Shapley value and Banzhaf value for a synthetic data valuation problem. Note that the ranking of Variational Index is more similar to that of Banzhaf index than that of Shapley value.

Table 2: Indices of the top 15 ranked players returned by different methods.

Rank of players	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Variational Index	9	13	11	3	54	7	18	36	32	42	46	40	6	18	23
Banzhaf Index	9	13	11	3	54	18	7	32	46	36	2	27	40	17	10
Shaplay Value	52	33	27	1	4	58	32	14	42	46	40	6	18	23	47

GT Labels: True	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Capital Gain	Marital Status	Education-Num	Relationship	Age	Hours per week	Occupation	Capital Loss	Sex	Country	Race	Workclass
Shapley	Capital Gain	Education-Num	Marital Status	Relationship	Age	Hours per week	Occupation	Sex	Capital Loss	Race	Country	Workclass
Banzhaf	Capital Gain	Education-Num	Marital Status	Relationship	Age	Hours per week	Occupation	Sex	Capital Loss	Race	Country	Workclass

GT Labels: False	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Capital Gain	Relationship	Education-Num	Capital Loss	Age	Marital Status	Hours per week	Sex	Occupation	Country	Workclass	Race
Shapley	Capital Gain	Relationship	Education-Num	Capital Loss	Marital Status	Age	Hours per week	Sex	Occupation	Workclass	Country	Race
Banzhaf	Capital Gain	Relationship	Capital Loss	Marital Status	Education-Num	Age	Hours per week	Sex	Occupation	Workclass	Country	Race

Figure 8: Statistics on valuations with the *MLP* classifier. First row: box plot of valuations returned by the three criteria. We always consider the predicted probability of the ground truth label. "True" means the samples with positive ground truth label and "False" means with the negative ground truth label. Second and third rows: Average ranking of the 12 features. Colored texts denote different rankings among the three criteria.

GT Labels: True	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Education-Num	Relationship	Capital Gain	Hours per week	Marital Status	Age	Sex	Capital Loss	Race	Occupation	Country	Workclass
Shapley	Education-Num	Capital Gain	Relationship	Hours per week	Marital Status	Age	Sex	Occupation	Race	Capital Loss	Country	Workclass
Banzhaf	Education-Num	Capital Gain	Relationship	Hours per week	Marital Status	Age	Sex	Occupation	Race	Capital Loss	Country	Workclass

GT Labels: False	1	2	3	4	5	6	7	8	9	10	11	12
Var. Index	Relationship	Capital Gain	Education-Num	Capital Loss	Age	Hours per week	Marital Status	Sex	Workclass	Race	Occupation	Country
Shapley	Relationship	Capital Gain	Education-Num	Capital Loss	Age	Hours per week	Marital Status	Sex	Workclass	Occupation	Race	Country
Banzhaf	Relationship	Capital Gain	Education-Num	Capital Loss	Age	Hours per week	Marital Status	Sex	Workclass	Occupation	Race	Country

Figure 9: Statistics on valuations with the *logistic regression* classifier. First row: box plot of valuations returned by the three criteria. We always consider the predicted probability of the ground truth label. "True" means the samples with positive ground truth label and "False" means with the negative ground truth label. Second and Third rows: Average ranking of the 12 features. Colored texts denote different rankings among the three criteria.