Time Discretization-Invariant
Safe Action Repetition for Policy Gradient Methods

Abstract

In reinforcement learning, continuous-time is often discretized by a discretization time scale δ, to which the resulting performance is known to be highly sensitive. In this work, we seek to find a δ-*invariant* algorithm for policy gradient (PG) methods, which performs well regardless of the choice of δ. We first identify the underlying reasons that cause PG methods to fail as $\delta \rightarrow 0$, proving that the variance of the PG estimator can diverge to infinity in stochastic environments. While durative actions or action repetition can be employed to have δ-invariance, previous action repetition methods cannot immediately react to unexpected situations in stochastic environments. We thus propose a novel δ-invariant method named *Safe Action Repetition (SAR)* applicable to any existing PG algorithms. SAR can handle the stochasticity of environments by adaptively reacting to changes in states during action repetition. We empirically show that our method is not only δ-invariant but also robust to stochasticity, outperforming previous δ-invariant approaches on eight MuJoCo environments with both deterministic and stochastic settings.

1 Introduction

Deep reinforcement learning (RL) has demonstrated phenomenal achievements in a wide array of tasks, including superhuman game-playing [19, 27] and controlling complex robots [8, 13]. Most RL algorithms assume a Markov Decision Process (MDP), which is a discrete-time control process for the iteration of observing a state and performing an action. However, numerous real-world problems such as robotic manipulation and autonomous driving are defined with continuous-time, which does not directly fit the MDP assumption. To fill this gap, the continuous-time is often discretized by a *discretization time scale δ*, where the RL agent makes a decision at every δ. It has been shown that RL algorithms are greatly sensitive to this hyperparameter [1, 35]. For instance, altering δ via frame skipping leads to drastic performance differences [1, 4]. Indeed, an excessively high δ precludes the agent from making fine-grained decisions, which is likely to cause performance degradation.

On average, the agent could perform equally well or better with a lower δ than with a higher δ, since the agent makes decisions more frequently. However, Baird [2] and Tallec et al. [35] theoretically proved that the standard Q-learning fails when $\delta \rightarrow 0$ as the action-value (Q) function collapses to the state-value (V) function eliminating preferences between actions. As will be shown in Section 4.1, policy gradient (PG) methods fail as well with an infinitesimal δ for the following three reasons: (1) The variance of the gradient estimator explodes. (2) Exploration range may become highly limited. (3) Infinitely many decision steps are required. The latter two also apply to Q-learning methods.

Therefore, it is generally required to differently set appropriate δ for different continuous environments. Indeed, continuous control environments in MuJoCo [36] have different discretization time scales from one another, ranging from 0.008s (Hopper) to 0.05s (InvertedDoublePendulum). However, such tuning of δ could be burdensome when applying RL algorithms to new environments, considering

its significant influence on the performance [1, 35]. Furthermore, even if the optimal δ is found in simulation, the trained policies may not be transferable to real-world settings, since physical sensors often have their unique sampling frequencies.

There have been proposed some methods for robustness to discretization of time scales. δ-invariant methods could bring several advantages: (1) It obviates the need for tuning δ on each continuous control environment. (2) They can achieve better performance by utilizing more fine-grained control with a low δ. (3) Using a policy with adaptive decision frequencies (as a variant of δ-invariant policies), the agent can efficiently take actions only when it is necessary, which could expedite training without losing its agility. Tallec et al. [35] introduced an algorithm based on Advantage Updating [2], which can make existing Q-learning methods (*e.g.* DQN [18] and DDPG [16]) invariant to δ by preventing the collapse of the Q function. For PG methods, Munos [21] and Wawrzynski [37] proposed methods that can cope with fine time discretization. However, these methods either assume the access to the gradient of the reward function or require an infinite number of decision steps (or training steps) when $\delta \rightarrow 0$, both of which could hinder its application to real-world environments.

We aim at proposing an efficient δ-invariant approach applicable to existing PG methods such as PPO [30], TRPO [28] and A2C [20]. One straightforward approach may be to take *durative actions* by making policies produce both *actions* and their *durations*. Such an approach is practically equivalent to prior work on *action repetition* whose policies output both actions and the number of action repetitions [15, 31], since continuous control environments such as MuJoCo often already provide discretized time scales. However, the prior approaches on action repetition possess some limitations. For example, there is no way to stop repeating a chosen action during the repetition period, which means that they are not capable of immediately handling unexpected events in stochastic environments. This could lead to catastrophic failures in some real-world settings such as autonomous driving.

We thus propose an alternative approach named *Safe Action Repetition* (SAR) with the key idea of repeating an action until the agent exits its *safe region*. Our policy produces both an *action* and a *safe region* in the state space only within which the chosen action is repeated. SAR enables any PG algorithms to be not only δ-invariant but also robust to stochasticity such as unexpected events in the environment, because such situations lead the agent's state to be outside the safe region, immediately causing the cease of the current action. We apply the proposed method to several PG algorithms and empirically show that SAR indeed exhibits its δ-invariance on various MuJoCo environments and outperforms baselines on both deterministic and stochastic settings.

Our contributions can be summarized as follows:

- We first provide a more general proof on the variance explosion of the PG estimator, which is the main reason why PG methods fail as $\delta \rightarrow 0$. We then show that temporally extended actions can resolve the failure mode of PG algorithms with a low δ.

- We introduce a novel δ-invariant method named SAR applicable to any PG methods on continuous control domains. To the best of our knowledge, this is the first action repetition (or durative action) method that repeats an action based on the agent's *state*, rather than a precomputed action duration. As a result, SAR can cope with unexpected situations in stochastic environments, which existing action repetition methods cannot handle.

- We apply SAR to three PG methods, PPO, TRPO and A2C, and empirically demonstrate that our SAR method is mostly invariant to δ on eight MuJoCo environments. We also verify its robustness to stochasticity via three different stochastic settings on each MuJoCo environment. Our method also outperforms previous δ-invariant approaches such as FiGAR-C [31] and DAU [35] on these settings.

2 Related Work

Continuous-time RL. Reinforcement learning in continuous-time domains has long been studied with various approaches [2, 3, 5, 6, 7, 21, 22]. Bradtke and Duff [3] extended existing Q-learning and temporal difference methods to semi-MDPs, which can be viewed as a continuous-time generalization of MDPs. Doya [5] developed a continuous actor-critic method based on the Hamilton-Jacobi-Bellman (HJB) equation, a continuous-time counterpart of the Bellman equation, approximating policies and value functions with radial basis functions.

Time discretization. Another line of research to cope with continuous-time environments is to use finely discretized MDPs. Baird [2] first informally presented that when $\delta \to 0$, two different Q values on the same state will eventually collapse to the V value, such that $Q(s, a_1) \approx Q(s, a_2) \approx V(s)$, since the influence of each action is vanished by the infinitesimal time scale. They proposed *Advantage Updating* as a solution to avoid the collapse by appropriately scaling the advantage function $A(s, a) = \frac{Q(s,a) - V(s)}{\delta}$. More recently, Tallec et al. [35] theoretically proved the existence of collapse in low-δ settings and extended Advantage Updating with deep neural networks, showing its δ-invariance on classic control benchmarks. For PG methods, Munos [21] first demonstrated that the variance of the policy gradient estimate can be infinite when $\delta \to 0$, and proposed an algorithm based on pathwise derivatives, in which the variance of the estimator decreases to 0 when $\delta \to 0$. However, it assumes that the gradient of the reward function $\nabla r(s, a)$ is known to the agent. Korenkevych et al. [14], Wawrzynski [37] proposed methods based on autocorrelated noise that could prevent the variance explosion. Notably, all of these approaches choose an action at every δ. However, this makes it infeasible to train when δ is nearly zero as the number of decision steps goes to infinity. In this work, we employ durative actions to possess δ-invariance with PG methods, which could resolve the problem of the variance explosion and infinite decision steps.

Action repetition. Our proposed method is closely related to existing action repetition methods. Most works on action repetition let the policy also determine how many times (or how long) an action is repeated. DFDQN [15] doubled the action space by mapping a half of it to actions repeated r_1 times and the other half to those repeated r_2 times, where r_1 and r_2 are fixed hyperparameters. FiGAR [31] introduced a repetition policy $\pi(x|s)$ in addition to the original action policy $\pi(a|s)$ so that the agent repeats the action a, x times, where x is selected from a predefined set W, *e.g.* $W = \{1, 2, \dots, 30\}$. Metelli et al. [17] theoretically analyzed the performance of the optimal policy when a fixed action repetition count is given, and proposed a heuristic to approximately choose the optimal control frequency. On the other hand, we take a completely different approach where our policy produces not repetition counts (or action durations) but *safe regions*, which enables the agent to adaptively stop action repetition when facing unexpected events in stochastic environments.

3 Preliminaries

We consider a continuous-time MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, r, F, \gamma)$ [3, 5], where $\mathcal{S}$ is a continuous state space, $\mathcal{A}$ is a bounded action space, $F \colon \mathcal{S} \times \mathcal{A} \to \mathcal{S}$ is a transition dynamics function, $r \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a reward function and $\gamma \in (0, 1]$ is a discount factor. For simplicity, we assume the environment has deterministic transition dynamics; we refer to Munos and Bourgine [22] for the stochastic case involving Brownian motion. The transition dynamics and the return $R(\tau)$ are given as

$$s(t) = s(0) + \int_0^t F(s(t'), a(t'))dt', \quad R(\tau) = \int_0^\infty \gamma^{t'} r(s(t'), a(t'))dt', \tag{1}$$

where $s(t)$ and $a(t)$ respectively denote the state and action at time t, and τ stands for the whole trajectory consisting of states and actions.

Following Tallec et al. [35], we define a discretized version of $\mathcal{M}$ as $\mathcal{M}_\delta = (\mathcal{S}, \mathcal{A}, r_\delta, F_\delta, \gamma_\delta)$ with a *discretization time scale* $\delta > 0$, where the agent observes a state and performs an action at every δ. We respectively denote the state and action at i-th step as s_i and a_i, where s_i in $\mathcal{M}_\delta$ corresponds to $s(i\delta)$ in $\mathcal{M}$ and a_i is maintained during the time interval $[i\delta, (i + 1)\delta]$. In $s(t)$, t indicates the *physical* time, and i in s_i is the number of steps taken. The reward r_i and return $R_\delta(\tau)$ are defined as

$$r_i = r_\delta(s_i, a_i) = r(s(i\delta), a(i\delta))\delta, \quad R_\delta(\tau) = \sum_{i=0}^\infty \gamma_\delta^i r_i, \tag{2}$$

where the discount factor is $\gamma_\delta = \gamma^\delta$. Given a deterministic policy $\pi \colon \mathcal{S} \to \mathcal{A}$, the continuous value function $V^\pi(s)$ and the discretized one V_δ^π are defined as $V^\pi(s) = \mathbb{E}_{\tau \sim p_\pi(\tau)}[R(\tau)|s(0) = s]$ and $V_\delta^\pi(s) = \mathbb{E}_{\tau \sim p_\pi(\tau)}[R_\delta(\tau)|s_0 = s]$. Tallec et al. [35] proved that V_δ^π converges to V^π when $\delta \to 0$ under smoothness assumptions.

In the rest of the paper, we will focus on $\mathcal{M}_\delta$ (*i.e.* $\mathcal{M}$ with time discretization) and omit the subscript δ unless it is necessary. Also, as in ordinary discrete-time MDPs [34], we consider stochastic transition dynamics $p(s_{i+1}|s_i, a_i)$ and stochastic policy $\pi(a_i|s_i)$ instead of deterministic ones.

4 Safe Action Repetition

We first show that $\delta \to 0$ leads to a failure in policy gradient (PG) methods (Section 4.1), and propose that durative actions or action repetition can be a solution for the failure mode. We then point out that existing action repetition methods have drawbacks in the presence of unexpected events in stochastic environments (Section 4.2). As a solution, we propose *Safe Action Repetition* (SAR) as a novel δ-invariant approach for PG algorithms, which is robust to such stochasticity (Section 4.3). We additionally suggest a variant of SAR to deal with non-Markovian environments (Section 4.4).

4.1 Policy Gradients with Infinitesimal Discretization of Time Scale

A smaller discretization time scale should not lead to worse maximum returns on average, since it allows the agent to perform more fine-grained actions. However, both Q-learning and PG methods are subjected to fail with a too small δ. We introduce three reasons why PG methods fail. We refer to Baird [2], Tallec et al. [35] for further discussion on Q-learning methods.

Variance explosion of the policy gradient estimator. We show that the variance of the PG estimator can diverge to infinity with decrease in δ. While this was first shown in Munos [21] via a simple illustrative example, we provide a more general proof without assuming a particular environment. Specifically, we prove that the variance explosion problem can arise in any stochastic environment where the variance of its return conditioned on actions is greater than a small positive constant.

Let us consider a stochastic environment that has a finite physical time limit T and a discretization time scale δ. It follows that the number of decision steps (or actions) in a single rollout is $N = T/\delta$. Let the policy $\pi_\theta(a_i|s_i)$ be parameterized by θ, the distribution over trajectories $\tau = (s_0, a_0, \ldots, s_N)$ be given as $p_\theta(\tau) = p(s_0) \prod_{i=0}^{N-1} \pi_\theta(a_i|s_i) p(s_{i+1}|s_i, a_i)$ and $p_\theta(s_{0:N})$ denote its state-marginal distribution. For simplicity, we assume that the policy is represented as a multivariate normal distribution with a learnable diagonal covariance matrix: $\pi_\theta(a_i|s_i) \sim \mathcal{N}(\mu_{\theta_\mu}(s_i), \Sigma)$ where the mean $\mu_{\theta_\mu}(s_i) = [\mu_{\theta_\mu,1}(s_i), \ldots, \mu_{\theta_\mu,K}(s_i)]^\top$ is modeled by a neural network, $\Sigma = \text{diag}(\sigma_1^2, \ldots, \sigma_K^2)$ is the learnable variance that is independent of states (as in the original TRPO [28] and PPO [30]). Thus, $\theta = [\theta_\mu^\top, \sigma_1, \ldots, \sigma_K]^\top$ is the whole parameters of the policy π_θ, and $K = \dim(\mathcal{A})$.

The derivative of the RL objective function $J(\theta) = \mathbb{E}_{\tau \sim p_\theta(\tau)}[R(\tau)]$ can be written as

$$\nabla_\theta J(\theta) = \mathbb{E}_{\tau \sim p_\theta(\tau)} \left[\left(\sum_{i=0}^{N-1} \nabla_\theta \log \pi_\theta(a_i|s_i) \right) R(\tau) \right] \triangleq \mathbb{E}_{\tau \sim p_\theta(\tau)}[G_\theta(\tau)], \tag{3}$$

which is often referred to as the *policy gradient estimator*.

We derive a lower bound for its total variation $\text{tr}[\mathbb{V}_{\tau \sim p_\theta(\tau)}[G_\theta(\tau)]]$, where $\mathbb{V}[X]$ is the variance of a variable X (or the covariance matrix when X is multidimensional), and tr is the trace operator.

Theorem 1 *If the environment is stochastic such that for any reparameterized actions $\epsilon_{0:N-1}$, the variance of returns conditioned on the actions is lower bounded by a small positive constant c (i.e.*

$$\mathbb{V}_{s_{0:N} \sim p_\theta(s_{0:N}|\epsilon_{0:N-1})}[R(\tau)] \geq c > 0 \text{ where } a_i = \mu_{\theta_\mu}(s_i) + \Sigma \epsilon_i \text{ and } \epsilon_i \overset{i.i.d.}{\sim} \mathcal{N}(0, I)), \text{ it holds that}$$

$$\text{tr}\left[\mathbb{V}_{\tau \sim p_\theta(\tau)}[G_\theta(\tau)]\right] \geq \frac{Tc}{\delta \sigma_1^2}. \tag{4}$$

We provide the full proof and further discussion in Appendix. Equation (4) indicates that $\delta \to 0$ can lead the variance of the PG estimator to explode, especially in stochastic environments. We emphasize that the two primary causes of this explosion are the independence of actions and the infinitely growing number of decision steps, both of which correspond to Equation (22) $\to$ (23) in Appendix. Practically, existing PG algorithms are implemented with standard variance reduction techniques such as reward-to-go policy gradient and baseline functions. However, even if such variance reduction is applied, the variance of the PG estimator is still likely to explode as $\delta \to 0$ considering the environment's stochasticity, if the learning rate and minibatch size remain the same.

Challenging exploration. Furthermore, existing PG methods are prone to perform worse with a low δ due to the difficulty of exploration. An example in Figure 1 compares 2-D random walks of the same physical time limit with different δ's. It is easier to get out of the blue box by chance with a high δ than a low δ. Intuitively, when $\delta \to 0$, the range that the agent can move at each step becomes smaller, which makes it challenging to reach distant states by pure exploration.

This originates again from independently sampled actions. We provide a more formal explanation in Appendix. This exploration problem has also been addressed in Q-learning literature [16, 35], which employs as a remedy autocorrelated noise such as an Ornstein-Uhlenbeck process.

(a) Low δ (b) High δ

Infinite decision steps. For a given time limit, the number of decision steps is inversely proportional to δ. This makes the size of the training data required for consuming the same number of episodes increase infinitely as $\delta \to 0$, and thereby impedes the training in terms of the computational cost.

Figure 1: An example of 2-D random walks having the same physical time limit with different δ's.

4.2 Durative Actions in Previous Works

For the aforementioned problems with PG methods given a low δ, *durative actions* can be a solution; that is, the policy does not decide an action at every δ but does only when it is necessary. With durative actions, (1) it naturally makes (δ-discretized) actions correlated with one another, and (2) it does not always require infinitely many decision steps even if $\delta \to 0$.

For durative actions, one may modify existing policies to produce both action a and its duration t. In discretized continuous-time environments, this approach is practically equivalent to prior methods that produce repetition counts [15, 31], as continuous durations should be converted into the repetitions of time-discretized actions. As one of such action repetition methods, FiGAR-A3C [31] defines the policy as $\pi(a, x|s)$ where $a \in \mathcal{A}$ and $x \in W$. W is a predefined set of action repetition counts, *e.g.* $W = \{1, 2, \ldots, 30\}$. At every decision step, FiGAR-A3C samples action a_i and repetition count x_i from the policy, and then performs the action x_i times, where i denotes the i-th *decision* step. It defines the n-step return $\hat{V}^{(n)}(s_i)$ as

$$\hat{V}^{(n)}(s_i) = \sum_{k=0}^{n-1} \gamma^{y_{i+k} - y_i} r_{i+k} + \gamma^{y_{i+n} - y_i} V(s_{i+n}), \tag{5}$$

where the cumulative repetition counts $\{y_i\}$ is defined as $y_0 = 0$ and $y_{i+1} = y_i + x_i$ for $i \geq 0$. The reward r_i at the i-th *decision* step is given as the discounted sum of environment rewards over the holding time. While FiGAR-A3C is based on the standard procedure of A3C [20], it is too applicable to other RL algorithms such as TRPO [28] and DDPG [16].

FiGAR can be naturally extended to its continuous variant, which we call FiGAR-C, by replacing $\pi(a, x|s)$ with $\pi(a, t|s)$ where $t \in [0, t_{\max}]$ stands for the *duration* of the action a. In δ-discretized environments, it translates the action duration t into $\lceil \frac{t}{\delta} \rceil$ times of repetition. FiGAR-C is inherently δ-invariant since it operates on the unit of physical time instead of the discretized time scale.

However, these approaches for durations of actions possess two limitations. First, since it does not consider stopping an action during repetition, it can not immediately react to unexpected events while repeating an action for t. This may lead to poor performance in stochastic environments. Second, in contrast to the fact that the optimal policy $\pi(a|s)$ for a fully observable MDP only depends on the state s, not the time t [34], previous methods *only* consider the locality of the time variable t, without caring underlying changes in s. This discrepancy can lead to degradation in performance, since even during a small time period, s can vary greatly in the environments with stochastic or non-continuous dynamics. In the next section, we will demonstrate that such limitations can still bring back the variance explosion problem in these action repetition approaches.

4.3 Safe Action Repetition

We propose an alternative approach named *Safe Action Repetition* (SAR) that resolves the limitations of existing action repetition methods. SAR repeats actions based on the locality of *states*, taking the same action only when states are close.

Following [32], we define a *perturbation set* for a state $s \in \mathcal{S}$ as $\mathbb{B}_\Delta(s, d) = \{s' | \Delta(s, s') \leq d\}$, which corresponds to the closed ball of radius d centered at s using the metric Δ in the state space. Employing the notion of perturbation sets, we propose the following action repetition scheme. At every decision step, SAR's policy $\pi(a_i, d_i|s_i)$ produces both action a_i and the radius d_i of a perturbation set, which we call the *safe region*. Then, SAR repeats the action a_i only within the safe

region $\mathbb{B}_\Delta(s_i, d_i)$, or equivalently

$$\Delta(s, s_i) \le d_i, \tag{6}$$

where s denotes the current state during the repetition. Once the agent goes outside the safe region, SAR stops the action repetition and selects a new action.

Having the durations of actions thresholded by Equation (6) grants two advantages. First, it naturally ensures δ-invariance, since its action duration, which is determined by the radius of a safe region, has no relation with how fine the discretization time scale is. Equation (6) is even completely agnostic to the physical time variable t and how it is scaled. Second, the agent becomes robust to stochasticity, *e.g.* encountering an unpredicted event, because such a situation would push the agent's state far away from the safe region, which immediately stops the action repetition.

To intuitively differentiate SAR with previous action repetition methods, we illustrate a simple example of a stochastic environment, where previous FiGAR-C fails to maintain the optimal policy due to the variance explosion of the PG estimator, while our method does not. Let us consider the following δ-discretized environment named *AlertThenOff*, whose physical time limit T is 1. The state is $s \in \{0 \text{ (normal)}, 1 \text{ (alerted)}\}$ with $s_0 =$

Figure 2: Illustration of *AlertThenOff* environment.

0 (normal). The 2-D action is $a = [\text{off}, \text{num}]^\top$ where $\text{off} \in \{0, 1\}$ and $\text{num} \in \mathbb{R}$. In this environment, s randomly changes once from 0 (normal) to 1 (alerted) at time $t \in [0, 1]$. When $s = 1$ (alerted), we should take an action of $\text{off} = 1$ within $[t, t + x]$ so that s can be back to 0 (normal), where $x > \delta > 0$ is an environment parameter known to us. Otherwise, the environment produces a penalty reward of $-\nu$ (a large negative number) and ends immediately. Conversely, if we set $\text{off} = 1$ when $s = 0$ (normal), it also causes a penalty of $-\nu$ and ends immediately. We illustrate this in Figure 2. The reward (before discretization) is given as $r(t) = f(\text{num})$, where f is an unknown reward function, and its discretized reward is given accordingly to Equation (2). When the time reaches $t = 1$, a noisy reward of $\xi \sim \mathcal{N}(0, 1)$ occurs. To sum up, we should perform $\text{off} = 1$ as soon as possible only when we get to know that s becomes 1 (alerted), while we should also perform good num actions to maximize $f(\text{num})$.

To find the optimal policy in this environment, we consider a deterministic policy for off that $\pi^{\text{off}}(s) = s$, which we already know is optimal, and a stochastic policy for num that $\pi^{\text{num}}(\text{num}|s) \sim \mathcal{N}(\mu, 1)$, where μ is the policy's parameter. Our goal is thus to find the optimal value of μ.

Proposition 2 *In AlertThenOff environment, for the optimal policy π_{θ_f} for FiGAR-C and the optimal policy π_{θ_s} for SAR, the following holds:*

$$\text{tr}\left[\mathbb{V}_{\tau \sim p_{\theta_f}(\tau)}[G_{\theta_f}(\tau)]\right] \to \infty, \quad \text{tr}\left[\mathbb{V}_{\tau \sim p_{\theta_s}(\tau)}[G_{\theta_s}(\tau)]\right] = 2, \tag{7}$$

when $\delta \to 0$, $x \to 0$, $\nu \to \infty$ and $f \equiv 0$.

We provide the full proof in Appendix. From Proposition 2, we can conclude that in contrast to FiGAR-C, our SAR policy does not suffer from the variance explosion in *AlertThenOff* environment. As the previous approach fails to maintain the optimal policy even in this very simple stochastic environment, it can be also at risk of failure in general stochastic environments. The intuition behind this failure is that they have no choice but to infinitely shorten action durations in order to optimally handle the stochasticity that requires immediate reactions from the agent, which leads both the number of decision steps and the variance of the policy gradient to explode. On the other hand, SAR can be free from the variance explosion despite such stochasticity, if SAR sets safe regions so that such an exigent state locates outside the safe regions, and thereby the number of decision steps can be finitely bounded.

4.4 SAR on Non-Markovian Environments

We derived SAR based on that the optimal policy in a fully observable MDP depends only on states. However, if the Markovian property does not hold (*e.g.* environments with partially observable MDPs

Figure 3: Training curves on deterministic MuJoCo environments with various δ's (ranging from $5e-4$ to $5e-2$). Shaded areas represent the 95% confidence intervals over eight runs. We compare SAR to FiGAR-C with two base PG algorithms, PPO and TRPO. SAR mostly has δ-invariance, showing similar or even better performance with lower δ's. We refer to Appendix for the full results.

[11] or time limits [23]), the optimal policy might not be fully determined by states alone. In this case, we can additionally incorporate temporal thresholds into SAR, by extending the definition of the safe region as follows:

$$\lambda \cdot \Delta(s, s_i) + (1 - \lambda)|t - t_i| \le d_i, \tag{8}$$

where t_i denotes the time at s_i and t denotes the current time during the repetition. $0 \le \lambda \le 1$ is the coefficient that controls the relative strength of the first term. Note that this variant of SAR, which we call λ-*SAR*, is δ-invariant too.

5 Experiments

We apply SAR to three policy gradient (PG) methods, PPO [30], TRPO [28] and A2C [20], and compare with baseline methods in multiple settings. We first demonstrate δ-invariance of our method on deterministic continuous control environments, comparing with previous δ-invariant algorithms (Section 5.1). We then evaluate SAR on stochastic environments to show its robustness to stochasticity (Section 5.2). We also provide illustrative examples for a better understanding of our method (Section 5.3). We describe the full experimental details in Appendix.

Experimental setup. We test on eight continuous control environments from MuJoCo [36]: InvertedPendulum-v2, InvertedDoublePendulum-v2, Hopper-v2, Walker2d-v2, HalfCheetah-v2, Ant-v2, Reacher-v2 and Swimmer-v2. We mainly compare our method to FiGAR-C described in Section 4.2, because it is the only prior method that is δ-invariant and does not always require infinite decision steps even if $\delta \to 0$. While other previous δ-invariant approaches either require access to the gradient of the reward function or are computationally demanding in lower-δ settings (Section 2), we additionally compare SAR to other methods in Section 5.1 and Appendix.

For SAR's distance function in Equation (6), we use $\Delta(s, s_i) = \|\tilde{s} - \tilde{s}_i\|_1 / \dim(\mathcal{S})$, where $\|\cdot\|_1$ is the ℓ_1 norm and $\tilde{s}$ is the state normalized by its moving average. This distance function corresponds to the average difference in each normalized state dimension, where the normalization permits sharing the hyperparameter $d_{\max}$ for all MuJoCo tasks. We also share $t_{\max}$ in FiGAR-C for all environments. Finally, we impose an upper limit of $t_{\max}$ on the maximum duration of actions in SAR for two reasons: (1) to further stabilize the training and (2) to ensure a fair comparison with FiGAR-C by setting the same limit on the duration.

5.1 Results on Deterministic Environments

We first train SAR and FiGAR-C with PPO, TRPO and A2C on the MuJoCo environments, which have deterministic transition dynamics (though they have randomized initial states), with various

Figure 4: Bar plots comparing the final performance of SAR-PPO to DAU's on deterministic MuJoCo environments with various δ's. Error bars represent the 95% confidence intervals over eight runs.

Figure 5: Training curves of SAR-PPO and FiGAR-C-PPO on MuJoCo environments with various types of stochasticity. Shaded areas represent the 95% confidence intervals over eight runs. SAR exhibits strong performance in the presence of stochasticity.

discretization time scales ranging from $5e-4$ to $5e-2$ (details in Appendix). We use suffixes such as '-PPO' to denote the base PG algorithms. Figure 3 shows the training curves of PPO and TRPO with SAR and with FiGAR-C on various MuJoCo environments, where the x and y axes denote the number of decision steps and the total reward, respectively. We provide the full results (including the result with A2C) and further comparison between SAR-PPO and PPO in Appendix. Figure 3 shows that while vanilla PG algorithms fail to maintain their performances in lower-δ settings, SAR is mostly robust to varying δ, often even achieving the best performance with the lowest δ. In a few environments such as Swimmer-v2, SAR's performance becomes slightly worse as δ decreases, which we hypothesize is because a higher δ aids the agent in getting out of local optima. Also, SAR exhibits similar or better performance compared to FiGAR-C on most deterministic environments.

For a more comprehensive evaluation, we additionally compare with DAU [35], which is another approach to δ-invariance for Q-learning methods such as DQN [18] and DDPG [16]. SAR-PPO and DAU have different underlying algorithms and training schemes. While DAU is based on DDPG and chooses an action at every environment step, SAR-PPO operates on PPO and makes action decisions only when needed. For the comparison, we use the official implementation of DAU [35]. Figure 4 compares the final performances of both methods with various δ's at the same physical time (equal to $1e6$ environment steps in the original δ) in each environment. Overall SAR-PPO outperforms DAU and exhibits better δ-invariance in most of the environments. Also, our method requires about $17.6\times$ fewer decision steps on average in the lowest-δ settings via temporally extended actions.

5.2 Results on Stochastic Environments

To demonstrate SAR's robustness with stochastic dynamics, we modify existing MuJoCo environments by adding various types of stochasticity. (1) "External Force": we apply an external force with a standard deviation of σ_{ext} to the agent's body with a probability of p_{ext} at each decision step. (2) "Strong External Force (Perceptible)": we make the external force perceptible by the agent, which allows it to react to stronger forces with $\sigma_{\text{ext2}} > \sigma_{\text{ext}}$. (3) "Action Noise": we apply noise with a

(a) InvertedPendulum-v2

(b) InvertedPendulum-v2 with external forces

Figure 6: Illustration of SAR on InvertedPendulum-v2 with $\delta = 2e - 3$. Our policy produces safe regions (rhombus) within which the agent repeats actions. Circle markers represent the *break points* of action repetitions and red fists represent the external forces applied to the agent.

standard deviation of σ_{act} to the action with a probability of p_{act} at each decision step. Throughout this experiment, we test with the lowest-δ settings. Figure 5 compares SAR-PPO's performance with FiGAR-C-PPO's, and shows that SAR outperforms FiGAR-C on most stochastic environments, often exhibiting drastic differences. We provide further details and the comparison with TRPO in Appendix.

5.3 Qualitative Analysis of SAR

In order to provide further insights on SAR, we illustrate how SAR works on InvertedPendulum-v2, where the goal is to maintain the balance of a pendulum. The state space consists of four dimensions: two for the position and the other two for the velocity, *i.e.* $s = [x_1, x_2, v_1, v_2]$. We demonstrate the behavior of SAR on a 2-D plane. For better interpretability, we slightly modify our method in this experiment: we use only the two (normalized) velocity dimensions for the distance function; that is, the agent stops action repetitions only by its velocity.

Figure 6a illustrates how a trained SAR model performs action repetition based on safe regions, where the x and y axes correspond respectively to v_1 and v_2, rhombuses represent safe regions, markers (either circle or cross) represent time-discretized states. It can be observed that our policy is learned to produce a large safe region when the agent's speed is low and, conversely, a small safe region when the speed is high, which fits with the intuition because the risk of losing the balance of the pendulum rises as the agent's speed increases. Additionally, we demonstrate how SAR operates in the presence of stochastic external forces (described in Section 5.2) in Figure 6b. It shows how SAR can quickly and adaptively handle such stochasticity with safe regions by immediately stopping repetitions.

6 Conclusion

We proposed Safe Action Repetition (SAR), a novel δ-invariant action repetition method for policy gradient (PG) algorithms. SAR can handle infinitesimal-δ settings using temporally extended actions without suffering from the variance explosion problem of PG methods, which we proved for general stochastic environments. It can agilely cope with the stochasticity of environments via learned safe regions. We exhibited that our method achieves both δ-invariance and robustness to stochasticity.

Limitations and future directions. We experimented with the ℓ_1 norm as SAR's distance function, which might not scale well to very high dimensional environments such as vision-based simulations. As such, we expect that combining our method with representation learning techniques [9, 10, 27] would be an interesting future research direction. Also, since SAR in Section 4.3 assumes fully observable MDPs so that it can exploit the locality of states, there is room for improvement in environments with noisy states or partially observable MDPs. Although we have suggested one possible solution in Section 4.4, this could also be the subject of future research.

References

[1] Marcin Andrychowicz, Anton Raichuk, Piotr Stańczyk, Manu Orsini, Sertan Girgin, Raphaël Marinier, Leonard Hussenot, Matthieu Geist, Olivier Pietquin, Marcin Michalski, Sylvain Gelly, and Olivier Bachem. What matters for on-policy deep actor-critic methods? a large-scale study. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=nIAxjsniDzg`.

[2] L. Baird. Reinforcement learning in continuous time: advantage updating. *Proceedings of 1994 IEEE International Conference on Neural Networks (ICNN'94)*, 4:2448–2453 vol.4, 1994.

[3] Steven J. Bradtke and M. O. Duff. Reinforcement learning methods for continuous-time markov decision problems. In *NIPS*, 1994.

[4] Alexander Braylan, Mark Hollenbeck, Elliot Meyerson, and R. Miikkulainen. Frame skip is a powerful parameter for learning to play atari. In *AAAI Workshop: Learning for General Competency in Video Games*, 2015.

[5] K. Doya. Reinforcement learning in continuous time and space. *Neural Computation*, 12: 219–245, 2000.

[6] Jianzhun Du, J. Futoma, and Finale Doshi-Velez. Model-based reinforcement learning for semi-markov decision processes with neural odes. *ArXiv*, abs/2006.16210, 2020.

[7] Nicolas Frémaux, H. Sprekeler, and W. Gerstner. Reinforcement learning using a continuous time actor-critic framework with spiking neurons. *PLoS Computational Biology*, 9, 2013.

[8] Shixiang Gu, Ethan Holly, T. Lillicrap, and S. Levine. Deep reinforcement learning for robotic manipulation with asynchronous off-policy updates. *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3389–3396, 2017.

[9] Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=S1lOTC4tDS`.

[10] Danijar Hafner, Timothy P Lillicrap, Mohammad Norouzi, and Jimmy Ba. Mastering atari with discrete world models. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=0oabwyZbOu`.

[11] M. Hausknecht and P. Stone. Deep recurrent q-learning for partially observable mdps. In *AAAI Fall Symposia*, 2015.

[12] Ashley Hill, Antonin Raffin, Maximilian Ernestus, Adam Gleave, Anssi Kanervisto, Rene Traore, Prafulla Dhariwal, Christopher Hesse, Oleg Klimov, Alex Nichol, Matthias Plappert, Alec Radford, John Schulman, Szymon Sidor, and Yuhuai Wu. Stable baselines. `https://github.com/hill-a/stable-baselines`, 2018.

[13] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, Eric Jang, Deirdre Quillen, Ethan Holly, Mrinal Kalakrishnan, V. Vanhoucke, and S. Levine. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *ArXiv*, abs/1806.10293, 2018.

[14] Dmytro Korenkevych, A. Mahmood, Gautham Vasan, and J. Bergstra. Autoregressive policies for continuous control deep reinforcement learning. In *IJCAI*, 2019.

[15] Aravind Lakshminarayanan, Sahil Sharma, and Balaraman Ravindran. Dynamic action repetition for deep reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2017.

[16] T. Lillicrap, Jonathan J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *CoRR*, abs/1509.02971, 2016.

[17] Alberto Maria Metelli, Flavio Mazzolini, L. Bisi, Luca Sabbioni, and Marcello Restelli. Control frequency adaptation via action persistence in batch reinforcement learning. In *ICML*, 2020.

[18] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, Ioannis Antonoglou, Daan Wierstra, and Martin A. Riedmiller. Playing atari with deep reinforcement learning. *ArXiv*, abs/1312.5602, 2013.

[19] V. Mnih, K. Kavukcuoglu, D. Silver, Andrei A. Rusu, J. Veness, Marc G. Bellemare, A. Graves, Martin A. Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, C. Beattie, A. Sadik, Ioannis Antonoglou, Helen King, D. Kumaran, Daan Wierstra, S. Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

[20] V. Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, A. Graves, T. Lillicrap, Tim Harley, D. Silver, and K. Kavukcuoglu. Asynchronous methods for deep reinforcement learning. *ArXiv*, abs/1602.01783, 2016.

[21] R. Munos. Policy gradient in continuous time. In *J. Mach. Learn. Res.*, 2005.

[22] R. Munos and P. Bourgine. Reinforcement learning for continuous stochastic control problems. In *NIPS*, 1997.

[23] Fabio Pardo, Arash Tavakoli, Vitaly Levdik, and Petar Kormushev. Time limits in reinforcement learning. In *International Conference on Machine Learning*, pages 4045–4054. PMLR, 2018.

[24] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, 2019.

[25] Antonin Raffin, Ashley Hill, Maximilian Ernestus, Adam Gleave, Anssi Kanervisto, and Noah Dormann. Stable baselines3. `https://github.com/DLR-RM/stable-baselines3`, 2019.

[26] R Tyrrell Rockafellar and Stanislav Uryasev. Conditional value-at-risk for general loss distributions. *Journal of banking & finance*, 26(7):1443–1471, 2002.

[27] Julian Schrittwieser, Ioannis Antonoglou, T. Hubert, K. Simonyan, L. Sifre, Simon Schmitt, A. Guez, Edward Lockhart, Demis Hassabis, T. Graepel, T. Lillicrap, and D. Silver. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588 7839:604–609, 2020.

[28] John Schulman, Sergey Levine, P. Abbeel, Michael I. Jordan, and P. Moritz. Trust region policy optimization. *ArXiv*, abs/1502.05477, 2015.

[29] John Schulman, P. Moritz, Sergey Levine, Michael I. Jordan, and P. Abbeel. High-dimensional continuous control using generalized advantage estimation. *CoRR*, abs/1506.02438, 2016.

[30] John Schulman, F. Wolski, Prafulla Dhariwal, A. Radford, and Oleg Klimov. Proximal policy optimization algorithms. *ArXiv*, abs/1707.06347, 2017.

[31] Sahil Sharma, Aravind S. Lakshminarayanan, and Balaraman Ravindran. Learning to repeat: Fine grained action repetition for deep reinforcement learning. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=B1GOWV5eg`.

[32] Qianli Shen, Yan Li, Haoming Jiang, Zhaoran Wang, and Tuo Zhao. Deep reinforcement learning with robust and smooth policy. In *International Conference on Machine Learning*, pages 8707–8718. PMLR, 2020.

[33] Rahul Singh, Qinsheng Zhang, and Yongxin Chen. Improving robustness via risk averse distributional reinforcement learning. In *Learning for Dynamics and Control*, pages 958–968. PMLR, 2020.

[34] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[35] C. Tallec, L. Blier, and Y. Ollivier. Making deep q-learning methods robust to time discretization. In *ICML*, 2019.

[36] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033, 2012.

[37] Pawel Wawrzynski. Control policy with autocorrelated noise in reinforcement learning for robotics. *International Journal of Machine Learning and Computing*, 5(2):91, 2015.