Synergistic Neuromorphic Federated Learning with ANN-SNN Conversion For Privacy Protection

Abstract

Federated Learning (FL) has been widely explored for the growing public data privacy issues, where only model parameters are communicated instead of private data. However, recent studies debunk the privacy protection of FL, showing that private data can be leaked from the communicated gradients or parameters updates. In this paper, we propose a framework called Synergistic Neuromorphic Federated Learning (SNFL) that enhances privacy during FL. Before uploading the updates of the client model, SNFL first converts clients' Artificial Neural Networks (ANNs) to Spiking Neural Networks (SNNs) via calibration algorithms. In a way that not only loses almost no accuracy but also encrypts the client model's parameters, SNFL manages to obtain a more performant model with high privacy. After aggregation of various SNNs parameters, server distributes the parameters back to clients to continue training under ANN architecture, providing smooth convergence. The proposed framework is demonstrated to be private, introducing a lightweight overhead as well as yielding prominent performance boosts. Extensive experiments with different kinds of datasets have demonstrated the efficacy and practicability of our method. In most of our experimental IID and not extreme Non-IID scenarios, the SNFL technique has significantly enhanced the model performance. For instance, SNFL improves the accuracy of FedAvg on Tiny-ImageNet by 13.79%. Also, the original image cannot be reconstructed after 280 iterations of attacks with the SNFL method, whereas it can be reconstructed after just 70 iterations with FedAvg.

1 Introduction

Recent advancements in machine learning, particularly deep learning, rely heavily on large data sets to obtain decent inference performance. Due to the growing demand for data, it is now necessary to feed models with information from multiple entities. However, this transfer, exchange, and trade of data among entities may violate the General Data Protection Regulation (GDPR) and get punished by the Act (Wachter, 2018), posing an unprecedented challenge to the field of machine learning. Federated learning (McMahan et al., 2017) then emerges and flourishes as a privacy-preserving approach by training a shared model collaboratively while keeping data locally. Despite that the data are stored locally, clients that join the federated learning need to transmit their local gradients to the server to update the shared model. Recent studies Zhu & Han (2020); Zhao et al. (2020); Huang et al. (2021) have revealed that sensitive local data could be leaked from these transmitted local gradient via model inversion attack Zhu & Han (2020). To defend such kind of attack and prevent the privacy leakage, defense strategies including differential privacy (Geyer et al., 2017), secure multi-party computation (Byrd & Polychroniadou, 2020), and MixUp (Zhang et al., 2017) have been developed. In exchange for privacy, the cost is then either severe computational overheads (Hardy et al., 2017) or unavoidable accuracy losses (Kim et al., 2021).

What's the intrinsic source of privacy in these defense strategies? If we consider this question from an information theory perspective, it is indeed the asymmetry of entropy in the encryption and decryption steps for clients and servers when partial encryption information is kept locally only. From this standpoint, as long as an encryption method is capable of inevitability between clients and servers while still allows for effective aggregation, it would be feasible to the improve the privacy

Figure 1: *Right*: Workflow of Synergistic Neuromorphic Federated Learning with ANN-SNN Conversion (SNFL). *Left*: In standard federated learning, clients communicate gradients ∇W_A generated by the model trained on client's private local data. The attacker updates its randomized dummy input and label to minimize the gradient distance $||\nabla W_A - \nabla W'||$. When the optimization finishes, the attacker is able to obtain the training set from clients. However, in SNFL, clients upload gradients ∇W_S are not generated by the data-trained model, which has been converted to SNN.

for federated learning. Recent progression in neuromorphic computing, especially the conversion from traditional artificial neural networks (ANNs) to spiking neural networks (SNNs) (Deng & Gu, 2020), provides a pair of source ANN and target SNN that both achieve high accuracy while the source ANN is not recoverable from the resulted SNN (Li et al., 2021b). This property fits naturally with the demand of privacy protection in federate learning. Indeed, if we train ANNs on clients and only send the converted SNNs with partial parameters to the server for aggregation, we can then expect to obtain a feasible privacy-protected FL algorithm with effective parameter sharing paradigm. In addition, such a ANN-SNN conversion is lightweight and performance-preserving (or even performance-improved) by careful design. The Fig. 1 illustrates the pipeline of our proposed method.

Besides the natural feasibility from SNNs (Esser et al., 2016; Kim et al., 2019), this synergistic framework also brings two additional benefits that are special for federated learning. First, in contrast to existing noise inject methods (*e.g.*, differential privacy Geyer et al. (2017)), our ANN-SNN conversion process is optimized to improve performance by fine-tuning SNN's weights rather than trading off performance drop versus noise level. As a result, our method is able to achieve even better performance against standard federated learning. Second, the SNN emits discrete spikes and is not differentiable, thus the induced synergistic FL could be more robust to small perturbations and adversarial attacks like white-box attacks (Liang et al., 2021). Our contributions are summarized as follows:

- Innovation/Privacy: We design a federated learning framework where the server and clients run two different models in a privacy preserving manner as a new solution. To the best of our knowledge, our work is one of the first to train different types of neural network models on server and clients.

- Accuracy: Compared to the conventional approach, extensive experiments validate SNFL can deliver similar or superior accuracy relative to other common methods.

- Effectiveness: Based on the SNFL framework, we analyze the backdoor attack and develop a method to simply detect it through abnormal SNN thresholds.

2 RELATED WORK

2.1 FEDERATED LEARNING (FL)

In Federated Learning, each client computes a model update, i.e. gradient, on its local data. While sharing gradients was assumed to leak little information about the client's private data, recent papers

(Zhu & Han, 2020; Zhao et al., 2020; Huang et al., 2021) devised a "gradient inversion attack" in which an attacker listening on a client's communications with the server can begin to reconstruct the client's private data. Robust methods commonly use techniques such as gradient clipping (Sun et al., 2019), perturbing gradients (Zhu & Han, 2020) or robust aggregation (Blanchard et al., 2017; Goryczka & Xiong, 2015; Yin et al., 2018).

2.2 Spiking Neural Network (SNN)

Conventionally, there are two distinct routes to obtain a deep SNN (Deng et al., 2020): (1) direct training SNN from scratch, and (2) converting a pretrained ANN to SNN. In this work, we mainly focus on the conversion-based method. ANN-SNN conversion directly reuses the features learned in ANN to obtain a performant SNN. However, it requires a trade-off between inference latency and task performance. Data based normalization (Diehl et al., 2016) and threshold balancing (Sengupta et al., 2018) are the basic methods of ANN-to-SNN conversion. Then Rueckauer et al. (2016); Han et al. (2020) propose the soft mechanism to reduce information loss by membrane potential reset. Recently, Deng & Gu (2020) analyse the conversion error and propose a shift method to reduce it by half. Li et al. (2020) propose a light pipeline and an advanced pipeline, which apply layer-wise calibration algorithms to modify the network parameters to diminish the conversion error, significantly reducing the required simulation length. We adopt the layer-wise calibration algorithm for high-performance and low-latency SNN in the SNFL framework.

3 Preliminaries

In this section, we briefly introduce the concept and the baseline method for Federated Learning (FL). We also point out the privacy issue in FL, which can lead to the leakage of user data.

Federated Learning (FL). FL enables mobile devices to collaboratively learn a shared prediction model while keeping all the training data on device, decoupling the ability to do machine learning from the need to store the data in the cloud. Formally, assume we have K clients, the optimization objective in FL is to solve the following empirical risk minimization problem:

$$\min_\theta L(\theta) = \frac{1}{K} \sum_{i=1}^{K} \ell_i(\theta), \text{ where } \ell_i(\theta) = \ell_{(\boldsymbol{x}_i, \boldsymbol{y}_i) \sim \mathcal{D}_i}(\boldsymbol{x}_i, \boldsymbol{y}_i; \theta). \tag{1}$$

Here, θ is the model parameters vector and $\ell_i(\theta)$ denotes the loss function of θ evaluated on the i-th client's dataset $\mathcal{D}_i$. $(\boldsymbol{x}_i, \boldsymbol{y}_i)$ is the input-label pair on $\mathcal{D}_i$. The goal of this objective is to achieve minimum average loss on each client. We assume $\{\mathcal{D}_i\}_{i=1}^{K}$ are randomly sampled from $\mathcal{D}_{\text{train}}$, where both IID sampling and Non-IID sampling are considered in this work.

To ensure the minimization of average loss on all clients while not sharing the local input data, the clients will upload their model parameters to the server periodically. A communication round is used for the client upload, server aggregation, and server distribution. Here we introduce the FedAvg (McMahan et al., 2017) communication for client-sever update.

- In the r-th communication round, each client i uploads its local model parameter change $\Delta\theta_i^{(r)}$ to server. Server aggregates the local model updates from all participating clients, given by

$$\theta^{(r)} = \theta^{(r-1)} + \frac{1}{K} \sum_{i=1}^{K} \Delta\theta_i^{(r)}, \tag{2}$$

  After which the server distributes the aggregated parameters $(\theta^{(r)})$ to clients.
- Upon receiving the aggregated parameters from server, the clients start their own local learning using the private datasets, *i.e.*, $\{\mathcal{D}_i\}_{i=1}^{K}$, which creates new model parameters update for the next round $\Delta\theta_i^{(r+1)}$, given by

$$\Delta\theta_i^{(r+1)} = \eta_i \nabla_{\theta^{(r)}} \ell_{(\boldsymbol{x}_i, \boldsymbol{y}_i) \sim \mathcal{D}_i}(\boldsymbol{x}_i, \boldsymbol{y}_i, \theta^{(r)}), \tag{3}$$

  where η_i is the learning rate in local learning. The clients usually updates multiple iterations with gradient descent (we only show one update in above equation).

Gradient-Inversion Attack. Proposed in Zhu & Han (2020), the Deep Leakage from Gradients (DLG) attack can utilize the gradient information to reverse the private local data and the label information, that is, given the model parameters update $\Delta\theta_i$ one can obtain the similar $(\boldsymbol{x}_i, \boldsymbol{y}_i)$ pairs. This is done by mimicking the real gradient, (also the the parameters update, see Eq. (3)). Formally, DLG first randomly initialize a dummy input and a dummy label $(\boldsymbol{x}_i', \boldsymbol{y}_i')$, and optimize them by minimizing the discrepancy between real gradients and current gradients, given by

$$\min_{\boldsymbol{x}_i', \boldsymbol{y}_i'} ||\nabla_\theta \ell(\boldsymbol{x}_i', \boldsymbol{y}_i') - \nabla_\theta \ell(\boldsymbol{x}_i, \boldsymbol{y}_i)||_F^2 + \alpha R(\boldsymbol{x}'), \qquad (4)$$

where $\nabla_\theta \ell(\boldsymbol{x}_i, \boldsymbol{y}_i)$ is the real gradient which is uploaded to the server. $R(\boldsymbol{x}')$ is some image prior loss function with α being the coefficient. The current gradient $\nabla_\theta \ell(\boldsymbol{x}_i')$, therefore, can be made as close as possible to the real gradient and generate corresponding input data and label.

So far, some defensive methods have been proposed. For examples, Gradient Pruning (Zhu & Han, 2020), Gradient Noise (Zhu & Han, 2020), Mixup (Zhang et al., 2017) aim to provide less or distributed information in gradients. However, these methods sacrifice the task performance for better privacy. In this paper, we seek a method for preserving the privacy during federated learning while not jeopardizing its accuracy.

4 METHODOLOGY

In this section, we introduce our method—combining both Artificial Neural Networks (ANNs) and Spiking Neural Networks (SNNs) for privacy-preserving federated learning. We first formulate the neuron model used for SNNs and present the conversion method for parameters encryption. Last, we discuss how does our method prevent the gradient-inversion attack.

4.1 SPIKING NEURAL NETWORKS

Compared to artificial neurons (*i.e.*, ReLU: $\max(0, x)$, spiking neurons are biologically-inspired, where each neuron maintains a variable dubbed membrane potential $\boldsymbol{v}$. Here, we describe the dynamics using the iterative expression of Integrate-and-Fire (IF) neuron model (Liu & Wang, 2001), which is favorable for ANN-SNN conversion regime (Rueckauer et al., 2016; Han et al., 2020). Formally, at time step t, the IF neuron receives the pre-synaptic input, and then charges the membrane potential, given by

$$\boldsymbol{v}(t) = \boldsymbol{v}(t) + \boldsymbol{I}(t), \quad \boldsymbol{s}(t) = \begin{cases} V_{th} & \text{if } \boldsymbol{v}(t+1) \geq V_{th} \\ 0 & \text{otherwise} \end{cases}, \quad \boldsymbol{v}(t+1) = \boldsymbol{v}(t) - \boldsymbol{s}(t), \qquad (5)$$

where $\boldsymbol{I}(t)$ is the pre-synaptic input calculated by the weights $\boldsymbol{W}$ and the spike $\boldsymbol{s}$ from last layer. As long as the membrane potential exceeds the firing threshold V_{th}, the neuron will elicit a spike $\boldsymbol{s}$, otherwise it will stay silent. For fired neurons, the membrane potential will be reset by subtraction, *i.e.*, the third term in Eq. (5). Noting that the threshold $V_{th}^{(l)}$ differs between layer, the server can further apply weight normalization (Diehl et al., 2016) to convert the output $\{0, V_{th}^{(l)}\}$ to a binary spike $\{0, 1\}$.

4.2 SYNERGISTIC NEUROMORPHIC FEDERATED LEARNING

In the conversion from a source ANN to a target SNN, the discrepancy of output activation between the two networks will accumulate layer-by-layer, resulting in significant different output at the final output layer. To address such issues, a layer-wise parameter calibration technique (Li et al., 2021b) is proposed to adjust the SNN parameters so that its activation frequency gets close to the activation in the source ANN. Mathematically, denote the average spike rate over time in SNNs is $\bar{s}$, we can write the conversion error as $\boldsymbol{e} = \boldsymbol{a} - \bar{s}$, where $\boldsymbol{a}$ is the activation in source ANNs. For each channel c, the average activation is then calculated as $\mu_c(\boldsymbol{a}) = \frac{1}{wh} \sum_{i=1}^{w} \sum_{j=1}^{h} x_{c,i,j}$, where w, h are the width and height of the feature. The bias calibration (BC) algorithm computes the spatial mean of error term, given by

$$\mu_c(\boldsymbol{e}) = \mu_c(\boldsymbol{a}) - \mu_c(\bar{s}). \qquad (6)$$

Afterwards, $\mu_c(\boldsymbol{e})$ can be added to the c-th channel of bias term $\boldsymbol{b}$ in SNNs. When calculating $\mu_c(\boldsymbol{e})$, we need to estimate $\mu_c(\boldsymbol{a})$ and $\mu_c(\bar{\boldsymbol{s}})$ based on a small calibration dataset (e.g. 128 images), which is not accessible on the server set. Considering that $\mu_c(\boldsymbol{e})$ is dependent on the data distribution rather than distribution free, we cannot use random dataset on the server side for the recovery. Our framework can take advantage of this algorithm to encrypt the gradient information, therefore improving the privacy in FL. The overall pipeline (Algo. 1) in our SNFL is described as follows:

Client Encryption. Before uploading the parameters update to the server, the clients convert the ANN models into SNN models. The conversion first replaces all the ReLU neurons into IF neurons. Due to there is no corresponding module in SNN for BN layer, Rueckauer et al. (2017) propose to absorb the BN parameters to the weight and bias, which can be represented as $W_S \leftarrow W_A \frac{\gamma}{\sigma}$, $b_S \leftarrow \beta + (b_A - \mu)\frac{\gamma}{\sigma}$, where W_A, b_A are the weight and bias of ANN model, W_S, b_S are the weight and bias of SNN model, μ, σ are the running mean and standard deviation and γ, β are the transformation parameters of the Batch Normalization (BN) layer. Then, all clients run bias calibration algorithm to update the bias parameters for SNN. Note that each local BC process will infer its own local model using their private dataset to record some activation, $i.e.$, $\boldsymbol{a}_i$ and $\bar{\boldsymbol{s}}_i$ for the i-th client's ANN and SNN. The bias parameters can then be calibrated as $\boldsymbol{b}_S^i \leftarrow \boldsymbol{b}_S^i + \mu(\boldsymbol{a}_i) - \mu(\bar{\boldsymbol{s}}_i)$. The BC algorithm has two advantages: (1) the uploaded SNN has higher accuracy since its parameters is calibrated, and (2) the uploaded parameters are not the same with original ANNs, which prevents the leakage from gradients. In the sharing step, the client sends parameters to the server, which include the weight (W_S^i), bias (b_S^i), threshold (V^i) of SNN model as well as BN layer ($\gamma^i, \sigma^i, \beta^i, \mu^i$) of ANN model.

Server Aggregation. In the global communication round, the server will receive the encrypted parameters from clients. Then, on the server side, we apply FedAvg (McMahan et al., 2017) ($cf.$ Eq. (2)) to aggregate the massive clients updates. The server averages parameters uploaded by all clients to obtain the averaged SNN model (W_S^S, b_S^S, V^S) and BN layer parameters ($\gamma^S, \sigma^S, \beta^S, \mu^S$), where the subscript S/A indicates that the parameters are from the SNN or ANN model and the superscript S indicates that the model is owned by the server. Thus the aggregated model is also SNN. Since SNNs have discrete spikes, it might be less sensitive to small amount of random noise, which leads to the robustness of SNNs (Venkatesha et al., 2021). In practise, we find that the aggregation of SNNs loses less task performance than that of ANNs in most cases. Note that clients do not require the aggregated SNN's parameters. So the server has to take an additional step while processing the W_A from each client to obtain the parameters that clients require. The server gets $W_A^i \leftarrow W_S^i \frac{\sigma^i}{\gamma^i}$ for the i-th client and then applies ($cf.$ Eq. (2)) to aggregate all W_A from clients to obtain W_A^S, which is the parameter required by clients. In the sharing step, the server sends $W_A^S, \gamma^S, \sigma^S, \beta^S, \mu^S$ to each client.

Server Distribution. Following the FedAvg setting, clients use these parameters updated by server to recreate the ANN model and continue to train the ANN using local dataset. Note that clients will not receive the update of bias parameters from server, rather, they continue to use their original ANN bias (before calibration) for the next round of training. On the client-end, they lose less information compared to FedAvg since the bias parameters are kept intact, which helps to learn a better local model. On the server-end, it always uses SNN model for evaluation.

5 EXPERIMENTS

In FL, it is frequently vital to consider the presence of semi-honest (honest-but-curious) adversaries for the sake of privacy protection. The adversary is honest in the sense that he/she faithfully follows the collaborative learning protocol, but he/she may be curious about the training data of other participants. So there exist two conflicting goals in designing an appropriate algorithm. On the one hand, given the presence of semi-honest partners, private data must be kept as secure as possible, yet a certain amount of information has to be transferred across other parties for the sake of learning utility. In the section, we conduct experiments to illustrate the advantages of SNFL in protecting privacy and even improving accuracy in most cases.

Algorithm 1 Synergistic Neuromorphic Federated Learning (SNFL)

Input:Set of K clients with local datasets; B is the local minibatch size, E_L is the number of local epochs, E_G is the number of Global communication round, and η is the learning rate.
Parameter: f_{SG} is the global SNN model of server, f_{SL} is the local SNN model of client, f_{AL} is the local ANN model of client
Output: Well-trained model f_{SG}
Algorithm: MAIN

1: Initialize global SNN model f_{SG} and local ANN model f_{AL} with random weights
2: **for** round $m \leftarrow 0$ to E_G **do**
3:     Broadcast the weight parameters of current global ANN model $w' \in f_{SG}$ to all clients
4:     **for** Client $c \leftarrow 0$ to K **do**
5:         Transplants w' to local ANN model f_{AL}
6:         **for** epoch $n \leftarrow 0$ to E_L **do**
7:             Train f_{AL} with local private dataset
8:         **end for**
9:         Perform ANN-TO-SNN() and obtain f_{SL}
10:     **end for**
11:     Randomly select P participating clients
12:     Aggregate the parameters of f_{SL} using FedAvg and obtain f_{SG}
13:     Send f_{SG} parameters to the clients
14: **end for**

Procedure:ANN-TO-SNN ()

1: **for** all $i = 1, 2, \ldots, p$-th layers in the ANN **do**
2:     Collect input data $x^{(i)}$,output data $x^{(i+1)}$ in one batch
3:     Get MMSE threshold $V_{th}^{(i)}$ using grid search
4:     Get SNN output $\bar{s}^{(i+1)}$
5:     Compute Error term $e^{(i+1)} = x^{(i+1)} - \bar{s}^{(i+1)}$
6:     Calibrate bias term $b(i) \leftarrow b(i) + \mu(e^{i+1})$
7: **end for**
8: **output** Converted SNN model

Figure 2: Results of gradient inversion attack. The left half shows the process of the ANN model being attacked and the right half shows the process of the SNN model being attacked

5.1 PRIVACY

Implementation Details: Here, we employ Gradient Inversion Attack (Zhu & Han, 2020) (*cf.* Eq. (4)). As mentioned in 4.2, the SNN replaces the ANN's differentiable ReLU neurons with non-differentiable IF neurons. That is, gradient inversion attack is not applicable to the SNN model. For SNFL, the real gradients generated by the ANN models on the client sides are not accessible to the server. The only thing the server can get is $\Delta W_S^i(r) = W_S^i(r) - W_S^i(r-1)$, $\Delta W_A^i(r) = W_A^i(r) - W_A^i(r-1)$, $\Delta b^i(r) = b^i(r) - b^i(r-1)$, where r is the global round and i is the i-th client. So the server can only obtain "real" gradients generated by $\Delta W^i(r), \Delta b^i(r)$. We experiment our method on LeNet (LeCun et al., 2015) with Batch Size 1 and optimize for 280 iterations. We use L-BFGS (Liu & Nocedal, 1989) with learning rate 0.01. All our experiments are using randomly initialized weights.

Table 1: Accuracy(%) on CIFAR10, CIFAR100 and TinyImageNet with IID. "P" means the number of participating clients. "Client Accuracy" shows the mean and variance of ANN models' accuracy for all clients on test dataset. "Server Accuracy" is the accuracy of server model on test dataset."S-" means applying SNFL.

Dataset	P	FedAvg	S-FedAvg	FedProx	S-Fedprox	MOON	S-MOON	SOLO
				Client Accuracy				
	5	94.4±0.06	94.7±0.06	94.6±0.06	95.4±0.05	94.8±0.08	95.3±0.04	89.6±0.18
CIFAR10	10	92.0±0.11	93.1±0.07	91.4±0.08	95.1±0.09	92.9±0.07	94.7±0.09	84.2±0.89
	15	88.6±0.18	91.1±0.08	84.8±0.10	95.0±0.12	89.5±0.09	94.4±0.08	79.7±1.07
	5	70.1±0.08	71.4±0.22	70.3±0.12	72.8±0.39	71.5±0.24	72.2±0.56	52.4±0.88
CIFAR100	10	67.0±0.13	68.9±0.17	67.5±0.19	72.8±0.18	69.2±0.10	72.1±0.45	40.2±0.46
	15	60.2±0.26	66.8±0.19	59.7±0.11	71.7±0.22	67.2±0.21	71.7±0.30	31.4±2.50
	5	39.0±0.02	43.7±0.01	38.2±0.01	41.7±0.00	25.2±0.12	34.6±3.08	19.5±1.45
Tiny-ImageNet	10	31.0±0.01	41.3±0.03	29.9±0.00	39.2±0.02	21.5±0.38	34.9±1.22	9.38±0.66
	15	22.1±0.02	35.9±0.04	26.5±0.02	37.7±0.31	18.2±0.24	32.8±0.84	5.31±0.38
				Server Accuracy				
	5	94.5	95.2	94.6	95.2	94.9	94.4	/
CIFAR10	10	92.2	95.3	91.6	95.1	92.8	94.6	/
	15	88.8	94.8	85.0	95.0	89.5	94.3	/
	5	70.2	73.1	70.4	73.5	72.2	73.6	/
CIFAR100	10	62.1	72.3	67.8	73.5	69.6	73.0	/
	15	60.9	72.4	60.1	72.0	68.0	72.2	/
	5	38.9	43.4	38.2	41.5	30.5	35.2	/
Tiny-ImageNe	10	31.1	41.3	30.0	38.7	25.9	35.5	/
	15	22.9	35.9	26.6	35.9	20.9	33.4	/

Validation: We use CIFAR10 (Krizhevsky et al., 2010) to evaluate the attack and defense performance. The leaking process is visualized in Fig. 2. We just show one image here, however this attack is capable of recovering every image in CIFAR10 from ANN model gradients. But, when the model is converted into SNN, the attack is rendered ineffective, allowing the user's private data to be secured.

5.2 ACCURACY

Implementation Details: We perform experiments on widely adopted benchmarks CIFAR10 (Krizhevsky et al., 2010), CIFAR100 (Krizhevsky et al., 2010) and Tiny-ImageNet constructed from ImageNet (Russakovsky et al., 2015). To simulate federated learning scenario, we randomly split the training set of each dataset into N parties, and assign one training party to each client. Namely, each client owns its local training set. We are interested in different partitions of the three datasets: IID and Non-IID, where the overall label distribution across clients is the same in the IID setting, whereas class proportions and number of data points of each client are unbalanced. Specially, for Non-IID setting, we impose data shift as follows (Li et al., 2022): The size of the local dataset $|D^i|$ varies across clients. We sample $q \sim Dir_N(\beta)$ and allocate a q_i proportion of the total data samples to client i. We should note that if β is set to a smaller value, then the partition is more unbalanced. we use $q \sim Dir_N(\beta)$ to denote such a partitioning strategy.

For all the experiments, we use ResNet-20 (Sengupta et al., 2018) architecture and SGD optimizer with a weight decay of 1e-5 and momentum of 0.9. The adopted learning is 0.1, which is multiplied by 0.1 at communication rounds 61 and 96. We set the total global communication rounds E_g at 100 and train each client for $E_l = 5$ epochs in every global communication round. The simulation length T of SNN model is 256.

Baselines: **(1) FedAvg** (McMahan et al., 2017): it involves multiple local random gradient updates on the client nodes, followed by server model averaging updates. **(2) FedProx**(Li et al., 2020): it improves the local objective based on FedAvg and introduces an additional L_2 regularization term in the local objective function to limit the distance between the local model and the global model. A hyper-parameter μ is introduced to control the weight of the L_2 regularization. **(3) MOON** (Li et al., 2021a): it corrects the local updates by maximizing the agreement of representation learned by the current local model and the representation learned by the global model. **(4) SOLO** : each client uses local private data to train its own model without communicating with others.

Table 2: Accuracy(%) on CIFAR10 and CIFAR100 with different degrees of Non-IID. There are 10 participating clients.

Dataset	Partition	FedAvg	S-FedAvg	FedProx	S-FedProx	MOON	S-MOON
CIFAR10	$q \sim Dir_N(2.0)$	92.15	94.74	92.54	94.87	92.59	94.74
	$q \sim Dir_N(1.0)$	90.83	94.6	91.8	94.45	91.83	94.6
	$q \sim Dir_N(0.5)$	88.67	86.88	89.97	93.88	90.95	93.38
CIFAR100	$q \sim Dir_N(2.0)$	68.81	72.54	68.52	72.4	69.07	73.95
	$q \sim Dir_N(1.0)$	66.3	72.47	67.58	71.78	70.27	73.02
	$q \sim Dir_N(0.5)$	68.17	71.47	67.81	71.63	70.23	72.29

Table 3: The impact of bias. "✓/✗" denotes whether to do bias calibration (BC), or whether the server shares its bias with clients (Bias Back). "T=" means the simulation length T of SNN model.

BC	Bias back	T=64	T=128	T=256
✗	✗	94.46	95.08	95.14
✗	✓	94.4	94.82	95.00
✓	✗	**94.75**	**95.05**	**95.14**
✓	✓	94.51	94.91	95.08

Validation in the IID Case: Since real-world federated systems involve a number of devices, a federated learning model must be scalable with the number of devices. In this experiment, we verify the case of 5, 10, and 15 clients respectively. As shown in Table. 5.1, we present the test accuracy on all datasets before and after applying out SNFL. As we can seen, SNFL consistently improves all baseline methods. From a horizontal perspective, it can be observed that applying SNN-conversion increases accuracies for all baseline methods, even with the accuracy gain up to 13.79%. This is particularly inspiring because SNPL requires no modification to the original federated training process. One can easily get considerable accuracy profits by simply post-processing the trained global model. Comparing the accuracy gains of different methods after applying SNFL and whole data calibration, we find that the accuracies of FedProx and MOON get the greatest increase. Form the vertical, the accuracy of baseline methods using SNFL drops more slowly as the number of clients increases. For example, on CIFAR100, when 5 clients participate, the accuracy of S-MOON is 0.71% higher than MOON, while the difference between S-MOON and MOON increase to 4.46% when 15 clients participate. This accurately reflects the SNFL benefits that are more suited to the federated learning situation with a large number of clients.

Validation in the non-IID Case: A key challenge in FL is the non-IID data among the parties. As shown in Table. 5.2, although accuracy decreases to varying degrees as β decreases, SNFL can still increase the performance of models, with MOON and Fed seeing the most benefit. For instance, on CIFAR10, when β=0.5, S-FedProx is 3.91% higher than FedProx and S-MOON is 2.43% higher than MOON.

5.3 BIAS ANALYSIS

Compared to standard FL, SNFL has two different operations on the bias. (1) In the conversion between ANN and SNN, client uses its local private data to calibrate model's bias. (2) When sending back server's model to clients, standard Fl returns all parameters of server's model including bias, but the server of SNFL keeps bias as a private key and does not share it with clients. Since both clients and server use bias as their private key, SNFL secures the privacy of all parties to some extent. To investigate the effect of the above two operations on bias, we design four ablation studies (Table. 5.2). It can be seen that the extra BC operations have no significant effect on the final server accuracy, when client uses its own saved bias instead of the server's bias. In other words, we are protecting privacy while maintaining the performance of the model, rather than trading precision for privacy as in previous studies.

Then, we simulated a honest but curious server, which attempts to infer the client ANN's full parameters. In this experiment, we used 10 clients with IID and non-IID ($q \sim Dir_N(0.5)$). Since

Figure 3: Bias and threshold analysis. *(A)* The l2 distance between the true bias ans the inferred bias. *(B)* Scatter image for the thresholds of the last two layers. 2/10 clients are attack clients. *(C)* The thresholds comparison between the normal clients and the poison client.

the malicious server cannot directly access the bias of client ANN in SNFL, it can only calculate a new bias using the bias of SNN and ANN's BN parameters. Fig. 3 shows the l2 distance between the true bias and the inferred bias. In the IID case, the disparity between them is much greater than in non-IID cases, showing BC needs more huge bias shift (more huge difference between ANN and SNN) when layer-by-layer calibration in the IID case.

5.4 BACKDOOR ATTACK AND DETECTION

In federated learning, backdoor attack (Bagdasaryan et al., 2020) attempt to cause the model to make wrong judgments about data with a certain characteristic (trigger), but the model has no effect on the main task. In other words, the attacked model still exhibits high accuracy on the test dataset, but its output will be different from the output of the clean model when input activates the backdoor trigger. Since the server cannot access the client's training data in federated learning, it is difficult to determine whether the global model has been poisoned through data detection.

In recent paper (Bhagoji et al., 2019), the server identifies the abnormal client based on clustering or mean detection on the model weight and bias. However, these detection methods are cumbersome since the number of parameters in ANN is enormous, e.g., the number of parameters in ResNet-20 has reached over 11 million. For the SNFL, the server adopt the SNN model, which has a special type of parameter–threshold. As shown in Fig. 3 B and C, we find that the thresholds (only 20 thresholds in ResNet-20 including converted pooling layer) for poison clients and normal clients are significantly different. The distance between the normal clients threshold set and the cluster center is less than 17.62, whereas the distance between the poison client and the cluster center is more than 103.53, making the distinction very clear.

6 CONCLUSION

In this paper, we propose that SNFL, a simple FL framework, protects privacy while improving model accuracy in most cases. To the best of our knowledge, this is the first paper that allows client and server to use different types of neural network models. SNFL can be thought of as a lightweight encryption component add-on for any global federated objective. We investigate the root cause of its privacy from both theoretical and experimental perspectives and conduct experiments to demonstrate that the framework does not jeopardize the model's performance. We also find that SNFL is good at exploring the knowledge in local models and transferring it to the global model, particularly as the number of clients grows or data distribution gets more uneven. In addition to that, we discover that the threshold of the client launching the attack is very different from that of the normal client. This allows us to find the malicious client among a large number of clients at a lower computational cost. Our empirical results demonstrate that SNFL can result in both more privacy and more accurate models compared with the strong baseline. Our work suggests several interesting directions for future study, such as exploring the applicability of SNFL to other attacks and its ability to migrate to other algorithms.

REFERENCES

Eugene Bagdasaryan, Andreas Veit, Yiqing Hua, Deborah Estrin, and Vitaly Shmatikov. How to backdoor federated learning. In *International Conference on Artificial Intelligence and Statistics*, pp. 2938–2948. PMLR, 2020.

Arjun Nitin Bhagoji, Supriyo Chakraborty, Prateek Mittal, and Seraphin Calo. Analyzing federated learning through an adversarial lens. In *International Conference on Machine Learning*, pp. 634–643. PMLR, 2019.

Peva Blanchard, El Mahdi El Mhamdi, Rachid Guerraoui, and Julien Stainer. Machine learning with adversaries: Byzantine tolerant gradient descent. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 118–128, 2017.

David Byrd and Antigoni Polychroniadou. Differentially private secure multi-party computation for federated learning in financial applications. In *Proceedings of the First ACM International Conference on AI in Finance*, pp. 1–9, 2020.

Lei Deng, Yujie Wu, Xing Hu, Ling Liang, Yufei Ding, Guoqi Li, Guangshe Zhao, Peng Li, and Yuan Xie. Rethinking the performance comparison between snns and anns. *Neural Networks*, 121:294 – 307, 2020.

Shikuang Deng and Shi Gu. Optimal conversion of conventional artificial neural networks to spiking neural networks. In *International Conference on Learning Representations*, 2020.

Peter U Diehl, Guido Zarrella, Andrew Cassidy, Bruno U Pedroni, and Emre Neftci. Conversion of artificial recurrent neural networks to spiking neural networks for low-power neuromorphic hardware. In *2016 IEEE International Conference on Rebooting Computing (ICRC)*, pp. 1–8. IEEE, 2016.

Steven K Esser, Paul A Merolla, John V Arthur, Andrew S Cassidy, Rathinakumar Appuswamy, Alexander Andreopoulos, David J Berg, Jeffrey L McKinstry, Timothy Melano, Davis R Barch, et al. Convolutional networks for fast, energy-efficient neuromorphic computing. *Proceedings of the national academy of sciences*, 113(41):11441–11446, 2016.

Robin C Geyer, Tassilo Klein, and Moin Nabi. Differentially private federated learning: A client level perspective. *arXiv preprint arXiv:1712.07557*, 2017.

Slawomir Goryczka and Li Xiong. A comprehensive comparison of multiparty secure additions with differential privacy. *IEEE transactions on dependable and secure computing*, 14(5):463–477, 2015.

Bing Han, Gopalakrishnan Srinivasan, and Kaushik Roy. Rmp-snn: Residual membrane potential neuron for enabling deeper high-accuracy and low-latency spiking neural network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13558–13567, 2020.

Stephen Hardy, Wilko Henecka, Hamish Ivey-Law, Richard Nock, Giorgio Patrini, Guillaume Smith, and Brian Thorne. Private federated learning on vertically partitioned data via entity resolution and additively homomorphic encryption. *arXiv preprint arXiv:1711.10677*, 2017.

Yangsibo Huang, Samyak Gupta, Zhao Song, Kai Li, and Sanjeev Arora. Evaluating gradient inversion attacks and defenses in federated learning. *Advances in Neural Information Processing Systems*, 34, 2021.

M. Kim, O Günlü, and R. F. Schaefer. Federated learning with local differential privacy: Trade-offs between privacy, utility, and communication. 2021.

Seijoon Kim, Seongsik Park, Byunggook Na, and Sungroh Yoon. Spiking-yolo: Spiking neural network for energy-efficient object detection. *arXiv preprint arXiv:1903.06530*, 2019.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research). *URL http://www. cs. toronto. edu/kriz/cifar. html*, 5(4):1, 2010.

Yann LeCun et al. Lenet-5, convolutional neural networks. *URL: http://yann. lecun. com/exdb/lenet*, 20(5):14, 2015.

Qinbin Li, Bingsheng He, and Dawn Song. Model-contrastive federated learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10713–10722, 2021a.

Qinbin Li, Yiqun Diao, Quan Chen, and Bingsheng He. Federated learning on non-iid data silos: An experimental study. In *2022 IEEE 38th International Conference on Data Engineering (ICDE)*, pp. 965–978. IEEE, 2022.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *Proceedings of Machine Learning and Systems*, 2:429–450, 2020.

Yuhang Li, Shikuang Deng, Xin Dong, Ruihao Gong, and Shi Gu. A free lunch from ann: Towards efficient, accurate spiking neural networks calibration. *arXiv preprint arXiv:2106.06984*, 2021b.

Ling Liang, Xing Hu, Lei Deng, Yujie Wu, Guoqi Li, Yufei Ding, Peng Li, and Yuan Xie. Exploring adversarial attack in spiking neural networks with spike-compatible gradient. *IEEE transactions on neural networks and learning systems*, 2021.

D. C. Liu and J. Nocedal. On the limited memory bfgs method for large scale optimization. *Mathematical Programming*, 45(1):503–528, 1989.

Ying-Hui Liu and Xiao-Jing Wang. Spike-frequency adaptation of a generalized leaky integrate-and-fire model neuron. *Journal of computational neuroscience*, 10(1):25–45, 2001.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Bodo Rueckauer, Iulia-Alexandra Lungu, Yuhuang Hu, and Michael Pfeiffer. Theory and tools for the conversion of analog to spiking convolutional neural networks. *arXiv: Statistics/Machine Learning*, (1612.04052):0–0, 2016.

Bodo Rueckauer, Iulia-Alexandra Lungu, Yuhuang Hu, Michael Pfeiffer, and Shih-Chii Liu. Conversion of continuous-valued deep networks to efficient event-driven networks for image classification. *Frontiers in neuroscience*, 11:682, 2017.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Abhronil Sengupta, Yuting Ye, Robert Wang, Chiao Liu, and Kaushik Roy. Going deeper in spiking neural networks: Vgg and residual architectures. *Frontiers in Neuroence*, 13, 2018.

Ziteng Sun, Peter Kairouz, Ananda Theertha Suresh, and H Brendan McMahan. Can you really backdoor federated learning? *arXiv preprint arXiv:1911.07963*, 2019.

Yeshwanth Venkatesha, Youngeun Kim, Leandros Tassiulas, and Priyadarshini Panda. Federated learning with spiking neural networks. *IEEE Transactions on Signal Processing*, 69:6183–6194, 2021.

Sandra Wachter. Normative challenges of identification in the internet of things: Privacy, profiling, discrimination, and the gdpr. *Computer law & security review*, 34(3):436–449, 2018.

Dong Yin, Yudong Chen, Ramchandran Kannan, and Peter Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. In *International Conference on Machine Learning*, pp. 5650–5659. PMLR, 2018.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

Bo Zhao, Konda Reddy Mopuri, and Hakan Bilen. idlg: Improved deep leakage from gradients. *arXiv preprint arXiv:2001.02610*, 2020.

Ligeng Zhu and Song Han. Deep leakage from gradients. In *Federated learning*, pp. 17–31. Springer, 2020.

A APPENDIX

A.1 IMPACT OF NUMBER OF CLIENTS

The total number of clients is one aspect of scalability that influences the performance of a federated learning system. To study the impact of client count, we use the case with CIFAR10 in IID setting. We observe, in Table. A.1, that there is a sharp drop as the number of clients increases in standard FL. However, in SNFL, the server model accuracy lowers just little as show in Fig. A.1.

Table 1: Impact of Number of Clients-CIFAR10

Dataset	Party	FedAvg	S-FedAvg	FedProx	S-Fedprox	MOON	S-MOON
Clients	5	94.38±0.06	94.71±0.06	94.59±0.06	95.40±0.05	94.80±0.08	95.26±0.04
	10	92.02±0.11	93.09±0.07	91.39±0.08	95.11±0.09	92.90±0.07	94.73±0.09
	15	88.62±0.18	91.10±0.08	84.76±0.10	95.01±0.12	89.50±0.10	94.36±0.08
	60	57.01±0.18	90.14±0.02	73.46±0.05	90.88±0.02	59.68±0.22	90.57±0.038
Server	5	94.45	95.22	94.64	95.18	94.85	94.44
	10	92.19	95.25	91.6	95.07	92.81	94.62
	15	88.80	94.76	84.97	94.98	89.5	94.27
	60	57.62	90.31	73.94	91.00	60.48	90.66

Figure 1: Impact of Number of Clients-CIFAR10

A.2 SENSITIVITY TO STRAGGLERS

Because real-world networks are inherently unstable, assuming updates communication would be effective from all selected devices is impracticable. Hence, the model needs to be robust enough to handle devices that fail to communicate updates. These devices are referred to as stragglers. In this section, we analyze the impact of stragglers on the performance of final SNN model. We use a case with a total of $N = 60$ clients. In each round, we randomly select PN clients upload parameters to server. We consider different levels of probabilities and summarize in Table. A.2. We found that when the number of stragglers decreased, the accuracy of FedAvg increased first and subsequently declined to 57.62%, whereas the accuracy of S-FedAvg increased amazingly consistently to 90.31%.

Table 2: The accuracy with various client drop probabilities.

Probability	0.1	0.2	0.5	0.7	1
FedAvg	65.07	66.05	68.16	65.76	57.62
S-FedAvg	73.29	83.53	89.87	90.13	90.31

A.3 SENSITIVITY TO THE LENGTH OF SIMULATION T

The forwarding pass in SNN is repeated for T steps to get the final result, where the final result is the expectation of the ultimate layer's output across T steps. This allows the flexibility of adjusting T to

balance between the latency and accuracy of SNNs for different application scenarios. We conduct experiments on CIFAR10 with different simulation length T, as shown in Table. A.3. We discovered that increasing T improved SNN accuracy to a certain extent. However, as T increases to a certain point, its influence on accuracy decreases.

Table 3: The accuracy with different SNN simulation steps.

Simulation steps	64	128	192	256	320
S-FedAvg	89.26	90	90.23	90.31	90.26
S-FedProx	90.52	90.96	90.94	91	90.99
S-MOON	89.95	90.51	90.66	90.66	90.74