COUNTERFACTUAL THINKING FOR LONG-TAILED INFORMATION EXTRACTION

ABSTRACT

Information Extraction (IE) aims to extract structured information from unstructured texts. However, in practice, the long-tailed and imbalanced data may lead to severe bias issues for deep learning models, due to very few training instances available for the tail classes. Existing works are mainly from computer vision society, leveraging re-balancing, decoupling, transfer learning and causal inference to address this problem on image classification and scene graph generation. However, these approaches may not achieve good performance on textual data, which involves complex language structures that have been proven crucial for the IE tasks. To this end, we propose a novel framework (named `Counterfactual-IE`) based on language structure and causal reasoning with three key ingredients. First, by fusing the syntax information to various structured causal models for mainstream IE tasks including relation extraction (RE), named entity recognition (NER), and event detection (ED), our approach is able to learn the direct effect for classification from an imbalanced dataset. Second, counterfactuals are generated based on an explicit language structure to better calculate the direct effect during the inference stage. Third, we propose a flexible debiasing approach for more robust prediction during the inference stage. Experimental results on three IE tasks across five public datasets show that our model significantly outperforms the state-of-the-arts by a large margin in terms of Mean Recall and Macro F1, achieving a relative 30% improvement in Mean Recall for 7 tail classes on the ACE2005 dataset. We also discuss some interesting findings based on our observations.

1 INTRODUCTION

The goal of Information Extraction (IE) (Sarawagi, 2008; Chiticariu et al., 2013) is to detect the structured information from unstructured texts. IE tasks, such as named entity recognition (NER) (Lample et al., 2016), relation extraction (RE) (Zeng et al., 2014; Peng et al., 2017) and event detection (ED) (Nguyen & Grishman, 2015) have developed rapidly with the data-hungry deep learning models trained on a large amount of data. However, in real-world settings, unstructured texts follow a long-tailed distribution (Doddington et al., 2004), leading to a significant performance drop on the instance-scarce (or tail) classes which have very few instances available. For example, in the ACE2005 (Doddington et al., 2004) dataset, nearly 70% of event triggers are long-tailed while they only take up 20% of training data. On a strong baseline (Jie & Lu, 2019), the macro F1 score of instance-rich (or head) classes can be 71.6, while the score of tail classes sharply drops to 41.7.

The underlying causes for the above issues are the biased statistical dependencies and spurious correlations between feature representations and classes learned from an imbalanced dataset. For example, an entity *Gardens* appears 13 times in the training set of OntoNotes5.0 (Pradhan et al., 2013), with the NER tag *LOC*, and only 2 times as organization *ORG*. A classifier trained on this dataset will build a spurious correlations between *Gardens* and *LOC*. As a result, an organization that contains the entity *Gardens* may be wrongly predicted as a location *LOC*.

There are only a few studies (Zhang et al., 2019; Han et al., 2018) in the Natural Language Processing (NLP) field to address such long-tailed issues. These works mostly rely on external and pre-constructed knowledge graphs, providing useful data-specific prior information which may not be available for other datasets. On the other hand, there are plenty of works from the computer vision

society, where the bias is also quite straightforward. Current solutions include re-balanced training (Lin et al., 2017) that re-balances the contribution of each class in the training stage, transfer learning (Liu et al., 2019b) that takes advantage of the knowledge in data-rich class to boost the performance of instance-scarce classes, decoupling (Kang et al., 2019) strategy that learns the representations and classifiers separately, and causal inference (Tang et al., 2020a;b; Abbasnejad et al., 2020) that relies on structured causal models for unbiased scene graph generation, image classification and visual question answering.

The aforementioned studies from the computer vision community may not achieve good performance on the textual datasets in the NLP area due to a significant difference between the two fields. For example, unlike images, texts involve complex language structures such as dependency tree and constituent tree that describe the syntactic or semantic level relations between tokens. For the long-tailed IE, how to explore the rich relational information as well as complex long-distance interactions among words as conveyed by such linguistic structures remains an open challenge. Furthermore, to capture a more informative context, the way of utilizing the syntax tree for three IE tasks varies: the RE task relies more on the context and entity type rather than entities themselves, while classifications in NER and ED tasks count more on entities than the context. Hence, it is challenging to decide properly on how to utilize language structures for the above three different IE tasks. One may also think that the prevalent pre-trained models such as BERT (Devlin et al., 2019) may address the long-tailed issues. However, we empirically show that such models still suffer from bias issues.

In this paper, we propose `CounterFactual-IE`, a novel framework that combines the language structure and counterfactual analysis in causal inference (Pearl et al., 2016) to alleviate the spurious correlations of the IE tasks including NER, RE and ED. From a causal perspective, counterfactuals (Bottou et al., 2013; Abbasnejad et al., 2020) state the results of the outcome if certain factors had been different. This concept entails a hypothetical scenario where the values in the causal graph can be altered to study the effect of the factor. Intuitively, the factor that yields the most significant changes in model predictions have the greatest impact and is therefore considered as main effect. Other factors with minor changes are categorized as side effects. In the context of IE with complex language structures, counterfactual analysis answers the question on "which tokens in the text would be the key clues for RE, NER or ED that could change the prediction result?". With that in mind, we can better eliminate the bias caused by the side effect and maintain the main effect for the classification. Our approach has three key ingredients. First, we build different structured causal models (SCMs) for the IE tasks and fuse the dependency structure to the models to better capture the main causality for the classification. There are many other language structures like constituent tree, abstract meaning representation (Flanigan et al., 2014) and semantic role labeling (Björkelund et al., 2009). We choose the dependency structure in our case as it is able to capture rich relational information as well as complex long-distance interactions that have been proven effective on IE tasks. Second, counterfactuals are generated by selecting the contextual tokens according to the dependency structure defined around the entities, so that the main effect can be better estimated by the intervention methodology. Third, we propose a novel flexible debiasing technique for more robust prediction that is more suitable for the IE tasks. We evaluate our model on five public datasets and achieve significant performance gain on instance-scarce classes. We will release our code to contribute the community.

Our major contributions are summarized as follows:

- To the best of our knowledge, our `CounterFactual-IE` is the first attempt that combines the counterfactual analysis and language structure to address the long-tailed IE issues.

- We generate counterfactuals based on syntax structure, where the counterfactuals can be used as interventions to alleviate spurious corrections on models.

- We also propose flexible classification debiasing approaches inspired by Total Direct Effect (TDE) in causal inference. Our proposed approach is able to make a good balance between the direct effect and counterfactuals representation to achieve more robust predictions.

2 MODEL

Figure 1 shows the work flow of our proposed `CounterFactual-IE`. We detail these components as follows.

Figure 1: Work flow of our `CounterFactual-IE` in five steps.

2.1 STEP1: CAUSAL REPRESENTATION LEARNING

In this step, we train a causal graph on an imbalanced dataset. Our goal here is to teach the model to identify the main cause (main effect) and the spurious correlations (side effect) for the classification.

Structural Causal Models (SCMs): We build SCMs with our prior knowledge for the task. In causal inference, an SCM can be represented as a directed acyclic graph (DAG) $\mathcal{G} = \{\mathbb{V}, \mathbb{F}\}$, where we denote a set of observables $\mathbb{V} = \{V_1, ..., V_n\}$ as the vertices, and a set of functions $\mathbb{F} = \{f_1, ..., f_n\}$ as the directed edges. Each observable V_i can be derived from

$$V_i := f_i(\mathbf{PA}_i, U_i), (i = 1, ..., n), \tag{1}$$

$\forall_i$, $\mathbf{PA}_i \subseteq \mathbf{V} \backslash V_i$ is the subset of $\mathbf{V}$ which are parents of V_i and U_i is the noise to ensure that overall object can represent a generation $p(V_i | \mathbf{PA}_i)$. Directed edges, such as $\mathbf{PA}_i \rightarrow V_i$ in the graph $\mathcal{G}$, i.e., f_i, refers to the direct causation from the parents $\mathbf{PA}_i$ variables to the child variable V_i. Figure 2 (a) demonstrates our unified SCMs for IE tasks. The variable S indicates the contextualized representations of an input sentence. Z_i, where $i \in [1, N]$, represents some features, like the NER tags and part-of-speech (POS) tagging. The variable X refers to relation representations for RE, entity representation for NER, or trigger representation for ED, and Y indicates the output logits for classification.

Take event detection task, whose $Z = \{POS(P), NER(N)\}$, as an example. The direct causation can be defined as follows. The direct causations $S \rightarrow X$, $X \rightarrow Y$, $S \rightarrow Y$, $N \rightarrow Y$, $P \rightarrow Y$ can be linear transformations, denoted by $\mathbf{W}_{sx}\mathbf{e}_s$, $\mathbf{W}_{xy}\mathbf{e}_x$, $\mathbf{W}_{sy}\mathbf{e}_s$, $\mathbf{W}_{ny}\mathbf{e}_n$, and $\mathbf{W}_{py}\mathbf{e}_P$, where $\mathbf{W}_{sx}, \mathbf{W}_{xy}, \mathbf{W}_{sy}, \mathbf{W}_{ny}$, and $\mathbf{W}_{py}$ refer to the parameters for corresponding links, and $\mathbf{e}_x$, $\mathbf{e}_s$, $\mathbf{e}_n$ and $\mathbf{e}_p$ indicate representations for relations or tokens, sentence embedding, NER and POS embeddings, respectively. The outputs are fused using simple summation $\mathbf{e}_y = \mathbf{W}_{xy}\mathbf{e}_x + \mathbf{W}_{sy}\mathbf{e}_s +$

Figure 2: (a) a unified structured causal models for IE tasks. (b) interventions on X.

$\mathbf{W}_{ny}\mathbf{e}_n + \mathbf{W}_{py}\mathbf{e}_p$ or gated mechanism $\mathbf{e}_y = \mathbf{W}_g\mathbf{e}_x \odot \sigma(\mathbf{W}_{xy}\mathbf{e}_x + \mathbf{W}_{sy}\mathbf{e}_s + \mathbf{W}_{ny}\mathbf{e}_n + \mathbf{W}_{py}\mathbf{e}_p)$, where $\odot$ is element-wise product, and $\sigma(\cdot)$ is the sigmoid function. Besides the loss for $\mathbf{e}_y$, we also add a cross entropy loss for each branch to better learn the main and side effects.

Fusing Syntax Structures Into SCMs: So far we have built basic SCMs for IE tasks. On the edge $S \rightarrow X$, we replace the linear transformation $\mathbf{W}_{sy}\mathbf{e}_s$ and use dependency trees to aggregate long-range relations with graph convolution networks (GCN) (Kipf & Welling, 2017) for RE, and a simple dependency-guided concatenation approach (Jie & Lu, 2019) for NER and ED. For the GCN, we generate a matrix $\mathbf{A} \in \mathbb{R}^{l_s \times l_s}$ from a dependency tree, where l_s denotes the length of the sentence. The convolution computation for the node i at the l-th layer takes the representation $\mathbf{u}_i^{l-1}$ from previous layer as input and outputs the updated representations $\mathbf{u}_i^l$. The formulation is given as:

$$\mathbf{u}_i^l = \sigma(\sum_{j=1}^{l} \mathbf{A}_{ij}\mathbf{W}^l\mathbf{u}_i^{l-1} + \mathbf{b}^l) \tag{2}$$

where $\mathbf{W}^l$ and $\mathbf{b}^l$ are the weight matrix and bias vector of the l-th layer respectively, and $\sigma(.)$ is the sigmoid function. For the dependency-guided approach, given a dependency edge (x_h,x_i,r) with x_h as parent, x_i as child and r is the dependency relation, the representations at the i-th position of a sentence can be denoted as:

$$\mathbf{u}_i = [\mathbf{w}_i; \mathbf{w}_h; \mathbf{v_r}], x_h = parent(x_i) \tag{3}$$

Where $\mathbf{w}_i$ and $\mathbf{w}_h$ are the word representations of the word x_i and its parent x_h. We now have fused dependency structure into SCMs. Next we will show how we generate counterfactuals based on these SCMs.

2.2 STEP 2 AND 3: INFERENCE AND COUNTERFACTUAL GENERATION

We have trained our SCMs in the first step. In the second step we perform inference with the SCMs, while in the third step we introduce interventions by generating dependency-based counterfactuals to better measure the main causality.

Interventions: For an SCM, an intervention indicates an operation that modifies a subset of assignments by replacing the structural mechanism $f_i(\mathbf{PA}_i, U_i)$ to $\hat{f}_i(\hat{\mathbf{PA}}_i, U_i)$. Such intervention can be expressed by do-notation $do(X = x^*)$ and where $X \in \mathbb{V}$ indicates the variable that will be manipulated and x^* is a given value.

Dependency-based Counterfactuals Generation: Counterfactuals lead us to think about: "what are the key clues that determine the relations of two entities for RE, and a certain span of a sentence to be an entity or an event trigger for NER and ED task respectively?". We rely on the dependency structure to capture the above clues. During the inference stage, for the RE task, we replace the tokens along the shortest path of the two entities of the relations and generate a new sequence S^*. For the NER and ED task, we mask entities, or the tokens in the scope of 1 hop on the dependency tree for S^*. Then we feed S^* to the function $S \rightarrow X$ to get x^*. By doing so, the key clues have been wiped off in the generated counterfactuals representations x^*, which can be used to strengthen the main effect while reduce spurious correlations and the side effect.

2.3 STEP 4 AND 5: CAUSAL EFFECT ESTIMATION

We estimate the causal effect in the fourth step and make use of the couterfactuals representation for a more robust prediction in the fifth step. By assigning $X = x^*$, we can compare two outcomes $Y_x(S)$ and $Y_{x^*}(S) = Y(do(X = x^*)|S)$ to estimate the causal effect. Inspired by Total Direct Effect (TDE) used in (Tang et al., 2020b), we use the subtraction of the two outputs to measure the effect of RE so that the side effect can be eliminated.

$$Effect = Y_x(S) - Y_{x^*}(S) \tag{4}$$

As both context and entity (or trigger) play important roles for the classification in the NER and ED tasks, we propose a novel approach to alleviate the spurious correlations caused by side effects, while strengthening the main effect at the same time.

$$Effect = Y_x(S) - Y_{x^*}(S) + \alpha\mathbf{W}_x x^* \tag{5}$$

where α is the hyperparameter that balances the importance of context and entity (or trigger) for the NER and ED task. The first part $Y_x(S) - Y_{x^*}(S)$ indicates the main effect, which reflects more about context, while the second part $\mathbf{W}_x x^*$ reflects more about the entity (or trigger). Combing these two parts yield more robust prediction.

Such a design is quite different from that of the previous work used in the vision community (Tang et al., 2020a). We believe such a novel approach is more suitable for IE tasks.

3 EXPERIMENTS

We conduct experiments on three IE related tasks across five public datasets to validate our proposed `CounterFactual-IE`.

3.1 DATASETS AND SETTINGS

The five datasets used in our experiments include OntoNotes5.0 (Pradhan et al., 2013) and ATIS (Tur et al., 2010) for the NER task, ACE2005 (Doddington et al., 2004) and MAVEN (Wang et al., 2020b) for the ED task, and NYT24 (Gardent et al., 2017) for the RE task. We use the same data split for all five datasets to the previous studies and finetune the parameters of our model based on the development sets. We leverage Stochastic Gradient Descent (SGD) optimizer with a 0.3 learning rate and 0.9 weight decay rate. The hidden size of the BiLSTM and GCNs are set as 300, and the number of layers of GCNs is configured as 3. 300-dimensional GloVe Pennington et al. (2014) is used to initialize the word embeddings [1].

We focus more on Mean Recall (MR) (Tang et al., 2020b) and Macro F1 (MF1), two more balanced metrics to measure the performance of long-tailed IE tasks, as MR is able to better reflect the capability in identifying the instance-scare class, and MF1 can better represent the model's ability for each class, while the conventional Micro F1 score highly depends on the data-rich classes and pays less attention to the tail classes. We report the Micro F1 score (F1) for each dataset in the Appendix. We also follow (Liu et al., 2019b) to report the MR and MF1 on three splits in Table 5 in the Appendix.

3.2 BASELINES

Conventional Models: These IE models include BiLSTM (Chiu & Nichols, 2016), BiLSTM+CRF (Ma & Hovy, 2016), C-GCN (Zhang et al., 2017), Dep-Guided LSTM (Jie & Lu, 2019), AGGCN (Guo et al., 2019) and BERT (Devlin et al., 2019). They do not explicitly take the long-tailed issues into consideration.

Re-weighting/Decoupling Models: These models refer to loss re-weighting approaches including Focal Loss (Lin et al., 2017), and two-stage decoupled learning approaches (Kang et al., 2019) that include τ-normalization, classifier retraining (cRT) and learnable weight scaling (LWS).

Causal Models: We use TDE model (Tang et al., 2020b) as our causal baseline. There are also recent studies based on the deconfounded methodology (Tang et al., 2020a; Yang et al., 2020), which however seem not applicable to be selected as a causal baseline in our case.

We reproduced the results for all the baselines as most of the results have not been reported on NLP datasets. Some F1 scores we reproduced may not align with the ones that had been reported, we believe that our scores are fair as all comparisons are under the same environment. We believe some recent strong baselines, which are not mentioned in this paper due to space limitation, may also further benefit our model by integrating them into the edge $S \rightarrow X$.

3.3 TASK DEFINITIONS

Named Entity Recognition: NER is a sequence labeling task that seeks to locate and classify named entities in unstructured text into pre-defined categories such as person, location, etc.

---

[1] The statistics of the datasets and detailed hyperparameters are attached in the Appendix

Table 1: Evaluation results on the OntoNotes5.0 dataset and ATIS dataset for the NER task.

| Model | OntoNotes5.0 | | | | ATIS | | | |
| | Few | | Overall | | Few | | Overall | |
	MR	MF1	MR	MF1	MR	MF1	MR	MF1
BiLSTM (Chiu & Nichols, 2016)	67.5	**69.9**	76.4	76.8	66.2	69.0	84.2	83.1
BiLSTM+CRF (Ma & Hovy, 2016)	60.7	63.6	71.6	73.5	58.1	60.4	81.0	80.2
C-GCN (Zhang et al., 2017)	68.3	69.8	77.3	76.8	63.2	65.3	82.0	80.1
Dep-Guided LSTM (Jie & Lu, 2019)	61.8	69.3	74.1	75.8	60.6	65.4	84.6	84.3
Focal Loss (Lin et al., 2017)	64.1	65.5	74.2	73.9	48.9	49.8	78.7	76.6
cRT (Kang et al., 2019)	64.1	68.5	75.0	76.1	68.1	71.7	85.7	84.8
τ - Normalization (Kang et al., 2019)	61.1	66.7	73.5	75.7	64.8	68.0	83.9	83.1
LWS (Kang et al., 2019)	58.7	64.9	72.1	74.7	66.2	69.1	84.3	83.2
TDE (Tang et al., 2020b)	71.9	68.8	80.4	76.7	67.5	67.1	87.1	84.5
Ours (Glove)	**76.7**	68.9	**83.8**	**77.3**	**71.8**	**73.1**	**88.6**	**87.0**
BERT (Devlin et al., 2019)	77.7	76.5	84.6	82.4	52.3	56.1	82.9	81.7
Roberta (Liu et al., 2019a)	78.7	**79.5**	86.5	**85.7**	**60.2**	61.1	84.3	82.3
BERT+GCN(Wadden et al., 2019)	80.2	77.7	85.6	82.6	53.3	56.6	83.0	81.3
Ours (BERT)	**80.6**	79.1	**86.7**	84.1	58.8	**62.2**	**85.5**	**82.6**

Table 2: Evaluation results on the NYT24 dataset for the relation extraction.

| Model | NYT24 | | | |
| | Few | | Overall | |
	MR	MF1	MR	MF1
C-GCN (Zhang et al., 2017)	24.0	26.7	51.2	52.6
Focal Loss (Lin et al., 2017)	52.0	48.3	62.9	61.9
cRT (Kang et al., 2019)	66.0	24.2	**65.6**	50.5
τ - Normalization (Kang et al., 2019)	40.0	40.0	53.5	54.6
LWS (Kang et al., 2019)	40.0	40.0	53.5	54.6
TDE (Tang et al., 2020b)	60.0	57.1	61.0	60.2
Ours (Glove)	**68.0**	**68.6**	65.3	**63.6**

Event Detection: ED aims to detect the occurrences of predefined events and categorize them as triggers from unstructured text. Event trigger is defined as the words or phase that most clearly expresses an event occurrence. Taking the sentence "a cameraman died in the Palestine Hotel" as an example, the word "died" is considered as the trigger with a "Death" event.

Relation Extraction: The goal of RE is to identify semantic relationships from text, given two or more entities. For example, "Paris is in France" states a "is in" relationship between two entities Paris to France. Their relation can be denoted by the triples (Paris, is in, France).

3.4 RESULTS

Named Entity Recognition: Table 1 shows the comparison results on both OntoNotes5.0 and ATIS datasets. Our models outperform the two classical models `BiLSTM` and `BiLSTM+CRF` under most settings, especially on the Few setting, e.g achieving 10.2 points higher Mean Recall (MR) against `BiLSTM` on OntoNotes5.0, and 12.7 points higher Mean F1 (MF1) against `BiLSTM+CRF` on ATIS. The results indicate the superiority of our proposed model in handling the instance-scarce classes. Comparing with the C-GCN model that makes use of dependency trees for information aggregation, our model also achieves 8.4 higher MR and comparable MF1, indicating the capability of a causal model in improving the long-tailed sequence labeling problem. Comparing with a recent causal baseline TDE, our model consistently perform better in terms of long-tailed scores, the results confirm our hypothesis that making good use of language structure helps a causal model to distinguish main effect from the side effect. Among re-balancing approaches such as Focal Loss, cRT and LWS, τ-Normalization performs best and this aligns with the findings in the previous study (Kang et al., 2019) for long-tailed image classification.

Table 3: Evaluation results on the ACE2005 dataset and MAVEN dataset for the event detection.

| Model | ACE2005 | | | | MAVEN | | | |
| | Few | | Overall | | Few | | Overall | |
	MR	MF1	MR	MF1	MR	MF1	MR	MF1
BiLSTM (Chiu & Nichols, 2016)	34.2	35.6	52.3	54.8	36.5	40.7	67.1	69.5
BiLSTM+CRF (Ma & Hovy, 2016)	41.4	45.1	51.8	54.1	43.4	46.8	69.6	71.1
C-GCN (Zhang et al., 2017)	41.4	44.1	52.0	56.1	49.7	51.7	73.1	73.0
Dep-Guided LSTM (Jie & Lu, 2019)	42.8	41.7	52.4	55.8	44.7	45.4	67.8	69.3
Focal Loss (Lin et al., 2017)	38.6	42.9	52.6	58.5	45.4	51.5	70.3	73.8
cRT (Kang et al., 2019)	44.8	47.4	57.6	58.9	49.7	55.4	71.0	74.6
τ - Normalization (Kang et al., 2019)	34.3	35.6	53.3	52.5	21.1	26.7	51.0	58.4
LWS (Kang et al., 2019)	34.3	35.6	58.2	56.9	33.3	38.7	65.9	68.7
TDE (Tang et al., 2020b)	34.3	33.9	58.5	56.5	39.8	36.2	71.9	67.4
Our (Glove)	**47.1**	**49.7**	**63.5**	**60.2**	**60.4**	**57.4**	**79.8**	**76.0**
BERT(Devlin et al., 2019)	47.6	48.9	66.5	65.1	38.1	39.3	73.5	72.3
Roberta (Liu et al., 2019a)	47.6	47.7	70.2	68.6	**43.1**	43.8	**75.0**	**73.6**
BERT+GCN (Wadden et al., 2019)	45.2	47.5	73.1	71.3	40.9	42.0	74.1	72.8
Ours (BERT)	**61.9**	**63.2**	**74.9**	**74.4**	**43.1**	**45.0**	71.3	71.7

Event Detection: Table 3 shows comparison results on both ACE2005 and MAVEN datasets. Overall, our model significantly outperforms the baselines under the Few setting by a large margin, e.g., 12.8 and 15.8 pointers higher in terms of MR and MF1 respectively on ACE2005 dataset, 20.6 and 20.8 points higher in terms of the two metrics on MAVEN dataset. Meanwhile, our model is able to achieve better or comparable results under other settings. The results further confirm the robustness of our model in improving the classifications for tail classes with few training instances available. Our model also performs better than BERT baselines under the Few setting, indicating that the pre-trained BERT models still suffer bias issues on the long-tailed IE tasks.

Relation Extraction: As shown in Table 2, we further evaluate `CounterFactual-IE` for the relation extraction on NYT24 dataset. Our method significantly outperforms all other methods in MF for both tail classes and overall F1. Although cRT achieves relatively high MR, having the lowest MF1 renders it incompetent for this task.

3.5 DISCUSSIONS

Does the language structure contribute to the long-tailed IE? One main contribution of our work is that we take advantage of dependency structure to two stages: building a causal graph and generating meaningful counterfactuals. To answer the above question, we design three baselines including: 1) `Causal Models w/o Syntax T` that doesn't employ dependency trees during the training stage, and only uses it for generating counterfactuals, 2) `Counterfactuals w/o Syntax I` that employs dependency structures for training but utilizes a null input as the intervention during the inference state. We refer such a setting from the previous study (Tang et al., 2020a), and 3) `No Syntax` that is the same to the previous work TDE (Tang et al., 2020b) which don't involve dependency structures in both training and inference stages. As shown in Figure 3, our full model outperforms the first two baselines on the ACE2005 dataset for tail classes and all classes, demonstrating the effectiveness of dependency structure in improving the causal models for long-tailed IE issues. An interesting finding is that dependency-based counterfactual generation brings more gains compare with the gains by applying the structure in the causal model.

How can we make good use of dependency structures in a causal model? To answer this question, we propose different approaches for training and inference. For training stage, in order to better utilize dependency structures, we compare two aggregation approaches described in Equation 2 and Equation 3. For generating counterfactuals during the inference stage, we design three pruning strategies based on the dependency structure, including 1) `CF-IE Mask 1-hop` which masks the tokens that directly connect to the targeting token in a dependency tree, 2) `CF-IE Mask token` which directly masks the targeting token, 3) `CF-IE Mask token&1-hop` which masks both the targeting token and its 1-hop neighbours in the dependency tree. As shown in Figure 4 and Figure

Figure 3: Syntax Contribution. Figure 4: Prune with DGLSTM. Figure 5: Prune with C-GCN.

5, masking 1-hop neighbours in the dependency tree achieves the best performance, which indicates the relevant importance of tokens themselves in NER task on OntoNotes5.0 dataset. Moreover, by comparing the two methods of information aggregation in the training stage, we draw a conclusion that the approach in Equation 3 can make better use of dependency structures.

Our proposed causal model aims to alleviate spurious correlations learned from an imbalanced dataset by learning to distinguish the main effect from the side effect, and hence our model can greatly benefit the recall of tail classes, leading to an improvement for the Mean F1. However, F1 depends more on the performance of head classes, which is not the focus of our model, although our `CounterFactual-IE` is able to get a comparable F1 score on five datasets. Interested readers can refer to details in the Appendix.

4   RELATED WORK

Long-tailed Information Extraction: Information extraction tasks, such as relation extraction (Zeng et al., 2014; Peng et al., 2017; Quirk & Poon, 2017), named entity recognition (Lample et al., 2016; Chiu & Nichols, 2016), and event extraction (Nguyen & Grishman, 2015; Huang et al., 2018) are fundamental NLP tasks and have been extensively studied in recent years. Recent models (Lei et al., 2018; Zhang et al., 2019) leverage external rules or transfer knowledge from data-rich classes to the tail classes.

Re-balancing/Decoupling Models: Re-balancing approaches include Re-sampling strategies (Mahajan et al., 2018; Wang et al., 2020a) that aim to alleviate statistical bias from head classes, and re-weighting approaches (Milletari et al., 2016; Lin et al., 2017) which assign balanced weights to the losses of training samples from each class to boost the discriminability via robust classifier decision boundaries. These techniques may inevitably suffer the under-fitting/over-fitting issue to head/tail classes (Tang et al., 2020a). There are also recent studies (Kang et al., 2019) that decouple the representation learning and classifier, which effectively mitigate the performance loss caused by direct re-sampling.

Casual Inference Models: Causal inference (Pearl, 2009; Pearl et al., 2016) and counterfactuals have been widely used in psychology, politics and epidemiology for years. There are much much in computer vision society (Tang et al., 2020b; Abbasnejad et al., 2020; Tang et al., 2020a; Niu et al., 2020; Yang et al., 2020; Zhang et al., 2020; Yue et al., 2020), which use Total Direct Effect (TDE) analysis framework and counterfactuals for Scene Graph Generation (SGG), visual question answering, image captioning, and image classifications. Our methods differ from these previous works in two aspects: 1) We explore the syntax structures of texts for building different causal graphs, 2) Counterfactuals are generated based on a task-specific pruned dependency tree.

5   CONCLUSION

In this paper, we present `CounterFactual-IE`, a novel approach to tackling the long-tailed information extraction issues via counterfactual analysis in causal inference. Experimental results on five datasets across three IE tasks show the effectiveness of our approach in improving the performance for tailed classes. The future research directions include applying the proposed framework to more challenging long-tailed document-level IE tasks.

REFERENCES

Ehsan Abbasnejad, Damien Teney, Amin Parvaneh, Javen Shi, and Anton van den Hengel. Counterfactual vision and language learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10044–10054, 2020.

Anders Björkelund, Love Hafdell, and Pierre Nugues. Multilingual semantic role labeling. In *Proceedings of the Thirteenth Conference on Computational Natural Language Learning (CoNLL 2009): Shared Task*, pp. 43–48, 2009.

Léon Bottou, Jonas Peters, Joaquin Quiñonero-Candela, Denis X Charles, D Max Chickering, Elon Portugaly, Dipankar Ray, Patrice Simard, and Ed Snelson. Counterfactual reasoning and learning systems: The example of computational advertising. *The Journal of Machine Learning Research*, 14(1):3207–3260, 2013.

Laura Chiticariu, Yunyao Li, and Frederick R. Reiss. Rule-based information extraction is dead! long live rule-based information extraction systems! In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pp. 827–832, Seattle, Washington, USA, October 2013. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/D13-1079.

Jason P.C. Chiu and Eric Nichols. Named entity recognition with bidirectional LSTM-CNNs. *Transactions of the Association for Computational Linguistics*, 4, 2016.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

George Doddington, Alexis Mitchell, Mark Przybocki, Lance Ramshaw, Stephanie Strassel, and Ralph Weischedel. The automatic content extraction (ACE) program – tasks, data, and evaluation. In *Proceedings of the Fourth International Conference on Language Resources and Evaluation (LREC'04)*, Lisbon, Portugal, May 2004. European Language Resources Association (ELRA). URL http://www.lrec-conf.org/proceedings/lrec2004/pdf/5.pdf.

Jeffrey Flanigan, Sam Thomson, Jaime G Carbonell, Chris Dyer, and Noah A Smith. A discriminative graph-based parser for the abstract meaning representation. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1426–1436, 2014.

Claire Gardent, Anastasia Shimorina, Shashi Narayan, and Laura Perez-Beltrachini. The WebNLG challenge: Generating text from RDF data. In *Proceedings of the 10th International Conference on Natural Language Generation*. Association for Computational Linguistics, 2017.

Zhijiang Guo, Yan Zhang, and Wei Lu. Attention guided graph convolutional networks for relation extraction. In *Proc. of ACL*, 2019.

Xu Han, Pengfei Yu, Zhiyuan Liu, Maosong Sun, and Peng Li. Hierarchical relation extraction with coarse-to-fine grained attention. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2236–2245, 2018.

Lifu Huang, Heng Ji, Kyunghyun Cho, Ido Dagan, Sebastian Riedel, and Clare Voss. Zero-shot transfer learning for event extraction. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Melbourne, Australia, July 2018. Association for Computational Linguistics.

Zhanming Jie and Wei Lu. Dependency-guided lstm-crf for named entity recognition. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3853–3863, 2019.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2019.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *Proc. of ICLR*, 2017.

Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. Neural architectures for named entity recognition. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, San Diego, California, June 2016. Association for Computational Linguistics.

Kai Lei, Daoyuan Chen, Yaliang Li, Nan Du, Min Yang, Wei Fan, and Ying Shen. Cooperative denoising for distantly supervised relation extraction. In *Proceedings of the 27th International Conference on Computational Linguistics*, Santa Fe, New Mexico, USA, 2018. Association for Computational Linguistics.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019a.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X Yu. Large-scale long-tailed recognition in an open world. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2537–2546, 2019b.

Xuezhe Ma and Eduard Hovy. End-to-end sequence labeling via bi-directional lstm-cnns-crf. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1064–1074, Berlin, Germany, August 2016. Association for Computational Linguistics.

Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens van der Maaten. Exploring the limits of weakly supervised pretraining. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018.

Fausto Milletari, Nassir Navab, and Seyed-Ahmad Ahmadi. V-net: Fully convolutional neural networks for volumetric medical image segmentation. In *2016 fourth international conference on 3D vision (3DV)*, pp. 565–571. IEEE, 2016.

Thien Huu Nguyen and Ralph Grishman. Event detection and domain adaptation with convolutional neural networks. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pp. 365–371, Beijing, China, July 2015. Association for Computational Linguistics. doi: 10.3115/v1/P15-2060. URL https://www.aclweb.org/anthology/P15-2060.

Yulei Niu, Kaihua Tang, Hanwang Zhang, Zhiwu Lu, Xian-Sheng Hua, and Ji-Rong Wen. Counterfactual vqa: A cause-effect look at language bias. *arXiv preprint arXiv:2006.04315*, 2020.

Judea Pearl. *Causality*. Cambridge university press, 2009.

Judea Pearl, Madelyn Glymour, and Nicholas P Jewell. *Causal inference in statistics: A primer*. John Wiley & Sons, 2016.

Nanyun Peng, Hoifung Poon, Chris Quirk, Kristina Toutanova, and Wen tau Yih. Cross-sentence n-ary relation extraction with graph lstms. *Transactions of the Association for Computational Linguistics*, 5:101–115, 2017.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *Proc. of EMNLP*, 2014.

Sameer Pradhan, Alessandro Moschitti, Nianwen Xue, Hwee Tou Ng, Anders Björkelund, Olga Uryupina, Yuchen Zhang, and Zhi Zhong. Towards robust linguistic analysis using OntoNotes. In *Proceedings of the Seventeenth Conference on Computational Natural Language Learning*. Association for Computational Linguistics, 2013.

Chris Quirk and Hoifung Poon. Distant supervision for relation extraction beyond the sentence boundary. In *Proc. of EACL*, 2017.

Sunita Sarawagi. *Information extraction*. Now Publishers Inc, 2008.

Kaihua Tang, Jianqiang Huang, and Hanwang Zhang. Long-tailed classification by keeping the good and removing the bad momentum causal effect, 2020a.

Kaihua Tang, Yulei Niu, Jianqiang Huang, Jiaxin Shi, and Hanwang Zhang. Unbiased scene graph generation from biased training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3716–3725, 2020b.

Gokhan Tur, Dilek Hakkani-Tür, and Larry Heck. What is left to be understood in atis? In *2010 IEEE Spoken Language Technology Workshop*, pp. 19–24. IEEE, 2010.

David Wadden, Ulme Wennberg, Yi Luan, and Hannaneh Hajishirzi. Entity, relation, and event extraction with contextualized span representations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5788–5793, 2019.

Tao Wang, Yu Li, Bingyi Kang, Junnan Li, Junhao Liew, Sheng Tang, Steven Hoi, and Jiashi Feng. The devil is in classification: A simple framework for long-tail instance segmentation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020a.

Xiaozhi Wang, Ziqi Wang, Xu Han, Wangyi Jiang, Rong Han, Zhiyuan Liu, Juanzi Li, Peng Li, Yankai Lin, and Jie Zhou. Maven: A massive general domain event detection dataset. In *arXiv: https://arxiv.org/abs/2004.13590*, 2020b.

Xu Yang, Hanwang Zhang, and Jianfei Cai. Deconfounded image captioning: A causal retrospect. *arXiv preprint arXiv:2003.03923*, 2020.

Zhongqi Yue, Hanwang Zhang, Qianru Sun, and Xian-Sheng Hua. Interventional few-shot learning. In *NeurIPS*, 2020.

Daojian Zeng, Kang Liu, Siwei Lai, Guangyou Zhou, and Jian Zhao. Relation classification via convolutional deep neural network. In *Proc. of COLING*, 2014.

Dong Zhang, Hanwang Zhang, Jinhui Tang, Xiansheng Hua, and Qianru Sun. Causal intervention for weakly-supervised semantic segmentation. In *NeurIPS*, 2020.

Ningyu Zhang, Shumin Deng, Zhanlin Sun, Guanying Wang, Xi Chen, Wei Zhang, and Huajun Chen. Long-tail relation extraction via knowledge graph embeddings and graph convolution networks. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.

Yuhao Zhang, Victor Zhong, Danqi Chen, Gabor Angeli, and Christopher D. Manning. Position-aware attention and supervised data improve slot filling. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, 2017.

A APPENDIX

A.1 DATASET STATISTICS

We give the statistics of five datasets as follows in Table 4. We follow the (Liu et al., 2019b) to split the training set as Few-shot(Few), Medium-shot(Medium) and Many-Shot(Many). We split the dataset based on the distribution of class types and numbers. Details are given in Table 5.

A.2 EXPERIMENT SETTINGS

We use spaCy[2] to generate the dependency tree, and POS tagging for a sentence. The hyperparameters that we used on three tasks are listed as follows.

---

[2] https://spacy.io/

Table 4: Data Statistics

Dataset	Task	Train	Dev	Test	Class Types
OntoNotes5.0	Named Entity Recognition	59924	8528	8262	18
ATIS	Named Entity Recognition	4479	498	893	79
ACE2005	Event Detection	19216	901	676	33
MAVEN	Event Detection	32431	8042	9400	168
NYT24	Relation Extraction	50577	5619	5000	24

Table 5: Number of instances per class for dataset splitting

Dataset	Task	Few	Medium	Many
OntoNotes5.0	Named Entity Recognition	≤ 4000	$4000 \sim 10000$	≥ 10000
ATIS	Named Entity Recognition	≤ 30	$30 \sim 100$	≥ 100
ACE2005	Event Detection	≤ 30	$30 \sim 150$	≥ 150
MAVEN	Event Detection	≤ 100	$100 \sim 1000$	≥ 1000
NYT24	Relation Extraction	≤ 100	$100 \sim 200$	≥ 200

A.3   MORE EXPERIMENTAL RESULTS

For the NER and ED tasks, we report more detailed comparisons on Ontonotes5.0, MAVEN, ACE2005, and ATIS datasets. We also report the result for RE in Table 13.

Table 6: Detailed Hyper-parameters for the NER task.

Batch size	32
Learning rate	0.005
Decay rate	0.90
Gradient clipping	5
Optimizer	Adam
Word embedding dimension	300
Input dropout	0.3
RNN Hidden size	200
RNN Layer size	1
RNN dropout	0.3
POS dim	30
Deprel dim	30
α(OntoNotes5.0)	0.9
α(ATIS)	1.2

Table 7: Detailed Hyper-parameters for the ED task.

Batch size	32
Learning rate	0.005
Decay rate	0.90
Gradient clipping	5
Optimizer	Adam
Word embedding dimension	300
Input dropout	0.3
RNN Hidden size	200
RNN Layer size	1
RNN dropout	0.3
POS dim	30
NER dim	30
Deprel dim	30
α	2

Table 8: Detailed Hyper-parameters for the RE task.

Batch size	50
Learning rate	0.03
Decay rate	0.90
Gradient clipping	5
Optimizer	SGD
Word embedding dimension	300
Input dropout	0.5
RNN Hidden size	300
RNN Layer size	2
RNN dropout	0.2
Block Number	2
Coarse-grained Hidden Size	300
Fine-grained Hidden Size	300
GCN first sub-layers	2
GCN second sub-layers	4
GCN dropout	0.3
Pooling L2	0.002

Table 9: Evaluation results on the ATIS dataset for the named entity recognition.

Model	Few		Medium		Many		Overall		
	MR	MF1	MR	MF1	MR	MF1	MR	MF1	Micro F1
BiLSTM	66.2	69.0	89.8	85.9	93.0	92.2	84.2	83.1	94.0
BiLSTM+CRF	58.1	60.4	87.4	83.5	93.0	**93.5**	81.0	80.2	95.2
CGGCN (Zhang et al., 2017)	63.2	65.3	87.3	83.2	91.8	89.3	82.0	80.1	91.8
Dep-Guided LSTM (Jie & Lu, 2019)	60.6	65.4	94.1	90.4	93.2	92.9	84.6	84.3	93.8
Focal Loss	48.9	49.8	89.3	84.6	91.1	89.8	78.7	76.6	90.0
cRT	68.1	71.7	92.3	88.0	92.8	92.2	85.7	84.8	94.2
τ - Normalization	64.8	68.0	89.9	86.2	93.0	92.5	83.9	83.1	94.0
LWS	66.2	69.1	89.9	85.9	93.0	92.2	84.3	83.2	94.0
TDE (Tang et al., 2020b)	67.5	67.1	95.3	89.4	93.7	93.5	87.1	84.5	94.4
Ours (Glove)	**71.8**	**73.1**	**95.6**	**91.4**	**94.3**	93.5	**88.6**	**87.0**	**95.3**
BERT(Devlin et al., 2019)	52.3	56.1	96.0	**90.6**	92.9	**92.7**	82.9	81.7	94.5
Roberta(Liu et al., 2019a)	**60.2**	61.1	93.8	89.1	93.1	92.2	84.3	82.3	94.3
BERT+GCN (Wadden et al., 2019)	53.3	56.6	95.4	89.6	93.1	92.2	83.0	81.3	94.5
Ours (BERT)	58.8	**62.2**	**97.2**	89.1	**93.6**	92.4	**85.5**	82.6	**94.6**

Table 10: Evaluation results on the MAVEN dataset for the event detection.

Model	Few		Medium		Many		Overall		
	MR	MF1	MR	MF1	MR	MF1	MR	MF1	Micro F1
BiLSTM	36.5	40.7	78.3	79.9	80.4	82.3	67.1	69.5	83.0
BiLSTM+CRF	43.4	46.8	79.0	79.8	82.3	83.0	69.6	71.1	83.3
CGGCN (Zhang et al., 2017)	49.7	51.7	81.8	80.8	82.6	82.1	73.1	73.0	83.6
Dep-Guided LSTM (Jie & Lu, 2019)	44.7	45.4	76.5	78.2	75.9	78.9	67.8	69.3	83.0
Focal Loss	45.4	51.5	78.6	81.3	85.4	87.2	70.3	73.8	**84.9**
cRT	49.7	55.4	78.4	81.3	82.1	85.0	71.0	74.6	**84.9**
τ - Normalization	21.1	26.7	60.0	68.5	74.4	80.0	51.0	58.4	76.0
LWS	33.3	38.7	77.6	79.7	81.6	81.7	65.9	68.7	83.0
TDE (Tang et al., 2020b)	39.8	36.2	83.3	78.0	87.8	85.2	71.9	67.4	79.1
Our (Glove)	**60.4**	**57.4**	**86.8**	**82.2**	**89.1**	86.6	**79.8**	**76.0**	84.6
BERT (Devlin et al., 2019)	38.1	39.3	**86.3**	84.0	**90.6**	88.3	73.5	72.3	86.2
Roberta (Liu et al., 2019a)	**43.1**	43.8	**86.3**	**84.1**	90.2	88.4	**75.0**	**73.6**	**86.2**
BERT+GCN (Wadden et al., 2019)	40.9	42.0	86.0	83.6	90.0	**88.6**	74.1	72.8	86.1
Ours (BERT)	**43.1**	**45.0**	80.7	80.5	88.3	87.6	71.3	71.7	85.0

Table 11: Evaluation results on the ACE2005 dataset for the event detection.

Model	Few		Medium		Many		Overall		
	MR	MF1	MR	MF1	MR	MF1	MR	MF1	Micro F1
BiLSTM (Chiu & Nichols, 2016)	34.2	35.6	55.1	58.2	64.9	67.0	52.3	54.8	66.7
BiLSTM+CRF (Ma & Hovy, 2016)	41.4	45.1	49.8	52.2	70.1	70.5	51.8	54.1	68.2
C-GCN (Zhang et al., 2017)	41.4	44.1	51.2	55.8	66.4	71.2	52.0	56.1	71.2
Dep-Guided LSTM (Jie & Lu, 2019)	42.8	41.7	49.8	56.0	71.1	71.6	52.4	55.8	70.7
Focal Loss (Lin et al., 2017)	38.6	42.9	50.7	58.8	74.6	**76.0**	52.6	58.5	**72.7**
cRT (Kang et al., 2019)	44.8	47.4	58.8	60.1	68.8	68.5	57.6	58.9	71.4
τ - Normalization (Kang et al., 2019)	34.3	35.6	50.9	53.8	**82.7**	68.3	53.3	52.5	67.6
LWS (Kang et al., 2019)	34.3	35.6	61.2	**60.2**	76.8	71.7	58.2	56.9	67.5
TDE (Tang et al., 2020b)	34.3	33.9	61.5	59.7	77.4	73.3	58.5	56.5	72.0
Our (Glove)	**47.1**	**49.7**	**64.3**	59.9	80.5	73.3	**63.5**	**60.2**	71.5
BERT (Devlin et al., 2019)	47.6	48.9	67.8	67.5	84.5	76.8	66.5	65.1	77.6
Roberta (Liu et al., 2019a)	47.6	47.7	73.7	72.6	86.0	**80.9**	70.2	68.6	**80.4**
BERT+GCN (Wadden et al., 2019)	45.2	47.5	**78.9**	**77.5**	**88.2**	80.3	73.1	71.3	80.3
Ours (BERT)	**61.9**	**63.2**	76.5	76.6	85.3	80.7	**74.9**	**74.4**	80.1

Table 12: Evaluation results on the OntoNotes5.0 dataset for the named entity recognition.

Model	Few		Medium		Many		Overall		
	MR	MF1	MR	MF1	MR	MF1	MR	MF1	Micro F1
BiLSTM (Chiu & Nichols, 2016)	67.5	**69.9**	72.6	75.3	88.1	85.4	76.4	76.8	83.7
BiLSTM+CRF (Ma & Hovy, 2016)	60.7	63.6	65.3	69.1	86.9	86.9	71.6	73.5	**85.5**
C-GCN (Zhang et al., 2017)	68.3	69.8	69.1	72.9	90.9	86.6	77.3	76.8	**85.5**
Dep-Guided LSTM (Jie & Lu, 2019)	61.8	69.3	70.2	73.7	89.8	84.3	74.1	75.8	84.0
Focal Loss (Lin et al., 2017)	64.1	65.5	69.9	71.2	87.7	84.7	74.2	73.9	85.2
cRT (Kang et al., 2019)	64.1	68.5	73.9	75.3	88.0	85.2	75.0	76.1	83.6
τ - Normalization (Kang et al., 2019)	61.1	66.7	72.8	**76.4**	88.0	85.7	73.5	75.7	84.9
LWS (Kang et al., 2019)	58.7	64.9	71.6	76.1	87.6	85.2	72.1	74.7	84.9
TDE (Tang et al., 2020b)	71.9	68.8	77.9	74.8	91.2	86.7	80.4	76.7	83.6
Ours (Glove)	**76.7**	68.9	**83.6**	76.2	**92.0**	**87.6**	**83.8**	**77.3**	85.4
BERT (Devlin et al., 2019)	77.7	76.5	81.4	78.6	94.0	90.7	84.6	82.4	88.7
Roberta (Liu et al., 2019a)	78.7	**79.5**	84.8	**85.1**	**96.3**	**93.1**	86.5	**85.7**	**90.7**
BERT+GCN (Wadden et al., 2019)	80.2	77.7	81.1	77.3	93.9	90.4	85.6	82.6	88.6
Ours (BERT)	**80.6**	79.1	**85.1**	80.4	94.5	91.4	**86.7**	84.1	88.9

Table 13: Evaluation results on the NYT24 dataset for the relation extraction task.

Model	Few		Medium		Many		Overall		
	MR	MF1	MR	MF1	MR	MF1	MR	MF1	Micro F1
C-GCN (Zhang et al., 2017)	24.0	26.7	60.6	65.5	58.8	59.1	51.2	52.6	74.4
Focal Loss (Lin et al., 2017)	52.0	48.3	78.0	74.8	63.5	64.0	62.9	61.9	74.5
cRT (Kang et al., 2019)	66.0	24.2	75.2	58.5	64.6	61.9	65.6	50.5	68.0
τ - Normalization (Kang et al., 2019)	40.0	40.0	59.0	64.7	57.1	57.7	53.5	54.6	74.3
LWS (Kang et al., 2019)	40.0	40.0	59.0	64.7	57.1	57.6	53.5	54.6	74.3
TDE (Tang et al., 2020b)	60.0	57.1	66.6	65.2	60.1	60.2	61.0	60.2	70.0
Ours (Glove)	**68.0**	**68.6**	67.0	70.5	59.3	60.3	65.3	63.6	72.3