Physical Reasoning and Object Planning for Household Embodied Agents

Abstract

In this study, we explore the sophisticated domain of task planning for robust household embodied agents, with a particular emphasis on the intricate task of selecting substitute objects. We introduce the **C**ommonSense **O**bject **A**ffordance **T**ask (**COAT**), a novel framework designed to analyze reasoning capabilities in commonsense scenarios. This approach is centered on understanding how these agents can effectively identify and utilize alternative objects when executing household tasks, thereby offering insights into the complexities of practical decision-making in real-world environments.Drawing inspiration from human decision-making, we explore how large language models tackle this challenge through three meticulously crafted commonsense question-and-answer datasets, featuring refined rules and human annotations. Our evaluation of state-of-the-art language models on these datasets sheds light on three pivotal considerations: 1) aligning an object's inherent utility with the task at hand, 2) navigating contextual dependencies (societal norms, safety, appropriateness, and efficiency), and 3) accounting for the current physical state of the object. To maintain accessibility, we introduce five abstract variables reflecting an object's physical condition, modulated by human insights to simulate diverse household scenarios. Our contributions include insightful Object-Utility mappings addressing the first consideration and two extensive QA datasets (15k and 130k questions) probing the intricacies of contextual dependencies and object states. The datasets, along with our findings, are accessible at: `https://github.com/com-phy-affordance/COAT`. This research not only advances our understanding of physical commonsense reasoning in language models but also paves the way for future improvements in household agent intelligence.

1 Introduction

Humans, as beings innately attuned to their surroundings, traverse a world where conversations, decisions, behaviors, and understanding are deeply embedded in the underlying fabric of situation. Their engagement with the world entails commonsense (background) knowledge about entities–properties, spatial relations, events, causes and effects, and other social norms ((McCarthy, 1959); (Winograd, 1972); (Davis & Marcus, 2015)). The importance of situational awareness is starkly evident in our daily tasks, where choosing objects for specific activities showcases our adaptability to different settings. Consider the straightforward task of cutting a cake—how do we determine which object is suitable for this task? When a person needs to select an object to accomplish this task, there can be an array of factors that might affect our choice. For example: we must choose something that is capable of cutting (*Utility*), suitable for cutting a cake

(*contextual appropriateness*), and likely in an appropriate physical condition to be used (*physical state*). These considerations would be to ensure the appropriateness, ease, and safety of those cutting the cake as well as who will eat the cake. These considerations although might seem trivial and intuitive to us humans, are still an important aspect to consider when developing embodied household agents. Such reasoning capabilities can be potentially leveraged by embodied agents to generate action plans for human requirements represented in natural language. In this work, we propose a **C**ommon**S**ense **O**bject **A**ffordance Task: a textual physical commonsense task to evaluate most appropriate object selection capabilities in the presence of various alternative objects.

Figure 1: We divide the whole decision-making process into 3 phases. Pruning out options firstly based on **Utility** then **Contextual Appropriateness** and finally on **Physical State**. This shows human adeptness in comparing appropriateness across an array of factors and coming up with a substitute object even in the absence of the ideal object [*Cake Knife*]. Our work provides QA datasets about this type of commonsense reasoning

Recent advancements in large language models (LLMs) (Zhu et al., 2023; Peng et al., 2023; Zhang et al., 2023; Brown et al., 2020; Chowdhery et al., 2022; Touvron et al., 2023; OpenAI, 2023) have significantly enhanced our ability to extract rich commonsense knowledge from extensive web data. To analyze this task and evaluate the current capabilities of Language Models across such human commonsense-oriented reasoning; we develop this task as a decision-making process spanning across 3 major aspects: **Utility**: The concept of *Utility*, a focal point in previous research Speer et al. (2017), elucidates our understanding of an object's functionality in a variety of situations. Although ConceptNet (Speer et al., 2017) has been a crucial tool for identifying object-utility relationships, its nature as a human-compiled knowledge graph has led to the pursuit of more dynamic sources. We curate Object-Utility mappings pertaining to this aspect and use this to further evaluate decision-making across both remaining aspects. **Context**: Our decision-making extends beyond mere utility. To account for the various situational factors such as safety, social norms adherence, effort optimization, efficiency, and situational appropriateness; we introduce the second aspect as: *contextual*

appropriateness This adeptness in judgment arises from our ingrained commonsense, sculpted by experience and intuitive physical understanding. To evaluate the reasoning capabilities of various language models across this aspect, we generate Object-Concept-Task mappings and curate a QA dataset consisting of 15K MCQ question-answer pairs. **Physical State**: Previous work Li et al. (2023) has shown how object choice depends on various physical variables. However, we humans don't think in terms of these variables. In order to make this aspect more human commonsense-oriented, we add a layer of abstraction and introduce 5 abstract variables to depict the current physical state of the object of interest. To observe how the object usability evolves with various abstract physical state variations, we generate human preference mappings and curate 2 QA datasets consisting of 130K MCQ question-answer pairs.

To illustrate an example of using these 3 aspects to select the best feasible object, let's continue with the task of cutting a cake where the following objects are available to use: a Broken Knife, Clean Scissors, a Clean Pillow, and a Clean Knife. As we begin, we subconsciously evaluate each object's utility for the task, and thus shift our focus primarily on Knife and Scissors. Further analysis typically leads to the dismissal of Scissors as a suitable tool for cake cutting. Finally, upon considering the physical state of Knives, the Clean Knife emerges as the obvious choice. This scenario highlights the three key factors humans prioritize when selecting an object for a task: the ***utility of the object***, its ***contextual appropriateness***, and its ***current physical state***.

Such commonsense reasoning capabilities not only allow us to judge the appropriateness of an object in the context of the given task but also help us in successfully coming up with an appropriate substitute object in the absence of the most ideal object(Here: *Cake Knife*). Such skills if equipped with embodied agents, will enhance their reasoning capabilities and make them adept in planning tasks in scenarios where the ideal object is not available. .

Main Contributions: In this study, we made the following contributions:

- Creation and provision of human-preference mappings across all 3 aspects of the **C**ommon**S**ense **O**bject **A**ffordance **T**ask(COAT)

- Introduction of three major novel CommonSense-based QA Datasets, facilitating an in-depth analysis of how object usability evolves under different contextual scenarios and physical states

- Evaluation of Large Language Model baselines on these datasets, accompanied by a detailed analysis of their performance in multi-step abstract reasoning scenarios.

2 Dataset Creation

To systematically investigate the capacity of LLM to conduct human-style physical commonsense reasoning and preferences across three crucial factors, we have devised an experimental framework centered around 75 household tasks, carefully curated to span 22 distinct utilities. The experiment involves a diverse inventory of 100 objects sourced from the AI2Thor Simulator (Speer et al., 2017), ensuring relevance and diversity within a household context.

1. `Tasks`: are high-level household activities that could be accomplished by a human or embodied agent. Example: `Cutting a Cake`. See Task List
2. `Utilities`: are extremely low-level utilities that could be assigned to a High-level task. Like, for the example of `Cutting Cake`, the utility that gets activated is `Cutting`. See Table 2a

3. `Objects`: are a subset of objects available in AI2Thor (Kolve et al., 2022) Simulator. See Table 2b

Utilities		
Carrying	Comfort	Heating(vessel)
Cleaning	Washing	Mixing(tool)
Disposing	Cutting	Mixing (vessel)
Storage	Entertainment	Heating(source)
Reading	Breaking	Increasing Height
Eating	Writing	Physical Activity
Decoration	Light Source	Surface Support

Objects		
Bowl	Bed	Pan
DishSponge	SinkBasin	Spoon
GarbageCan	Knife	Cup
Fridge	Laptop	Microwave
Newspaper	BaseballBat	Chair
Apple	Pen	Dumbell
Statue	Floor Lamp	CounterTop

(a) A representational subset of utilized Utilities (b) A representational subset of utilized Objects

The following section gives an overview of the Annotation Tasks and the process of creation of CommonSense Reasoning Datasets.

2.1 Human Preference Collection

2.1.1 Utility

Incorporating GPT3.5-turbo (Brown et al., 2020) along with human commonsense annotations, we meticulously established a mapping between utilities and objects. These are called `Utility Objects`. Notably, each object may be associated with multiple utilities, and conversely, a single utility can be linked to various objects. Table 8 provides an overview of the utilities along with their associated objects utilized in our experiments. More Information about the annotation process can be found in Appendix D

2.1.2 Contextual Appropriateness

In evaluating object utility, it is crucial to recognize that suitability for specific tasks can vary significantly. Take, for example, the multifaceted use of a candle. While it possesses the inherent ability to generate heat, employing a candle for the purpose of heating soup introduces a range of practical limitations. This observation underscores the complexity of human preference and decision-making in the context of object utility. Key factors influencing these choices include efficiency (as illustrated by the impracticality of using a candle for heating soup), safety considerations (such as the risks associated with standing on an armchair), social norms and constructs (exemplified by the unconventional choice of serving wine in a bowl), and the overall appropriateness of an action (e.g., the disposal of eggshells in a sink basin). To systematically explore these dynamics, we engaged human annotators in a study designed to assess the selection of appropriate objects for specified tasks and utilities

2.1.3 Physical State

The selection of objects for specific tasks is influenced not only by intangible factors such as safety and social constructs but also by the object's current physical state. Prior research, including the works of Li et al. (2023) and Gao et al. (2023), has employed various physical parameters to examine Language Learning Models' (LLMs) comprehension of an object's physical attributes. In our study, we shift the focus to task planning under non-ideal conditions, necessitating reasoning about potential substitute objects. To this end, we have

developed five distinct variables, each represented by abstract symbolic terms. These variables have been derived directly from the AI2Thor Simulator, facilitating their broader applicability and potential integration into the burgeoning field of Embodied AI. Table 1 delineates these variables and their corresponding abstract values. Here, `Already In Use` variable is used to represent the availability of an object for use. Some examples of an object in `reversible-using` state are: the object getting recharged, a wet object or an object in a reversible state (meaning it will need time to get back to the ideal state or is temporarily being used by someone else). Whereas in an `irreversible-using` state, the object could be broken, depleted, out of stock, and thus is in an irreversible state of use. Further details about the chosen physical variables are elaborated in Appendix A.1

Variables	Abstract Values
material	Metal, Wood, Plastic, Glass, Ceramic, Stone, Wax, Fabric, Rubber, Food, Paper Sponge, Organic, Soap
mass	Light, Medium, Heavy, Super-Heavy
temperature	Cold, RoomTemp, Hot
already in use	Free, Reversible-Using , Irreversible-Using
condition	Dirty, Clean, Broken

Table 1: Abstract Values for Various Variables

Gathering Common Object Configuration In the context of this study, a `Configuration` denotes the physical state of an object characterized by five variables. While a wax chair might be conceivable in the realm of Madame Tussauds, it remains highly improbable in everyday household scenarios. Thus to ensure the relevance of configurations to common household scenes, human annotators were tasked with selecting plausible and frequently occurring variable values for each object. (See Appendix D)

Ranking Object Configurations In our study, we not only provided configurations that occur commonly but also tasked the annotators with categorizing the configurations of an object into three distinct classes: `Ideal`, `Moderate`, and `Bad`. This classification was predicated on their assessment of the anticipated time required for an agent to commence the task with a given object configuration. Utilizing these categorizations, we constructed two comprehensive datasets comprising 130,000 questions specifically designed to assess the physical commonsense reasoning capabilities of Large Language Models. Further details on this process are elaborated in Appendix D

2.2 CommonSense QnA Datasets

Based on `Contextual Appropriateness` and `Physical State`. We created 3 CommonSense QA datasets.

1. **Task-0**[1]: This experiment was based on pruning *Objects* based on contextual factors affecting the appropriateness of an object for a particular task. We utilized ***Object Level Dataset*** for its evaluation.

2. **Task-1** & **Task-2**: These experiments were based on pruning out Object Configurations (Physical State) represented by 5 symbolic variables. We utilized ***Variable Level Datasets*** for its evaluation.

---

[1]These are different from the tasks(activities) used to curate datasets

Figure 3: A mapping created between Tasks and Concepts was utilized to sample out <Task,Utility> combination to frame a question for all 3 datasets (1 Object Level, 2 Variable Level)

2.2.1 Object Level Dataset

To evaluate the reasoning capabilities of LLM across choosing objects over contextual factors we curate an Object Level QA dataset. Here, previously recorded Context Mappings were kept as Ground Truth. (See Annotation Task 2.1.2)

Question   Every question can be assigned a <Task, Utility> combination and was framed in the way shown below:

Question

What object would you be choosing for <**utility**> when you are tasked to <**task**>?

Options   Based on the sampling strategy and the number of options provided in the prompt, we created **4** variations of object level dataset. An example of such variation is shown below.

1. **Variation-1** : For each question, we randomly sampled **1 context object** and **1 utility object** both belonging to the same utility.[2]

Example Task 0 Variation 1

Question ID: 1,
Utility: heating(source),
Question: Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?
Options:

    (A) Toaster

    (B) StoveBurner

Correct Answer: B

---

[2]Details about other variations for Task 0,1,2 can be found here Appendix B

2.2.2 Physical Configuration Level Dataset

Based on `Common Configurations` generated in the annotation task [2.1.3], we create 2 Variable Level QA datasets to analyze the reasoning capabilities of Language Models on pruning out options based on their current physical state. The 2 datasets differ in the level of difficulty and the level of reasoning required to answer the questions correctly. We describe the creation process in this section. The question in both datasets remains the same as that of Object Level Dataset However, unlike the first dataset where the options were objects, this time we give various `Configurations` of `Context Objects` as options.

Configuration

object name: Microwave, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal **already in use**: free **condition**: clean

---

Here, a distinct approach is employed compared to the `Object level Dataset`, where Context Objects were previously sampled randomly based on a combination of the question's `Task` and `Utility`. In this study, we have classified the configurations of Context Objects into three broad categories: "Ideal," "Moderate," and "Bad." Each category is defined by specific annotation variables that delineate their characteristics. The "Ideal" category represents configurations in their optimal states, facilitating the specified task without the need for additional adjustments. In contrast, the "Moderate" category includes configurations that deviate from these ideal states, resulting in both time and material costs for their utilization. The models assess these options based on their estimated penalties. Lastly, the "Bad" category comprises configurations that render the Context Objects ineffective, even when considering potential penalties. Both "Moderate" and "Bad" configurations are grouped under Sub-Optimal Configurations, offering a nuanced understanding of the varying degrees of object usability.

By sampling options from these 3 sets of configurations [2.1.3], we divide our effort into 2 datasets:

A. Ideal Configuration Dataset   In alignment with its name, the "Ideal Configuration" dataset involves questions with the correct answer as `Ideal Configuration` of `Context Object` of the question's associated `<Task,Utility>` combination. To systematically analyze the behavior of models, we introduce 12 distinct variations of this dataset. The creation of these variations is designed to progressively augment the complexity of the datasets, facilitating a comprehensive analysis of model behaviors. Each of the 12 variations comprises approximately 5,000 question-answer pairs, with differing counts of options—ranging from 5 options to 2 options per question. Along with the varying number of options, we also ablated on various sampling techniques. This deliberate variation in the number of options aims to evaluate the impact on success rates of Large Language Models (LLMs) as the level of reasoning complexity increases. Whereas, the different sampling techniques help us study their behavior concerning different object distribution.

Process: To create these 12 variation datasets, we sampled a `Task` for n number of times, where n is proportional to the total count of all Commonly Occurring Configurations of its `Utility Objects`. [Annotation Task 2.1.1] For a given Question's `<Task, Utility>` Combination, we randomly sample a Context Object from the pool of Context objects. (obtained from 2.1.2). An example of sampling the remaining options is explained below:

For 5 option datasets:

1. **Variation-1** : randomly selected Context Object's Ideal Configuration + 4 randomly sampled sub-optimal configurations of the `same` Context Object
2. **Variation-2** : randomly selected Context Object's Ideal Configuration + 2 randomly sampled sub-optimal configurations of the `same` Context Object + 2 randomly sampled sub-optimal configurations of `different` Context Object belonging to the same `<Task,Utility>` combination [3]

Example for Task 1 Variation 1

Question ID: 1,
Utility: `heating(source)`,
Question: `Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?`
Options:

(A) **object name**: `Microwave`, **mass**: `super-heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `free`, **condition**: `clean`

(B) **object name**: `StoveBurner`, **mass**: `super-heavy`, **temperature**: `RoomTemp`, **material**: `Metal` **already in use**: `irreversible-using`, **condition**: `dirty`

(C) **object name**: `CoffeeMachine`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal` **already in use**: `irreversible-using`, **condition**: `dirty`

(D) **object name**: `Microwave`, **mass**: `super-heavy`, **temperature**: `RoomTemp`, **material**: `Metal` **already in use**: `reversible-using`, **condition**: `clean`

(E) **object name**: `Microwave`, **mass**: `super-heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `irreversible-using`, **condition**: `broken`

Correct Answer: A

B. Sub-Optimal Configuration Dataset   The process of selecting an ideal configuration, while challenging for language models, typically does not require intricate multi-step reasoning or the consideration of a wide range of factors. To more rigorously evaluate their reasoning abilities, particularly when faced with only sub-optimal options, we have intentionally excluded all ideal configurations from our sampling methodology. This deliberate exclusion necessitates that the models engage in more sophisticated reasoning, considering various physical state variables, thereby highlighting their capacity for abstract reasoning. By focusing exclusively on sub-optimal configurations, this methodological shift enables a more thorough investigation into the language models' ability to navigate and reason through complex scenarios in the absence of clear-cut ideal solutions.

Process: To comprehensively assess language models' abstract reasoning capabilities when confronted with sub-optimal configurations, we create another `Variable Level QA dataset` and introduce 14 variations of this dataset. Like the previous dataset, each dataset is constructed using distinct sampling strategies and by varying number of options. Across all 14 datasets, we maintain a consistent structure of nearly 5,000 questions.

---

[3] The remaining variations in sampling techniques and option count can be found in Appendix B

Each question in this dataset variation is associated with a `Task` and `Utility` combination. While the set of questions remains consistent with previous datasets, the sampling of each task is now proportional to the count of "Moderate Configurations + Bad Configurations" (i.e the count of Sub-Optimal Configurations for that question's associated <Task, Utility> combination). An example of 2 sampling techniques used for generating variation datasets is explained below:

For 5 option dataset

1. **Variation-1**: We sample all 5 options from Moderate Configurations of the Context object of the question's associated <Task,Utility> combination.

2. **Variation-2**: We sample 4 options from Moderate Configurations and 1 option from the Bad Configurations of the Context object of the question's associated <Task,Utility> combination. [4]

Example Task 2 Variation 1

Question ID: 1,
Utility: `heating(source)`,
Question: `Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?`
Options:

    (A) **object name**: `CoffeeMachine`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `reversible-using`, **condition**: `dirty`

    (B) **object name**: `StoveBurner`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `reversible-using`, **condition**: `clean`

    (C) **object name**: `StoveBurner`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `free`, **condition**: `dirty`

    (D) **object name**: `CoffeeMachine`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `reversible-using`, **condition**: `clean`

    (E) **object name**: `Microwave`, **mass**: `heavy`, **temperature**: `RoomTemp`, **material**: `Metal`, **already in use**: `reversible-using`, **condition**: `clean`

Correct Answer: C

---

[4]The remaining variations in sampling techniques and option count can be found in Appendix B

3 Experimental Setup & Results

Upon curation of Datasets, we evaluate various Large Language Models to benchmark their performance on:

1. **R1**: Object-level Commonsense Reasoning (performance on various contextual factors including: social constructs, feasibility aspects, etc.)

2. **R2**: Physical State level Commonsense Reasoning (performance on commonsense understanding of various physical variables and how they affect decision making)

We evaluate and compare the performances of various large Language Models on the following metrics:

1. **Accuracy**: The fraction of a number of questions answered correctly by the Language Model.

2. **Bad Rate**: The fraction of questions in which the chosen answer belonged to the "Bad" configuration pool.

3.1 Dataset Summary

Task	#Variation	#Q	Av	Options	GT
0	4	15.5K	3.8K	Utility Objects	Context Objects [Õ]
1	12	58,7K	4.9K	Õ's Configurations	Õ's Ideal Configurations
2	14	68.9K	4.9K	Õ's SuboptConfigurations	Õ's BestSubopt Configurations

Table 2: Summary of Datasets Used for Experiments

3.2 Glossary

Term	*Definition*
objects	a set of 100 household objects
utilities	a set of 22 abstract utilities
tasks	a set of 75 household activities
question	a `<Task,Utility>` combination indicating the specific task aspect to emphasize
variable	a symbolic variable used to explain an object's physical state
configuration	complete description of an object using 5 symbolic variables
utility-mapping	mapping between utility and object; facilitates `Utility-Objects`
context-mapping	mapping between task and object; facilitates `Context-Objects`
ideal-configuration	A state where an object is ready to perform a task without requiring additional time or effort, marked by the simultaneous occurrence of all ideal variable values in its description
moderate-configuration	A state requiring additional effort to reach an ideal condition for task performance, marked by the presence of moderate variable values.
bad-configuration	An inoperative state of an object with irreparable issues, marked by the presence of "Bad Variable" values.
sub-optimal configuration	group of "Moderate" and "Bad" configurations

---

[4]#Q=question count; Av=average question count

3.3 Results

Task 0 Analysis: We observe from Table 3; that the performance of GPT3.5-Turbo and PaLM outperform other models with a much smaller number of parameters. This may be attributed to their size as well as the amount of internet data they've been trained on. They both showcased similar performance suggesting similar object-level reasoning capabilities suggesting an impressive object-level commonsense Reasoning. Even though the performance of every model was observed to be impressive; Mistral-7B outshone all other models of similar size as well as both 13B models. Upon analyzing the trend of average accuracy across various datasets for Task-0[Figure 4] we note an important trend implying a drop in accuracy as we increase the number of options. This suggests degradation in reasoning capabilities as the number of comparisons increases. This trend was observed in Task 1 and Task 2 as well[5]. Table 3 and Figure 4 provide a fair evaluation of the reasoning capabilities of Language Models over Object Level Affordance Reasoning tasks. **[R1]**

Model	Task-0 Variations			
	`2-opt`	`3-opt`	`4-opt`	`5-opt`
	v1	**v2**	**v3**	**v4**
PaLM	**90.0**	**74.2**	**68.3**	**65.0**
GPT3.5-Turbo	88.8	71.9	68.3	66.9
vicuna13B	71.0	54.5	49.3	46.2
LLama2-13B	**76.5**	**58.2**	**50.9**	**46.9**
Vicuna7b	51.0	34.5	28.5	26.5
Mistral-7B	**76.2**	**57.9**	**50.2**	**47.2**
ChatGLM-6B	62.0	42.0	34.2	27.6
ChatGLM2-6B	**62.9**	**44.6**	**34.3**	**35.4**

Table 3: Accuracies for Different Models when evaluated on Task-0 : Object Level QA Dataset

Figure 4: Average Accuracy of Various models on Task 0 as we increase option count

Task 1 Analysis: Table 4 summarizes the performance accuracy of different models on Task-1 Datasets where models were tasked to reason based on Physical Configuration of Objects (using `Ideal Configuration Datasets`). This task was aimed at judging if language models have an understanding of the difference between `Ideal Configuration` and Sub-Optimal Configurations. Here as well we witness the superior reasoning capabilities of GPT3.5-Turbo and PaLM, with the latter outperforming the former on each dataset by an average of **8.8%**. Amongst the smaller models, we see Mistral7B dominating all other 7B and 6B models with Vicuna7B and ChatGLM-6B performing very close to random performances. For 13B models, LLama2-13B showcased its superior reasoning capabilities and was on average **7.6%** more accurate than Vicuna13B. Here apart from the falling average accuracy with increasing options, we also notice some interesting behaviors when we increased the Object Diversity (i.e an increase in the number of sub-optimal configurations of `different` context object (of same `<Task, Utility>` Combination) other than the object who's Ideal Configuration is already in the options as the correct answer).

---

[5]See Figure 10a, 10b for trends in Task:1 and Task:2 Average Accuracies for each dataset type

Figure 5 illustrates the decreasing performance of all small models as we increase the Object Diversity in the

Model	Accuracy for Task_1 Variations⇑											
	5-option			4-option				3-option			2-option	
	v1	v2	v3	v4	v5	v6	v7	v8	v9	v10	v11	v12
PaLM (Chowdhery et al., 2022)	**85.9**	**74.6**	**81.4**	**89.4**	**80.0**	**80.5**	**84.8**	**92.0**	**84.6**	**88.5**	**95.0**	**91.7**
GPT3.5-Turbo (Brown et al., 2020)	74.0	64.5	70.7	78.9	69.5	69.3	75.2	89.2	78.0	82.6	91.3	80.4
Vicuna13B(Chiang et al., 2023)	44.5	44.0	36.4	53.2	50.9	53.3	42.9	60.6	59.9	54.1	67.8	66.6
LLama2-13B(Touvron et al., 2023)	**49.1**	**48.2**	**46.9**	**54.2**	**54.0**	**56.5**	**54.3**	**70.6**	**67.3**	**70.2**	**78.96**	**75.5**
Vicuna7B(Chiang et al., 2023)	24.0	24.6	24.5	31.7	32.8	32	32.2	40.5	39.2	41.0	56.8	56.8
Mistral-7B(Jiang et al., 2023)	**37.2**	**34.6**	**30.7**	**44.4**	**42.4**	**44.2**	**39**	**53.6**	**51.9**	**47.0**	**74.2**	**69.7**
ChatGLM-6B(Du et al., 2022b)	25.8	25.6	21.7	31.2	30.4	31.6	28.3	38.8	39.5	36.0	53.4	52.0
ChatGLM2-6B(Du et al., 2022a)	**31.8**	**31.4**	**30.0**	**39.4**	**40.9**	**40.6**	**40.5**	**54.0**	**53.4**	**51.2**	**68.0**	**66.0**

Table 4: Performance Accuracy for Various Models when evaluated on Task 1 (Ideal Configuration Dataset)

Figure 5: Comparative Plot showcasing the variations in Task:1 performances as we keep increasing the **Object Diversity** in Options from left to right.

options. This sheds light on the existing bias towards using a commonly used object rather than choosing an object after reasoning over every object's complete physical state. However, for big models like PaLM and GPT3.5-Turbo, we notice an improvement in accuracy with the Object Diversity at the extreme. Thus we could conclude that even though there was a drop in accuracy with more diverse options in PaLM and GPT3.5-Turbo; unlike the small models they were not answering excessively based on their bias towards the commonly used object.

Task 2 Analysis: Table 5 summarizes the performance of various models on Task-2, where the models were asked to reason over the best choice of object configurations from the Sub-Optimal Configuration Datasets. This task could be interpreted as finding the option that would be the least time-consuming and most appropriate amongst a variety of Sub-optimal Configurations of Context Objects of the question's <Task,Utility> combination. Here we sampled some moderate configurations (neither Ideal nor Bad)

Model	Accuracy for Task_2 Variations ⇑													
	5-option					4-option				3-option			2-option	
	v1	v2	v3	v4	v5	v6	v7	v8	v9	v10	v11	v12	v13	v14
PaLM	**32.4**	**38.0**	**46.3**	**55.3**	**64.1**	**40.8**	**47.6**	**57.7**	**63.2**	**52.4**	**64.8**	69.0	**70.2**	**80.7**
GPT3.5-Turbo	28.3	30.6	37.5	46.4	61.6	34.6	40.1	50.72	61.2	46.1	56.7	**71.3**	61.1	80.2
vicuna13B	22.5	23.9	28.0	32.0	32.8	27.7	31.0	35.3	44.2	37.3	42.9	50.0	54.8	68.4
LLama2-13B	**23.0**	**24.4**	**33.5**	**42.2**	**44.9**	**31.6**	**32.0**	**43.4**	**53.9**	**39.9**	**50.5**	**66.2**	**57.4**	**75.7**
Mistral-7B	20.7	**22.4**	**27.8**	25.8	27.8	**25.8**	29.0	32.3	**37.6**	35.0	40.6	47.7	52.6	**63.7**
ChatGLM2-6B	**21.6**	22.2	26.5	**28.2**	**29.0**	25.6	**30.6**	**33.6**	36.3	**36.5**	**41.9**	**50.7**	**53.7**	61.4
Vicuna-7B	20.3	21.6	21.6	21.7	22.7	**26.4**	25.9	27.6	28.2	**33.3**	**35.6**	**38.3**	**48.5**	50.8
ChatGLM-6B	**21.5**	**22.4**	**22.6**	**23.9**	**23.5**	25.0	**27.3**	**29.2**	**29.2**	33.1	34.8	36.3	48.2	**53.6**

Table 5: Performance Accuracy for Various Models when evaluated on Task 2 (Suboptimal Configuration Dataset)

and some `Bad Configurations`. The best amongst the moderate ones was kept as the Ground Truth. [Refer Appendix D] Our observations reveal consistent superiority of GPT-3.5-Turbo and PaLM across all models. Notably, GPT-3.5-Turbo consistently lags behind PaLM by an average margin of **3.7%**. Despite their commendable comparative performance, both models exhibit limitations in comparing across various physical variables of moderate configurations, resulting in a significant performance downturn. Even this time, we observed Vicuna7B and ChatGLM-6B exhibiting random erratic behaviors reflected in their consistent random outputs. While LLama2-13B performed superior to all other small-scale models, the general observed order was ChatGLM2-6B ∼ Mistral-7B < Vicuna13B < LLama2-13B < GPT3.5-Turbo < PaLM. In addition

Figure 6: Comparative Plot showcasing the variations in Task:2 performances as we keep increasing the **Count of Bad Configurations** in Options from left to right.

to the drop in average accuracy with increasing options, Figure 6 shows the trend of enhanced performance as we increase the count of Bad Configurations within a type of dataset. This could be attributed to the ability of models to differentiate bad configurations from moderate configurations. To delve deeper and analyze what fraction of the responses were correct and what fraction were from the "Bad Configurations" we make use of another metric: `Bad Rate`.

Table 6 shows the percentage of questions where a "Bad Configuration" was predicted as the correct answer. In our evaluations, this would mean that the model went wrong with reasoning in these questions. To probe LLM reasoning when presented with a varied amount of "bad configurations", we went on to increase the fraction of bad configurations present in each question's options as we moved from left to right([v1→v5], [v6→v9], [v10→v12]). With an increased fraction of options belonging to "bad configurations", we expected an increase in the bad rate. A good model would have a smaller magnitude of the bad rate as well as a larger gap between the fraction of bad options line (dotted line) and their bad rate value. Figure [7, 8a 8b] further showcases the trend of observed bad rates and the trend of the increase of the fraction of bad options we inserted in the prompt. While PaLM and GPT2.5-Turbo showed the least rise in bad rates, we observed LLama2-13B outperforming all other models and consistently trying to achieve PaLM and GPT3.5-Turbo's performance. Based on these figures and analyses we can safely conclude that most of the models had a sense of what a Bad Configuration is but showed limited reasoning capabilities to evaluate moderate configurations based on physical abstract variables. Thus through Task 1 and Task 2, we were able to evaluate and analyze commonsense reasoning capabilities of Language Models over physical state variables **[R2]**

Model	Bad Rate For Task_2 Variations ⇓													
	5-option					4-option				3-option			2-option	
	v1	v2	v3	v4	v5	v6	v7	v8	v9	v10	v11	v12	v13	v14
PaLM	-	**4.2**	**10.3**	**21.2**	**35.9**	-	**6.0**	**15.3**	36.8	-	**8.8**	31	-	**19.3**
GPT3.5-Turbo	-	5.5	12.5	24.4	38.4	-	7.7	17.5	38.8	-	9.7	**28.7**	-	19.8
vicuna13B	-	11.2	23.2	39.0	67.2	-	15.0	33.3	55.8	-	18.7	50	-	31.6
LLama2-13B	-	**7.2**	**18.8**	**29.3**	**55.1**	-	**9.6**	**24.6**	**46.1**	-	**13.0**	**33.8**	-	**24.3**
Mistral-7B	-	15.8	**28.7**	**48.2**	72.2	-	**17.0**	35.7	**62.4**	-	**19.5**	52.3	-	**36.3**
ChatGLM2-6B	-	**15.0**	31.5	48.6	**71.0**	-	**17.0**	34.6	63.7	-	20.4	**49.3**	-	38.6

Table 6: Bad Rate for various models when evaluated on Task 2 (Suboptimal Configuration Dataset). It signifies what fraction of the chosen options were Bad choices. (-) is used for datasets where there were no Bad options

Figure 7: Bad rates for various 5 option datasets as we increase the count of bad options. The difference tells us the models's ability to not get confused as we increase the count of bad options from left to right

(a) Bad rates for various 4 option datasets as we increase the count of bad options. The difference tells us the models's ability to not get confused as we increase the count of bad options from left to right

(b) Bad rates for various 3 option datasets as we increase the count of bad options. The difference tells us the models's ability to not get confused as we increase the count of bad options from left to right

4 Conclusion & Future Work

Accurately reasoning over an object's current physical state is an important aspect of developing robust embodied agents that can accomplish tasks even if the ideal objects are not available. We created a 3 step framework to break the decision-making process that we humans go through mentally while choosing an object for task completion. We further created 3 major datasets to evaluate object-level reasoning capabilities and physical state-level reasoning capabilities in Large Language Models. We found that even small models have a fair amount of object-based reasoning capabilities [**R1**] with their performance decreasing over increasing the number of options provided. While evaluating commonsense reasoning over an object's physical state we noticed the Language Model's impressive abilities to segregate out `Ideal Configurations` and `Bad Configurations`. However, their reasoning capabilities for analyzing `Moderate Configurations` seem to take a downturn. Here also, along with the decrease in performance with increasing options; for small models we noticed a decreasing accuracy within each option ideal level dataset(task-1) as we increased the object diversity. This brings forth the internal bias of these small models to stick to an object commonly used for a task, even if it is not in an Ideal State or a condition to be readily used. However, for larger models, we observed a lesser degradation in accuracy. Further, as we varied the number of bad configurations within each type of moderate-level dataset (task-2), we noticed the abilities of larger models like GPT3.5-Turbo and PaLM to not get confused into choosing "bad configurations" with an increase in such options. However, when the bad rates were compared across smaller models, we observed Llama2-13B showing small bad rates consistently across all variations. In view of these observations, we can safely conclude that Language Models like GPT3.5-Turbo, PaLM, and Llama2-13B can prune out appropriate Objects [Task 0] and Extremes (Ideal and Bad Configurations) to an impressive extent. However, they face a certain level of difficulty in comparing against moderate Configurations which require a certain amount of abstract reasoning equipped with a commonsense understanding of the world around them [**R2**]. However, smaller language models perform sub-optimally over [**R1**] and [**R2**] both showcasing poor commonsense reasoning capabilities and poor generalization beyond the data it was trained on.

Our work opens up an avenue for improving the language model's abstract multi-step reasoning for estimating the physical affordance of everyday objects that are used in household activities. Future efforts would be directed towards integrating these datasets to train Embodied Language agents and proving their competence of our 3-step architecture in successful task completion when situations aren't ideal. Judging the variable values in the real world could be a tricky affair, thus although the current work focused on handcrafted variables, calculating these variables and learning new latent variables from multi-modal inputs for effective analysis and reasoning about an object's applicability seems a foreseeable domain to explore.

Limitations

This work focuses on dealing with contextual connotations associated with an object when deciding whether to use it as a substitute for task execution. We further considered abstract physical variable level analysis to highlight the evolution of usability with various physical abstractions. While determining the values of these variables may appear straightforward in the Ai2Thor Simulator, achieving the same in real-life scenarios requires a resilient model. Even if we are able to calculate the variables, there is a limitation to which an object's state could be represented using abstract physical variables. When comparing objects, sometimes we need to understand their exact situation to make a decision about their usability. To develop robust embodied agents capable of dealing with such explicit reasoning along with abstract commonsense reasoning capabilities, further work needs to be directed along with integrating multi-modal reasoning capabilities in addition to commonsense reasoning. In addition to this, in this study, we assumed that all the objects were allowed to be used by the agent. In some cases, it might be possible that the human companion of the agent might have kept an object because of a certain way and didn't want it disturbed. Thus the agent might need to re-calculate the object use preference in accordance with this newly imposed human preference. Further works along this line would enable us to move an inch closer toward Embodied agents capable of such constrained planning capabilities in addition to multi-modal commonsense reasoning.

5 Related Works

Previous work has been done in the domains related to the scope of this paper. In this section, we summarize some of them:

Probing Language Models   Understanding what LMs know after large-scale pre-training is an active research area (Rogers et al., 2020). Various probing methods have been developed (Tenney et al., 2019b); (Petroni et al., 2019), and investigations show that LMs capture linguistic (Tenney et al., 2019a); (Liu et al., 2019), factual (Petroni et al., 2019); (Roberts et al., 2020); (Dai et al., 2022), commonsense knowledge (Wang et al., 2019); (Forbes et al., 2019), and even acquire grounded concepts (Patel & Pavlick, 2021).

CommonSense QA Datasets   Evaluating to what level commonsense world understanding LMs possess has been explored by many. (Gu et al., 2023) analyses mental models of LLMs and aligns them with improved models about everyday things; (Bisk et al., 2019) consisted of questions requiring physical commonsense reasoning. Recently, there has been a lot of work in NLP to utilize commonsense for QA, NLI, etc. (Sap et al., 2019); (Talmor et al., 2019). Many of these approaches seek to effectively utilize ConceptNet by reducing the noise retrieved from it (Lin et al., 2019) (Kapanipathi et al., 2020) There have been several other QA Datasets to benchmark CommonSense Reasoning abilities in Language Models, Some of them include: (Geva et al., 2021); (Yang et al., 2018); (Mihaylov et al., 2018);

Reasoning in LLMs   Reasoning is a crucial aspect of intelligence, influencing decision-making, problem-solving, and other cognitive abilities. (Huang & Chang, 2023) presents the current state of research on LLMs' reasoning abilities, exploring approaches to improve and evaluate their reasoning skills. (Dziri et al., 2023) investigates problems associated with multistep reasoning with LLMs Some of the works dealing with tackling reasoning in small models are: (Magister et al., 2023) (Fu et al., 2023) (Shridhar et al., 2023)

References

Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. Piqa: Reasoning about physical commonsense in natural language, 2019.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality, March 2023. URL `https://lmsys.org/blog/2023-03-30-vicuna/`.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. Palm: Scaling language modeling with pathways, 2022.

Yuqian Dai, Marc de Kamps, and Serge Sharoff. BERTology for machine translation: What BERT knows about linguistic difficulties for translation. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pp. 6674–6690, Marseille, France, June 2022. European Language Resources Association. URL `https://aclanthology.org/2022.lrec-1.719`.

Ernest Davis and Gary Marcus. Commonsense reasoning and commonsense knowledge in artificial intelligence. *Commun. ACM*, 58(9):92–103, aug 2015. ISSN 0001-0782. doi: 10.1145/2701413. URL `https://doi.org/10.1145/2701413`.

Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. Glm: General language model pretraining with autoregressive blank infilling. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 320–335, 2022a.

Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. Glm: General language model pretraining with autoregressive blank infilling. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 320–335, 2022b.

Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jiang, Bill Yuchen Lin, Peter West, Chandra Bhagavatula, Ronan Le Bras, Jena D. Hwang, Soumya Sanyal, Sean Welleck, Xiang Ren, Allyson Ettinger, Zaid Harchaoui, and Yejin Choi. Faith and fate: Limits of transformers on compositionality, 2023.

Maxwell Forbes, Ari Holtzman, and Yejin Choi. Do neural language representations learn physical commonsense?, 2019.

Yao Fu, Hao Peng, Litu Ou, Ashish Sabharwal, and Tushar Khot. Specializing smaller language models towards multi-step reasoning, 2023.

Jensen Gao, Bidipta Sarkar, Fei Xia, Ted Xiao, Jiajun Wu, Brian Ichter, Anirudha Majumdar, and Dorsa Sadigh. Physically grounded vision-language models for robotic manipulation. In *arXiv preprint arXiv:2309.02561*, 2023.

Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies, 2021.

Yuling Gu, Bhavana Dalvi Mishra, and Peter Clark. Do language models have coherent mental models of everyday things? In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1892–1913, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.106. URL `https://aclanthology.org/2023.acl-long.106`.

Jie Huang and Kevin Chen-Chuan Chang. Towards reasoning in large language models: A survey, 2023.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b, 2023.

Pavan Kapanipathi, Veronika Thost, Siva Sankalp Patel, Spencer Whitehead, Ibrahim Abdelaziz, Avinash Balakrishnan, Maria Chang, Kshitij Fadnis, Chulaka Gunasekara, Bassem Makni, Nicholas Mattei, Kartik Talamadupula, and Achille Fokoue. Infusing knowledge into the textual entailment task using graph convolutional networks. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(05):8074–8081, Apr. 2020. doi: 10.1609/aaai.v34i05.6318. URL `https://ojs.aaai.org/index.php/AAAI/article/view/6318`.

Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Matt Deitke, Kiana Ehsani, Daniel Gordon, Yuke Zhu, Aniruddha Kembhavi, Abhinav Gupta, and Ali Farhadi. Ai2-thor: An interactive 3d environment for visual ai, 2022.

Klaus Krippendorff. Computing krippendorff's alpha-reliability. *Departmental Papers (ASC). University of Pennsylvania*, 2011. URL `https://repository.upenn.edu/asc_papers/43`.

Lei Li, Jingjing Xu, Qingxiu Dong, Ce Zheng, Qi Liu, Lingpeng Kong, and Xu Sun. Can language models understand physical concepts?, 2023.

Bill Yuchen Lin, Xinyue Chen, Jamin Chen, and Xiang Ren. Kagnet: Knowledge-aware graph networks for commonsense reasoning, 2019.

Nelson F. Liu, Matt Gardner, Yonatan Belinkov, Matthew E. Peters, and Noah A. Smith. Linguistic knowledge and transferability of contextual representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1073–1094, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1112. URL `https://aclanthology.org/N19-1112`.

Lucie Charlotte Magister, Jonathan Mallinson, Jakub Adamek, Eric Malmi, and Aliaksei Severyn. Teaching small language models to reason, 2023.

John McCarthy. Programs with common sense. In *Proceedings of the Teddington Conference on the Mechanization of Thought Processes*, pp. 75–91, London, 1959. Her Majesty's Stationary Office. URL http://www-formal.stanford.edu/jmc/mcc59.html.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering, 2018.

OpenAI. Gpt-4 technical report, 2023.

Roma Patel and Ellie Pavlick. Mapping language models to grounded conceptual spaces. In *International Conference on Learning Representations*, 2021.

Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. Instruction tuning with gpt-4, 2023.

Fabio Petroni, Tim Rocktäschel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, Alexander H. Miller, and Sebastian Riedel. Language models as knowledge bases?, 2019.

Adam Roberts, Colin Raffel, and Noam Shazeer. How much knowledge can you pack into the parameters of a language model? In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 5418–5426, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.437. URL https://aclanthology.org/2020.emnlp-main.437.

Anna Rogers, Olga Kovaleva, and Anna Rumshisky. A primer in BERTology: What we know about how BERT works. *Transactions of the Association for Computational Linguistics*, 8:842–866, 2020. doi: 10.1162/tacl_a_00349. URL https://aclanthology.org/2020.tacl-1.54.

Maarten Sap, Ronan Le Bras, Emily Allaway, Chandra Bhagavatula, Nicholas Lourie, Hannah Rashkin, Brendan Roof, Noah A. Smith, and Yejin Choi. Atomic: An atlas of machine commonsense for if-then reasoning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):3027–3035, Jul. 2019. doi: 10.1609/aaai.v33i01.33013027. URL https://ojs.aaai.org/index.php/AAAI/article/view/4160.

Kumar Shridhar, Alessandro Stolfo, and Mrinmaya Sachan. Distilling reasoning capabilities into smaller language models, 2023.

Robyn Speer, Joshua Chin, and Catherine Havasi. Conceptnet 5.5: An open multilingual graph of general knowledge. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, AAAI'17, pp. 4444–4451. AAAI Press, 2017.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. Commonsenseqa: A question answering challenge targeting commonsense knowledge, 2019.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. BERT rediscovers the classical NLP pipeline. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4593–4601, Florence, Italy, July 2019a. Association for Computational Linguistics. doi: 10.18653/v1/P19-1452. URL https://aclanthology.org/P19-1452.

Ian Tenney, Patrick Xia, Berlin Chen, Alex Wang, Adam Poliak, R Thomas McCoy, Najoung Kim, Benjamin Van Durme, Samuel R. Bowman, Dipanjan Das, and Ellie Pavlick. What do you learn from context? probing for sentence structure in contextualized word representations, 2019b.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.

Cunxiang Wang, Shuailong Liang, Yue Zhang, Xiaonan Li, and Tian Gao. Does it make sense? and why? a pilot study for sense making and explanation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4020–4026, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1393. URL `https://aclanthology.org/P19-1393`.

Terry Winograd. Understanding natural language. *Cognitive Psychology*, 3(1):1–191, 1972. ISSN 0010-0285. doi: https://doi.org/10.1016/0010-0285(72)90002-3. URL `https://www.sciencedirect.com/science/article/pii/0010028572900023`.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering, 2018.

Renrui Zhang, Jiaming Han, Chris Liu, Peng Gao, Aojun Zhou, Xiangfei Hu, Shilin Yan, Pan Lu, Hongsheng Li, and Yu Qiao. Llama-adapter: Efficient fine-tuning of language models with zero-init attention, 2023.

Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models, 2023.

A Appendix

A.1 Dataset Specifics

(a) Plot showing number of objects(x) for each utility(y), as obtained after Utility based pruning 2.1.1

(b) Plot showing number of tasks(x) for each utility(y)

A.2 Variables

Here we describe the variables used to describe an object's physical state. We kept it at an abstract level to judge basic commonsense reasoning capabilities.

1. **Mass**: Based on an estimate of the weight of an object: **(i)** light[0,1 Kg] **(ii)** medium[1,5 Kg] **(iii)** heavy[5,10 Kg] **(iv)** super-heavy[> 10 Kg]

2. **Material**: what material is used to make that object

3. **Temperature**: the surface temperature of the object: Cold/Hot/RoomTemp

4. **already in use**: tells us about the availability of the object: reversible-using/irreversible-using/free

5. **condition**: tells us about the condition of the object: broken/clean/dirty

A.3 Human Annotations: Object-Utility Mappings

Table 2.1.1 summarizes the collected and refined Object-Utility pairings. Throughout this work, we have referred to these as `Utility Mappings`.

B Dataset Creation

In addition to the variations explained in 2.2.2, we further create 3 more types of datasets for each of the 3 tasks. These would be each consisting of 4, 3, and 2 options. The method we choose for sampling these options enables us to analyze the performance and reasoning capabilities of LLMs in zero-shot commonsense reasoning. The datasets are:

B.1 Task 0

1. **Variation-2**: For each question, we sampled 1 context object and 2 utility objects belonging to the same utility.

2. **Variation-3**: For each question, we sampled 1 context object and 3 utility objects belonging to the same utility.

3. **Variation-4**: For each question, we sampled 1 context object and 4 utility objects belonging to the same utility.

B.2 Task 1

5 option datasets :

1. **Variation-3**: Random context object's Ideal Configuration + 4 randomly sampled sub-optimal configurations of same Task and Utility's different context object

4 option datasets :

1. **Variation-4** : Random context object's Ideal Configuration + 3 randomly sampled sub-optimal configurations of the same context object

2. **Variation-5**: Random context Object's Ideal Configuration + 2 randomly sampled sub-optimal configurations of the same context object + 1 randomly sampled sub-optimal configurations of different context object belonging to the same `<Task,Utility>` combination

3. **Variation-6**: Random context Object's Ideal Configuration + 1 randomly sampled sub-optimal configurations of the same context object + 2 randomly sampled sub-optimal configurations of different context object belonging to the same `<Task,Utility>` combination

4. **Variation-7**: Random context object's Ideal Configuration + 3 randomly sampled sub-optimal configurations of the different context object belonging to the same `<Task,Utility>` combination

3 option datasets :

1. **Variation-8** : Random context object's Ideal Configuration + 2 randomly sampled sub-optimal configurations of the same context object

2. **Variation-9**: Random context object's Ideal Configuration + 1 randomly sampled sub-optimal configuration of the same context object + 1 randomly sampled sub-optimal configuration of different context object belonging to the same `<Task,Utility>` combination

3. **Variation-10**: Random context object's Ideal Configuration + 2 randomly sampled sub-optimal configurations of the different context object belonging to the same `<Task,Utility>` combination

2 option dataset

1. **Variation-11**: Random context object's Ideal Configuration + 1 randomly sampled sub-optimal configurations of the same context object.

2. **Variation-12**: Random context object's Ideal Configuration + 1 randomly sampled sub-optimal configurations of the different context object belonging to the same <Task,Utility> combination

B.3   Task 2

5 option dataset

1. **Variation-3**: We sample 3 options from the Moderate Configurations and 2 options from the Bad Configurations of the same <Task, Utility> combination's context objects
2. **Variation-4**: We sample 2 options from the Moderate Configurations and 3 options from the Bad Configurations of the same <Task, Utility> combination's context objects

3. **Variation-5**: We sample 1 option from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, we allow sampling equivalent options as long as either of them is not the correct answer. We also sample 4 options from the Bad Configurations of context objects of that particular <Task, Utility> combination

4 option dataset

1. **Variation-6**: We sample 4 options from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, here we allow sampling equivalent options as long as either of them is not the correct answer.

2. **Variation-7**: We sample 3 options from the Moderate Configurations of the context object of that particular <Task,Utility> combination, we allow sampling equivalent options as long as either of them is not the correct answer. We also sample 1 option from the Bad Configurations of the random context objects of that particular <Task, Utility> combination

3. **Variation-8**: We sample 2 options from the Moderate Configurations of the context object of that particular <Task,Utility> combination, we allow sampling equivalent options as long as either of them is not the correct answer. We also sample 2 options from the Bad Configurations of the random context objects of that particular <Task, Utility> combination

4. **Variation-9**: We sample 1 option from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, here we allow sampling equivalent options as long as either of them is not the correct answer. We also sample 3 options from the Bad Configurations of context objects of that particular <Task, Utility> combination

3 option dataset

1. **Variation-10**: We sample 3 options from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, here we allow sampling equivalent options as long as either of them is not the correct answer.

2. **Variation-11**: We sample 2 options from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, here we allow sampling equivalent options as long as either of them is not the correct answer. We also sample 1 option from the Bad Configurations of context objects of that particular <Task,Utility> combination

3. **Variation-12**: We sample 1 option from the Moderate Configurations of the context object of that particular <Task,Utility> combination. We also sample 2 options from the Bad Configurations of the random context objects of that particular <Task, Utility> combination

2 option dataset

1. **Variation-13**: We sample 2 options from the Moderate Configurations of the context objects of that particular <Task, Utility> combination, here we allow sampling equivalent options as long as either of them is not the correct answer.

2. **Variation-14**: We sample 1 option from the Moderate Configurations of the context object of that particular <Task,Utility> combination. We also sample 1 option from the Bad Configurations of the random context objects of that particular <Task, Utility> combination

C   Results

(a) Average Accuracy of Various models on Task 1 as we increase option count

(b) Average Accuracy of Various models on Task 2 as we increase option count

Model	Top-2 Accuracy for Task_2 Variations ⇑													
	5-option					4-option				3-option			2-option	
	v1	v2	v3	v4	v5	v6	v7	v8	v9	v10	v11	v12	v13	v14
PaLM	65.4	71.8	78.7	78.8	-	74.4	81.7	84.7	-	87.6	91.2	-	-	-
GPT3.5-Turbo	63.7	67.8	74.3	75.6	-	72.1	77.7	82.5	-	85.4	90.3	-	-	-
vicuna13B	51.4	54.8	58.5	61.0	-	61.6	65.0	66.7	-	76.6	81.3	-	-	-
LLama2-13B	53.4	60.6	69.7	70.7	-	63.6	70.7	75.4	-	76.4	87.0	-	-	-
Mistral-7B	47.4	49.9	55.5	51.8	-	59.7	62	64.3	-	76.5	80.5	-	-	-
ChatGLM2-6B	51	50.8	52.7	51.4	-	60.2	64.7	65.4	-	77.0	79.6	-	-	-

Table 7: Top-2 Performance Accuracy for Various Models when evaluated on Task 2 (Suboptimal Configuration Dataset). (-) is used for datasets for less than 1 moderate option which makes Top-2 accuracy useless

D   Annotation Process

The entire annotation process was text-based and was executed by circulating a text-based questionnaire. Figure 11 summarizes the entire annotation process for generating Ground Truths for all 3 datasets.

Figure 11: Figure summarizing our annotation process

D.1   Human Annotations: Utility-Object Mappings

Creation of utility-object mappings that were further used as the backbone for all the tasks and datasets, involved the use of GPT3.5-Turbo and Human Annotation. The annotators were asked to label 100 objects with utilities from a list of 22 utilities. The inter-annotator agreement was calculated by formulating this as a multi-annotator-multi-label scenario where each annotator could annotate a variable number of labels per object. The annotator agreement was **89.2%**, suggesting a high degree of agreement within the annotators. The consolidated utility-object mappings are found Link

D.2   Human Annotations: Task-Object Mappings

To curate ground truth task-object mappings also called `Context Mappings`; we ask the annotators to choose objects appropriate for a `<Task, Utility>` combination amongst the utility objects. As one question can have more than 1 possible correct object, we calculated inter-annotator agreement by modeling this as a process similar to the previous annotation task. The annotator agreement was observed to be: **81.0%**, suggesting a high degree of agreement amongst the annotators. The question posed to the annotators was similar to the ones used to curate Task 0 (Object Level Dataset) and the obtained responses were used as Ground Truth for Task 0 Dataset. The processed GT can be found here: Link

D.3   Human Annotations: Common Object-Variables Mappings

To get the common variable values for all the objects; we further ask the annotators to provide all commonly occurring variable values of each object. Using these we created all possible configurations. Upon calculating

the inter-annotator agreement as earlier annotation tasks, we observed an inter-annotator agreement of **89.9** when averaged across all 5 variables. The processed output can be found here: Link

D.4   Human Annotations: Ideal Object Configurations

Further, we ask the annotators to categorize variable values into 3 categories: Ideal, Moderate, and Bad. "Ideal" refers to an ideal state of the object; "moderate" means you have to spend some time getting the object in an ideal state before it can be used whereas "bad" means the object is unusable. Some variable values are obvious; like: "free" would be ideal whereas; "reversible-using" would be moderate; and "irreversible-using" would be bad. So we only ask them to give preference for variables like Material. The observed Krippendorff's reliability alpha (Krippendorff, 2011) among the raters for classifying material variable values into categorical variables: "Ideal", "Moderate" and "Bad" was **0.87**, suggesting a high degree of agreement amongst the annotators. The Ideal Configurations can be found Link.

D.5   Human Annotations: Moderate Configurations

After classifying the variable values into these 3 categories, we asked them to arrange the values in increasing order of their appropriateness for a given <Task,Utility> combination. For ranks as ordinal variables, we observed Krippendorff's alpha value to be **0.89**, showing a high agreement amongst the annotators. Further, we set a penalty for each moderate variable value and consequently generate 2 penalty scores for each configuration: material penalty and time penalty. It is using these penalties we further arrange the configurations based on a time penalty and then a material penalty. This helps us create a relative ranking within the moderate configurations and enables us to sample "moderate" options when curating Task 2 Dataset.

D.6   Human Annotations: Bad Configurations

For the Bad Configurations, we set abnormally high values for material and time penalties. These configurations help us sample "bad" options when curating Task 2 Dataset. The sub-optimal configurations including "moderate" and "bad" configurations can be found here: Link

E   Prompts used

Prompts used for various models can be found at this link. Link

F Example Responses

Task 0

Question ID: 1,
Utility: `heating(source)`,
Question: `Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?`
Options:

    (A) **object name**: `Toaster`,

    (B) **object name**: `StoveBurner`

Correct Answer: B

PaLM

Answer: B
Reason: Stove burners are safe and feasible, require minimal effort, and reheat coffee in a minimal amount of time.

GPT3.5-Turbo

Answer: B
Reason: Option B, StoveBurner, would be best suited for the purpose of reheating coffee in terms of safety, feasibility, minimum effort, and minimum time. Using a stove burner allows for precise control of heat, enabling a gradual and controlled reheating of the coffee. It's a common method for reheating liquids and is safer than using a toaster, which is not designed for reheating liquids and could pose a safety risk or result in spillage or damage to the toaster.

LLama2-13B

Answer: A
Reason: Toaster is the best option for reheating coffee as it is designed specifically for heating bread and other toastable items, and it can heat up quickly and evenly. Using a stove burner would require more effort and time to heat the coffee, and it may not heat it evenly. Additionally, using a toaster is generally safer than using an open flame on a stove burner, as it has built-in safety features such as a cool-touch exterior and automatic shut-off.

Vicuna7B

Answer: B
Reason: Option B, a stove burner, is the best choice for reheating coffee as it is a safe and efficient heating source that requires minimal effort and time. It allows for precise temperature control and can be easily used to reheat coffee without causing any damage to the coffee or creating any safety hazards.

Vicuna-13B

Answer: B
Reason: A stove burner would be the best option for reheating coffee as it provides precise temperature control, allowing for easy adjustment to the desired temperature. This ensures that the coffee is heated evenly and efficiently, without the risk of burning or over-heating. Additionally, a stove burner is a convenient and easily accessible option, requiring minimal effort and time to use. On the other hand, a toaster may not be the best option as it is not designed for heating liquids and may not provide consistent or accurate temperature control.

Mistral7B

Answer: B
Reason: While a toaster is a convenient option, a stove burner would be the best suited for heating coffee as it provides more control over the temperature and the amount of heat being applied. It also allows for a larger surface area to be heated, which can be beneficial in reheating coffee. Additionally, using a stove burner is safer and more energy-efficient than using a toaster

ChatGLM-6B

Answer: A
Reason: Toaster is a more convenient and efficient option for reheating coffee compared to a stove burner.

ChatGLM2-6B

Answer: A
Reason: Toaster is a device that heats up food items such as coffee. It is a more convenient and safer option compared to a stove burner. The toaster has a simple operation, low maintenance and can be used to heat up a single serving of coffee at a time. The time it takes to heat up the coffee is minimal and there is no need for additional effort to operate it.

Task 1

Question ID: 1,
Utility: heating(source),
Question: Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?,
Options:

(A) **object name**: Microwave, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: free, **condition**: clean

(B) **object name**: StoveBurner, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal **already in use**: irreversible-using, **condition**: dirty

(C) **object name**: CoffeeMachine, **mass**: heavy, **temperature**: RoomTemp, **material**: Metal **already in use**: irreversible-using, **condition**: dirty

(D) **object name**: Microwave, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal **already in use**: reversible-using, **condition**: clean

(E) **object name**: Microwave, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: irreversible-using, **condition**: broken

Correct Answer: A

PaLM

Answer: A
Reason: Microwaves are safe and easy to use, and they can heat coffee quickly and evenly. They are also relatively lightweight and easy to move, so they can be used in a variety of settings.

GPT3.5-Turbo

Answer: D
Reason: Microwave (option D) is the best choice as it is available (reversible-using), in clean condition, and suitable for reheating coffee. It is not irreversibly occupied and can be used for the task without a time penalty.

LLama2-13B

Answer: A
Reason: Microwaves are designed specifically for heating and cooking, making them a safer choice compared to stovetop burners or coffee machines. Additionally, microwaves are generally made of durable materials and have a more delicate design, which makes them less fragile than stovetop burners or coffee machines. Furthermore, microwaves are quick and efficient when it comes to heating up liquids, taking less time than stovetop burners or coffee machines. Finally, option A has already been used (already in use: "free") and its condition is clean, which suggests that it is ready for immediate use.

Vicuna7B

Answer: D
Reason: This is because a microwave is a common and convenient appliance for reheating coffee quickly and efficiently, and it can be used multiple times without any issues. Additionally, a microwave is generally safe and easy to use, and it does not require any time penalty or additional setup to get started with the task.

Vicuna13B

Answer: A
Reason: A microwave is the best suited object for the purpose of reheating coffee as it is a fast and efficient way to heat liquids. It is also a reversible use object as it can be used again after the task is completed. Additionally, a microwave is a safe and convenient option as it eliminates the need for hot surfaces or open flames, which can be hazardous. The mass and material properties of a microwave also make it a safe and practical choice for this task.

Mistral-7B

Answer: A
Reason: Based on the given physical variables, object A (Microwave) would be the best suited for the purpose of heating(source) when tasked to reheating coffee. The microwave is readily available and clean, which means it can be used immediately without any additional time required for cleaning or preparation. Additionally, microwaves are generally safe for use in heating food and are less likely to break down compared to other materials. The microwave temperature is also at a safe level for heating food. While other options such as stove burners and coffee machines may also be suitable for heating coffee, they may require additional time and effort to clean and prepare for use, and their availability may be limited due to current use or maintenance requirements. Therefore, the microwave is the best choice for reheating coffee in a household setting.

ChatGLM-6B

Answer: D
Reason: The best option for reheating coffee would be the Microwave object with id 5, which has already been mentioned to be reversible and in use, but also has a lower mass compared to other options, making it easier to handle and transport. Additionally, it is a metal microwave, which can provide better heating efficiency compared to other options made of different materials.

ChatGLM2-6B

Answer: B
Reason: The stove burner is suitable for heating coffee as it has a high temperature and is made of metal, which is conductive and can efficiently transfer heat. Additionally, it is in a state of reversible using, which means it is temporarily unavailable but can be used after some time. The condition is dirty, which is not relevant to the task of reheating coffee.

Task 2

Question ID: 1,
Utility: heating(source),
Question: Which of the following objects would be best suited for the purpose of "heating(source)" when tasked to "reheating coffee"?,
Options:

(A) **object name**: CoffeeMachine, **mass**: heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: reversible-using, **condition**: dirty

(B) **object name**: CoffeeMachine, **mass**: heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: irreversible-using, **condition**: clean

(C) **object name**: CoffeeMachine, **mass**: heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: free, **condition**: dirty

(D) **object name**:Microwave, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: reversible-using, **condition**: dirty

(E) **object name**:StoveBurner, **mass**: super-heavy, **temperature**: RoomTemp, **material**: Metal, **already in use**: irreversible-using, **condition**: clean

Correct Answer: C

PaLM

Answer: A
Reason: The coffee machine is the most efficient way to reheat coffee, and it is also the safest option.

GPT3.5-Turbo

Answer: E
Reason: StoveBurner is available, clean, and can be used without time penalty (reversible-using). It is suitable for heating and reheating tasks and is generally quick to heat up.

LLama2-13B

Answer: C
Reason: The Coffee Machine is the best configuration for reheating coffee because it is the least time-consuming and most reliable option. Although it is currently dirty, it can be cleaned after use, making it a more reliable choice than the Microwave or StoveBurner, which may have permanent damage if used with dirty or wet objects. Additionally, the Coffee Machine is already available and does not require any time to "get started" like the Microwave or StoveBurner, which need time to heat up. Therefore, the Coffee Machine is the best option for reheating coffee based on commonsense reasoning related to the provided physical variables.

Vicuna-7B

Answer: C
Reason: The Coffee Machine is the best option for the purpose of "heating(source)" when tasked to "reheating coffee" because it is already available and not in use, and it is also in a dirty condition. Therefore, it is the most suitable option to use for this task.

Vicuna-13B

Answer: A
Reason: The best option for reheating coffee is the 'Coffee Machine' because it is specifically designed for making and heating coffee. It has a 'reversible-using' availability status, meaning it can be used after some time. It is also made of metal, which is a safe and durable material for heating purposes. Additionally, it is already dirty, which means it can be cleaned after use without any extra time penalty. Overall, the 'Coffee Machine' is the most suitable option for reheating coffee.

Mistral-7B

Answer: A
Reason: The Coffee Machine with already in use = reversible using and condition = dirty is the best option for reheating coffee. It is readily available and can be easily cleaned before use, making it safe and efficient

ChatGLM-6B

Answer: A
Reason: The Coffee Machine is the best suited for the purpose of heating(source) when tasked to reheating coffee, as it is lightweight, easy to handle and can be used multiple times without any loss of heat. Additionally, it is metal and can be easily heated to a high temperature, making it suitable for heating coffee.

ChatGLM2-6B

Answer: C
Reason: The Coffee Machine has a free state which means it can be readily used without time penalty. Additionally, it has a dirty condition which is temporary and can be overcome. It is also made of metal which may not be safe for food contact. It is also a heavy object which may be difficult to move.

Utility	Objects
Heating (source)	Microwave, Stove Burner, Toaster, Oven, Coffee Machine, Candle
Carrying	Wine Bottle, Watering Can, Vase, Bottle, Cup, Mug, Pot, Kettle, Bowl, Plate, Spray Bottle
Cleaning	Dish Sponge, Scrub Brush, Plunger, Paper Towel Roll, Soap Bar, Soap Bottle, Towel, Newspaper, Toilet Paper, Cloth, Hand Towel, Tissue Box, Vacuum Cleaner
Washing	Bathtub Basin, Sink Basin, Toilet
Cutting	Butter Knife, Knife, Fork, Spatula, Spoon
Disposing	Garbage Can, Bathtub Basin, Sink Basin, Toilet
Mixing (tool)	Ladle, Fork, Spoon, Spatula, Butter Knife, Knife
Mixing (vessel)	Pan, Bowl, Kettle, Cup, Plate, Pot, Mug
Heating (vessel)	Pan, Bowl, Kettle, Cup, Plate, Pot, Mug
Storage	Drawer, Cabinet, Dresser, Fridge, Laundry Hamper, Safe, Shelf, Shelving Unit, Desk, Box
Entertainment	Television, CD, Remote Control, Cell Phone, Laptop, Desktop
Comfort	Bed, Armchair, Chair, Dog Bed, Sofa, Ottoman
Reading	Book, Newspaper, Desktop, Laptop, Cell Phone
Increasing Height	Desk, Armchair, Chair, Coffee Table, Footstool, Dining Table, Countertop, Stool, Ottoman, Sofa, Side Table, Dresser, Bed
Time	Watch, Alarm Clock, Cell Phone, Desktop, Laptop
Eating	Apple, Bread, Potato, Lettuce, Egg, Coffee, Tomato, Salt
Physical Exercise	Basketball, Baseball Bat, Dumbell, Tennis Racket
Writing	Pen, Pencil, Cell Phone, Laptop, Desktop
Surface Support	Coffee Table, Countertop, Desk, Dining Table, Dog Bed, Dresser, Floor, Footstool, Ottoman, Side Table, Sofa, Stool, Chair, Armchair, Bed
Light Source	Light Switch, Window, Desk Lamp, Blinds, Curtains, Candle, Floor Lamp
Decoration	Statue, House Plant, Room Decor, Teddy Bear, Tabletop Decor, Poster, Painting
Breaking	Butter Knife, Knife, Fork, Spatula, Plate, Ladle, Basketball, Tennis Racket, Dumbbell, Remote Control, Baseball Bat, Spoon

Table 8: Utilities and Objects