Do Language Models Update their Forecasts with New Information?

Abstract

Prior work has largely treated future event prediction as a static task, failing to consider how forecasts should evolve as new evidence emerges. To address this gap, we introduce EVOLVECAST, a framework for evaluating whether large language models (LLMs) appropriately revise their predictions in response to new information. In particular, EVOLVECAST assesses whether models adjust their forecasts when presented with evidence released after their training cutoff, using human forecasters as a comparative reference for prediction shifts and confidence calibration. We find that while models often track the correct update direction, their quantitative shifts remain heavily under-responsive. Furthermore, both verbalized and logits-based confidence estimates are poorly calibrated compared to the human reference standard. These findings suggest current LLMs are fundamentally limited in their response to new evidence; models treat new information as mere retrieval context rather than as variables that dynamically shift posterior probabilities. EVOLVECAST highlights the critical need for robust mechanisms to incorporate external knowledge into dynamic belief updating.

1 Introduction

Large language models (LLMs) have achieved strong performance across a wide range of NLP tasks, particularly those involving factual recall and reasoning over known information (Lin et al., 2022; Guo et al., 2023) including temporal information (Ding et al., 2025). However, most evaluations remain static and retrospective: they assess what models know about the world up to their training cutoff. In contrast, real-world decision-making often requires reasoning about uncertain future events, where outcomes are not yet known and relevant information evolves over time.

Forecasting plays a central role in domains such as policymaking, science, and technology. It requires anticipating future developments based on incomplete or uncertain evidence, and adjusting those beliefs as new signals arrive. Unlike fact retrieval tasks, forecasting is inherently temporal and dynamic. For instance, given the question, "Will GPT-6 be released in 2026?", an LLM might answer "Yes" based on existing trends in AI development. However, without a way to incorporate emerging information, such as announcements or delays, such forecasts remain static, and may quickly become outdated or misleading. To illustrate the dynamic nature of forecasting, see the example in Figure 1.

Prior work has begun to explore the forecasting capabilities of LLMs (Jin et al., 2020; Zou et al., 2022; Yuan et al., 2024a). These efforts typically frame forecasting as a static problem, where the model produces a categorical answer based on its existing knowledge. Some studies incorporate external information, including textual evidence such as news (Ye et al., 2024; Halawi et al., 2024), but use this information to improve the model's *final prediction*, not to evaluate how forecasts change over time. More recently, forecasting has been reframed as a probabilistic task, where models are expected to produce confidence scores in addition to predictions (Karger et al., 2024; Yuan et al., 2025). In this setting, the goal is not just to answer the mentioned question with "Yes", but to provide a confidence level, e.g., 70%, that reflects the model's uncertainty. These works though showed that even when models make correct predictions, their confidence is often miscalibrated.

Yet even confidence-aware predictions remain static if models cannot revise their beliefs. In practice, forecasters routinely update their views as new information becomes available. For example, as illustrated in Figure 1, if a forecaster initially assigns a 60% chance to an event but later encounters positive supporting evidence, they might appropriately revise their estimate upward to 65%. A capable

Figure 1: EVOLVECAST evaluates the direction and magnitude of forecast updates ($P_0 \rightarrow P_t$) given new evidence.

forecasting model should exhibit similar adaptive behavior. However, current LLMs frequently fail to assimilate this evidence correctly, sometimes even shifting their confidence in the opposite direction by dropping to 55%. Evaluating these belief dynamics provides insight into how well models reason under uncertainty and adapt over time, which remains a blind spot in most LLMs.

This paper introduces EVOLVECAST, a framework for evaluating whether language models revise their forecasts and confidence in response to emerging evidence. Crucially, we assess the reasoning process of belief revision rather than the static accuracy of the final outcome. Unlike benchmarks measuring performance against a final resolution (0 or 1), we measure alignment with the aggregate human forecast—treating it as a proxy for the *ideal* belief state given currently available evidence. This distinguishes rational updating from clairvoyance, avoiding erroneous penalties for maintaining uncertainty when the outcome is not yet determined. To this end, we construct a benchmark of scenarios where information becomes available after training cutoffs, evaluating belief changes against human forecasters. We also provide a setting where models leverage historical human forecasts as a contextual reference, mimicking real-world observations without prescribing ground truth.

Our evaluation focuses on the direction and magnitude of prediction shifts and the calibration of updated confidence scores as exampled in Figure 1.

Our evaluation focuses on the direction and magnitude of prediction shifts and the calibration of updated confidence scores. Our findings show that while LLMs often capture the correct update direction, their quantitative shifts lack sufficient responsiveness, and as Figure 1 demonstrates, they can occasionally update in the wrong direction en-

tirely. Furthermore, their confidence estimates fall short of human standards. These challenges suggest current LLMs treat new information as mere retrieval context rather than as evidence that dynamically shifts posterior probabilities. This highlights fundamental difficulties in modeling belief dynamics and underscores the need for evaluation frameworks that extend beyond static forecasting accuracy. EVOLVECAST provides such a framework, offering a setting for analyzing how models adapt their predictions as the world evolves.

2 Related Work

A growing body of research has investigated the forecasting capabilities of language models, though most efforts emphasize event prediction rather than belief dynamics or confidence calibration. Open-Forecast (Wang et al., 2025) introduces a large-scale benchmark for open-ended multi-step forecasting, but focuses primarily on model accuracy rather than the calibration of confidence estimates. ForecastBench (Karger et al., 2024) frames forecasting as a probabilistic task with evolving predictions over time, but does not explicitly examine how models adjust their beliefs in light of new information. Time-R1 (Liu et al., 2025) presents a reinforcement learning framework to endow smaller LLMs with temporal understanding and future event generation capabilities, showing strong performance on forecasting beyond training cutoff.

Concurrently, the need to incorporate dynamic information has motivated retrieval-augmented approaches in forecasting. While Tire et al. (2024) and Liu et al. (2024) adapt retrieval mechanisms to improve quantitative time-series foundation and diffusion models, integrating emerging textual evidence into LLM forecasts remains a distinct challenge. Closely aligned with our perspective,

Murphy (2026) recently proposed an agentic system that performs sequential Bayesian updating on a structured linguistic belief state. Their approach explicitly counters the standard LLM practice of appending evidence as unstructured retrieval context. While their work focuses on achieving state-of-the-art forecasting via agentic workflows, EVOLVECAST provides the complementary evaluation framework needed to isolate, quantify, and expose these specific belief revision deficits in base and reasoning models.

Beyond forecasting, several benchmarks target reasoning and plausibility assessment. COPA (Roemmele et al., 2011) and HellaSwag (Zellers et al., 2019) evaluate causal and commonsense reasoning via multiple-choice inference tasks. PRobELM (Yuan et al., 2024b) examines models' ability to rank outcomes by plausibility, drawing on general world knowledge. While these evaluations probe important reasoning capabilities, they do not test how models reason under uncertainty or update beliefs.

3 EvolveCast: Dynamic Forecasting Evaluation Formalization

3.1 Task Definition

We formalize EVOLVECAST as a dynamic forecasting task, where the goal is to evaluate whether a language model revises its predictions and confidence in response to new information in a manner comparable to a reference standard. Let q denote a forecasting question about a future event (e.g., "Will GPT-6 be released in 2026?"). At time t, new information x_t (e.g., a news headline or update) becomes available, and we measure how the model's belief changes when conditioned on it. For binary questions ($\mathcal{Y} = \{\text{Yes}, \text{No}\}$), the model's belief at time t reduces to a scalar confidence $p_t = P_t(\text{Yes} \mid x_t) \in [0, 1]$, and the belief update is defined as $\Delta p = p_t - p_0$.

3.2 Evaluation Criteria

We evaluate the quality of model belief updates by comparing the change in model confidence, $\Delta p = p_t - p_0$, to the corresponding reference shift in human forecasts, $\Delta h = h_t - h_0$. It is important to note that a key methodological choice here is evaluating against Δh rather than the final resolution ($y \in \{0, 1\}$). The final resolution captures the state of the world at T_{end} but does not represent the rational belief state at intermediate time t.

Scoring updates against the final resolution forces the model to act as an oracle, penalizing valid epistemic uncertainty (e.g., assigning $P = 1.0$ to an unlikely event that eventually happens). By comparing against the human aggregate, we isolate the reasoning step: *How should a rational agent's uncertainty update given this specific piece of news?*

We assess this alignment on three aspects:

Directional Agreement. We use *Mean Directional Accuracy (MDA)* to assess whether the model and reference forecasts tend to update their beliefs in the same direction. For a set of N instances:

$$\text{MDA} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}\left[\text{sign}(\tilde{\Delta}_p^{(i)}) = \text{sign}(\tilde{\Delta}_h^{(i)})\right],$$

where Δp_i and Δh_i are the model and reference forecast deltas for the i-th instance. We apply a minimal change threshold ϵ to avoid counting negligible shifts as meaningful updates. Specifically, we treat both Δp_i and Δh_i as zero when $|\Delta| < \epsilon$, and consider the signs to match in such cases. Let $\tilde{\Delta}_p$ denote the thresholded version of Δp, where $\tilde{\Delta}_p = 0$ if $|\Delta p| < \epsilon$, and similarly for Δh. *Precision, Recall, and F1 (micro-averaged)* are also computed binary target by treating "directional match" as the positive class. In practice, this means micro-averaged recall is always equal to the MDA, since both reduce to the proportion of correctly classified instances; in addition, this reduces each update to one of three labels: `Up` ($\Delta > \epsilon$), `Down` ($\Delta < -\epsilon$), or `Still` ($|\Delta| < \epsilon$); and we evaluate whether the model's label matches the reference.

Magnitude Alignment. We measure how closely the magnitude of the model's belief update matches that of reference forecasters. We report two complementary metrics: *Mean Squared Error (MSE)* and *Symmetric Mean Squared Percentage Error (SMSPE)*. The MSE is defined as:

$$\text{MSE} = \frac{1}{N} \sum_{i=1}^{N} (\Delta p_i - \Delta h_i)^2,$$

To evaluate relative alignment, we define the symmetric percentage change in belief as:

$$\delta_p^{(i)} = \frac{p_t^{(i)} - p_0^{(i)}}{(p_t^{(i)} + p_0^{(i)})/2}, \quad \delta_h^{(i)} = \frac{h_t^{(i)} - h_0^{(i)}}{(h_t^{(i)} + h_0^{(i)})/2},$$

where $p_0^{(i)}$ and $p_t^{(i)}$ are the model's confidence before and after seeing new information (similarly for

the reference forecasts), similar to MAPE (De Myttenaere et al., 2016). The SMSPE is given by:

$$\text{SMSPE} = \frac{1}{N} \sum_{i=1}^{N} \left(\delta_p^{(i)} - \delta_h^{(i)} \right)^2 .$$

Confidence Calibration. To assess whether models produce well-calibrated confidence estimates, we compute the *Brier Score* (Brier, 1950). This allows us to evaluate whether the model's confidence aligns with reference before and after new information is introduced. The Brier score between model prediction p and reference forecast h is defined as: $\text{Brier}(p, h) = (p - h)^2$. The change in calibration directly as the average difference in squared errors before and after conditioning on new information:

$$\Delta\text{Brier} = \frac{1}{N} \sum_{i=1}^{N} \left[(p_t^{(i)} - h_t^{(i)})^2 - (p_0^{(i)} - h_0^{(i)})^2 \right].$$

A negative ΔBrier indicates improved calibration after observing new information (lower Brier is better), while a positive value suggests degradation.

4 EvolveCast Dataset Construction

EVOLVECAST is constructed from Metaculus (www.metaculus.com; see examples in Appendix C), an online forecasting platform where users submit probability estimates to questions spanning domains such as politics, economics, health, and technology. Metaculus aggregates these into a community prediction that is continuously updated until shortly before resolution. Each question is associated with predefined resolution criteria, and the platform enforces strict guidelines to ensure that forecasts are consistent with those criteria. Metaculus also has a strong empirical track record: over the past five years, community predictions on resolved binary questions have shown close alignment to observed outcomes, with roughly half of observed frequencies lying within the 90% credible interval around the ideal calibration line.[1] This calibration performance provides confidence that the platform's aggregated predictions are reliable.

We apply several filtering steps to ensure data quality. First, we discard questions that Metaculus marks as ambiguous or that are resolved in ways that make forecasting infeasible. For example, when the outcome falls outside the prediction range or when resolution criteria are modified after

---

[1]https://www.metaculus.com/questions/track-record

submission. Second, we only include questions with at least 100 individual forecasts to maintain statistical reliability in the aggregated reference prediction. Finally, we restrict the dataset to binary (Yes/No) questions. The resulting dataset consists of 1,613 question–news pairs with timestamp.

4.1 Reference Forecasts and Confidence Extraction

In our setting, ground-truth confidence values are not directly observable. We therefore follow prior work that uses human forecast distributions as a proxy for uncertainty (Plank, 2022; Baan et al., 2024; Yuan et al., 2025). The intuition is that aggregated human forecasts, even when forecasters disagree, provide informative signals of uncertainty that reflect the latent probability of the event at that specific moment in time, which the final binary outcome cannot capture. Disagreement itself reflects the inherent ambiguity and difficulty of the task, similar to how disagreement among annotators is leveraged in natural language tasks with multiple plausible interpretations. This approach has several advantages. First, it captures the fact that some forecasting questions are inherently uncertain, so variance across forecasters represents a genuine property of the task rather than annotation noise. Second, aggregation over many individuals smooths out idiosyncratic biases while preserving collective uncertainty, yielding a stable yet informative signal. Third, these distributions are updated dynamically as new evidence appears, making them suited for evaluating belief revision.

For Boolean questions, where the community assigns probability P to the correct outcome, we compute a normalized confidence score as $h = \sigma\left(\frac{\ln P - \ln 0.5}{\ln 2}\right)$. This ensures that confidence is scaled relative to a chance-level (50%) baseline. While absolute aggregate human probabilities may occasionally carry idiosyncratic platform biases, the collective updates and directional shifts of the crowd reliably reflect rational belief revision as new signals emerge. Consequently, these aggregate human shifts serve as an ideal proxy for tracking evidence integration, prioritizing the logical trajectory of the belief update over static numerical perfection (Dezecache et al., 2022; Jeen et al., 2026).

4.2 News Retrieval and Alignment

In addition to questions and forecasts, EVOLVECAST pairs each instance with a contemporaneous news update. The key challenge is to deter-

mine when new information becomes available that could plausibly shift forecasts. We detect these moments by monitoring the comment streams associated with each Metaculus question: whenever a new comment is posted, we treat this as a candidate signal that new evidence has emerged. To reduce noise, we filter out bot-generated or automated comments as well as very short entries (fewer than 20 characters). Once a candidate timestamp is identified, we search for relevant news articles within a one-week window preceding the comment to account for possible delays between publication of external information and the time at which it is reflected in forecaster discussion. News articles are retrieved via the Google Search API, using the original question as the query, and for each candidate timestamp we collect up to 100 related articles.

To select the most relevant update, we compute semantic similarity between the comment text and each retrieved article using sentence embeddings (Reimers and Gurevych, 2019). Articles are then ranked by similarity score, and by default we retain the top-ranked article, storing both its title and headline as the associated news update. This procedure ensures that each question–forecast pair is aligned with a news item that is both temporally plausible and semantically linked to the corresponding forecaster discussion. Because a single question may be associated with multiple updates over time, the dataset may contain repeated questions paired with different news events. In total, this process yields 1,613 aligned question–news pairs.

5 Experimental Setup

5.1 Models

We evaluate three openly available *reasoning* models from the DeepSeek-R1 series (Guo et al., 2025): `DeepSeek-R1-Distill-Qwen-1.5B` and 7B, and `DeepSeek-R1-Distill-LLaMA-8B`, together with their published *base* counterparts from the same backbones (Qwen 2.5 (Bai et al., 2025) and Llama 3.1 (Dubey et al., 2024) families, as indicated in the official model cards).[2] This choice serves two purposes. First, it provides coverage across both Qwen and Llama backbones and multiple parameter scales (1.5B/7B/8B), enabling us to probe how *scale* and *architecture* relate to belief-updating behavior. Second and critically, it al-

---

[2] We pair each R1-distilled model with the corresponding base instruction model from its backbone family following the mapping described in the providers' model cards.

lows us to isolate the effect of *reasoning-style post-training* (e.g., distillation/RL procedures specific to R1) by comparing each R1 model against a matched base model. Including unrelated weaker models would introduce confounds (different tokenizers, pretraining corpora, and objectives) that obscure the contribution of reasoning post-training and inflate variance without strengthening causal claims about update dynamics. All models are evaluated with identical prompts and decoding settings.

5.2 Inference Procedure

For each question, we run two conditions with identical instructions: (i) a *question-only* condition (no external update) and (ii) a *question+news* condition where we augment the prompt with a retrieved news snippet aligned to the question (Sec. 4). Full details are provided in Appendix D.

Because the exact training cutoffs of these models are undisclosed, we restrict evaluation to questions first posted strictly *after October 2023*. For each instance we use two explicit evaluation dates: T_0 is the question date (the prompt states "today is T_0"), and T_1 is the publication date of the associated news update (the prompt states "today is T_1" and includes the dated snippet), with $T_0 < T_1$. In both conditions the prompt instructs the model to use only information available up to the stated date (e.g., "You do not have access to updates after T").

This dynamic anchoring serves two goals. First, it closely mirrors the real forecaster workflow: form a view at T_0, then revise at T_1 when new evidence arrives, thereby avoiding hindsight effects. Second, it minimizes leakage concerns and unknown-cutoff confounds: our primary metrics evaluate the *within-instance change* $\Delta p = p_t - p_0$ from T_0 to T_1. By comparing the same model on the same question before vs. after dated evidence, we largely cancel effects of any static knowledge in pretraining and directly test responsiveness to new information rather than recall of facts.

5.3 Confidence Extraction

Following prior work on eliciting model self-assessments (Xiong et al., 2023), we evaluate model confidence using two complementary approaches: verbalized and logit-based probabilities.

Black-box (verbalized) confidence. The model is instructed to provide a binary prediction ("Yes" or "No") and to assign a probability on a 1–10 scale with descriptive anchors ("1: extremely un-

likely" ... "10: extremely likely"). We normalize this verbalized score to $[0, 1]$ for evaluation. This setting aligns with how human forecasters typically express uncertainty through explicit probability estimates, facilitating direct comparison with the aggregated human reference.

White-box (logit-based) confidence. We also derive confidence estimates directly from the model's output probabilities. For a single generated answer $y = (y_1, \ldots, y_T)$, we compute the mean token probability $\hat{p} = \frac{1}{T} \sum_{t=1}^{T} P(y_t \mid y_{<t}, x)$, where $P(y_t \mid y_{<t}, x)$ is the model's predicted probability of token y_t given the context. This logit-based measure reflects the model's internal certainty about its produced sequence and provides a complementary perspective to the verbalized estimates.

6 Results

6.1 Black- vs. White-box Confidence: No Clear Winner, but Reasoning Helps

Table 1 compares verbalized (black-box) and logit-based (white-box) confidence across reasoning-tuned and base models. Overall, neither approach emerges as a clear winner: both exhibit low directional agreement and poor calibration relative to human forecasters. Reasoning-tuned models consistently outperform their base counterparts, particularly at larger scales (7B and 8B), yet within each backbone the gap between black- and white-box methods remains small and inconsistent. Several factors likely contribute to the underperformance of both approaches. Verbalized probabilities show slightly greater stability across settings, yet they remain imperfect: models often default to conservative or generic values, which blunts the fidelity of their probability estimates. Logit-based confidences, by contrast, draw more directly on internal activations but are highly sensitive to prompt length, decoding hyperparameters, and normalization schemes, which can undermine robustness. Neither approach therefore provides a consistently reliable signal, and small numerical differences between them should be interpreted with caution.

Beyond the mechanics of confidence elicitation, forecasting itself poses distinctive challenges for LLMs. The task demands not only access to broad domain knowledge but also the capacity to integrate novel information and update beliefs in a calibrated fashion. Current models show limited ability to perform these updates reliably, leading to systematic miscalibration even when directional reasoning is

sound. This pattern echoes prior findings (Karger et al., 2024), which likewise identified forecasting as a setting that exposes fundamental weaknesses in both reasoning and calibration. To better understand these dynamics, we narrow our subsequent ablations to a subset of settings that more clearly isolate model behavior under controlled conditions. Even with this refinement, the central result remains unchanged: LLMs are far from human-like in belief updating, regardless of whether confidence is elicited in black-box or white-box form.

6.2 Ablation: Directional QA Prompting

In this ablation, instead of eliciting probabilities before and after a news update and then computing their difference, we directly prompt the model to predict whether the news should make the forecast go "Up," "Down," or remain "Still." This reduces the task to a single classification run rather than two probability-estimation runs, and removes dependence on the quality of numeric calibration. Prompt templates are provided in Appendix F. The motivation for this setting is twofold. First, subtraction of two noisy probability estimates is fragile: even when the direction of change is clear, imperfect calibration or over/under-confidence can obscure it. Second, this format mirrors how human forecasters often reason qualitatively, e.g., "this headline makes outcome X more likely," without attaching precise numbers. Direct directional prompting therefore probes whether LLMs can at least capture the *sign* of belief updates, independent of their ability to express calibrated probabilities.

Table 2 reports directional agreement metrics under this setting. Compared to the probability-based approach, the direct method yields markedly higher MDA and F1, especially for larger models. For example, DS R1 LLaMA-8B achieves nearly 0.49 MDA with single updates, compared to only 0.34 under verbalized confidence (cf. Table 1). This indicates that models are substantially better at reasoning about the qualitative *direction* of change than at producing well-calibrated probabilities. Similar as before, accumulated news again does not improve performance: both DS R1 Qwen-7B and DS R1 LLaMA-8B see declines in MDA and F1 when given the full sequence of updates. Together with Sec. 6.3, this highlights that concatenating news does not help models integrate evidence and may in fact dilute the signal. Overall, this ablation suggests that while LLMs struggle with precise probability calibration, they are relatively more reliable

Table 1: Main results. Top: black-box confidence. Bottom: white-box confidence. Columns: Directional agreement (MDA/Prec/Rec/F1), Magnitude error (MSE/SMSPE), and Calibration change (ΔBrier; negative is better).

Black-box (verbalized) confidence

| Model | Directional agreement | | | | Magnitude | | Cal. |
	MDA	Prec	Rec	F1	MSE	SMSPE	ΔBrier
Qwen backbone							
DS R1 Qwen-1.5B	0.2529	0.4413	0.2529	0.2559	0.0258	0.1033	0.0232
Qwen-2.5 1.5B	0.2372	0.4768	0.2372	0.2455	0.0262	0.1059	0.0238
DS R1 Qwen-7B	0.3534	0.4639	0.3534	0.3791	0.0232	0.0939	0.0210
Qwen-2.5 7B	0.2603	0.4361	0.2603	0.2654	0.0256	0.1015	0.0231
LLaMA backbone							
DS R1 LLaMA-8B	0.3360	0.4710	0.3360	0.3607	0.0237	0.0947	0.0214
LLaMA-3.1 8B	0.2199	0.3003	0.2199	0.2063	0.0267	0.1067	0.0244

White-box (logit-based) confidence

| Model | Directional agreement | | | | Magnitude | | Cal. |
	MDA	Prec	Rec	F1	MSE	SMSPE	ΔBrier
Qwen backbone							
DS R1 Qwen-1.5B	0.2461	0.4740	0.2461	0.2325	0.0260	0.1050	0.0236
Qwen-2.5 1.5B	0.2298	0.4505	0.2298	0.2360	0.0266	0.1065	0.0241
DS R1 Qwen-7B	0.3440	0.4422	0.3440	0.3650	0.0237	0.0951	0.0217
Qwen-2.5 7B	0.2545	0.4228	0.2545	0.2592	0.0259	0.1022	0.0234
LLaMA backbone							
DS R1 LLaMA-8B	0.3271	0.4595	0.3271	0.3510	0.0242	0.0960	0.0219
LLaMA-3.1 8B	0.2144	0.2925	0.2144	0.2018	0.0273	0.1082	0.0249

at qualitative directional reasoning.

Inspecting the directional confusion matrices (Appendix E.2, Fig. 6) reveals distinct biases across scales. Under the Single setting, the larger models (DS R1 Qwen-7B and LLaMA-8B) exhibit a conservative bias, strongly favoring the "Still" label. In contrast, DS R1 Qwen-1.5B behaves noisily, frequently predicting "Up" on true "Down" or "Still" cases. In the Accumulated condition, the larger models remain conservative but become increasingly prone to spurious "Up" predictions on "True Still" instances (e.g., rising from 221 to 278 for Qwen-7B), while 1.5B remains scattered. Overall, smaller models overreact noisily, whereas the conservatism of larger models is easily disrupted into spurious upward shifts by multiple updates. This confirms that accumulated context introduces noise rather than improving directional agreement.

Table 2: Directional QA format results under Single (S) and Accumulated (A) settings. Metrics cover directional agreement for Up/Down/Still labels.

Model	MDA	Prec	Rec	F1
DS R1 Qwen-1.5B (S)	0.3521	0.4401	0.3521	0.3762
DS R1 Qwen-1.5B (A)	0.3620	0.4366	0.3620	0.3838
DS R1 Qwen-7B (S)	0.4675	0.4538	0.4675	0.4581
DS R1 Qwen-7B (A)	0.4314	0.4387	0.4314	0.4320
DS R1 LLaMA-8B (S)	0.4923	0.4621	0.4923	0.4714
DS R1 LLaMA-8B (A)	0.4389	0.4383	0.4389	0.4351

6.3 Ablation: Accumulated News Context

Table 3 reports results when models are given access to the *entire sequence of news updates from T_0 to T_1* (Accumulated) rather than only the latest update (Single). This setting tests whether richer temporal context improves belief updating. A single forecasting question can be associated with multiple news items over time, and the accumulated condition passes all updates in chronological order, while the single condition isolates only the most recent update.

To focus our ablation studies on temporal context, we restrict our analysis to the DeepSeek R1 models and report only verbalized confidence, which demonstrated greater stability in the main setting. Interestingly, Table 3 shows that providing accumulated news yields no consistent improvement and often degrades directional agreement for larger models like Qwen-7B and LLaMA-8B. This suggests that language models struggle to weight temporally ordered snippets effectively. Unlike human forecasters who dynamically discount older information, models appear to treat all updates with equal salience or become distracted by longer contexts. Ultimately, simply concatenating updates does not guarantee better adaptation, highlighting the broader challenge of enabling models to mean-

Table 3: Ablation on news context. Models are evaluated with only the most recent update (S) or the full sequence (A). Metrics grouped as in Table 1. Magnitude error and calibration change added once available.

Model	Directional agreement				Magnitude error		Calibration
	MDA	Prec	Rec	F1	MSE	SMSPE	ΔBrier
DS R1 Qwen-1.5B (S)	0.2529	0.4413	0.2529	0.2559	0.0258	0.1033	0.0232
DS R1 Qwen-1.5B (A)	0.2554	0.4564	0.2554	0.2512	0.0262	0.1052	0.0237
DS R1 Qwen-7B (S)	0.3534	0.4639	0.3534	0.3791	0.0232	0.0939	0.0210
DS R1 Qwen-7B (A)	0.3236	0.4565	0.3236	0.3473	0.0251	0.1024	0.0228
DS R1 LLaMA-8B (S)	0.3360	0.4710	0.3360	0.3607	0.0242	0.0960	0.0219
DS R1 LLaMA-8B (A)	0.3013	0.4687	0.3013	0.3196	0.0268	0.1083	0.0247

(a) Qwen-1.5B (S) (b) Qwen-7B (S) (c) LLaMA-8B (S)

(d) Qwen-1.5B (A) (e) Qwen-7B (A) (f) LLaMA-8B (A)

Figure 2: Normalized confusion matrices. DeepSeek R1 (S) vs (A) updates. Values: $\Pr(\text{pred} \mid \text{true})$ in %.

ingfully integrate evolving evidence.

The confusion matrices in Fig. 2 reinforce these findings. In the Single condition, all three models struggle to accurately predict "Still," frequently confusing "Up" and "Down." This bias worsens in the Accumulated condition, where Qwen-7B and LLaMA-8B increasingly misclassify "Still" cases as movement. Rather than meaningfully integrating signals over time, the models appear to accumulate noise. They interpret multiple temporal snippets as directional evidence, amplifying minor fluctuations into spurious updates even when the reference forecasters remained stable. Consequently, as shown in Table 3, providing accumulated news fails to improve consistency with the human reference and often drives models further from calibrated updating. Appendix E.1 provides *delta* heatmaps (A−S) detailing exactly how this confusion mass shifts.

6.4 Additional Ablations

We briefly summarize two further ablations, with full results and visualizations in Appendix G: 1. *Similarity-Sensitive Confidence* implements a semantics-aware estimate (Kuhn et al., 2023) by clustering multiple generations into groups of similar answers and aggregating their confidence. In practice, since our task is binary, the clustering almost always reduces to two groups, limiting its usefulness. While such methods may prove more valuable in open-ended generation settings, here they do not offer additional insight over simpler probability estimates; 2. *Human Forecast Reference as Context* augments prompts with an aggregate human forecast at the corresponding time, providing the model with an explicit calibration anchor. However, we observe no measurable improvements, suggesting that models are unable to effectively exploit even strong external reference signals.

7 Conclusion

We introduced EVOLVECAST, the first framework to assess how language models revise forecasts when new evidence emerges. We find that while models often track the correct update direction, their quantitative shifts are systematically underresponsive, with confidence estimates falling far short of human references. These results suggest current LLMs treat new information merely as static retrieval context rather than evidence that dynamically shifts posterior probabilities, underscoring the critical need for more robust approaches to sequential belief updating.

Limitations

Our study is limited in scope in several ways. We focus on binary forecasting questions, which provides clarity for evaluation but does not cover all types of forecasting tasks. We also evaluate a small set of openly available reasoning models, so results should not be overgeneralized. Finally, because the data construction relies on public APIs and human discussion timestamps, exact replication of forecaster information exposure is not possible. These constraints are inherent to working with real-world forecasting data, and we have aimed to minimize their impact in this paper.

Ethical Statement

This work evaluates how large language models update their forecasts when exposed to new information. Our experiments are conducted entirely on publicly available models and datasets. The forecasting questions and human reference data are sourced from Metaculus, an open platform with strict guidelines for question resolution and user conduct. The news snippets paired with questions are retrieved from publicly accessible web sources, and only short excerpts (title and headline) are included for research purposes. No private or sensitive data are used.

We recognize that forecasting research can have downstream societal implications. Forecasts produced by models may influence decision making in domains such as politics, economics, or health. Our goal is not to deploy automated forecasters, but to analyze their current limitations in belief updating and calibration. By highlighting where models fall short relative to human references, we aim to support the responsible use of AI in forecasting contexts and to discourage premature deployment of uncalibrated systems. All results should therefore be interpreted as a diagnostic study of model behavior, not as actionable forecasts.

References

Joris Baan, Raquel Fernández, Barbara Plank, and Wilker Aziz. 2024. Interpreting predictive probabilities: Model confidence or human label variation? *arXiv preprint arXiv:2402.16102*.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, and 1 others. 2025. Qwen2. 5-vl technical report. *arXiv preprint arXiv:2502.13923*.

Glenn W Brier. 1950. Verification of forecasts expressed in terms of probability. *Monthly weather review*, 78(1):1–3.

Arnaud De Myttenaere, Boris Golden, Bénédicte Le Grand, and Fabrice Rossi. 2016. Mean absolute percentage error for regression models. *Neurocomputing*, 192:38–48.

Guillaume Dezecache, Martin Dockendorff, Dardo N Ferreiro, Ophelia Deroy, and Bahador Bahrami. 2022. Democratic forecast: Small groups predict the future better than individuals and crowds. *Journal of Experimental Psychology: Applied*, 28(3):525.

Zifeng Ding, Sikuan Yan, Zhangdie Yuan, Xianglong Hu, Fangru Lin, and Andreas Vlachos. 2025. Tcp: a benchmark for temporal constraint-based planning. *arXiv preprint arXiv:2505.19927*.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Zishan Guo, Renren Jin, Chuang Liu, Yufei Huang, Dan Shi, Linhao Yu, Yan Liu, Jiaxuan Li, Bojian Xiong, Deyi Xiong, and 1 others. 2023. Evaluating large language models: A comprehensive survey. *arXiv preprint arXiv:2310.19736*.

Danny Halawi, Fred Zhang, Chen Yueh-Han, and Jacob Steinhardt. 2024. Approaching human-level forecasting with language models. *arXiv preprint arXiv:2402.18563*.

Scott Jeen, Matthew Aitchison, and Mantic. 2026. Training llms to predict world events. *Thinking Machines Lab: News*. Https://thinkingmachines.ai/news/training-llms-to-predict-world-events/.

Woojeong Jin, Rahul Khanna, Suji Kim, Dong-Ho Lee, Fred Morstatter, Aram Galstyan, and Xiang Ren. 2020. Forecastqa: A question answering challenge for event forecasting with temporal text data. *arXiv preprint arXiv:2005.00792*.

Ezra Karger, Houtan Bastani, Chen Yueh-Han, Zachary Jacobs, Danny Halawi, Fred Zhang, and Philip E Tetlock. 2024. Forecastbench: A dynamic benchmark of ai forecasting capabilities. *arXiv preprint arXiv:2409.19839*.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2023. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. *arXiv preprint arXiv:2302.09664*.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. TruthfulQA: Measuring How Models Mimic Human Falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

Jingwei Liu, Ling Yang, Hongyan Li, and Shenda Hong. 2024. Retrieval-augmented diffusion models for time series forecasting. *Advances in Neural Information Processing Systems*, 37:2766–2786.

Zijia Liu, Peixuan Han, Haofei Yu, Haoru Li, and Jiaxuan You. 2025. Time-r1: Towards comprehensive temporal reasoning in llms. *arXiv preprint arXiv:2505.13508*.

Kevin Murphy. 2026. Agentic forecasting using sequential bayesian updating of linguistic beliefs. *arXiv preprint arXiv:2604.18576*.

Barbara Plank. 2022. The "problem" of human label variation: On ground truth in data, modeling and evaluation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10671–10682, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S Gordon. 2011. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *2011 AAAI spring symposium series*.

Kutay Tire, Ege Onur Taga, Muhammed Emrullah Ildiz, and Samet Oymak. 2024. Retrieval augmented time series forecasting. *arXiv preprint arXiv:2411.08249*.

Zhen Wang, Xi Zhou, Yating Yang, Bo Ma, Lei Wang, Rui Dong, and Azmat Anwar. 2025. Openforecast: A large-scale open-ended event forecasting dataset. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 5273–5294.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. 2023. Can llms express their uncertainty? an empirical evaluation of confidence elicitation in llms. *arXiv preprint arXiv:2306.13063*.

Chenchen Ye, Ziniu Hu, Yihe Deng, Zijie Huang, Mingyu Derek Ma, Yanqiao Zhu, and Wei Wang. 2024. Mirai: Evaluating llm agents for event forecasting. *arXiv preprint arXiv:2407.01231*.

Chenhan Yuan, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024a. Back to the future: Towards explainable temporal reasoning with large language models. In *Proceedings of the ACM on Web Conference 2024*, pages 1963–1974.

Moy Yuan, Eric Chamoun, Rami Aly, Chenxi Whitehouse, and Andreas Vlachos. 2024b. PRobELM: Plausibility ranking evaluation for language models. In *First Conference on Language Modeling*.

Zhangdie Yuan, Zifeng Ding, and Andreas Vlachos. 2025. Forecast: The future outcome reasoning and confidence assessment benchmark. *arXiv preprint arXiv:2502.19676*.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. HellaSwag: Can a Machine Really Finish Your Sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4791–4800, Florence, Italy. Association for Computational Linguistics.

Andy Zou, Tristan Xiao, Ryan Jia, Joe Kwon, Mantas Mazeika, Richard Li, Dawn Song, Jacob Steinhardt, Owain Evans, and Dan Hendrycks. 2022. Forecasting future world events with neural networks. *Advances in Neural Information Processing Systems*, 35:27293–27305.

A The Use of Large Language Models

Large language models were used in the preparation of this paper as writing assistants. Specifically, they were employed to refine phrasing, improve clarity, and suggest alternative structures for sections and subsections. Models were also used to draft prompt templates in an iterative process, which were then carefully reviewed, tested, and adjusted by the authors.

B Reproducibility Statement

We have taken several steps to make our study as reproducible as possible. We provide a number of implementation details in the paper, including data construction steps, hyperparameter choices, and prompt templates. We also release the full set of processed question–news pairs used in our experiments, together with cleaned code, as supplementary material.

One limitation is that our news retrieval step relies on the Google Search API. Because search

results may vary over time and are influenced by ranking algorithms, exact replication of the retrieval stage cannot be guaranteed. Despite this, we make available the aligned data used in our experiments so that downstream evaluation can be reproduced. We believe these materials, combined with the methodological details provided in the text, give future researchers the necessary resources to replicate and extend our work.

C Example Metaculus Questions

To illustrate how human forecasts evolve over time, consider a question:

Q1: Will the US Senate weaken or eliminate the filibuster before January 3, 2029?

For Q1, Figure 3 shows how community forecasts changed over time, while Figure 4 presents the histogram of the final forecast distribution.

Figure 3: Community prediction trend for a Metaculus question on the US Senate filibuster issue.

Figure 4: Histogram of final community forecasts.

D Experimental Details

D.1 Implementation Details

Decoding parameters. All models are evaluated with identical sampling hyperparameters: temperature = 0.6 and top_p = 0.95. We set the maximum output length to max_tokens = 1024 for verbalized (black-box) confidence runs, and max_tokens = 2048 for logit-based (white-box) runs.

Evaluation thresholds. Directional agreement metrics (Sec. 3.2) use a minimal change threshold ϵ. For verbalized confidence we set $\epsilon = 0$, treating even small probability movements as valid shifts. For logit-based confidence we set $\epsilon = 0.05$ to reduce noise from minor fluctuations in token-level probabilities.

Implementation. All experiments are run with identical random seeds to ensure consistency across model conditions. In cases where models fail to produce valid JSON outputs, we assign the lowest possible score for that instance. A detailed list of hyperparameters and scripts used for inference are included in the supplementary code release.

D.2 Prompt Templates

We used standardized prompt templates across all models to ensure comparability. Each template contains three blocks: a <question> field with the forecasting question, a <metadata> field with the evaluation date and optional news update, and a <task> field describing the required output format. Prompts also include a <think> tag to encourage reasoning before producing the final answer when necessary.

Verbalized confidence. The model is instructed to provide a probability estimate on a 1–10 scale with descriptive anchors. We normalize the returned score to $[0, 1]$ for evaluation. An example template is:

```
<question>
${title}
</question>

<metadata>
- Today is ${start_time}.
- You do not have access to updates
after ${start_time}.
- A recent news update: "${best_news}"
</metadata>

<task>
You are an AI model predicting the
likelihood of future events, now
incorporating recent news.
Your task is to estimate the probability
of the following event occurring, given
the recent news update.

Provide your confidence score on a
scale of 1 to 10, where:
1 - Extremely unlikely
2 - Very unlikely
3 - Unlikely
4 - Somewhat unlikely
5 - Neutral (50-50 chance)
6 - Somewhat likely
7 - Likely
8 - Very likely
9 - Extremely likely
10 - Almost certain

Return the confidence score in this
format after thinking:
{ "confidence": X }
</task>
<think>
```

Logit-based confidence. The model is prompted to output a binary answer ("Yes"/"No"). Token-level probabilities are then extracted directly from the output distribution. An example template is:

```
<question>
${title}
</question>

<metadata>
- Today is ${start_time}.
- You do not have access to updates
after ${start_time}.
- A recent news update: "${best_news}"
</metadata>

<task>
You are an AI model predicting the
likelihood of future events, now
incorporating recent news.
Your task is to answer if the following
event will occur, given the recent news
update.
You must also provide an answer with
your best guess.

Return the answer in this format after
thinking:
{ "answer": "Yes" / "No" }
</task>
<think>
```

E   Additional Visualizations

E.1   Delta Heatmaps: Accumulated minus Single

Figure 5 visualizes the difference between Accumulated and Single news contexts as *delta* heatmaps (A−S). Blue cells indicate reduced probability mass in the accumulated condition, while red cells indicate increased mass. Across models, the largest shifts occur in the "Still" column: accumulated updates tend to reduce correct "Still" predictions and redistribute probability into "Up" or "Down." This pattern complements the quantitative results in Table 3 and the confusion matrices in Fig. 2, confirming that accumulated context often introduces spurious directional movement rather than improving alignment with the reference.

E.2   Additional Visualizations for Direct Directional Prompting

The visualization complements Table 2 by highlighting systematic biases in how models allocate their predictions. The smaller DS R1 1.5B model produces noisy outputs and often overpredicts "Up," even when the true label is "Down" or "Still." By contrast, DS R1 7B and 8B show a strong conservative bias toward "Still" in the Single setting,

but under Accumulated context they shift toward predicting "Up" more frequently. Together, these trends illustrate how accumulated evidence can introduce spurious movements and reduce directional accuracy, especially in larger models.

F   Direct Directional Prompting Template

For the direct directional prompting setting, models are asked to classify the impact of a news update as "Up," "Down," or "Still." This approach removes the need to compare before/after probabilities and directly probes whether the model can identify the directional effect of new information. The exact prompt is shown below:

```
<question>
${title}
</question>

<metadata>
- Today is ${start_time}.
- You do not have access to updates
after ${start_time}.
- A recent news update: "${best_news}"
</metadata>

<task>
You are an AI model analyzing how recent
news impacts event predictions.
Your task is to determine whether the
confidence in this event occurring
should increase, decrease, or remain
the same after seeing the news.

Return the predicted_trend in this
format after thinking:

{ "trend": "Up" / "Down" / "Still" }
</task>
<think>
```

This minimal QA-style interface makes the task closer to classification benchmarks and avoids dependence on numeric probability estimation, which often suffers from poor calibration.

G   Additional Ablations

G.1   Similarity-Sensitive Confidence

In this ablation, we implement a semantics-aware confidence estimation method inspired by clustering-based approaches (Kuhn et al., 2023). The intuition is that if a model generates multiple plausible answers, the distribution of these generations can provide a more robust uncertainty estimate than any single output. Concretely, we sample N candidate outputs $\{y^{(1)}, \ldots, y^{(N)}\}$ and group them into K clusters based on cosine similarity

Figure 5: Delta confusion heatmaps (**A−S**) for **DS R1** models. Each plot shows the difference between column-normalized confusion matrices under Accumulated vs. Single updates, i.e., changes in $\Pr(\text{pred} \mid \text{true})$ (percentage points). Positive values indicate increased mass under Accumulated; negative values indicate decreased mass.

(a) DS R1 Qwen-1.5B (A−S)   (b) DS R1 Qwen-7B (A−S)   (c) DS R1 LLaMA-8B (A−S)

Figure 6: Normalized predicted distributions for the **Directional QA** setting. Bars show the distribution of predicted labels (Up = blue, Down = orange, Still = green) for each true label across DS R1 models under Single (S) and Accumulated (A) news conditions.

of sentence embeddings (Reimers and Gurevych, 2019). Confidence for cluster C_k is then defined as

$$\hat{p}_k = \frac{\sum_{i:y^{(i)} \in C_k} P(y^{(i)} \mid x)}{\sum_{j=1}^{K} P(C_j)},$$

where $P(y^{(i)} \mid x)$ is the sequence-level probability of output $y^{(i)}$, computed as the average token probability across the sequence. For binary questions ($K = 2$), we report $\hat{p}_{\text{Yes}}$ as the final confidence estimate.

In practice, this approach does not yield benefits in EVOLVECAST, since binary Yes/No questions naturally collapse to two clusters. Thus, while clustering may offer richer signals in open-ended generation tasks (e.g., free-form QA or summarization), in binary forecasting it effectively reduces to re-labeling outputs without adding new information. Full quantitative results are shown in Table 4.

To further illustrate, Figs. 7 plots the confusion matrices for DS R1 Qwen-1.5B under both the baseline logits method and the clustering variant. The matrices show that clustering does not meaningfully shift the distribution of errors: the model still predicts "Still" excessively, and when it does move, the confusion between "Up" and "Down" persists.

Table 4: Comparison of logits-based confidence with and without semantic clustering for DS R1 Qwen-1.5B. Metrics are directional agreement (MDA/Prec/Rec/F1).

Method	MDA	Prec	Rec	F1
Logits (S)	0.252	0.494	0.252	0.236
Logits (A)	0.259	0.491	0.259	0.236
Logits+Clust. (S)	0.247	0.442	0.247	0.239
Logits+Clust. (A)	0.259	0.471	0.259	0.260

G.2 Human Forecast Reference as Context

We also test an ablation where the model is provided with the contemporaneous aggregate human

(a) Logits (Single)   (b) Logits+Clustering (Single)

(c) Logits (Accumulated)   (d) Logits+Clustering (Accumulated)

Figure 7: Normalized confusion matrices for DS R1 Qwen-1.5B under logits-based confidence and logits+clustering, for Single and Accumulated news. Values are column-normalized, showing $\Pr(\text{pred} \mid \text{true})$ (%). Clustering yields no qualitative change in error distribution.

forecast as an additional context feature. Prompts are augmented with a line such as: *"Human forecast for this question on t is $h_t\%$."* This setting gives the model an explicit calibration anchor that, in principle, should simplify the task by showing where expert forecasters stood at the time.

The motivation is twofold. First, it simulates a collaborative human–AI forecasting scenario, where models can build on expert input rather than starting entirely from scratch. Second, it allows us to probe whether models meaningfully reason about how new evidence shifts beliefs relative to the anchor, or whether they simply mirror the human input.

Table 5 reports results under this setting for three DS R1 models using verbalized confidence (black-box) and direct directional prompting. While direct prompting again achieves higher directional agreement than verbalized probabilities, providing the human forecast reference itself does not yield any measurable improvement. This is somewhat surprising, as human forecasters rely heavily on such

reference anchors; the lack of benefit here suggests that current models are unable to incorporate even strong external signals into their belief updating in a meaningful way.

Table 5: Results for human forecast reference as context, comparing verbalized confidence and direct directional prompting under the Single Update setting. Direct prompting consistently outperforms verbalized confidence, but including human forecasts as anchors produces no measurable gains.

Model	Method	MDA	Precision	Recall	F1
DS R1 Qwen-1.5B	Verbalized	0.279	0.487	0.279	0.284
	Directional QA	0.350	0.441	0.350	0.376
DS R1 Qwen-7B	Verbalized	0.308	0.461	0.308	0.329
	Directional QA	0.457	0.462	0.457	0.457
DS R1 LLaMA-8B	Verbalized	0.307	0.479	0.307	0.327
	Directional QA	0.487	0.455	0.487	0.467