COLA: CONSISTENT LEARNING WITH OPPONENT-LEARNING AWARENESS

ABSTRACT

Optimization problems with multiple, interdependent losses, such as Generative Adversarial Networks (GANs) or multi-agent RL, are commonly formalized as *differentiable games*. Learning with Opponent-Learning Awareness (LOLA) introduced *opponent shaping* to this setting. More specifically, LOLA introduced an augmented learning rule that accounts for the agent's influence on the anticipated learning step of the other agents. However, the original LOLA formulation is *inconsistent* because LOLA models other agents as *naive learners* rather than LOLA agents. Contrary to claims made, we show that Competitive Gradient Descent (CGD) does not solve the consistency problem and does not recover high-order LOLA (HOLA) as a series expansion. Working towards remedy, we formalise the concept of consistency and show that HOLA is consistent whenever it converges (while CGD may not). However, it may fail to converge altogether and we propose a new method called Consistent LOLA (COLA) which *learns* update functions that are consistent under mutual opponent shaping. Finally, we empirically compare the performance and consistency of LOLA, HOLA, and COLA on a set of general-sum learning games.

1 INTRODUCTION

Multi-objective problems can be found in many domains, such as GANs (Goodfellow et al., 2014) or single- and multi-agent reinforcement learning (RL) in the form of imaginative agents (Racanière et al., 2017), hierarchical RL (Barto & Mahadevan, 2002), and intrinsic curiosity (Schmidhuber, 1991). A popular framework to understand systems with multiple, interdependent losses is differentiable games (Balduzzi et al., 2018). For example, in the case of GANs, the differentiable game framework models the generator and the discriminator as competing agents, each trying to optimize their respective loss. The action space of the game consists of choosing the respective network parameters (Balduzzi et al., 2018).

An effective paradigm to improve learning in differentiable games is *opponent shaping*, where the players use their ability to shape each other's learning steps. LOLA (Foerster et al., 2018) was the first work to make explicit use of opponent shaping in the differentiable game setting. LOLA is also one of the only general learning methods designed for differentiable games that obtains mutual cooperation with the Tit-for-Tat strategy in the Iterated Prisoner's Dilemma (IPD). The Tit-for-Tat strategy starts out cooperating and retaliates once whenever the opponent does not cooperate. It achieves mutual cooperation and has proven to be successful at IPD tournaments (Axelrod, 1984; Harper et al., 2017). In contrast, naive gradient descent and other more sophisticated methods typically converge to the mutual defection policy under random initialization (Letcher et al., 2019b).

While LOLA discovers these interesting equilibria, the original LOLA formulation is inconsistent because LOLA agents assume that their opponent is a *naive learner*. This assumption is clearly violated if two LOLA agents learn together in a game. It has been suggested that this inconsistency is the root cause for LOLA's shortcomings, such as not converging to SFPs in some simple quadratic games (Letcher et al., 2019b).

Contributions. How can LOLA's inconsistency be resolved? To answer this question, we first revisit the concept of *higher-order* LOLA (HOLA) (Foerster et al., 2018) in Section 4.1. For example, *second-order* LOLA assumes that the opponent is a *first-order* LOLA agent (which in turn

assumes the opponent is a naive learner) and so on. Assuming that HOLA converges with increasing order, we define *infinite-order* LOLA (iLOLA) as the limit of HOLA whenever it exists. Intuitively, it should follow that two iLOLA agents have a consistent view of each other, meaning they make an accurate assumption about the learning behavior of the opponent under mutual opponent shaping. We introduce a formal definition of consistency and prove that iLOLA is indeed self-consistent under mutual opponent shaping.

Second, previous work has claimed that a series expansion of Competitive Gradient Descent (CGD) (Schäfer & Anandkumar, 2020) recovers high-order LOLA. This would imply that CGD corresponds to iLOLA and thus solves the consistency problem. In Section 4.2, we prove that this is false: CGD does not in general correspond to iLOLA, and, unlike iLOLA, does not resolve the problem of consistency. In particular, we show that, contrary to previous claims, the series expansion of CGD does *not* correspond to higher-order LOLA.

Third, there are a number of problems with addressing consistency using a limiting update (iLOLA): the process may not converge, and requires computation of arbitrarily high derivatives. In Section 4.3, we propose Consistent LOLA (COLA) as a more general and efficient alternative. Instead of repeatedly applying the LOLA learning rule (iLOLA), COLA learns a pair of consistent update functions by explicitly minimizing a consistency loss. By reframing the problem as such, the method only requires up to second-order derivatives, and instead of having a handcrafted update function as for LOLA or CGD, we use the representation power of neural networks to *learn* the update step.

Finally, in Sections 5 and 6, we report our experimental setup and results, investigating COLA and HOLA and comparing it to LOLA and CGD in a range of games. We demonstrate that, contrary to prior belief, resolving the inconsistency problem with iLOLA does not resolve LOLA's shortcomings (maintaining the original SFPs). Moreover, we provide evidence that COLA finds the iLOLA solution when HOLA converges but finds different solutions when HOLA diverges. These solutions are shown to be more consistent (as defined in Section 4.1) and converge under a broader range of learning rates than LOLA and HOLA. We support this empirical evidence for more robust convergence with a theoretical result for the Hamiltonian game (Section 6.1). Our experiments also show that, while COLA does not find Tit-for-Tat on the IPD (unlike LOLA), it does learn policies with near-optimal total payoff (Section 6.3).

2 RELATED WORK

General-sum learning algorithms and their consequences have been investigated from different perspectives in the reinforcement learning, game theory, and GAN literature, see e.g. (Schmidhuber, 1991; Barto & Mahadevan, 2002; Racanière et al., 2017; Goodfellow et al., 2014) to name a few. Next, we will highlight a few of the approaches to the mutual opponent shaping problem.

Opponent modeling maintains an explicit belief of the opponent, which allows to reason over their strategies and compute optimal responses. Opponent modeling can be divided into different subcategories: There are classification methods, classifying the opponents into pre-defined types (Weber & Mateas, 2009; Synnaeve & Bessiere, 2011), or policy reconstruction methods, where we explicitly predict the actions of the opponent (Mealing & Shapiro, 2017). Most closely related to opponent shaping is recursive reasoning, where methods model nested beliefs of the opponents (He et al., 2016; Albrecht & Stone, 2019; Wen et al., 2019).

In comparison, COLA assumes that we have access to the ground-truth model of the opponent, e.g., the opponent's payoff function, parameters, and gradients, which puts COLA into the framework of differentiable games (Balduzzi et al., 2018). Various methods have been proposed, investigating the local convergence properties to different solution concepts (Mescheder et al., 2018; Mazumdar et al., 2019; Letcher et al., 2019b; Azizian et al., 2020; Schäfer & Anandkumar, 2020; Schäfer et al., 2020; Hutter, 2020). Most of the work in differentiable games has not focused on the issue of opponent shaping and consistency. Mescheder et al. (2018) and Mazumdar et al. (2019) focus solely on zero-sum games without shaping. Letcher et al. (2019b) improve on LOLA, but do not investigate the consistency issue. CGD (Schäfer & Anandkumar, 2020) addresses the consistency issue of LOLA for zero-sum games but not for general-sum games. The exact difference between CGD and LOLA is addressed in the Section 4.2.

3 BACKGROUND

3.1 DIFFERENTIABLE GAMES

The framework of differentiable games has become increasingly popular to model the problem of multi-agent learning. Whereas in the framework of stochastic games we are typically limited to parameters such as action-state probabilities, differentiable game generalizes to any parameters as long as the loss function is differentiable with respect to them (Balduzzi et al., 2018). We restrict our attention on two-player games, as is standard in the current differentable games literature.

Definition 1 (Differentiable games). In a two-player differentiable game, players $i = 1, 2$ control parameters $\theta_i \in \mathbb{R}^{d_i}$ to minimize twice continuously differentiable losses $L^i : \mathbb{R}^{d_1+d_2} \to \mathbb{R}$. We adopt the convention to write $-i$ to denote the respective other player.

A fundamental challenge of the multi-loss setting is finding a meaningful solution concept. Whereas in the single loss setting the typical solution concept is local minima, in multi-loss settings there are different sensible solution concepts. Most prominently, there are Nash Equilibria (Osborne & Rubinstein, 1994). However, Nash Equilibria include unstable saddle points that cannot be reasonably found via gradient-based learning algorithms (Letcher et al., 2019b). A more appropriate concept are stable fixed points (SFPs), which could be considered a differentiable game analogon to local minima in single loss optimization. We will omit a formal definition here for brevity and point the interested reader to previous work on the topic (Letcher et al., 2019a).

3.2 LOLA

Let us assume we are modeling a differentiable game with two players. A LOLA agent θ_1 uses its access to the opponents parameters θ_2 to differentiate through the learning step of the opponent. In other words, agent 1 reformulates their loss to $L^1 (\theta_1, \theta_2 + \Delta\theta_2)$, where $\Delta\theta_2$ represents the assumed learning step of the opponent. In first-order LOLA we assume the opponent to be a naive learner: $\Delta\theta_2 = -\alpha \nabla_2 L^2$, which is what makes LOLA inconsistent if the opponent was any other type of learner. Note that ∇_2 denotes the gradient with respect to θ_2. Also note that α represents the *look-ahead* rate, which is the assumed learning rate of the opponent. In the original paper the loss was approximated using a Taylor expansion $L^1 + (\nabla_2 L^1)^\top \Delta\theta_2$. For agent 1, their first-order (Taylor) LOLA update is then defined as

$$\Delta\theta_1 := -\alpha \left(\nabla_1 L^1 + \nabla_{12} L^1 \Delta\theta_2 + (\nabla_1 \Delta\theta_2)^\top \nabla_2 L^1 \right).$$

Alternatively, in *exact* LOLA, the derivative is taken directly with respect to $L^1 (\theta_1, \theta_2 + \Delta\theta_2)$.

LOLA has had some empirical success, being one of the first general learning methods to discover Tit-for-Tat like solutions in social dilemmas. However, later work showed that LOLA does not preserve SFPs $\bar{\theta}$ since the rightmost term can be nonzero at $\bar{\theta}$. In fact, LOLA agents show "arrogant" behavior: they assume they can shape the learning of their *naive* opponents without having to adapt to the shaping of the opponent. Prior work hypothesized that this arrogant behavior is due to LOLA's inconsistent formulation (Letcher et al., 2019a).

3.3 CGD

CGD (Schäfer & Anandkumar, 2020) proposes updates that are themselves Nash Equilibra of a local bilinear approximation of the game. It stands out by its robustness to different step sizes of opponents and its ability to find SFPs. However, CGD does not find Tit-for-Tat on the IPD, instead converging to mutual defection (see Figure 13). CGDs update rule can be written as

$$\begin{pmatrix} \Delta\theta_1 \\ \Delta\theta_2 \end{pmatrix} = -\alpha \begin{pmatrix} \text{Id} & \alpha \nabla_{12} L^1 \\ \alpha \nabla_{21} L^2 & \text{Id} \end{pmatrix}^{-1} \begin{pmatrix} \nabla_1 L^1 \\ \nabla_2 L^2 \end{pmatrix} \tag{1}$$

One can recover different orders of CGD by approximating the inverse matrix via the series expansion $\|A\| < 1 \Rightarrow (\text{Id} - A)^{-1} = \lim_{N \to \infty} \sum_{k=0}^{N} A^k$. For example, at N=1, we recover a version called Linearized CGD (LCGD), defined via $\Delta\theta_1 := -\alpha \nabla_1 L^1 + \alpha^2 \nabla_{12} L^1 \nabla_2 L^2$.

Table 1: (a) This table shows the log of the squared consistency loss on the Tandem game, where e.g. HOLA6 is sixth-order higher-LOLA. (b) Cosine similarity between COLA and LOLA, HOLA2, and HOLA6 over different look-ahead rates on the Tandem game.

(a)

α	LOLA	HOLA2	HOLA6	COLA
1.0	128.0	512	131072	4.84e-14
0.5	12.81	14.05	12.35	2.62e-14
0.3	2.61	2.05	0.66	4.09e-14
0.1	0.08	9.13e-3	1.62e-6	6.55e-14
0.01	1.41e-5	2.10e-8	3.69e-14	8.58e-14

(b)

α	LOLA	HOLA2	HOLA4
1.0	0.57	0.58	0.60
0.5	0.61	0.46	0.15
0.3	0.92	0.51	0.72
0.1	0.94	0.98	0.99
0.01	0.99	1.0	1.0

4 METHOD AND THEORY

4.1 CONVERGENCE AND CONSISTENCY OF HIGHER-ORDER LOLA

To begin, we define and analyze iLOLA. In this section, we focus on exact LOLA, but we provide a version of our definition and proof of consistency for Taylor LOLA in Appendix C. HOLAn is defined by the recursive relation

$$h_1^n := -\alpha \nabla_1 \left(L^1(\theta_1, \theta_2 + h_2^{n-1}) \right)$$
$$h_2^n := -\alpha \nabla_2 \left(L^2(\theta_1 + h_1^{n-1}, \theta_2) \right)$$

with $h_1^{-1} = h_2^{-1} = 0$, omitting arguments (θ^1, θ^2) for convenience. In particular, HOLA0 coincides with simultaneous gradient descent while HOLA1 coincides with LOLA.

Definition 2 (iLOLA). If HOLA$n = (h_1^n, h_2^n)$ converges pointwise as $n \to \infty$, define

$$\text{iLOLA} := \lim_{n \to \infty} \begin{pmatrix} h_1^n \\ h_2^n \end{pmatrix}$$

as the limiting update.

We show in Appendix A that HOLA does not always converge, even in simple quadratic games. On the other hand, iLOLA satisfies a criterion of *consistency* whenever HOLA does converge (under some assumptions), formally defined as follows:

Definition 3 (Consistency). Any update functions $h_1 \colon \mathbb{R}^d \to \mathbb{R}^{d_1}$ and $h_2 \colon \mathbb{R}^d \to \mathbb{R}^{d_2}$ are *consistent* (under mutual opponent shaping) if for all $\theta_1 \in \mathbb{R}^{d_1}, \theta_2 \in \mathbb{R}^{d_2}$, they satisfy

$$h_1 = -\alpha \nabla_1 (L^1(\theta_1, \theta_2 + h_2)) \tag{2}$$
$$h_2 = -\alpha \nabla_2 (L^2(\theta_1 + h_1, \theta_2)) \tag{3}$$

Proposition 1. *Let* HOLA$n = (h_1^n, h_2^n)$ *denote player i's exact n-th order LOLA update. Assume that* $\lim_{n \to \infty} h_i^n(\theta) = h_i(\theta)$ *and* $\lim_{n \to \infty} \nabla_i h_{-i}^n(\theta) = \nabla_i h_{-i}(\theta)$ *for all θ and $i \in \{1, 2\}$. Then iLOLA is consistent under mutual opponent shaping.*

Proof. In Appendix B. □

4.2 CGD DOES NOT RECOVER HIGHER-ORDER LOLA

Schäfer & Anandkumar (2020) claim that "LCGD coincides with first order LOLA" (page 6), and moreover that the "series-expansion [of CGD] would recover higher-order LOLA" (page 4). Unfortunately, we prove that this is untrue in general games. LCGD coincides instead with LookAhead (Zhang & Lesser, 2010), an algorithm that distinctly lacks opponent shaping. Similarly, the series-expansion of CGD recovers high-order LookAhead but not high-order LOLA (neither exact nor Taylor).

Proposition 2. *In general, CGD is inconsistent and does not coincide with iLOLA. In particular, the series-expansion of CGD does not recover HOLA (but does recover high-order LookAhead); moreover, LCGD does not coincide with LOLA (but does coincide with LookAhead).*

Figure 1: Subfigure (a), (b) and (c) depicts the log of the consistency loss over the training of the update functions for the Tandem, MP and Ultimatum games. Subfigure (d), (e) and (f) show the performance of COLA in comparison to HOLA:0.1, LOLA:0.1 and CGD:0.1. COLA:0.1 denotes COLA with a look-ahead rate of 0.1.

Proof. In Appendix D. For the negative results, it suffices to construct a single counter-example: we show that LCGD and LOLA differ almost-everywhere in the tandem game (excluding a set of measure zero). Proving that the series-expansion of CGD does not recover HOLA relies on noticing that this would imply CGD satisfying the consistency equations for α sufficiently small. We prove that this also fails almost-everywhere in the tandem game. We then show that LCGD = LookAhead and that the series-expansion of CGD recovers high-order LookAhead in general games. □

4.3 COLA

iLOLA is consistent under mutual opponent shaping. However, HOLA does not always converge and, even when it does, it may be expensive to recursively compute HOLAn for sufficiently high n to achieve convergence.

As an alternative, we propose consistent LOLA (COLA). COLA finds consistent update functions and avoids an infinite regress by directly solving the equations in Definition 3 numerically. To do so, we define the *consistency losses* for a pair of update functions (h_1, h_2) parameterized by (ϕ_1, ϕ_2), obtained for a given θ as the difference between RHS and LHS in Definition 3:

$$C_1(\phi_1, \phi_2, \theta_1, \theta_2) = \left\| h_1(\theta_1, \theta_2) + \alpha \nabla_1 (L^1(\theta_1, \theta_2 + h_2(\theta_1, \theta_2))) \right\| \tag{4}$$

$$C_2(\phi_1, \phi_2, \theta_1, \theta_2) = \left\| h_2(\theta_1, \theta_2) + \alpha \nabla_2 (L^2(\theta_1 + h_1(\theta_1, \theta_2), \theta_2)) \right\| . \tag{5}$$

If both losses are minimised to 0 for all θ, then the two update functions are consistent. For this paper, we define h_1 and h_2 as neural networks parameterized by ϕ_1 and ϕ_2 respectively, and numerically minimize the sum of both losses over a region of interest using Adam (Kingma & Ba, 2017).

The parameter region of interest Θ depends on the game being played. For a game with probabilities as actions, we select an area that captures most of the probability space (e.g. we sample a pair of parameters $(\theta_1, \theta_2) \sim [-7, 7]$ as $\sigma(7) \approx 1$, where σ is the Sigmoid function).

The expected aggregate consistency loss over the region is then defined as

$$C(\phi_1, \phi_2) = \mathbb{E}_{(\theta_1, \theta_2) \sim \mathcal{U}(\Theta)} \left[C_1(\phi_1, \phi_2, \theta_1, \theta_2) + C_2(\phi_1, \phi_2, \theta_1, \theta_2) \right]. \tag{6}$$

Table 2: (a) Comparison of consistency losses over multiple look-ahead rates on the MP game. (b) Cosine similarity between COLA and LOLA, HOLA2 and HOLA4 over different look-ahead rates on the MP game.

(a)

α	LOLA	HOLA2	HOLA4	COLA
10	0.06	0.70	6.56	0.24
5	4.59e-3	0.03	0.15	9.47e-3
1.0	8.79e-6	3.25e-8	4.37e-9	2.35e-7
0.5	4.80e-7	2.53e-10	5.18e-12	1.30e-7
0.01	1.07e-13	5.58e-17	5.30e-17	6.99e-8

(b)

α	LOLA	HOLA2	HOLA4
10	0.90	0.87	0.68
5	0.98	0.95	0.89
1.0	0.99	0.99	0.99
0.5	0.99	0.99	0.99
0.01	0.99	0.99	0.99

Concretely, we optimize this loss by sampling parameter pairs (θ_1, θ_2) uniformly from Θ and feeding them to the neural networks h_1 and h_2 respectively, each outputting the parameter update for an agent. We then update ϕ_1, ϕ_2 by taking a gradient step to minimize C.

We train the update functions until the loss has converged. We then use these update functions to train a pair of agent policies in the given game.

5 EXPERIMENTS

We carry out our investigation on a set of games from the literature (Balduzzi et al., 2018; Letcher et al., 2019b) using SOS and CGD as baselines. For details on the training procedure of COLA, we refer the reader to Appendix F.

First, we compare HOLA and COLA on quadratic, general-sum games, including the Tandem game (Letcher et al., 2019b), where LOLA fails to converge to SFPs. Second, we investigate non-quadratic games, such as the zero-sum Matching Pennies (MP) game, the general-sum Ultimatum game (Hutter, 2020) and the iterated prisoner's dilemma (IPD) (Axelrod, 1984; Harper et al., 2017).

We investigate the convergence behavior of HOLA and COLA by comparing the consistency losses over a range of look-ahead rates, where COLA is retrained for each look-ahead rate to ensure a fair comparison. To compare the solutions found by HOLA and COLA, we compute the cosine similarity between the two across randomly sampled parameters across our region of interest.

5.1 QUADRATIC GAMES

Tandem Game. In the Tandem game (Letcher et al., 2019b), two agents sit on a tandem bike, facing opposite directions. Their actions, $\theta_1 = x$ and $\theta_2 = y$, are the forces applied to the pedals respectively. An agent can pedal backward by using negative values. The goal is to move in one direction, e.g. $x \approx -y$, however, the agents receive a penalty for pedaling backward. This is captured in the loss

$$L^1(x, y) = (x + y)^2 - 2x \quad \text{and} \quad L^2(x, y) = (x + y)^2 - 2y \tag{7}$$

for agent 1 and 2 respectively. The Tandem game was originally introduced to show that LOLA fails to preserve SFPs at $x + y = 1$ and instead converges to sub-optimal solutions (Letcher et al., 2019b). Additionally to the Tandem game, we investigate the algorithms on the quadratic Balduzzi and Hamiltonian games (Balduzzi et al., 2018). The details of the experiments are in Appendix G.2.

5.2 NON-QUADRATIC GAMES

Matching Pennies. Matching Pennies (MP) is a single-shot, zero-sum game, where two players, A and B, each flip a biased coin (Lee & K, 1967). Player A wins if the outcomes of both flips are the same and player B wins if they are different. The payoff matrix is shown in Table 6. Each policy is parameterized with a single parameter, the log-odds of choosing heads $p_{\text{heads}} = \sigma(\theta_A)$. In this game, the unique Nash equilibrium is playing heads half the time.

Ultimatum Game. The binary, single-shot Ultimatum game (Güth et al., 1982; Sanfey et al., 2003; Oosterbeek et al., 2004; Henrich et al., 2006) is set up as follows. There are two players, player A

Figure 2: Training in MP at look-ahead rate of $\alpha = 10$. (a) Axes are on a log-scale. Increasing the consistency helps with decreasing the variance of the solution. (b) LOLA and HOLA find non-convergent or even diverging solutions, while COLA is convergent.

and B. Player A has access to \$10. They can split the money fairly with B (\$5 for each player) or they can split it unfairly (\$8 for player A, \$2 for player B). Player B can either accept or reject the proposed split. If player B rejects, the reward is 0 for both players. If player B accepts, the reward follows the proposed split. Player A's parameter is the log-odds of proposing a fair split $p_{\text{fair}} = \sigma(\theta_A)$. Player B's parameter is the log-odds of accepting the unfair split (assuming that player B always accepts fair splits) $p_{\text{accept}} = \sigma(\theta_B)$.

$$V_A = 5p_{\text{fair}} + 8(1 - p_{\text{fair}})p_{\text{accept}} \quad \text{and} \quad V_B = 5p_{\text{fair}} + 2(1 - p_{\text{fair}})p_{\text{accept}} \tag{8}$$

IPD. We next investigate the infinitely iterated prisoners' dilemma with discount factor $\gamma = 0.96$ and the usual payout function (see Appendix G.6). An agent i is defined through 5 parameters, the log-odds of cooperating for the first time step and for the four possible tuples of past actions of both players in the later steps.

6 RESULTS

Here, we outline our experimental results, providing evidence on the empirical behavior of COLA and comparing COLA to HOLA and our baselines. We also provide a theoretical result on the convergence of COLA in the Hamiltonian game. Additional results can be found in Appendix G.

6.1 QUADRATIC GAMES

Table 1a shows the log of the squared consistency loss on the Tandem game for COLA and different orders of HOLA. Note that HOLA's consistency losses decrease with increasing order of HOLA for look-ahead rates below 0.5. The decrease in consistency loss with increasing order indicates that HOLA converges with increasing order. However, the consistency losses increase with look-ahead rates above 0.5. Therefore, HOLA does not always converge, even on simple quadratic games such as the Tandem game.

Table 1b shows the cosine similarities between the HOLA and COLA update functions over Θ. When HOLA converges, COLA also finds a consistent solution, and HOLA and COLA become more similar with increasing order, indicating that they find the same solution. In the cases where HOLA does not converge, COLA still finds consistent solutions. Here, the similarity scores indicate no similarity and fluctuate greatly, probably because the higher-order gradients of HOLA become increasingly noisy. COLA still finds convergent solutions in this case, as shown by the performance of COLA at a look-ahead rate of 0.8 in Figure 1d, showcasing the benefits of higher consistency.

For a qualitative comparison between HOLA and COLA, note that on Figure 1d the solution of HOLA and COLA are nearly identical in the Tandem game, given the same look-ahead rate. Also,

(a) (b) (c)

(d) (e) (f)

Figure 3: Results are on the IPD. Subfigure (a) / (d), show the consistency loss for look-ahead rate of 0.03 / 1.0 respectively, (b) / (e) the average loss and (c) / (f) the policy for the first player, both for the same pair of look-ahead rates. At low look-ahead HOLA defects and at high ones it diverges, also leading to high loss.

COLA or HOLA still do not find the SFP, showing that the consistency issue was not the (only) reason for the arrogant behavior of LOLA.

It is unclear whether the consistency equations in Definition 3 have a unique solution, even for simple games such as Matching Pennies or the Tandem game. However, we find that our COLA algorithm recovers very similar solutions in these games over 5 convergent training runs. For more details we refer to Table 7 in the Appendix. Note that COLA's training does not always find a good solution at high look-ahead rates. In Appendix G.2, we confirm our results on the Balduzzi and Hamiltonian games.

The following proposition provides further theoretical evidence that consistency leads to more robust convergence:

Proposition 3. *For any non-zero initial parameters and any $\alpha > 1$, LOLA and SOS have divergent iterates in the Hamiltonian game. By contrast, any linear solution to the consistency equations converges to the origin for any initial parameters and **any** look-ahead rate $\alpha > 0$; moreover, the speed of convergence strictly increases with α.*

Proof. In Appendix E. $\square$

6.2 NON-QUADRATIC GAMES

Next, we will address our questions for a set of non-quadratic games. Like with the quadratic games, we find that HOLA only converges under certain look-ahead rates and in those cases COLA finds very similar solutions. In contrast to the quadratic games, when HOLA converges, COLA's consistency loss is now higher than HOLA's. Nonetheless, the similarity scores show that COLA's solution is nearly the same. While the consistency loss for high look-ahead rates is high compared to small ones, in those cases COLA finds more consistent solutions than HOLA. The exact consistency losses are given in Table 2a and Appendices G.4 and G.5.

In a visual comparison between the gradient fields of HOLA and COLA, we see that a diverging HOLA results in chaotic gradients, whereas COLA is still able to learn meaningful and convergent update functions, which further reinforces the importance of consistency. Visualizations are given in Appendices G.3, G.4 and G.5.

Table 3: (a) Comparison of consistency losses over multiple look-ahead rates on the IPD game. (b) Cosine similarity between COLA and LOLA, HOLA2 and HOLA4 over different look-ahead rates, α on the IPD game.

	(a)					(b)		
α	LOLA	HOLA2	HOLA4	COLA	α	LOLA	HOLA2	HOLA4
1.0	39.56	21.16	381.21	0.65	1.0	0.77	0.70	0.53
0.03	1.72e-3	4.72e-6	9.72e-8	0.33	0.03	0.96	0.98	0.98

Our results show various benefits of increased consistency in MP. We compare the losses of HOLA and COLA with different look-ahead rates in MP in Figure 1e. The high look-ahead rate case is shown in Figure 2b. With small look-ahead rates COLA shows slower convergence than HOLA. While HOLA at high look-ahead rates diverges quickly, COLA is still able to find a convergent solution. In Figure 2a, we plot the variance of the solutions found by different methods against their respective consistency loss, at a high look-ahead rate. The variance of the solution on the MP game decreases significantly with decreasing consistency loss.

We can also confirm empirically that COLA finds similar solutions over multiple convergent runs in Appendix G.3. For more results and qualitative comparisons, we refer the reader to Appendices G.3, G.4 and G.5.

6.3 IPD

For the IPD we look at two different look-ahead rates, one where HOLA converges and one where it diverges. Previous work investigated the IPD on look-ahead rates where HOLA diverges (Letcher et al., 2019b).

Both LOLA and COLA find the Defect-Defect strategy under the look-ahead regimes where HOLA converges, as can be seen in Figure 3. Furthermore, the consistency loss of COLA is relatively high, as shown in Table 3a. However, in Table 3b we see that we find a very similar solution to the one found by HOLA.

For a look-ahead rate of 1.0, COLA's consistency loss is relatively high and as such might not constitute a solution to the consistency problem. We leave it to future work to find methods that obtain better solutions. Nonetheless, the consistency loss for COLA is much lower than the losses for HOLA, as seen in Table 3a. We see in Figure 3e that COLA does not learn a pure Tit-for-Tat strategy but achieves close to the optimal loss, whereas HOLA's loss becomes worse and more stochastic, corresponding roughly to a fully random policy.

7 CONCLUSION AND FUTURE WORK

In this paper we cleared up the relation between the CGD and LOLA algorithms. We also showed that iLOLA solves part of the consistency problem of LOLA. We introduced a new method, called Consistent LOLA, that finds consistent solutions without requiring many recursive computations like iLOLA . It was commonly believed that the inconsistency lead to arrogant behaviour and lack of preservation for SFPs. Empirically, we show that even with consistency, opponent shaping behaves arrogantly, pointing towards a fundamental open problem for the method.

Furthermore, we empirically investigated the consistency behavior of higher-order LOLA and COLA and found that HOLA's updates do not converge with increasing order in each hyperparameter regime, even for low-dimensional games with polynomial losses. Moreover, we showed empirically that increased consistency increases robustness to different look-ahead rates.

This work opens more questions for future work than it answers. Some fundamental questions are the existence and uniqueness of the COLA equations and their relationship to learning outcomes.

Additional work is needed to scale COLA to large settings such as GANs or Deep RL, or settings with more than two-players. Another interesting axis is accounting for further inconsistent aspects of LOLA as identified in Letcher et al. (2019b) and address them via an extension of COLA.