Embodied Scene-aware Human Pose Estimation

Figure 1: From a monocular video input in a known scene, we estimate 3D absolute body pose by controlling a simulated character to match 2D observation in a sequential manner.

Abstract

We propose *embodied scene-aware human pose estimation* where we estimate 3D poses based on a simulated agent's proprioception and scene awareness, along with external third-person observations. Unlike prior methods that often resort to multistage optimization, non-causal inference, and complex contact modeling to estimate human pose and human scene interactions, our method is one stage, causal, and recovers global 3D human poses in a simulated environment. Since 2D third-person observations are coupled with the camera pose, we propose to disentangle the camera pose and use a multi-step projection gradient defined in the global coordinate frame as the movement cue for our embodied agent. Leveraging a physics simulation and prescanned scenes (*e.g.,* 3D mesh), we simulate our agent in everyday environments (libraries, offices, bedrooms, *etc.*) and equip our agent with environmental sensors to intelligently navigate and interact with scene geometries. Our method also relies only on 2D keypoints and can be trained on synthetic datasets derived from popular human motion databases. To evaluate, we use the popular H36M and PROX datasets and, for the first time, achieve a success rate of 96.7% on the challenging PROX dataset without ever using PROX motion sequences for training.

1   Introduction

We consider a 3D human pose estimation setting where a calibrated camera is situated within a prescanned environment (with known 3D geometries such as meshes). Such a setting has a wide

range of applications in mixed reality telepresence, animation and gaming, at-home robotics, video surveillance, *etc.*, where a single fixed RGB camera is often used to observe human movement. However, even under such constraints, severe occlusion, low-textured garments, and human-scene interactions often cause pose estimation methods to fail catastrophically. Especially when estimating global 3D human pose estimation, state-of-the-art methods often resort to expensive multistage batch optimization [5], motion prior or infilling [26, 42], and depth information to recover reasonable global translation and orientation. Consequently, these methods cannot be applied in a streaming fashion and have limited use cases in time-critical applications. Multistage optimization can also suffer from failure of convergence, where the optimizer cannot find a good solution due to either occlusion, numerical instability, or bad initialization.

Effective use of scene information is also critical for estimating human pose. Unfortunately, the lack of datasets with paired ground truth 3D body pose and annotated contact labels make it difficult to incorporate scene information to estimate pose. Thus, popular methods often resort to minimizing the distance between predefined contact points in the body and the scene [5], using vertex-based proximity [43] as a proxy scene representation, or semantic labels as affordance cues [15]. These methods, while effective in modeling human-scene interactions, are expensive to compute and heavily rely on an batch optimization procedure to achieve good performance. More complex scenes are also harder to model in a batch optimization framework, as the number of contact constraints increases significantly as the number of geometries increases.

We hypothesize that **embodiment** may be a key element in estimating accurate absolute 3D human poses. Here we define embodiment as having a tangible existence in a simulated environment in which the agent can act and perceive. In particular, humans move according to their current body joint configuration (proprioception), movement destination (goal), and an understanding of their environment's physical laws (scene awareness and embodiment). Under these guiding principles, we propose **embodied scene-aware human pose estimation** as an alternative to optimization-based and regression-based methods. Concretely, we estimate poses by controlling a physically simulated agent equipped with environmental sensors to mimic visual observations in a streaming fashion. At each timestep, our agent receives movement goal from a third-person observation and computes its torque actuation based on (1) current agent state: body pose, velocities, *etc.*, (2) comparison between its current pose and visual observation, and (3) environmental features from the agent's point of view. Acting in a physics simulator, our agent can receive timely feedback about physical plausibility, contact, and scene geometry to compute the next time frame pose estimate. While there exist prior methods that also use simulated characters, we draw the distinction in how the next-frame target pose is computed. Previous work often directly regresses the kinematic pose [3, 40] without considering the current state of the body and environmental signals. As a result, when the kinematic pose estimation method fails due to occlusion, these embodied agents will receive unreasonable target poses. Our method, on the other hand, predicts body velocities by comparing the current body pose with visual observations. When 2D observations are occluded, body velocities will be computed based on environment cues and current body states. Thus, our method is more robust to occlusion and can recover from consecutive frames of missing body part observations. Our method is also able to estimate pose for long-term (several minutes), in sub-real-time (10 fps), while creating physically realistic human scene interactions.

To achieve this, we propose a multistep projection gradient (MPG) to provide movement cues to our embodied agent from 2D observations. At each time step, MPG performs an iterative gradient descent starting from the current pose of the humanoid to exploit the temporal coherence of human movement and better avoid local minima. MPG also directly provides temporal body and root movement signals in the world coordinate frame to our agent, so our method does not need to explicitly take the 3D camera pose as input. To control a simulated character, we extend the Universal Humanoid Controller (UHC) and the kinematic policy proposed in previous work [18] to support the control of humanoids with different body shapes in environments with diverse geometries. Finally, we equip our agent with an occupancy-based environmental sensor to learn about affordances and avoidance. Since only 2D keypoint coordinates are needed by our method to estimate body motion, our model can also be learned from purely synthetic data.

To summarize, our contribution is as follows: 1) we propose embodied scene-aware human pose estimation, where we control a simulated scene-aware humanoid to mimic visual observations and recover accurate global 3D human pose and human-scene interactions; 2) we formulate a multistep projection gradient(MPG) to provide camera-agnostic movement signal for an embodied agent to

match 2D observations; and 3) we achieve state-of-the-art result on the challenging PROX dataset while our method remains sub-real-time, causal, and trained on synthetic data derived from popular human motion databases.

2   Related Work

Local and Absolute 3D Human Pose Estimation.   It is popular to estimate the 3D human pose in the body local coordinate system (relative to the root) [1, 9, 10, 11, 12, 13, 14, 17, 21, 22, 24, 25, 32, 34] where translation is discarded and root rotation is relative to the camera coordinate frame. Among these methods, some focus on lifting 2D keypoints to 3D [1, 24], while others use a template 3D human mesh (the SMPL [16] body model and its extensions [23, 27]) and jointly recover body shape and joint angles. Among these methods, some [13, 32, 40] make use of iterative optimization to better fit 2D keypoints. SPIN [13] devises an optimization-in-the-loop fitting procedure to provide a better starting point for a pose regressor. NeuralGD [32] and SimPOE [40] both utilize a learned gradient update to iteratively refine body pose and shape, where the optimization starts from either zero pose (NeuralGD) or estimated kinematic pose (SimPOE). Compared to these methods, our MPG starts the optimization process from previous time-step pose to leverage the temporal coherence in human motion. While the estimating pose in the local coordinate frame is useful in certain applications, it is often desirable to recover the pose in the absolute/global space to fully leverage the estimated pose for animation or telepresence. However, recovering the absolute 3D body pose (which includes root translation) is challenging due to limb articulation, occlusion, and depth ambiguity. Among the works that attempt to estimate the absolute human pose [21, 24, 25, 28], most take a two-stage approach where the root-relative body pose is first regressed from a single image, and then a root translation module is used to estimate the absolute depth from image-level features. In comparison to these methods, we leverage physical laws and motion cues to autoregressively recover both root movement and body pose.

Scene-aware Human Pose and Motion Modeling   The growing interest in jointly modeling human pose and human-scene interactions has led to a growing popularity in datasets containing both human and scenes [6, 20, 36]. In this work, we focus on the PROX [6] dataset, where a single human is recorded moving in daily indoor environments such as offices, libraries, bedrooms, etc. Due to the diversity of motion and human-scene interaction (sitting on chairs, lying on beds, etc.) and lack of ground-truth training data, the Prox dataset remains highly challenging. Consequently, state-of-the-art methods are mainly optimization-based [6, 26, 41] while leveraging the full set of observations (scene scans, camera pose, depth). HuMoR [26] and LEMO [41] achieves impressive result by using large-scale human motion datasets to learn strong prior of human movement to constrain or infill the missing human motion. However, multistage optimization can often become unstable due to occlusion or failures in 2D keypoint detections.

Physics-based humanoid control for pose estimation   Physical laws guard every aspect of human motion and there is growing interest in enforcing physics prior in human pose estimation [3, 7, 18, 30, 31, 37, 38, 39, 40]. Some methods prefer to use physics as a postprocessing step and refine initial kinematic pose estimates [30, 31, 37], while ours follows the line of work where a simulated character is controlled to estimate pose inside a physics simulation [3, 7, 18, 40]. Although both approaches have their respective strong suites, utilizing a physics simulation simplifies the process of incorporating unknown scene geometries for contact and can empower real-time pose estimation applications. Among simulated character control-based methods, Neural Mocon [7] utilizes sampling-based control and relies on the learned distribution of human motion from the training split of the dataset to acquire quality motion samples. SimPOE [40] first extracts the kinematic pose using off-the-shelf method [11] and then uses simulated agent for imitation. PoseTriplet [3] proposes using a self-supervised framework to co-evolve a pose estimator, imitator, and hallucinator. Compared to ours, SimPoE and PoseTriplet both relies on a kinematic pose estimator as backbones [11, 24] and requires well-observed 2D keypoints for reliable pose estimates. They also require lengthy policy training time and do not model any scene geometries. Our work also extends Kin_poly [18], where a simulated character is used to perform the *first-person* pose estimation. While Kin_poly uses egocentric motion as the only motion cue we proposes a multi-step Projection Gradient to leverage thrid-person observations. Compared to their object-pose based scene feature, we use an occupancy-based scene feature inspired by the graphics community [4, 33] to better model affordance.

Figure 2: Our embodied human pose estimation framework: given 2D keypoint features, our model computes the next-time frame pose based on 2D observation (multi-step projection gradient ϕ_t), proprioception features (body pose $_t$), and scene features (occupancy s_t).

3 Method

Given a monocular video $I_{1:T}$ taken using a calibrated camera in a known environment, our aim is to estimate, track, and simulate 3D human motion in metric space. We denote the 3D human pose as $q_t \triangleq (r_t^R, r_t^T, \theta_t)$, consisting of the 3D root position r_t^T, the orientation r_t^R and the angles of the body joints θ_t. As a notation convention, we use $\tilde{\cdot}$ to represent kinematic poses (without physics simulation), $\hat{\cdot}$ to denote ground-truth quantities from Motion Capture (MoCap), and normal symbols without accents for values from the physics simulation. In Sec 3.1, we will first summarize our extension to the Universal Humanoid Controller [18] to support controlling people with different body proportions. Then, in Sec.3.2, we will describe the state space of our character's control policy: the multistep projection gradient (MPG) as a feature and occupancy scene feature. Finally, we will detail the training procedure to learn our embodied pose estimator using synthetic datasets in Sec 3.3. Our pose estimation pipeline is visualized at Fig.2.

3.1 Preliminaries: Physics-based Character and Universal Humanoid Controller (UHC)

To simulate people with varying body shapes, we first use an automatic simulated character creation process similar to SimPoE [40] to generate human bodies with realistic joint limits, body proportions, and other physical properties based on the popular human mesh model SMPL [16]. In SMPL, body joints are recovered from mesh vertices and a joint regressor, so length of each limb may vary depending on body pose. This is undesirable as computing a large number of vertices (6890) is time-consuming and varying body limb length is physically inaccurate. Therefore, we fix the lengths of the limbs using those calculated from T-pose (zeroing the angles of the joints) and use forward kinematics to recover the 3D location of the body joints J_t. Given the shape of the body β and the pose q_t, we define the forward kinematics function as $\text{FK}_\beta(q_t) \rightarrow J_t$.

To learn a universal humanoid controller that can perform everyday human motion with different body types, we follow the standard formulation in physics-based character and model controlling a humanoid for motion imitation as a Markov Decision Process (MDP) defined as a tuple $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{T}, R, \gamma \rangle$ of states, actions, transition dynamics, reward function, and discount factor. The state $s \in \mathcal{S}$, reward $r \in \mathcal{R}$, and transition dynamics $\mathcal{T}$ are determined by the physics simulator, while the action $a \in \mathcal{A}$ is given by the control policy $\pi_{\text{UHC}}(a_t|s_t, \hat{q}_t, \beta)$. Here we extend the Universal Humanoid Controller proposed in Kin_poly [18] condition the control policy on the current simulation state s_t, the reference motion $\hat{q}_t$, and the body shape β. We employ Proximal Policy Optimization (PPO) [29] to find the optimal control policy π_{UHC} to maximize the expected discounted reward $\mathbb{E}\left[\sum_{t=1}^{T} \gamma^{t-1} r_t\right]$. For more information on the UHC network architecture and training procedure, please refer to Kin_poly [18] and our Appendix.

3.2 Embodied Scene-Aware Human Pose Estimation

To estimate the global body pose from the image observations, we control a simulated character to follow 2D keypoint observations sequentially. Assuming a known camera pose and scene geometry, we first use an off-the-shelf 2D keypoint pose estimator, DEKR [2], to extract 2D keypoints kp_t^{2D} at a per-frame level. Then, we use an off-the-shelf pose and body shape estimator, HuMoR [26] to extract the first-frame 3D pose $\widetilde{\boldsymbol{q}}_0$ and body shape $\boldsymbol{\beta}$ from RGB observations as initialization. Given $\widetilde{\boldsymbol{q}}_0$ and $\boldsymbol{\beta}$, we initialize our simulated character inside pre-scanned scene, and then we attempt to estimate poses which matches the observed 2D keypoints in a streaming fashion.

Multi-step Projection Gradient (MPG) as a Motion Feature   To match the motion of the 3D simulated humanoids to 2D keypoint observations, it is essential to provide 3D information about how poses should be modified in the global coordinate frame (coordinate frame of the scene geometry and the 3D humanoid). As 2D keypoints are coupled with camera pose (the same body pose corresponds to different 2D keypoints based on the camera pose), it is problematic to directly input 2D observations without a proper coordinate transform. To avoid this issue, prior arts that use simulated character control [3, 40] often estimate the kinematic human pose in the camera coordinates using a kinematic pose estimator. However, since the up-vector of the camera is not always aligned with the direction of gravity, corrections to the character's z direction are often needed for a successful simulation [3].

To decouple the pose of the camera from the pose estimation pipeline, we propose using a multi-step projection gradient (MPG) feature as an alternative to an estimated kinematic pose feature as an input to the policy. Intuitively, the MPG is a modified (learned) sum of 2D projection loss gradients that encodes how much the 3D pose should be adjusted for a better fit. Given the current global state of the humanoid $\boldsymbol{q}_t$ and the camera projection function π_{cam}, we define MPG ϕ as:

$$\phi_t = \boldsymbol{q}_t^K - \boldsymbol{q}_t^0 = \sum_{k=0}^{K} \mathcal{G}\left(\frac{\partial \mathcal{L}_{\text{proj}}}{\partial \boldsymbol{q}_t^k}, \boldsymbol{q}_t^k, \text{kp}_{t-\mu:t+1}^{\text{2D}}\right), \text{ where } \boldsymbol{q}_t^{k+1} = \boldsymbol{q}_t^k - s \cdot \mathcal{G}\left(\frac{\partial \mathcal{L}_{\text{proj}}}{\partial \boldsymbol{q}_t^k}, \boldsymbol{q}_t^k, \text{kp}_{t-\mu:t+1}^{\text{2D}}\right)$$
(1)

and $\mathcal{L}_{\text{proj}} = \|\pi_{\text{cam}}(\text{FK}_\beta(\boldsymbol{q}_t)) - \text{kp}_{t+1}^{\text{2D}}\|_2$ is the L_2 reprojection loss with respect to the observed 2D keypoints $\text{kp}_{t+1}^{\text{2D}}$. s is the step size of the gradient and k indexes into the total number of gradient descent steps K. The 2D project loss gradient $\frac{\partial \mathcal{L}}{\partial \boldsymbol{q}_t}$ represents how the root pose and body joints should change to better match the 2D keypoints of the next frame and contains rich geometric information independent of the camera projection function π_{cam}.

Due to noise in 2D keypoint detection, occlusion, and depth ambiguity, a single instantaneous projection gradient $\frac{\partial \mathcal{L}_{\text{proj}}}{\partial \boldsymbol{q}_t^k}$ can be erroneous and noisy, especially the gradient of root translation and orientation. Thus, we augment $\frac{\partial \mathcal{L}_{\text{proj}}}{\partial \boldsymbol{q}_t^k}$ with a geometric and learning-based transform $\mathcal{G}$ which is intended to remove noise. In this way, the MPG feature is an aggregation of a collection of modified gradients to compute a more stable estimate of the 2D projection loss gradient.

Inspired by PoseTriplet [3], we use a temporal convolution model (TCN) similar to VideoPose3D [24] to regress the camera-space root orientation from 2D keypoints. We note that while TCN may produce unreasonable pose estimate during server occlusion, its root orientation estimation remains stable. We compute the camera space root orientation using a causal TCN $\mathcal{F}_{\text{TCN}}$ and transforms it into the world coordinate system root orientation $r_t'^{\text{R}}$ using the inverse camera rotation: $r_t'^{\text{R}} = \mathcal{F}_{\text{TCN}}(\text{kp}_{t-\mu:t+1}^{\text{2D}})$. We then compute the difference between current root rotation r_t^{R} and $r_t'^{\text{R}}$ as an additional movement gradient signal. Given the current 3D pose $\boldsymbol{q}_t^k$ and the projection function π_{cam}, we can obtain a better root translation $\boldsymbol{r}_t^T$ by treating the obtained 3D keypoints as fixed on a rigid body and solving for translation using linear least squares. Combining the $\mathcal{F}_{\text{TCN}}$ model and the geometric transformation step, we obtain the function $\mathcal{G}$ to obtain a better root translation and orientation gradient. By taking multiple steps, we avoid getting stuck in local minima and obtain better gradient estimates. For a more complete formulation of MPG, see our Appendix.

Scene Representation   To provide our embodied agent with an understanding of its environment, we use a voxel-based occupancy map to indicate the location and size of the scene geometries, similar to [4, 33]. Occupancy provides a basic level scene and object awareness to our agent and is robust

212 to changing scene geometries. Concretely, we create a cube of 2 meters in diameter as the sensing
213 range of our agent's surroundings, and creates a 16 by 16 by 16 evenly spaced grid. At the center of
214 each point on the grid, we sample the signed distance function of the scene $\mathcal{F}_s$ to acquire how far the
215 sampling point is from the geometries of the scene. Then, we threshold the gird feature to provide a
216 finer scene information. In time step t, for threshold $\sigma = 0.05$, the value for point p_i in the grid can
217 be computed as:

$$s_t^i = \begin{cases} 1 & \mathcal{F}_s(p_i) \leq 0 \\ 0 & \mathcal{F}_s(p_i) > \sigma \quad (2) \\ 1 - \mathcal{F}_s(p_i)/\sigma & \text{otherwise} \end{cases}$$

Figure 3: Our simplified scene for simulation.

218 As the scanned meshes provided by the PROX dataset often have incorrect volumes, we use an
219 automatic geometric fitting procedure to approximate the scene by simple shapes such as rectangles
220 and cylinders. The simplified scene can be visualized together in Equ.2. For more information about
221 our scene simplification process, please refer to Appendix.

Scene-aware Kinematic Policy To train and control our embodied agent in the physics simulator,
223 we extend a policy network similar to Kin_poly [18], with the important distinction that our kinematic
224 policy is scene-aware and performs third-person pose estimation. Under the guiding principle of
225 embodied human pose estimation, our kinematic policy $\boldsymbol{\pi}_{\text{KIN}}$ computes residual 3D movement $\tilde{\tilde{\boldsymbol{q}}}_t$
226 based on proprioception $\boldsymbol{q}_t$, movement goal $\boldsymbol{\phi}_t$, and scene awareness $\boldsymbol{s}_t$:

$$\tilde{\tilde{\boldsymbol{q}}}_t = \boldsymbol{\pi}_{\text{KIN}}(\boldsymbol{q}_t, \boldsymbol{\phi}_t, \boldsymbol{s}_t), \quad \tilde{\boldsymbol{q}}_{t+1} = \tilde{\tilde{\boldsymbol{q}}}_t + \tilde{\boldsymbol{q}}_t. \tag{3}$$

227 Specifically, the input $\boldsymbol{q}_t$ contains the current body joint configurations, $\boldsymbol{\phi}_t$ provides the movement
228 signal per step, while $\boldsymbol{s}_t$ provides awareness to the agent's surroundings. Within $\boldsymbol{\pi}_{\text{KIN}}$, an agent-
229 centric transform T_{AC} is used to transform $\boldsymbol{q}_t$, $\boldsymbol{\phi}_t$ and $\boldsymbol{s}_t$ into the agent-centirc coordinate system.
230 The output $\tilde{\tilde{\boldsymbol{q}}}_t$, is defined as $\tilde{\tilde{\boldsymbol{q}}}_t \triangleq (\tilde{\boldsymbol{r}}_t^{\text{R}}, \tilde{\boldsymbol{r}}_t^{\text{T}}, \tilde{\tilde{\boldsymbol{\theta}}}_t)$, which computes the velocity in root translation $\tilde{\boldsymbol{r}}_t^{\text{R}}$ and
231 orientation $\tilde{\boldsymbol{r}}_t^{\text{T}}$, as well as the joint angles $\tilde{\tilde{\boldsymbol{\theta}}}_t$. Notice that $\tilde{\tilde{\boldsymbol{q}}}_t$ computes the residual body movement
232 instead of the the full kinematic body pose $\tilde{\boldsymbol{q}}_{t+1}$ and establishes a better connection between the
233 movement feature $\boldsymbol{\phi}_t$. During inference, $\boldsymbol{\pi}_{\text{KIN}}$ works in tandem with $\boldsymbol{\pi}_{\text{UHC}}$ and computes the next-
234 step target pose $\tilde{\boldsymbol{q}}_{t+1}$ for the humanoid controller to mimic. In turn, $\boldsymbol{\pi}_{\text{KIN}}$ receives timely feedback
235 about physical realism, contact, and scene features based on physics simulation and agent's state.

3.3 Learning the embodied human pose estimator

237 Since $\boldsymbol{\pi}_{\text{KIN}}$ relies only on 2D keypoints, we can leverage the large-scale human motion data base
238 and train our pose estimation network using synthetic data. We use the AMASS [19], H36M [8],
239 and Kin_poly [18] datasets to dynamically generate 2D keypoints and 3D pose pairs for training.
240 At the beginning of each episode, we sample a motion sequence and randomly change its direction
241 and starting position in a valid range, similar to the procedure defined in NeuralGD [32]. Then we
242 use a randomly selected camera projection function π_{cam} to project 3D keypoints onto 2D images
243 to obtain paired 2D keypoints and human motion sequences. During training, we initialize the
244 agent with the ground-truth 3D location and pose. The H36M and Kin_poly dataset contains simple
245 human-scene interactions, such as sitting on chairs and stepping on boxes. To better learn object
246 affordance and collision avoidance, we also randomly sample scenes from the PROX dataset and pair
247 them with motions from the AMASS dataset. Although these motion sequences do not correspond to
248 the sampled scene, the embodied agent will hit the scene geometries while trying to follow the 2D
249 observations. We then stop the simulation when the agent deviates too far away from the ground-truth
250 motion to learn scene affordance and avoidance.

251 We train the kinematic policy as a per-step model together with physics simulation, following the
252 dynamics-regulated training procedure defined in [18]. Combining our UHC and our kinematic
253 policy, we can leverage the pre-learned motor skills from the UHC and let the kinematic policy act

ALGORITHM 1: Learning embodied pose estimator via dynamics-regulated training.

Input: Pre-trained controller π_{UHC}, ground truth motion dataset $\widehat{Q}$;
while *not converged* **do**

    $M_{\mathrm{dyna}} \leftarrow \emptyset$ initialize sampling memory ;
    while M_{dyna} *not full* **do**

        $q_{1:T} \leftarrow$ sample random sequence of human pose ;
        $\mathrm{kp}_{1:T}^{2D} \leftarrow \pi_{\mathrm{cam}}(q_{1:T})$ `// compute paired 2D projection . ;`
        $s_1 \leftarrow (q_1, \dot{q}_1)$ `// compute the initial state. ;`
        for $t \leftarrow 1...T$ **do**

            $\phi_t \leftarrow \sum_{k=0}^{K} \mathcal{G}(\frac{\partial \mathcal{L}_{\mathrm{proj}}}{\partial q_t^k}, q_t^k)$ `// acquires movement cues from 2D observations. ;`
            $\widetilde{q}_{t+1} \leftarrow \pi_{\mathrm{KIN}}(q_t, \phi_t, s_t) + q_t$
            $s_t \leftarrow (q_t, \dot{q}_t)$
            $s_{t+1} \leftarrow \mathcal{T}(s_{t+1}|s_t, a_t), a_t \leftarrow \pi_{\mathrm{UHC}}(a_t|s_t, \widetilde{q}_{t+1})$ `// physics simulation and agent`
            ` control using ` π_{UHC}
            store $(s_t, a_t, r_t, s_{t+1}, \widehat{q}_t, \widetilde{q}_{t+1})$ into memory M_{dyna}
        end

    end

end
$\pi_{\mathrm{KIN}} \leftarrow$ Supervised learning update using experiences collected in M_{dyna} for 10 epoches.

---

directly in a simulated physical space to obtain feedback on physical plausibility. The procedure for dynamics-regulated training is described in Alg. 1. In each episode, we connect the UHC and the kinematic policy using the result of the UHC and the physics simulation q_{t+1} to compute the input features to the kinematic policy. Using q_{t+1} verifies that $\widetilde{q}_t$ can be followed by our controller and informs our π_{KIN} of the current humanoid state to encourage the policy to adjust its predictions to improve stability. Here we only train our π_{KIN} using supervised learning, as we have third-person pose estimation is a more well-posed problem and requires less exploration than estimating pose from only egocentric videos [18]. For each motion sequence, our loss function is defined as $L1$ distance between the predicted kinematic pose and the ground truth plus a prior loss using a leaned motion transition prior p_θ and the encoder q_ϕ from HuMoR [26]. The prior term encourages the generated motion to be smoother:

$$\mathcal{L} = \sum_{t=0}^{T} w_{\mathrm{L1}} \|\hat{q}_t - \tilde{q}_t\|_1 + w_{\mathrm{prior}} D_{\mathrm{KL}}(q_\phi(z_t|\tilde{q}_t, \tilde{q}_{t-1})||p_\theta(z_t|\tilde{q}_{t-1})), \quad (4)$$

4 Experiments

Implementation details. We use the MuJoCo [35] physics simulator and use the simplified scene geometries as environments. The training process or our embodied pose estimator takes around 1 day on a RTX 3090 with 30 CPU threads. During inference, our network is causal and runs at 10 FPS on an Intel desktop CPU (not counting the time for 2D keypoint pose estimation, which runs at around 30 FPS [2]). For more implementation details and network architecture, please refer to Appendix.

Datasets Our Universal Humanoid Controller is trained on the training split of AMASS dataset which contains high-quality SMPL parameters of 11402 sequences curated from the various MoCap datasets. For training our pose estimator, we use motions from the AMASS training split, the Kin_poly dataset, and H36M dataset. The Kin_poly dataset contains 266 motion sequences of type sitting, stepping, pushing, and avoiding, and H36M dataset consists of 210 indoor videos with 51 different unique actions. Notice that we only use the motion sequences from these dataset and not the paired videos. For evaluation, we use videos from the PROX [6] dataset and the test split of H36M.

Metrics and Baselines. We compare against a series of state-of-the-art methods HyperIK [14], MeTRAbs [28], VIBE [11], and SimPOE [40] on the H36M dataset. On the PROX dataset, we compare against SOTA methods HuMoR [26], LEMO [41], and HyberIK with RootNet [21]. We use the official implementation for the above methods, all of which are under the MIT license. We

use pose-based and plausibility-based metrics for evaluation. To evaluate pose estimation when there is ground truth MoCap pose, we report the absolute/global and root-relative mean per joint position error: A-MPJPE and MPJPE. On the PROX dataset, since there is no ground truth 3D pose annotation, we report: success rate SR (whether the optimization procedure converges and whether the simulated agents loses balance), average chamfer distance from the point cloud (ACD, acceleration (ACC), and scene penetration frequency Freq. and distance Pen.. For a full definition of our evaluation metrics, please refer to Appendix.

4.1 Results

Results on H36M We report pose estimation on the H36M dataset at Table 1. Here we can see that our method achieves reasonable pose estimation result on both root-relative and global pose metrics. Notice that our experiment on the H36M dataset is meant to

Table 1: Our pose estimation result on the H36M dataset as a sanity check. *Since our method does not directly use any image-level feature and uses a different set of 2D keypoints for observation and 3D keypoints for evaluation, it is not a completely fair comparison against SOTA methods.

	Image-features	A-MPJPE ↓	MPJPE ↓	PA-MPJPE ↓	Accel.-D ↓
MeTRAbs [28]	✓	223.9	49.3	34.7	-
VIBE [14]	✓	-	61.3	43.1	15.2
SimPoE [40]	✓	-	56.7	41.6	6.7
HybrIK [14] w/ RootNet [21]	✗	135.9	65.2	43.4	-
Ours*	✗	258.6	92.8	72.3	8.4

be as a sanity check on our pose estimation framework and is not a fair comparison. Our method only uses a sparse set of detected 2D keypoints (12 keypoints) as input and does not directly use any image feature. We also evaluate on a different subset of 3D keypoints, as our use of forward kinematics FK_β causes our joint definition to be different from prior works.

Results on PROX Table 2 shows our result on the PROX dataset where we compare against SOTA multi-stage batch optimization based methods LEMO [41] and HuMoR [26]. We also report the result using HyperIK with RootNet [14] to show that severe occlusion and human scene interaction on the Prox dataset is also challenging to SOTA regression methods. From Table 2 we can see that our method achieves best ACD (chamfer distance) *without* using any depth information, and is competitive on all other metrics against both RGB and RGB-D based methods. Notice that LEMO and HuMoR both directly optimizes chamfer distance and ground penetration in their optimization formulation, our method only relies 2D keypoints and laws of physics to achieve plausible pose estimates. Since motion is best seen in videos, please refer to our supplementary video and appendix for quantitative comparison.

Table 2: Evaluation of plausibility on the PROX dataset. Notice that the success rate SR is defined different from our method and optimization based methods. For ours, SR is defined as whether the embodied agent loses balance and can not finish the sequence, while for optimization-based methods it is whether the procedure converges.

		Phys.	Scene	SR	ACD ↓	Ground Accel. ↓	Ground Freq. ↓	Scene Pen. ↓	Scene Freq. ↓	Pen. ↓
RGB-D	PROX [6]	✗	✓	90.0%	335.9	57.9	3.6	100.4	4.17	35.9
	HuMoR [26]	✗	✗	100.0%	77.7	3.2	0.2	44.7	0.26	37.1
	LEMO [41]	✗	✓	71.6%	313.7	2.37	0.0	14.47	0.16	22.84
RGB	HybrIK [14] w/ RootNet [21]	✗	✗	-	23512.7	311.04	4.7	368.9	0.60	48.6
	HuMoR [26]	✗	✗	98.3%	435.7	**3.48**	4.01	101.62	0.63	48.08
	Ours	✓	✓	96.7%	**148.8**	9.2	0.0	33.5	**0.0**	**10.60**

4.2 Ablation

In Table 3, we ablate the main components of our framework. Row 1 (R1) corresponds to not using any scene awareness; R2 uses MPG with only one time-step, which results in nosier gradients; R3 trains a model without using the geometric translation step in $\mathcal{G}$; R4 does not use the TCN model $\mathcal{F}_{TCN}$ in $\mathcal{G}$. Comparing R3 and R4 with R5, we can see that the learned function $\mathcal{G}$ is essential to obtain better root translation and orientation movement signal, without which the agent drifts significantly. R2 also showcases the importance of taking the gradient step multiples times to obtain

better gradients. R1 demonstrates that the scene-awareness further improves our result, where our agent learns important affordance information about chairs and sofas to improve sauces rate.

Table 3: Ablation study of different components of our framework.

w/ Scene Awareness	MGP w/o multi-step	MPG w/o Geometric	MPG w/o TCN	SR ↑	ACD↓	Accel. ↓	Ground Freq. ↓	Ground Pen. ↓	Scene Freq. ↓	Scene Pen. ↓
✗	✓	✓	✗	90.0%	261.9	10.6	0.0	32.6	0.0	14.4
✓	✗	✓	✓	63.3%	243.5	10.3	0.0	33.4	0.0	13.9
✓	✓	✗	✓	76.7%	404.5	11.4	0.0	32.1	0.0	**10.3**
✓	✓	✓	✗	85.0%	308.2	9.9	0.0	33.5	0.0	16.1
✓	✓	✓	✓	**96.7%**	**148.2**	**9.2**	0.0	33.5	0.0	10.6

5 Discussions

Failure Cases   While our method can estimate human pose and human-scene interaction from the PROX dataset with high success rate, there is still much room for improvement. We simplify all the humanoids and scene geometries as rigid bodies and do not model any soft materials such as human skin, cushions, or beds. As a result, our sitting and lying motion can often result in jittery motion, since contact occurs only in a very small surface area on the simulated body and hard surfaces. Prolonged occlusion can also cause our agent to lose track of the 2D keypoints and result in erroneous translation estimation. Therefore, our agent can get stuck between chairs and tables. Please refer to our supplementary and Appendix for visualization of failure cases.

Conclusion and Future Work   We introduce embodied scene-aware human pose estimation, where we formulate pose estimation in a known environment by controlling a simulated agent to follow 2D visual observations. Based on the 2D observation, its current body pose, and environmental features, our embodied agent acts in a simulated environment to estimate pose and interact with the environment. A multistep projection gradient (MPG) is proposed to provide global movement cues to the agent by comparing the current body pose and target 2D observations. The experimental result shows that our method, trained only on synthetic dataset derived from popular motion dataset bases, can estimate accurate global 3D body pose on the challenging PROX dataset while using only RGB input. Future work includes providing a movement prior for the embodied agent to intelligently sample body motion based on scene features to better deal with occlusion.

References

[1] Y.-F. Cheng, B. Yang, B. Wang, Y. Wending, and R. T. Tan. Occlusion-aware networks for 3d human pose estimation in video. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 723–732, 2019.

[2] Z. Geng, K. Sun, B. Xiao, Z. Zhang, and J. Wang. Bottom-up human pose estimation via disentangled keypoint regression. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 14671–14681, 2021.

[3] K. Gong, B. Li, J. Zhang, T. Wang, J. Huang, M. B. Mi, J. Feng, and X. Wang. Posetriplet: Co-evolving 3d human pose estimation, imitation, and hallucination under self-supervision. *ArXiv*, abs/2203.15625, 2022.

[4] M. Hassan, D. Ceylan, R. Villegas, J. Saito, J. Yang, Y. Zhou, and M. J. Black. Stochastic scene-aware motion prediction. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11354–11364, 2021.

[5] M. Hassan, V. Choutas, D. Tzionas, and M. J. Black. Resolving 3d human pose ambiguities with 3d scene constraints. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 2282–2292, 2019.

[6] M. Hassan, V. Choutas, D. Tzionas, and M. J. Black. Resolving 3D human pose ambiguities with 3D scene constraints. In *International Conference on Computer Vision*, Oct. 2019.

[7] B. Huang, L. Pan, Y. Yang, J. Ju, and Y. Wang. Neural mocon: Neural motion control for physically plausible human motion capture. *ArXiv*, abs/2203.14065, 2022.

[8] C. Ionescu, D. Papava, V. Olaru, and C. Sminchisescu. Human3.6m: Large scale datasets and predictive methods for 3d human sensing in natural environments. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 36(7):1325–1339, jul 2014.

[9] A. Kanazawa, M. J. Black, D. W. Jacobs, and J. Malik. End-to-end recovery of human shape and pose. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7122–7131, 2018.

[10] A. Kanazawa, J. Y. Zhang, P. Felsen, and J. Malik. Learning 3d human dynamics from video. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5607–5616, 2019.

[11] M. Kocabas, N. Athanasiou, and M. J. Black. Vibe: Video inference for human body pose and shape estimation. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5252–5262, 2020.

[12] M. Kocabas, C.-H. P. Huang, J. Tesch, L. Muller, O. Hilliges, and M. J. Black. Spec: Seeing people in the wild with an estimated camera. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11015–11025, 2021.

[13] N. Kolotouros, G. Pavlakos, M. J. Black, and K. Daniilidis. Learning to reconstruct 3d human pose and shape via model-fitting in the loop. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 2252–2261, 2019.

[14] J. Li, C. Xu, Z. Chen, S. Bian, L. Yang, and C. Lu. Hybrik: A hybrid analytical-neural inverse kinematics solution for 3d human pose and shape estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3383–3393, 2021.

[15] X. Li, S. Liu, K. Kim, X. Wang, M.-H. Yang, and J. Kautz. Putting humans in a scene: Learning affordance in 3d indoor environments. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12360–12368, 2019.

[16] M. Loper, N. Mahmood, J. Romero, G. Pons-Moll, and M. J. Black. Smpl: a skinned multi-person linear model. *ACM Trans. Graph.*, 34:248:1–248:16, 2015.

[17] Z. Luo, S. A. Golestaneh, and K. M. Kitani. 3d human motion estimation via motion compression and refinement. In *ACCV*, 2020.

[18] Z. Luo, R. Hachiuma, Y. Yuan, and K. Kitani. Dynamics-regulated kinematic policy for egocentric pose estimation. In *Advances in Neural Information Processing Systems*, 2021.

[19] N. Mahmood, N. Ghorbani, N. Troje, G. Pons-Moll, and M. J. Black. Amass: Archive of motion capture as surface shapes. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 5441–5450, 2019.

[20] A. Monszpart, P. Guerrero, D. Ceylan, E. Yumer, and N. J. Mitra. imapper: Interaction-guided joint scene and human motion mapping from monocular videos. *ArXiv*, abs/1806.07889, 2019.

[21] G. Moon, J. Y. Chang, and K. M. Lee. Camera distance-aware top-down approach for 3d multi-person pose estimation from a single rgb image. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10132–10141, 2019.

[22] G. Moon and K. M. Lee. I2l-meshnet: Image-to-lixel prediction network for accurate 3d human pose and mesh estimation from a single rgb image. *ArXiv*, abs/2008.03713, 2020.

[23] G. Pavlakos, V. Choutas, N. Ghorbani, T. Bolkart, A. A. A. Osman, D. Tzionas, and M. J. Black. Expressive body capture: 3D hands, face, and body from a single image. In *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, pages 10975–10985, 2019.

[24] D. Pavllo, C. Feichtenhofer, D. Grangier, and M. Auli. 3d human pose estimation in video with temporal convolutions and semi-supervised training. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7745–7754, 2019.

[25] N. Reddy, L. Guigues, L. Pischulini, J. Eledath, and S. G. Narasimhan. Tessetrack: End-to-end learnable multi-person articulated 3d pose tracking. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15185–15195, 2021.

[26] D. Rempe, T. Birdal, A. Hertzmann, J. Yang, S. Sridhar, and L. J. Guibas. Humor: 3d human motion model for robust pose estimation. In *International Conference on Computer Vision (ICCV)*, 2021.

[27] J. Romero, D. Tzionas, and M. J. Black. Embodied hands: Modeling and capturing hands and bodies together. *ArXiv*, abs/2201.02610, 2022.

[28] I. Sárándi, T. Linder, K. O. Arras, and B. Leibe. MeTRAbs: metric-scale truncation-robust heatmaps for absolute 3D human pose estimation. *IEEE Transactions on Biometrics, Behavior, and Identity Science*, 3(1):16–30, 2021.

[29] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *ArXiv*, abs/1707.06347, 2017.

[30] S. Shimada, V. Golyanik, W. Xu, P. Pérez, and C. Theobalt. Neural monocular 3d human motion capture. *ACM Transactions on Graphics*, 40(4), aug 2021.

[31] S. Shimada, V. Golyanik, W. Xu, and C. Theobalt. Physcap: Physically plausible monocular 3d motion capture in real time. *ACM Trans. Graph.*, 39:235:1–235:16, 2020.

[32] J. Song, X. Chen, and O. Hilliges. Human body model fitting by learned gradient descent. *ArXiv*, abs/2008.08474, 2020.

[33] S. Starke, H. Zhang, T. Komura, and J. Saito. Neural state machine for character-scene interactions. *ACM Transactions on Graphics (TOG)*, 38:1 – 14, 2019.

[34] Y. Tian, H. Zhang, Y. Liu, and L. Wang. Recovering 3d human mesh from monocular images: A survey. *ArXiv*, abs/2203.01923, 2022.

[35] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 5026–5033, Oct. 2012.

[36] Z. Wang, L. Chen, S. Rathore, D. Shin, and C. C. Fowlkes. Geometric pose affordance: 3d human pose with scene constraints. *ArXiv*, abs/1905.07718, 2019.

[37] K. Xie, T. Wang, U. Iqbal, Y. Guo, S. Fidler, and F. Shkurti. Physics-based human motion estimation and synthesis from videos. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11512–11521, 2021.

[38] Y. Yuan and K. Kitani. 3d ego-pose estimation via imitation learning. In *The European Conference on Computer Vision (ECCV)*, Sep. 2018.

[39] Y. Yuan and K. Kitani. Ego-pose estimation and forecasting as real-time pd control. In *IEEE International Conference on Computer Vision (ICCV)*, pages 10082–10092, Oct. 2019.

[40] Y. Yuan, S.-E. Wei, T. Simon, K. Kitani, and J. Saragih. Simpoe: Simulated character control for 3d human pose estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[41] S. Zhang, Y. Zhang, F. Bogo, P. Marc, and S. Tang. Learning motion priors for 4d human body capture in 3d scenes. In *International Conference on Computer Vision (ICCV)*, Oct. 2021.

[42] S. Zhang, Y. Zhang, F. Bogo, M. Pollefeys, and S. Tang. Learning motion priors for 4d human body capture in 3d scenes. *ArXiv*, abs/2108.10399, 2021.

[43] S. Zhang, Y. Zhang, Q. Ma, M. J. Black, and S. Tang. Place: Proximity learning of articulation and contact in 3d environments. *2020 International Conference on 3D Vision (3DV)*, pages 642–651, 2020.