NEURAL CONTEXTUAL BANDITS WITH DEEP REPRESENTATION AND SHALLOW EXPLORATION

ABSTRACT

We study neural contextual bandits, a general class of contextual bandits, where each context-action pair is associated with a raw feature vector, but the specific reward generating function is unknown. We propose a novel learning algorithm that transforms the raw feature vector using the last hidden layer of a deep ReLU neural network (deep representation learning), and uses an upper confidence bound (UCB) approach to explore in the last linear layer (shallow exploration). We prove that under standard assumptions, our proposed algorithm achieves $\widetilde{O}(\sqrt{T})$ finite-time regret, where T is the learning time horizon. Compared with existing neural contextual bandit algorithms, our approach is computationally much more efficient since it only needs to explore in the last layer of the deep neural network.

1 INTRODUCTION

Multi-armed bandits (MAB) (Auer et al., 2002; Audibert et al., 2009; Lattimore & Szepesvári, 2020) are a class of online decision-making problems where an agent needs to learn to maximize its expected cumulative reward by repeatedly interacting with a partially known environment. Following a bandit algorithm (also called a strategy or policy), in each round, the agent adaptively chooses an arm, and then receives a reward associated with that arm. Since only the reward of the chosen arm will be observed (bandit information feedback), a good bandit algorithm has to deal with the exploration-exploitation dilemma: trade-off between pulling the best arm based on existing knowledge/history data (exploitation) and trying the arms that have not been fully explored (exploration).

In many real-world applications, the agent will also be able to access detailed contexts associated with the arms. For example, when a company wants to choose an advertisement to present to a user, the recommendation will be much more accurate if the company takes into consideration the contents, specifications, and other features of the advertisements in the arm set as well as the profile of the user. To encode the contextual information, contextual bandit models and algorithms have been developed, and widely studied both in theory and in practice (Dani et al., 2008; Rusmevichientong & Tsitsiklis, 2010; Li et al., 2010; Chu et al., 2011; Abbasi-Yadkori et al., 2011). Most existing contextual bandit algorithms assume that the expected reward of an arm at a context is a linear function in a known context-action feature vector, which leads to many useful algorithms such as LinUCB (Chu et al., 2011), OFUL (Abbasi-Yadkori et al., 2011), etc. The representation power of the linear model can be limited in applications such as marketing, social networking, clinical studies, etc., where the rewards are usually counts or binary variables. The linear contextual bandit problem has also been extended to richer classes of parametric bandits such as the generalized linear bandits (Filippi et al., 2010; Li et al., 2017) and kernelised bandits (Valko et al., 2013; Chowdhury & Gopalan, 2017).

With the prevalence of deep neural networks (DNNs) and their phenomenal performances in many machine learning tasks (LeCun et al., 2015; Goodfellow et al., 2016), there has emerged a line of work that employs DNNs to increase the representation power of contextual bandit algorithms (Allesiardo et al., 2014; Riquelme et al., 2018; Collier & Llorens, 2018; Zahavy & Mannor, 2019; Zhou et al., 2020; Deshmukh et al., 2020; Zhang et al., 2020). The problems they solve are usually referred to as *neural contextual bandits*. For example, Zhou et al. (2020) developed the NeuralUCB algorithm, which can be viewed as a natural extension of LinUCB (Chu et al., 2011; Abbasi-Yadkori et al., 2011), where they use the output of a deep neural network with the feature vector as input to approximate the reward. Zhang et al. (2020) adapted neural networks in Thompson Sampling (Thompson, 1933; Chapelle & Li, 2011; Russo et al., 2018) for both exploration and exploitation

and proposed NeuralTS . For a fixed time horizon T, it has been proved that both NeuralUCB and NeuralTS achieve a $O(\widetilde{d}\sqrt{T})$ regret bound, where $\widetilde{d}$ is the effective dimension of a neural tangent kernel matrix which can potentially scale with $O(TK)$ for K-armed bandits. This high complexity is mainly due to that the exploration is performed over the entire huge neural network parameter space, which is inefficient and even infeasible when the number of neurons is large. A more realistic and efficient way of learning neural contextual bandits may be to just explore different arms using the last layer as the exploration parameter. More specifically, Riquelme et al. (2018) provided an extensive empirical study of benchmark algorithms for contextual-bandits through the lens of Thompson Sampling, which suggests decoupling representation learning and uncertainty estimation improves performance.

In this paper, we show that the decoupling of representation learning and the exploration can be theoretically validated. We study a new neural contextual bandit algorithm, which learns a mapping to transform the raw features associated with each context-action pair using a deep neural network (*deep representation*), and then performs an upper confidence bound (UCB)-type exploration over the linear output layer of the network (*shallow exploration*). We prove a sublinear regret of the proposed algorithm by exploiting the UCB exploration techniques in linear contextual bandits (Abbasi-Yadkori et al., 2011) and the analysis of deep overparameterized neural networks using neural tangent kernels (Jacot et al., 2018). Our theory confirms the empirically observed effectiveness of decoupling the deep representation learning and the UCB exploration in contextual bandits (Riquelme et al., 2018; Zahavy & Mannor, 2019).

Contributions we summarize the main contributions of this paper as follows.

- We propose a contextual bandit algorithm, Neural-LinUCB, for solving a general class of contextual bandit problems without knowing the specific reward generating function. The proposed algorithm learns a deep representation to transform the raw feature vectors and performs UCB-type exploration in the last layer of the neural network, which we refer to as deep representation and shallow exploration. Compared with LinUCB (Li et al., 2010; Chu et al., 2011) and neural bandits such as NeuralUCB (Zhou et al., 2020) and NeuralTS (Zhang et al., 2020), our algorithm enjoys the best of two worlds: strong expressiveness due to the deep representation and computational efficiency due to the shallow exploration.
- Despite the usage of a DNN as the feature mapping, we prove a $\widetilde{O}(\sqrt{T})$ regret for the proposed Neural-LinUCB algorithm, which matches the regret bound of linear contextual bandits (Chu et al., 2011; Abbasi-Yadkori et al., 2011). To the best of our knowledge, this is the first work that theoretically shows the convergence of bandits algorithms under the scheme of deep representation and shallow exploration. It is notable that a similar scheme called Neural-Linear was proposed by Riquelme et al. (2018) for Thompson sampling algorithms, and they empirically showed that decoupling representation learning and uncertainty estimation improves the performance. Our work confirms this observation from a theoretical perspective.
- We conduct experiments on contextual bandit problems based on real-world datasets, demonstrating a better performance and computational efficiency of Neural-LinUCB over LinUCB and existing neural bandits algorithms such as NeuralUCB, which well aligns with our theory.

1.1 ADDITIONAL RELATED WORK

There is a line of related work to ours on the recent advance in the optimization and generalization analysis of deep neural networks. In particular, Jacot et al. (2018) first introduced the neural tangent kernel (NTK) to characterize the training dynamics of network outputs in the infinite width limit. From the notion of NTK, a fruitful line of research emerged and showed that loss functions of deep neural networks trained by (stochastic) gradient descent can converge to the global minimum (Du et al., 2019b; Allen-Zhu et al., 2019b; Du et al., 2019a; Zou et al., 2018; Zou & Gu, 2019). The generalization bounds for overparameterized deep neural networks are also established in Arora et al. (2019a;b); Allen-Zhu et al. (2019a); Cao & Gu (2019a;b). Recently, the NTK based analysis is also extended to the study of sequential decision problems including bandits (Zhou et al., 2020; Zhang et al., 2020), and reinforcement learning algorithms (Cai et al., 2019; Liu et al., 2019; Wang et al., 2020; Xu & Gu, 2020).

Our algorithm is also different from Langford & Zhang (2008); Agarwal et al. (2014) which reduce the bandit problem to supervised learning. Moreover, their algorithms need to access an oracle that

returns the optimal policy in a policy class given a sequence of context and reward vectors, whose regret depends on the VC-dimension of the policy class.

Notation We use $[k]$ to denote a set $\{1, \ldots, k\}$, $k \in \mathbb{N}^+$. $\|\mathbf{x}\|_2 = \sqrt{\mathbf{x}^\top \mathbf{x}}$ is the Euclidean norm of a vector $\mathbf{x} \in \mathbb{R}^d$. For a matrix $\mathbf{W} \in \mathbb{R}^{m \times n}$, we denote by $\|\mathbf{W}\|_2$ and $\|\mathbf{W}\|_F$ its operator norm and Frobenius norm respectively. For a semi-definite matrix $\mathbf{A} \in \mathbb{R}^{d \times d}$ and a vector $\mathbf{x} \in \mathbb{R}^d$, we denote the Mahalanobis norm as $\|\mathbf{x}\|_{\mathbf{A}} = \sqrt{\mathbf{x}^\top \mathbf{A} \mathbf{x}}$. Throughout this paper, we reserve the notations $\{C_i\}_{i=0,1,\ldots}$ to represent absolute positive constants that are independent of problem parameters such as dimension, sample size, iteration number, step size, network length and so on. The specific values of $\{C_i\}_{i=0,1,\ldots}$ can be different in different context. For a parameter of interest T and a function $f(T)$, we use notations such as $O(f(T))$ and $\Omega(f(T))$ to hide constant factors and $\widetilde{O}(f(T))$ to hide constant and logarithmic dependence of T.

2 PRELIMINARIES

In this section, we provide the background of contextual bandits and deep neural networks.

2.1 LINEAR CONTEXTUAL BANDITS

A contextual bandit is characterized by a tuple $(\mathcal{S}, \mathcal{A}, r)$, where $\mathcal{S}$ is the context (state) space, $\mathcal{A}$ is the arm (action) space, and r encodes the unknown *reward generating function* at all context-arm pairs. A learning agent, who knows $\mathcal{S}$ and $\mathcal{A}$ but does not know the true reward r (values bounded in $(0, 1)$ for simplicity), needs to interact with the contextual bandit for T rounds. At each round $t = 1, \ldots, T$, the agent first observes a context $s_t \in \mathcal{S}$ chosen by the environment; then it needs to adaptively select an arm $a_t \in \mathcal{A}$ based on its past observations; finally it receives a reward

$$\widehat{r}_t(\mathbf{x}_{s,a_t}) = r(\mathbf{x}_{s,a_t}) + \xi_t, \tag{2.1}$$

where $\mathbf{x}_{s,a} \in \mathbb{R}^d$ is a known feature vector for context-arm pair $(s, a) \in \mathcal{S} \times \mathcal{A}$, and ξ_t is a random noise with zero mean. The agent's objective is to maximize its expected total reward over these T rounds, which is equivalent to minimizing the pseudo regret (Audibert et al., 2009):

$$R_T = \mathbb{E}\left[\sum_{t=1}^{T} \left(\widehat{r}(\mathbf{x}_{s_t, a_t^*}) - \widehat{r}(\mathbf{x}_{s_t, a_t}) \right) \right], \tag{2.2}$$

where $a_t^* \in \operatorname{argmax}_{a \in \mathcal{A}} \{ r(\mathbf{x}_{s_t, a}) = \mathbb{E}[\widehat{r}(\mathbf{x}_{s_t, a})] \}$. To simplify the exposition, we use $\mathbf{x}_{t,a}$ to denote $\mathbf{x}_{s_t, a}$ since it only depends on the round index t in most bandit problems, and we assume $\mathcal{A} = [K]$.

In linear contextual bandits, the reward function in (2.1) is assumed to have a linear structure $r(\mathbf{x}_{s,a}) = \mathbf{x}_{s,a}^\top \boldsymbol{\theta}^*$ for some unknown weight vector $\boldsymbol{\theta}^* \in \mathbb{R}^d$. One provably sample efficient algorithm for linear contextual bandits is Linear Upper Confidence Bound (LinUCB) (Chu et al., 2011) or Optimism in the Face of Uncertainty Linear bandit algorithm (OFUL) (Abbasi-Yadkori et al., 2011). Specifically, at each round t, LinUCB chooses the action $a_t = \operatorname{argmax}_{a \in [K]} \{ \mathbf{x}_{t,a}^\top \boldsymbol{\theta}_t + \alpha_t \|\mathbf{x}_{t,a}\|_{\mathbf{A}_t^{-1}} \}$, where $\boldsymbol{\theta}_t$ is a point estimate of $\boldsymbol{\theta}^*$, $\mathbf{A}_t = \lambda \mathbf{I} + \sum_{i=1}^{t} \mathbf{x}_{i,a_i} \mathbf{x}_{i,a_i}^\top$ with some $\lambda > 0$ is a matrix defined based on the historical context-arm pairs, and $\alpha_t > 0$ is a tuning parameter that controls the exploration rate in LinUCB.

2.2 DEEP NEURAL NETWORKS

In this paper, we use $f(\mathbf{x})$ to denote a neural network with input data $\mathbf{x} \in \mathbb{R}^d$. Let L be the number of hidden layers and $\mathbf{W}_l \in \mathbb{R}^{m_l \times m_{l-1}}$ be the weight matrices in the l-th layer, where $l = 1, \ldots, L$, $m_1 = \ldots = m_{L-1} = m$ and $m_0 = m_L = d$. Then a L-hidden layer neural network is defined as

$$f(\mathbf{x}) = \sqrt{m} \boldsymbol{\theta}^{*\top} \sigma_L(\mathbf{W}_L \sigma_{L-1}(\mathbf{W}_{L-1} \cdots \sigma_1(\mathbf{W}_1 \mathbf{x}) \cdots)), \tag{2.3}$$

where σ_l is an activation function and $\boldsymbol{\theta}^* \in \mathbb{R}^d$ is the weight of the output layer. To simplify the presentation, we will assume $\sigma_1 = \sigma_2 = \ldots = \sigma_L = \sigma$ is the ReLU activation function, i.e., $\sigma(x) = \max\{0, x\}$ for $x \in \mathbb{R}$. We denote $\mathbf{w} = (\operatorname{vec}(\mathbf{W}_1)^\top, \ldots, \operatorname{vec}(\mathbf{W}_L)^\top)^\top$, which is the concatenation of the vectorized weight parameters of all hidden layers of the neural network. We

also write $f(\mathbf{x}; \boldsymbol{\theta}^*, \mathbf{w}) = f(\mathbf{x})$ in order to explicitly specify the weight parameters of neural network f. It is easy to show that the dimension p of vector $\mathbf{w}$ satisfies $p = (L-2)m^2 + 2md$. To simplify the notation, we define $\boldsymbol{\phi}(\mathbf{x}; \mathbf{w})$ as the output of the L-th hidden layer of neural network f.

$$\boldsymbol{\phi}(\mathbf{x}; \mathbf{w}) = \sqrt{m}\sigma(\mathbf{W}_L\sigma(\mathbf{W}_{L-1}\cdots\sigma(\mathbf{W}_1\mathbf{x})\cdots)). \tag{2.4}$$

Note that $\boldsymbol{\phi}(\mathbf{x}; \mathbf{w})$ itself can also be viewed as a neural network with vector-valued outputs.

3 DEEP REPRESENTATION AND SHALLOW EXPLORATION

3.1 HIGH-LEVEL IDEA OF THE PROPOSED ALGORITHM

The linear parametric form in linear contextual bandits might produce biased estimates of the reward due to the lack of representation power (Snoek et al., 2015; Riquelme et al., 2018). In contrast, it is well known that deep neural networks are powerful enough to approximate an arbitrary function (Cybenko, 1989). Therefore, a natural extension of linear contextual bandits is to use a deep neural network to approximate the reward generating function $r(\cdot)$. Nonetheless, DNNs usually have a prohibitively large dimension for weight parameters, which makes the exploration in neural networks based UCB algorithm inefficient (Kveton et al., 2020; Zhou et al., 2020).

In this work, we study a neural contextual bandit algorithm, where the hidden layers of a deep neural network are used to represent the features and the exploration is only performed in the last layer of the neural network. In particular, for any arm feature vector $\mathbf{x}$, we use $\langle\boldsymbol{\theta}^*, \boldsymbol{\phi}(\mathbf{x}; \mathbf{w})\rangle$ to approximate the unknown reward function $r(\mathbf{x})$, where $\boldsymbol{\phi}(\mathbf{x}; \mathbf{w})$ defined as in (2.4) is a neural network with weight $\mathbf{w}$, and $\boldsymbol{\theta}^*$ is a unknown weight parameter. Note that we can also view $\langle\boldsymbol{\theta}^*, \boldsymbol{\phi}(\mathbf{x}; \mathbf{w})\rangle$ as a neural network with $\boldsymbol{\phi}(\mathbf{x}; \mathbf{w})$ being the output of the last hidden layer and $\boldsymbol{\theta}^*$ the weight parameter of the last (linear) layer. Different from existing neural bandit algorithms, we only add a UCB bonus term involving the last layer instead of all the weight parameter of this large neural network.

This decoupling of the representation and the exploration will achieve the best of both worlds: efficient exploration in shallow (linear) models and high expressive power of deep models. To learn the unknown feature mapping, we propose to use a neural network to approximate it. In what follows, we will describe a neural contextual bandit algorithm that uses the output of the last hidden layer of a neural network to transform the raw feature vectors (*deep representation*) and performs UCB-type exploration in the last layer of the neural network (*shallow exploration*). Since the exploration is performed only in the last linear layer, we call this procedure Neural-LinUCB, which is displayed in Algorithm 1.

3.2 DETAILED IMPLEMENTATION OF DEEP REPRESENTATION AND SHALLOW EXPLORATION

Now we describe the details of Algorithm 1. In round t, the agent receives an action set with raw features $\mathcal{X}_t = \{\mathbf{x}_{t,1}, \ldots, \mathbf{x}_{t,K}\}$. Then the agent chooses an arm a_t that maximizes the following upper confidence bound:

$$a_t = \operatorname*{argmax}_{k \in [K]} \left\{ \langle\boldsymbol{\phi}(\mathbf{x}_{t,k}; \mathbf{w}_{t-1}), \boldsymbol{\theta}_{t-1}\rangle + \alpha_t\|\boldsymbol{\phi}(\mathbf{x}_{t,k}; \mathbf{w}_{t-1})\|_{\mathbf{A}_{t-1}^{-1}} \right\}, \tag{3.1}$$

where $\boldsymbol{\theta}_{t-1}$ is a point estimate of the unknown weight in the last layer, $\boldsymbol{\phi}(\mathbf{x}; \mathbf{w})$ is defined as in (2.4), $\mathbf{w}_{t-1}$ is an estimate of all the weight parameters in the hidden layers of the neural network, $\alpha_t > 0$ is the algorithmic parameter controlling the exploration, and $\mathbf{A}_t$ defined as follows.

$$\mathbf{A}_t = \lambda\mathbf{I} + \sum_{i=1}^{t} \boldsymbol{\phi}(\mathbf{x}_{i,a_i}; \mathbf{w}_{i-1})\boldsymbol{\phi}(\mathbf{x}_{i,a_i}; \mathbf{w}_{i-1})^\top, \tag{3.2}$$

and $\lambda > 0$. After pulling arm a_t, the agent will observe a noisy reward $\widehat{r}_t := \widehat{r}(\mathbf{x}_{t,a_t}) = r(\mathbf{x}_{t,k}) + \xi_t$, where ξ_t is an independent ν-subGaussian random noise for some $\nu > 0$ and $r(\cdot)$ is an unknown reward function. In this paper, we will interchangeably use notation $\widehat{r}_t$ to denote the reward received at the t-th step and an equivalent notation $\widehat{r}(\mathbf{x})$ to express its dependence on the feature vector $\mathbf{x}$.

Upon receiving the reward $\widehat{r}_t$, the agent updates its estimate $\boldsymbol{\theta}_t$ of the output layer weight by using the same ℓ^2-regularized least-squares estimate in linear contextual bandits (Abbasi-Yadkori et al., 2011). In particular, we have $\boldsymbol{\theta}_t = \mathbf{A}_t^{-1}\mathbf{b}_t$, where $\mathbf{b}_t = \sum_{i=1}^{t} \widehat{r}_i\boldsymbol{\phi}(\mathbf{x}_{i,a_i}; \mathbf{w}_{i-1})$.

To save the computation, the neural network $\phi(\cdot; \mathbf{w}_t)$ will be updated once every H steps. Therefore, we have $\mathbf{w}_{(q-1)H+1} = \ldots = \mathbf{w}_{qH}$ for $q = 1, 2, \ldots$. We call the time steps $\{(q-1)H+1, \ldots, qH\}$ an epoch with length H. At time step $t = Hq$, for any $q = 1, 2, \ldots$, Algorithm 1 will retrain the neural network based on all the historical data. In Algorithm 2, our goal is to minimize the following empirical loss function:

$$\mathcal{L}_q(\mathbf{w}) = \sum_{i=1}^{qH} \left(\boldsymbol{\theta}_i^\top \phi(\mathbf{x}_{i,a_i}; \mathbf{w}) - \widehat{r}_i \right)^2. \tag{3.3}$$

In practice, one can further save computational cost by only feeding data $\{\mathbf{x}_{i,a_i}, \widehat{r}_i, \boldsymbol{\theta}_i\}_{i=(q-1)H+1}^{qH}$ from the q-th epoch into Algorithm 2 to update the parameter $\mathbf{w}_t$, which does not hurt the performance since the historical information has been encoded into the estimate of $\boldsymbol{\theta}_i$. In this paper, we will perform the following gradient descent step

$$\mathbf{w}_q^{(s)} = \mathbf{w}_q^{(s-1)} - \eta_q \nabla_{\mathbf{w}} \mathcal{L}_q(\mathbf{w}^{(s-1)}).$$

for $s = 1, \ldots, n$, where $\mathbf{w}_q^{(0)} = \mathbf{w}^{(0)}$ is chosen as the same random initialization point. We will discuss more about the initial point $\mathbf{w}^{(0)}$ in the next paragraph. Then Algorithm 2 outputs $\mathbf{w}_q^{(n)}$ and we set it as the updated weight parameter $\mathbf{w}_{Hq+1}$ in Algorithm 1. In the next round, the agent will receive another action set $\mathcal{X}_{t+1}$ with raw feature vectors and repeat the above steps to choose the sub-optimal arm and update estimation for contextual parameters.

Initialization: Recall that $\mathbf{w}$ is the collection of all hidden layer weight parameters of the neural network. We will follow the same initialization scheme as used in Zhou et al. (2020), where each entry of the weight matrices follows some Gaussian distribution. Specifically, for any $l \in \{1, \ldots, L-1\}$, we set $\mathbf{W}_l = \begin{bmatrix} \mathbf{W} & \mathbf{0} \\ \mathbf{0} & \mathbf{W} \end{bmatrix}$, where each entry of $\mathbf{W}$ follows distribution $N(0, 4/m)$ independently; for $\mathbf{W}_L$, we set it as $[\mathbf{V} \quad -\mathbf{V}]$, where each entry of $\mathbf{V}$ follows distribution $N(0, 2/m)$ independently.

Comparison with LinUCB and NeuralUCB: Compared with linear contextual bandits in Section 2.1, Algorithm 1 has a distinct feature that it learns a deep neural network to obtain a deep representation of the raw data vectors and then performs UCB exploration. This deep representation allows our algorithm to characterize more intrinsic and latent information about the raw data $\{\mathbf{x}_{t,k}\}_{t\in[T],k\in[K]} \subset \mathbb{R}^d$. However, the increased complexity of the feature mapping $\phi(\cdot; \mathbf{w})$ also introduces great hardness in training. For instance, a recent work by Zhou et al. (2020) also studied the neural contextual bandit problem, but different from (3.1), their algorithm (NeuralUCB) performs the UCB exploration on the entire network parameter space, which is $\mathbb{R}^{\widetilde{p}+d}$, where $\widetilde{p} = m + md + (L-1)m^2$. Note that in Zhou et al. (2020), they need to compute the inverse of a matrix $\mathbf{Z}_t \in \mathbb{R}^{(\widetilde{p}+d)\times(\widetilde{p}+d)}$, which is defined in a similar way to the matrix $\mathbf{A}_t$ in our paper except that $\mathbf{Z}_t$ is defined based on the gradient of the network instead of the output of the last hidden layer as in (3.2). In sharp contrast, $\mathbf{A}_t$ in our paper is only of size $d \times d$ and thus is much more efficient and practical in implementation, which will be seen from our experiments in later sections.

We note that there is also a similar algorithm to our Neural-LinUCB presented in Deshmukh et al. (2020), where they studied the self-supervised learning loss in contextual bandits with neural network representation for computer vision problems. However, no regret analysis has been provided. When the feature mapping $\phi(\cdot; \mathbf{w})$ is an identity function, the problem reduces to linear contextual bandits where we directly use $\mathbf{x}_t$ as the feature vector. In this case, it is easy to see that Algorithm 1 reduces to LinUCB (Chu et al., 2011) since we do not need to learn the representation parameter $\mathbf{w}$ anymore.

Comparison with Neural-Linear: The high-level idea of decoupling the representation and exploration in our algorithm is also similar to that of the Neural-Linear algorithm (Riquelme et al., 2018; Zahavy & Mannor, 2019), which trains a deep neural network to learn a representation of the raw feature vectors, and then uses a Bayesian linear regression to estimate the uncertainty in the bandit problem. However, these two algorithms are significantly different since Neural-Linear (Riquelme et al., 2018) is a Thompson sampling based algorithm that uses posterior sampling to estimate the weight parameter $\boldsymbol{\theta}^*$ via Bayesian linear regression, whereas Neural-LinUCB adopts upper confidence bound based techniques to estimate the weight $\boldsymbol{\theta}^*$. Nevertheless, both algorithms share the same idea of deep representation and shallow exploration, and we view our Neural-LinUCB algorithm as one instantiation of the Neural-Linear scheme.

Algorithm 1 Deep Representation and Shallow Exploration (Neural-LinUCB)

1: **Input**: regularization parameter $\lambda > 0$, number of total steps T, episode length H, exploration parameters $\{\alpha_t > 0\}_{t \in [T]}$
2: **Initialization:** $\mathbf{A}_0 = \lambda \mathbf{I}$, $\mathbf{b}_0 = \mathbf{0}$; entries of $\boldsymbol{\theta}_0$ follow $N(0, 1/d)$, and $\mathbf{w}^{(0)}$ is initialized as described in Section 3; $q = 1$; $\mathbf{w}_0 = \mathbf{w}^{(0)}$
3: **for** $t = 1, \ldots, T$ **do**
4:     receive feature vectors $\{\mathbf{x}_{t,1}, \ldots, \mathbf{x}_{t,K}\}$
5:     choose arm $a_t = \operatorname{argmax}_{k \in [K]} \boldsymbol{\theta}_{t-1}^{\top} \boldsymbol{\phi}(\mathbf{x}_{t,k}; \mathbf{w}_{t-1}) + \alpha_t \|\boldsymbol{\phi}(\mathbf{x}_{t,k}; \mathbf{w}_{t-1})\|_{\mathbf{A}_{t-1}^{-1}}$, and obtain reward $\widehat{r}_t$
6:     update $\mathbf{A}_t$ and $\mathbf{b}_t$ as follows:
        $\mathbf{A}_t = \mathbf{A}_{t-1} + \boldsymbol{\phi}(\mathbf{x}_{t,a_t}; \mathbf{w}_{t-1}) \boldsymbol{\phi}(\mathbf{x}_{t,a_t}; \mathbf{w}_{t-1})^{\top}$,
        $\mathbf{b}_t = \mathbf{b}_{t-1} + \widehat{r}_t \boldsymbol{\phi}(\mathbf{x}_{t,a_t}; \mathbf{w}_{t-1})$,
7:     update $\boldsymbol{\theta}_t = \mathbf{A}_t^{-1} \mathbf{b}_t$
8:     **if** $\operatorname{mod}(t, H) = 0$ **then**
9:         $\mathbf{w}_t \leftarrow$ output of Algorithm 2
10:        $q = q + 1$
11:     **else**
12:        $\mathbf{w}_t = \mathbf{w}_{t-1}$
13:     **end if**
14: **end for**
15: **Output** $\mathbf{w}_T$

Algorithm 2 Update Weight Parameters with Gradient Descent

1: **Input:** initial point $\mathbf{w}_q^{(0)} = \mathbf{w}^{(0)}$, maximum iteration number n, step size η_q, and loss function defined in (3.3).
2: **for** $s = 1, \ldots, n$ **do**
3:     $\mathbf{w}_q^{(s)} = \mathbf{w}_q^{(s-1)} - \eta_q \nabla_{\mathbf{w}} \mathcal{L}_q(\mathbf{w}_q^{(s-1)})$.
4: **end for**
5: **Output** $\mathbf{w}_q^{(n)}$

---

4   MAIN RESULTS

To analyze the regret bound of Algorithm 1, we first lay down some important assumptions on the neural contextual bandit model.

Assumption 4.1. For all $i \geq 1$ and $k \in [K]$, we assume that $\|\mathbf{x}_{i,k}\|_2 = 1$ and its entries satisfy $[\mathbf{x}_{i,k}]_j = [\mathbf{x}_{j,k}]_{j+d/2}$.

The assumption that $\|\mathbf{x}_{i,k}\|_2 = 1$ is not essential and is only imposed for simplicity, which is also used in Zou & Gu (2019); Zhou et al. (2020). Finally, the condition on the entries of $\mathbf{x}_{i,k}$ is also mild since otherwise we could always construct $\mathbf{x}'_{i,k} = [\mathbf{x}_{i,k}^{\top}, \mathbf{x}_{i,k}^{\top}]^{\top}/\sqrt{2}$ to replace it. An implication of Assumption 4.1 is that the initialization scheme in Algorithm 1 results in $\boldsymbol{\phi}(\mathbf{x}_{i,k}; \mathbf{w}^{(0)}) = \mathbf{0}$ for all $i \in [T]$ and $k \in [K]$.

We assume the following stability condition on the spectral norm of the neural network gradient:

Assumption 4.2. There is a constant $\ell_{\text{Lip}} > 0$ such that it holds $\left\|\frac{\partial \boldsymbol{\phi}}{\partial \mathbf{w}}(\mathbf{x}; \mathbf{w}_0) - \frac{\partial \boldsymbol{\phi}}{\partial \mathbf{w}}(\mathbf{x}'; \mathbf{w}_0)\right\|_2 \leq \ell_{\text{Lip}} \|\mathbf{x} - \mathbf{x}'\|_2$ for all $\mathbf{x}, \mathbf{x}' \in \{\mathbf{x}_{i,k}\}_{i \in [T], k \in [K]}$.

The inequality in Assumption 4.2 resembles the Lipschitz condition on the gradient of the neural network. However, it is essentially different from the smoothness condition since here the gradient is taken with respect to the neural network weights while the Lipschitz condition is imposed on the feature parameter $\mathbf{x}$. Similar conditions are widely made in nonconvex optimization (Wang et al., 2014; Balakrishnan et al., 2017; Xu et al., 2017), in the name of first-order stability, which is essential to derive the convergence of alternating optimization algorithms. Furthermore, Assumption 4.2 is only required on the TK training data points and a specific weight parameter $\mathbf{w}_0$. Therefore, the

condition will hold if the raw feature data lie in a certain subspace of $\mathbb{R}^d$. We provided some further discussions in the supplementary material about this assumption for interested readers.

In order to analyze the regret bound of Algorithm 1, we need to characterize the properties of the deep neural network in (2.3) that is used to represent the feature vectors. Following a recent line of research (Jacot et al., 2018; Cao & Gu, 2019a; Arora et al., 2019b; Zhou et al., 2020), we define the covariance between two data point $\mathbf{x}, \mathbf{y} \in \mathbb{R}^d$ as follows.

$$\widetilde{\boldsymbol{\Sigma}}^{(0)}(\mathbf{x}, \mathbf{y}) = \boldsymbol{\Sigma}^{(0)}(\mathbf{x}, \mathbf{y}) = \mathbf{x}^\top \mathbf{y},$$

$$\boldsymbol{\Lambda}^{(l)}(\mathbf{x}, \mathbf{y}) = \begin{bmatrix} \boldsymbol{\Sigma}^{l-1}(\mathbf{x}, \mathbf{x}) & \boldsymbol{\Sigma}^{l-1}(\mathbf{x}, \mathbf{y}) \\ \boldsymbol{\Sigma}^{l-1}(\mathbf{y}, \mathbf{x}) & \boldsymbol{\Sigma}^{l-1}(\mathbf{y}, \mathbf{y}) \end{bmatrix},$$

$$\boldsymbol{\Sigma}^{(l)}(\mathbf{x}, \mathbf{y}) = 2\mathbb{E}_{(u,v)\sim N(\mathbf{0}, \boldsymbol{\Lambda}^{(l-1)}(\mathbf{x}, \mathbf{y}))}[\sigma(u)\sigma(v)],$$

$$\widetilde{\boldsymbol{\Sigma}}^{(l)}(\mathbf{x}, \mathbf{y}) = 2\widetilde{\boldsymbol{\Sigma}}^{(l-1)}(\mathbf{x}, \mathbf{y})\mathbb{E}_{u,v}[\dot{\sigma}(u)\dot{\sigma}(v)] + \boldsymbol{\Sigma}^{(l)}(\mathbf{x}, \mathbf{y}), \tag{4.1}$$

where $(u, v) \sim N(\mathbf{0}, \boldsymbol{\Lambda}^{(l-1)}(\mathbf{x}, \mathbf{y}))$, and $\dot{\sigma}(\cdot)$ is the derivative of activation function. We denote the neural tangent kernel (NTK) matrix $\mathbf{H} \in \mathbb{R}^{TK \times TK}$ based on all feature vectors $\{\mathbf{x}_{t,k}\}_{t\in[T],k\in[K]}$. Renumbering $\{\mathbf{x}_{t,k}\}_{t\in[T],k\in[K]}$ as $\{\mathbf{x}_i\}_{i=1,\ldots,TK}$, then each entry $\mathbf{H}_{ij}$ is defined as

$$\mathbf{H}_{ij} = \frac{1}{2}\big(\widetilde{\boldsymbol{\Sigma}}^{(L)}(\mathbf{x}_i, \mathbf{x}_j) + \boldsymbol{\Sigma}^{(L)}(\mathbf{x}_i, \mathbf{x}_j)\big), \tag{4.2}$$

for all $i, j \in [TK]$. Based on the above definition, we impose the following assumption on $\mathbf{H}$.

Assumption 4.3. The neural tangent kernel defined in (4.2) is positive definite, i.e., $\lambda_{\min}(\mathbf{H}) \geq \lambda_0$ for some constant $\lambda_0 > 0$.

Assumption 4.3 essentially requires the neural tangent kernel matrix $\mathbf{H}$ to be non-singular, which is a mild condition and also imposed in other related work (Du et al., 2019a; Arora et al., 2019b; Cao & Gu, 2019a; Zhou et al., 2020). Moreover, it is shown that Assumption 4.3 can be easily derived from Assumption 4.1 for two-layer ReLU networks (Oymak & Soltanolkotabi, 2020; Zou & Gu, 2019). Therefore, Assumption 4.3 is mild or even negligible given the non-degeneration assumption on the feature vectors. Also note that matrix $\mathbf{H}$ is only defined based on layers $l = 1, \ldots, L$ of the neural network, and does not depend on the output layer $\boldsymbol{\theta}$. It is easy to extend the definition of $\mathbf{H}$ to the NTK matrix defined on all layers including the output layer $\boldsymbol{\theta}$, which would also be positive definite by Assumption 4.3 and the recursion in (4.2).

Before we present the regret analysis of the neural contextual bandit, we need to modify the regret defined in (2.2) to account for the randomness of the neural network initialization. For a fixed time horizon T, we define the regret of Algorithm 1 as follows.

$$R_T = \mathbb{E}\bigg[\sum_{t=1}^{T}\big(\widehat{r}(\mathbf{x}_{t,a_t^*}) - \widehat{r}(\mathbf{x}_{t,a_t})\big)|\mathbf{w}^{(0)}\bigg], \tag{4.3}$$

where the expectation is taken over the randomness of the reward noise. Note that R_T defined in (4.3) is still a random variable since the initialization of Algorithm 2 is randomly generated.

Now we are going to present the regret bound of the proposed algorithm.

Theorem 4.4. Suppose Assumptions 4.1, 4.2 and 4.3 hold. Assume that $\|\boldsymbol{\theta}^*\|_2 \leq M$ for some positive constant $M > 0$. For any $\delta \in (0, 1)$, let us choose α_t in Neural-LinUCB as

$$\alpha_t = \nu\sqrt{2\big(d\log(1 + t\log(HK)/\lambda) + \log(1/\delta)\big)} + \lambda^{1/2}M.$$

We choose the step size η_q of Algorithm 2 as $\eta_q \leq C_0\big(d^2mnT^{5.5}L^6\log(TK/\delta)\big)^{-1}$ and the width of the neural network satisfies $m = \text{poly}(L, d, 1/\delta, H, \log(TK/\delta))$. With probability at least $1 - \delta$ over the randomness of the initialization of the neural network, it holds that

$$R_T \leq C_1\alpha_T\sqrt{Td\log\Big(1 + \frac{TG^2}{\lambda d}\Big)} + \frac{C_2\ell_{\text{Lip}}L^3d^{5/2}T\sqrt{\log m\log(\frac{1}{\delta})\log(\frac{TK}{\delta})}\|\mathbf{r} - \widetilde{\mathbf{r}}\|_{\mathbf{H}^{-1}}}{m^{1/6}},$$

where $\{C_i\}_{i=0,1,2}$ are absolute constants independent of the problem parameters, $\mathbf{r} = (r(\mathbf{x}_1), r(\mathbf{x}_2), \ldots, r(\mathbf{x}_{TK}))^\top \in \mathbb{R}^{TK}$ and $\widetilde{\mathbf{r}} = (f(\mathbf{x}_1; \boldsymbol{\theta}_0, \mathbf{w}_0), \ldots, f(\mathbf{x}_{TK}; \boldsymbol{\theta}_{T-1}, \mathbf{w}_{T-1}))^\top \in \mathbb{R}^{TK}$, and $\|\mathbf{r}\|_{\mathbf{A}} = \sqrt{\mathbf{r}^\top \mathbf{A}\mathbf{r}}$.

Remark 4.5. Theorem 4.4 shows that the regret of Algorithm 1 can be bounded by two parts: the first part is of order $\widetilde{O}(\sqrt{T})$, which resembles the regret bound of linear contextual bandits (Abbasi-Yadkori et al., 2011); the second part is of order $\widetilde{O}(m^{-1/6}T\sqrt{(\mathbf{r}-\widetilde{\mathbf{r}})^{\top}\mathbf{H}^{-1}(\mathbf{r}-\widetilde{\mathbf{r}})})$, which depends on the estimation error of the neural network f for the reward generating function r and the neural tangent kernel $\mathbf{H}$.

It is worth noting that our theoretical analysis depends on the reward structure assumption that $r(\cdot) = \langle \boldsymbol{\theta}_*, \boldsymbol{\psi}(\cdot) \rangle$. However, the linear structure between $\boldsymbol{\theta}_*$ and $\boldsymbol{\psi}(\cdot)$ is not essential. As long as the deep representation of the feature vector and the uncertainty weight parameter can be decoupled, Algorithm 1 can be easily extended to settings with milder assumptions on the reward structure such as generalized linear models (Sarkar, 1991; Filippi et al., 2010; Li et al., 2017; Kveton et al., 2020). For more general bandit models where no assumption is imposed to the reward generating function, it is still unclear whether the decoupled deep representation and shallow exploration would work especially in cases a thorough exploration may be needed.

Based on the result in Theorem 4.4, we can easily verify the following conclusion:

Corollary 4.6. Under the same conditions of Theorem 4.4, if we choose a sufficiently overparameterized neural network mapping $\phi(\cdot)$ such that $m \geq T^3$, then the regret of Algorithm 1 is $R_T = \widetilde{O}(\sqrt{T}\sqrt{(\mathbf{r}-\widetilde{\mathbf{r}})^{\top}\mathbf{H}^{-1}(\mathbf{r}-\widetilde{\mathbf{r}})})$.

Remark 4.7. For the ease of presentation, let us denote $\mathcal{E} := \|\mathbf{r}-\widetilde{\mathbf{r}}\|_{\mathbf{H}^{-1}}$. If we have $\mathcal{E} = O(1)$, the total regret in Theorem 4.4 becomes $\widetilde{O}(\sqrt{T})$ which matches the regret of linear contextual bandits (Abbasi-Yadkori et al., 2011). We remark that there is a similar assumption in Zhou et al. (2020) where they assume that $\mathbf{r}^{\top}\mathbf{H}^{-1}\mathbf{r}$ can be upper bounded by a constant. They show that this term can be bounded by the RKHS norm of $\mathbf{r}$ if it belongs to the RKHS induced by the neural tangent kernel (Arora et al., 2019a;b; Lee et al., 2019). In addition, $\mathcal{E}$ here is the difference between the true reward function and the neural network function, which can also be small if the deep neural network function well approximates the reward generating function $r(\cdot)$.

5 EXPERIMENTS

In this section, we provide empirical evaluations of Neural-LinUCB on real-world datasets. As we have discussed in Section 3, Neural-LinUCB could be viewed as an instantiation of the Neural-Linear scheme studied in Riquelme et al. (2018) except that we use the UCB exploration instead of the posterior sampling exploration therein. Note that there has been an extensive comparison (Riquelme et al., 2018) of the Neural-Linear methods with many other baselines such as greedy algorithms, Variational Inference, Expectation-Propagation, Bayesian Non-parametrics and so on. Therefore, we do not seek a thorough empirical comparison of Neural-LinUCB with all existing bandits algorithms. In this experiment, we only aim to validate the advantages of our algorithm over the following baselines: (1) Neural-Linear (Riquelme et al., 2018); (2) LinUCB (Chu et al., 2011), which does not have a *deep representation* of the feature vectors; (3) NeuralUCB (Zhou et al., 2020), and (4) NeuralTS (Zhang et al., 2020) which perform UCB/TS exploration on all the parameters of the neural network. All numerical experiments were run on a workstation with Intel(R) Xeon(R) CPU E5-2637 v4 @ 3.50GHz.

Datasets: we evaluate the performances of all algorithms on bandit problems created from real-world data. Specifically, following the experimental setting in Zhou et al. (2020),we use datasets *(Shuttle) Statlog*, *Magic* and *Covertype* from UCI machine learning repository (Dua & Graff, 2017), and the *MINST* dataset from LeCun et al. (1998). The details of these datasets are presented in Table 1. In Table 1, each instance represents a feature vector $\mathbf{x} \in \mathbb{R}^d$ that is associated with one of the K arms, and dimension d is the number of attributes in each instance.

Table 1: Specifications of datasets from the UCI machine learning repository used in this paper.

	Statlog	Magic	Covertype	MNIST
Number of attributes	9	11	54	784
Number of arms	7	2	7	10
Number of instances	58,000	19,020	581,012	60,000

Figure 1: The cumulative regrets of LinUCB, NeuralUCB, Neural-Linear and Neural-LinUCB over $15,000$ rounds. Experiments are averaged over 10 repetitions.

Implementations: for LinUCB, we follow the setting in Li et al. (2010) to use disjoint models for different arms. For neural network based algorithms, we use a ReLU neural network defined as in (2.3) with $L = 2$ and $m = 100$ for the UCI datasets (*Statlog*, *Magic*, *Covertype*). Thus the neural network weights are $\mathbf{W}_1 \in \mathbb{R}^{m \times d}$, $\mathbf{W}_2 \in \mathbb{R}^{k \times m}$, and $\boldsymbol{\theta} \in \mathbb{R}^k$ respectively, where $k = 100$, $m = 100$, and d is the dimension of features in the corresponding task. Since the problem size of the MNIST dataset is larger, inspired by Hinton & Salakhutdinov (2006), we use a deeper NN and set $L = 3$, $k = 100$ and $m = 100$, with weights $\mathbf{W}_1 \in \mathbb{R}^{m \times d}$, $\mathbf{W}_2 \in \mathbb{R}^{m \times m}$, $\mathbf{W}_3 \in \mathbb{R}^{k \times m}$, and $\boldsymbol{\theta} \in \mathbb{R}^k$. We set the time horizon $T = 15,000$, which is the total number of rounds for each algorithm on each dataset. We use gradient decent to optimize the network weights, with a step size $\eta_q =$ 1e-5 and maximum iteration number $n = 1,000$. To speed up the training process, the network parameter $\mathbf{w}$ is updated every $H = 100$ rounds starting from round 2000. We also apply early stopping when the loss difference of two consecutive iterations is smaller than a threshold of 1e-6. We set $\lambda = 1$ and $\alpha_t = 0.02$ for all algorithms, $t \in [T]$. For NeuralUCB and NeuralTS, since it is computationally unaffordable to perform the original UCB exploration as displayed in Zhou et al. (2020), we follow their experimental setting to replace the matrix $\mathbf{Z}_t \in \mathbb{R}^{(d+\widetilde{p}) \times (d+\widetilde{p})}$ in their papers with its diagonal matrix.

Results: we plot the cumulative regret of all algorithms versus round in Figures 1(a), 1(b) and 1(c) for UCI datasets and in Figure 1(d) for MNIST. The results are reported based on the average of 10 repetitions over different random shuffles of the datasets. It can be seen that algorithms based on neural network representations (NeuralUCB, NeuralTS, Neural-Linear and Neural-LinUCB) consistently outperform the linear contextual bandit method LinUCB, which shows that linear models may lack representation power and find biased estimates for the underlying reward generating function. Furthermore, our proposed Neural-LinUCB achieves a comparable regret with NeuralUCB in all experiments despite the fact that our algorithm only explores in the output layer of the neural network, which is more computationally efficient as we will show in the sequel.The results in our experiment are well aligned with our theory that deep representation and shallow exploration are sufficient to guarantee a good performance of neural contextual bandit algorithms, which is also consistent with the findings in existing literature (Riquelme et al., 2018) that decoupling the representation learning and uncertainty estimation improves the performance.

We also conducted experiments to study the effects of different widths of deep neural networks on the regret performance and to show the computational efficiency of Neural-LinUCB compared with existing neural bandit algorithms. Due to the space limit, we defer the results to Appendix A.

6 CONCLUSIONS

In this paper, we propose a new neural contextual bandit algorithm called Neural-LinUCB, which uses the hidden layers of a ReLU neural network as a deep representation of the raw feature vectors and performs UCB type exploration on the last layer of the neural network. By incorporating techniques in liner contextual bandits and neural tangent kernels, we prove that the proposed algorithm achieves a sublinear regret when the width of the network is sufficiently large. This is the first regret analysis of neural contextual bandit algorithms with deep representation and shallow exploration, which have been observed in practice to work well on many benchmark bandit problems (Riquelme et al., 2018). We also conducted experiments on real-world datasets to demonstrate the advantage of the proposed algorithm over LinUCB and existing neural contextual bandit algorithms.

REFERENCES

Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pp. 2312–2320, 2011.

Alekh Agarwal, Daniel Hsu, Satyen Kale, John Langford, Lihong Li, and Robert Schapire. Taming the monster: A fast and simple algorithm for contextual bandits. In *International Conference on Machine Learning*, pp. 1638–1646, 2014.

Zeyuan Allen-Zhu, Yuanzhi Li, and Yingyu Liang. Learning and generalization in overparameterized neural networks, going beyond two layers. In *Advances in neural information processing systems*, pp. 6155–6166, 2019a.

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via overparameterization. In *International Conference on Machine Learning*, pp. 242–252, 2019b.

Robin Allesiardo, Raphaël Féraud, and Djallel Bouneffouf. A neural networks committee for the contextual bandit problem. In *International Conference on Neural Information Processing*, pp. 374–381. Springer, 2014.

Sanjeev Arora, Simon Du, Wei Hu, Zhiyuan Li, and Ruosong Wang. Fine-grained analysis of optimization and generalization for overparameterized two-layer neural networks. In *International Conference on Machine Learning*, pp. 322–332, 2019a.

Sanjeev Arora, Simon S Du, Wei Hu, Zhiyuan Li, Russ R Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In *Advances in Neural Information Processing Systems*, pp. 8139–8148, 2019b.

Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári. Exploration–exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science*, 410(19):1876–1902, 2009.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

Sivaraman Balakrishnan, Martin J Wainwright, Bin Yu, et al. Statistical guarantees for the em algorithm: From population to sample-based analysis. *The Annals of Statistics*, 45(1):77–120, 2017.

Qi Cai, Zhuoran Yang, Jason D Lee, and Zhaoran Wang. Neural temporal-difference learning converges to global optima. In *Advances in Neural Information Processing Systems*, 2019.

Yuan Cao and Quanquan Gu. A generalization theory of gradient descent for learning overparameterized deep relu networks. *arXiv preprint arXiv:1902.01384*, 2019a.

Yuan Cao and Quanquan Gu. Generalization bounds of stochastic gradient descent for wide and deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 10835–10845, 2019b.

Olivier Chapelle and Lihong Li. An empirical evaluation of thompson sampling. In *Advances in neural information processing systems*, pp. 2249–2257, 2011.

Sayak Ray Chowdhury and Aditya Gopalan. On kernelized multi-armed bandits. In *International Conference on Machine Learning*, pp. 844–853, 2017.

Wei Chu, Lihong Li, Lev Reyzin, and Robert Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pp. 208–214, 2011.

Mark Collier and Hector Urdiales Llorens. Deep contextual multi-armed bandits. *arXiv preprint arXiv:1807.09809*, 2018.

George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of control, signals and systems*, 2(4):303–314, 1989.

Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. In *Conference on Learning Theory*, 2008.

Aniket Anand Deshmukh, Abhimanu Kumar, Levi Boyles, Denis Charles, Eren Manavoglu, and Urun Dogan. Self-supervised contextual bandits in computer vision. *arXiv preprint arXiv:2003.08485*, 2020.

Simon Du, Jason Lee, Haochuan Li, Liwei Wang, and Xiyu Zhai. Gradient descent finds global minima of deep neural networks. In *International Conference on Machine Learning*, pp. 1675–1685, 2019a.

Simon S. Du, Xiyu Zhai, Barnabas Poczos, and Aarti Singh. Gradient descent provably optimizes over-parameterized neural networks. In *International Conference on Learning Representations*, 2019b. URL https://openreview.net/forum?id=S1eK3i09YQ.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Sarah Filippi, Olivier Cappe, Aurélien Garivier, and Csaba Szepesvári. Parametric bandits: The generalized linear case. In *Advances in Neural Information Processing Systems*, pp. 586–594, 2010.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Geoffrey E Hinton and Ruslan R Salakhutdinov. Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507, 2006.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in neural information processing systems*, pp. 8571–8580, 2018.

Branislav Kveton, Manzil Zaheer, Csaba Szepesvari, Lihong Li, Mohammad Ghavamzadeh, and Craig Boutilier. Randomized exploration in generalized linear bandits. In *International Conference on Artificial Intelligence and Statistics*, pp. 2066–2076, 2020.

John Langford and Tong Zhang. The epoch-greedy algorithm for multi-armed bandits with side information. In *Advances in neural information processing systems*, pp. 817–824, 2008.

Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In *Advances in neural information processing systems*, pp. 8570–8581, 2019.

Lihong Li, Wei Chu, John Langford, and Robert E Schapire. A contextual-bandit approach to personalized news article recommendation. In *Proceedings of the 19th international conference on World wide web*, pp. 661–670, 2010.

Lihong Li, Yu Lu, and Dengyong Zhou. Provably optimal algorithms for generalized linear contextual bandits. In *International Conference on Machine Learning*, pp. 2071–2080, 2017.

Boyi Liu, Qi Cai, Zhuoran Yang, and Zhaoran Wang. Neural trust region/proximal policy optimization attains globally optimal policy. In *Advances in Neural Information Processing Systems*, pp. 10564–10575, 2019.

Samet Oymak and Mahdi Soltanolkotabi. Towards moderate overparameterization: global convergence guarantees for training shallow neural networks. *IEEE Journal on Selected Areas in Information Theory*, 2020.

Carlos Riquelme, George Tucker, and Jasper Snoek. Deep bayesian bandits showdown: An empirical comparison of bayesian deep networks for thompson sampling. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=SyYe6k-CW.

Paat Rusmevichientong and John N Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

Daniel J. Russo, Benjamin Van Roy, Abbas Kazerouni, Ian Osband, and Zheng Wen. A tutorial on thompson sampling. *Foundations and Trends® in Machine Learning*, 11(1):1–96, 2018. ISSN 1935-8237.

Jyotirmoy Sarkar. One-armed bandit problems with covariates. *The Annals of Statistics*, pp. 1978–2002, 1991.

Jasper Snoek, Oren Rippel, Kevin Swersky, Ryan Kiros, Nadathur Satish, Narayanan Sundaram, Mostofa Patwary, Mr Prabhat, and Ryan Adams. Scalable bayesian optimization using deep neural networks. In *International conference on machine learning*, pp. 2171–2180, 2015.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

Michal Valko, Nathan Korda, Rémi Munos, Ilias Flaounas, and Nello Cristianini. Finite-time analysis of kernelised contextual bandits. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pp. 654–663, 2013.

Lingxiao Wang, Qi Cai, Zhuoran Yang, and Zhaoran Wang. Neural policy gradient methods: Global optimality and rates of convergence. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=BJgQfkSYDS.

Zhaoran Wang, Han Liu, and Tong Zhang. Optimal computational and statistical rates of convergence for sparse nonconvex learning problems. *Annals of statistics*, 42(6):2164, 2014.

Pan Xu and Quanquan Gu. A finite-time analysis of q-learning with neural network function approximation. In *International Conference on Machine Learning*, 2020.

Pan Xu, Jian Ma, and Quanquan Gu. Speeding up latent variable gaussian graphical model estimation via nonconvex optimization. In *Advances in Neural Information Processing Systems*, pp. 1933–1944, 2017.

Tom Zahavy and Shie Mannor. Deep neural linear bandits: Overcoming catastrophic forgetting through likelihood matching. *arXiv preprint arXiv:1901.08612*, 2019.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Sy8gdB9xx.

Weitong Zhang, Dongruo Zhou, Lihong Li, and Quanquan Gu. Neural thompson sampling. *arXiv preprint arXiv:2010.00827*, 2020.

Dongruo Zhou, Lihong Li, and Quanquan Gu. Neural contextual bandits with ucb-based exploration. In *International Conference on Machine Learning*, 2020.

Difan Zou and Quanquan Gu. An improved analysis of training over-parameterized deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 2053–2062, 2019.

Difan Zou, Yuan Cao, Dongruo Zhou, and Quanquan Gu. Stochastic gradient descent optimizes over-parameterized deep relu networks. *arXiv preprint arXiv:1811.08888*, 2018.