BISPECTRAL NEURAL NETWORKS

ABSTRACT

We present a neural network architecture, Bispectral Neural Networks (BNNs) for learning representations that are invariant to the actions of compact commutative groups on the space over which a signal is defined. The model incorporates the ansatz of the bispectrum, an analytically defined group invariant that is *complete*—that is, it preserves all signal structure while removing only the variation due to group actions. Here, we demonstrate that BNNs are able to simultaneously learn groups, their irreducible representations, and corresponding complete invariant maps purely from symmetries implicit in data. Further, we demonstrate that the completeness property endows these networks with strong adversarial robustness. This work establishes Bispectral Neural Networks as a powerful computational primitive for robust invariant representation learning.

1 INTRODUCTION

A fundamental problem of intelligence is to model the transformation structure of the natural world. In the context of vision, translation, rotation, and scaling define symmetries of object categorization—the transformations that leave perceived object identity invariant. In audition, pitch and timbre define symmetries of speech recognition. Biological neural systems have learned these symmetries from the statistics of the natural world—either through evolution or accumulated experience. Here, we tackle the problem of learning symmetries in artificial neural networks.

At the heart of the challenge lie two requirements that are frequently in tension: *invariance* to transformation structure and *selectivity* to pattern structure. In deep networks, operations such as `max` or `average` are commonly employed to achieve invariance to local transformations. Such operations are invariant to many natural transformations; however, they are also invariant to unnatural transformations that destroy image structure, such as pixel permutations. This lack of selectivity may contribute to failure modes such as susceptibility to adversarial perturbations [11, 17] and selectivity for textures rather than objects [2]. Thus, there is a need for computational primitives that selectively parameterize natural transformations and facilitate robust invariant representation learning.

An ideal invariant would be *complete*. A complete invariant preserves all pattern information and is invariant only to specific transformations relevant to a task. Transformations in many datasets arise from the geometric structure of the natural world. The mathematics of *groups* and their associated objects give us the machinery to precisely define, represent, and parameterize these transformations, and hence the problem of invariant representation learning. In this work, we present a novel neural network primitive based on the *bispectrum*, a complete invariant map rooted in harmonic analysis and group representation theory [19, 18].

Bispectral Neural Networks (BNNs, Figure 1) flexibly parameterize the bispectrum for arbitrary compact commutative groups, enabling both the group and the invariant map to be learned from data. The architecture is remarkably simple. It is composed of two layers: a single learnable linear layer, followed by a fixed collection of triple products computed from the output of the previous layer. Provably, this architecture parameterizes a large family of group-invariant maps, where the weights of the first layer determine the group. BNNs are trained with an objective function consisting of two terms: one that collapses all transformations of a pattern to a single point in the output (invariance), and another that prevents information collapse in the first layer (selectivity).

We demonstrate that BNNs trained to separate orbit classes in augmented data learn both the group and its irreducible representations purely from the symmetries implicit in the data (Section 4.1). Because the model has learned the fundamental structure of the group, we show that it generalizes to

Figure 1: Bispectral Neural Networks. Leveraging the ansatz of the generalized bispectrum, Bispectral Neural Networks simultaneously learn the group structure in a dataset and its corresponding group-invariant and -equivariant representation spaces. The module is comprised of two layers: (1) a learnable linear transformation parameterized by W, and (2) a fixed collection of triple products.

novel, out-of-distribution classes with the same group structure and facilitates downstream group-invariant classification (Section 4.2). Further, we demonstrate that the trained network inherits the completeness of the analytical model, which endows the network with strong adversarial robustness (Section 4.3). Finally, we demonstrate that the weights of the network can be used to recover the group Cayley table—the fundamental signature of a group's structure (Section 4.4). Thus, an explicit model of the group can be learned and extracted from the network weights. To our knowledge, our work is the first to demonstrate that either a bispectrum or a group Cayley table can be learned from data alone. Our results set the foundation of a new computational primitive for robust and interpretable representation learning.

1.1 RELATED WORK

The great success and efficiency of convolutional neural networks owes much to built-in *equivariance* to the group of 2D translations. In recent years, an interest in generalizing convolution to non-Euclidean domains such as graphs and 3D surfaces has led to the incorporation of additional group symmetries into deep learning architectures [6, 4]. In another line of work, Kakarala [22] and Kondor [26] pioneered the use of the analytical bispectrum in signal processing and machine learning contexts. These approaches require specifying the group of transformations *a priori* and explicitly building their structure into the network architecture. However, the group transformations latent in a dataset are often either unknown or too complex to specify analytically—for example, when the structure arises from the interaction of many groups, or when the group acts on latent features in data.

Rather than specifying the relevant group transformations by hand, another line of work has sought to learn latent group structure solely from symmetries contained in data. The majority of these approaches use structured models that parameterize irreducible representations or Lie algebra generators, which act on the data through the group exponential map [34, 28, 8, 37, 7, 5]. In these models, the objective is typically to infer the group element that acts on a template to generate the observed data, with inference accomplished through Expectation Maximization or other Bayesian approaches. One drawback of these models is that both the group exponential map and inference schemes are relatively computationally expensive; thus, they are difficult to integrate into large-scale systems. A recent feed-forward approach [1] learns distributions over the group of 2D affine transformations in a deep learning architecture; however, the group is still specified in advance.

Here, we present a novel approach for learning groups from data in an efficient, interpretable, and fully feed-forward model that requires no prior knowledge of the group, computation of the exponential map, or bayesian inference. The key insight in our approach is to harness the generality of the form of the group-invariant bispectrum, which can be defined for arbitrary compact groups, both commutative and non-commutative. Here, we focus on the class of compact commutative groups.

2 THE BISPECTRUM

The theory of groups and their representations provides a natural framework for constructing computational primitives for robust machine learning systems. We provide a one-page introduction to these mathematical foundations in Appendix A. Extensive treatment of these concepts can be found in the

excellent textbooks of Hall [13] and Gallier & Quaintance [9].We now define the concepts essential to this work: invariance, equivariance, orbits, complete invariance, and irreducible representations.

Let G be a group and X a space on which G acts. First, a function $\phi : X \to Y$ is *G-equivariant* if $\phi(gx) = g'\phi(x)$ for all $g \in G$ and $x \in X$, with $g' \in G'$ homomorphic to G. That is, a group transformation on the input space results in a corresponding group transformation on the output space. A function $\phi : X \to Y$ is *G-invariant* if $\phi(x) = \phi(gx)$ for all $g \in G$ and $x \in X$. This means that a group action on the input space has no effect on the output. Another important construct in the context of image transformations, called an *orbit*, defines the set of all transformed versions of a canonical image—for example, if G is the group of translations, then the orbit contains all translated versions of that image. Formally, given a point $x \in X$, the *orbit Gx* of x is the set $\{gx : g \in G\}$.

With the notion of an orbit in hand, we now more precisely define complete invariance. We say ϕ is a *complete invariant* when $\phi(x_1) = \phi(x_2)$ if and only if $x_2 = gx_1$ for some $g \in G$ and $x_1, x_2 \in X$. A complete invariant collapses each orbit to a single point while also guaranteeing that different orbits map to different points. In the context of vision, for example, this implies that the only information lost through the map ϕ is that of the specific "pose" of the object.

Finally, we introduce the notion of an irreducible representation. A *representation* of a group G is map $\rho : G \to GL(V)$ that assigns elements of G to elements of the group of linear transformations (e.g. matrices) over a vector space V such that $\rho(g_1 g_2) = \rho(g_1)\rho(g_2)$. That is, ρ is a group homomorphism. In our case, V is $\mathbb{C}^n$. A representation is *reducible* if there exists a change of basis that decomposes the representation into a direct sum of other representations. An *irreducible representation* is one that cannot be further reduced in this manner, and the set $Irr(G)$ are often simply called the *irreps* of G. The irreducible representations of all finite commutative groups are one-dimensional and in bijection with the group itself. In particular, it is straightforward to compute $Irr(G)$ for such groups given their classification as products of cyclic groups $\mathbb{Z}/n\mathbb{Z}$.

2.1 FOURIER ANALYSIS ON GROUPS

A powerful approach for constructing invariants leverages the group theoretic generalization of the classical Fourier Transform [35]. Let $f(g)$ be a signal over the domain G, and let $Irr(G)$ denote the irreducible representations of G. We assume that $\rho \in Irr(G)$ are also *unitary* representations (i.e., $\rho^{-1} = \rho^\dagger$, with $\rho^\dagger$ the conjugate transpose). The *Generalized Fourier Transform* (GFT) is the linear map $f \mapsto \hat{f}$, in which Fourier frequencies are indexed by $\rho \in Irr(G)$:

$$\hat{f}_\rho = \sum_{g \in G} \rho(g) f(g). \tag{1}$$

Readers familiar with the classical Fourier transform should identify $\rho(g)$ with the exponential term in the usual sum or integral. Here, they arise naturally as the representations of $\mathbb{Z}/n\mathbb{Z}$ or S^1. Intuitively, these ρ are the "fundamental frequencies" of the group. In particular, for $G = \mathbb{Z}/n\mathbb{Z}$—the group of *integers modulo n*—they are the classical n discrete Fourier frequencies: $\rho_k(g) = e^{-2\pi \mathbf{i} kg/n}$, for $k = 0, \ldots, n - 1$ and $g \in \mathbb{Z}/n\mathbb{Z}$. For compact continuous groups G, the sum above is replaced by an integral $\int \rho(u) f(u) du$ over a Haar measure du for the group.

Importantly, the Fourier transform is *equivariant* to the action of translation on the domain of the input—a fundamental, if not defining, property. That is, if $f^t = f(g - t)$ is the translation of f by $t \in G$, its Fourier transform becomes:

$$(\hat{f}^t)_\rho = \rho(t)\hat{f}. \tag{2}$$

For the classical Fourier transform, this is the familiar *Fourier shift property*: translation of the input results in phase rotations of the complex Fourier coefficients. This property is exploited in one particularly well-known Fourier invariant—the *power spectrum*:

$$q_\rho = \hat{f}_\rho^\dagger \hat{f}_\rho. \tag{3}$$

The power spectrum preserves only the magnitude of the Fourier coefficients, eliminating the phase information entirely by multiplying each coefficient by its conjugate:

$$q_k^t = \left(e^{-\mathbf{i}2\pi kt/n} \hat{f}_k \right)^\dagger \left(e^{-\mathbf{i}2\pi kt/n} \hat{f}_k \right) = e^{\mathbf{i}2\pi kt/n} e^{-\mathbf{i}2\pi kt/n} \hat{f}_k^\dagger \hat{f}_k = q_k.$$

Although this approach eliminates variations due to translations of the input, it also eliminates much of the signal structure, which is largely contained in relative phase relationships [32]. Thus, the power

spectrum is *incomplete*. As a result, it is easy to create "adversarial examples" demonstrating the incompleteness of this invariant: any two images with identical Fourier magnitudes but non-identical phase have the same power spectra (Appendices C and D).

2.2 THE BISPECTRUM

The *bispectrum* is a lesser known Fourier invariant parameterized by pairs of frequencies in the Fourier domain. The translation-invariant *bispectrum* for 1D signals $f \in \mathbb{R}^n$ is the complex matrix $B \in \mathbb{C}^{n \times n}$:

$$B_{ij} = \hat{f}_i \hat{f}_j \hat{f}_{i+j}^\dagger, \tag{4}$$

where $\hat{f} = (\hat{f}_0, \ldots, \hat{f}_{n-1})$ is the 1D Fourier transform of f and the sum $i + j$ is taken modulo n. Intuitively, bispectral coefficients B_{ij} indicate the strength of couplings between different phase components in the data, preserving the phase structure that the power spectrum loses. Again, the equivariance property of the GFT is key to B's invariance. Like the power spectrum, it cancels out phase shifts due to translation. However it does so while preserving the relative phase structure of the signal. This remarkable property may be seen as follows:

$$
\begin{aligned}
B_{k_1,k_2}^t &= e^{-i2\pi k_1 t/n} \hat{f}_{k_1} e^{-\mathbf{i}2\pi k_2 t/n} \hat{f}_{k_2} e^{\mathbf{i}2\pi(k_1+k_2)t/n} \hat{f}_{k_1+k_2}^\dagger \\
&= e^{-\mathbf{i}2\pi k_1 t/n} e^{-\mathbf{i}2\pi k_2 t/n} e^{\mathbf{i}2\pi k_1 t/n} e^{\mathbf{i}2\pi k_2 t/n} \hat{f}_{k_1} \hat{f}_{k_2} \hat{f}_{k_1+k_2}^\dagger = B_{k_1,k_2}.
\end{aligned}
$$

Unlike the power spectrum, the bispectrum (for compact groups) is complete and can be used to reconstruct the original signal up to translation [43]. Moreover, the bispectrum can be defined on *any compact group*—commutative or non-commutative—while retaining the property of completeness [21]. For a commutative group, the bispectrum is defined similarly as above—as a product of three (complex) linear forms, with addition modulo n being replaced by the operation in the corresponding group. For non-commutative groups, the bispectrum has a similar trilinear structure; however it is modified to accommodate the fact that the irreps of non-commutative groups map to matrices rather than scalars (Appendix B).

Historically, the bispectrum emerged from the study of the higher-order statistics of non-Gaussian random processes, and was used as a tool to measure the non-Gaussianity of a signal [39, 3, 31]. The work of Yellott and Iverson [43] established that every integrable function with compact support is completely identified—up to translation—by its three-point autocorrelation and thus its bispectrum (Appendix F). Later work of Kakarala tied the bispectrum to the more general formulation of Fourier analysis and thus defined it for all compact groups [23, 20, 22]. Kakarala went on to prove that it is complete [21] in both commutative and non-commutative formulations (Appendix D).

3 BISPECTRAL NEURAL NETWORKS

We draw inspiration from the group-invariant bispectrum to define Bispectral Neural Networks, a neural network architecture that parameterizes the *ansatz* of the bispectrum. The key idea behind this approach is to constrain the optimization problem by building in the *functional form* of a solution known to exist. Importantly, we build in only the generic functional form and allow the network to learn the appropriate parameters (and thus the group over which it is defined) from data. We draw upon two key properties of the bispectrum, which allow it to be naturally parameterized and learned:

1. The bispectrum is computed on a group-equivariant Fourier transform. The Fourier transform is a linear map and can be written as $z = Wx$, with W a matrix of irreducible representations—e.g. the Discrete Fourier Transform (DFT) matrix, in the classical case. If the group (and thus its irreps) are unknown, we can treat W as a matrix of parameters to be learned through optimization. The bispectrum computation is identical regardless of the structure of the irreps; thus we can use a single network architecture to learn arbitrary (compact commutative) groups.

2. The bispectrum separates orbits. Here, we use orbit separation at the output of the bispectrum computation as the criterion to optimize the parameters defining the group-equivariant Fourier transform. This requires knowing only which datapoints are in the same orbit (but not the group that generates the orbit), and is similar in spirit to contrastive learning [12].

3.1 MODEL ARCHITECTURE

Concretely, given an input vector $x \in \mathbb{R}^n$, the Bispectral Neural Network module is completely specified by one complex matrix $W \in \mathbb{C}^{n \times n}$, where each row $W_i \in \mathbb{C}^n$ plays the role of an irreducible representation. This matrix defines the linear transformation:

$$z = Wx. \tag{5}$$

If W defines a Fourier transform on G, then each element of z is a coefficient on a different irreducible representation of G. The bispectrum can then be computed from triples of coefficients as:

$$\beta_{i,j} = z_i z_j z_{i,j}^{\dagger} \tag{6}$$

However, if the group is unknown, then we do not know *a priori* which element in the vector z corresponds to the $(i,j)^{\text{th}}$ irrep. Conveniently, for commutative groups, all irreducible representations are in bijection with the group elements. That is, each irreducible representation can be uniquely identified with a group element. Consequently, the $(i,j)^{\text{th}}$ representation can obtained from the element-wise multiplication of the i^{th} and j^{th} irreducible representations. Thus, the (conjugated) $(i,j)^{\text{th}}$ coefficient can be obtained as

$$z_{i,j}^{\dagger} = (W_i \odot W_j)^{\dagger} x, \tag{7}$$

with $\odot$ indicating the Hadamard (element-wise) product and $\dagger$ the complex conjugate. Plugging this into Equation 6 and expanding the terms, we obtain the Bispectral Network:

$$\beta_{i,j}(x) = W_i x \cdot W_j x \cdot (W_i \odot W_j)^{\dagger} x \tag{8}$$

Each linear term $W_i x$ is an inner product, yielding a scalar value, and the three terms are combined with scalar multiplication operation $\times$ in $\mathbb{C}$. Note that this equation shows the computation of a single scalar output $\beta_{i,j}$. A schematic is shown in Figure 2.

Figure 2: Bispectral Network Architecture

While the bispectrum is a third-order polynomial, it only results in n^2 rather than n^3 products, due to the constraint on the third term. Moreover, the bispectrum has many symmetries and is thus highly redundant. The most obvious symmetry is reflection over the diagonal—i.e. $\beta_{i,j} = \beta_{j,i}$. However, there are many more (see Appendix G). Here, we compute only the upper triangular of the matrix.

As the Bispectral Network computes third-order products of the input, the output values can be both very large and very small, which can result in numerical instability during optimization. To combat this, we normalize the output of the network to the unit sphere in $\mathbb{C}^n$:

$$\bar{\beta}(x) = \frac{\beta(x)}{||\beta(x)||_2} \tag{9}$$

We demonstrate in Appendix E that the analytical bispectrum can be normalized to the unit sphere while preserving completeness up to a scalar factor (Appendix E, Theorem E.3). Thus, we similarly expect that this normalization will not impact the robustness of the network.

3.2 ORBIT SEPARATION LOSS

Given a dataset $X = \{x_1, ..., x_m\}$ with latent group structure and labels $Y = \{y_1, ..., y_m\}$ indicating which datapoints are equivalent up to transformation (but without information about the transformation itself, i.e. *how* they are related), we wish to learn an invariant map that collapses elements of the same group orbit and separates distinct orbits. Critically, we want this map to be both *invariant* to group actions and *selective* to pattern structure—that is, to be *complete* [21]. A network that successfully learns such a map will have implicitly *learned the group* that structures transformations in the data.

To that end, we introduce the *Orbit Separation Loss*. This loss encourages the network to map elements of the same orbit to the same point in the representation space, while ensuring degenerate

solutions (i.e. mapping all inputs to the same point) are avoided:

$$L(x_i) = \sum_{j|y_j=y_i} ||\bar{\beta}(x_i) - \bar{\beta}(x_j)||_2 + \gamma||x_i - W^{\dagger}W\,x_i||_2. \tag{10}$$

The first term measures the Euclidean distance in the output space between points in the same orbit. Thus, minimizing the loss encourages them to be closer. In the second term, the input x_i is reconstructed by inverting the linear transform as $W^{\dagger}W x_i$. The second term is thus a measure of whether information is preserved in the map. During training, each row vector in the weight matrix W is normalized to unit length after every gradient update, which pushes W towards the manifold of unitary matrices. The coefficient γ weights the contribution of the reconstruction error to the loss.

4 EXPERIMENTS AND ANALYSES

We now test the capacity of Bispectral Networks to learn to separate orbit classes in datasets containing known transformation structure: 2D translation ($S^1 \times S^1$) and 2D rotation ($SO(2)$). A key feature of the bispectrum is that the same ansatz (i.e. model) can be used regardless of the form of the pattern signals and the (commutative) group transformation structure. This has two important implications. First, the same network can learn invariance to one of a wide variety of group actions, merely by descending the objective function in Equation 10 for a given dataset. Second, once a network has converged, it can generalize across arbitrary patterns provided that they share the same transformation structure. This strong generalization arises from the completeness properties of the bispectrum. We conduct four experiments to test these expectations: (1) Learning irreducible representations, (2) Group-invariant classification, (3) Adversarial robustness, and (4) Learning the group.

4.1 LEARNING IRREDUCIBLE REPRESENTATIONS

We train Bispectral Networks on datasets consisting of natural image patches from the van Hateren database [40] and their orbits under the two groups (2D translation and $SO(2)$ rotation). We evaluate the learned structure of the model in terms of: (a) whether the learned weights converge to the irreducible representations of that group, (b) whether the output of the linear transformation is equivariant to the group action on the input, and (c) whether the output of the network is invariant to the group action. We test the invariance and equivariance properties on unseen, out-of-distribution signal classes that the model was not trained on to test the generality of the learned map, using rotated and translated versions of the MNIST [27] dataset for the test set.

Models are trained on datasets consisting of 100 randomly sampled (16, 16) natural image patches from the van Hateren dataset [40] that have been transformed by the groups $S^1 \times S^1$ (2D cyclic translation) or $SO(2)$ (2D rotation) to generate orbit classes. Further details about the dataset can be found in Appendix H. Networks are trained to convergence on the Orbit Separation Loss, Equation 10. All hyperparameters and other details about the training procedure can be found in Appendix I.1.

Figure 3: A representative selection of the learned filters. Real components of weights learned in the Bispectral Network trained on the van Hateren Natural Images dataset. (Left) the Cyclic 2D Translation dataset and (Right) the 2D Rotation dataset.. The full set of learned weights can be found in Appendix J.

Remarkably, we find that the relatively loose constraints of the orbit separation loss and the trilinear structure of the network architecture is sufficient to encourage the network to learn a group-equivariant Fourier transform and its corresponding bispectrum from these small datasets. This is observed in the structure of the network weights, which converge to the representations of the group (i.e. the 2D Fourier basis for $S^1 \times S^1$ and the disk harmonics for $SO(2)$) (Figure 3).

Moreover, the learned linear map (i.e. Equation 5) is equivariant to the action of the group on the input, and the learned invariant map (i.e. the Bispectral Network output, Equation 9) is invariant to

the group action on arbitrary input signals. We visualize this in Figure 4 for transformed exemplars from the MNIST dataset, which the model was not trained on.

Figure 4: Model Outputs on Transformed Data. Outputs of the linear transform (Wx, top row) and full network output (Eq. 9, bottom row). Data inputs are cyclically translated/rotated in one direction (x-axis) and layer/network outputs are computed for each transformation. Each colored line represents the output of a single neuron, with the activation value on the y-axis. In the top row, only four neuron outputs are visualized, for clarity.

4.2 GROUP-INVARIANT CLASSIFICATION

We now examine the utility of the rotation model learned in Section 4.1 for facilitating performance on a downstream image classification task: digit classification for the Rotated MNIST dataset. For this experiment, we append a simple multi-layer fully-connected ReLU network (MLP; the "classification network") to the output of the Bispectral Network and train it on the classification objective. While the Bispectral Network learns to eliminate factors of variation due to group actions, the classification network learns to eliminate other variations within digit classes irrelevant to classification, i.e. those due to handwriting style.

Model	**Learns Group**	**Feedforward**	**Accuracy**
Linear SVM (Baseline)	N	NA	54.7%
Cohen & Welling (2014) [7]	**Y**	N	$\sim 97\%^{*}$
Harmonic Networks (2017) [42]	N	**Y**	98.3%
Augerino (2020) [1]	N	**Y**	98.9%
E2CNN (2019) [41]	N	**Y**	99.3%
Bispectral Network + MLP (ours)	**Y**	**Y**	98.1%

Table 1: Classification Accuracy on RotMNIST. Our model scores within 1.2% of the model with top classification accuracy, despite never having trained the bispectrum module on RotMNIST data. The leading models require explicit specification of the group structure in their design, whereas ours learns the group from data alone. Further, our model is complete and robust to adversarial attack (see 5), which is not the case for the leading models (E2CNN and Augerino), as shown in Figure 5. *This number was estimated from the bar plot in Figure 4 of [7] and approved by the first author of the paper in personal communication, as numbers were not explicitly reported in the text.

We train the classification model using the scheme described in Appendix I. We compare the performance of our model to four leading approaches to group-invariant classification, in addition to a Linear Support Vector Machine (SVM) model that we train as a baseline (Table 1). Our model obtains a competitive 98.1% classification accuracy on this task—within $0.2 - 1.2\%$ of the state-of-the-art methods compared to here. Although the network is outperformed by other methods in the table, our model possesses notable differences and advantages. First, our model *learns the group* from data, in contrast to Harmonic Networks [42] and E2CNNs [41], which build in $SO(2)$-equivariance, and [1], which builds in 2D affine transformations of the image grid into their algorithm. Second, the bispectrum component of the model was exclusively trained on natural image patches, then fixed. Only the downstream classifier was trained on the RotMNIST training data, yet the model generalizes competitvely to RotMNIST test data. Third, our model is fully feedforward, and it does not rely

on the computationally intensive EM inference scheme, as in [7], or the exponential map as used in [7] and [1]. Finally, in the next section, we demonstrate that our model is complete and robust to adversarial attack, while the leading models use `max` and `average` operations that make them susceptible to adversarial attack. We demonstrate this adversarial susceptibility for the leading model, E2CNN, in the next section.

4.3 ADVERSARIAL ROBUSTNESS

The goal of many adversarial attacks is to discover input points which are similar to a target sample in the model's representation space, yet perceptually dissimilar to the true sample in the input space. Under this kind of attack, adversarial robustness implies that all points which are similar in the model output space must be perceptually similar. A key property of the analytical bispectrum is its *completeness*: only signals that are exactly equal up to the group action will map to the same point in bispectrum space. Thus, the analytical bispectrum is highly robust to "adversarial attacks." That is, for a signal x, and bispectrum $B(x)$, the only perturbations in pixel space that will give rise to identical bispectra are those due to the group action, i.e. the orbit $Gx = \{gx : g \in G\}$.

Here, we test whether the learned Bispectral Networks possess the same robustness property by conducting adversarial attacks on the models, as follows. First, we pick a target x and initialize $N = 100$ standard normal random vectors $\bar{x}_i$ in $\mathbb{R}^m$. Both the target and randomly initialized vectors are passed through the network to yield $\bar{\beta}(x)$ (target) and $\bar{\beta}(\bar{x}_i)$ (adversarial inputs). The following objective is optimized with respect to the $\bar{x}_i$:

$$L = \sum_{i=0}^{N} ||\bar{\beta}(x) - \bar{\beta}(\bar{x}_i)||_2 \tag{11}$$

If the models contain nearby points which are not equivalent up to group action (a failure in completeness), then one would expect sucessful adversarial examples to emerge. If, however, the learned models are complete, then all random samples will converge to the orbit of the target.

Figure 5: Robustness to Adversarial Attacks. Candidate adversarial examples after convergence to an equivalent output as a target 5. (Left) $N = 25$ (a) Bispectral Network trained on 2D Cyclic Translation $S^1 \times S^1$ (b) Bispectral Network trained on 2D Rotation $SO(2)$ (Right) $N = 9$ (c) E2CNN (d) Augerino

Figure 5 shows the target image and the converged input vectors for the Bispectral Networks trained on translation and rotation in the van Hateren dataset, and the E2CNN and Augerino models trained on Rotated MNIST. Remarkably, the Bispectral Network is completely robust to adversarial attacks. Even though targets are selected from a dataset the network was not trained on (MNIST), the candidate "adversarial" inputs consistently converge to the orbit of the target across all random initializations, suggesting that the approximate bispectra learned by the models are close to "complete." By contrast, many adversarial examples misclassified by E2CNN and Augerino can be found.

4.4 LEARNING THE GROUP: EXTRACTING THE CAYLEY TABLE

Finally, we demonstrate that the converged networks weights can be used to *construct the group itself*, by recovering the group Cayley table. A *Cayley table* contains all information about a finite group: i.e. the structure of all pairwise products between group elements. Each entry in the table is the element of the group formed from the product of two group elements, i.e. $C(i, j) = g_i \cdot g_j$. It generalizes the familiar addition or multiplication table for $\mathbb{R}$. To construct the Cayley table from the learned irreducible representations, we exploit the fact that the irreducible representations of all commutative groups are in bijection with the group elements and define a novel algorithm that maps the irreps to their corresponding Cayley table, described below and in Appendix K.

According to the Fundamental Theorem of Finite Abelian Groups, every finite commutative group can be expressed as a direct product of cyclic groups. We generate datasets transformed by arbitrary

products of cyclic groups: $\mathbb{Z}/8\mathbb{Z}$, $\mathbb{Z}/4\mathbb{Z} \times \mathbb{Z}/2\mathbb{Z}$, and $\mathbb{Z}/2\mathbb{Z} \times \mathbb{Z}/2\mathbb{Z} \times \mathbb{Z}/2\mathbb{Z}$. For each group, we generate a synthetic dataset consisting of 100 randomly sampled exemplars in $\mathbb{R}^8$. Note that these samples are random functions over each group G, i.e. each exemplar is a signal $f : G \to \mathbb{R}$. For example, these groups could represent the action of shifting a time-series, a 2D image, and a 3D voxel image, respectively. We then generate samples for each class by transforming the domain of each exemplar with the group action, i.e. we generate the orbit. A model is then trained for each dataset. Networks are trained to convergence on the Orbit Separation Loss, Equation 10. All details about the training procedure can be found in Appendix I. After a model has converged, we use its learned weights to compute a Cayley table using Algorithm 1 in Appendix K.

Figure 6: Learned Group Cayley Tables. In each table, rows and columns are labeled with integers that index group elements. Each cell of the table contains the index of the group element obtained by composing the group elements indexed in the row and column. The Cayley table thus contains all information about the group structure. Remarkably, Bispectral Networks perfectly recover the Cayley tables for all groups tested here.

Importantly, the rows of the weight matrix W are not necessarily ordered. For this reason, the estimated Cayley table $\hat{C}$ will also be a permuted version of the true table C computed from the group G. To check if the two groups are isomorphic, we compute a Cayley table for each permutation $\pi \in S_n$ of G, denoted G_π, using 2 above, then check equality with the estimated Cayley table $\hat{C}$ computed from W. We describe this procedure in Algorithm 3 in Appendix K. Remarkably, our model recovers the exact structure of the group underlying transformations in the data. We illustrate this in Figure 6. For each dataset, the Cayley tables computed from the learned network weights are identical to the known ground-truth group structure. To our knowledge, this is the first method to explicitly learn and concretely construct a group from data alone.

5 DISCUSSION

In this work, we have introduced a novel method for learning transformations from data in a network architecture that simultaneously learns a group-equivariant Fourier transform and its corresponding bispectrum. The result is an interpretable model that contains information about the group and its irreducible representations. This enables it to generalize to arbitrary unseen datasets that are structured by the same transformation group. Critically, *the model generalizes to novel, out-of-distribution classes* and is *strongly robust to adversarial attacks*. To our knowledge, the work presented here provides the first demonstration that a bispectrum can be parameterized and learned simply from the symmetries in data alone. Our method has key advantages over previous methods for group-invariant representation learning: it is a fully feed-forward model that requires no complicated inference schemes, knowledge of the group, or the computation of the exponential map. Futher, the model is efficient, requiring only n^2 complex-valued parameters, with n the dimension of the input.

Many paths for future research open as a result of this work. A primary limitation of the results presented here is the demonstration on relatively simple datasets (i.e. transformed natural image patches and MNIST). To scale to more complex data, the Bispectral Network model can be localized, replacing the inner product in a standard convolutional network with the bispectrum calculation to compute localized bispectra. We are pursuing this path in ongoing work. Another notable limitation is that we present results only for commutative groups here. However, the Bispectral Network model can be naturally extended to non-commutative groups, using the ansatz of the non-commutative bispectrum (Appendix 12), which we are pursuing in ongoing work. We view the work presented here as a starting point for learning the more complex groups needed to recognize 3D objects in natural imagery. The success demonstrated on these relatively simple datasets gives us encouragement that such a research trajectory is feasible.

REPRODUCIBILITY STATEMENT

The code to implement all models and experiments in this paper can be found at `github.com/bispectral-networks/bispectral-networks`. We provide files containing the trained models, configs containing all hyperparameters used in these experiments, notebooks to generate all visualizations in the paper, and donwload links for the datasets used in these experiments.

REFERENCES

[1] Gregory Benton et al. "Learning invariances in neural networks from training data". In: *Advances in neural information processing systems* 33 (2020), pp. 17605–17616.

[2] Wieland Brendel and Matthias Bethge. "Approximating cnns with bag-of-local-features models works surprisingly well on imagenet". In: *arXiv preprint arXiv:1904.00760* (2019).

[3] D Brillinger. "Some history of higher-order statistics and spectra". In: *Stat. Sin.* 1 (1991), pp. 465–476.

[4] Michael M Bronstein et al. "Geometric Deep Learning: Grids, Groups, Graphs, Geodesics, and Gauges". In: *arXiv preprint arXiv:2104.13478* (2021).

[5] Ho Yin Chau et al. "Disentangling images with Lie group transformations and sparse coding". In: *arXiv preprint arXiv:2012.12071* (2020).

[6] Taco Cohen and Max Welling. "Group equivariant convolutional networks". In: *International conference on machine learning*. PMLR. 2016, pp. 2990–2999.

[7] Taco Cohen and Max Welling. "Learning the irreducible representations of commutative lie groups". In: *International Conference on Machine Learning*. PMLR. 2014, pp. 1755–1763.

[8] Benjamin J Culpepper and Bruno A Olshausen. "Learning transport operators for image manifolds." In: *NIPS*. 2009, pp. 423–431.

[9] Jean Gallier and Jocelyn Quaintance. *Differential Geometry and Lie Groups: A Computational Perspective*. Vol. 12. Springer Nature, 2020.

[10] Georgios B Giannakis. "Signal reconstruction from multiple correlations: frequency-and time-domain approaches". In: *JOSA A* 6.5 (1989), pp. 682–697.

[11] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. "Explaining and harnessing adversarial examples". In: *arXiv preprint arXiv:1412.6572* (2014).

[12] Raia Hadsell, Sumit Chopra, and Yann LeCun. "Dimensionality reduction by learning an invariant mapping". In: *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*. Vol. 2. IEEE. 2006, pp. 1735–1742.

[13] Brian C Hall. "Lie groups, Lie algebras, and representations". In: *Quantum Theory for Mathematicians*. Springer, 2013, pp. 333–366.

[14] Christopher A Haniff. "Least-squares Fourier phase estimation from the modulo 2π bispectrum phase". In: *JOSA A* 8.1 (1991), pp. 134–140.

[15] J H van Hateren and A van der Schaaf. "Independent Component Filters of Natural Images Compared with Simple Cells in Primary Visual Cortex". In: *Proceedings: Biological Sciences* 265.1394 (Mar. 1998), pp. 359–366.

[16] Kaiming He et al. "Delving deep into rectifiers: Surpassing human-level performance on imagenet classification". In: *Proceedings of the IEEE international conference on computer vision*. 2015, pp. 1026–1034.

[17] Jörn-Henrik Jacobsen et al. "Excessive invariance causes adversarial vulnerability". In: *arXiv preprint arXiv:1811.00401* (2018).

[18] R. Kakarala. "A group theoretic approach to the triple correlation". In: *IEEE Workshop on higher order statistics*. 1993, pp. 28–32.

[19] R. Kakarala. "Triple correlation on groups". PhD thesis. Department of Mathematics, UC Irvine, 1992.

[20] Ramakrishna Kakarala. "A group-theoretic approach to the triple correlation". In: *[1993 Proceedings] IEEE Signal Processing Workshop on Higher-Order Statistics*. IEEE. 1993, pp. 28–32.

[21] Ramakrishna Kakarala. "Completeness of bispectrum on compact groups". In: *arXiv preprint arXiv:0902.0196* 1 (2009).

[22] Ramakrishna Kakarala. "The bispectrum as a source of phase-sensitive invariants for Fourier descriptors: a group-theoretic approach". In: *Journal of Mathematical Imaging and Vision* 44.3 (2012), pp. 341–353.

[23] Ramakrishna Kakarala. "Triple correlation on groups". PhD thesis. University of California, Irvine, 1992.

[24] Diederik P Kingma and Jimmy Ba. "Adam: A method for stochastic optimization". In: *arXiv preprint arXiv:1412.6980* (2014).

[25] R. Kondor. *Group theoretical methods in machine learning*. Columbia University, PhD Thesis, 2008.

[26] Risi Kondor. "A novel set of rotationally and translationally invariant features for images based on the non-commutative bispectrum". In: *arXiv preprint cs/0701127* (2007).

[27] Y LeCun, C Cortes, and C Burges. "The MNIST Dataset of Handwritten Digits (Images)". In: *NYU: New York, NY, USA* (1999).

[28] Xu Miao and Rajesh PN Rao. "Learning the lie groups of visual invariance". In: *Neural computation* 19.10 (2007), pp. 2665–2693.

[29] Kevin Musgrave, Serge Belongie, and Ser-Nam Lim. "Pytorch metric learning". In: *arXiv preprint arXiv:2008.09164* (2020).

[30] Ivan Nazarov and Hendrick Schroter. *CplxModule*. https://github.com/ivannz/cplxmodule. 2021.

[31] Chrysostomos L Nikias and Jerry M Mendel. "Signal processing with higher-order spectra". In: *IEEE Signal processing magazine* 10.3 (1993), pp. 10–37.

[32] Alan V Oppenheim and Jae S Lim. "The importance of phase in signals". In: *Proceedings of the IEEE* 69.5 (1981), pp. 529–541.

[33] Adam Paszke et al. "Pytorch: An imperative style, high-performance deep learning library". In: *Advances in neural information processing systems* 32 (2019), pp. 8026–8037.

[34] Rajesh PN Rao and Daniel L Ruderman. "Learning Lie groups for invariant visual perception". In: *Advances in neural information processing systems* (1999), pp. 810–816.

[35] Walter Rudin. *Fourier analysis on groups*. Courier Dover Publications, 1962.

[36] Leslie N Smith. "Cyclical learning rates for training neural networks". In: *2017 IEEE winter conference on applications of computer vision (WACV)*. IEEE. 2017, pp. 464–472.

[37] Jascha Sohl-Dickstein, Ching Ming Wang, and Bruno A Olshausen. "An unsupervised algorithm for learning lie group transformations". In: *arXiv preprint arXiv:1001.1027* (2010).

[38] Chiheb Trabelsi et al. "Deep complex networks". In: *arXiv preprint arXiv:1705.09792* (2017).

[39] J. Tukey. "The spectral representation and transformation properties of the higher moments of stationary time series". In: *Reprinted in The Collected Works of John W. Tukey* 1 (1953), pp. 165–184.

[40] J Hans Van Hateren and Arjen van der Schaaf. "Independent component filters of natural images compared with simple cells in primary visual cortex". In: *Proceedings of the Royal Society of London. Series B: Biological Sciences* 265.1394 (1998), pp. 359–366.

[41] Maurice Weiler and Gabriele Cesa. "General e (2)-equivariant steerable cnns". In: *Advances in Neural Information Processing Systems* 32 (2019).

[42] Daniel E Worrall et al. "Harmonic networks: Deep translation and rotation equivariance". In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. 2017, pp. 5028–5037.

[43] JI Yellott Jr and GJ Iverson. "Uniqueness theorems for generalized autocorrelations". In: *Journal of the Optical Society of America* 9 (1992), pp. 388–404.

APPENDIX A MATHEMATICAL BACKGROUND

Groups. A *group* $(G, \cdot)$ is a set G with a binary operation $\cdot$, which we can generically call the *product*. The notation $a \cdot b$ denotes the product of two elements in the set; however, it is standard to omit the operator and write simply ab. Concretely, a group G may define a class of transformations, such as two-dimensional translations or rotations in the plane. The elements of the group $g \in G$ define *particular* transformations, such as *rotation by* $30°$ or *rotation by* $90°$. The binary operation $\cdot$ provides a means for combining two particular transformations—for example, first rotating by $30°$ and then rotating by $90°$. For a set of transformations G to be a group under the operation $\cdot$, the four following axioms must hold:

1. *Closure*: The product of any two elements of the group is also an element of the group, i.e. for all $a, b \in G$, $ab \in G$.

2. *Associativity*: The grouping of elements under the operation does not change the outcome, so long as the order of elements is preserved, i.e. $(ab)c = a(bc)$.

3. *Identity*: There exists a "do-nothing" *identity* element e that such that the product of e with any other element g returns g, i.e. $ge = eg = g$ for all $g \in G$.

4. *Inverse*: For every element g, there exists an *inverse* element g^{-1} such that the product of g and g^{-1} returns the identity, i.e. $gg^{-1} = g^{-1}g = e$.

Homomorphisms. Two groups $(G, \cdot)$ and $(H, *)$ are *homomorphic* if there exists a correspondence between elements of the groups that respect the group operation. Concretely, a *homomorphism* is a map $\rho : G \to H$ such that $\rho(u \cdot v) = \rho(u) * \rho(v)$. An *isomorphism* is a bijective homomorphism.

Product Groups. A *product group* as a set is the cartesian product $G \times H$ of two given groups G and H. The new group product is given by $(g_1, h_1) \cdot (g_2, h_2) = (g_1 g_2, h_1 h_2)$.

Commutativity. A group $(G, +)$ is *commutative* or *abelian* if the order of operations does not matter, i.e. $ab = ba$. If this does not hold for all elements of the group, then the group is called *non-commutative*. The classification of finite commutative groups says that each such group is a product of cyclic groups.

Group Actions. A *group action* is a map $T : G \times X \to X$ that maps (g, x) pairs to elements of X. We say a group G *acts* on a space X if the following properties of the action T hold:

1. The identity $e \in G$ maps an element of $x \in X$ to itself, i.e. $T(e, x) = x$

2. Two elements $g_1, g_2 \in G$ can be combined before or after the map to yield the same result, i.e. $T(g_1, T(g_2, x)) = T(g_1 g_2, x)$

For simplicity, we will use the shortened notation $T_g x$ to denote $T(g, x)$, often expressed by saying that a point x maps to gx ($= T_g(x)$).

Invariance. A function $\phi : X \mapsto Y$ is *G-invariant* if $\phi(x) = \phi(gx)$ for all $g \in G$ and $x \in X$. This means that group actions on the input space have no effect on the output.

Equivariance. A function $\phi : X \mapsto Y$ is *G-equivariant* if $\phi(gx) = g'\phi(x)$ for all $g \in G$ and $x \in X$, with $g' \in G'$, a group homomorphic to G that acts on the output space. This means that a group action on the input space results in a corresponding group action on the output space.

Orbits. Given a point $x \in X$, the *orbit Gx* of x is the set $\{gx : g \in G\}$. In the context of image transformations, the orbit defines the set of all transformed versions of a canonical image—for example, if G is the group of translations, then the orbit contains all translated versions of that image.

Homogeneous Spaces. We say that X is a *homogeneous space* for a group G if G acts transitively on X—that is, if for every pair $x_1, x_2 \in X$ there exists an element of $g \in G$ such that $gx_1 = x_2$. A homogeneous space X equipped with the action of G is called a **G**-*space*. The concept can be clearly illustrated by considering the surface of a sphere, the space S^2. The group $SO(3)$ of orthogonal 3×3 matrices with determinant one defines the group of 3-dimensional rotations. The sphere S^2 is a homogeneous space for $SO(3)$. For every pair of points on the sphere, one can define a 3D rotation matrix that takes one to the other.

Representations. A *representation* of a group G is map $\rho : G \to GL(V)$ that assigns elements of G to elements of the group of linear transformations over a vector space V such that $\rho(g_1 g_2) = \rho(g_1)\rho(g_2)$. That is, ρ is a group homomorphism. In many cases, V is $\mathbb{R}^n$ or $\mathbb{C}^n$. A representation is *reducible* if there exists a change of basis that decomposes the representation into a direct sum of other representations. An *irreducible representation* is one that cannot be further reduced in this manner, and the set of them $Irr(G)$ are often simply called the *irreps* of G. The irreducible representations of a finite commutative group are all one-dimensional and in bijection with the group itself. In particular, it is straightforward to compute $Irr(G)$ for such groups given their classification as products of cyclic groups $\mathbb{Z}/n\mathbb{Z}$.

APPENDIX B THE BISPECTRUM ON NON-COMMUTATIVE GROUPS

The theory of the bispectrum applies also in the setting of non-commutative groups and can be expressed in terms of the generalized Fourier transform and the (not necessarily one-dimensional) representations of the group. The more general, non-commutative form of the bispectrum is:

$$\beta_{\rho_1,\rho_2} = [\hat{f}\rho_1 \otimes \hat{f}\rho_2]C_{\rho_1,\rho_2}\Big[\bigoplus_{\rho \in \rho_1 \otimes \rho_2} \hat{f}_\rho^\dagger \Big]C_{\rho_1,\rho_2}^\dagger, \tag{12}$$

where $\otimes$ is the tensor product, $\oplus$ is a direct sum over irreps, and the unitary matrix C_{ρ_1,ρ_2} defines a Clebsch-Gordan decomposition on the tensor product of a pair of irreps ρ_1, ρ_2 [26].

APPENDIX C INCOMPLETENESS OF THE POWER SPECTRUM

Figure 7: The Power Spectrum is a Non-Selective Invariant. Two images with identical power spectra (top and middle) can have very different image structure. However, images with identical phase spectra and non-identical power spectra (top and bottom) share much of the meaningful image structure—that which defines edges and contours. May require enlargement to see. Note that the sharp horizontal and vertical lines in the power and phase spectra are artifacts due to the wrap-around of the image boundaries.

APPENDIX D COMPLETENESS OF THE BISPECTRUM

As described in the main text, the bispectrum is a (generically) complete invariant map with respect to a given compact group G [21]. Here, *generic* is a technical term that means "outside of a set of

measure zero." For instance, in the finite commutative group case, this amounts to uniqueness for all elements of the space that have all-nonzero Fourier coefficients.

In practice, this property is easily derived from the exactly computable inverse of the bispectrum; see, for instance, algorithms spelled out in [10, 25]. In these computations, an inverse is defined whenever denominators – which end up being Fourier coefficients recursively computed – appearing in the calculations are nonzero.

Figure 8: **The Bispectrum is a Complete Invariant.** (Left) Three hand-written characters and their corresponding orbits under one dimension of cyclic translation. (Middle Left) All samples mapped through the Fourier transform, then plotted in the plane formed by the first two principal components. (Middle Right) The power spectrum collapses the orbits of each character, successfully achieving invariance to translation. However, it is *excessively* invariant. A phase-scrambled image (light blue) maps to the same point as the purple digit class because it has the same power spectrum. (Right) The bispectrum is a complete invariant, mapping *all* points equivalent under group action to a unique point for each equivalence class of points.

APPENDIX E   COMPLETENESS OF THE NORMALIZED BISPECTRUM

A useful observation is that this generalizes somewhat to a normalized form of the bispectrum, where we project features to the unit sphere in $\mathbb{C}^n$ (normalization).

Definition E.1. The *normalized bispectrum* of a function f is defined as

$$\bar{\beta}(f) = \frac{\beta(f)}{||\beta(f)||_2}.$$

First, we show that any scalar multiple of the bispectrum preserves completeness up to positive scalar multiplication of the input signal f. Using this result, we show that the normalized bispectrum is generically complete up to the action of G and scalar multiplication.

Lemma E.1. *The bispectrum of a scalar $c > 0$ times a function f is:*
$$\beta(cf) = c^3\beta(f).$$

Proof. By linearity of the Fourier transform, we have: $\hat{cf} = c\hat{f}$. From the definition, the commutative bispectrum of cf therefore satisfies:

$$\beta(cf) = c\hat{f}_i c\hat{f}_j c\hat{f}_{i+j}$$
$$= c^3 \hat{f}_i \hat{f}_j \hat{f}_{i+j} = c^3\beta(f). \tag{13}$$

This is easily seen to also work for the non-commutative formulation. $\qquad\square$

Lemma E.2. *If the bispectra of two (generic) functions f and g differ by a constant factor $c > 0$, then the orbits of the two functions differ by a constant factor, i.e.*
$$\beta(f) = c\beta(g) \implies Gf = c^{\frac{1}{3}}Gg.$$

Proof. Assume $\beta(f) = c\beta(g)$ and let $h = c^{\frac{1}{3}}g$. By Lemma E.1, we have: $\beta(h) = c\beta(g)$, and by assumption, $\beta(f) = c\beta(g)$ so that $\beta(f) = \beta(h)$. By (generic) completeness of the bispectrum, the

orbits of f and h are equivalent; that is, $Gf = Gh$. Because h is a scalar multiple of g, the orbits of h and g are related by a constant factor: $Gh = c^{\frac{1}{3}} Gg$. Finally, because the orbit of f equals that of h, we see that the orbit of f is related to that of g by the same factor: $Gf = c^{\frac{1}{3}} Gg$. $\qquad\square$

Theorem E.3. *Two (generic) functions f and g have equivalent normalized bispectra if and only if their orbits under G are related by a scalar factor $c \in \mathbb{R}$.*

$$\hat{\beta}(f) = \hat{\beta}(g) \iff Gf = cGg.$$

Proof. ($\Leftarrow$) By assumption, $Gf = cGg$, which, together with Lemma E.1, implies $\beta(f) = c^3 \beta(g)$.

Writing out the definition of the normalized bispectrum, we see

$$
\begin{aligned}
\bar{\beta}(f) &= \frac{\beta(f)}{||\beta(f)||} \\
&= \frac{c^3 \beta(g)}{||c^3 \beta(g)||} \\
&= \frac{c^3 \beta(g)}{c^3 ||\beta(g)||} \\
&= \frac{\beta(g)}{||\beta(g)||} = \bar{\beta}(g).
\end{aligned}
\tag{14}
$$

($\Rightarrow$) Given $\bar{\beta}(f) = \bar{\beta}(g)$, we expand and see the following relation:

$$
\begin{aligned}
\bar{\beta}(f) &= \bar{\beta}(g) \\
\frac{\beta(f)}{||\beta(f)||} &= \frac{\beta(g)}{||\beta(g)||} \\
\beta(f) &= \frac{||\beta(f)||}{||\beta(g)||} \beta(g).
\end{aligned}
\tag{15}
$$

Letting $c = \frac{||\beta(f)||}{||\beta(g)||}$, we have:

$$\beta(f) = c\beta(g),$$

which by Lemma E.2 implies that $Gf = cGg$. $\qquad\square$

APPENDIX F POLYSPECTRA AND AUTOCORRELATIONS

Both the power spectrum and bispectrum are intimately related to the second- and third-order statistics of a signal, as the Fourier transforms of the two- and three-point autocorrelation functions, respectively. The two-point *autocorrelation* A_2 of a complex-valued function f on the real line is the integral of that function multiplied by a shifted copy of it:

$$A_{2,f}(s) = \int_{-\infty}^{\infty} f^{\dagger}(x) f(x+s) dx, \tag{16}$$

where s denotes the increment of the shift. Taking its Fourier transform, it becomes:

$$\hat{A}_{2,f}(s) = \hat{f}_k \hat{f}_k^{\dagger}, \tag{17}$$

which is the power spectrum. The three-point autocorrelation, also called the *triple correlation*, is the integral of a function multiplied by two independently shifted copies of it:

$$A_{3,f}(s_1, s_2) = \int_{-\infty}^{\infty} f^{\dagger}(x) f(x+s_1) f(x+s_2) dx. \tag{18}$$

Taking its Fourier transform it becomes:

$$\hat{A}_{2,f}(s_1, s_2) = \hat{f}_{k_1} \hat{f}_{k_2} \hat{f}^{\dagger}_{k_1+k_2}, \tag{19}$$

which is the bispectrum.

APPENDIX G   SYMMETRIES IN THE BISPECTRUM

The bispectrum has n^2 terms (with $n =$ number of frequencies). However, the object is highly redundant and is reducible to $\frac{n^2}{12}$ terms without loss of information for a real-valued signal [31]. This is due to the following symmetries, depicted in Figure 9. For $\omega_1 = 2\pi k_1$:

$$
\begin{aligned}
\beta_{\omega_1,\omega_2} &= \beta_{\omega_2,\omega_1} \\
&= \beta_{-\omega_2,-\omega_1} = \beta_{-\omega_1-\omega_2,\omega_2} \\
&= \beta_{\omega_1,-\omega_1-\omega_2} = \beta_{-\omega_1-\omega_2,\omega_1} \\
&= \beta_{\omega_2,-\omega_1-\omega_2}.
\end{aligned}
$$

Thus, the subset of bispectral coefficients for which $\omega_2 >= 0$, $\omega_1 >= \omega_2$, $\omega_1 + \omega_2 <= \pi$ is sufficient for a complete description of the bispectrum.

Symmetries of the Triple Correlation and Bispectrum

Figure 9: Symmetries of the Triple Correlation and Bispectrum. For a real-valued signal, the six-fold symmetry of the triple product becomes a twelve-fold symmetry in which six paris of regions are conjugate symmetric (with the complex conjugate indicated in grey). Adapted from [31].

It is also known that, in fact, the bispectrum can be further reduced. For example, for the bispectrum on 1D translation, only $n + 1$ coefficients are needed to reconstruct the input up to translation, and thus define a complete description of the signal structure in the quotient space [25]. The reconstruction algorithm proposed in [25] requires that the signal has no Fourier coefficients equal to zero. More robust reconstruction algorithms, such as least squares approaches, use more elements of the bispectrum matrix [14] for stability purposes.

APPENDIX H   DATASETS

H.1   VAN HATEREN NATURAL IMAGES

A data sample is a function $x : M \to \mathbb{R}$ sampled at m regular intervals over an input manifold M. Given a set of c "exemplars" $\{x^{(1)}, ..., x^{(c)}\}$ and a group G acting on M with actions T_g, the orbit of each datapoint is $O_i = \{x^{(i)}(T_g m) \mid g \in G\}$. The dataset is the union of all c orbits, with each orbit defining an equivalence class that is assigned an integer label y_i. The final samples are reshaped into a column vector in $\mathbb{R}^m$.

We use natural image patches from the Van Hateren database [40] as the data on which the groups act, and generate two datasets, each using a different group action: Cyclic 2D Translation ($S^1 \times S^1$) and 2D Rotation $SO(2)$. For each group, we randomly select 100 image patches as the "exemplars" on which the group acts. Each image patch is augmented by each element of the group to generate the orbit of the image under the transformation. The group $S^1 \times S^1$ is discretized into integer translations, and all 256 possible discrete translations are used to generate the data. The group $SO(2)$ is discretized into 360 integer degree rotations and 30% of these rotations are randomly drawn for each image to generate its orbit. Following orbit generation, image patches are normalized to have zero mean and unit standard deviation. For the 2D rotation dataset, patterns are cropped to a circle with diameter equal to the side length of the image, with values outside of the circle set to zero, to maintain perfect rotational symmetry. Appendix H shows examples from the dataset. A random 20% of each dataset is set aside for model validation and is used to tune hyperparameters. The remaining 80% is used for training.

Figure 10: Examples from the Cyclic 2D Translation and 2D Rotation Datsets. Image patches are randomly sampled from the Van Hateren natural image database [15]. The orbit of each patch under 2D translation (Left) and rotation (Right) are generated.

H.2 ROTATED MNIST

The Rotated MNIST dataset is generated by rotating each digit in the MNIST [27] training and test datasets by a random angle. This results in a training and test sets with the standard sizes of $60,000$ and $10,000$. A random 10% of the training dataset is set aside for model validation and is used to tune hyperparameters. The remaining 90% is used for training. Images are additionally downsized with interpolation to 16×16 pixels.

Figure 11: Examples from the Rotated MNIST Dataset.

APPENDIX I   TRAINING PROCEDURES

All networks were implemented and trained in PyTorch [33]. We additionally made use of the open-source CplxModule library [30], which provides implementations of the various complex-valued operations and initializations used in this work.

I.1   LEARNING IRREDUCIBLE REPRESENTATIONS

The weight matrix W is a square complex-valued matrix of dimension 256×256, matching the dimension of the (raveled) $(16, 16)$ image patches in the dataset. Weights were initialized using the complex orthogonal weight initialization method proposed in [38]. Each parameter vector in W was normalized to unit length after every gradient step. We used a batch sampler from the Pytorch Metric Learning library [29] to load batches with M random examples per class, with $M = 10$ and a batch size of 100. Networks were trained with the Adam optimizer [24] until convergence, using an initial learning rate of 0.002 and a cyclic learning rate scheduler [36], with 0.0001 and 0.005 as the lower and upper bounds, respectively, of the cycle.

I.2   GROUP-INVARIANT CLASSIFICATION

The images in the Rotated MNIST dataset were down-scaled with interpolation to 16×16 pixels to match the trained model size. The dataset is passed through the Bispectral Network to yield a rotation-invariant representation of the images. The complex-valued output vector is reduced to 500 dimensions with PCA. The real and imaginary components of the output vectors are then horizontally concatenated before being passed to the classifier network.

The classifier model consists of a four-layer feedforward network with hidden layer dimension [128, 128, 64, 32], ReLU activation functions between each hidden layer and a softmax activation at the output that generates a distribution over the 10 digit classes. The MLP is trained with the cross-entropy loss on the labeled digits using the Adam optimizer with an initial learning rate of 0.002, which is reduced by a factor of 0.95 when the validation loss plateaus for 30 epochs, until a minimum learning rate of 0.00005 is reached. Weights in the network are initialized using the Kaiming initialization [16] and biases are initialized to zero. The network is trained until convergence at 1500 epochs.

The baseline Linear SVM model is trained with the L2-penalty, a squared-hinge loss, and a regularization parameter of 1.0.

I.3   ADVERSARIAL ROBUSTNESS

A target sample is randomly drawn from the MNIST dataset. We initialize $N = 100$ standard normal random vectors in $\mathbb{R}^m$, $\{x_*^{(0)}, x_*^{(1)}, ..., x_*^{(N)}\}$, which are used as the inputs to the trained models from 4.1. The target sample is fed through the network to get the target output $\bar{B}(x)$. The inputs are fed through the network to get the output $\bar{B}(x_*^{(i)})$. The vectors x_* are then optimize to minimize the following objective with respect to the $x_*^{(i)}$:

$$L = \sum_{i=0}^{N} ||\bar{B}(x) - \bar{B}(x_*^{(i)})||_2 \tag{20}$$

The inputs are optimized to convergence using the Adam optimizer. An initial learning rate of 0.1 is used for both models, which is reduced by 0.1 when the loss plateaus for 10 epochs.

APPENDIX J   LEARNING THE IRREDUCIBLE REPRESENTATIONS OF EACH GROUP

We show the model's learned weights W for each experiment: 2D Cyclic Translation and Planar Rotation. Each tile is the real part of one row of W reshaped into a 16×16 image.

Figure 12: Learned Filters. Real components of weights learned in the Bispectral Network trained on the van Hateren Natural Images dataset. (Left) the Cyclic 2D Translation dataset and (Right) the 2D Rotation dataset.

APPENDIX K   RECOVERING CAYLEY TABLES FROM IRREPS

Below we list the algorithms used to recover Cayley tables from a group's irreducible representations.

Algorithm 1 GETCAYLEYFROMIRREPS
Compute the Cayley table from the (unordered) irreducible representations of a commutative group.

> **procedure** GETCAYLEYFROMIRREPS(W)
>   **for** $i = 1, ..., n$ **do**
>   **for** $j = 1, ..., n$ **do**
> $\rho \leftarrow W_i \odot W_j$
> $k^* \leftarrow \underset{k}{\mathrm{argmax}} |\langle \rho, W_k \rangle|$
> $\hat{C}(i,j) \leftarrow k^*$
>   **end for**
>   **end for**
>   **return** $\hat{C}$
> **end procedure**

Algorithm 2 GETCAYLEYFROMGROUP
Compute the Cayley table of a group G.

> **procedure** GETCAYLEYFROMGROUP(G)
>   **for** $g_1 \in G$ **do**
>   **for** $g_2 \in G$ **do**
> $C(g_1, g_2) \leftarrow g_1 \cdot g_2$
>   **end for**
>   **end for**
>   **return** C
> **end procedure**

Algorithm 3 ISISOMORPHIC
Check whether the learned group and the provided group are isomorphic by checking equality of their Cayley tables under permutation of group elements.
Let S_n be the group of all permutations of n elements.

> **procedure** ISISOMORPHIC(G, W)
>   **for** $\pi \in S_n$ **do**
> $G_\pi \leftarrow \pi \circ G$ ▷ Permute the elements of G according to the permutation element π
> $C_\pi \leftarrow$ GETCAYLEYFROMGROUP(G_π)
> $\hat{C} \leftarrow$ GETCAYLEYFROMIRREPS(W)
>   **if** $C = \hat{C}$ **then**
>   **return** True
>   **end if**
>   **end for**
>   **return** False
> **end procedure**