FeLMi : Few shot Learning with hard Mixup

Aniket Roy
Johns Hopkins University
Baltimore, USA
aroy28@jhu.edu

Anshul Shah
Johns Hopkins University
Baltimore, USA
ashah95@jhu.edu

Ketul Shah
Johns Hopkins University
Baltimore, USA
kshah33@jhu.edu

Prithviraj Dhar
Reality Labs, Meta
Sunnyvale, USA
prithvirj95@fb.com

Anoop cherian
MERL
Cambridge, MA
cherian@merl.com

Rama Chellappa
Johns Hopkins University
Baltimore, USA
rchella4@jhu.edu

Abstract

Learning from few examples is a challenging computer vision task. Traditionally, meta-learning based methods have been used to solve this problem. However recent approaches show improvements by learning a feature extractor on the abundant base examples and transferring these to the fewer novel examples. However, the finetuning stage is often prone to overfitting due to the small size of the novel dataset. To this end, we propose **Fe**w shot **L**earning with hard **Mi**xup (**FeLMi**) using manifold mixup to synthetically generate samples which helps in mitigating the data scarcity issue. Different from naive mixup, our approach selects the hard mixup samples using an uncertainty based criteria. To the best of our knowledge, we are the first to use hard-mixup for few-shot learning problem. Our approach allows to better exploit the pseudo-labeled base examples through base-novel mixup and entropy based filtering. We evaluate our approach on common few-shot benchmarks, e.g., FC-100, CIFAR-FS, miniImageNet and tieredImageNet and obtain improvement in both 1-shot and 5-shot settings. Additionally, we experimented on cross-domain few-shot setting (miniImageNet -> CUB) and obtain significant improvements in both 1-shot and 5-shot settings. Code:https://github.com/aniket004/Felmi.git

1 Introduction

Supervised deep learning has revolutionized data-driven computer vision tasks, e.g., object detection, segmentation [5] etc. However, it is expensive to collect and annotate large amounts of data, especially in some fields like medical image diagnosis where one needs to rely on highly-trained experts for annotating data. Despite recent progress in learning from large data, learning robust models using few labeled examples still remains quite challenging. Few-shot learning (FSL) [31, 28, 33] deals with this problem, where there exists base classes with plenty of training examples, and novel classes with few training samples. The goal is to learn a representation from the base classes, then quickly and efficiently adapt to the novel classes from few examples.

There are two paradigms for training few-shot learner - (1) episodic training and (2) transfer learning based approach. During episodic training, in each episode, a few examples from the training data are sampled to form the "support set", on which training is performed and evaluated on the "query set" drawn from the test dataset. Generally, the model is trained for a large number of episodes to get better generalization. However, this approach is both time consuming and also incurs inductive (prior knowledge driven bias) and sampling bias. On the other hand, recent approaches use simple transfer learning to the novel classes and obtained comparative or even better performance. Tian et al. [31]

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

show that pretraining on the large scale base dataset to learn a good representation, followed by finetuning on the few novel class examples using a simple linear classifier significantly outperforms the more complicated meta-learning approaches in most of the FSL benchmarks. The performance is further boosted using self-distillation and distillation across base and novel class representations [21].

Data scarcity is a fundamental issue in few-shot learning problem. To mitigate that, AssoAlign [1] has proposed to use the nearest neighbor base examples in addition to the novel examples with adversarial augmentation. Jian et al. [11] generates pseudolabels for the base class samples and retrain on the entire dataset by "hallucinating" the labels of the base class samples. However, literature in semi-supervised learning has shown that poorly labeled psedolabeled samples hurt performance [21].

We overcome issues in these prior approaches by entropy filtering the noisy pseudolabels. This step helps improve the training by discarding noisy pseudolabeled base samples during training. Next, we propose a solution to the data scarcity issue by synthetically generating training examples with both the novel and base examples using mixup. These mixup samples are generated with minimal overhead while adding the much needed regularization by synthesizing new points close to the novel distribution. Motivated by the efficacy of hard example mining in computer vision [26], we propose to improve naive mixup with uncertainty guided hard-mixup. Further, we propose a technique to make use of base samples for mixup in addition to the novel samples. Note that Mangla et. al [16] has also used Mixup for few-shot learning, but the motivation is completely different in our setting. [16] used Mixup as a regularizer across layers, therefore, not adding any more samples for training. To the contrary, we are the first to propose generating hard mixup samples to tackle the data scarcity issue in FSL.

Another contribution of our work is that we redefine hard-mixup for few-shot learning setup. Note that hard-mixup has been used in contrastive learning, where positive and negative classes are already defined [12]. In contrast, for N-way K-shot problem, where there exists N classes where the notion of hard examples is not straight forward. While hard mixup similar to these approaches could be extended in our setup by mixing and assigning a hard label, we instead work with soft labels and figure out the optimal examples to mix and the right lambda. To this end, we define hard example mixing based on margin based uncertainty measure, inspired from active learning. We use margin to select hardness of a sample which measures uncertainty in predicting a particular class with high probability.

In summary, the contributions in this work are as follows:

1. To handle the data scarcity problem in few-shot learning, we use mixup-based data augmentation to improve the performance.

2. We perform hard mixup based on margin based uncertainty measure, which further elevates performance. To the best of our knowledge, we are the first to use hard-mixup for few-shot learning.

3. We propose a way to make use of both base and novel examples for generating more samples for novel training.

4. We validate our approach using extensive experimentation of standard few-shot benchmarks, e.g., FC100, CIFAR-FS, miniImageNet and tieredImageNet. Experiments on cross-domain benchmark (miniImageNet -> CUB) also provide significant improvements.

2   Related Work

Few-shot learning methods can be divided into two broad categories, (1) Meta-learning, (2) Transfer learning based methods.

Meta Learning Traditionally meta-learning based methods have been effective for few-shot learning setting, which consists of meta-training and meta-testing phase. In each of the meta-training and testing phase, multiple episodes are sampled from a task distribution and the model is trained on the support samples of the episode and evaluated on the query set. Thus the model is trained on unseen classes by learning to learn. Meta-learning methods can also be subdivided into two categories, i.e., metric-based meta learning and optimization based meta-learning.

Metric based meta-learning methods predicts the label of the query as a weighted sum of the labels over the support samples. Popular metric based meta-learning methods include Prototypical

Networks [28], Relation Network [30], Matching network [33], TADAM [17] etc. Optimization based meta-learning methods try to adapt to the model parameters using small numbers of gradient steps, e.g., MAML [9], LEO [23] etc. MetaOptNet [19] uses a differentiable convex optimization problem for few-shot learning problem with better generalization. There are other meta-learning based methods using earth-mover's distance [38], set-to-set functions [35], human interpretable concepts [5] etc.

Transfer learning based methods Recent methods have shown that contrastive pretraining on large base example dataset and simple finetuning on the scarce novel examples performs surprisingly better than the complex meta learning based methods. E.g., RFS [31] outperforms all the meta learning baselines by learning a self-supervised representation followed by simple logistic classifier. Following the similar trend, SKD [18] uses rotational self-supervised distillation to further improve the performance. Rizve et al. [22] explored complementary strength of invariant and equivariant representation and self distillation for better pretraining and performed significantly better than previous methods. Partner assisted learning [15], which also uses feature level knowledge distillation has also been proven to be effective.

Base examples for few-shot learning AssoAlign [1] makes use of large base dataset by searching nearest neighbors of the novel examples in the pool of base examples along with adversarial associative alignmentment. Pseudolabeling is a well-known technique for semi-supervised learning and successfully used in several vision tasks, e.g., image and video classification [21]. Jian et al. [11] used pseudolabeling of the entire base examples and obtained significant performance boost. Afrasiyabi et al. [2] also used mixture based feature space learning [2] and matching feature sets [3] to further improve the performance.

Mixup Mixup is a simple yet effective regularization technique for training deep networks. Several variants of mixup have been proposed in the literature, viz., input mixup [39], cutmix [37], manifold-mixup [32] etc. Manifold mixup uses feature level mixup, which provides smoother decision boundary and flattened class representations. Mangla et al. [16] used manifold mixup for few-shot learning from a regularization perspective. However, instead we are using manifold mixup to tackle the data scarcity problem in few-shot learning by generating more samples.

3   Problem Statement

We first define the few-shot classification problem addressed in this work. Typically, there exists a large scale labeled base dataset and comparatively less number of novel classes with few samples per class. The task is to learn a feature representation on the base class with abundant samples and then discriminatively learn a representation to recognize subsequent novel classes. Let the base dataset be denoted as $\mathcal{D}^{\texttt{base}} = \{x_t^{\texttt{base}}, y_t^{\texttt{base}}\}_{t=1}^{N^{\texttt{base}}}$, where $x_t^{\texttt{base}}$ is the base class sample and the corresponding label is $y_t^{\texttt{base}} \in C^{\texttt{base}}$. Similarly, the novel dataset is denoted by $\mathcal{D}^{\texttt{novel}} = \{x_t^{\texttt{novel}}, y_t^{\texttt{novel}}\}_{t=1}^{N^{\texttt{novel}}}$, where $x_t^{\texttt{novel}}$ is the novel class sample and the corresponding label is $y_t^{\texttt{novel}} \in C^{\texttt{novel}}$. The base and novel classes are disjoint, i.e., $C^{\texttt{base}} \cap C^{\texttt{novel}} = \emptyset$, and $|C^{\texttt{base}}| \geq |C^{\texttt{novel}}|$.

The training and testing is performed in episodes on the novel class samples. In each episode i of a N-way K-shot problem, the few-shot learner is trained on a support set, i.e., $\mathcal{D}_i^{\texttt{support}} = \{x_{i,t}^{\texttt{support}}, y_{i,t}^{\texttt{support}}\}_{t=1}^{NK}$ for N novel classes containing K samples per class. Then the few-shot learner is evaluated on the query set $\mathcal{D}_i^{\texttt{query}} = \{x_{i,t}^{\texttt{query}}, y_{i,t}^{\texttt{query}}\}_{t=1}^{N'K}$ on the same N classes of $D_i^{\texttt{support}}$.

4   Proposed Methodology

Inspired by the efficacy of pseudolabeling, we further increase sample size by mixup and choose more informative samples by hard mixup based sample selection. Our proposed method which is outlined in Fig. 1 consists of six stages as follows: 1. Learning embedding on the base dataset ($\mathcal{D}^{\texttt{base}}$). 2. Pseudo labeling of base dataset. 3. Entropy based filtering of base dataset. 4. Mixup sample generation using both base and novel examples. 5. Uncertainty based hard-mixup sample selection. 6. Finetune on the entire dataset using base example, novel example and hard-mixed examples.

The detailed methodology is discussed as follows:

Figure 1: Our proposed method, FeLMi consists of six stages. Stage (1): backbone (f_θ) is pretrained on the base dataset B. Stage (2): pseudolabels ($\hat{y}_t^{base}$) of the entire base dataset is generated using classifier g_ϕ. Stage (3): base samples are filtered based on entropy to obtain reduced dataset B'. Stage (4): novel-novel (x_{mix}^{N-N}) and base-novel (x_{mix}^{B-N}) mixup samples are generated. Stage (5): hard examples (x_t^{hard}) are selected based on margin. Stage (6): finally, the model is trained on the combination of losses.

4.1 Learning embedding on the base dataset

We first learn a discriminative representation from the base dataset D^{base}. The convolutional neural network consists of a backbone f_θ and a final classification layer h_ϕ and the parameters (θ, ϕ) are jointly learned using cross-entropy loss on the base dataset D^{base}. We use the self-supervised Invariant and Equivariant Represenatation learning (IER) framework by Rizve et al. [22] framework which makes use of self-supervised losses in addition to standard cross-entropy loss to learn good representations.

$$(\theta^{base}, \phi^{base}) = \text{argmin}_{\theta,\phi} \mathbb{E}_{\{x,y\} \in D^{base}} L_{CE}(h_\phi(f_\theta(x)), y) \tag{1}$$

Large size of base dataset ensures that we have a good pretrained model to use for meta-testing stage.

4.2 Pseudo labeling of base dataset using classifier trained on novel dataset

In this step, we train a linear logistic regression classifier using the novel examples. Then using the trained classifier we generate the pseudolabels of the entire base dataset as performed by Jian et al. [11]. This pseudolabeling step partially mitigate the data scarcity problem prevalent in few-shot learner training. For each episode i, we learn a linear classifier ϕ_i using the support set novel examples $D_i^{support}$, such that

$$\phi_i = \text{argmin}_\phi \mathbb{E}_{\{x,y\} \in D_i^{support}} L_{CE}(g_\phi(f_{\theta^{base}}(x)), y) \tag{2}$$

Then the classifier g_{ϕ_i} is used to generate pseudolabels for the entire base dataset, i.e., $\hat{y}_t^{base} = g_{\phi_i}(f_{\theta^{base}}(x_t))$ for $t = 1, .., N^{base}$.

4.3 Entropy based Pseudolabel filtering

Given that base classes are disjoint from novel classes, not all classes will provide information useful for the task at hand. Specifically, base samples with high entropy pseudolabels might lead to

confusing samples. Therefore, we perform a simple pseudolabel filtering based on entropy.

$$\mathcal{Y}^{\texttt{filt}} = \{\hat{y}_t^{\texttt{base}} | H(\hat{y}_t^{\texttt{base}}) \leq \tau \text{ where } t = 1, \cdots, N^{\texttt{base}}\} \tag{3}$$

We empirically select the entropy threshold τ. After refinement we have $|\mathcal{Y}^{\texttt{filt}}|$ base examples. $H(.)$ here denotes the entropy. We call these filtered pseudolabeled base sample set be $\mathcal{D}^{\texttt{base\_filt}}$

4.4 Mixup sample generation

Handling the data scarcity problem using pseudolabels motivate us to generate even more samples using simple yet effective mixup strategy. Particularly, we are using feature level manifold mixup to generate more synthetic samples. Since we have both the base and novel examples, we have the freedom of mixing up both base-novel and novel-novel pairs. Note that, since the mixed samples should be close to novel examples, we are only performing novel-novel and base-novel mixup. A straightforward way of generating synthetic examples through mixup is to mix two *pure* novel examples. We call this strategy 'Novel-Novel' mixup.

4.4.1 Novel-Novel Mixup

We perform manifold mixup on novel-novel samples to create a pool of mixed up samples $P_{N,N}$. We select $\{(x^{\texttt{novel}}, y^{\texttt{novel}}), (\bar{x}^{\texttt{novel}}, \bar{y}^{\texttt{novel}})\} \in D^{\texttt{support}}$, pass through the feature extractor $f_{\theta^{\texttt{base}}}$ and mixup with $\lambda_n \sim \text{Beta}(\alpha, \alpha)$ to generate (x_{mix}, y_{mix}) such that,

$$x_{mix}^{N-N} = \lambda_n . f_{\theta^{\texttt{base}}}(x^{\texttt{novel}}) + (1 - \lambda_n) f_{\theta^{\texttt{base}}}(\bar{x}^{\texttt{novel}})$$
$$y_{mix}^{N-N} = \lambda_n . y^{\texttt{novel}} + (1 - \lambda_n) \bar{y}^{\texttt{novel}} \tag{4}$$

The pool of novel-novel mixup samples of size l are generated through randomly sampling λ_n, i.e., $P_{N,N} = \{(x_{mix}^{N-N}, y_{mix}^{N-N})_i\}_{i=1}^{l}$.

4.4.2 Base-Novel Mixup

Access to the base examples during training and their pseudolabels allows us to make use of these for mixup. The motivation behind using mixup is to generate and augment the small novel set. Since the base classes are disjoint from novel classes and we have a weak mapping only through the pseudo-labels we employ the following tricks while using base examples with mixup. 1) We refrain from mixing two base examples, always mixing a base example with a novel example. 2) We only mix with base examples that are close to novel examples. We ensure this by choosing base examples which have a low pseudo-label entropy. 3) We choose a small mixup lambda corresponding to the base examples when mixing them which ensures that we do not stray too far away from the novel distribution. Specifically, we sample $\lambda_b \sim \text{Uniform}(0, 0.2)$. For example, from $(x^{\texttt{base}}, \hat{y}^{\texttt{base}}) \in D^{\texttt{base}}$, we select k-lowest entropy base examples, i.e., $(x_{sel}^{\texttt{base}}, \hat{y}_{sel}^{\texttt{base}})$, such that,

$$(x_{sel}^{\texttt{base}}, \hat{y}_{sel}^{\texttt{base}}) = \{(x_i, y_i) | i \in \texttt{bottom\_k}(H(\hat{y}))\} \tag{5}$$

Novel examples are $(x^{\texttt{novel}}, y^{\texttt{novel}}) \in D^{\texttt{support}}$ mixed with these selected base examples to generate $(x_{mix}^{B-N}, y_{mix}^{B-N})$ as follows.

$$x_{mix}^{B-N} = \lambda_b . f_{\theta^{\texttt{base}}}(x_{sel}^{\texttt{base}}) + (1 - \lambda_b) f_{\theta^{\texttt{base}}}(x^{\texttt{novel}})$$
$$y_{mix}^{B-N} = \lambda_b . \hat{y}_{sel}^{\texttt{base}} + (1 - \lambda_b) y^{\texttt{novel}} \tag{6}$$

The pool of base-novel mixup samples of size l are generated through randomly sampling λ_b, i.e., $P_{B,N} = \{(x_{mix}^{B-N}, y_{mix}^{B-N})_i\}_{i=1}^{l}$

4.5 Hard mixup sample generation

In the section above, we have generated a pool of base-novel and novel-novel mixed up samples denoted by $P_{B,N}$ and $P_{N,N}$ respectively. Now, we concatenate those to generate a larger pool of mixed-up samples, i.e., $P_{mix} = P_{B,N} \cup P_{N,N}$ and then choose hardest N samples based on a uncertainty measure. To the best of our knowledge, we are the first to use hard-mixup for few-shot learning problem.

More specifically, to get an estimate of hardness of a mixed example chosen from P_{mix}, we first obtain a (potentially noisy) estimate of the class probability p ($= g_{\phi_i}(x)$) using the classifier trained in step(2). We then estimate margin (difference in top-2 probabilities), a measure of uncertainty that is commonly used in Active learning [24] and pick mixed samples which have a low margin. Intuitively, samples with a lower margin lie close to the class boundary thus providing a stronger learning signal.

We choose k-smallest margin values as hard examples (denoted as P_{hard_mix}) chosen from both the base and novel mixed up samples are as follows.

$$\mathcal{P}_{hard\_mix} = \texttt{bottom\_k}\{\texttt{margin}(g_{\phi_i}(f_{\theta^{\texttt{base}}}(x)) \,|\, (x,y) \in P_{mix}\} \tag{7}$$

4.6 Finetune on the entire dataset

In the last stage, the model is finetuned on combined loss computed using the filtered base examples ($\mathcal{D}^{\texttt{base\_filt}}$), the novel examples ($\mathcal{D}^{\texttt{novel}}$) and the hard mixup samples ($\mathcal{P}_{\texttt{hard\_mix}}$). For the base examples, KL divergence loss is used, whereas Cross-entropy loss has been used for novel and mixup samples. The final loss is denoted as,

$$\begin{aligned}
\mathcal{L} = \,& \mathbb{E}_{\{x,\hat{y}\} \in \mathcal{D}^{\texttt{base\_filt}}} L_{KD}(g_\phi(f_\theta(x)), \hat{y}) \\
& + \beta \mathbb{E}_{\{x,y\} \in \mathcal{D}^{\texttt{novel}}} L_{CE}(g_\phi(f_\theta(x)), y) + \gamma \mathbb{E}_{\{x,y\} \in \mathcal{P}_{\texttt{hard\_mix}}} L_{CE}(g_\phi(f_\theta(x)), y)
\end{aligned} \tag{8}$$

β and γ are scaling parameters for losses corresponding to novel and mixed up samples respectively.

Finally, the trained model is evaluated on the query set of the episode i ($D_i^{\texttt{query}}$) and averaged accuracy over all the episodes are reported.

5 Experimental Results

5.1 Experimental Setup

Datasets: We experiment on four widely used few-shot benchmarks: FC-100 [17], CIFAR-FS [4] and miniImageNet [33] and tieredImageNet [20]. FC-100 is a subset of CIFAR-100, containing 60 classes for meta-training, 20 classes for meta-validation and 20 classes for meta-testing. CIFAR-FS is also obtained from CIFAR-100, containing 64 classes for meta-training, 16 classes for meta-validation and 20 classes for meta-testing. miniImageNet is derived from ImageNet with images downsampled to a resolution of 84×84 pixels. It has 64 classes for meta-training, 16 classes for meta-validation and 20 classes for meta-testing. tieredImageNet [20] is also another subset of ImageNet, containing total of 608 classes, from which 351 classes used for meta-training, 97 classes for meta-validation and 160 classes for meta-testing.

Implementation details: For fair comparison, we have used the ResNet-12 architecture as the backbone network. On top of that, we train a two layer MLP, which outputs N-way logits. We used SGD optimizer with momentum 0.9, learning rate of backbone and classifier be 0.025 and 0.05 respectively with weight decay of 5e-4. Following [11], we use the temperature coefficient as of 4.0 for our KD loss. We use a minibatch size of 250 for training. Using standard setting, we also perform data augmentation using color jittering, random crop and horizontal flip. Further details of the network architecture and training will be provided in the supplementary material.

5.2 Results on benchmark datasets

We have compared our proposed method (FeLMi) with state-of-the-art techniques on the benchmark datasets: FC-100, CIFAR-FS, miniImageNet and tieredImageNet. We show consistent improvements against state-of-the-art showing efficacy of our approach on the all the aforementioned fewshot benchmarks across both the 1-shot and 5-shot settings in Table 1, Table 2 and Table 3.

5.3 Results on cross-domain benchmark

We tested our approach for more challenging cross-domain setting, where the base-pretraining is done on miniImageNet and the novel class stems from samples from another domain, e.g., CUB [34]. Our approach achieves significant performance improvements for both the 5-shot and 1-shot setting in this setting as shown in Table 4.

Table 1: Comparison of FeLMi (ours) to prior works on CIFAR-FS. Following prior work, we report our results with 95% confidence intervals on meta-testing split of the dataset. § denotes our reproduced numbers using publicly available implementations.

| model | backbone | CIFAR-FS 5-way | |
		1-shot	5-shot
ProtoNet [28] (NIPS'17)	ResNet-12	72.2 ± 0.7	83.5 ± 0.5
MetaOptNet [13] (CVPR'19)	ResNet-12	72.6 ± 0.7	84.3 ± 0.5
Shot-Free [19] (ICCV'19)	ResNet-12	$69.2 \pm$ n/a	$84.7 \pm$ n/a
DSN-MR [27] (CVPR'20)	ResNet-12	75.6 ± 0.9	86.2 ± 0.6
RFS-simple [31] (ECCV'20)	ResNet-12	71.5 ± 0.8	86.0 ± 0.5
RFS-distill [31] (ECCV'20)	ResNet-12	73.9 ± 0.8	86.9 ± 0.5
SKD-GEN1 [18] (Arxiv'20)	ResNet-12	76.6 ± 0.9	88.6 ± 0.5
IER-distill [22] (CVPR'21)	ResNet-12	77.6 ± 1.0	89.7 ± 0.6
PAL [15] (ICCV'21)	ResNet-12	77.1 ± 0.7	88.0 ± 0.5
Label-Halluc [11] (AAAI'22)	ResNet-12	78.0 ± 1.0[§]	89.37 ± 0.6[§]
FeLMi	ResNet-12	$\mathbf{78.22 \pm 0.7}$	$\mathbf{89.47 \pm 0.5}$

Table 2: Comparison of FeLMi (ours) to prior works on FC-100. Following prior work, we report our results with 95% confidence intervals on meta-testing split of the dataset. § denotes our reproduced numbers using publicly available implementations.

| model | backbone | FC-100 5-way | |
		1-shot	5-shot
ProtoNet [28] (NIPS'17)	ResNet-12	37.5 ± 0.6	52.5 ± 0.6
TADAM [17] (NIPS'18)	ResNet-12	40.1 ± 0.4	56.1 ± 0.4
MetaOptNet [13] (CVPR'19)	ResNet-12	41.1 ± 0.6	55.5 ± 0.6
MTL [29] (CVPR'19)	ResNet-12	45.1 ± 1.8	57.6 ± 0.9
DeepEMD [38] (CVPR'20)	ResNet-12	46.5 ± 0.8	63.2 ± 0.7
RFS-simple [31] (ECCV'20)	ResNet-12	42.6 ± 0.7	59.1 ± 0.6
RFS-distill [31] (ECCV'20)	ResNet-12	44.6 ± 0.7	60.9 ± 0.6
AssoAlign [1] (ECCV'20)	ResNet-18	45.8 ± 0.5	59.7 ± 0.6
SKD-GEN1 [18] (Arxiv'20)	ResNet-12	46.5 ± 0.8	64.2 ± 0.8
InfoPatch [10] (AAAI'21)	ResNet-12	43.8 ± 0.4	58.0 ± 0.4
IER-distill [22] (CVPR'21)	ResNet-12	48.1 ± 0.8	65.0 ± 0.7
PAL [15] (ICCV'21)	ResNet-12	47.2 ± 0.6	64.0 ± 0.6
Label-Halluc [11] (AAAI'22)	ResNet-12	47.37 ± 0.7[§]	67.92 ± 0.7[§]
FeLMi	ResNet-12	$\mathbf{49.02 \pm 0.7}$	$\mathbf{68.68 \pm 0.7}$

(a) FC-100   (b) CIFAR-FS   (c) mini-ImageNet

Figure 2: Effect of changing number of mixup samples (N). In this experiment we investigate the effect of N on the final cumulative accuracy for the 5-way 1-shot on the three datasets. We notice that N=1000 shows consistent improvements across all datasets.

Table 3: Comparison of our method (FeLMi) against the state-of-the-art on miniImageNet. Following prior work, we report our results with 95% confidence intervals on meta-testing split of the dataset. § denotes our reproduced numbers using publicly available implementations.

model	backbone	miniImageNet 5-way		tieredImageNet 5-way	
		1-shot	5-shot	1-shot	5-shot
ProtoNet [28] (NIPS'17)	ResNet-12	60.37 ± 0.83	78.02 ± 0.57	65.65 ± 0.92	83.40 ± 0.65
TADAM [17] (NIPS'18)	ResNet-12	58.50 ± 0.30	76.70 ± 0.30	-	-
TapNet [36] (ICML'19)	ResNet-12	61.65 ± 0.15	76.36 ± 0.10	63.08 ± 0.15	80.26 ± 0.12
MetaOptNet [13] (CVPR'19)	ResNet-12	62.64 ± 0.61	78.63 ± 0.46	65.99 ± 0.72	81.56 ± 0.53
MTL [29] (CVPR'19)	ResNet-12	61.20 ± 1.80	75.50 ± 0.80	65.62 ± 1.80	80.61 ± 0.90
Shot-Free [19] (ICCV'19)	ResNet-12	59.04 ± 0.43	77.64 ± 0.39	66.87 ± 0.43	82.64 ± 0.43
DSN-MR [27] (CVPR'20)	ResNet-12	64.60 ± 0.72	79.51 ± 0.50	67.39 ± 0.83	82.85 ± 0.56
DeepEMD [38] (CVPR'20)	ResNet-12	65.91 ± 0.82	82.41 ± 0.56	71.16 ± 0.87	86.03 ± 0.58
FEAT [35] (CVPR'20)	ResNet-12	66.78 ± 0.20	82.05 ± 0.14	70.80 ± 0.23	84.79 ± 0.16
Neg-Cosine [14] (ECCV'20)	ResNet-12	63.85 ± 0.81	81.57 ± 0.56	-	-
RFS-simple [31] (ECCV'20)	ResNet-12	62.02 ± 0.63	79.64 ± 0.44	69.74 ± 0.72	84.41 ± 0.55
RFS-distill [31] (ECCV'20)	ResNet-12	64.82 ± 0.82	82.41 ± 0.43	71.52 ± 0.69	86.03 ± 0.49
AssoAlign [1] (ECCV'20)	ResNet-18	59.88 ± 0.67	80.35 ± 0.73	69.29 ± 0.56	85.97 ± 0.49
AssoAlign [1] (ECCV'20)	WRN-28-10	65.92 ± 0.60	82.85 ± 0.55	-	-
SKD-GEN1 [18] (Arxiv'20)	ResNet-12	66.54 ± 0.97	83.18 ± 0.54	74.40 ± 0.68	86.61 ± 0.59
P-Transfer [25] (AAAI'21)	ResNet-12	64.21 ± 0.77	80.38 ± 0.59	-	-
MELR [8] (ICLR'21)	ResNet-12	67.40 ± 0.43	83.40 ± 0.28	-	-
IEPT [40] (ICLR'21)	ResNet-12	67.05 ± 0.44	82.90 ± 0.30	72.24 ± 0.50	86.73 ± 0.34
IER-distill [22] (CVPR'21)	ResNet-12	66.85 ± 0.76	84.50 ± 0.53	72.71 ± 0.89	86.57 ± 0.81
Label-Halluc [11](AAAI'22)	ResNet-12	$67.04 \pm 0.7^{\S}$	$85.87 \pm 0.48^{\S}$	71.97 ± 0.89	86.80 ± 0.58
FeLMi	ResNet-12	$\mathbf{67.47 \pm 0.78}$	$\mathbf{86.08 \pm 0.44}$	71.63 ± 0.89	$\mathbf{87.07 \pm 0.55}$

Table 4: Comparison of FeLMi (ours) in cross-domain setting (miniImageNet -> CUB)

model	backbone	miniImageNet -> CUB 5-way	
		1-shot	5-shot
Baseline++ [6] (ICLR'19)	ResNet-18	40.44 ± 0.75	56.64 ± 0.72
MetaOptNet [13] (CVPR'19)	ResNet-18	44.79 ± 0.75	64.98 ± 0.68
S2M2R [16] (WACV'20)	ResNet-18	48.24 ± 0.84	70.44 ± 0.75
AssoAlign [1] (ECCV'20)	ResNet-18	47.25 ± 0.76	72.37 ± 0.89
MixFSL [2] (ICCV'21)	ResNet-18	-	68.77 ± 0.9
MT-ConFT [7] (ICCV'21)	ResNet-10	49.25 ± 0.83	74.45 ± 0.71
FeLMi	ResNet-12	$\mathbf{51.66 \pm 0.82}$	$\mathbf{77.61 \pm 0.69}$

(a) FC-100   (b) CIFAR-FS   (c) mini-ImageNet

Figure 3: Effect of changing number of α parameter of the Beta distribution. In this experiment we investigate the effect of α on the final cumulative accuracy for the 5-way 1-shot on the three datasets. Note that α effectively controls the λ values that we sample for N-N mixup. A value of 1 implies sampling from a uniform distribution whereas 0.5 samples λ closer to 0 or 1. We notice that $\alpha = 1$ shows consistent improvements across all datasets.

5.4 Ablation and Analyses

Ablation of each individual contribution: In this section, we investigate the effect on each stage on the overall performance. We start with the base pretraining following IER [22] and following

Table 5: Contribution of our proposed techniques to the final performance on FC-100 for 5-way 5-shot classification. We see that each of our proposed techniques leads to an improvement.

Approach	Accuracy
IER [22]	65.00
+ Pseudolabel [11]	67.92
+ entropy filtering	67.96
+ Mixup	68.49
+ hard selection	68.68

Table 6: Evaluating different mixup strategies for 5-way 5-shot classification. Our proposed approach of using N-N mixup improves performance. Additionally using B-N mixup leads to further gains.

Mixup Approach	λ_b	λ_n	FC-100	CIFAR-FS
B-N + N-N	$U(0,0.2)$	$B(1,1)$	68.68	89.47
B-N + N-N	$B(1,1)$	$B(1,1)$	68.49	89.26
N-N	-	$B(1,1)$	68.57	89.4
None	-	-	67.92	89.37

(a) First training step

(b) Last training step

Figure 4: tSNE visualizations. We visualize the tSNE plots of the learned representations at the start of training and at the end for one random episode. We see that as training progresses, the data gets more clustered and query labels (denoted by y_Q) get close to the support set clusters. We also overlay the generated mixup samples. These samples offer a good training signal to learn better class boundaries.

Jian et al. [11] method of pseudolabeling the entire base dataset. Entropy based filtering of the pseudolabels provides an improvement of 0.04%. Using both base and novel sample mixup, we get an improvement of 0.53%. Margin-based hard mixup sample selection additionally provide a performance boost of 0.19% on FC-100 dataset in 5-way 5-shot setting as shown in Table. 5.

Effect of mixup strategies: In this section, we evaluate different mixup strategies, as shown in Tab. 6 on both FC-100 and CIFAR-FS in 5-way 5-shot settings. In both the cases, we observe that best results are obtained when incorporating base-novel mixup with $\lambda_b \sim$ Uniform(0,0.2) in addition to novel-novel mixup with $\lambda_n \sim$ Beta(1,1). This aforementioned setting ensures the mixed up base-novel samples (denoted by yellow points in Fig. 4 (a)) lie close to the novel examples (labeled 0-4 in the Fig. 4 (a)).

Effect of mixup sample size: We observe the variation of 5-way 5-shot classification accuracy vs number of mixup sample size for FC-100, CIFAR-FS and miniImageNet in Fig. 2a, Fig. 2b and Fig. 2c respectively. We notice that in all the settings, mixup sample size of 1000 performs the best. Increasing the number of mixed up samples seems to hurt the performance a bit. We hypothesize this might be due to the increasing imbalance between 'real' and 'generated' points thus hurting the optimization.

Effect of mixup parameters: The variation of 5-way 5-shot classification accuracy with respect to mixup parameter α for FC-100, CIFAR-FS and miniImageNet used for performing novel-novel sample mixup is shown in Fig. 3 . In CIFAR-FS and miniImageNet, $\alpha = 0.5$ seems to perform better. However, in FC-100, we observe the opposite trend.

tSNE visualizations: Next, we analyse the tSNE visualizations of the representations learned using our approach. The visualizations (Figure 4) show these for representations at the first step of training and after the training is completed for one episode. We observe that the representations for each class

get more clustered as the training progresses. Further, representations of the query samples get closer to the corresponding class support samples. Our generated hard mixup samples are close to the query samples as seen in the figure, which provide the necessary training signal to improve the model.

6 Limitations

Like most prior approaches, we make use of the base examples when adapting the classifier for novel examples. This requires storing of the base example features which can be difficult for very large scale datasets. We would like to fix this requirement in future work.

7 Conclusion

Few-shot learning is an important computer vision problem. The inherent data scarcity issue makes this problem more challenging. To address this issue, we propose to use hard mixup to synthetically generate mixup samples based on lowest margin based uncertainty measure. To the best of our knowledge, we are the first to propose hard mixup for few-shot learning. Moreover, we also performed hard mixup on the novel-novel and base-novel samples and further improve performance on the benchmark datasets, e.g., FC-100, CIFAR-FS, miniImageNet and tieredImageNet in both the 1-shot and 5-shot settings. Our approach also significantly outperform the state-of-the-art in cross-domain few-shot (miniImageNet -> CUB) settings.

8 Acknowledgement

The authors would like to thank ONR MURI grant N00014-20-1-2787 for funding the research.

References

[1] Arman Afrasiyabi, Jean-François Lalonde, and Christian Gagné. Associative alignment for few-shot image classification. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020.

[2] Arman Afrasiyabi, Jean-François Lalonde, and Christian Gagné. Mixture-based feature space learning for few-shot image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9041–9051, 2021.

[3] Arman Afrasiyabi, Hugo Larochelle, Jean-François Lalonde, and Christian Gagné. Matching feature sets for few-shot image classification. *arXiv preprint arXiv:2204.00949*, 2022.

[4] Luca Bertinetto, Joao F. Henriques, Philip Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. In *International Conference on Learning Representations*, 2019.

[5] Kaidi Cao, Maria Brbic, and Jure Leskovec. Concept learners for few-shot learning. In *International Conference on Learning Representations*, 2021.

[6] Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Frank Wang, and Jia-Bin Huang. A closer look at few-shot classification. *arXiv preprint arXiv:1904.04232*, 2019.

[7] Rajshekhar Das, Yu-Xiong Wang, and José MF Moura. On the importance of distractors for few-shot classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9030–9040, 2021.

[8] Nanyi Fei, Zhiwu Lu, Tao Xiang, and Songfang Huang. {MELR}: Meta-learning via modeling episode-level relationships for few-shot learning. In *International Conference on Learning Representations*, 2021.

[9] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 1126–1135, 2017.

[10] Yizhao Gao, Nanyi Fei, Guangzhen Liu, Zhiwu Lu, Tao Xiang, and Songfang Huang. Contrastive prototype learning with augmented embeddings for few-shot learning. *arXiv preprint arXiv:2101.09499*, 2021.

[11] Yiren Jian and Lorenzo Torresani. Label hallucination for few-shot classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2022.

[12] Yannis Kalantidis, Mert Bulent Sariyildiz, Noe Pion, Philippe Weinzaepfel, and Diane Larlus. Hard negative mixing for contrastive learning. *Advances in Neural Information Processing Systems*, 33:21798–21809, 2020.

[13] Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[14] Bin Liu, Yue Cao, Yutong Lin, Qi Li, Zheng Zhang, Mingsheng Long, and Han Hu. Negative margin matters: Understanding margin in few-shot classification. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm, editors, *Computer Vision – ECCV 2020*, 2020.

[15] Jiawei Ma, Hanchen Xie, Guangxing Han, Shih-Fu Chang, Aram Galstyan, and Wael Abd-Almageed. Partner-assisted learning for few-shot image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10573–10582, 2021.

[16] Puneet Mangla, Nupur Kumari, Abhishek Sinha, Mayank Singh, Balaji Krishnamurthy, and Vineeth N Balasubramanian. Charting the right manifold: Manifold mixup for few-shot learning. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2218–2227, 2020.

[17] Boris N. Oreshkin, Pau Rodríguez López, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. In *NeurIPS*, 2018.

[18] Jathushan Rajasegaran, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Mubarak Shah. Self-supervised knowledge distillation for few-shot learning. *arXiv preprint arXiv:2006.09785*, 2020.

[19] Avinash Ravichandran, Rahul Bhotika, and Stefano Soatto. Few-shot learning with embedded class models and shot-free meta training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019.

[20] Mengye Ren, Sachin Ravi, Eleni Triantafillou, Jake Snell, Kevin Swersky, Josh B. Tenenbaum, Hugo Larochelle, and Richard S. Zemel. Meta-learning for semi-supervised few-shot classification. In *International Conference on Learning Representations*, 2018.

[21] Mamshad Nayeem Rizve, Kevin Duarte, Yogesh S Rawat, and Mubarak Shah. In defense of pseudo-labeling: An uncertainty-aware pseudo-label selection framework for semi-supervised learning. *arXiv preprint arXiv:2101.06329*, 2021.

[22] Mamshad Nayeem Rizve, Salman Khan, Fahad Shahbaz Khan, and Mubarak Shah. Exploring complementary strengths of invariant and equivariant representations for few-shot learning. *arXiv preprint arXiv:2103.01315*, 2021.

[23] Andrei A. Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. In *International Conference on Learning Representations*, 2019.

[24] Burr Settles. Active learning literature survey. 2009.

[25] Zhiqiang Shen, Zechun Liu, Jie Qin, Marios Savvides, and Kwang-Ting Cheng. Partial is better than all: Revisiting fine-tuning strategy for few-shot learning. *CoRR*, abs/2102.03983, 2021.

[26] Abhinav Shrivastava, Abhinav Gupta, and Ross Girshick. Training region-based object detectors with online hard example mining. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 761–769, 2016.

[27] Christian Simon, Piotr Koniusz, Richard Nock, and Mehrtash Harandi. Adaptive subspaces for few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[28] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, 2017.

[29] Qianru Sun, Yaoyao Liu, Tat-Seng Chua, and Bernt Schiele. Meta-transfer learning for few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[30] Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip H.S. Torr, and Timothy M. Hospedales. Learning to compare: Relation network for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[31] Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B. Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: A good embedding is all you need? In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm, editors, *Computer Vision – ECCV 2020*, 2020.

[32] Vikas Verma, Alex Lamb, Christopher Beckham, Amir Najafi, Ioannis Mitliagkas, David Lopez-Paz, and Yoshua Bengio. Manifold mixup: Better representations by interpolating hidden states. In *International Conference on Machine Learning*, pages 6438–6447. PMLR, 2019.

[33] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, koray kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, 2016.

[34] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.

[35] Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[36] Sung Whan Yoon, Jun Seo, and Jaekyun Moon. TapNet: Neural network augmented with task-adaptive projection for few-shot learning. In *Proceedings of the 36th International Conference on Machine Learning*, Proceedings of Machine Learning Research, pages 7115–7123. PMLR, 09–15 Jun 2019.

[37] Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6023–6032, 2019.

[38] Chi Zhang, Yujun Cai, Guosheng Lin, and Chunhua Shen. Deepemd: Few-shot image classification with differentiable earth mover's distance and structured classifiers. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[39] Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

[40] Manli Zhang, Jianhong Zhang, Zhiwu Lu, Tao Xiang, Mingyu Ding, and Songfang Huang. {IEPT}: Instance-level and episode-level pretext tasks for few-shot learning. In *International Conference on Learning Representations*, 2021.