LEARNING STABLE CLASSIFIERS BY TRANSFERRING UNSTABLE FEATURES

ABSTRACT

While unbiased machine learning models are essential for many applications, bias is a human-defined concept that can vary across tasks. Given only input-label pairs, algorithms may lack sufficient information to distinguish stable (causal) features from unstable (spurious) features. However, related tasks often share similar biases – an observation we may leverage to develop stable classifiers in the transfer setting. In this work, we explicitly inform the target classifier about unstable features in the source tasks. Specifically, we derive a representation that encodes the unstable features by contrasting different data environments in the source task. We achieve robustness by clustering data of the target task according to this representation and minimizing the worst-case risk across these clusters. We evaluate our method on both text and image classifications. Empirical results demonstrate that our algorithm is able to maintain robustness on the target task, outperforming the best baseline by 22.9% in absolute accuracy across 12 transfer settings. Our code and data will be publicly available.

1 INTRODUCTION

Automatic de-biasing (Sohoni et al., 2020; Creager et al., 2021; Sanh et al., 2021) has emerged as a promising direction for learning stable classifiers. The key premise here is that no additional annotations for the bias attribute are required. However, bias is a human-defined concept and can vary from task to task. Provided with only input-label pairs, algorithms may not have sufficient information to distinguish stable (causal) features from unstable (spurious) features.

To address this challenge, we note that related tasks are often fraught with similar spurious correlations. For instance, when classifying animals such as camels vs. cows, their backgrounds (desert vs. grass) may constitute a spurious correlation (Beery et al., 2018). The same bias between the label and the background also persists in other related classification tasks (such as sheep vs. antelope). In the resource-scarce target task, we only have access to the input-label pairs. However, in the source tasks, where training data is sufficient, identifying biases may be easier. For instance, we may have examples collected from multiple environments, in which correlations between bias features and the label are different (Arjovsky et al., 2019). These source environments help us define the exact bias features that we want to regulate.

One obvious approach to utilize the source task is direct transfer. Specifically, given multiple source environments, we can train an unbiased source classifier and then apply its representation to the target task. However, we empirically demonstrate that while the source classifier is not biased when making its final predictions, its internal continuous representation can still encode information about the unstable features. Figure 1 shows that in Colored MNIST, where the digit label is spuriously correlated with the image color, direct transfer by either re-using or fine-tuning the representation learned on the source task fails in the target task, performing no better than the majority baseline.

In this paper, we propose to explicitly inform the target classifier about unstable features from the source data. Specifically, we derive a representation that encodes these unstable features using the source environments. Then we identify distinct subpopulations by clustering examples based on this representation and apply group DRO (Sagawa et al., 2019) to minimize the worst-case risk over these subpopulations. As a result, we enforce the target classifier to be robust against different values of the unstable features. In the example above, animals would be clustered according to backgrounds, and the classifier should perform well regardless of the clusters (backgrounds).

Figure 1: Transferring across tasks in Colored MNIST (Arjovsky et al., 2019). On the source task, we learn a color-invariant model that achieves oracle performance (given direct access to the unstable features). However, directly transferring this model to the target task, by reusing or fine-tuning its feature extractor, severely overfits the spurious correlation and underperforms the majority baseline (50%) on a test set where the spurious correlation flips. By explicitly transferring the unstable features, our algorithm TOFU (Transfer OF Unstable features) is able to reach the oracle performance.

The remaining question is how to compute the unstable feature representation using the source data environments. Following Bao et al. (2021), we hypothesize that unstable features are reflected in mistakes observed during classifier transfer across environments. For instance, if the classifier uses the background to distinguish camels from cows, the camel images that are predicted correctly would have a desert background while those predicted incorrectly are likely to have a grass background. More generally, we prove that among examples with the same label value, those with the same prediction outcome will have more similar unstable features than those with different predictions. By forcing examples with the same prediction outcome to stay closer in the feature space, we obtain a representation that encodes these latent unstable features.

We evaluate our approach, Transfer OF Unstable features (TOFU), on both image and text classification tasks. Our experiments first confirm our hypothesis that standard transfer approaches fail to learn a stable classifier for the target task. By explicitly transferring the unstable features, our method significantly improves over the best baseline across 12 transfer settings (22.9% in absolute accuracy), and reaches the performance of an oracle model that has direct access to the unstable features (0.3% gap). Qualitatively, we show that by contrasting different source environments, our method is able to encode examples based on the unstable features. Quantitatively, our generated clusters achieve 92% V-measure when evaluated against the ground truth unstable features.

2 RELATED WORK

Removing bias via annotations: Due to idiosyncrasies of the data collection process, annotations are often coupled with unwanted biases (Buolamwini and Gebru, 2018; Schuster et al., 2019; McCoy et al., 2019; Yang et al., 2019). To address this issue and learn robust models, researchers leverage extra information (Belinkov et al., 2019; Stacey et al., 2020; Hinton, 2002; Clark et al., 2019; He et al., 2019; Mahabadi et al., 2020). One line of work assumes that the bias attributes are known and have been annotated for each example, e.g., group distributionally robust optimization (DRO) (Hu et al., 2018; Oren et al., 2019; Sagawa et al., 2020). By defining groups based on these bias attributes, we explicitly specify the distribution family to optimize over. However, identifying the hidden biases is time-consuming and often requires domain knowledge (Zellers et al., 2019; Sakaguchi et al., 2020). To address this issue, another line of work (Peters et al., 2016; Krueger et al., 2020; Chang et al., 2020; Jin et al., 2020; Ahuja et al., 2020; Arjovsky et al., 2019; Bao et al., 2021) only assumes access to a set of data environments. These environments are defined based on readily-available information of the data collection circumstances, such as location and time. The main assumption is that while spurious correlations vary across different environments, the association between the causal features and the label should stay the same. Thus, by learning a representation that is invariant across all environments, they alleviate the dependency on spurious features. In contrast to previous works, we don't have access to any additional information besides the labels in our target task. We show that we can achieve robustness by transferring the unstable features from a related source task.

Automatic de-biasing A number of recent approaches focus on a more common setting where the algorithm only has access to the input-label pairs. Sanh et al. (2021); Nam et al. (2020); Utama et al. (2020) find that weak models are more vulnerable to spurious correlations as they only learn shallow

heuristics. By boosting from their mistakes, they obtain a more robust model. Creager et al. (2021); Sohoni et al. (2020); Ahmed et al. (2020); Matsuura and Harada (2020) propose to identify minority groups by looking at the features produced by a biased ERM classifier.

These automatic approaches are intriguing as they do not require additional annotation. However, we note that bias is a human-centric concept and can vary from tasks to tasks. For models that only have access to the input-label pairs, they have no information to distinguish causal features from bias features. For example, consider the Colored MNIST dataset, where color and digit shape are correlated in the training set but not in the test set. If our task is to predict the digit, then color becomes the spurious bias that we want to remove. Vice versa, if we want to predict the color, then digit shape is spurious. Creager et al. (2021); Nam et al. (2020) empirically demonstrate that they can learn a color-invariant model for the digit prediction task. However, their approaches will result in the same color-invariant model for the color prediction task, and thus fail at test time, when color and digit are no longer correlated. In this work, we leverage source tasks to define the exact bias that we want to remove for the target task.

Transferring robustness across tasks: Prior work has also studied the transferability of adversarial robustness across tasks. For example, Hendrycks et al. (2019); Shafahi et al. (2020) show that by pre-training the model on a large-scale source task, we can improve the model robustness against adversarial perturbations over l_∞ norm. We note that these perturbations measure the smoothness of the classifier, rather than the stability of the classifier against spurious correlations. In fact, our results show that if we directly re-use or fine-tune the pre-trained feature extractor on the target task, the model will quickly over-fit to the unstable correlations present in the data. We propose to address this issue by explicitly inferring the unstable features using the source environments and use this information to guide the target classifier during training. Empirically, we demonstrate that our method is able to learn a robust classifier without multiple target environments.

3 METHOD

Problem formulation We consider the transfer problem from a source task to a target task. For the source task, we assume the standard setting (Arjovsky et al., 2019) where the training data contain n environments $E_1, \ldots, E_n$. Within each environment E_i, examples are drawn from the joint distribution $P_i(x, y)$. Following Woodward (2005), we define unstable features $\mathcal{Z}(x)$ as features that are *differentially* correlated with the label across the environments. We note that $\mathcal{Z}(x)$ is unknown to the model.

For the target task, we only have access to the input-label pairs (x, y) (i.e. no environments). We assume that the target label is *not* causally associated with the above unstable features $\mathcal{Z}$. However, due to collection biases, the target data may contain *spurious correlations* between the label and $\mathcal{Z}$. Our goal is to transfer the knowledge that $\mathcal{Z}$ is unstable in the source task, so that the target classifier will not rely on these spurious features.

Overview If the unstable features have been identified for the target task, we can simply apply group DRO to learn a stable classifier. By grouping examples based on the unstable features and minimizing the worst-case risk over these *manually-defined* groups, we explicitly address the bias from these unstable features (Hu et al., 2018; Oren et al., 2019; Sagawa et al., 2020). In our setup, while these unstable features are not accessible, we can leverage the source environments to derive groups over the target data that are informative of these biases. Applying group DRO on these *automatically-derived* groups, we can eliminate the unstable correlations in the target task.

Our overall transfer paradigm is depicted in Figure 2. It consists of two steps: inferring unstable features from the source task (Section 3.1) and learning stable correlations for the target task (Section 3.2). First, for the source task we use a classifier trained on one environment to partition data from another environment based on the correctness of its predictions. Starting from the theoretical results in (Bao et al., 2021), we show that these partitions reflect the similarity of the examples in terms of their unstable features: among examples with the same label value, those that share the same prediction outcome have more similar unstable features than those with different predictions (Theorem 1). We can then derive a representation $f_{\mathcal{Z}}$ where examples are distributed based on the unstable features $\mathcal{Z}$. Next, we cluster target examples into groups based on the learned unstable feature representation

Figure 2: Our algorithm TOFU 1) infers unstable features from the source task (Section 3.1) and 2) learns stable correlations for the target task (Section 3.2). We create partitions for all environment pairs. For ease of illustration, we only depict using f_1 to partition E_2. Best viewed in color.

$f_{\mathcal{Z}}$. These *automatically-derived* groups correspond to different modes of the unstable features, and they act as proxies to the *manually-defined* groups in the oracle setting where unstable features are explicitly annotated. Finally, we use group DRO to obtain our robust target classifier by minimizing the worst-case risk over these groups.

Extension to multiple source tasks: Environments from a single source task may not describe all unwanted unstable features. In this situation, we would like to leverage multiple source tasks to compose their individual unstable features together. We can naturally extend TOFU to accomplish this goal by learning the unstable feature representation jointly across all source tasks. In this work, we focus on the basic setting and leave this extension to Appendix C.

3.1 INFERRING UNSTABLE FEATURES FROM THE SOURCE TASK

Given the data environments from the source task, we would like to 1) identify the unstable correlations across these environments; 2) learn a representation $f_{\mathcal{Z}}(x)$ that encodes the unstable features $\mathcal{Z}(x)$. We achieve the first goal by contrasting the empirical distribution of different environments (Figure 2.S.1 and Figure 2.S.2) and the second goal by metric learning (Figure 2.S.3).

Let E_i and E_j be two different data environments. Bao et al. (2021) shows that by training a classifier f_i on E_i and using it to make predictions on E_j, we can reveal the unstable correlations from its prediction results. Intuitively, if the unstable correlations are stronger in E_i, the classifier f_i will overuse these correlations and make mistakes on E_j when these stronger correlations do not hold.

In this work, we connect the prediction results directly to the unstable features. We show that the prediction results of the classifier f_i on E_j estimate the relative distance of the unstable features.

Theorem 1 (Simplified). *Consider examples in E_j with label value y. Let $X_1^{\checkmark}, X_2^{\checkmark}$ denote two batches of examples that f_i predicted correctly, and let $X_3^{\times}$ denote a batch of incorrect predictions. We use $\overline{\cdot}$ to represent the mean across a given batch. Following the same assumption in (Bao et al.,*

2021), we have

$$\|\overline{\mathcal{Z}}(X_1^{\checkmark}) - \overline{\mathcal{Z}}(X_2^{\checkmark})\|_2 < \|\overline{\mathcal{Z}}(X_1^{\checkmark}) - \overline{\mathcal{Z}}(X_3^{\times})\|_2$$

almost surely for large enough batch size.[1]

The result makes intuitive sense as we would expect example pairs that share the same prediction outcome should be more similar than those with different prediction outcomes. We note that it is critical to look at examples with the same label value; otherwise, the unstable features will be coupled with the task-specific label in the prediction results.

While the value of the unstable features $\mathcal{Z}(x)$ is still not directly accessible, Theorem 1 enables us to learn a feature representation $f_{\mathcal{Z}}(x)$ that preserves the distance between the examples in terms of their unstable features. We adopt standard metric learning (Chechik et al., 2010) to minimize the following triplet loss:

$$\mathcal{L}_{\mathcal{Z}}(X_1^{\checkmark}, X_2^{\checkmark}, X_3^{\times}) = \max(0, \|\overline{f_{\mathcal{Z}}}(X_1^{\checkmark}) - \overline{f_{\mathcal{Z}}}(X_2^{\checkmark})\|_2^2 - \|\overline{f_{\mathcal{Z}}}(X_1^{\checkmark}) - \overline{f_{\mathcal{Z}}}(X_3^{\times})\|_2^2 + \delta), \quad (1)$$

where δ is a hyper-parameter. By minimizing Eq equation 1, we encourage examples that have similar unstable features to be close in the representation $f_{\mathcal{Z}}$. To summarize, inferring unstable features from the source task consists of three steps (Figure 2.S):

S.1 For each source environment E_i, train an environment-specific classifier f_i.

S.2 For each pair of environments E_i and E_j, use classifier f_i to partition E_j into two sets: $E_j^{i\checkmark}$ and $E_j^{i\times}$, where $E_j^{i\checkmark}$ contains examples that f_i predicted correctly and $E_j^{i\times}$ contains those predicted incorrectly.

S.3 Learn an unstable feature representation $f_{\mathcal{Z}}$ by minimizing Eq equation 1 across all pairs of environments E_i, E_j and all possible label value y:

$$f_{\mathcal{Z}} = \arg\min \sum_{y, E_i \neq E_j} \mathbb{E}_{X_1^{\checkmark}, X_2^{\checkmark}, X_3^{\times}} \left[\mathcal{L}_{\mathcal{Z}}(X_1^{\checkmark}, X_2^{\checkmark}, X_3^{\times}) \right],$$

where batches $X_1^{\checkmark}, X_2^{\checkmark}$ are sampled uniformly from $E_j^{i\checkmark}|_y$ and batch $X_3^{\times}$ is sampled uniformly from $E_j^{i\times}|_y$ ($\cdot|_y$ denotes the subset of $\cdot$ with label value y).

3.2 LEARNING STABLE CORRELATIONS FOR THE TARGET TASK

Given the unstable feature representation $f_{\mathcal{Z}}$, our goal is to learn a target classifier that focuses on the stable correlations rather than using unstable features. Inspired by group DRO (Sagawa et al., 2020) we minimize the worst-case risk across groups of examples that are representative of different unstable feature values. However, in contrast to DRO, these groups are constructed automatically based on the previously learned representation $f_{\mathcal{Z}}$.

For each target label value y, we use the representation $f_{\mathcal{Z}}$ to cluster target examples with label y into different clusters (Figure 2.T.1). Since these clusters capture different modes of the unstable features, they are approximations of the typical manually-defined groups when annotations of the unstable features are available. By minimizing the worst-case risk across all clusters, we explicitly enforce the classifier to be robust against unstable correlations (Figure 2.T.2). We note that it is important to cluster within examples of the same label, as opposed to clustering the whole dataset. Otherwise, the cluster assignment may be correlated with the target label.

Concretely, learning stable correlations for the target task has two steps (Figure 2.T).

T.1 For each label value y, apply K-means (l_2 distance) to cluster examples with label y in the feature space $f_{\mathcal{Z}}$. We use $C_1^y, \ldots, C_{n_c}^y$ to denote the resulting cluster assignment, where n_c is a hyper-parameter.

T.2 Train the target classifier f by minimizing the worst-case risk over all clusters:

$$f = \arg\min \max_{i,y} \mathcal{L}(C_i^y),$$

where $\mathcal{L}(C_i^y)$ is the empirical risk on cluster C_i^y.

---

[1]See Appendix A for the full theorem and proof.

Table 1: Pearson correlation coefficient between the spurious feature $\mathcal{Z}$ and the label Y for each task. The validation environment E^{val} follows the same distribution as E_1^{train}. We study the transfer problem between different task pairs. For the source task S, the model can access $E_1^{\text{train}}(S)$, $E_2^{\text{train}}(S)$ and $E^{\text{val}}(S)$. For the target task T, the model can access $E_1^{\text{train}}(T)$ and $E^{\text{val}}(T)$.

$\rho(\mathcal{Z}, Y)$	MNIST		BEER REVIEW			ASK2ME		WATERBIRD	
	ODD	EVEN	LOOK	AROMA	PALATE	PENE.	INCI.	WATER	SEA.
E_1^{train}	0.87	0.87	0.60	0.60	0.60	0.31	0.44	0.36	0.39
E_2^{train}	0.75	0.75	0.80	0.80	0.80	0.52	0.66	0.63	0.64
E^{val}	0.87	0.87	0.60	0.60	0.60	0.31	0.44	0.36	0.39
E^{test}	−0.11	−0.11	−0.80	−0.80	−0.80	0.00	0.00	0.00	0.00

4   EXPERIMENTAL SETUP

4.1   DATASETS AND SETTINGS

We evaluate our approach on both image classification and text classification. We start with controlled experiments on MNIST (LeCun et al., 1998) and BeerReview (McAuley et al., 2012), where we inject spurious features into the input (background colors for MNIST and pseudo tokens for BeerReview). We then consider a practical setting on ASK2ME (Bao et al., 2019a) and Waterbird (Sagawa et al., 2019), where the spurious feature corresponds to an attribute of the input and is unknown to the model (`breast_cancer` for ASK2ME and `background` for Waterbird).

For each dataset, we consider multiple tasks and study the transfer between these tasks. Specifically, for each task, we split its data into four environments: $E_1^{\text{train}}, E_2^{\text{train}}, E^{\text{val}}, E^{\text{test}}$, where spurious correlations vary across the two training environments $E_1^{\text{train}}, E_2^{\text{train}}$. For the source task S, the model can access both of its training environments $E_1^{\text{train}}(S), E_2^{\text{train}}(S)$. For the target task T, the model only has access to one training environment $E_1^{\text{train}}(T)$. We note that the validation set $E^{\text{val}}(T)$ plays an important role in early-stopping and hyper-parameter tuning, especially when the distribution of the data is different between training and testing (Gulrajani and Lopez-Paz, 2020). In this work, since we don't have access to multiple training environments on the target task, we assume that the validation data E^{val} follows the same distribution as the training data E_1^{train}. Table 1 summarizes the level of the spurious correlations for different tasks. Additional details can be found in Appendix B.1[2].

4.2   BASELINES

We compare our algorithm against the following baselines. For fair comparison, all methods share the same representation backbone and hyper-parameter search space. Implementation details can be found in Appendix B.2.

ERM baseline   We learn a classifier on the target task from scratch by minimizing the average loss across all examples. Note that this classifier is independent of the source task. Its performance reflects the deviation between the training distribution and the testing distribution of the target task.

Transfer methods   Since the source task contains multiple environments, we can learn a stable model on the source task and transfer it to the target task (Arjovsky et al., 2019; Bao et al., 2021). We consider the following methods for transfer.

REUSE: We first learn a stable model on the source task by contrasting different source environments (Bao et al., 2021). We then directly transfer its feature extractor to the target task. By keeping this feature extractor fixed when learning the target classifier (a linear layer followed by Softmax activation), we hope the resulting model will not rely on these unstable features.

---

[2] All data splits are available in the supplementary materials.

Table 2: Target task accuracy of different methods on image classification (MNIST and WATERBIRD) and text classification (BEER REVIEW and ASK2ME). All methods are tuned based on a held-out validation set that follows from the same distribution as the target training data. Bottom right: standard deviation across 5 runs. Upper right: source task testing performance (if applicable).

	SOURCE	TARGET	ERM	REUSE	FINETUNE	MT	TOFU	ORACLE
MNIST	ODD	EVEN	$12.3_{\pm0.6}$	$14.4_{\pm1.0}^{(70.9)}$	$11.2_{\pm2.1}^{(70.1)}$	$11.6_{\pm0.6}^{(69.6)}$	$\mathbf{69.1}_{\pm1.6}$	$68.7_{\pm0.9}$
	EVEN	ODD	$9.7_{\pm0.6}$	$19.2_{\pm2.3}^{(71.1)}$	$11.5_{\pm1.2}^{(71.1)}$	$10.1_{\pm0.7}^{(70.0)}$	$\mathbf{66.8}_{\pm0.8}$	$67.8_{\pm0.5}$
BEER REVIEW	LOOK	AROMA	$55.5_{\pm1.7}$	$31.9_{\pm1.0}^{(70.1)}$	$53.7_{\pm1.4}^{(70.1)}$	$54.1_{\pm2.2}^{(76.0)}$	$\mathbf{75.9}_{\pm1.4}$	$77.3_{\pm1.3}$
	LOOK	PALATE	$46.9_{\pm0.3}$	$22.8_{\pm1.9}^{(70.0)}$	$49.3_{\pm2.1}^{(73.2)}$	$52.8_{\pm2.9}^{(73.3)}$	$\mathbf{73.8}_{\pm0.7}$	$74.0_{\pm1.2}$
	AROMA	LOOK	$63.9_{\pm0.6}$	$40.1_{\pm3.1}^{(68.6)}$	$65.2_{\pm1.8}^{(66.4)}$	$64.0_{\pm0.6}^{(71.5)}$	$\mathbf{80.9}_{\pm0.5}$	$80.1_{\pm0.6}$
	AROMA	PALATE	$46.9_{\pm0.3}$	$14.0_{\pm2.4}^{(68.3)}$	$47.9_{\pm3.3}^{(63.2)}$	$50.0_{\pm1.4}^{(71.2)}$	$\mathbf{73.5}_{\pm1.1}$	$74.0_{\pm1.2}$
	PALATE	LOOK	$63.9_{\pm0.6}$	$40.4_{\pm2.8}^{(57.2)}$	$64.3_{\pm2.7}^{(60.1)}$	$63.1_{\pm1.0}^{(75.9)}$	$\mathbf{81.0}_{\pm1.0}$	$80.1_{\pm0.6}$
	PALATE	AROMA	$55.5_{\pm1.7}$	$23.1_{\pm3.3}^{(59.2)}$	$54.5_{\pm1.2}^{(58.7)}$	$56.5_{\pm1.3}^{(73.3)}$	$\mathbf{76.9}_{\pm1.5}$	$77.3_{\pm1.5}$
ASK.	PENE	INCI.	$79.3_{\pm1.3}$	$71.7_{\pm0.5}^{(72.7)}$	$79.3_{\pm0.8}^{(71.2)}$	$71.1_{\pm1.4}^{(73.5)}$	$\mathbf{83.2}_{\pm1.8}$	$84.8_{\pm1.2}$
	INCI.	PENE.	$71.6_{\pm1.8}$	$64.1_{\pm1.5}^{(83.4)}$	$72.0_{\pm3.1}^{(83.4)}$	$61.9_{\pm0.7}^{(82.4)}$	$\mathbf{78.1}_{\pm1.4}$	$78.3_{\pm0.9}$
BIRD	WATER	SEA.	$81.8_{\pm4.3}$	$87.8_{\pm1.1}^{(99.5)}$	$82.0_{\pm4.0}^{(99.5)}$	$88.0_{\pm0.9}^{(99.5)}$	$\mathbf{93.1}_{\pm0.4}$	$93.7_{\pm0.7}$
	SEA.	WATER	$75.1_{\pm6.3}$	$94.6_{\pm1.6}^{(93.3)}$	$78.2_{\pm8.1}^{(93.1)}$	$93.5_{\pm1.9}^{(92.7)}$	$\mathbf{99.0}_{\pm0.4}$	$98.9_{\pm0.5}$
	Average		55.2	43.7	55.8	56.4	79.3	79.6

FINETUNE: Based on REUSE, but we also update the feature extractor when training the target classifier. (Shafahi et al., 2020) has shown that FINETUNE may improve adversarial robustness of the target task.

MT: We adopt the standard multi-task learning approach (Caruana, 1997) where the source model and the target model share the same feature extractor and are jointly trained together. For the source task, we first partition the source data into subsets with opposite spurious correlations (Bao et al., 2021). During multi-task training, we minimize the worst-case risk over all these subsets for the source task and minimize the average empirical risk for the target task. MULTITASK is more flexible than REUSE since we tune feature extractor to fit the target data. Compared to FINETUNE, MULTITASK is more constrained as the source model prevents over-utilization of unstable features during joint training.

Automatic de-biasing methods For the target task, we can also apply de-biasing approaches that do not require environments.

GEORGE: Following Sohoni et al. (2020), we first train an ERM classifier on the target task. Then we uses its feature representations and apply K-means to cluster the training data. Finally, we apply group DRO to minimize the worst-case loss over all clusters.

LFF: Following Nam et al. (2020), we train a biased classifier together with a de-biased classifier. The biased classifier amplifies its bias by minimizing the generalized cross entropy loss (Zhang and Sabuncu, 2018). The de-biased classifier then up-weights examples that are mis-labeled by the biased classifier during training.

EIIL: Following Creager et al. (2021), we first train an ERM classifier on the target task. Based on the classifier's prediction logits, we infer an environment assignment that maximally violates the invariant learning principle (Arjovsky et al., 2019). Finally, we apply group DRO to minimize the worst-case loss over all inferred environments.

ORACLE model We can use the hidden unstable features to define groups and train an oracle model using group DRO. For example, in task SEABIRD, this oracle model will minimize the worst-case risk

Figure 3: PCA visualization of the unstable feature representation $f_{\mathcal{Z}}$ for examples in MNIST EVEN. $f_{\mathcal{Z}}$ is trained on MNIST ODD. While the spurious color features are not accessible, TOFU is able to identify them by contrasting different source environments.

Figure 4: Word importance for the unstable feature representation $f_{\mathcal{Z}}$ trained on BEER LOOK. We observe that $f_{\mathcal{Z}}$ behaves as a spurious token detector: it focuses mostly on the spurious token despite the presence of sentiment words.

Table 3: Comparison between TOFU and automatic de-biasing methods on ASK2ME and WATERBIRD

	SOURCE	TARGET	ERM	GEORGE	LFF	EIIL	TOFU	ORACLE
ASK.	PENE	INCI.	$79.3_{\pm1.3}$	$80.2_{\pm0.7}$	$81.0_{\pm1.7}$	$80.9_{\pm0.9}$	$\mathbf{83.2}_{\pm1.8}$	$84.8_{\pm1.2}$
ASK.	INCI.	PENE.	$71.6_{\pm1.8}$	$72.4_{\pm1.6}$	$73.5_{\pm2.1}$	$73.4_{\pm1.3}$	$\mathbf{78.1}_{\pm1.4}$	$78.3_{\pm0.9}$
BIRD	WATER	SEA.	$81.8_{\pm4.3}$	$87.2_{\pm0.6}$	$88.1_{\pm1.0}$	$88.0_{\pm0.5}$	$\mathbf{93.1}_{\pm0.4}$	$93.7_{\pm0.7}$
BIRD	SEA.	WATER	$75.1_{\pm6.3}$	$91.5_{\pm0.8}$	$93.0_{\pm1.3}$	$93.4_{\pm1.2}$	$\mathbf{99.0}_{\pm0.4}$	$98.9_{\pm0.5}$
Average			76.9	82.8	83.9	83.9	88.3	88.9

over the following four groups: {seabird with water}, {seabird with land} {landbird with water}, {landbird with land}. Like ERM, this oracle model is independent of the source task. It helps us analyze the robustness of our proposed algorithm separately from the inherent limitations (such as model capacity and data size) of the target task.

5 RESULTS

Table 2 and Table 3 summarize the results. We observe that standard transfer methods (REUSE, FINETUNE, MULTITASK) fail to improve over the ERM baseline. On the other hand, TOFU consistently achieves the best performance across 12 transfer settings, outperforming the best baseline by 22.9% in absolute accuracy. Comparing with automatic de-biasing methods, TOFU leverages the source task to better pinpoint the bias and reduces the error rate by 27.3%. While TOFU doesn't have access to the unstable features, by inferring them from the source environments, it matches the oracle performance with only 0.30% absolute difference.

Why do the baselines behave so differently across different datasets? As (Bao et al., 2019b) pointed out, the transferability of the low-level features is very different in image classification and in text classification. For example, the keywords for identifying the sentiment of LOOK are very different from the ones for PALATE. Thus, fine-tuning the feature extractor is crucial. This explains why REUSE underperforms other baselines on text data. Conversely, in image classification, the low-level patterns (such as edges) are more transferable across tasks. Directly reusing the feature extractor helps improve model stability against spurious correlations. Finally, we note that since TOFU transfers the unstable features instead of the task-specific causal features, it performs robustly across all the settings.

Is TOFU able to identify the unstable features? Yes. For image classification, we visualize the unstable feature representation produced by $f_{\mathcal{Z}}$ on MNIST EVEN. Figure 3 demonstrates that while

Table 4: Quantitative evaluation of the generated clusters against the ground truth unstable features. The ERM baseline clusters target example based on a feature extractor learned on the source task. For both methods, we generate two clusters for each target label value and report the average performance across all label values. We observe that the ERM representation, while biased by the spurious correlations, fails to recover the ground truth unstable features. By explicitly contrasting the source environments, TOFU derives clusters that are highly-informative of the unstable features.

	SOURCE	TARGET	Homogeneity		Completeness		V measure	
			ERM	TOFU	ERM	TOFU	ERM	TOFU
MNIST	ODD	EVEN	0.2584	**0.6820**	0.2714	**0.9561**	0.2535	**0.7960**
	EVEN	ODD	0.1454	**0.6764**	0.0983	**0.9988**	0.1173	**0.8055**
BEER REVIEW	LOOK	AROMA	0.0019	**0.9256**	0.0014	**0.9218**	0.0016	**0.9236**
	LOOK	PALATE	0.0088	**0.9095**	0.0064	**0.8988**	0.0074	**0.9039**
	AROMA	LOOK	0.0017	**1.0000**	0.0012	**1.0000**	0.0014	**1.0000**
	AROMA	PALATE	0.0088	**1.0000**	0.0064	**1.0000**	0.0074	**1.0000**
	PALATE	LOOK	0.0005	**0.9816**	0.0003	**0.9811**	0.0004	**0.9813**
	PALATE	AROMA	0.0028	**0.9585**	0.0020	**0.9561**	0.0024	**0.9573**

$f_{\mathcal{Z}}$ only sees source examples (ODD) during training, it can distribute target examples based on their unstable color features. For text classification, we visualize word importance of $f_{\mathcal{Z}}$ on BEER LOOK. Figure 4 shows that $f_{\mathcal{Z}}$ primarily focuses on the spurious token when generating the representation.

How many clusters to generate? We study the effect of the number of clusters on ASK2ME. Figure 5 shows that while generating more clusters in the unstable feature space $f_{\mathcal{Z}}$ reduces the variance, it doesn't improve the performance by much. This is not very surprising as the training data is primarily biased by a single `breast_cancer` attribute. We expect that having more clusters will be beneficial for tasks with more sophisticated underlying biases.

How do the generated clusters compare to the oracle groups? We quantitatively evaluate the generated clusters based on three metrics: *homogeneity* (each cluster contain only examples with the same unstable feature value), *completeness* (examples with the same unstable feature value belong to the same cluster), and *V-measure* (the harmonic mean of homogeneity and completeness). From Table 4, we see that TOFU is able to derive clusters that resemble the oracle groups on BEER REVIEW. In MNIST, we note that since we

Figure 5: Accuracy of TOFU on ASK2ME as we vary the number of clusters n_c generated for each label value. Empirically, we see that while having more clusters doesn't improve the performance, it helps reduce the variance.

generate two clusters for each label value and there are five different colors, it is impossible to recover the oracle groups. However, TOFU still achieves almost perfect completeness. For comparison, we directly apply K-means clustering to the feature representation learned by ERM on the source environments (as in GEORGE). Although this representation is biased by the unstable feature, the resulting clusters fail to uncover the oracle groups.

6 CONCLUSION

We study transfer learning in the presence of spurious correlations. Current transfer techniques fail as the target model is unaware of these spurious correlations during training. In this paper, we propose to explicitly inform the target model of the unstable features, thereby enabling it to regularize the impact of these biases. Experimental results validate that our algorithm generates clusters that are informative of the unstable feature and learns a stable classifier.

REFERENCES

F. Ahmed, Y. Bengio, H. van Seijen, and A. Courville. Systematic generalisation with group invariant predictions. In *International Conference on Learning Representations*, 2020.

K. Ahuja, K. Shanmugam, K. Varshney, and A. Dhurandhar. Invariant risk minimization games. In *International Conference on Machine Learning*, pages 145–155. PMLR, 2020.

M. Arjovsky, L. Bottou, I. Gulrajani, and D. Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Y. Bao, Z. Deng, Y. Wang, H. Kim, V. D. Armengol, F. Acevedo, N. Ouardaoui, C. Wang, G. Parmigiani, R. Barzilay, D. Braun, and K. S. Hughes. Using machine learning and natural language processing to review and classify the medical literature on cancer susceptibility genes. *JCO Clinical Cancer Informatics*, (3):1–9, 2019a. doi: 10.1200/CCI.19.00042. URL https://doi.org/10.1200/CCI.19.00042. PMID: 31545655.

Y. Bao, M. Wu, S. Chang, and R. Barzilay. Few-shot text classification with distributional signatures. In *International Conference on Learning Representations*, 2019b.

Y. Bao, S. Chang, and R. Barzilay. Predict then interpolate: A simple algorithm to learn stable classifiers. In *International Conference on Machine Learning (ICML)*, 2021.

S. Beery, G. Van Horn, and P. Perona. Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 456–473, 2018.

Y. Belinkov, A. Poliak, S. M. Shieber, B. Van Durme, and A. M. Rush. Don't take the premise for granted: Mitigating artifacts in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 877–891, 2019.

J. Buolamwini and T. Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference on fairness, accountability and transparency*, pages 77–91, 2018.

R. Caruana. Multitask learning. *Machine learning*, 28(1):41–75, 1997.

S. Chang, Y. Zhang, M. Yu, and T. S. Jaakkola. Invariant rationalization. *arXiv preprint arXiv:2003.09772*, 2020.

G. Chechik, V. Sharma, U. Shalit, and S. Bengio. Large scale online learning of image similarity through ranking. 2010.

C. Clark, M. Yatskar, and L. Zettlemoyer. Don't take the easy way out: Ensemble based methods for avoiding known dataset biases. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4060–4073, 2019.

E. Creager, J.-H. Jacobsen, and R. Zemel. Environment inference for invariant learning. In *International Conference on Machine Learning*, pages 2189–2200. PMLR, 2021.

Z. Deng, K. Yin, Y. Bao, V. D. Armengol, C. Wang, A. Tiwari, R. Barzilay, G. Parmigiani, D. Braun, and K. S. Hughes. Validation of a semiautomated natural language processing–based procedure for meta-analysis of cancer susceptibility gene penetrance. *JCO clinical cancer informatics*, 3:1–9, 2019.

I. Gulrajani and D. Lopez-Paz. In search of lost domain generalization. *arXiv preprint arXiv:2007.01434*, 2020.

H. He, S. Zha, and H. Wang. Unlearn dataset bias in natural language inference by fitting the residual. *EMNLP-IJCNLP 2019*, page 132, 2019.

D. Hendrycks, K. Lee, and M. Mazeika. Using pre-training can improve model robustness and uncertainty. In *International Conference on Machine Learning*, pages 2712–2721. PMLR, 2019.

G. E. Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 14(8):1771–1800, 2002.

W. Hu, G. Niu, I. Sato, and M. Sugiyama. Does distributionally robust supervised learning give robust classifiers? In *International Conference on Machine Learning*, pages 2029–2037. PMLR, 2018.

W. Jin, R. Barzilay, and T. Jaakkola. Enforcing predictive invariance across structured biomedical domains, 2020.

Y. Kim. Convolutional neural networks for sentence classification. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1746–1751, Doha, Qatar, Oct. 2014. Association for Computational Linguistics. doi: 10.3115/v1/D14-1181. URL https://www.aclweb.org/anthology/D14-1181.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

D. Krueger, E. Caballero, J.-H. Jacobsen, A. Zhang, J. Binas, D. Zhang, R. L. Priol, and A. Courville. Out-of-distribution generalization via risk extrapolation (rex), 2020.

Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

T. Lei, R. Barzilay, and T. Jaakkola. Rationalizing neural predictions. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 107–117, 2016.

Z. Liu, P. Luo, X. Wang, and X. Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

R. K. Mahabadi, Y. Belinkov, and J. Henderson. End-to-end bias mitigation by modelling biases in corpora. ACL, 2020.

T. Matsuura and T. Harada. Domain generalization using a mixture of multiple latent domains. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 11749–11756, 2020.

J. McAuley, J. Leskovec, and D. Jurafsky. Learning attitudes and attributes from multi-aspect reviews. In *2012 IEEE 12th International Conference on Data Mining*, pages 1020–1025. IEEE, 2012.

T. McCoy, E. Pavlick, and T. Linzen. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3428–3448, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1334. URL https://www.aclweb.org/anthology/P19-1334.

T. Mikolov, E. Grave, P. Bojanowski, C. Puhrsch, and A. Joulin. Advances in pre-training distributed word representations. In *Proceedings of the International Conference on Language Resources and Evaluation (LREC 2018)*, 2018.

J. Nam, H. Cha, S. Ahn, J. Lee, and J. Shin. Learning from failure: Training debiased classifier from biased classifier. *arXiv preprint arXiv:2007.02561*, 2020.

Y. Oren, S. Sagawa, T. Hashimoto, and P. Liang. Distributionally robust language modeling. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4218–4228, 2019.

J. Peters, P. Bühlmann, and N. Meinshausen. Causal inference by using invariant prediction: identification and confidence intervals. *Journal of the Royal Statistical Society. Series B (Statistical Methodology)*, pages 947–1012, 2016.

S. Sagawa, P. W. Koh, T. B. Hashimoto, and P. Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. *arXiv preprint arXiv:1911.08731*, 2019.

S. Sagawa, P. W. Koh, T. B. Hashimoto, and P. Liang. Distributionally robust neural networks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=ryxGuJrFvS.

K. Sakaguchi, R. Le Bras, C. Bhagavatula, and Y. Choi. Winogrande: An adversarial winograd schema challenge at scale. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8732–8740, 2020.

V. Sanh, T. Wolf, Y. Belinkov, and A. M. Rush. Learning from others' mistakes: Avoiding dataset biases without modeling them. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=Hf3qXoiNkR.

T. Schuster, D. Shah, Y. J. S. Yeo, D. Roberto Filizzola Ortiz, E. Santus, and R. Barzilay. Towards debiasing fact verification models. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3410–3416, Hong Kong, China, Nov. 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1341. URL https://www.aclweb.org/anthology/D19-1341.

A. Shafahi, P. Saadatpanah, C. Zhu, A. Ghiasi, C. Studer, D. Jacobs, and T. Goldstein. Adversarially robust transfer learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=ryebG04YvB.

N. S. Sohoni, J. A. Dunnmon, G. Angus, A. Gu, and C. Ré. No subclass left behind: Fine-grained robustness in coarse-grained classification problems. *arXiv preprint arXiv:2011.12945*, 2020.

J. Stacey, P. Minervini, H. Dubossarsky, S. Riedel, and T. Rocktäschel. Avoiding the Hypothesis-Only Bias in Natural Language Inference via Ensemble Adversarial Training. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8281–8291, Online, Nov. 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.665. URL https://www.aclweb.org/anthology/2020.emnlp-main.665.

P. A. Utama, N. S. Moosavi, and I. Gurevych. Towards debiasing nlu models from unknown biases. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7597–7610, 2020.

P. Welinder, S. Branson, T. Mita, C. Wah, F. Schroff, S. Belongie, and P. Perona. Caltech-UCSD Birds 200. Technical Report CNS-TR-2010-001, California Institute of Technology, 2010.

J. Woodward. *Making things happen: A theory of causal explanation*. Oxford university press, 2005.

K. Yang, K. Swanson, W. Jin, C. Coley, P. Eiden, H. Gao, A. Guzman-Perez, T. Hopper, B. Kelley, M. Mathea, et al. Analyzing learned molecular representations for property prediction. *Journal of chemical information and modeling*, 59(8):3370–3388, 2019.

R. Zellers, A. Holtzman, Y. Bisk, A. Farhadi, and Y. Choi. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4791–4800, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1472. URL https://www.aclweb.org/anthology/P19-1472.

Z. Zhang and M. R. Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels. In *32nd Conference on Neural Information Processing Systems (NeurIPS)*, 2018.