Composition Theorems for Interactive Differential Privacy

Abstract

An interactive mechanism is an algorithm that stores a data set and answers adaptively chosen queries to it. The mechanism is called differentially private, if any adversary cannot distinguish whether a specific individual is in the data set by interacting with the mechanism. We study composition properties of differential privacy in concurrent compositions. In this setting, an adversary interacts with k interactive mechanisms in parallel and can interleave its queries to the mechanisms arbitrarily. Previously, Vadhan and Wang [2021] proved an optimal concurrent composition theorem for pure-differential privacy. We significantly generalize and extend their results. Namely, we prove optimal parallel composition properties for several major notions of differential privacy in the literature, including approximate DP, Rényi DP, and zero-concentrated DP. Our results demonstrate that the adversary gains no advantage by interleaving its queries to independently running mechanisms. Hence, interactivity is a feature that differential privacy grants us for free.

1 Introduction

By now, differential privacy [Dwork et al., 2006b] has been widely accepted as a standard framework for protecting individual privacy when performing data analysis on data sets that may contain sensitive information of individuals (see, e.g., the surveys by Dwork and Roth [2014], Vadhan [2017]).

Let $\mathcal{M}$ be an algorithm that runs on a data set x and calculates some information about it. Roughly speaking, $\mathcal{M}$ is called differentially private, if the output distribution of $\mathcal{A}$ remains nearly identical when we arbitrarily modify a single entry in x.

One essential feature of differential privacy is its *composability*. Composition captures the scenario where a data analyst runs k differentially private algorithms sequentially, and releases the results afterward. Typically, a composition theorem has the following form: if each of the k algorithms satisfies differential privacy, then the analyst's output is still differentially private with moderately degraded privacy parameters.

Composition theorems are important for at least two reasons. First, we might want to perform computation tasks on the same data set multiple times and still have reasonable control over the privacy loss. In this case, composition theorems reveal how the privacy guarantee degrades over time. More importantly, composition theorems allow us to build more complex and powerful differentially-private algorithms from simple primitives, and argue the privacy guarantee of the combined algorithm in a straightforward way.

There is a rich literature concerning the composition property of differential privacy (see, e.g., Dwork et al. [2006a, 2010], Kairouz et al. [2015], Murtagh and Vadhan [2018], Bassily et al. [2021]). However, most existing composition theorems only consider the scenario where an analyst runs

several private algorithms *sequentially*. That is, the analyst will only move on to the next algorithm after finishing their computation with the previous one. In contrast, many fundamental primitives in differential privacy are interactive in nature, such as the sparse vector technique [Dwork et al., 2009, Roth and Roughgarden, 2010] and private multiplicative weight updates [Hardt and Rothblum, 2010]. Hence, the interactivity issue appears to be a significant limitation of current composition theorems. Namely, the data analyst may want to communicate with several interactive mechanisms *concurrently*, and interleave its queries to the mechanisms arbitrarily. A sequential composition theorem completely fails to capture this scenario. Also, in practice, deployments of DP algorithms often demand a better understanding of concurrent compositions of interactive mechanisms [Hay et al., 2020].

Recently, Vadhan and Wang [2021] initiated a study of concurrent compositions and proved an optimal concurrent composition theorem for pure differential privacy. In this work, we significantly advance this research direction by proving optimal concurrent composition theorems for several popular notions of differential privacy, including approximate DP, Rényi DP, zero-concentrated DP and truncated concentrated DP.

1.1 Setup

Before we continue, we set up necessary pieces of notation. We use $\mathcal{X}$ and $\mathcal{Y}$ to denote the domain of query messages and responses, respectively. We assume that both $\mathcal{X}$ and $\mathcal{Y}$ are finite sets. This assumption is for easing some mathematical manipulation and is not restrictive: all practical applications of differential privacy have finite input and output spaces anyway.

For a set S, denote by $\Delta(S)$ the set of all possible distributions supported over S. We define interactive systems below.

Definition 1 (Interactive system). An interactive system is a (randomized) algorithm $\mathcal{M} \colon (\mathcal{X} \times \mathcal{Y})^* \times \mathcal{X} \to \Delta(\mathcal{Y})$. The input to $\mathcal{M}$ is an interaction history $(x_1, y_1), (x_2, y_2), \ldots, (x_t, y_t) \in (\mathcal{X} \times \mathcal{Y})^t$ together with a query x_{t+1}. The output of $\mathcal{M}$ is denoted by $y_{t+1} \sim \mathcal{M}((x_i, y_i)_{i \in [t]}, x_{t+1})$.

A technicality worth mentioning is that due to the internal memory and randomness of an interactive system $\mathcal{M}$, the response of $\mathcal{M}$ to the $(t+1)$-th query might be correlated with its responses to previous queries. Although the internal randomness of $\mathcal{M}$ is not explicitly stated as a parameter, Definition 1 captures this correlation by requiring that each query x_{t+1} to $\mathcal{M}$ is attached with the interaction history $(x_1, y_1), \ldots, (x_t, y_t)$. This history is sufficient for determining the conditional distribution of the response $\mathcal{M}((x_i, y_i)_{i \in [t]}, x_{t+1})$ without specifying the internal randomness and memory.

We make a distinction between mechanisms and systems. By "mechanism" we mean a differentially private algorithm $\mathcal{M}$ that holds a sensitive input d and answers queries about it. When applied to a concrete input d, $\mathcal{M}$ induces an interactive system, denoted by $\mathcal{M}^d$. According to the definition of differential privacy, studying the privacy of a mechanism boils down to studying the pair of systems $(\mathcal{M}^d, \mathcal{M}^{d'})$ induced by running $\mathcal{M}$ on every pair of neighboring inputs (d, d'). For brevity, we usually assume W.L.O.G. that the input only consists of a single bit $b \in \{0, 1\}$, and we compare the two systems $\mathcal{M}^0, \mathcal{M}^1$ induced by $\mathcal{M}$.

Concurrent composition. We define concurrent composition of interactive systems. Suppose $\mathcal{M}_1, \mathcal{M}_2, \ldots, \mathcal{M}_k$ are k systems. The concurrent composition of them is an interactive system $\mathrm{COMP}(\mathcal{M}_1 \ldots \mathcal{M}_k)$ with query domain $[k] \times \mathcal{X}$ and response domain $\mathcal{Y}$. An adversary is a (possibly randomized) query algorithm $\mathcal{A} \colon ([k] \times \mathcal{X} \times \mathcal{Y})^* \to \Delta([k] \times \mathcal{X})$. The interaction between $\mathcal{A}$ and $\mathrm{COMP}(\mathcal{M}_i)$ is a stochastic process that runs as follows. $\mathcal{A}$ first[1] computes a pair $(i_1, x_1) \in [k] \times \mathcal{X}$, sends a query x_1 to $\mathcal{M}_{i_1}$ and gets the response y_1. In the t-th step, $\mathcal{A}$ calculates the next pair (i_t, x_t) based on the history, sends the t-th query x_t to $\mathcal{M}_{i_t}$ and receives y_t. There is no communication or interaction between the interactive systems. Each system $\mathcal{M}_i$ can only see its own interaction with $\mathcal{A}$. Let $\mathbf{IT}(\mathcal{A} \colon \mathcal{M}_1, \ldots, \mathcal{M}_k)$ denote the random variable recording the transcript of the interaction.

In the special case $k = 1$, there is only one system $\mathcal{M}$ and the adversary is interacting with it. We define approximate differential privacy for interactive mechanisms in this case.

Definition 2 (Indistinguishability and (ε, δ)-DP). Two interactive systems $\mathcal{M}^0, \mathcal{M}^1$ are called (ε, δ)-indistinguishable, if for every $b \in \{0, 1\}$, every adversary $\mathcal{A}$ and every collection of transcripts

---

[1] We assume it is always the adversary who sends the first message. This is without loss of generality: we can let the first message sent from the adversary to each system be an "Initiliazation" instruction.

87 $S \subseteq \{(x_i, y_i)_{i \in [T]}\}$, it holds that

$$\Pr[\mathbf{IT}(\mathcal{A} : \mathcal{M}^b) \in S] \le e^\varepsilon \Pr[\mathbf{IT}(\mathcal{A} : \mathcal{M}^{1-b}) \in S] + \delta. \tag{1}$$

88 Let $\mathcal{M}$ be an interactive mechanism. $\mathcal{M}$ is called (α, ε)-approximate differentially private (or
89 (ε, δ)-DP for short), if for every two neighboring data sets d and d', the systems $\mathcal{M}^d$ and $\mathcal{M}^{d'}$ are
90 (ε, δ)-indistinguishable.

1.2 Differential Privacy in Concurrent Compositions

92 We study the privacy guarantee under concurrent compositions. Let $\mathcal{M}_1^b, \ldots, \mathcal{M}_k^b$ be k interactive
93 mechanisms, each satisfying (ε, δ)-DP. Consider their concurrent composition $\mathrm{COMP}(\mathcal{M}_1^b \ldots \mathcal{M}_k^b)$.
94 We want to find out the smallest parameters ε', δ' such that $\mathrm{COMP}(\mathcal{M}_i^b)$ satisfies (ε', δ')-DP. In the
95 sequential composition, the adversary $\mathcal{A}$ interacts with $\mathcal{M}_i$'s in order and cannot interleave its queries.
96 In this case, it is known by the advanced composition theorem [Dwork et al., 2010] that $\mathbf{IT}(\mathcal{A} :$
97 $\mathcal{M}_1^0, \ldots, \mathcal{M}_k^0)$ and $\mathbf{IT}(\mathcal{A} : \mathcal{M}_1^1, \ldots, \mathcal{M}_k^1)$ are $(O(\sqrt{k \log(1/\delta')}\varepsilon), k\delta + \delta')$-indistinguishable.

98 However, in general, the adversary can interleave its queries arbitrarily, and the differential privacy
99 guarantee warranted by $\mathrm{COMP}(\mathcal{M}_i)$ is less clear. Vadhan and Wang [2021] were the first to formally
100 study this question. They showed that in the special case $\delta = 0$, an optimal composition holds for
101 $\mathrm{COMP}(\mathcal{M}_i)$. That is, if we can prove an (ε', δ') upper bound on the privacy parameter for sequential
102 compositions of $\mathcal{M}_1^b, \ldots, \mathcal{M}_k^b$, then the concurrent composition $\mathrm{COMP}(\mathcal{M}_i)$ also enjoys the same
103 (ε', δ')-DP.

104 Vadhan and Wang [2021] also considered the case $\delta > 0$ (i.e., approximate DP). However, for this
105 case, they only showed an upper bound on ε', δ' that is inferior to the basic composition in the
106 sequential setting. It was asked as an open question in Vadhan and Wang [2021] whether the optimal
107 composition theorem for approximate DP still holds in the concurrent composition.

108 Besides pure and approximate DP, there are also other notions of differential privacy that are
109 extensively studied in the literature. A non-exhaustive list includes Rényi DP [Mironov, 2017],
110 concentrated DP [Dwork and Rothblum, 2016, Bun and Steinke, 2016, Bun et al., 2018], Gaussian
111 DP and f-DP [Dong et al., 2022] etc. Compared with the standard notion of (ε, δ)-approximate DP,
112 these variants of DP either allow for a simplified analysis of private algorithms or give sharper bounds
113 of privacy guarantee. In the sequential composition, the composition property of these variants has
114 been well understood. It is also interesting to extend these composition theorems to the concurrent
115 composition, thereby expanding the potential applicability of these DP notions.

2 Our Results

117 In this work, we give an affirmative answer to the open question mentioned above. Moreover, our
118 result confirms that several major differential privacy definitions in the literature enjoy the same
119 composition guarantee in the concurrent composition, just as they do in the sequential composition.

120 **Approximate differential privacy.** (ε, δ)-DP is arguably the most widely studied notion of differ-
121 ential privacy and is deemed the "standard" definition of DP. As our first main result, we show an
122 optimal concurrent composition theorem for approximate DP.

123 **Theorem 1.** *Let $\mathcal{M}_1, \ldots, \mathcal{M}_k$ be k interactive mechanisms that run on the same data set. Suppose*
124 *that each mechanism $\mathcal{M}_i$ satisfies $(\varepsilon_i, \delta_i)$-DP. Then $\mathrm{COMP}(\mathcal{M}_1 \ldots \mathcal{M}_k)$ is (ε', δ')-DP, where ε', δ'*
125 *are given by the optimal (sequential) composition theorem [Kairouz et al., 2015, Murtagh and Vadhan,*
126 *2018].*

127 *In particular, when the privacy parameter for each mechanism is the same (ε, δ), their concurrent*
128 *composition satisfies $O(\sqrt{k \log(1/\delta')}\varepsilon, \delta' + k\delta)$-DP for all $\delta' \in (0, 1)$.*

129 **Rényi differential privacy.** Rényi differential privacy was first defined by Mironov [2017]. We recall
130 its definition.

131 **Definition 3** (Rényi divergence and differential privacy). *Let P, Q be two distributions supported*
132 *over $\mathcal{X}$. For each $\alpha > 1$, define the Rényi divergence of order α of P from Q as*

$$D_\alpha(P \| Q) := \frac{1}{\alpha - 1} \log \left(\mathop{\mathbb{E}}_{x \sim P} \left[\left(\frac{P(x)}{Q(x)} \right)^{\alpha - 1} \right] \right).$$

Two interactive systems are called (α, ε)-Rényi close, if for every adversary $\mathcal{A}$ and every $b \in \{0, 1\}$, it holds that

$$D_\alpha(\mathbf{IT}(\mathcal{A} : \mathcal{M}^b) \| \mathbf{IT}(\mathcal{A} : \mathcal{M}^{1-b})) \leq \varepsilon.$$

Let $\mathcal{M}$ be a mechanism. $\mathcal{M}$ is called (α, ε)-Rényi differentially private (or (α, ε)-RDP for short), if for every two neighboring data sets d and d', the systems $\mathcal{M}^d$ and $\mathcal{M}^{d'}$ are (α, ε)-Rényi close.

A main advantage of Rényi DP is that it has a natural and simple composition. In the sequential setting, it is known that if two mechanisms $\mathcal{M}_1, \mathcal{M}_2$ are (α, ε_1) and (α, ε_2)-RDP, respectively, then the composition of $\mathcal{M}_1$ and $\mathcal{M}_2$ is $(\alpha, \varepsilon_1 + \varepsilon_2)$-RDP. Our next theorem generalizes this result to the concurrent composition.

Theorem 2. *Let $\mathcal{M}_1, \ldots, \mathcal{M}_k$ be k interactive mechanisms that run on the same data set. Suppose that each mechanism $\mathcal{M}_i$ is (α, ε_i)-RDP. Then $\mathrm{COMP}(\mathcal{M}_1 \ldots \mathcal{M}_k)$ is $(\alpha, \sum_{i=1}^k \varepsilon_i)$-RDP.*

One implication of Theorem 2 is that the zero-concentrated differential privacy by Bun and Steinke [2016] and the truncated concentrated differential privacy by Bun et al. [2018] also compose nicely under the concurrent composition. We state the corollary below, and prove it in Appendix for completeness.

Corollary 1. *Let $\mathcal{M}_1, \ldots, \mathcal{M}_k$ are k interactive mechanisms that run on the same data set. Suppose that each mechanism $\mathcal{M}_i$ is η_i-zCDP (resp. (ρ_i, ω)-tCDP). Then $\mathrm{COMP}(\mathcal{M}_1 \ldots \mathcal{M}_k)$ is $(\sum_i \eta_i)$-zCDP (resp. $(\sum_i \rho_i, \omega)$-tCDP).*

Theorem 1, 2 and Corollary 1 provide compelling evidence that the adversary gains no advantage by interleaving its queries to independently running mechanisms. Consequently, interactivity can be viewed as a feature that differential privacy grants us for free.

Concurrent and independent work. Concurrently to our work, a recent work by Vadhan and Zhang [2022] proves optimal concurrent composition theorems for all standard variants of DP, including approximate DP, Rényi DP, concentrated DP considered in this work, as well as f-DP [Dong et al., 2022]. However, we remark that our techniques are very different than theirs. In particular, our proof for approximate DP is arguably more elementary: we do not need to work through f-DP as their proof does. Besides, our proof comes with several interesting technical ingredients that might be of independent interests. This includes a structural result for interactive mechanisms (Theorem 3), as well as a dual perspective to reason about Rényi divergences (Lemma 4).

3 Implications of Our Results

In this section, we discuss implications of our results, and demonstrate how they offer more than the sequential composition theorems.

Designing new algorithms. The optimal concurrent composition theorem makes it possible to design new differentially private algorithm that involves running several building blocks concurrently. As one motivating example, consider the Sparse Vector Technique (SVT). The standard SVT (as in Dwork and Roth [2014]) and its variants have been studied extensively in the literature. In particular, it was observed by Lyu et al. [2017], Zhu and Wang [2020] that one can add noise to the threshold only *once*, and then use the noisy threshold to answer $c > 1$ "meaningful" queries (namely, after reporting each meaningful query, the SVT algorithm does NOT refresh the noisy threshold). It was argued in [Lyu et al., 2017, Zhu and Wang, 2020] that this variant of SVT can offer a higher accuracy while consuming the same amount of privacy budget, both theoretically and empirically.

However, this variant of SVT has received relatively less attention in literature. We think one reason is that it is unclear what happens if we compose this SVT with other mechanisms. In particular, the standard SVT refreshes its threshold after answering each "meaningful" query, which allows one to decompose the algorithm into c pieces of smaller SVT algorithms, and then compose with other mechanisms via the sequential computation. In contrast, the variants by Lyu et al. [2017], Zhu and Wang [2020] work by answering each "meaningful query" using the *same* noisy threshold, which do not seem to admit such a decomposition. This makes this variant less appealing: in most applications, people want to use SVT as a supporting subroutine for other algorithms. Therefore, it is crucial to understand the (concurrent) composition behavior of SVT with other mechanisms.

Now, with the new concurrent composition theorem, we can plug this variant of SVT in any algorithm, and argue the privacy guarantee of the whole computation by black-box applying Theorems 1 and 2 (depending on whether we are working with (ε, δ)-DP or RDP). To illustrate the idea, in Appendix, we apply Theorem 1 to analyze a simple algorithm: private "Guess-and-Check" with the aforementioned variant of SVT as a subroutine. We hope our example can motivate people to design more powerful algorithms by concurrently composing simple building blocks.

Practical Implication. Besides the theoretical interests, our theorem has implications for practical deployments of interactive DP mechanisms. For one example, suppose there is a data center that holds the private information of individuals and offers data analysts access to the database (interactively and differentially-privately). Without knowing the concurrent composition theorem, it might be possible that some $k > 1$ analysts can collude by coordinating their (interactive) queries to the database and extracting much more sensitive information. Our result refutes the possibility of such an attack. In particular, suppose each data analyst has only an (ε, δ)-DP amount of privacy "quota". Then, even if they collude and spend their privacy budget in whatever way, their computation result is still $(O(\sqrt{k \log(1/\delta')}\varepsilon), k\delta + \delta')$-DP with respect to the private database.

4 Proof of Main Results

In this section, we show the proof of our results. We start with a very brief proof overview. We prove Theorem 1 by a reduction to the sequential composition of k (approximate) randomized response mechanisms. This generalizes the idea developed by Vadhan and Wang [2021]. To prove Theorem 2, we take a completely different approach, and our technique offers new tools to analyze Rényi DP. Namely, we propose an alternative characterization of Rényi divergence (Lemma 4), which allows for a fine-grained account of the privacy loss in the complex interaction involving multiple mechanisms. The characterization of Rényi divergence might find itself useful in other applications.

Notation. Let P, Q be two distributions supported over X. For a real $\eta > 0$, we say that $P \geq \eta Q$, if for every $S \subseteq X$, it holds that
$$\Pr_{x \sim P}[x \in S] \geq \eta \Pr_{x \sim Q}[x \in S].$$
Furthermore, we say $P \equiv Q$, if P and Q are identically distributed.

4.1 Approximate Differential Privacy

To prove Theorem 1, we follow the approach by Vadhan and Wang [2021], where they showed that one can simulate two $(\varepsilon, 0)$-indistinguishable interactive systems by post-processing a randomized response mechanism. This simulation enables them to reduce the concurrent composition to a sequential composition, and the optimal composition theorem follows. It was asked as an open question in Vadhan and Wang [2021] whether the same simulation can be carried out for approximate DP. We answer this question affirmatively.

Review of the Vadhan-Wang approach. It would be instructive to review the proof by Vadhan and Wang [2021] first. Let $\mathcal{M}^0, \mathcal{M}^1$ be the pair of systems by running the private mechanism on a pair of neighboring data sets. The adversary $\mathcal{A}$ interacts with $\mathcal{M}^b$ for some $b \in \{0, 1\}$ and wants to find out the value of b. An intuitive yet delicate fact due to Vadhan and Wang [2021] is that, if $\mathcal{M}^0$ and $\mathcal{M}^1$ are $(\varepsilon, 0)$-indistinguishable, then there exist two systems $\mathcal{N}^0, \mathcal{N}^1$ such that, for every adversary $\mathcal{A}$, the distribution of $\mathbf{IT}(\mathcal{A} : \mathcal{M}^b)$ is identical to $\frac{e^\varepsilon}{1+\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^b) + \frac{1}{1+e^\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^{1-b})$. This enables one to simulate the many-round interaction between $\mathcal{A}$ and $\mathcal{M}^b$ by running a one-round randomized response mechanism.

In more detail, let $\mathrm{RR}_\varepsilon^b$ denote the standard randomized response mechanism, defined as follows. $\mathrm{RR}_\varepsilon^b$ only accepts one query. On the query, $\mathrm{RR}_\varepsilon^b$ ignores the query message, returns b with probability $\frac{e^\varepsilon}{1+e^\varepsilon}$, and returns $1 - b$ otherwise. We modify $\mathcal{A}$ to a new adversary $\mathcal{A}'$: $\mathcal{A}'$ first sends a query to $\mathrm{RR}_\varepsilon^b$ and receives a bit b'. Then $\mathcal{A}'$ simulates the interaction between $\mathcal{A}$ and $\mathcal{N}^{b'}$, and outputs the transcript (i.e., $\mathbf{IT}(\mathcal{A} : \mathcal{N}^{b'})$). Let $\mathbf{Output}(\mathcal{A}' : \mathrm{RR}_\varepsilon^b)$ denote the output distribution of $\mathcal{A}'$ when interacting with $\mathrm{RR}_\varepsilon^b$. It is clear that

$$\mathbf{Output}(\mathcal{A}' : \mathrm{RR}_\varepsilon^b) \equiv \frac{e^\varepsilon}{1+\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^b) + \frac{1}{1+e^\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^{1-b}) \equiv \mathbf{IT}(\mathcal{A} : \mathcal{M}^b).$$

229 Therefore, $\mathcal{A}'$ simulates the interaction between $\mathcal{A}, \mathcal{M}^b$ faithfully, by a single query to $\mathrm{RR}_\varepsilon^b$.

230 Now, suppose the adversary $\mathcal{A}$ is interacting with k mechanisms $\mathcal{M}_1^b, \ldots, \mathcal{M}_k^b$ in parallel. For
231 each $i \in [k]$, assuming that $\mathcal{M}_i^0$ and $\mathcal{M}_i^1$ are $(\varepsilon_i, 0)$-indistinguishable, there is a decomposition
232 of $\mathcal{M}_i^0, \mathcal{M}_i^1$ by some $\mathcal{N}_i^0$ and $\mathcal{N}_i^1$. Again, we modify $\mathcal{A}$ to a new mechanism $\mathcal{A}'$. $\mathcal{A}'$ first queries
233 $\mathrm{RR}_{\varepsilon_i}^b, i \in [k]$ in order, and receives k bits $b_1', \ldots, b_k'$. Then $\mathcal{A}'$ simulates the interaction between $\mathcal{A}$
234 and $(\mathcal{N}_i^{b_i'})_{i \in [k]}$ and outputs the transcript. One can show that

$$\mathbf{Output}(\mathcal{A}' : \mathrm{RR}_{\varepsilon_1}^b, \ldots, \mathrm{RR}_{\varepsilon_k}^b) \equiv \mathbf{IT}(\mathcal{A} : \mathcal{M}_1^b, \ldots, \mathcal{M}_k^b). \tag{2}$$

235 Note that the left hand side of (2) can be simulated by the sequential composition of k randomized
236 response mechanisms. Invoking the optimal composition theorem for sequential composition [Kairouz
237 et al., 2015, Murtagh and Vadhan, 2018] concludes the proof.

Extension to approximate DP. Now, if $\mathcal{M}^0$ and $\mathcal{M}^1$ are (ε, δ)-indistinguishable with $\delta > 0$,
239 there might not be a nice decomposition of $\mathcal{M}^b$ into $\frac{e^\varepsilon}{1+e^\varepsilon}\mathcal{N}^b + \frac{1}{1+e^\varepsilon}\mathcal{N}^{1-b}$. Still, it is plausible to
240 conjecture that there is a decomposition of $\mathcal{M}^0, \mathcal{M}^1$ with four systems $\mathcal{N}^0, \mathcal{N}^1, \mathcal{E}^0, \mathcal{E}^1$ such that for
241 each $b \in \{0, 1\}$,

$$\mathcal{M}^b = \delta\mathcal{E}^b + (1 - \delta)\left(\frac{e^\varepsilon}{1 + e^\varepsilon}\mathcal{N}^b + \frac{1}{1 + e^\varepsilon}\mathcal{N}^{1-b}\right). \tag{3}$$

242 Our main technical result in this subsection proves the existence of such a decomposition.

243 **Theorem 3.** *Two systems $\mathcal{M}^0, \mathcal{M}^1$ are (ε, δ)-indistinguishable, if and only if there are four systems*
244 *$\mathcal{N}^0, \mathcal{N}^1, \mathcal{E}^0, \mathcal{E}^1$ satisfying the following: for every adversary $\mathcal{A}$ and $b \in \{0, 1\}$, it holds that*

$$\mathbf{IT}(\mathcal{A} : \mathcal{M}^b) \equiv \delta\mathbf{IT}(\mathcal{A} : \mathcal{E}^b) + (1 - \delta)\left(\frac{e^\varepsilon}{1 + \varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^b) + \frac{1}{1 + e^\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^{1-b})\right). \tag{4}$$

245 Theorem 3 implies Theorem 1 by a similar reduction to (approximate) random response. For
246 completeness, we include a proof in Appendix.

247 We prove Theorem 3 by establishing a series of lemmas. In the following, we state these lemmas and
248 explain their intuition. We defer the formal proof to Appendix.

249 **Lemma 1.** *Suppose $\mathcal{M}^0, \mathcal{M}^1$ are (ε, δ)-indistinguishable. There are two systems $\mathcal{E}^0, \mathcal{E}^1$ satisfying*
250 *the following.*

251 - *For every adversary $\mathcal{A}$ and $b \in \{0, 1\}$, it holds that $\mathbf{IT}(\mathcal{A} : \mathcal{M}^b) \geq \delta \cdot \mathbf{IT}(\mathcal{A} : \mathcal{E}^b)$.*

252 - *For every adversary $\mathcal{A}$, every set of transcripts $S \subseteq \{(x_i, y_i)_{i \in [T]}\}$ and $b \in \{0, 1\}$, it holds*
253 *that*
$$\Pr[\mathbf{IT}(\mathcal{A} : \mathcal{M}^b) \in S] - \delta\Pr[\mathbf{IT}(\mathcal{A} : \mathcal{E}^b) \in S]$$
$$\leq e^\varepsilon\left(\Pr[\mathbf{IT}(\mathcal{A} : \mathcal{M}^{1-b}) \in S] - \delta\Pr[\mathbf{IT}(\mathcal{A} : \mathcal{E}^{1-b}) \in S]\right).$$

254 Roughly, Lemma 1 says that there are two systems $\mathcal{E}^0, \mathcal{E}^1$ that capture the low-probability "bad
255 behavior" of $\mathcal{M}^0, \mathcal{M}^1$. It is the primary technical contribution of this section.

256 **Lemma 2.** *Suppose $\mathcal{M}, \mathcal{E}$ are two systems such that for every adversary $\mathcal{A}$, it holds that $\mathbf{IT}(\mathcal{A} :$*
257 *$\mathcal{M}) \geq \delta\mathbf{IT}(\mathcal{A} : \mathcal{E})$. Then there is a system $\mathcal{N}$ such that for every adversary $\mathcal{A}$, it holds that*

$$\mathbf{IT}(\mathcal{A} : \mathcal{M}) \equiv \delta\mathbf{IT}(\mathcal{A} : \mathcal{E}) + (1 - \delta)\mathbf{IT}(\mathcal{A} : \mathcal{N}).$$

258 For intuition, suppose P, Q are two distributions such that $P \geq \delta Q$. Then one can easily find a
259 distribution Q' such that $P \equiv \delta Q + (1 - \delta)Q'$. The proof of Lemma 2 extends this simple idea.

260 **Lemma 3** (Vadhan and Wang [2021]). *Suppose $\mathcal{N}^0, \mathcal{N}^1$ are $(\varepsilon, 0)$-indistinguishable. Then there are*
261 *two systems $\mathcal{N}^{0'}, \mathcal{N}^{1'}$ such that for every adversary $\mathcal{A}$, it holds that*

$$\mathbf{IT}(\mathcal{A} : \mathcal{N}^b) \equiv \frac{e^\varepsilon}{1 + e^\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^{b'}) + \frac{1}{1 + e^\varepsilon}\mathbf{IT}(\mathcal{A} : \mathcal{N}^{(1-b)'}).$$

Wrap-up. We can conclude the proof for Theorem 3 now. The "if" direction is obvious: the existence of a decomposition satisfying (4) implies that $\mathcal{M}^0, \mathcal{M}^1$ are (ε, δ)-indistinguishable. For the other direction, we start by constructing $\mathcal{E}^0, \mathcal{E}^1$ using Lemma 1. Then we construct $\mathcal{N}^0, \mathcal{N}^1$ by Lemma 2. Lemma 1 and 2 together ensure that $\mathcal{N}^0$ and $\mathcal{N}^1$ are $(\varepsilon, 0)$-indistinguishable, which enables us to invoke Lemma 3 and decompose $\mathcal{N}^0, \mathcal{N}^1$ into $\mathcal{N}^{0'}, \mathcal{N}^{1'}$. $(\mathcal{E}^0, \mathcal{E}^1, \mathcal{N}^{0'}, \mathcal{N}^{1'})$ forms the final decomposition. It is straightforward to verify that they satisfy (4).

4.2 Rényi Differential Privacy

Our result for Rényi differential privacy (Theorem 2) takes a completely different approach.

An intuition. Let $\mathcal{M}_1$ be an (α, ε)-Rényi DP mechanism. Intuitively, (α, ε)-Rényi DP means that $\mathcal{M}_1$ has ε unit of privacy budget and can distribute it to T queries. Viewing the privacy budget as a form of "deposit", we hope to argue that two or more independently running mechanisms spend their deposit independently, and an adversary cannot trigger any mechanism to spend more privacy budget than it holds by interacting with other mechanisms.

However, unlike some intuitive and easy-to-measure resources such as time and energy, the notion of privacy loss looks somewhat illusive. Even worse, we need to reason about this elusive resource in a stochastic process consisting of interactions with multiple systems. It was not clear how one can quantify the privacy loss in such an interactive and complex process. Nonetheless, we manage to find a new approach to do so.

A new characterization for Rényi DP. We introduce a new characterization of Rényi divergence based on Hölder's inequality and duality. That is, we prove

Lemma 4 (An alternative characterization of Rényi divergence). *Suppose P, Q are two distributions supported over $\mathcal{Y}$. For every $\alpha > 1$ and $B \geq 0$, let $\beta = \frac{\alpha}{\alpha - 1}$ be the Hölder conjugate of α. The following statements are equivalent.*

- $D_\alpha(P\|Q) \leq B$.

- *For every function $h : \mathcal{Y} \to \mathbb{R}^{\geq 0}$, it holds that $\mathbb{E}_{y \sim P}[h(y)] \leq e^{\frac{B(\alpha-1)}{\alpha}} \mathbb{E}_{y \sim Q}[h(y)^\beta]^{1/\beta}$.*

Note that if we let $\alpha \to \infty$, then Lemma 4 converges to a characterization of pure-DP. That is, $D_\infty(P\|Q) \leq B$ if and only if $\Pr[P = y] \leq e^B \Pr[Q = y]$ for every $y \in \mathcal{Y}$.

Lemma 4 provides a convenient tool to reason about the privacy loss in an interactive environment consisting of multiple rounds. Intuitively, this is because Condition 2 in the statement above is more amenable to a "hybrid argument". However, to quantify the privacy loss during an interaction, we still need to find a way to track the privacy loss.

Measure theory setup. Before we continue, it would be more convenient to switch to a measure-theoretic language. Consider two measures P, Q on a space $\mathcal{Y}$ (P and Q are not necessarily probability measures), we say that P is β-dominated by Q, denoted by $P \preceq_\beta Q$, if for every measurable function $f : \mathcal{Y} \to \mathbb{R}^{\geq 0}$, it holds that

$$\|f\|_{P,1} := \int f(y) dP(y) \leq \left(\int f(y)^\beta dQ(y) \right)^{1/\beta} =: \|f\|_{Q,\beta}.$$

When $\mathcal{Y}$ is a finite set, the integral coincides with an equivalent summation. i.e.,

$$\int f(y) dP(y) = \sum_y P(y) f(y).$$

We will use integral and summation interchangeably.

In this notation, Lemma 4 can be equivalently stated as $D_\alpha(P\|Q) \leq B$ if and only if P is β-dominated by $e^B Q$ for $\beta = \frac{\alpha}{\alpha - 1}$.

The following lemma is essential for us.

Lemma 5. *Let $\mathcal{Y}_1 \times \mathcal{Y}_2$ be a space. Consider two distributions P, Q on $\mathcal{Y}_1 \times \mathcal{Y}_2$. Assume $\mathrm{supp}(P) = \mathrm{supp}(Q) = \mathcal{Y}_1 \times \mathcal{Y}_2$. Let P_1, P_2 be the margin of P on $\mathcal{Y}_1, \mathcal{Y}_2$. For each $y_1 \in \mathcal{Y}_1$, denote by $P_2|_{P_1 = y_1}$ the marginal distribution of y_2 conditioning on y_1. Also define the same notation for Q.*

Let $\beta \geq 1, B \geq 0$ be two reals. Let $\alpha = \frac{\beta}{\beta-1}$. For each $y_1 \in \mathcal{Y}_1$, define

$$\ell_1(y_1) = \inf_K \{K : P_2|_{P_1=y_1} \preceq_\beta K \cdot Q_2|_{Q_1=y_1}\} = \exp(D_\alpha(P_2|_{P_1=y_1}\|Q_2|_{Q_1=y_1})).$$

Suppose $P \preceq_\beta e^B Q$. Consider the measure spaces $(\mathcal{Y}_1, P_1(y_1) \cdot \ell_1(y_2)^{1/\beta})$ and $(\mathcal{Y}_1, Q_2)$. We have

$$P_1 \ell_1^{1/\beta} \preceq_\beta e^B Q_1.$$

Intuitively, the function $\ell(y_1)$ serves as the role of "privacy budget monitor". To see this, fix an adversary $\mathcal{A}$ and think of (y_1, y_2) as the responses of the system to the adversary[2]. After observing y_1, the adversary wants to distinguish between two conditional distributions $P_2|_{P_1=y_1}$ and $Q_2|_{Q_1=y_1}$. At this moment, $\ell(y_1)$ shows up as an upper bound of "extra information" that the adversary can extract by utilizing their second query. Alternatively, $\ell(y_1)$ quantifies the amount of the remaining privacy budget the mechanism has after outputting y_1. On average, the function $\ell_1(y_1)$ provides a fine-grained control of the privacy loss in the sense that $P_1 \ell_1^{1/\beta} \preceq_\beta e^B Q_1$.

Proof for a 3-round toy example. We are ready to describe the proof for Theorem 2. To illustrate the idea, we prove a toy case here and defer the full proof to Appendix. The proof for the toy case includes all the important ideas. Extending it to a full proof is straightforward.

We describe the toy scenario now. Suppose there are two mechanisms $\mathcal{M}_1, \mathcal{M}_2$ that run on a sensitive input bit $b \in \{0, 1\}$. The interaction consists of 3 rounds. The adversary $\mathcal{A}$ communicates with $\mathcal{M}_1, \mathcal{M}_2, \mathcal{M}_1$ in order, and outputs the response (y_1, y_2, y_3). For brevity, we assume that each response y_i contains a copy of the query message x_i, so that we recover the whole transcript $((x_1, y_1), (x_2, y_2), (x_3, y_3))$ only from the responses.

Let $P, Q \in \Delta(\mathcal{Y} \times \mathcal{Y} \times \mathcal{Y})$ be the output distribution when $\mathcal{A}$ interacts with $(\mathcal{M}_1^0, \mathcal{M}_2^0)$ and $(\mathcal{M}_1^1, \mathcal{M}_2^1)$, respectively. Suppose $\mathcal{M}_1, \mathcal{M}_2$ are $(\alpha, \varepsilon_1), (\alpha, \varepsilon_2)$-Rényi DP respectively. Our goal is to prove that

$$\max\{D_\alpha(P\|Q), D_\alpha(Q\|P)\} \leq \varepsilon_1 + \varepsilon_2.$$

We bound $D_\alpha(P\|Q)$ below. The bound for $D_\alpha(Q\|P)$ is symmetric. Be Lemma 4, it suffices to show that for every $h : \mathcal{Y} \times \mathcal{Y} \to \mathcal{Y} \to \mathbb{R}^{\geq 0}$ that

$$\sum_{y=(y_1,y_2,y_3)} P(y)h(y) \leq \left(e^{\varepsilon_1+\varepsilon_2} \sum_{y=(y_1,y_2,y_3)} Q(y)h(y)^\beta \right)^{1/\beta} \tag{5}$$

where $\beta = \frac{\alpha}{\alpha-1}$ is the Hölder conjugate of α. Let P_1, P_2, P_3 be the projection of P onto the three rounds, and let $P_i|_{y<i}$ denote the distribution of y_i conditioning on $y_1, \ldots, y_{i-1}$. Also define the same notation for Q. Then we write

$$\sum_{y=(y_1,y_2,y_3)} P(y)h(y) = \sum_{y_1} \left(P_1(y_1) \sum_{y_2} \left(P_2|_{y_1}(y_2) \sum_{y_3} P_3|_{y<3}(y_3)h(y) \right) \right). \tag{6}$$

For every $y_1 \in \mathcal{Y}$, let $\mathcal{M}_1^0|_{y_1}$ (resp. $\mathcal{M}_1^1|_{y_1}$) denote the interactive system $\mathcal{M}_1^0$ (resp. $\mathcal{M}_1^1$) *conditioning on* that it has answered y_1 to the first query (recall we have assumed that y_1 contains x_1). Formally, for every $b \in \{0, 1\}$, $(x_2, y_2), \ldots, (x_t, y_t)$ and x_{t+1}, define

$$\mathcal{M}_1^b|_{y_1}((x_j, y_j)_{2 \leq j \leq t}, x_{t+1}) := \mathcal{M}_1^b((x_j, y_j)_{1 \leq j \leq t}, x_{t+1}).$$

Next, define

$$\ell_1(y_1) := \exp\left(\sup_{A:\text{adversary}} \{D_\alpha\big(\mathbf{IT}(A : \mathcal{M}_1^0|_{y_1})\|\mathbf{IT}(A : \mathcal{M}_1^1|_{y_1}))\} \right). \tag{7}$$

---

[2]Although the query made by $\mathcal{A}$ is not explicitly recorded, the pair (y_1, y_2) can capture this information by requiring that each response y_i must be attached with the query message x_i. This does not leak any additional information because x_i is solely chosen by $\mathcal{A}$.

From Lemma 5, one can show that $P_1 \ell_1^{1/\beta} \preceq e^B Q_1$. Turning back to (5), we then have

$$\sum_{y_1} \left(P_1(y_1) \sum_{y_2} \left(P_2|_{y_1}(y_2) \sum_{y_3} P_3|_{y_{<3}}(y_3) \underline{h(y)} \right) \right) \tag{8}$$

$$\leq \sum_{y_1} \left(P_1(y_1) \sum_{y_2} \left(P_2|_{y_1}(y_2) \underline{\left(\ell_1(y_1) \sum_{y_3} Q_3|_{y_{<3}}(y_3) h(y)^\beta \right)^{1/\beta}} \right) \right) \tag{9}$$

$$\leq \sum_{y_1} \left(P_1(y_1) \left(e^{\varepsilon_2} \sum_{y_2} \left(Q_2|_{y_1}(y_2) \ell_1(y_1) \sum_{y_3} Q_3|_{y_{<3}}(y_3) h(y)^\beta \right) \right)^{1/\beta} \right) \tag{10}$$

$$= \sum_{y_1} \left(P_1(y_1) \ell_1(y_1)^{1/\beta} \underline{\left(e^{\varepsilon_2} \sum_{y_2} \left(Q_2|_{y_1}(y_2) \sum_{y_3} Q_3|_{y_{<3}}(y_3) h(y)^\beta \right) \right)^{1/\beta}} \right) \tag{11}$$

$$\leq \left(e^{\varepsilon_1 + \varepsilon_2} \sum_{y_1} \left(Q_1(y_1) \sum_{y_2} \left(Q_2|_{y_1}(y_2) \sum_{y_3} Q_3|_{y_{<3}}(y_3) h(y)^\beta \right) \right) \right)^{1/\beta} \tag{12}$$

$$= \left(e^{\varepsilon_1 + \varepsilon_2} \sum_{y} Q(y) h(y)^\beta \right)^{1/\beta}. \tag{13}$$

Here, we used inequalities of the form $\sum_y P(y) \cdot h(y) \leq \left(C \cdot \sum_y Q(y) \cdot h(y)^\beta \right)^{1/\beta}$ three times (they are (8) $\Rightarrow$ (9) $\Rightarrow$ (10) and (11) $\Rightarrow$ (12)). We use underlines to highlight the "h" part of each step in the deductions above.

(8) $\Rightarrow$ (9) is the most critical step. To see this, observe that knowing y_2 does not change the view of the first mechanism, because the second query is sent to the independently running mechanism $\mathcal{M}_2^b$. Therefore, $\mathcal{M}_1^b|_{y_1}$ remains the same after conditioning on *both* y_1 and y_2. Now, note that $P_3|_{y_{<3}}$ (resp. $Q_3|_{y_{<3}}$) exactly describes one round of interaction between the adversary and $\mathcal{M}_1^0|_{y_1}$ (resp. $\mathcal{M}_1^1|_{y_1}$). Consequently, the information leaked by y_3 must be subject to the bound (7) and the inequality holds. Having verified (8) $\Rightarrow$ (9), the steps (9) $\Rightarrow$ (10) and (11) $\Rightarrow$ (12) are straightforward.

Having justified (13) for every measure function h, we conclude that $D_\alpha(P\|Q) \leq e^{\varepsilon_1 + \varepsilon_2}$. A symmetric argument shows that $D_\alpha(Q\|P) \leq e^{\varepsilon_1 + \varepsilon_2}$. This completes the proof for the toy example.

Proof sketch for the general case. The proof for the general case extends the idea above with some minor twists. By induction, we only need to prove the composition theorem for the case with two mechanisms and many rounds. An issue worth noting is that $\mathcal{A}$ can choose the next query object based on previous responses. However, we can suppose without loss of generality that $\mathcal{A}$ always communicates with mechanisms alternately, by adding a vanilla query x^* to the query space. If the current mechanism is not the one $\mathcal{A}$ wishes to speak with, $\mathcal{A}$ just sends the vanilla query x^*. The mechanism then returns a fixed response, which does not leak any information. We refer to Appendix for the detail of the proof.

5 Conclusion and Future Directions

In this work, we consider the concurrent composition of interactive mechanisms. Regarding the general privacy guarantee under the concurrent composition, our result gives optimal composition theorems for several popular definitions of differential privacy, including (ε, δ)-DP and Rényi DP. Our work is purely theoretical, and we do not see any negative societal impacts it may cause.

For future directions, we ask whether one can use our composition theorems to design new differentially-private algorithms that may involve running several differentially-private mechanisms in parallel. It is also interesting to explore more practical implications of the concurrent composition phenomena.

References

Raef Bassily, Kobbi Nissim, Adam D. Smith, Thomas Steinke, Uri Stemmer, and Jonathan R. Ullman. Algorithmic stability for adaptive data analysis. *SIAM J. Comput.*, 50(3), 2021. doi: 10.1137/16M1103646. URL https://doi.org/10.1137/16M1103646.

Mark Bun and Thomas Steinke. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In Martin Hirt and Adam D. Smith, editors, *Theory of Cryptography - 14th International Conference, TCC 2016-B, Beijing, China, October 31 - November 3, 2016, Proceedings, Part I*, volume 9985 of *Lecture Notes in Computer Science*, pages 635–658, 2016. doi: 10.1007/978-3-662-53641-4_24. URL https://doi.org/10.1007/978-3-662-53641-4_24.

Mark Bun, Cynthia Dwork, Guy N. Rothblum, and Thomas Steinke. Composable and versatile privacy via truncated CDP. In Ilias Diakonikolas, David Kempe, and Monika Henzinger, editors, *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing, STOC 2018, Los Angeles, CA, USA, June 25-29, 2018*, pages 74–86. ACM, 2018. doi: 10.1145/3188745.3188946. URL https://doi.org/10.1145/3188745.3188946.

Jinshuo Dong, Aaron Roth, and Weijie J. Su. Gaussian differential privacy. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 84, 2022.

Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9(3-4):211–407, 2014. doi: 10.1561/0400000042. URL https://doi.org/10.1561/0400000042.

Cynthia Dwork and Guy N. Rothblum. Concentrated differential privacy. *CoRR*, abs/1603.01887, 2016. URL http://arxiv.org/abs/1603.01887.

Cynthia Dwork, Krishnaram Kenthapadi, Frank McSherry, Ilya Mironov, and Moni Naor. Our data, ourselves: Privacy via distributed noise generation. In Serge Vaudenay, editor, *Advances in Cryptology - EUROCRYPT 2006, 25th Annual International Conference on the Theory and Applications of Cryptographic Techniques, St. Petersburg, Russia, May 28 - June 1, 2006, Proceedings*, volume 4004 of *Lecture Notes in Computer Science*, pages 486–503. Springer, 2006a. doi: 10.1007/11761679_29. URL https://doi.org/10.1007/11761679_29.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam D. Smith. Calibrating noise to sensitivity in private data analysis. In Shai Halevi and Tal Rabin, editors, *Theory of Cryptography, Third Theory of Cryptography Conference, TCC 2006, New York, NY, USA, March 4-7, 2006, Proceedings*, volume 3876 of *Lecture Notes in Computer Science*, pages 265–284. Springer, 2006b. doi: 10.1007/11681878_14. URL https://doi.org/10.1007/11681878_14.

Cynthia Dwork, Moni Naor, Omer Reingold, Guy N. Rothblum, and Salil P. Vadhan. On the complexity of differentially private data release: efficient algorithms and hardness results. In Michael Mitzenmacher, editor, *Proceedings of the 41st Annual ACM Symposium on Theory of Computing, STOC 2009, Bethesda, MD, USA, May 31 - June 2, 2009*, pages 381–390. ACM, 2009. doi: 10.1145/1536414.1536467. URL https://doi.org/10.1145/1536414.1536467.

Cynthia Dwork, Guy N. Rothblum, and Salil P. Vadhan. Boosting and differential privacy. In *51th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2010, October 23-26, 2010, Las Vegas, Nevada, USA*, pages 51–60. IEEE Computer Society, 2010. doi: 10.1109/FOCS.2010.12. URL https://doi.org/10.1109/FOCS.2010.12.

Moritz Hardt and Guy N. Rothblum. A multiplicative weights mechanism for privacy-preserving data analysis. In *51th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2010, October 23-26, 2010, Las Vegas, Nevada, USA*, pages 61–70. IEEE Computer Society, 2010. doi: 10.1109/FOCS.2010.85. URL https://doi.org/10.1109/FOCS.2010.85.

Michael Hay, Marco Gaboardi, and Salil Vadhan. A programming framework for opendp, 2020. URL https://projects.iq.harvard.edu/files/opendp/files/opendp_programming_framework_11may2020_1_01.pdf.

Peter Kairouz, Sewoong Oh, and Pramod Viswanath. The composition theorem for differential privacy. In Francis R. Bach and David M. Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pages 1376–1385. JMLR.org, 2015. URL http://proceedings.mlr.press/v37/kairouz15.html.

Min Lyu, Dong Su, and Ninghui Li. Understanding the sparse vector technique for differential privacy. *Proc. VLDB Endow.*, 10(6):637–648, 2017. doi: 10.14778/3055330.3055331. URL http://www.vldb.org/pvldb/vol10/p637-lyu.pdf.

Ilya Mironov. Rényi differential privacy. In *30th IEEE Computer Security Foundations Symposium, CSF 2017, Santa Barbara, CA, USA, August 21-25, 2017*, pages 263–275. IEEE Computer Society, 2017. doi: 10.1109/CSF.2017.11. URL https://doi.org/10.1109/CSF.2017.11.

Jack Murtagh and Salil P. Vadhan. The complexity of computing the optimal composition of differential privacy. *Theory Comput.*, 14(1):1–35, 2018. doi: 10.4086/toc.2018.v014a008. URL https://doi.org/10.4086/toc.2018.v014a008.

Aaron Roth and Tim Roughgarden. Interactive privacy via the median mechanism. In Leonard J. Schulman, editor, *Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, Cambridge, Massachusetts, USA, 5-8 June 2010*, pages 765–774. ACM, 2010. doi: 10.1145/1806689.1806794. URL https://doi.org/10.1145/1806689.1806794.

Salil P. Vadhan. The complexity of differential privacy. In Yehuda Lindell, editor, *Tutorials on the Foundations of Cryptography*, pages 347–450. Springer International Publishing, 2017. doi: 10.1007/978-3-319-57048-8_7. URL https://doi.org/10.1007/978-3-319-57048-8_7.

Salil P. Vadhan and Tianhao Wang. Concurrent composition of differential privacy. In Kobbi Nissim and Brent Waters, editors, *Theory of Cryptography - 19th International Conference, TCC 2021, Raleigh, NC, USA, November 8-11, 2021, Proceedings, Part II*, volume 13043 of *Lecture Notes in Computer Science*, pages 582–604. Springer, 2021. doi: 10.1007/978-3-030-90453-1_20. URL https://doi.org/10.1007/978-3-030-90453-1_20.

Salil P. Vadhan and Wanrong Zhang. Concurrent composition theorems for all standard variants of differential privacy. *CoRR*, abs/2207.08335, 2022. doi: 10.48550/arXiv.2207.08335. URL https://doi.org/10.48550/arXiv.2207.08335.

Yuqing Zhu and Yu-Xiang Wang. Improving sparse vector technique with renyi differential privacy. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/e9bf14a419d77534105016f5ec122d62-Abstract.html.