Figure Captioning with Large Generative Models: A Survey

Abstract

Figures, such as charts, graphs, and scientific visualizations, are essential for communicating data-driven insights, yet their interpretation often depends on clear and informative captions. Recent advances in large generative models, particularly multimodal large language models (MLLMs), have enabled significant progress in automatic figure captioning. In this paper, we present the first comprehensive survey of figure captioning with large generative models. We introduce an intuitive taxonomy that categorizes these techniques across key dimensions. We formalize the figure captioning task, and provide a systematic overview of the underlying techniques. In addition, we survey benchmarks, datasets, and evaluation methodologies, including both traditional metrics and modern MLLM-as-a-judge approaches. Finally, we propose important open problems and future directions, including personalized caption generation, heterogeneous figure types, and high-fidelity figure understanding. This survey unifies recent progress and provides a foundation for advancing research at the intersection of vision, language, and scientific communication.

1 Introduction

Figures[1] are critical for communicating complex information across a wide range of domains (Chen et al., 2020; Corio and Lapalme, 1999; Feng and Lapata, 2013; Qian et al., 2021; Mittal et al., 1998; Demir et al., 2008; Zhang et al., 2024; Yan et al., 2025; Li et al., 2024, 2025a). However, their interpretability relies critically on the presence of clear, accurate, and semantically rich captions (Hsu et al., 2023, 2024). The task of figure captioning aims to generate natural language descriptions that effectively convey the salient patterns, key findings, and contextual insights in figures. As illustrated in Figure 1, high-quality captions may integrate six key dimensions, ranging from basic OCR and visual statistics to high-level takeaways and helpfulness.

---

[1]Figure, chart, visualization, diagram, and graph are often used synonymously in the literature.

Comparing change in GDP since 2004 for global and German economies. The Y-axis represents the *percentage change since 2004*, ranging from 0% to +80%, while the X-axis spans 2004 to 2016. The blue line denotes Global GDP growth, whereas the green line denotes German GDP growth. Both GDPs increased from 2004-09, peaking around +45%, but diverged afterward. The Global GDP continued a strong upward trajectory, reaching around +80% by 2015 whereas the German GDP was more volatile post-2009, fluctuating between +30% and +50%, and ultimately declining to around +30% in 2016. Overall, we see sustained global economic expansion after the 2008-09 crisis.

Figure 1: Overview of the figure-captioning task. High-quality captions integrate six criteria, highlighted in color to align with the example caption: **helpfulness** (improves understanding), **OCR** (mentions words from figure), **visual** (mentions visual characteristics, color, etc), **relations** (describe relationships), **stats** (mentions values from the figure), **takeaway** (describe conclusions or insights). See Section 5.2 for further details.

Despite rapid progress in figure captioning (Hsu et al., 2021; Yan et al., 2025; Yin et al., 2025), most existing approaches including those based on large generative models, remain limited in their ability to capture key findings and high-level insights conveyed by visualizations. Rather than generating captions that communicate the salient patterns, trends, or takeaways embedded in a figure, current methods predominantly extract and rephrase textual elements such as axis labels, titles, and legends. This reliance on surface-level textual cues overlooks the deeper semantic content and often fails to support effective interpretation or decision-making. As a result, figure captioning remains unsolved (Liu et al., 2025; Mukhopadhyay et al., 2024). One goal of this survey is to succinctly summarize existing figure captioning approaches and highlight the fundamental open problems and remaining challenges. We hope that the findings from this survey helps enable researchers to develop novel approaches that solve these challenges

Table 1:

Method	MODALITIES (Section 3)				TECHNIQUES (Section 4)						FIGURE TYPES (Section 2.2)							EVALUATION (Section 5)		
	Figure Only (§3.1)	Figure-Caption Pairs (§3.2)	Fig-Cap + Aux. Text (§3.3)	Conversational (§3.4)	In-Context (§4.1)	Fine-Tuning (§4.2)	RL / RLHF (§4.3)	Distillation (§4.4)	Retrieval/Hybrid (§4.5)	Personalization (§4.6)	Bar	Line	Scatter	Pie	Heatmap	Flowchart	Other	Human Evaluation	Traditional Metrics	M(LLM)-as-Judge
FigCAP (Chen et al., 2019)	✗	✓	✗	✗	✗	✗	✓	✗	✗	✗	✓	✓	✗	✓	✗	✗	✗	✗	✓	✗
SciCap (Hsu et al., 2021)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✓	✓	✗	✗	✓	✗	✓	✗
DePlot (Liu et al., 2022)	✗	✓	✗	✗	✓	✓	✗	✗	✗	✗	✓	✓	✗	✓	✗	✗	✗	✗	✓	✗
VisText (Tang et al., 2023)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗	✓	✗
StructChart (Xia et al., 2023)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗	✓	✗
ChartLlama (Han et al., 2023)	✗	✓	✗	✗	✓	✓	✗	✗	✗	✗	✓	✓	✓	✓	✓	✗	✓	✗	✓	✗
UniChart (Masry et al., 2023)	✗	✓	✗	✗	✗	✓	✗	✓	✗	✗	✓	✓	✗	✗	✗	✗	✗	✗	✓	✗
FigCaps-HF (Singh et al., 2023)	✗	✓	✗	✗	✗	✗	✓	✗	✗	✓	✓	✓	✗	✓	✗	✗	✗	✓	✓	✗
SciCap+ (Yang et al., 2024)	✗	✓	✓	✗	✗	✓	✗	✗	✗	✗	✓	✓	✓	✓	✗	✓	✓	✓	✓	✗
FlowLearn (Pan et al., 2024)	✗	✓	✗	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗	✗	✓	✗
ChartAssistant (Meng et al., 2024)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✗	✗	✗	✗	✓	✗	✓	✗
ChartThinker (Liu et al., 2024)	✗	✓	✓	✗	✓	✓	✗	✗	✓	✗	✓	✓	✓	✓	✗	✗	✗	✓	✓	✗
ChartGemma (Masry et al., 2024b)	✓	✗	✗	✗	✗	✓	✗	✓	✗	✗	✓	✓	✓	✓	✗	✗	✓	✗	✓	✗
FigurA11y (Singh et al., 2024)	✗	✗	✓	✓	✓	✗	✗	✗	✗	✗	✓	✓	✓	✓	✗	✓	✓	✓	✗	✗
ChartInstruct (Masry et al., 2024a)	✓	✗	✗	✗	✗	✓	✗	✓	✗	✗	✓	✓	✗	✗	✗	✗	✗	✓	✓	✗
LaMP-Cap (Ng et al., 2025c)	✗	✓	✓	✗	✓	✗	✗	✗	✗	✓	✓	✓	✓	✓	✗	✗	✗	✓	✓	✗
ChartCap (Lim et al., 2025)	✗	✓	✗	✗	✓	✓	✗	✗	✗	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✗
ChartMoE (Xu et al., 2025)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✓	✓	✗	✗	✓	✗	✓	✗
Arrow-Guided (Omasa et al., 2025)	✓	✗	✗	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓	✓	✓	✗	✓
Pluto (Srinivasan et al., 2025)	✗	✗	✓	✓	✓	✗	✗	✗	✗	✗	✓	✓	✓	✗	✗	✗	✓	✓	✗	✗
ChartVLM (Xia et al., 2025)	✗	✓	✗	✗	✗	✓	✗	✗	✗	✗	✓	✓	✓	✓	✓	✗	✓	✗	✓	✓

Table 1: Taxonomy of figure captioning methods categorized by input modalities, techniques, figure types, and evaluation metrics.

leading to significantly better captions.

Motivated by the increasing importance of this unsolved problem, we present the first comprehensive survey on figure captioning with large generative models. Our goal is to synthesize existing approaches, datasets, and evaluation methods, and to establish a roadmap for advancing research at the intersection of vision, language, and reasoning.

Summary of Main Contributions: A summary of the key contributions are as follows:

1. **A formalization of figure captioning as a unified multimodal generation problem.** We introduce a formal problem formulation that captures the multimodal nature of figure captioning. This formulation serves as a foundation for understanding how large generative models perceive, interpret, and describe figures.

2. **A survey and taxonomy of techniques for figure captioning.** We present a comprehensive taxonomy that organizes the approaches across two dimensions: input modalities and techniques.
   • **Input Modalities**: Figure-Only, Figure-Caption Pairs, Fig-Cap Pairs + Auxiliary Text, and Conversational Captioning
   • **Techniques**: In-Context, Fine-Tuning, RL/RLHF, Distillation, Retrieval/Hybrid, Personalization

   This taxonomy gives rise to a systematic framework for categorizing the capabilities and limitations of current methods. We provide a detailed summary of this taxonomy in Table 1.

3. **An in-depth evaluation framework for assessing caption quality and figure understanding.** We review evaluation metrics for figure captioning, covering reference based measures (e.g.,

ROUGE, BLEU), human centered criteria (e.g., takeaway, helpfulness), and emerging MLLM as a judge approaches. The survey highlights their limitations and calls for metrics focused on reasoning and content fidelity.

4. **A comprehensive overview of benchmarks and datasets for figure captioning.** We curate and categorize existing datasets based on key characteristics like figure type, task objective, and dataset size.

5. **An overview of key open problems and challenges that future work should address.** We identify key remaining challenges and failure cases that are important to solve in the future.

This survey offers a unified view of recent advances in figure captioning, providing a unified framework that serves as a basis for studying and developing more advanced approaches, datasets, and evaluations. By proposing intuitive taxonomies for these aspects, we aim to chart a path forward for researchers and practitioners building next-generation models that understand, describe, and interact with visual data. Table 2 also shows the trending of figure captioning research.

Scope of this Survey. While there has been a few recent surveys on image captioning (Thobhani et al., 2025; Salgotra et al., 2025), there is no survey focused on figure captioning. A related survey on chart understanding (Huang et al., 2024) covers a wider landscape of visualization analysis but does not deeply examine figure captioning as a standalone multimodal problem. Our work complements this by presenting, to our knowledge, the first focused and systematic survey of the figure-captioning task, its modeling paradigms, evaluation dimensions, and remaining challenges. Appendix E illustrates the difference between figure captioning and image captioning.

2 Problem Formulation

2.1 Preliminaries & Notation

Let $\mathcal{I}$ be the space of figures, where $I \in \mathbb{R}^{H \times W \times C}$ and $\mathcal{Y} = \bigcup_{T=1}^{T_{\max}} \mathcal{V}^T$ is the space of captions over vocabulary $\mathcal{V}$. A caption is $Y = (w_1, \ldots, w_T) \in \mathcal{Y}$. We use C to denote *additional context* available at generation time, with domain $\mathcal{C}$, such as surrounding text, document metadata, retrieved items, or dialogue history. Captioning is posed as conditional decoding:

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} s_\theta(Y \mid I, C), \qquad (1)$$

where $s_\theta(\cdot)$ is a scoring function (e.g., $\log p_\theta$). Evaluation compares $\hat{Y}$ with reference Y via a utility $Q(\hat{Y}, Y, I)$

2.2 Figure Types

Figures vary widely in form, each emphasizing different data or relationships. We categorize them into common types such as **bar**, **line**, **scatter**, and **pie** charts that represent core statistical patterns, and specialized types like **heatmaps** and **flowcharts** that show higher dimensional or structural relations. An **other** category covers domain specific or unconventional visualizations. This taxonomy captures real world diversity and informs captioning methods, since each type presents distinct reasoning and description challenges.

3 Input Modality

This section reviews prior studies on MLLM-based figure captioning, organized by the input modalities. We highlight representative approaches and provide a structured view of the diverse methodologies explored in this field.

3.1 Figure Only

Given a figure I, there is no additional context, we set $C = \phi$. In practice, $\hat{Y}$ is obtained via approximate decoding, such as greedy, beam, or nucleus sampling. Adapting pretrained MLLMs to figure captioning is difficult under limited labeled data. Prior work therefore relies on synthetic supervision via in-context exemplars or teacher-student distillation. ChartInstruct (Masry et al., 2024a) creates large-scale instruction data from chart tables, and ChartGemma (Masry et al., 2024b) extends this by generating visual instruction-tuning data directly from chart images to fine-tune student models. The same pipeline can support preference alignment and personalization by collecting human feedback, and training preference-aligned models, such as RLHF (Mnih et al., 2015; Ouyang et al., 2022).

Beyond synthetic data, structured guidance methods (Omasa et al., 2025) represent figures as graphs built from detected objects and text to improve grounding. Accessibility focused studies (Kakehi et al., 2024) examine summaries such as grouped bars that balance informativeness, accuracy, and cognitive load for visually impaired readers.

3.2 Figure-Caption Pairs

In this setting, the dataset is $\mathcal{D} = \{(I_i, Y_i)\}_{i=1}^n$ with $I_i \in \mathcal{I}$ and $Y_i \in \mathcal{Y}$. In training time, we set $C = Y_i$ and learn θ by maximizing $\sum_{i=1}^n \log p_\theta(Y_i \mid I_i)$. At test time, $C = \phi$.

Recent work improves paired data quality and supervision. VisText (Tang et al., 2023) augments

Year Range	# Papers (approx.)	Key Model Architecture	Representative Datasets
2016–2018	~24	CNN, RNN/LSTM, early attention models	DVQA (Kafle et al., 2018), FigureQA (Kahou et al., 2017)
2019–2021	~81	Transformer-based encoder-decoder	FigCap (Chen et al., 2019), SciCap (Hsu et al., 2021)
2022–2023	~137	Vision–language pre-training	DePlot (Liu et al., 2022), VisText (Tang et al., 2023), ACL-Fig (Karishma et al., 2023a)
2024–2025	~220	Large VLMs, instruction-tuned VLMs	ChartX (Xia et al., 2025), SciCap+ (Yang et al., 2024), LaMP-Cap (Ng et al., 2025b)

Table 2: Approximate publication volume and dominant modeling trends by period. To obtain these approximate publication counts, we conducted a manual Google Scholar search using a consistent set of keywords that directly relate to our survey scope. Specifically, we queried terms such as "figure captioning", "chart captioning", "scientific figure description", "diagram captioning", "plot captioning", and combinations of these with model architectures.

charts with tables and scene graphs, while ChartLlama (Han et al., 2023) and UniChart (Masry et al., 2023) leverage MLLMs for synthetic data creation and distillation. To reduce factual errors, ChartCap (Lim et al., 2025) proposes dense, type specific captions, and FlowLearn (Pan et al., 2024) contributes annotated scientific flowcharts for few shot evaluation.

Other approaches strengthen reasoning and simplify generation. FigCAP (Chen et al., 2019) models relations among chart elements, and structure aware contrastive learning (Sasaki, 2025) uses diagram code to construct hard examples that encourage fine grained understanding. A common pipeline converts charts to structured intermediates before generation, as in DePlot (Liu et al., 2022), StructChart (Xia et al., 2023), ChartAssistant (Meng et al., 2024), and ChartVLM (Xia et al., 2025), while ChartMoE (Xu et al., 2025) improves capacity via specialized experts. Beyond supervised tuning, FigCaps-HF (Singh et al., 2023) applies preference optimization, and LaMP-Cap (Ng et al., 2025c) supports personalized captioning using multimodal figure profiles.

3.3 Fig-Cap Pairs + Auxiliary Text

To formally define this setting, the dataset is:

$$\mathcal{D} = \{(I_i, Y_i, T_i)\}_{i=1}^n, \quad T_i \in \mathcal{T}$$

where T_i is the auxiliary text corresponding to the figure-caption pair. Using this triplet data naturally gives rise to two general regimes:

- *Auxiliary text available only at training:* In this setting, we do not have the auxiliary text at inference time. One possible approach is to learn a teacher distribution p_θ with $C = T_i$ and distill into a student q_ϕ that operates without C at test time. Intuitively, despite not having the auxiliary text for inference, by leveraging $\mathcal{D}$ for training,

we can optimize a model that generates better captions that accurately reflect the figure.

- *Auxiliary text available at both training and test:* When auxiliary text is available for both training and inference, we set $C = T_i$. One possibility is to learn a single conditional model $p_\theta(Y \mid I, C)$ and then leverage it to generate $\hat{Y}$.

Auxiliary text provides semantic grounding that improves caption fidelity. Prior work shows consistent gains from leveraging nearby context. Rojas et al. (Rojas and Carranza, 2024) fuse visual features with paragraph representations, SciCap+ (Yang et al., 2024) adds mention paragraphs and OCR tokens to enable joint visual and textual modeling, and Hsu et al. (Hsu et al., 2025) find that conditioning GPT 4V on surrounding paragraphs yields captions preferred by expert editors over author written ones.

When text is available only during training, teacher student distillation transfers contextual knowledge to a text free captioner. When text is available at inference, retrieval can supply it on demand. LaMP Cap (Ng et al., 2025c) builds multimodal figure profiles for personalized generation, and ChartThinker (Liu et al., 2024) combines retrieval with explicit reasoning to improve coherence and logical accuracy.

3.4 Conversational Captioning

In this setting, the input consists of a figure I together with a conversational history $C = \{(u_1, a_1), (u_2, a_2), \ldots, (u_m, a_m)\}$, where u_j and a_j denote the jth user query and model response, respectively. Since the models prior captions naturally appear in C, the conversation history already contains Y_{prev}, the previously generated captions

for I. Thus, the next caption $\hat{Y}$ is generated as:

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} \ p_\theta(Y \mid I, C)$$

As an aside, it is sometimes useful to explicitly distinguish the most recent caption Y_{prev} from the broader conversational context:

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} \ p_\theta(Y \mid I, C, Y_{\text{prev}})$$

This formulation captures multimodal assistants and figure grounded chat systems, where the goal is not only to describe visual content but also to follow user intent expressed in the dialogue. Compared to figure only captioning, effective generation requires grounding in both modalities and maintaining conversational consistency.

Practically, conversational captioning is often an iterative refinement process. Captions evolve through successive turns based on visual evidence and user feedback, with Y_{prev} serving as the anchor for revision and the conversation providing constraints and preferences. Pluto (Srinivasan et al., 2025) illustrates a mixed initiative workflow that combines MLLMs with heuristic parsing to support auto completion, verification, and guided edits, while FigurA11y (Singh et al., 2024) demonstrates interactive suggestions that help authors incrementally improve figure captions.

4 Techniques

This section overviews the main techniques used in various ways to solve the figure captioning problem. For a summary of the techniques and the settings applicable for each, see Table 5 in Appendix.

4.1 In-context

In-context techniques (Brown et al., 2020; Wei et al., 2022; Dong et al., 2022; Min et al., 2022) leverage a pretrained model $\mathcal{M}$ in its frozen state and guide its predictions by conditioning on exemplars or prompts at inference time, without modifying the model parameters (Liu et al., 2022; Han et al., 2023; Liu et al., 2024; Ng et al., 2025c; Lim et al., 2025; Omasa et al., 2025; Srinivasan et al., 2025). More formally, given a figure I and k figure-caption pairs $\{(I_j, Y_j)\}_{j=1}^k$ along with a prompt P, the model infers the following caption:

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} p_{\mathcal{M}}(Y \mid I, \{(I_j, Y_j)\}_{j=1}^k, P),$$

where the prompt P encodes instructions and formatting. This approach is especially attractive in data scarce settings, including zero and few shot regimes, enabling rapid adaptation to new domains.

Common variants include chain of thought prompting (Wei et al., 2022), instruction style prompts, and iterative prompting that progressively refines outputs. While in context learning provides a flexible, training free way to leverage pretrained MLLMs, performance is highly sensitive to prompt design and often yields weaker grounding than approaches that adapt model parameters.

4.2 Fine-tuning

Fine-tuning (Parthasarathy et al., 2024; Hu et al., 2022) adapts a pretrained base model to the figure–caption distribution by updating its parameters on a dataset $\mathcal{D} = \{(I_i, Y_i)\}_{i=1}^n$. The learning objective is typically formulated as cross-entropy under teacher forcing, which is equivalent to maximizing conditional likelihood of the ground-truth captions:

$$\hat{\theta} = \arg\max_{\theta} \sum_{i=1}^n \log p_\theta(Y_i \mid I_i).$$

This objective fits model parameters to the empirical training distribution. Unlike in-context methods that keep parameters fixed, fine-tuning updates them directly, ranging from full end-to-end optimization to parameter-efficient alternatives such as LoRA and adapters (Hu et al., 2022). Fine-tuning can target specific domains or individual users (see Sec. 4.6), enabling strong task adaptation and typically more stable, faithful captions. However, it requires labeled data and can overfit or reduce generality when the fine-tuning distribution is narrow.

4.3 RL & RLHF

Reinforcement learning (RL) (Sutton et al., 1998; Mnih et al., 2015; Schulman et al., 2017a; Mnih et al., 2013) techniques optimize captions with respect to a quality metric Q (*e.g.*, CIDEr, CLIP, or a human preference score) rather than a likelihood surrogate. Given a generated caption $\hat{Y}$ for figure I and reference caption Y, a scalar reward is computed as $r = Q(\hat{Y}, Y, I)$. Model parameters θ are then updated to maximize expected reward:

$$\nabla_\theta J(\theta) = \mathbb{E}_{\hat{Y} \sim p_\theta(\cdot|I)}\big[\nabla_\theta \log p_\theta(\hat{Y} \mid I)\, r\big],$$

where $p_\theta(\hat{Y} \mid I)$ is the models distribution over captions. Intuitively, captions that better capture factual content and relationships receive higher reward r, increasing their likelihood under p_θ. Unlike cross entropy fine tuning, which matches the empirical training distribution, reinforcement learning optimizes the target metric directly. With human preferences, RLHF (Christiano et al., 2017; Ouyang et al., 2022) replaces Q with a learned re-

ward model $R_\phi(I, \hat{Y})$ to better reflect human judgment, improving relevance and faithfulness. Common optimization choices include PPO (Schulman et al., 2017b) and DPO (Rafailov et al., 2023a), which have been applied to large captioning models (Rafailov et al., 2023b; Zhang et al., 2021), among others (Srivastava and Aggarwal, 2025). While this paradigm targets human preferred qualities such as informativeness and factuality, it depends on reliable reward signals and careful tuning, and can be costly and unstable in practice.

4.4 Distillation & Model Transfer

Distillation and model transfer methods (Hinton et al., 2015; Gou et al., 2021; Xu et al., 2024b) adapt a captioning model by first training a *teacher* that conditions on all available modalities, including the figure $I \in \mathcal{I}$, auxiliary text $T \in \mathcal{T}$, and the ground-truth captions Y_i that are paired with I_i in the dataset. The teacher parameters θ are optimized to maximize the likelihood of Y_i:

$$\hat{\theta} = \arg\max_\theta \sum_{i=1}^{n} \log p_\theta(Y_i \mid I_i, T_i).$$

Once trained, its distribution is distilled into a student $q_\phi(Y \mid I)$ with parameters ϕ by minimizing

$$\mathcal{L}_{\text{distill}} = \sum_{i=1}^{n} \text{KL}\Big[p_\theta(\cdot \mid I_i, T_i) \parallel q_\phi(\cdot \mid I_i)\Big],$$

where $\text{KL}[\cdot \parallel \cdot]$ measures divergence between teacher and student outputs. This formulation naturally gives rise to a two-stage process: (i) a teacher trained with full multimodal supervision (I, T, Y) and (ii) a distilled student that preserves the semantic grounding induced by T and Y but requires only I at inference. As a result, the student yields captions that remain faithful to the figure and aligned with the distribution of gold captions while being efficient and deployable in scenarios where auxiliary text is unavailable. Although distillation effectively compresses richer teacher supervision into smaller models, the student may inherit teacher biases or lose fine-grained reasoning that is not preserved during transfer.

4.5 Retrieval & Hybrid

Retrieval augments caption generation with non-parametric memory (Liu et al., 2024) and is commonly used as a component in hybrid pipelines. Given a figure I, a retrieval function $\mathcal{R}(I)$ selects top-k related figure–caption pairs $\{(I_j, Y_j)\}_{j=1}^{k}$ from a corpus, providing additional visual and textual evidence beyond the parametric knowledge in p_θ. The caption is then generated by conditioning jointly on the input figure and the retrieved examples:

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} p_\theta\big(Y \mid I, \mathcal{R}(I)\big).$$

This formulation combines learned priors with contextually relevant exemplars, often improving grounding and enabling rapid adaptation to new domains or figure styles without full retraining. However, performance is highly sensitive to retrieval quality, and the added retrieval and prompting pipeline increases system complexity and can reduce interpretability.

4.6 Personalization

Personalization adapts caption generation to an individual user by conditioning on user preferences, style, or interaction history (Singh et al., 2023; Ng et al., 2025c). Let U denote a user representation (e.g., an embedding from prior behavior or style cues), and generate

$$\hat{Y} = \arg\max_{Y \in \mathcal{Y}} p_\theta(Y \mid I, U),$$

where I is the input figure. In practice, U can be implemented via user-specific fine-tuning, in-context exemplars reflecting the user's style, or latent conditioning inferred from prior conversations. Personalization is especially important for assistive systems and figure-grounded agents, and can also operate at the level of broader personas when per-user data are scarce. While it improves stylistic alignment and domain conventions, it depends on reliable user signals and may reduce robustness when examples are limited or narrowly distributed.

4.7 Hybrid Approaches

Retrieval-Augmented In-Context Learning. Methods such as LaMP-Cap (Ng et al., 2025b) and ChartThinker (Liu et al., 2024) retrieve figures, captions, or paragraphs and insert them as in-context exemplars, enabling adaptation to author-specific style or domain structure. These systems leverage non-parametric memory alongside in-context reasoning.

Distillation for Fine-Tuning. UniChart (Masry et al., 2023), ChartInstruct (Masry et al., 2024a), and ChartGemma (Masry et al., 2024b) first use a teacher model to generate synthetic captions or structured supervision, then fine-tune a student model on the enriched data. This couples teacher supervision with parametric fine-tuning.

Generation with Intermediate Representations. Approaches such as DePlot (Liu et al., 2022), StructChart (Xia et al., 2023), ChartAssistant (Meng et al., 2024), and ChartVLM (Xia et al., 2025) produce an intermediate structured representation, such as tables, and then condition caption generation on it. This blends structured perception, intermediate reasoning, and generative modeling.

RLHF with Synthetic Supervision. Works like FigCaps-HF (Singh et al., 2025) apply RLHF on captions that are distilled or synthetically generated, combining supervised fine-tuning, teacher-based distillation, and reward-aligned optimization.

Retrieval-Enhanced Personalization. LaMP-Cap (Ng et al., 2025b) retrieves user-specific historical captions and feeds them into the prompt or encoder, blending retrieval with personalization and in-context learning.

In Table 1, we assign each method to the category corresponding to its dominant operational component, while this hybrid section clarifies overlaps for completeness.

5 Evaluation Metrics

In this section, we discuss evaluation criterion, and the fundamental evaluation methodology that can be used including traditional metrics, human evaluation, and MLLM-as-a-Judge. More details are in Appendix A.

5.1 Traditional Metrics

Traditional figure captioning is typically evaluated with text-similarity metrics such as BLEU (Papineni, 2002), ROUGE (Lin, 2004), METEOR (Banerjee and Lavie, 2005), and CIDEr (Vedantam et al., 2015), which measure N-gram overlap between generated and reference captions. Although efficient, these metrics poorly reflect human judgment and are sensitive to phrasing, length, and reference quality.

5.2 Human Evaluation

Recent studies (Hsu et al., 2025; Ng et al., 2025a; Hsu et al., 2023; Yang et al., 2024; Singh et al., 2023; Liu et al., 2024; Masry et al., 2024b,a; Singh et al., 2024; Ng et al., 2025c; Omasa et al., 2025; Srinivasan et al., 2025) advocate human centric evaluations that emphasize **informativeness**, **factual correctness**, and **structure** (Masry et al., 2024a,b), along with criteria such as **hallucination avoidance** (Lim et al., 2025), **reasoning correctness** (Liu et al., 2024), and **helpfulness**, **OCR**, **relation**, **stats**, **takeaway**, and **visual** quality (Hsu et al., 2023; Singh et al., 2023; Ng et al., 2025c).

A practical concern is score reliability across annotators and evaluation setups. Only a few works report agreement statistics: SciCap-EVAL (Yang et al., 2024) finds a Kendall correlation of 0.401 between GPT-4 zero-shot ratings and PhD students' rankings of helpfulness, with moderate agreement between two expert annotators on a subset. Recent multi-LLM collaborative captioning further reports low to moderate Fleiss' kappa (0.15–0.38) for best or worst caption selection, and the SciCap Challenge similarly observes modest Kendall values across judges (Kim et al., 2025), underscoring the difficulty of consensus.

In contrast, some chart captioning and visualization studies (Ashok, 2025) report high inter rater agreement under narrow, well specified coding schemes with trained annotators, suggesting stricter protocols can improve reliability at the cost of evaluation breadth. Overall, most figure captioning papers report at most small scale checks, and no common standard exists.

5.3 MLLM-as-a-Judge

To address the limits of reference based and human evaluations, recent work introduces MLLMs as judges (Chen et al., 2024; Gu et al., 2024). Pairwise methods such as AutoJ (Li et al., 2023) and PandaLM (Wang et al., 2023) train models on preference data for consistent judgments, while score based systems such as GEval (Liu et al., 2023) and JudgeLM (Zhu et al., 2023) provide aspect wise ratings (e.g., factuality, coherence, completeness) using GPT4 annotations. In figure captioning, GPT4 has proven effective as a zero shot evaluator aligned with expert judgments (Hsu et al., 2023).

6 Datasets

We summarize key figure captioning datasets in Table 3, comparing scale, visualization types, and task focus. Existing resources span from synthetic captioning benchmarks, such as FigCAP (Chen et al., 2019) to large-scale real-world corpora, such as SciCAP (Hsu et al., 2021). Recent extensions add richer supervision and new settings. SciCAP+ (Yang et al., 2024) incorporates OCR tokens and mention paragraphs for knowledge-augmented generation, while LaMP-Cap (Ng et al., 2025b) introduces personalized captioning conditioned on user writing style. Furthermore, Chart-to-Text (Kantharaj et al., 2022) and ChartSumm (Rahman et al., 2023) target insight-oriented summarization, and reasoning benchmarks such as FigureQA (Kahou et al., 2017), DVQA (Kafle et al., 2018), and ChartX (Xia et al., 2025) evaluate compositional and higher-order understanding across

Dataset Name	Data Size (Images / Text)	Visualization Types	Core Task
FigCAP (Chen et al., 2019)	100k images / 1.2M captions	Line, Dot-Line, Bar, Pie	Caption Generation
SciCAP (Hsu et al., 2021)	416k plots / 416k captions	Line, Scatter, Histogram, Bar	Scientific Captioning
SciCAP+ (Yang et al., 2024)	414k charts / 394k captions	Scientific figures (enhanced)	Knowledge-augmented captioning
LaMP-Cap (Ng et al., 2025c)	307k images / 110k captions	Line, Bar, Scatter, Histogram	Personalized Captioning
Chart-to-Text (Kantharaj et al., 2022)	44,096 images / 44,096 captions	Line, Bar, Pie, etc.	Chart-to-Text generation
ChartSumm (Xu et al., 2024a)	190k images / 1 90k summaries	Line, Bar, Pie, Scatter, Histogram	Chart Summarization
ACL-Fig (Karishma et al., 2023b)	112k figures / 1.67k labeled	19 academic figure types	Classification,QA,Captioning
FigureQA (Kahou et al., 2017)	100k images / 1.32M questions	Line, Dot-Line, Bar, Pie	Visual QA (Yes/No)
DVQA (Kafle et al., 2018)	300k images / 3.48M QA pairs	Vertical Bar, Horizontal Bar	Structure, Data, Reasoning
SciFIBench (Roberts et al., 2024)	- / 2k QA pairs	Line, Dor-Line, Bar, Line	Figure Interpretation
ChartX (Xia et al., 2025)	48k charts / 48k multimodal sets	Heatmap, Candlestick, Bar, Line, etc.	Multi-task Evaluation
SCICAP-EVAL (Hsu et al., 2023)	600 images / 3.6k captions	Line, Bar, Scatter (CV, NLP, HCI)	Caption Quality Evaluation

Table 3: Summary of key datasets used for training and evaluating MLLMs. Each dataset varies in image/text scale, covered chart types, and core tasks.

diverse chart types. Detailed dataset descriptions are deferred to Appendix B.

7 Open Problems & Challenges

This section discusses open problems and highlights important challenges for future work. Appendix C further ellaborates on these challenges.

Complex Figure Types: Emerging figure types such as animated, interactive, and immersive visualizations introduce significant challenges for figure captioning. Animated figures require temporal reasoning over motion and evolving semantics, while interactive figures demand captions that adapt to user-driven context and exploration. Immersive 3D or virtual environment figures add occlusion and viewpoint variation that complicate spatial understanding. These settings motivate models that ensure temporal consistency, incorporate user context, and reason over 3D structure.

Personalized Caption: Caption personalization adapts generation to either the author's style or the target reader's perspective. The former reflects the author's linguistic and interpretive preferences, while the latter accounts for the reader's background, intent, and potential biases. Future work should model both dimensions via data design, fine-tuning, and prompt conditioning.

Figure Editing: A main challenge in figure editing is generating a new figure that correctly reflects the given editing instructions while preserving the original layout and meaning. Models often struggle to modify only the intended parts without introducing visual errors or misleading changes. Future work should focus on maintaining both visual accuracy and data integrity during edits.

Captioning for Complex Figures: Most works have focused on generating captions for relatively simple chart types such as bar charts or line charts. Captioning for complex figures, such as flow charts or multi-panel figures with heterogeneous chart types, remains challenging. Such complex figures may require more advanced planning-based captioning techniques to ensure correctness and to maximize readability and understandability.

Attribution-Aware Grounding: One important open problem is attribution-aware and fine-grained grounding of captions to the insights, legend, and other parts of the figure. Achieving such grounding requires accurately linking textual claims to their precise visual or data sources, which is challenging due to overlapping visual elements, implicit references, and varying figure styles. Moreover, existing grounding models often lack fine-grained, attribution-aware evidence to justify insights.

Generated Caption Evaluation: Evaluating generated captions requires verifying whether key data-driven insights are both logically supported by the underlying dataset and correctly expressed in the caption. Emerging methods such as MLLM-as-a-Judge, combined with OCR-based text extraction and grounding (Jiang et al., 2019), offer promising automated evaluation strategies for assessing semantic and visual alignment. However, challenges remain in calibrating MLLMs' visual understanding and ensuring stable, human-aligned evaluation across diverse figure types.

8 Conclusions

This survey provides a comprehensive survey on figure captioning with large generative models through a unified framework along four input settings and six techniques. We reviewed an overview of existing methods to generate figure captions, summarized available datasets and benchmarks, discussed the evaluation metrics. Finally, we highlighted open challenges that point toward future research on complex and reliable figure captioning.

9 Limitations

While this survey aims to provide a comprehensive overview of figure captioning, it has several limitations. First, our main taxonomy is centered around the available input provided (figure only, figure-captions, and so on), then we categorize the works further by the general technique leveraged. While this taxonomy is intuitive, we could have also discussed works by other factors such as the categories of charts and other facets to the problem. Nevertheless, we did summarize all the works surveyed along with a few additional facets in Table 1 focused on the chart types supported and evaluation used.

10 Ethics

This survey aims to advance understanding of figure captioning in scientific contexts, and we aim to support researchers in developing robust and accurate figure captioning methods. All datasets referenced are publicly available and used solely for research purposes under their respective licenses. No personally identifiable or sensitive information was collected or used. Therefore, we do not anticipate any ethical issues emerging from this survey.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Tejas Tumakuru Ashok. 2025. Llm-powered chart captioning and insight generation: Towards trustworthy visualization narratives. *Authorea Preprints*.

Satanjeev Banerjee and Alon Lavie. 2005. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 65–72.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Charles Chen, Ruiyi Zhang, Eunyee Koh, Sungchul Kim, Scott Cohen, and Ryan Rossi. 2020. Figure captioning with relation maps for reasoning. In *2020 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pages 1526–1534.

Charles Chen, Ruiyi Zhang, Eunyee Koh, Sungchul Kim, Scott Cohen, Tong Yu, Ryan Rossi, and Razvan Bunescu. 2019. Figure captioning with reasoning and sequence-level training.

Dongping Chen, Ruoxi Chen, Shilin Zhang, Yaochen Wang, Yinuo Liu, Huichi Zhou, Qihui Zhang, Yao Wan, Pan Zhou, and Lichao Sun. 2024. Mllm-as-a-judge: Assessing multimodal llm-as-a-judge with vision-language benchmark. In *Forty-first International Conference on Machine Learning*.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30.

Marc Corio and Guy Lapalme. 1999. Generation of texts for information graphics. In *Proceedings of the 7th European Workshop on Natural Language Generation EWNLG'99*, pages 49–58.

Seniz Demir, Sandra Carberry, and Kathleen F McCoy. 2008. Generating textual summaries of bar charts. In *Proceedings of the Fifth International Natural Language Generation Conference*, pages 7–15.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Tianyu Liu, et al. 2022. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*.

Yansong Feng and Mirella Lapata. 2013. Automatic caption generation for news images. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(4):797–812.

Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. 2021. Knowledge distillation: A survey. *International journal of computer vision*, 129(6):1789–1819.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, et al. 2024. A survey on llm-as-a-judge. *arXiv preprint arXiv:2411.15594*.

Yucheng Han, Chi Zhang, Xin Chen, Xu Yang, Zhibin Wang, Gang Yu, Bin Fu, and Hanwang Zhang. 2023. Chartllama: A multimodal llm for chart understanding and generation.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*.

Ting-Yao Hsu, C Lee Giles, and Ting-Hao'Kenneth' Huang. 2021. Scicap: Generating captions for scientific figures. *arXiv preprint arXiv:2110.11624*.

Ting-Yao Hsu, Chieh-Yang Huang, Shih-Hong Huang, Ryan Rossi, Sungchul Kim, Tong Yu, C Lee Giles, and Ting-Hao Kenneth Huang. 2024. Scicapenter: Supporting caption composition for scientific figures with machine-generated captions and ratings. In *Extended Abstracts of the CHI Conference on Human Factors in Computing Systems*, pages 1–9.

Ting-Yao Hsu, Chieh-Yang Huang, Ryan Rossi, Sungchul Kim, C Lee Giles, and Ting-Hao K Huang. 2023. Gpt-4 as an effective zero-shot evaluator for scientific figure captions. *arXiv preprint arXiv:2310.15405*.

Ting-Yao E. Hsu, Yi-Li Hsu, Shaurya Rohatgi, Chieh-Yang Huang, Ho Yin Sam Ng, Ryan Rossi, Sungchul Kim, Tong Yu, Lun-Wei Ku, C. Lee Giles, and Ting-Hao K. Huang. 2025. Do large multimodal models solve caption generation for scientific figures? lessons learned from scicap challenge 2023.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. 2022. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3.

Kung-Hsiang Huang, Hou Pong Chan, May Fung, Haoyi Qiu, Mingyang Zhou, Shafiq Joty, Shih-Fu Chang, and Heng Ji. 2024. From pixels to insights: A survey on automatic chart understanding in the era of large foundation models. *IEEE Transactions on Knowledge and Data Engineering*, 37(5):2550–2568.

Ming Jiang, Qiuyuan Huang, Lei Zhang, Xin Wang, Pengchuan Zhang, Zhe Gan, Jana Diesner, and Jianfeng Gao. 2019. Tiger: Text-to-image grounding for image caption evaluation. *arXiv preprint arXiv:1909.02050*.

Kushal Kafle, Scott Cohen, Brian Price, and Christopher Kanan. 2018. Dvqa: Understanding data visualizations via question answering. In *CVPR*.

Samira Ebrahimi Kahou, Vincent Michalski, Adam Atkinson, Ákos Kádár, Adam Trischler, and Yoshua Bengio. 2017. Figureqa: An annotated figure dataset for visual reasoning. *arXiv preprint arXiv:1710.07300*.

Banri Kakehi, Masakazu Iwamura, Kazunori Minatani, and Koichi Kise. 2024. Grouping effect for bar graph summarization for people with visual impairments. In *Proceedings of the 26th International ACM SIGACCESS Conference on Computers and Accessibility*, pages 1–6.

Shankar Kantharaj, Rixie Tiffany Ko Leong, Xiang Lin, Ahmed Masry, Megh Thakkar, Enamul Hoque, and Shafiq Joty. 2022. Chart-to-text: A large-scale benchmark for chart summarization.

Zeba Karishma, Shaurya Rohatgi, Kavya Shrinivas Puranik, Jian Wu, and C Lee Giles. 2023a. Acl-fig: A dataset for scientific figure classification. *arXiv preprint arXiv:2301.12293*.

Zeba Karishma, Shaurya Rohatgi, Kavya Shrinivas Puranik, Jian Wu, and C. Lee Giles. 2023b. Acl-fig: A dataset for scientific figure classification.

Daniel A Keim. 2002. Information visualization and visual data mining. *IEEE transactions on Visualization and Computer Graphics*, 8(1):1–8.

Jaeyoung Kim, Jongho Lee, Hong-Jun Choi, Ting-Yao Hsu, Chieh-Yang Huang, Sungchul Kim, Ryan Rossi, Tong Yu, Clyde Lee Giles, Ting-Hao 'Kenneth' Huang, et al. 2025. Multi-llm collaborative caption generation in scientific documents. In *International Workshop on AI for Transportation*, pages 142–160. Springer.

Junlong Li, Shichao Sun, Weizhe Yuan, Run-Ze Fan, Hai Zhao, and Pengfei Liu. 2023. Generative judge for evaluating alignment. *arXiv preprint arXiv:2310.05470*.

Li Li, Wei Ji, Yiming Wu, Mengze Li, You Qin, Lina Wei, and Roger Zimmermann. 2024. Panoptic scene graph generation with semantics-prototype learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pages 3145–3153.

Shawn Li, Huixian Gong, Hao Dong, Tiankai Yang, Zhengzhong Tu, and Yue Zhao. 2025a. Dpu: Dynamic prototype updating for multimodal out-of-distribution detection. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 10193–10202.

Shawn Li, Jiashu Qu, Yuxiao Zhou, Yuehan Qin, Tiankai Yang, and Yue Zhao. 2025b. Treble counterfactual vlms: A causal approach to hallucination. *arXiv preprint arXiv:2503.06169*.

Junyoung Lim, Jaewoo Ahn, and Gunhee Kim. 2025. Chartcap: Mitigating hallucination of dense chart captioning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81.

Fangyu Liu, Julian Martin Eisenschlos, Francesco Piccinno, Syrine Krichene, Chenxi Pang, Kenton Lee, Mandar Joshi, Wenhu Chen, Nigel Collier, and Yasemin Altun. 2022. Deplot: One-shot visual language reasoning by plot-to-table translation. *arXiv preprint arXiv:2212.10505*.

Junteng Liu, Weihao Zeng, Xiwen Zhang, Yijun Wang, Zifei Shan, and Junxian He. 2025. On the perception bottleneck of vlms for chart understanding. *arXiv preprint arXiv:2503.18435*.

Mengsha Liu, Daoyuan Chen, Yaliang Li, Guian Fang, and Ying Shen. 2024. Chartthinker: A contextual chain-of-thought approach to optimized chart summarization. *arXiv preprint arXiv:2403.11236*.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: Nlg evaluation using gpt-4 with better human alignment. *arXiv preprint arXiv:2303.16634*.

Ahmed Masry, Parsa Kavehzadeh, Xuan Long Do, Enamul Hoque, and Shafiq Joty. 2023. Unichart: A universal vision-language pretrained model for chart comprehension and reasoning. *arXiv preprint arXiv:2305.14761*.

Ahmed Masry, Mehrad Shahmohammadi, Md Rizwan Parvez, Enamul Hoque, and Shafiq Joty. 2024a. Chartinstruct: Instruction tuning for chart comprehension and reasoning. *arXiv preprint arXiv:2403.09028*.

Ahmed Masry, Megh Thakkar, Aayush Bajaj, Aaryaman Kartha, Enamul Hoque, and Shafiq Joty. 2024b. Chartgemma: Visual instruction-tuning for chart reasoning in the wild. *arXiv preprint arXiv:2407.04172*.

Fanqing Meng, Wenqi Shao, Quanfeng Lu, Peng Gao, Kaipeng Zhang, Yu Qiao, and Ping Luo. 2024. ChartAssistant: A universal chart multimodal language model via chart-to-table pre-training and multitask instruction tuning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 7775–7803, Bangkok, Thailand. Association for Computational Linguistics.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? *arXiv preprint arXiv:2202.12837*.

Vibhu O Mittal, Johanna D Moore, Giuseppe Carenini, and Steven Roth. 1998. Describing complex charts in natural language: A caption generation system. *Computational Linguistics*, 24(3):431–467.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. 2013. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. 2015. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533.

Srija Mukhopadhyay, Adnan Qidwai, Aparna Garimella, Pritika Ramu, Vivek Gupta, and Dan Roth. 2024. Unraveling the truth: Do vlms really understand charts? a deep dive into consistency and robustness. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 16696–16717.

Ho Yin Ng, Ting-Yao Hsu, Jiyoo Min, Sungchul Kim, Ryan A. Rossi, Tong Yu, Hyunggu Jung, and Ting-Hao 'Kenneth' Huang. 2025a. Understanding how paper writers use ai-generated captions in figure caption writing. In *AI for Research and Scalable, Efficient Systems*, pages 173–192, Singapore. Springer Nature Singapore.

Ho Yin 'Sam' Ng, Ting-Yao Hsu, Aashish Anantha Ramakrishnan, Branislav Kveton, Nedim Lipka, Franck Dernoncourt, Dongwon Lee, Tong Yu, Sungchul Kim, Ryan A. Rossi, and Ting-Hao 'Kenneth' Huang. 2025b. Lamp-cap: Personalized figure caption generation with multimodal figure profiles.

Ho Yin 'Sam' Ng, Ting-Yao Hsu, Aashish Anantha Ramakrishnan, Branislav Kveton, Nedim Lipka, Franck Dernoncourt, Dongwon Lee, Tong Yu, Sungchul Kim, Ryan A Rossi, et al. 2025c. Lamp-cap: Personalized figure caption generation with multimodal figure profiles. *arXiv preprint arXiv:2506.06561*.

Takamitsu Omasa, Ryo Koshihara, and Masumi Morishige. 2025. Arrow-guided vlm: Enhancing flowchart understanding via arrow direction encoding. *arXiv preprint arXiv:2505.07864*.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Huitong Pan, Qi Zhang, Cornelia Caragea, Eduard Dragut, and Longin Jan Latecki. 2024. Flowlearn: Evaluating large vision-language models on flowchart understanding. *arXiv preprint arXiv:2407.05183*.

Kishore Papineni. 2002. Machine translation evaluation: N-grams to the rescue. In *LREC*.

Venkatesh Balavadhani Parthasarathy, Ahtsham Zafar, Aafaq Khan, and Arsalan Shahid. 2024. The ultimate guide to fine-tuning llms from basics to breakthroughs: An exhaustive review of technologies, research, best practices, applied research challenges and opportunities. *arXiv preprint arXiv:2408.13296*.

Xin Qian, Eunyee Koh, Fan Du, Sungchul Kim, Joel Chan, Ryan A Rossi, Sana Malik, and Tak Yeon Lee. 2021. Generating accurate caption units for figure captioning. In *Proceedings of the Web Conference 2021*, pages 2792–2804.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023a. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023b. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Raian Rahman, Rizvi Hasan, Abdullah Al Farhad, Md Tahmid Rahman Laskar, Md Hamjajul Ashmafee, and Abu Raihan Mostofa Kamal. 2023. Chartsumm: A comprehensive benchmark for automatic chart summarization of long and short summaries. In *Canadian AI*.

Jonathan Roberts, Kai Han, Neil Houlsby, and Samuel Albanie. 2024. Scifibench: Benchmarking large multimodal models for scientific figure interpretation. *Advances in Neural Information Processing Systems*, 37:18695–18728.

Mateo Alejandro Rojas and Rafael Carranza. 2024. Enhancing scientific figure captioning through cross-modal learning. *arXiv preprint arXiv:2406.17047*.

Garima Salgotra, Pawanesh Abrol, and Arvind Selwal. 2025. A survey on automatic image captioning approaches: Contemporary trends and future perspectives. *Archives of Computational Methods in Engineering*, 32(3):1459–1497.

Hiroshi Sasaki. 2025. Structure-aware contrastive learning for diagram understanding of multimodal models. *arXiv preprint arXiv:2509.01959*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017a. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017b. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Ashish Singh, Prateek Agarwal, Zixuan Huang, Arpita Singh, Tong Yu, Sungchul Kim, Victor Bursztyn, Nikos Vlassis, and Ryan A Rossi. 2023. Figcaps-hf: A figure-to-caption generative framework and benchmark with human feedback. *arXiv preprint arXiv:2307.10867*.

Ashish Singh, Ashutosh Singh, Prateek Agarwal, Zixuan Huang, Arpita Singh, Tong Yu, Sungchul Kim, Victor Bursztyn, Nesreen K. Ahmed, Puneet Mathur, Erik Learned-Miller, Franck Dernoncourt, and Ryan A. Rossi. 2025. Figcaps-hf: A figure-to-caption generative framework and benchmark with human feedback.

Nikhil Singh, Lucy Lu Wang, and Jonathan Bragg. 2024. Figura11y: Ai assistance for writing scientific alt text. In *Proceedings of the 29th International Conference on Intelligent User Interfaces*, IUI '24, page 886–906, New York, NY, USA. Association for Computing Machinery.

Arjun Srinivasan, Vidya Setlur, and Arvind Satyanarayan. 2025. Pluto: Authoring semantically aligned text and charts for data-driven communication. In *Proceedings of the 30th International Conference on Intelligent User Interfaces*, pages 1123–1140.

Saksham Sahai Srivastava and Vaneet Aggarwal. 2025. A technical survey of reinforcement learning techniques for large language models. *arXiv preprint arXiv:2507.04136*.

Richard S Sutton, Andrew G Barto, et al. 1998. *Reinforcement learning: An introduction*, volume 1. MIT press Cambridge.

Benny Tang, Angie Boggust, and Arvind Satyanarayan. 2023. VisText: A benchmark for semantically rich chart captioning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7268–7298, Toronto, Canada. Association for Computational Linguistics.

Alaa Thobhani, Beiji Zou, Xiaoyan Kui, Amr Abdussalam, Muhammad Asim, Sajid Shah, and Mohammed Elaffendi. 2025. A survey on enhancing image captioning with advanced strategies and techniques. *Computer Modeling in Engineering & Sciences (CMES)*, 142(3).

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. 2015. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4566–4575.

Yidong Wang, Zhuohao Yu, Zhengran Zeng, Linyi Yang, Cunxiang Wang, Hao Chen, Chaoya Jiang, Rui Xie, Jindong Wang, Xing Xie, et al. 2023. Pandalm: An automatic evaluation benchmark for llm instruction tuning optimization. *arXiv preprint arXiv:2306.05087*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Renqiu Xia, Bo Zhang, Haoyang Peng, Hancheng Ye, Xiangchao Yan, Peng Ye, Botian Shi, Yu Qiao, and Junchi Yan. 2023. Structchart: Perception, structuring, reasoning for visual chart understanding. *arXiv preprint arXiv:2309.11268*.

Renqiu Xia, Bo Zhang, Hancheng Ye, Xiangchao Yan, Qi Liu, Hongbin Zhou, Zijun Chen, Peng Ye, Min Dou, Botian Shi, Junchi Yan, and Yu Qiao. 2025. Chartx chartvlm: A versatile benchmark and foundation model for complicated chart reasoning.

Peixin Xu, Yujuan Ding, and Wenqi Fan. 2024a. Chartadapter: Large vision-language model for chart summarization.

Xiaohan Xu, Ming Li, Chongyang Tao, Tao Shen, Reynold Cheng, Jinyang Li, Can Xu, Dacheng Tao, and Tianyi Zhou. 2024b. A survey on knowledge distillation of large language models. *arXiv preprint arXiv:2402.13116*.

Zhengzhuo Xu, Bowen Qu, Yiyan Qi, SiNan Du, Chengjin Xu, Chun Yuan, and Jian Guo. 2025. Chartmoe: Mixture of diversely aligned expert connector for chart understanding. In *The Thirteenth International Conference on Learning Representations*.

Chuqiao Yan, Hans-Peter Hutter, Felix M Schmitt-Koopmann, and Alireza Darvishy. 2025. Chart accessibility: A review of current alt text generation. *IEEE Access*.

Zhishen Yang, Raj Dabre, Hideki Tanaka, and Naoaki Okazaki. 2024. Scicap+: A knowledge augmented dataset to study the challenges of scientific figure captioning. *Journal of Natural Language Processing*, 31(3):1140–1165.

Ho Yin, Ting-Yao Hsu, Jiyoo Min, Sungchul Kim, Ryan A Rossi, Tong Yu, Hyunggu Jung, Ting-Hao'Kenneth' Huang, et al. 2025. Understanding how paper writers use ai-generated captions in figure caption writing. *arXiv preprint arXiv:2501.06317*.

Le Zhang, Yanshuo Zhang, Xin Zhao, and Zexiao Zou. 2021. Image captioning via proximal policy optimization. *Image and Vision Computing*, 108:104126.

Zhehao Zhang, Weicheng Ma, and Soroush Vosoughi. 2024. Is GPT-4V (ision) all you need for automating academic data visualization? exploring vision-language models' capability in reproducing academic charts. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 8271–8288, Miami, Florida, USA. Association for Computational Linguistics.

Lianghui Zhu, Xinggang Wang, and Xinlong Wang. 2023. Judgelm: Fine-tuned large language models are scalable judges. *arXiv preprint arXiv:2310.17631*.

A Additional Details on Evaluations

A.1 Traditional metrics

Early figure captioning systems were evaluated using metrics borrowed from machine translation and summarization. In general, these metrics evaluate the generated caption by comparing it with human-generated reference captions using n-gram analysis. Specifically, **BLEU** (Papineni, 2002) measures n-gram precision against reference captions. **ROUGE** (Lin, 2004) focuses on recall, comparing overlapping sequences between candidate and reference texts. **METEOR** (Banerjee and Lavie, 2005) introduced the harmonic mean of precision/recall with stemming, synonym matching, and paraphrase tables for improved flexibility. In the general image-captioning literature, **CIDEr** (Vedantam et al., 2015) was proposed specifically for captions, using TF–IDF weighted n-gram matching to reward consensus across multiple human references. While these methods offer computational efficiency and consistency in evaluation, they suffer from multiple drawbacks: **(1) low agreement with human judgment** when captions are phrased differently than references and **(2) sensitivity to sentence length and detail**, where descriptive captions that include additional correct details not present in references are unreasonably penalized and finally **(3) over-dependence on good reference captions** wherein, effectiveness of these methods is limited by the quality of the reference captions, which can often be inadequately written.

A.2 Human Evaluation

Human evaluation methods can be broadly categorized based on following high-level criteria:

Evaluation Form: A common approach followed by most works (Yang et al., 2024; Singh et al., 2023; Hsu et al., 2023; Liu et al., 2024; Masry et al., 2024b,a) is to define specific qualitative metrics for evaluation and record human evaluator ratings on a Likert scale. These scores are then aggregated across samples and subjects to generate absolute ratings. Contrary to this, some methods rely on ranking generated captions (Hsu et al., 2023; Lim et al., 2025; Ng et al., 2025c) based on specific qualitative properties. Finally, in (Omasa et al., 2025), human evaluation focuses on single-item judgment (binary) where correctness is determined by comparing the predicted caption with ground-truth caption.

Qualitative Metrics: (Masry et al., 2024a,b) defines **Informativeness**, **Factual correctness** and **Structure** as qualitative criteria for human

evaluation. They are defined as:

1. **Informativeness:** *How much useful and relevant information from the chart does the summary cover? Does it effectively convey the main trends and insights?*

2. **Factual correctness:** *How accurate is the summary in reflecting the information presented in the chart?*

3. **Structure:** *How well-structured is the summary? Does it include an introduction, a body with key insights, and a conclusion?*

Apart from informativeness, (Lim et al., 2025) also defines **Hallucinations** as another key criterion, which is formulated as: *Does the caption avoid information that cannot be inferred from the chart?* Other key metrics includes: **Reasoning Correctness** (Liu et al., 2024), **Helpfulness** (Hsu et al., 2023; Singh et al., 2023; Ng et al., 2025c), **OCR (Optical Character Recognition)** (Hsu et al., 2023; Singh et al., 2023), **Relation**, **Stats** (Hsu et al., 2023), **Takeaway** and **Visual** (Hsu et al., 2023; Singh et al., 2023; Li et al., 2025b). They are defined as follows:

1. **Helpfulness:** *Does this caption help you understand the figure?*

2. **OCR (Optical Character Recognition):** *Does this caption mention any words or phrases that appear in the figure?*(Examples include the figure title, X or Y axis titles, legends, names of models, methods, subjects, etc.)

3. **Relation:** *Does this caption describe a relationship among two or more elements or subjects in the figure?* (For example, "A is lower than B," "A is higher than B," or "A is the lowest/highest in the figure.")

4. **Stats:** *Does this caption mention any statistics or numbers from the figure?* (For example, "20% of..." or "The value of .. is 0.33...".)

5. **Takeaway:** *Does this caption describe the high-level takeaways, conclusions, or insights the figure tries to convey?*

6. **Visual:** *Does this caption mention any visual characteristics of the figure?* (Examples include color, shape, direction, size, position, or opacity of any elements in the figure.)

While human evaluation schemes provides an extremely precise and reliable metric for evaluating generated figure captions with respect to reader preferences, it is costly and time-consuming. Human evaluation is primarily constrained by the need for domain expertise and a thorough understanding of the entire scholarly article by the human evaluators. This severely limits its scalability and makes solely relying on human evaluation impractical for large-scale evaluation. Thus while it is recommended to conduct human evaluation, it should also be accompanied with automatic evaluation methods.

A.3 MLLM-as-a-Judge

To address the shortcomings of human and traditional reference based evaluation, recent work has begun treating MLLMs as reference-free evaluators (Chen et al., 2024; Gu et al., 2024). These MLLM-based judges can provide scalable, context-sensitive assessments that approximate expert judgment without needing human-authored references. In particular, pairwise comparison has proven especially effective: LLM judgments on paired outputs tend to align closely with human preferences.For example, systems like Auto-J (Li et al., 2023) and PandaLM (Wang et al., 2023) adopt this approach by fine-tuning open-source MLLMs on pairwise preference data. In practice they train on data labeled by strong models (e.g. GPT-3.5/GPT-4 (Achiam et al., 2023)) and generate an evaluator that chooses the better of two responses, yielding judgments that are far more consistent and robust than classical metric scores.

Complementing pairwise methods, score-based frameworks have emerged to rate multiple quality dimensions. For instance, G-Eval (Liu et al., 2023) and JudgeLM (Zhu et al., 2023) use Likert-style ratings to score aspects like factuality, coherence, and completeness. These systems are trained on datasets annotated by powerful LLMs (such as GPT-4 (Achiam et al., 2023)), which helps their scores better mimic human evaluators. Notably, (Hsu et al., 2023) demonstrated the approach in the figure-caption domain: they built a dataset of scientific figure captions and showed that GPT-4 can serve as a zero-shot caption-quality judge. In their work, GPT-4 was prompted (with the figure and context) to score each caption on a 1–6 scale based on how well it aids reader understanding – all without any human-written reference caption. GPT-4's scores even correlated well with expert rankings, illustrating a cost-effective, reference-free evaluation of captions.

B Details on Benchmarks and Datasets

In this section, we summarize the existing datasets that enable the development and evaluation of large

generative models for figure captioning and reasoning tasks. We summarize the datasets and their properties in Table 3.

There are many different figure-captioning benchmark datasets. FigCAP (Chen et al., 2019) builds upon FigureQA images to provide both high-level (FigCAP-H) and detailed (FigCAP-D) descriptions for five chart types. It enhances linguistic diversity through paraphrasing templates and introduces logically structured long-form captions, posing greater challenges for multimodal models. SciCAP (Hsu et al., 2021) is a dataset of over 416,000 scientific charts extracted from arXiv papers. Its multi-granularity captioning design and strict train-validation-test split establish a new benchmark for understanding visual content. SciCap+ (Yang et al., 2024) is an enhanced dataset for scientific figure captioning, extending SciCap with mention-paragraphs and OCR tokens to improve model comprehension. It supports multimodal tasks like automated caption generation and scientific summarization.

One recent work by Ng et al. (2025c) focused on personalized caption generation focused on generation captions of figures that align with the style of a specific user. In particular, they introduce a benchmark called LaMP-Cap that leverages the large corpus of SciCAP in the style of a specific user extends SciCAP with personalized context by including up to three background charts and descriptions per target chart. It enables research on context-aware, personalized multimodal generation by aligning captions with individual writing styles.

A few other benchmarks have focused on a slightly different setting of figure-captioning that focused on generating a summary from an input figure (Kantharaj et al., 2022; Xu et al., 2024a) and also on generating captions from a large variety of traditional and more complex chart types (Karishma et al., 2023b). One such work called chart-to-text (Kantharaj et al., 2022) introduced a large-scale benchmark for the chart summarization task. The dataset consists of two subsets with a total of 44k charts, covering a wide range of topics and chart types. It is designed to generate natural language summaries to help people infer key information from charts. This work also introduces several neural network-based models as baselines for tackling the chart-to-text generation task. Similarly, another more recent work called ChartSumm (Xu et al., 2024a) introduced a benchmark consisting of over 190,000 samples across diverse chart types. By providing semantically aligned data, it provides semantically aligned summaries to support multilingual and cross-domain chart understanding, aiding

the development of large-scale multimodal summarization models. Finally, one recent benchmark called ACL-Fig (Karishma et al., 2023b) focused on many different diverse and complex figure types (flowcharts and beyond). This benchmark includes 112,052 scientific figures extracted from 56,000 ACL papers, including a manually labeled subset (1,671 figures, 19 classes) called ACL-Fig-PILOT, designed for figure classification and captioning.

Figure understanding is also a closely related problem that can also be leveraged to improve figure captioning in more advanced techniques, since figure understanding is crucial to generate the best caption for a specific figure. One such dataset is the FigureQA benchmark (Kahou et al., 2017) which is a large-scale synthetic benchmark designed to test visual reasoning on chart images. It includes over 1.3 million yes/no questions grounded in more than 100,000 charts. Differentiated color schemes and auxiliary annotations (e.g., bounding boxes) prevent shortcut learning, making it a key benchmark for visual reasoning on structured figures. DVQA (Kafle et al., 2018) is a visual question answering dataset focused on bar chart understanding. It contains 300,000 synthetic images and 3.48 million question-answer pairs, covering three tasks: structure understanding, data retrieval, and logical reasoning. The charts are generated using Matplotlib with diverse styles and are supplemented with detailed metadata such as bar bounding boxes and underlying table data. More recently, SciFIBench (Roberts et al., 2024) evaluates the scientific figure interpretation of MLLMs using adversarially-filtered multiple-choice questions that require matching figures to their correct captions.

A few other recent works have focused on other aspects of this problem. ChartX (Xia et al., 2025) is a multimodal benchmark featuring 18 chart types and 22 scientific domains. Each sample contains an image, CSV data, Python code, and textual description. Its dual-layer tasks—perception and cognition—enable comprehensive evaluation of chart understanding in LLMs. SCICAP-EVAL (Hsu et al., 2023) is an evaluation dataset with 600 scientific charts and 3,600 captions (human- and model-generated). It introduces a 1–6 readability score and expert annotations to assess caption quality, offering a robust framework for comparing automatic captioning methods.

C   Additional Details on Open Challenges

C.1   Animated Figure

Animated figures evolve automatically over time, allowing temporal changes in data to be commu-

nicated through motion. Such dynamics are typically author-driven, as seen in animations that visualize evolving phenomena or transitions across datasets. Data visualization often employs animation to represent datasets that unfold along an additional temporal dimension. Examples include heatmaps of eye-tracking data, where gaze density changes across time, or airflow simulations visualized over geographic maps. Similarly, scientific visualizations such as CT (Computer Tomography) or MRI (Magnetic Resonance Imaging) scans sequentially present slices of 3D objects to convey volumetric structures. As in computer vision, where models analyze object tracking, segmentation, and motion patterns, animated figures could similarly incorporate such analytical reasoning into captions to reflect temporal transitions more accurately. Building on video understanding capabilities, extending multimodal models to animated figures could enable more comprehensive and temporally aware captioning of visualization content.

C.2 Interactive Figure

Interactive figures, in contrast, invite reader-driven exploration by enabling users to manipulate what is shown or emphasized. Through techniques such as filtering, zooming, or brushing and linking, readers can dynamically shift focus and reveal different aspects of a dataset (Keim, 2002). These interactions alter how relationships among data points are represented, meaning that the same dataset may produce multiple narratives depending on user intent and engagement. Understanding how such representational flexibility affects caption generation calls for models that integrate awareness of interaction context. Rather than generating isolated captions for each state, models could incorporate exploration history or user actions to produce captions that align with the reader's interpretive trajectory, bridging the gap between static description and dynamic sense-making.

C.3 Immersive Figure

Data visualization has also been actively studied across different modalities. A representative example is rendering 3D data visualization in VR and AR environments rather than on traditional 2D displays. Captioning a snapshot of such a 3D figure, or generating captions that incorporate auxiliary information from immersive interactions such as free exploration or guided tours, could be an interesting research direction.

Because data points and compositional elements exist in 3D space, issues such as occlusion and distortion depending on camera settings often arise.

Captioning methods that can account for these visual characteristics of immersive environments would be valuable. Moreover, problems commonly studied in computer vision for video, such as object segmentation, classification, and tracking, could be extended to this setting.

C.4 Personalized Caption

Caption personalization can be considered from two complementary perspectives. First, personalization for transferring the author's writing style into the model. This includes adapting to the author's preferred style of interpretation and explanation, adherence to auxiliary texts, or alignment with the persona of the author as the narrator. Research in this direction could explore how author-specific characteristics can bias or guide the caption generation process. Second, personalization for the target reader of the generated caption. When the author has a particular audience persona in mind, the generation pipeline should accommodate the author's intentions and design considerations. However, authors may often have only limited knowledge of their readers, or may want to reduce uncertainty by leveraging the model's ability to anticipate reader needs. This involves considerations such as what kind of experience the reader might have, what responses they might show, whether visual perception could lead to biased interpretations, or whether misleading representations arise due to the reader's mental model. If the model is not already aware of these factors, benchmarks and strategies based on fine-tuning or prompt engineering could be proposed to help address them.

C.5 Accurate Evaluation

For evaluating the generated captions, it is often necessary to require the inclusion of a specific argument or data-driven takeaway, and to verify whether the generated caption successfully contains this insight. To address this, an evaluation framework should automatically assess two aspects: (1) whether the generated insight is logically supported by the underlying dataset, and (2) whether this insight is indeed entailed in the generated caption. Developing evaluation metrics through NLP-based approaches, or conducting a comprehensive investigation into whether stable and reliable evaluation is feasible, would be valuable directions. MLLM-as-a-Judge is emerging as a promising solution, as it can rapidly apply diverse evaluator perspectives to analyze the relationship between a provided figure and a generated caption. Combined with robust text extraction methods such as OCR, MLLMs can help ensure accurate chart infor-

mation retrieval while also supporting evaluation dimensions that may otherwise remain subjective. However, concerns remain that MLLMs' ways of visually interpreting figures are not always aligned with human perception, highlighting the need to calibrate these models and to training them for a broader space of figures. In addition, evaluation strategies from general image captioning can be adapted. For example, one could regenerate a figure from the information contained in a generated caption and then assess the degree of visual or semantic alignment with the original figure. Another approach is to decompose the image and caption into visual elements and analyze their correspondence. For example, text–image grounding methods like TIGEr (Jiang et al., 2019) evaluate which parts of a caption are matched to which regions of an image. In the case of figures, visual regions like axes, legends, or data marks can often be defined algorithmically, making this approach especially feasible for chart caption evaluation.

D   Applications

Figure captioning serves as a foundational capability across a wide range of domains, enabling more effective interpretation, interaction, and automation of visual content (Yan et al., 2025). In particular, it gives rise to countless applications, from making figures more accessible to better knowledge extraction and beyond. In this section, we highlight a few important application areas where figure captioning has become increasingly relevant.

D.1   Accessibility

One important application of figure captioning is for improving the accessibility of charts (Yan et al., 2025). By converting figures and diagrams into natural language, it enables screen readers and other assistive tools to convey visual information that would otherwise be lost. This capability gives rise to scalable alt-text generation, reducing manual annotation effort and supporting compliance with accessibility standards such as Web Content Accessibility Guidelines (WCAG). It also naturally lends itself to adaptive interfaces, including educational platforms and interactive dashboards, where dynamic captioning improves usability and inclusivity. Further, figure captioning plays a critical role in enhancing document accessibility. Automatically generated descriptions of figures serve as alt-text in compliance with web accessibility standards, supporting screen readers for visually impaired users. This capability ensures that charts are equally accessible to all users, regardless of visual ability.

D.2   Scientific Document Understanding

A primary application of figure captioning lies in the automated understanding of scientific documents. Generating accurate and context-aware captions enables more effective document summarization, improves figure indexing and retrieval across large-scale repositories (e.g., arXiv, PubMed), and supports a variety of downstream tasks such as citation analysis and scientific QA. Furthermore, captioned figures assist reviewers and editors in quickly grasping the intent and insight behind visualizations.

D.3   Knowledge Extraction and Structured Data Generation

Figure captioning enables the transformation of unstructured visual content into machine-readable form. Captions can be leveraged to extract entities and relations, populate multimodal knowledge graphs, and align figure data with textual evidence. In data-centric domains, this facilitates semantic indexing, metadata enrichment, and automatic report generation from charts and tables.

D.4   Cross-modal Retrieval and Search

High-quality figure captions serve as a semantic bridge between visual figure and textual modalities. They enable figure-to-text and text-to-figure retrieval, improving figure search and recommendation systems. In addition, figure captions enhance the performance of multimodal QA and reasoning systems by grounding language understanding in figure evidence. This can greatly improve the quality of such systems.

D.5   Educational Technology

In education, figure captioning improves learner engagement and comprehension by providing natural language explanations of complex figures and diagrams. Captioned figures can be used in intelligent tutoring systems, interactive textbooks, and personalized learning environments to provide on-demand clarification, contextual feedback, and improved learning. These capabilities are particularly impactful in STEM education where figures are central to instruction.

D.6   News and Media Automation

In journalism and media, figure captioning enables scalable content generation and summarization for data-driven stories. Automatically generated captions can describe charts, graphs, and infographics used in news articles, dashboards, and social media. This capability supports automated writing pipelines and improves reader comprehension by

Symbol	Description
$\mathcal{I}$	Space of figures, e.g., tensors in $\mathbb{R}^{H \times W \times C}$
$\mathcal{Y}$	Space of all possible captions composed of tokens from the vocabulary
$\mathcal{V}$	Vocabulary of textual tokens used in captions
$Y = (w_1, \ldots, w_T)$	Caption consisting of T tokens $w_t \in \mathcal{V}$, t is the time variable
$\mathcal{T}$	Space of auxiliary texts, such as paragraphs or surrounding context
$\mathcal{D}$	Dataset of tuples containing figures, captions, and possibly auxiliary text
$\ell(\cdot, \cdot)$	Loss function between predicted and true captions (e.g., negative log-likelihood)
$Q(\cdot)$	Quality or utility function for evaluating captions (e.g., BLEU, human judgment)
$p_\theta(Y \mid \cdot)$	Conditional probability of caption Y given input(s) under model parameters θ
$s_\theta(Y \mid \cdot)$	Scoring function (e.g., $\log p_\theta$) used during decoding
$\hat{Y}$	Predicted caption
$\hat{\mathbb{Y}}$	Set of predicted captions
I	Input figure to be captioned
T	Auxiliary text associated with the figure
C	Conversational history containing user and model utterances
U	User or persona embedding used for personalized captioning
$Q(\hat{Y}, Y, I)$	Caption evaluation metric comparing generated caption $\hat{Y}$ with reference Y and figure I
$p_\mathcal{M}(Y \mid I, P)$	Probability assigned by a pretrained model $\mathcal{M}$ given figure I and prompt P
P	Text prompt or instruction used during inference or in-context learning
k	Number of in-context examples or retrieved figure–caption pairs
$\mathcal{R}(I)$	Retrieval function returning top-k relevant figure–caption pairs for figure I
$q_\phi(Y \mid I)$	Student model's conditional distribution after distillation
$p_\theta(Y \mid I, T)$	Teacher model's distribution given both figure and auxiliary text
r	Reward in RL or RLHF computed from metric or human preference
$R_\phi(I, \hat{Y})$	Learned reward model approximating human judgments
$\hat{\theta}, \hat{\phi}$	Optimal or fine-tuned model parameters
$\mathbb{X}, \mathbb{Y}, \mathbb{S}, \mathbb{G}$	Abstract spaces used for figures, captions, sentences, or graphs

Table 4: List of mathematical notations and their meanings used in the paper.

Table 5: Taxonomy of input modalities and corresponding technique categories for figure captioning.

Input Modality	In-Context (§4.1)	Fine-Tuning (§4.2)	RL / RLHF (§4.3)	Distillation (§4.4)	Retrieval/Hybrid (§4.5)	Personalization (§4.6)
Figure Only	✓	✓		✓		
Figure–Caption Pairs	✓	✓	✓	✓	✓	✓
Auxiliary Text	✓	✓			✓	✓
Conversational Captioning	✓					

contextualizing figures with relevant narrative. Furthermore, it can also help to personalize the caption to improve the ability of the user to understand and comprehend the figure in an easy and accessible fashion that is personalized specifically for that user.

D.7 Human-AI Collaboration

Figure captioning gives rise to new forms of collaborative workflows between humans and AI. For instance, (Yin et al., 2025) explores how writers leverage AI-generated captions for writing figure captions. In creative and analytical settings, captions can assist users by automatically generating textual narratives for figures, suggesting titles or annotations, and supporting data storytelling. These capabilities streamline content creation and support interactive authoring tools that adapt to user intent and context.

D.8 Digital Archives and Libraries

For historical and technical archives, figure captioning provides a mechanism to enrich content with missing or outdated annotations. This is particularly valuable in digitization workflows, where legacy documents often contain figures with degraded or absent descriptions. Captioning facilitates improved organization, retrieval, and semantic analysis of figure content in archival collections.

E Relation to General Image Captioning

Figure captioning shares a strong methodological foundation with general image captioning, as both tasks aim to translate visual information into natural language. Consequently, the majority of figure captioning systems leverage architectures originally developed for natural images, including the use of visual encoders and the adoption of encoder and decoder paradigms for sequence generation. Evaluation methodologies have also been directly adapted; metrics such as CIDEr and text image grounding techniques were pioneered in the general domain before being applied to chart evaluation. However, the direct application of general image captioning techniques often yields suboptimal results due to the unique semantic density of scientific figures. While general image captioning typically focuses on perceptual description, such as identifying objects, actions, and scenes, figure captioning requires logical reasoning to extract salient patterns and data driven insights. Generic mod-

els often fail to capture the specialized context of figures, such as correctly interpreting axis scales, legend mappings, or specific scientific nomenclature. Unlike natural scenes where approximations are often acceptable, scientific captioning demands high fidelity because a failure to recognize a specific data trend or axis label can lead to hallucinations that fundamentally misrepresent the underlying data. Furthermore, effective figure captioning demands a significantly higher degree of OCR and statistical integration to ground textual claims in specific data points, which is a requirement rarely present in natural scene description. Where a general caption might suffice with visual descriptors, a figure caption must precisely articulate relationships and quantitative shifts. Consequently, recent trends in the field have had to diverge from general image captioning by emphasizing attribution aware grounding and the curation of knowledge augmented datasets to bridge the gap between visual perception and scientific interpretation.