Contrastive Learning of 3D Shape Descriptor with Dynamic Adversarial Views

Abstract

View-based deep learning models have shown the capability to learn 3D shape descriptors with superior performance on 3D shape recognition, classification, and retrieval. Most popular techniques often leverage the class label to train deep neural networks under supervision to learn to extract 3D deep representation by aggregating information from a static and pre-selected set of different views used for all shapes. Those approaches, however, often face challenges posed by the requirement of a large amount of annotated training data and the lack of a mechanism for the adaptive selection of shape-instance-dependent views towards the learning of more informative 3D shape representation. This paper addresses those two challenging issues by introducing the concept of adversarial views and developing a new mechanism to generate views for adversarial training of a self-supervised contrastive model for 3D shape descriptor, denoted as CoLAV. In particular, compared to the recent advances in multi-view approaches, our proposed CoLAV gains advantages by leveraging the contrastive learning techniques for self-supervised learning of 3D shape representations without the need for labeled data. In addition, CoLAV introduces a novel mechanism for the dynamic generation of shape-instance-dependent adversarial views as positive pairs to adversarially train robust contrastive learning models towards the learning of more informative 3D shape representation. Comprehensive experimental results on 3D shape classification demonstrate that the 3D shape descriptor learned by CoLAV exhibits superior performance for 3D shape recognition over other state-of-the-art techniques, even though CoLAV is completely self-trained with unlabeled 3D datasets (e.g., ModelNet40).

1 Introduction

The impressive performance of Deep Neural Networks (DNNs) for 2D visual feature learning naturally motivates 3D computer vision researchers to develop deep learning models for 3D representation for downstream 3D tasks (e.g., shape classification (Qi et al. (2017b)), shape correspondence (Li et al. (2019)), shape retrieval (Han et al. (2018)), shape registration (Miao et al. (2016))). To this end, researchers developed the first family of 3D deep learning models that operate directly on 3D raw data represented by point clouds (Qi et al. (2017b); Shi et al. (2020)), triangulated meshes (Hanocka et al. (2019)), or 3D regular voxels (Choy et al. (2019)). The recent advancement of approaches in this category has significantly contributed to the shape classification, correspondence, segmentation, registration, and detection. The second important family of 3D deep learning models starts with rendering multiple 2D projections of a 3D object from a static and pre-selected set of different views, followed by learning the compact 3D representation via fusing the deep feature maps of these 2D views. As they can straightforwardly leverage the latest developments of convolutional neural networks, the view-based methods have shown a very attractive capability to learn 3D shape descriptors with superior performance on 3D shape recognition, classification, and retrieval (Li et al. (2020); Yuan & Fang (2020); Shi et al. (2020)). Particularly, recent advances in view-based approaches lead to impressive state-of-the-art performances in various 3D vision tasks such as 3D shape classification, retrieval, correspondence, and segmentation (Wei et al. (2020)). The most popular techniques often leverage the ground truth label to train deep neural networks and learn to extract deep representations by aggregating information from a static and pre-selected set of different views. Those approaches, however, often faced challenges posed by the requirement of

a large amount of annotated training data and the lack of a mechanism for the adaptive selection of shape-instance-dependent views towards the learning of more informative 3D shape representation.

This paper addresses those two challenging issues by introducing the concept of adversarial views (Xiang et al. (2019)) and developing a new mechanism to generate views for the adversarial training of a self-supervised model for 3D representation learning, denoted as CoLAV. Specifically, different from the recent advances in multi-view approaches (Kanezaki et al. (2018)), CoLAV gains advantages by learning the 3D shape representation without the need for labeled data. In addition, in contrast to using a static set of views as input during the training of a multiview-based 3D shape representation learning framework, we take a further step to investigate the effect of using dynamically rendered views as input during the 3D shape representation learning. To this end, we introduce an adversarial view generator that enables the dynamic generation of shape-instance-dependent adversarial views, which can fool the deep learning model to misidentify its instance-wise identity, as positive pairs to adversarially train robust contrastive learning models towards the learning of more informative 3D shape representation.

In this paper, we introduce a novel concept of adversarial views of a 3D shape and develop a new mechanism to adaptively and dynamically render shape-instance-dependent views towards the learning of more informative 3D shape representation via CoLAV. The proposed CoLAV is capable of learning 3D shape representations from multiple 2D views without requiring ground truth annotations. In addition, our comprehensive experimental results on 3D shape classification and retrieval demonstrate that the 3D shape descriptor learned by CoLAV exhibits superior performance for 3D shape recognition over other state-of-the-art techniques, even though CoLAV is completely self-trained with unlabeled 3D datasets (e.g., ModelNet40).

2 Related Works

2.1 Multi-View Learning

In recent research, multi-view-based methods have become a popular topic in 3D computer vision. Basically, these methods start with rendering projections of 3D objects from different view perspectives, generate representation features for each projection, and merge them into a global descriptor of the 3D object. The compact descriptor can be used to improve performance and robustness in 3D object learning tasks such as classification and retrieval. One of the earliest methods in multi-view-based learning is called multi-view convolutional neural network (MVCNN) (Su et al. (2015)), which fuses feature representations extracted from multiple views into one compact descriptor by a max-pooling layer. Ruizhongtai Qi et al. (2016) advances the progress by incorporating a multi-resolution component into MVCNN to boost the classification accuracy. However, using a max-pooling layer to fuse representation features from multiple views can only retain the maximum value on each dimension and may lose information. The group-view convolutional neural network (GVCNN) (Feng et al. (2018)) is proposed to solve this problem, which generates the descriptor via a grouping strategy that keeps more information from different views. There is also research attaching attention-based models to the framework, which leverages spatial relationship among different views' feature representation (Han et al. (2018; 2019)). Yang & Wang (2019) also leverages the relationship between views and constructs a model that connects corresponding regions on each projection and strengths the representation learned from each individual viewpoint. The aforementioned view-based methods have achieved promising performance on various tasks, however, their training process requires a large amount of annotated data. To alleviate the dependency of annotated data, Ho et al. (2020) proposed a self-supervised method that randomly selects a view feature out of several pre-selected static views of a 3D object as a prototype to learn an invariant stochastic object embedding which is further used to generalize the method (Ho et al. (2020)) on test data. Different from all previous view-based methods, we investigate the effect of using dynamic views. Instead of using pre-selected static views, in our work, dynamically rendered views are used to learn an informative multi-view-based 3D object representation, meanwhile, no annotated class labels are given. This encourages the proposed model to better generalize on various unseen views.

Figure 1: **Illustration of our pipeline:** Two key components are employed to learn informative 3D shape descriptors without ground truth supervision. The first one is **adversarial view generation**. In this part, our model takes a 3D shape instance x as input and generates an augmented 3D shape $t(x)$ by adopting a set of augmentation operations t sampled from a pool of predefined augmentations. Then, for both x and $t(x)$, we render k 2D images representing projections from different prospective using the differentiable renderer $r_\tau(\cdot)$. The rendered images are fed to a descriptor learning module to extract shape descriptors. After we obtain the descriptors, we use a contrastive loss function to measure the mutual information of descriptors. The forward path is denoted by the black arrow in the figure. The loss term is used to compute the gradient with respect to the rotation matrix (characterized by α, β, and γ) which is required for the generation of an adversarial 3D shape instance $t_{adv}(x)$ and its corresponding adversarial views. This adversarial sample generation is represented by the purple path. The second component is the **contrastive learning module with a shape-instance-dependent adversarial attack**, represented in the red path, which is adopted towards the learning of more informative and robust 3D shape representation.

2.2 ADVERSARIAL LEARNING

In the concept of adversarial learning, adversarial examples are treated as hard positive samples in the model training process to improve the robustness of neural networks (Szegedy et al. (2013)). Goodfellow et al. introduced the fast gradient sign method (FGSM) (Goodfellow et al. (2014)) which increases the robustness of the model by perturbing input samples along with gradient directions. Following this direction, numerous methods (Kurakin et al. (2016); Papernot et al. (2016); Shafahi et al. (2019); Xie & Yuille (2019); Xie et al. (2020)) were proposed and have obtained impressive robustness against adversarial attack in image space. Recently, Zeng et al. (2019) claimed that instead of generating adversarial samples in 2D space, finding adversarial 3D objects behind the projected 2D images is crucial to improve the robustness. In their work (Zeng et al. (2019)), FGSM is used to perturb the input sample in 3D space governed by a supervised loss, and ground truth class labels are required to generating adversarial 3D objects. Unlike Zeng et al. (2019), in this work, we introduce a new approach to generates adversarial views based on 3D objects without using ground truth labels.

2.3 CONTRASTIVE LEARNING

The concept of contrastive learning has been extensively used in recent studies, especially in self-supervised (SSL) learning scenarios. In SSL 3D object learning, contrastive learning can help re-trieve an invariant descriptor for each 3D object by applying random augmentations to each object

and minimizing the contrastive loss by measuring the similarity between the feature vectors representing original and augmented shapes. There have been a certain amount of augmentation strategies that came up by previous studies in the 2D computer vision field (Wu et al. (2018); Ye et al. (2019); Tian et al. (2019)), implementing data augmentation by rotation, cropping, and other transformation methods. Such augmentations can force the network to learn sophisticated descriptors to represent input instances while training and thus boost robustness. By comparing different methods of augmentation, Chen et al. (2020) indicates that the effectiveness of contrastive learning can be enhanced by employing stronger data augmentation. On the other hand, although we have various augmentation methods to boost performance, it is arduous for contrastive learning models to overcome the hard negative mining problem mentioned in Sohn (2016); Wu et al. (2017); Schroff et al. (2015). One of the possible solutions to that problem is to select negative samples from a distribution of noise that treats all negative instances equally, which is proposed by the contrastive noise estimation (NCE) (Gutmann & Hyvärinen (2010)), by which contrastive learning is directly inspired (Bose et al. (2018); Bose et al.; Ho & Vasconcelos (2020)).

3 METHODS

The pipeline of our proposed module is illustrated in Fig. 1. The CoLAV is a generic module that generates instance-wise adversarial views to adversarially train a contrastive learning model towards the goal of learning a more informative and robust shape descriptor for a given task.

3.1 ADVERSARIAL VIEWS

We introduce our novel approach to obtain adversarial views while alleviating the dependency of annotated data. As we illustrate in Section 2, although many multi-view-based methods have been proposed, their performances rely on the contents of input views which are subject to camera positions and annotated data. As we observed from existing work (Su et al. (2015); Feng et al. (2018)) camera positions are static across the entire 3D shape dataset, which leads the trained model vulnerable to unseen views. To address these issues, we introduce adversarial views as hard positive training samples during the model training, which aims to fool the predictor to make wrong predictions by maximizing the objective function.

Adversarial Views Generation Concretely, with the fixed camera position, the generation of dynamic adversarial views depends on the generation of an adversarial 3D sample x^{adv}. To generate adversarial 3D samples, existing researches focus on perturbing 3D point positions within a certain range in 3D space. This perturbation is almost indistinguishable by human eyes, i.e., a perturbed 3D sample is visually identical to the original 3D object. To this end, the direct adaptation of this adversarial sample generation method prevents us dynamically generating adversarial views due to fixed viewpoints. Hence, we propose a new method to generate visually different adversarial views of each 3D instance with the aim to fake the model to treat the generated views as new instances. Given a 3D shape x from the dataset $\mathbb{D}$, a differentiable renderer $r_\tau(\cdot) : x \to I$, a rotation matrix M controlled by three randomly initialized parameters α, β, γ, a differentiable renderer $r_\tau(\cdot)$, a descriptor learning model $f_\theta(\cdot)$ and a task-specific predictor $g_\phi \cdot$, the generation of x^{adv} is defined as:

$$x^{adv} = \begin{cases} Mx, & i = 0 \\ \hat{M}x_{i-1}^{adv}, & i > 0, \end{cases}$$

(1)

where i denotes the generation iterations and $\hat{M}$ denotes the updated rotation matrix controlled by $\hat{\alpha}, \hat{\beta}, \hat{\gamma}$ which is formulated as follow:

$$\hat{\alpha}, \hat{\beta}, \hat{\gamma} = p(\epsilon sign(\nabla_{\alpha,\beta,\gamma}\mathcal{L}_{\phi,\theta}(x_{i-1}^{adv}, t(x_{i-1}^{adv}), t(x')) + [\alpha, \beta, \gamma]),$$

(2)

where $\mathcal{L}$ is the loss for training the neural network with parameter ϕ and θ, the $sign(\cdot)$ gives the sign of gradients, and ϵ represents the step size of one gradient attack. We employ a function $p(\cdot)$ as projection function to clip three angles $\hat{\alpha}, \hat{\beta}, \hat{\gamma}$ with in $[-180°, 180°]$. The adversarial views $Iadv$ is rendered by:

$$I^{adv} = r(x^{adv})$$

(3)

To adversarially train a neural network against using adversarial samples generated from Equation 1, we can directly minimize the $\mathcal{L}$ of I^{adv}. This adversarial learning process can be formulated as

follow:

$$\arg\min_{\theta,\phi} \mathbb{E}_{(I)\sim r(\mathbb{D})}[\max_{I^{adv}} \mathcal{L}_{\phi,\theta}] \tag{4}$$

The computation of loss term $\mathcal{L}_{\phi,\theta}$, such as cross-entropy loss requires the ground truth labels, which prevents us from applying this approach to unannotated datasets. To address this, we alleviate the dependency of ground truth annotations by adopting a self-supervised contrastive loss.

Self-Supervised Adversarial Views Generation Specifically, given a pool of augmentation operation T, such as random rotation, random jittering, random scaling, random noise, and random dropout, we randomly select two augmentation operation sets $t \sim T$. The specific data augmentation operation that we adopt in our method can be found in Section **??** and Section **??**. Our goal is to maximize the similarity between $f_\theta(r(x))$ and $f_\theta(t(r(x)))$, since $r(x), t(r(x))$ has the same instance-level proprieties, and minimize the similarity between $f_\theta(t(r(x)))$ and $f_\theta(t(r(x')))$, where x' is a different 3D shape instance. For a clear illustration, we denote $r(x)$ as I, $t(r(x))$ as I_{pos}, and $t(r(x'))$ as I_{neg}. Then, the constrastive learning process as be formulated as minimize the following loss function:

$$\mathcal{L}_{\mathbf{co},\theta}(I, I_{pos}, I_{neg}) = -\log \frac{e^{(sim(f(I),f(I_{pos}))/\Gamma)}}{e^{sim(f(I),f(I_{pos}))/\Gamma} + e^{sim(f(I),f(I_{neg}))/\Gamma}}, \tag{5}$$

where we follow the SimCLR (Chen et al. (2020)) to adopt Γ as a temperature parameter and the $sim(\cdot,\cdot)$ function, which is defined as follow:

$$sim(a,b) = a^T b / \|a\|\|b\|. \tag{6}$$

By adopting this formulation, we can reformulate Equation and make it self-supervised, which relaxes the constrain of requiring annotated datasets during adversarial view generation. The self-supervised version of adversarial view generation can be formulated as follow:

$$\hat{\alpha}, \hat{\beta}, \hat{\gamma} = p(\epsilon sign(\nabla_{\alpha,\beta,\gamma}\mathcal{L}_{\mathbf{co},\theta}(x_{i-1}^{adv}, t(x_{i-1}^{adv}), t(x')) + [\alpha,\beta,\gamma]), \tag{7}$$

3.2 Contrastive Learning with Shape-Instance-Dependent Adversarial View

Once we have the adversarial views as our positive samples, generated from Equation 1, 3, 7, we can learn a robust and informative 3D shape descriptor through contrastive learning. The learning process can now be formulated as follow:

$$\arg\min_{\theta} \mathbb{E}_{x\sim\mathbb{D}}[\max_{x^{adv}} \mathcal{L}_{\mathbf{3Dco},\theta}(x^{adv}, t(x^{adv}), t(x'))]. \tag{8}$$

The final loss function $\mathcal{L}_{\mathbf{3Dco}}$ can be described as:

$$\mathcal{L}_{\mathbf{3Dco}}(x^{adv}, t(x^{adv}), t(x')) = -\log \frac{e^{(sim(f(r(x^{adv})),f(r(t(x^{adv}))))/\Gamma)}}{e^{sim(f(r(x^{adv})),f(r(x')))/\Gamma} + e^{sim(f(r(x^{adv})),f(r(x')))/\Gamma}}, \tag{9}$$

The training of CoLAV can be found in Algorithm 1.

Algorithm 1 The training process of our proposed method

Input: Original 3D shapes: x, augmented 3D shapes: $t(x)$, augmented negative 3D shapes: $t(x')$, descriptor learning model: f, parameter of model: θ, adversarial view generation iterations: i;

    for all iteration $\in$ training stage **do**

        for all $x \in$ minibatch **do**

            for attack iteration $\in [0, i)$ **do**

                update rotation matrix M.

            end for

            Generate adversarial views using Equation 1, Equation 3 and Equation 7.

        end for

        calculate objective function $\mathcal{L}_{final}$ using equation 9.

        updating model parameter θ

    end for

---

4 EXPERIMENTS

In this section, we conduct experiments to evaluate the performance of our proposed method on three benchmark datasets. More specifically, we evaluate our module when adopting various multi-view base backbone, including GVCNN (Feng et al. (2018)), MVCNN (Su et al. (2015)), as our descriptor learning module. Section 4.1 provides a description of datasets used in our experiments and we introduce our implementation details and network architecture. In the following sections, we carry out experiments to classify and retrieve 3D objects. In Section 4.3, we demonstrate the descriptor extracted by our model are robust to rotation. In section 4.4, we further investigate our model's effectiveness when adopting different settings, such as different representations of 3D inputs, different numbers of views, etc.

4.1 DATASET, IMPLEMENTATION AND TRAINING DETAILS

Dataset. We perform our experiments on the ModelNet40 (Wu et al. (2015)). ModelNet40 is one of the first benchmark datasets that acquired from CAD objects. This dataset contains 12,311 high-resolution, water eight 3D shapes in the mesh format. All 3D meshes are labeled into 40 categories. In our experiment, we apply the standard of splitting the dataset and use 9,843 shapes for training and 2,468 shapes for testing. In addition to ModelNet40 benchmark dataset, we also evaluate our method on ScanObjectNN (Uy et al. (2019)) dataset. Due to the page limit, we include this part in our supplementary materials.

Implementation and Training Details We adopt a Pytorch3D as the renderer $r_\tau(\cdot)$ to render 2D images for each 3D instance one-the-fly. In the following experiments, we adopt two descriptor learning modules $f_\theta(\cdot)$, GVCNN and MVCNN, to learn to extract robust and informative shape descriptors. From Algorithm 1, the network parameters are not increased. The entire model is implemented in Pytorch. An Adam optimizer with a batch size of 16 is used to train the entire network. The momentum was 0.9, and the weight decay rate is set to 10^{-5}. The learning rate starts at 0.0005 and then decreases by a factor of 0.5 every 20 epochs.

Method	Modality	Supervision	Classification	Retrieval
PointNet	point cloud	✓	89.2	70.5
PointNet++	point cloud	✓	91.9	85.3
PointCNN	point cloud	✓	91.8	83.8
Shi. et. al.	point cloud	✗	84.7	71.8
VoxNet	voxel grid	✓	83.0	-
SubvolumeSup	voxel grid	✓	89.2	-
Voxception-ResNet	voxel grid	✓	91.3	-
3D-DescripNet	voxel grid	✗	83.8	-
3D-GAN	voxel grid	✗	83.3	-
T-L Network	image + voxel	✗	74.4	-
MVCNN	12 views	✓	89.9	70.1
MVCNN, metric	12 views	✓	89.5	80.2
RotationNet	12 views	✓	90.7	-
MHBN	12 views	✓	93.4	-
3D2SeqViews	12 views	✓	93.4	90.8
MVCNN	12 views	✓	92.2	74.1
MVCNN (GoogLeNet), metric	12 views	✓	92.2	83.0
GVCNN (GoogLeNet)	12 views	✓	92.6	81.3
Ours (MVCNN)	dynamic views	✗	**93.6**	**85.3**
Ours (GVCNN)	dynamic views	✗	**94.3**	**85.9**

Table 1: **3D Shape classification and shape retrieval results on ModelNet40 dataset.** We compare the classification and retrieval performance of our CoLAV model with previous methods on the ModelNet40 dataset. Our model is trained without any supervision of ground truth but still outperforms most of the supervised methods on classification accuracy and retrieval mAP.

4.2 RESULTS ON MODELNET40

3D Object Classification: To the best of our knowledge, our work is the first to extract 3D shape descriptors from dynamic viewpoints without using ground truth labels. To validate the generalization ability of our proposed model, we conduct experiments for the task of 3D object classification on the ModelNet40 benchmark and compare our method against various baseline 3D shape descriptor learning methods. In this comparison, we not only compare with multi-view-based methods but also take methods using other types of 3D representation, such as point clouds, voxel grids, into consideration. For the 3D object classification task, we incorporate our model into GVCNN and MVCNN. We then train our network on the ModelNet40 dataset and test the classification accuracy. As part of the input, we employ random rotation,random scaling, and random jittering operations as $t(\cdot)$ to generate $t(x)$. Specifically, for a mesh object x, we random rotate the object in the range of $[-180°, 180°]$ around three axes (x, y, z) and random scaling the mash object in the range of $[0.75, 1.15]$. After random rotation and random scaling, we apply random jittering on each vertex of the 3D mesh. To that end, we add random displacement to each point and clip this displacement in the range of $[-0.04.0.04]$. Connotations of all feces remain the same as origin, which preserves the water-tight propriety of 3D mesh. We use same data augmentation but apply on other 3D shape instance to produce $t(x')$ as a negative sample. In this experiment, we render 12 images of each 3D shape instance and use $i = 5$ to perform the adversarial attack. For each step of adversarial attack, we use step size $\epsilon = 0.015$ to update rotation parameters α, β, γ. We evaluate the unsupervised learned 3D representation z by using a linear SVM with default parameters.

Experiment Results: Table 1 shows the classification accuracy of ColAV as well as other state-of-the-art methods on the ModelNet40 dataset. In spite of the fact that our method is completely self-supervised, Our MVCNN based model achieves 93.6% accuracy on 3D object classification on the ModelNet40 dataset, which surpasses the classification accuracy of previously proposed supervised methods listed on the table. Our GVCNN based model achieves 94.3% accuracy which further improves the classification accuracy and surpasses the supervised methods. Compared with MVCNN, our CoLAV(MVCNN) has an improvement of 1.5% on accuracy. Compared with GVCNN, which is used as another backbone model, our CoLAV network outperforms GVCNN by 1.7% of accuracy. Another notable difference is that in previous multi-view-based methods on the table, views are all generated statically before training.

Our CoLAV incorporates a dynamic view generating procedure leveraging the principle of adversarial attacks and boost performance. Our adversarial model can generate views on the fly dynamically. This indicates that for each iteration, a new set of 12 views will be generated. Throughout the entire training process, without adding new network parameters or adding extra data pre-processing, more views can be automatically rendered for the training process. To this end, a significant advantage of our proposed method raises, compared with static view-based multi-view methods.

3D Object Retrieval: Furthermore, we follow the same training setup we presented above to conduct the experiment on the task of 3D object retrieval. For each 3D object x_i, its respective shape representation z_i is used to perform the object retrieval. We calculate the distance between every two latent representations to conduct retrieval. Specifically, given a learned 3D shape representation z of a query shape x, we aim to find similar shapes by comparing the distance between z and every other shape descriptors z_i and select top j objects ranked by near distance in the latent space as its retrieval results. To evaluate the shape retrieval performance, we employ the mean average precision (mAP) as the evaluation metric.

Experiment Results: As shown in the last column of Table 1, our MVCNN based self-supervised method obtains 85.3 mAP when performing 3D object retrieval tasks on the ModelNet40 dataset, and GVCNN based method achieves the mAP of 85.9, which exceeds the performance of most of the supervised methods proposed by previous studies. In comparison to our baseline method MVCNN and GVCNN, our methods improve the retrieval mAP by 2.3 and 4.6 respectively.

4.3 ROBUSTNESS TO ROTATION

In this section, we conduct further experiments to explore the resistance to rotation. Since our model dynamically generates 2D views by performing adversarial attacks to force the network to take the worst object rotation into consideration, our model is expected to be highly robust to the rotation. This test is designed to measure our performance dealing with 3D objects which are rotated into

Figure 2: **Adversarial Views:** We observe the adversarial views generated during the adversarial attack procedure. Our model gradually rotates the 3D objects to capture less informative views that can fool the network. These views are utilized to provide difficulty to the following training process and urge the network to draw more powerful feature representations.

different angles. **Experiment Setup:** In this experiment, test the rotation robustness of our model on the ModelNet40 benchmark dataset. We rotated the testing data around a random axis by either 90 or 180 degrees and reported the performance. In this experiment, we validate the robustness of our model and compared it with both point cloud and multi-view based methods.

Experiment Results: As shown in Table 2 our self-supervised CoLAV network with both 6 views and 12 views configuration achieves attractive robustness to the rotation. Dealing with 90 degrees of rotation along the gravity axis, our 6 views model performs 90.8 acc of classification, which is the best among all the previous methods, including all the supervised methods listed on the table. For 180 degrees of rotation along the Y-axis, our 12 views model outperforms all the previous methods, obtaining 90.9 acc.

Method	Modality	Supervision	90°	180°
PointNet Qi et al. (2017a)	point cloud	✓	42.5	38.6
PointNet++ Qi et al. (2017b)	point cloud	✓	47.9	39.7
RSCNN Hu et al. (2021)	point cloud	✓	90.3	90.3
MVCNN Su et al. (2015)	12 views	✓	84.4	84.2
ViewGCN Wei et al. (2020)	12 views	✓	86.0	86.0
GVCNN Feng et al. (2018)	12 views	✓	88.9	89.7
Ours(MVCNN)	6 views	✗	89.3	89.4
Ours(MVCNN)	12 views	✗	90.1	89.7
Ours(GVCNN)	6 views	✗	**90.8**	90.3
Ours(GVCNN)	12 views	✗	90.4	**90.9**

Table 2: **Rotation Robustness of 3D Methods.** We test our CoLAV model's robustness against rotations around Y-axis (vertical to the ground) on ModelNet40. Without ground truth supervision, our model with 6 and 12 views configuration performs the highest level of robustness to 90° and 180° rotation among all methods.

4.4 Ablation study

In this section, We study the effect of the components of our model by ablating various designs of our method. First, we investigate the effect of the number of views during training and testing, then, analyze the adversarial views generated by our network is presented. Due to the page limitation, the experiment conducted to explore the effect of different augmentation operations we adopt during the model training process and the effectiveness of our proposed adversarial attack are included in the Appendix.

Training V.	Testing V.	GVCNN	MVCNN	Ours(G.)	Ours(M.)
8	2	71.2	68.3	91.2	88.7
8	4	91.1	84.5	92.9	90.1
8	8	93.1	87.4	93.6	91.9
8	12	91.5	86.8	94.1	93.1
12	2	76.8	71.1	91.7	90.2
12	4	90.3	87.6	92.1	91.6
12	8	92.1	90.5	93.9	92.2
12	12	92.6	92.2	94.3	93.6

Table 3: **Ablation Study on Number of Views:** We conduct an ablation study to examine the effect of different numbers of training and testing views selected on our multi-view network. "Training V." indicates the number of views used during the network training, and "Testing V." indicates the number of views used during the inference period. Our network achieves an impressive accuracy even if only two testing views are applied, where "Our (G.)" indicates the GCVNN based network and "Our (M.)" indicates the MVCNN based network.

4.4.1 EFFECT OF NUMBER OF VIEWS:

In this study, we investigate the impact of different numbers of views on our model performing 3D object classification. We apply $\{8, 12\}$ views to train CoLAV and retrain the MVCNN and GVCNN. We adopt $\{2, 4, 8, 12\}$ views during the testing phase. As is listed in Table 3, our model outperforms our baseline GVCNN and MVCNN in all the combinations of training and testing views selected. Even when we employ two views for testing, which is arduous for other methods, our model can still achieve a high level of accuracy. We attribute this success to the adversarial attack procedure that generates challenging positive samples for the network to learn from and causes the network to draw informative descriptors from the two views selected via contrastive learning.

4.4.2 ADVERSARIAL VIEW ANALYSIS:

We analyze the effectiveness of our adversarial attack procedure by observing the adversarial views generated by our model. As shown in Figure 2, with i defined in Equation 1 representing the number of iterations of adversarial attack, we can see that our model will gradually rotate the adversarial views to challenging angles which depict less informative details of the 3D object. When $i = 5$, the adversarial views of the sofa are highly ambiguous that even human eyes cannot recognize the object easily. And with the help of the contrastive learning procedure in the following steps, the network is expected to draw a more sophisticated and invariant descriptor for each 3D object to enhance classification accuracy on these challenging views.

5 CONCLUSION

In this paper, we introduce a novel concept of adversarial views generated via a self-supervised contrastive learning mechanism that augments the positive training samples by performing shape-instance-dependent adversarial attacks and introduce a novel multi-view pipeline that directly takes 3D instance as input. More importantly, different from the previous multi-view-based methods using pre-rendered static views for the training of deep neural networks, CoLAV can dynamically generate views for a given 3D instance on the fly without requiring additional network parameters. Extensive experiments conducted on different benchmark datasets demonstrate the effectiveness of the newly introduced adversarial views generated from CoLAV. Our self-supervised CoLAV boosts the 3D classification accuracy and 3D retrieval mAP to outperform the supervised methods previously proposed. In addition, ablation studies of our model prove the effectiveness and efficiency of the proposed components. Our method highly improves robustness to rotation thanks to the adversarial views dynamically generated by our adversarial attack procedure.

REFERENCES

Avishek Joey Bose, Huan Ling, and Yanshuai Cao. Compositional hard negatives for visual semantic embeddings via an adversary.

Avishek Joey Bose, Huan Ling, and Yanshuai Cao. Adversarial contrastive estimation. *arXiv preprint arXiv:1805.03642*, 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Christopher Choy, JunYoung Gwak, and Silvio Savarese. 4d spatio-temporal convnets: Minkowski convolutional neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3075–3084, 2019.

Yifan Feng, Zizhao Zhang, Xibin Zhao, Rongrong Ji, and Yue Gao. Gvcnn: Group-view convolutional neural networks for 3d shape recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304. JMLR Workshop and Conference Proceedings, 2010.

Zhizhong Han, Mingyang Shang, Zhenbao Liu, Chi-Man Vong, Yu-Shen Liu, Matthias Zwicker, Junwei Han, and CL Philip Chen. Seqviews2seqlabels: Learning 3d global features via aggregating sequential views by rnn with attention. *IEEE Transactions on Image Processing*, 28(2): 658–672, 2018.

Zhizhong Han, Honglei Lu, Zhenbao Liu, Chi-Man Vong, Yu-Shen Liu, Matthias Zwicker, Junwei Han, and CL Philip Chen. 3d2seqviews: Aggregating sequential views for 3d global feature learning by cnn with hierarchical attention aggregation. *IEEE Transactions on Image Processing*, 28(8):3986–3999, 2019.

Rana Hanocka, Amir Hertz, Noa Fish, Raja Giryes, Shachar Fleishman, and Daniel Cohen-Or. Meshcnn: a network with an edge. *ACM Transactions on Graphics (TOG)*, 38(4):1–12, 2019.

Chih-Hui Ho and Nuno Vasconcelos. Contrastive learning with adversarial examples. *arXiv preprint arXiv:2010.12050*, 2020.

Chih-Hui Ho, Bo Liu, Tz-Ying Wu, and Nuno Vasconcelos. Exploit clues from views: Self-supervised and regularized learning for multiview object recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9090–9100, 2020.

Linshu Hu, Mengjiao Qin, Feng Zhang, Zhenhong Du, and Renyi Liu. Rscnn: A cnn-based method to enhance low-light remote-sensing images. *Remote Sensing*, 13(1):62, 2021.

Asako Kanezaki, Yasuyuki Matsushita, and Yoshifumi Nishida. Rotationnet: Joint object categorization and pose estimation using multiviews from unsupervised viewpoints. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5010–5019, 2018.

Roman Klokov and Victor Lempitsky. Escape from cells: Deep kd-networks for the recognition of 3d point cloud models. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 863–872, 2017.

Alexey Kurakin, Ian Goodfellow, Samy Bengio, et al. Adversarial examples in the physical world, 2016.

Chun-Liang Li, Tomas Simon, Jason Saragih, Barnabás Póczos, and Yaser Sheikh. Lbs autoencoder: Self-supervised fitting of articulated meshes to point clouds. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11967–11976, 2019.

Xiang Li, Congcong Wen, Lingjing Wang, and Yi Fang. Topology-constrained shape correspondence. *IEEE transactions on visualization and computer graphics*, 2020.

Daniel Maturana and Sebastian Scherer. Voxnet: A 3d convolutional neural network for real-time object recognition. In *Intelligent Robots and Systems (IROS), 2015 IEEE/RSJ International Conference on*, pp. 922–928. IEEE, 2015.

Shun Miao, Z Jane Wang, and Rui Liao. A cnn regression approach for real-time 2d/3d registration. *IEEE transactions on medical imaging*, 35(5):1352–1363, 2016.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *2016 IEEE European symposium on security and privacy (EuroS&P)*, pp. 372–387. IEEE, 2016.

Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. *Proc. Computer Vision and Pattern Recognition (CVPR), IEEE*, 1(2):4, 2017a.

Charles R Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *arXiv preprint arXiv:1706.02413*, 2017b.

Charles Ruizhongtai Qi, Hao Su, Matthias Niessner, Angela Dai, Mengyuan Yan, and Leonidas Guibas. Volumetric and multi-view cnns for object classification on 3d data. 04 2016.

Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 815–823, 2015.

Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! *arXiv preprint arXiv:1904.12843*, 2019.

Yi Shi, Mengchen Xu, Shuaihang Yuan, and Yi Fang. Unsupervised deep shape descriptor with point distribution learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9353–9362, 2020.

Kihyuk Sohn. Improved deep metric learning with multi-class n-pair loss objective. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pp. 1857–1865, 2016.

Hang Su, Subhransu Maji, Evangelos Kalogerakis, and Erik Learned-Miller. Multi-view convolutional neural networks for 3d shape recognition. In *Proceedings of the IEEE international conference on computer vision*, pp. 945–953, 2015.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv preprint arXiv:1906.05849*, 2019.

Mikaela Angelina Uy, Quang-Hieu Pham, Binh-Son Hua, Thanh Nguyen, and Sai-Kit Yeung. Revisiting point cloud classification: A new benchmark dataset and classification model on real-world data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1588–1597, 2019.

Xin Wei, Ruixuan Yu, and Jian Sun. View-gcn: View-based graph convolutional network for 3d shape analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1850–1859, 2020.

Chao-Yuan Wu, R Manmatha, Alexander J Smola, and Philipp Krahenbuhl. Sampling matters in deep embedding learning. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2840–2848, 2017.

Jiajun Wu, Chengkai Zhang, Tianfan Xue, Bill Freeman, and Josh Tenenbaum. Learning a probabilistic latent space of object shapes via 3d generative-adversarial modeling. In *Advances in neural information processing systems*, pp. 82–90, 2016.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1912–1920, 2015.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3733–3742, 2018.

Chong Xiang, Charles R Qi, and Bo Li. Generating 3d adversarial point clouds. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9136–9144, 2019.

Cihang Xie and Alan Yuille. Intriguing properties of adversarial training at scale. *arXiv preprint arXiv:1906.03787*, 2019.

Cihang Xie, Mingxing Tan, Boqing Gong, Jiang Wang, Alan L Yuille, and Quoc V Le. Adversarial examples improve image recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 819–828, 2020.

Ze Yang and Liwei Wang. Learning relationships for multi-view 3d object recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7505–7514, 2019.

Mang Ye, Xu Zhang, Pong C Yuen, and Shih-Fu Chang. Unsupervised embedding learning via invariant and spreading instance feature. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6210–6219, 2019.

Shuaihang Yuan and Yi Fang. Ross: Robust learning of one-shot 3d shape segmentation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1961–1969, 2020.

Xiaohui Zeng, Chenxi Liu, Yu-Siang Wang, Weichao Qiu, Lingxi Xie, Yu-Wing Tai, Chi-Keung Tang, and Alan L Yuille. Adversarial attacks beyond the image space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4302–4311, 2019.

Figure 3: **Qualitative results of 3D shape retrieval task on ModelNet40 dataset:**

A APPENDIX

A.1 3D SHAPE RETRIEVAL TASK ON MODELNET40

We show examples of our 3D object retrieval in Figure 3. For each group of 3D shapes, the shape to the left of the vertical line is the query object from the test set, and on the right side of the line, we show the retrieved objects from the training set.

A.2 SCANOBJECTNN.

In addition to ModelNet40 benchmark dataset, we also evaluate our method on ScanObjectNN Uy et al. (2019) dataset. ScanObjectNN is the newest and one of the most challenging datasets for 3D object recognition. It is acquired from the real-world object in 3D point cloud representation and three variants are proposed for different levels of difficulty. 1) Vanilla ScanObjectNN dataset contains clean 3D object point clouds. 2) Background ScanObjectNN dataset which includes real-world background information of each 3D object. 3) Perturbed ScanObjectNN dataset performs random perturbation on the Background ScanObjectNN dataset to increase the difficulty of 3D object recognition tasks. In our experiment, we adopt the Vanilla ScanObjectNN dataset to evaluate our method. The reason why we use the "vanilla" version is that other versions of ScanObjectNN contain backgrounds which could lead the propped adversarial view only to reflect the background and occlude the 3D objects. The first variant is composed of 2902 3D point clouds and each 3D point cloud has its unique label from 1 to 15. ScanObjectNN Uy et al. (2019) randomly split into a training set (80%) and test set (20%) and we follow this protocol to conduct our experiment.

3D Object Classification: In this section, we conduct experiments for the task of 3D object classification on the ScanObjectNN benchmark and compare our method with many other methods retrained on the ScanObjectNN dataset. In this comparison, we consider multiple representation learning methods taking different 3D modalities as input such as point clouds into consideration. Similar to Section **??**, we use GVCNN and MVCNN as two different backbone module $f_\theta(\cdot)$. Different from ModelNet40, ScanObjectNN is a point cloud based dataset. To apply multi-view based

Method	Modality	Supervision	Classification	Retrieval
PointNet	point cloud	✓	79.2	64.8
PointNet++	point cloud	✓	84.3	76.6
KD-Networks	point cloud	✓	84.1	76.1
Shi. et. al.	point cloud	✗	78.7	65.1
MVCNN	12 views	✓	79.8	63.9
MVCNN, metric	12 views	✓	80.1	64.1
RotationNet	12 views	✓	81.4	-
MHBN	12 views	✓	83.6	-
3D2SeqViews	12 views	✓	83.8	75.5
MVCNN (GoogLeNet)	12 views	✓	82.0	74.1
MVCNN (GoogLeNet), metric	12 views	✓	82.1	74.3
GVCNN (GoogLeNet)	12 views	✓	83.1	75.9
Ours (MVCNN)	dynamic views	✗	**84.1**	**76.2**
Ours (GVCNN)	dynamic views	✗	**85.4**	**76.8**

Table 4: **3D Shape classification and retrieval results on ScanObjectNN dataset.** We compare the classification and retrieval performance of our CoLAV model with previous methods on the ScanObjectNN dataset. Our model is trained without any supervision of ground truth but still outperforms most of the supervised methods on classification accuracy.

3D representation learning method, we re-render 3D objects from multiple viewpoints. Here, we adopt 12 viewpoints in this experiment. An elevation angle of $\pi/9$ is applied for all viewpoints with azimuths sampled form $[0, \pi)$ uniformly.

In our proposed model, we adopt Pytorch3D as differentiable renderer and use its point cloud rendering utilities. We also employ random rotation, random scaling, and random jittering operations as $t/(\cdot)$ to generate $t(x)$ as we specified in Section **??**. Furthermore, we add the random dropout in $t(\cdot)$ operation as the last augmentation. In this experiment, we use $i = 8$ to perform the adversarial attack with step size $\epsilon = 0.005$ to update rotation parameters α, β, γ. we adopt the same default linear SVM from scikit-learn library to perform the downstream task of 3D object classification.

Experiment Results: In Table 4, we compare the classification accuracy of ColAV with other retrained methods, including PointNet Qi et al. (2017a), PointNet++ Qi et al. (2017b), KD-Networks Klokov & Lempitsky (2017), VoxNet Maturana & Scherer (2015), 3D-GAN Wu et al. (2016), MVCNN Su et al. (2015) and GVCNN Feng et al. (2018), on the ScanObjectNN dataset. As listed in Table 4, Our two backbones achieve 84.1% and 85.4% of accuracy on 3D object classification, which outperforms existing supervised methods. This demonstrates our proposed method can effectively find challenging views and hence increase the generalize ability of the backbone model. Specifically, compared with MVCNN, our CoLAV(MVCNN) improve the performance by 2% on accuracy and our CoLAV(GCVNN) network outperforms GVCNN by 2.3% of accuracy.

3D Object Retrieval In this subsection, we follow the protocol that was presented in Section **??** to evaluate our proposed method on 3D object retrieval.

Experiment Results: As shown in the last column of Table 4, our methods achieve the best result compared with other methods listed in the table. Specifically, CoLAV(MVCNN) improves the mAP by 1.9 compared with MVCNN (GoogLeNet), metric Su et al. (2015). CoLAV(GVCNN) achieve the retrieval mAP of 76.8 which outperform the baseline result, GVCNN (GoogLeNet) Feng et al. (2018) 75.9, by 0.9. This improvement validates the effectiveness of our proposed method in the 3D object recognition task.

A.3 EFFECT OF DIFFERENT AUGMENTATION OPERATION:

In section 3.3, we introduce our unsupervised method which leverages the power of contrastive learning which relies on different data augmentation operations. In this section, we conduct various experiments on ModelNet40 to investigate the effect of different data augmentations. As presented in Table 5, we adopt three different sets of data augmentation operations for mesh objects. The first set of operations contains random rotation, random scaling, and random jittering. The second set of

operations contains random scaling and random jittering. The third set of operations only contains random jittering. In addition to mesh objects, we also conduct experiments on point clouds and three sets of augmentations are used moreover, a random dropout of point cloud is also been added to $t(\cdot)$. To validate the performance on the point cloud, we first randomly sample 2048 points from ModelNet40 data set and we use the point cloud rendering function from Pytorch3D library to render 3D point clouds. From Table 5 we can see that our proposed method achieves the best result when adopting complex data augmentation. Observing from the second, fourth rows, and eighth and tenth rows of Table 5 we find that the rotation operation contributes less during the learning process. This can be attributed to our proposed adversarial attack which can generate rotated adversarial samples.

Method	Modality	Augmentations	Accuracy
Ours(MV.)	Mesh	Set 1	93.6
Ours(GV.)	Mesh	Set 1	**94.3**
Ours(MV.)	Mesh	Set 2	93.5
Ours(GV.)	Mesh	Set 2	**94.3**
Ours(MV.)	Mesh	Set 3	93.1
Ours(GV.)	Mesh	Set 3	94.1
Ours(MV.)	Point Cloud	Set 1+dropout	93.1
Ours(GV.)	Point Cloud	Set 1+dropout	**93.8**
Ours(MV.)	Point Cloud	Set 2+dropout	93.1
Ours(GV.)	Point Cloud	Set 2+dropout	**93.78**
Ours(MV.)	Point Cloud	Set 3+dropout	92.6
Ours(GV.)	Point Cloud	Set 3+dropout	93.2

Table 5: **Effect of Different Augmentation** We investigate the effect of different augmentations that are adopted during our experiment. Our model is insensitive to the rotation augmentation.

Method	Modality	Accuracy
Ours(MV.)	Mesh	93.6
Self-Supervised MV.	Mesh	92.3
Ours(GV.)	Mesh	**94.3**
Self-Supervised GV.	Mesh	93.2
Ours(MV.)	Point Cloud	93.1
Self-Supervised MV.	Point Cloud	91.8
Ours(GV.)	Point Cloud	**93.8**
Self-Supervised GV.	Point Cloud	92.7

Table 6: **Effect of Adversarial Attack** We investigate the effect of our proposed adversarial attack by comparing it with a supervised version.

A.3.1 EFFECT OF ADVERSARIAL ATTACK:

In this section, we further investigate the effectiveness of our proposed adversarial attack from two aspects. We train CoLAV(GVCNN) on ModelNet40 dataset using 9,843 shapes and compare our proposed method with our method that depreciates the adversarial attack which is a self-supervised multi-view based 3D representation learning method. Specifically, we use random rotation, random scaling, and random jittering as $t(\cdot)$ and we use

$$\mathcal{L}_{\mathbf{3dco},\theta}(x, t(x), t(x')) = \tag{10}$$
$$- \log \frac{e^{(sim(f(r(x)), f(r(t(x))))/\Gamma)}}{e^{sim(f(r(x)), f(r(t(x))))/\Gamma} + e^{sim(f(r(x)), f(r(t(x'))))/\Gamma}},$$

as the objective function to unsupervisedly train the network. The experimental results can be found in Table 6. Our adversarial attack achieved over 1.0% of improvement on classification accuracy comparing with the self-supervised approach. Moreover, our supervised methods also outperform GVCNN and MVCNN by 0.4% and 0.1% respectively.