Collaborative Linear Bandits with Adversarial Agents: Near-Optimal Regret Bounds

Abstract

We consider a linear stochastic bandit problem involving M agents that can collaborate via a central server to minimize regret. A fraction α of these agents are adversarial and can act arbitrarily, leading to the following tension: while collaboration can potentially reduce regret, it can also disrupt the process of learning due to adversaries. In this work, we provide a fundamental understanding of this tension by designing new algorithms that balance the exploration-exploitation trade-off via carefully constructed robust confidence intervals. We also complement our algorithms with tight analyses. First, we develop a robust collaborative phased elimination algorithm that achieves $\tilde{O}\left(\alpha + 1/\sqrt{M}\right)\sqrt{dT}$ regret for each good agent; here, d is the model-dimension and T is the horizon. For small α, our result thus reveals a clear benefit of collaboration despite adversaries. Using an information-theoretic argument, we then prove a matching lower bound, thereby providing the first set of tight, near-optimal regret bounds for collaborative linear bandits with adversaries. Furthermore, by leveraging recent advances in high-dimensional robust statistics, we significantly extend our algorithmic ideas and results to (i) the generalized linear bandit model that allows for non-linear observation maps; and (ii) the contextual bandit setting that allows for time-varying feature vectors.

1 Introduction

One of the primary challenges in modern large-scale computing systems is that of *security*. Given that the individual agents in such large systems are often vulnerable to attacks, it is important to understand how the overall system behaves in the face of adversarial corruptions. This observation has spurred a line of research dedicated to the design and analysis of distributed algorithms that are provably robust to a small fraction of adversarial agents; notably, motivated by emerging learning paradigms such as federated learning [1–3], this body of work has focused primarily on empirical risk minimization/stochastic optimization [4–14]. However, when it comes to multi-agent sequential decision-making problems under uncertainty (e.g., bandits and reinforcement learning), our understanding of analogous questions is quite limited. Our goal in this paper is to bridge the above gap by studying a collaborative linear bandit [15, 16] problem in the presence of adversaries.

In our model, M agents interact with the same linear bandit characterized by a d-dimensional unknown parameter θ_*, and a finite set of K arms. These agents can collaborate via a central server to improve performance, as measured by cumulative regret. As examples, consider (i) a team of robots exploring actions (arms) in a common environment and interacting with a central controller; and (ii) a group of people exploring restaurants (arms) and writing reviews for a web-recommendation server. In the absence of adversaries, there is a clear reason to collaborate in either case: by exchanging information, each agent can reduce it's uncertainty about the arms faster than it could when it acts alone, and thereby incur lesser regret. The situation becomes murkier and more delicate when certain

agents *misbehave*: What if certain robots get attacked or certain people deliberately write spam reviews? More generally, the main question we ask in this paper is the following.

In a multi-agent linear stochastic bandit problem, can we still hope for benefits of collaboration when a fraction α of the agents are adversarial? If so, what are the fundamental limits of such benefits?

As far as we are aware, the answers to these questions have thus far remained elusive, motivating our current study. The main technical hurdle we must overcome is to delicately balance the exploration-exploitation trade-off in the presence of both statistical uncertainties due to the environment, and *worst-case* adversarial behavior. Importantly, the above trade-off - intrinsic to sequential decision-making - is absent in static optimization problems. Thus, the ideas used to guarantee robustness for distributed optimization do not apply to our problem, making our task quite non-trivial.

Our Contributions. In this paper, we contribute to a principled study of several canonical *structured* linear bandit settings with adversarial agents. Our specific contributions are as follows.

• **Robust Collaborative Linear Bandit Algorithm.** We propose RCLB - a phased elimination algorithm that relies on distributed exploration, and balances the exploration-exploitation dilemma in the presence of adversaries via carefully constructed *robust confidence intervals*. We prove that RCLB guarantees $\tilde{O}\left(\left(\alpha + 1/\sqrt{M}\right)\sqrt{dT}\right)$ regret for each good agent; see Theorem 1. This result is both novel, and significant in that it reveals a clear benefit of collaboration (despite adversaries) for small values of α. In particular, when $\alpha = 0$, the regret bound of RCLB is minimax-optimal in all relevant parameters: the model-dimension d, the horizon T, and the number of agents M.

• **Fundamental Limits.** At this stage, one may ask: *Is the additive $\alpha\sqrt{T}$ term in Theorem 1 simply an artifact of our analysis?* In Theorem 2, we establish a fundamental lower bound, revealing that such a term is in fact unavoidable; it is the price one must pay due to adversarial corruptions. A key implication of this result is that *our work is the first to provide tight, near-optimal regret bounds for collaborative linear bandits with adversaries.* The proof of Theorem 2 relies on a novel connection between the information-theoretic arguments in [17], and ideas from the robust mean estimation literature [18, 19]. As such, our proof technique may be relevant for related settings.

In our next set of contributions, we significantly extend our results to more general bandit models.

• **Generalized Linear Bandit Setting.** In Theorem 3, we prove that one can achieve bounds akin to that in Theorem 1 for the generalized linear bandit model (GLM) [20, 21] that accounts for non-linear observation maps. To achieve this result, we propose a variant of RCLB that leverages very recently developed tools from high-dimensional robust Gaussian mean estimation [22]. Deriving robust confidence intervals for this setting requires some work: we exploit regularity properties of the non-linear observation model along with error bounds from [22] for this purpose. As far as we are aware, Theorem 3 is the first result to establish adversarial-robustness for GLMs, allowing our framework to be applicable to a broad class of problems (e.g., logistic and probit regression models).

• **Contextual Bandit Setting.** Finally, we turn our attention to the contextual bandit setting where the feature vectors of the arms can change over time. This setting is practically quite relevant as web-recommendation systems are often modeled as contextual bandits [23]. The main challenge here arises from the need to simultaneously contend with time-varying optimal arms and adversaries. To handle this scenario, we develop a robust variant of the SUPLINREL algorithm [24] that guarantees a near-optimal regret bound identical to that of Theorem 1; see Theorem 4.

Overall, via the proposal of new robust algorithms complemented with tight analyses, our work takes an important step towards multi-agent sequential decision-making in the presence of adversaries.

Related Work. There is a growing strand of literature that studies the effect of reward corruption in stochastic bandits (for a single-agent setting) where the adversary has a fixed corruption budget [25–31]. The techniques in these papers do not apply to our work as our setting is very different: the adversarial agents in our model can act *arbitrarily*, and have no budget constraints. Several papers study multi-agent bandit problems in the absence of adversaries [32–51]. A few very recent ones [52–55] also look at the effect of attacks, but for the simpler unstructured multi-armed bandit problem. Accounting for adversarial agents in the structured linear bandit setting we consider here requires significantly different techniques that we develop in this paper.

Notation. For any positive integer n, we use $[n]$ to denote the set $\{1, \ldots, n\}$. We use a' to represent the transpose of a vector a, and I_p to denote the identity matrix of dimension p.

2 Problem Formulation

We consider a setting comprising of a central server and M agents; the agents can communicate only via the server. Each agent $i \in [M]$ interacts with the same linear bandit model characterized by an unknown parameter θ_* that belongs to a known compact set $\Theta \subset \mathbb{R}^d$. We assume $\|\theta_*\| \leq 1$.[1] The set of actions $\mathcal{A}$ for each agent is given by K distinct vectors in $\mathbb{R}^d$, i.e., $\mathcal{A} = \{a_1, \ldots, a_K\}$, where K is a finite, positive integer. Based on all the information acquired by an agent up to time $t - 1$, it takes an action $a_{i,t} \in \mathcal{A}$ at time t, and receives a reward $y_{i,t}$ given by the following observation model:

$$y_{i,t} = \langle \theta_*, a_{i,t} \rangle + \eta_{i,t}. \tag{1}$$

Here, $\{\eta_{i,t}\}$ is a sequence of independent Gaussian random variables with zero mean and unit variance. Thus far, we have essentially described a distributed/multi-agent linear stochastic bandit model. Departing from this standard model, we focus on a setting where a fraction $\alpha \in [0, 1/2)$ of the agents are adversarial; the adversarial set is denoted by $\mathcal{B}$, where $|\mathcal{B}| = \alpha M$. In particular, we consider a *worst-case* attack model, where each adversarial agent $i \in \mathcal{B}$ is assumed to have complete knowledge of the system, and is allowed to act arbitrarily. Under this attack model, an agent $i \in \mathcal{B}$ can transmit arbitrarily corrupted messages to the central server.

Our performance measure of interest is the following group regret metric R_T defined w.r.t. the non-adversarial agents:

$$R_T = \mathbb{E}\left[\sum_{i \in [M] \setminus \mathcal{B}} \sum_{t=1}^{T} \langle \theta_*, a_* - a_{i,t} \rangle \right], \tag{2}$$

where $a_* = \operatorname{argmax}_{a \in \mathcal{A}} \langle \theta_*, a \rangle$ is the optimal arm, and T is the time horizon.[2] We will work under a regime where the horizon T is large, satisfying $T \geq Md$. The goal of the good (non-adversarial) agents is to collaborate via the server and play a sequence of actions that minimize the group regret R_T. Let us now make a few key observations. In principle, each good agent can choose to act independently throughout (i.e., not talk to the server at all), and achieve $\tilde{O}(\sqrt{dT})$ regret by playing a standard bandit algorithm. Clearly, the group regret R_T would scale as $\tilde{O}\left((1-\alpha)M\sqrt{dT}\right)$ in such a case. In the absence of adversaries however, one can achieve a significantly better group regret bound of $\tilde{O}\left(\sqrt{MdT}\right)$ via collaboration, i.e., the regret per good agent can be reduced by a factor of $\sqrt{M}$ relative to the case when it acts independently (see, for instance, [40] and [44]). Our specific interest in this paper is to investigate whether, and to what extent, one can retain the benefits of collaboration despite the worst-case attack model described above. Said differently, we ask: *Can we improve upon the trivial per agent regret bound of $\tilde{O}(\sqrt{dT})$ in the presence of adversaries?*

Throughout the rest of the paper, we will answer the above question in the affirmative by deriving novel robust algorithms for several canonical bandit models, and then establishing near-optimal regret bounds for each such model.

3 Robust Collaborative Phased Elimination Algorithm for Linear Bandits

In this section, we develop a robust phased elimination algorithm that achieves the near-optimal regret bound of $\tilde{O}\left(\left(\alpha + \sqrt{1/M}\right)\sqrt{dT}\right)$ per good agent. This is non-trivial as we must account for the worst-case attack model described in Section 2. To highlight the challenges that we need to overcome, consider the following scenario. During the initial stages of the learning process, when the arms in $\mathcal{A}$ have not been adequately sampled by the agents, even a good agent i may have "poor estimates" of the true payoffs associated with each arm, i.e., the variance associated with such estimates may be large. This statistical uncertainty can be exploited by the adversarial agents to their benefit. In particular, we need to devise an approach that can distinguish between benign stochastic perturbations (due to the noise in our model) and deliberate adversarial behavior. In what follows, we describe our proposed algorithm - `Robust Collaborative Phased Elimination for Linear Bandits (RCLB)` - that precisely does so in a principled way.

---

[1] Unless otherwise mentioned, $\|\cdot\|$ will be used to represent the Euclidean norm.

[2] For ease of exposition, we assume that there is an unique optimal arm.

Algorithm 1 Robust Collaborative Phased Elimination for Linear Bandits (`RCLB`)

Input: Action set $\mathcal{A} = \{a_1, \ldots, a_K\}$, confidence parameter δ, and corruption fraction α.

Initialize: $\ell = 1$ and $\mathcal{A}_1 = \mathcal{A}$.

1: Let $V_\ell(\pi) \triangleq \sum_{a \in \mathcal{A}_\ell} \pi(a) a a'$ and $g_\ell(\pi) \triangleq \max_{a \in \mathcal{A}_\ell} \|a\|^2_{V_\ell(\pi)^{-1}}$. Server solves an approximate G-optimal design problem to compute a distribution π_ℓ over $\mathcal{A}_\ell$ such that $g_\ell(\pi_\ell) \leq 2d$ and $|\mathrm{Supp}(\pi_\ell)| \leq 48d \log\log d$.

2: For each $a \in \mathcal{A}_\ell$, server computes $m_a^{(\ell)}$ via Eq. (5), and broadcasts $\{m_a^{(\ell)}\}_{a \in \mathcal{A}_\ell}$ to all agents.

3: **for** $i \in [M] \setminus \mathcal{B}$ **do**

4:     For each arm $a \in \mathcal{A}_\ell$, pull it $m_a^{(\ell)}$ times. Let $r_{i,a}^{(\ell)}$ be the average of the rewards observed by agent i for arm a during phase ℓ.

5:     Compute local estimate $\hat{\theta}_i^{(\ell)}$ of θ_* as follows.[3]

$$\hat{\theta}_i^{(\ell)} = \tilde{V}_\ell^{-1} Y_{i,\ell}, \quad \text{where} \ \ \tilde{V}_\ell = \sum_{a \in \mathrm{Supp}(\pi_\ell)} m_a^{(\ell)} a a' \ ; \ \ Y_{i,\ell} = \sum_{a \in \mathrm{Supp}(\pi_\ell)} m_a^{(\ell)} r_{i,a}^{(\ell)} a. \tag{3}$$

6:     Transmit $\hat{\theta}_i^{(\ell)}$ to server. Adversarial agents can transmit arbitrary vectors at this stage.

7: **end for**

8: Server computes robust mean pay-offs for each active arm: for each $a \in \mathcal{A}_\ell$, estimate $\mu_a^{(\ell)}$ as

$$\mu_a^{(\ell)} = \mathtt{Median}\left(\{\langle \hat{\theta}_i^{(\ell)}, a \rangle, i \in [M]\}\right).$$

9: Define robust confidence threshold $\gamma_\ell \triangleq \sqrt{2}C\left(1 + \alpha\sqrt{M}\right)\epsilon_\ell$, where C is as in Lemma 1. Server performs phased elimination with the robust means and γ_ℓ to update active arm set:

$$\mathcal{A}_{\ell+1} = \{a \in \mathcal{A}_\ell : \max_{b \in \mathcal{A}_\ell} \mu_b^{(\ell)} - \mu_a^{(\ell)} \leq 2\gamma_\ell\}. \tag{4}$$

10: $\ell = \ell + 1$ and **Goto** line 1.

Description of `RCLB` (Algorithm 1). The `RCLB` algorithm we propose is inspired by the phased elimination algorithm in [56, Chapter 22], but features some key differences due to the distributed and adversarial nature of our problem. The algorithm proceeds in epochs/phases, and in each phase ℓ, the server maintains an active candidate set $\mathcal{A}_\ell$ of potential optimal arms. The exploration of arms in $\mathcal{A}_\ell$ is distributed among the agents. Upon such exploration, each agent i reports back a local estimate $\hat{\theta}_i^{(\ell)}$ of the unknown parameter θ_*; adversarial agents can transmit arbitrarily corrupted messages at this stage. Using the local parameter estimates $\{\hat{\theta}_i^{(\ell)}\}_{i \in [M]}$, the server then constructs (i) a *robust* estimate of the true mean payoff $\langle \theta_*, a \rangle$ for each active arm $a \in \mathcal{A}_\ell$, and (ii) an *inflated* confidence interval that captures both statistical and adversarial uncertainties associated with such robust mean estimates. This step is crucial to our scheme and requires a lot of care as we explain shortly. With the robust mean payoffs and associated confidence intervals in hand, the server eliminates arms with rewards far away from that of the optimal arm a_*. We now elaborate on the above ideas.

● *Optimal Experimental Design.* To minimize the regret incurred in each phase ℓ, we need to minimize the number of arm-pulls made to arms in $\mathcal{A}_\ell$. To that end, we appeal to a concept from statistics known as optimal experimental design. The concept is as follows. Let $\pi : \mathcal{A} \to [0, 1]$ be a distribution on $\mathcal{A}$ such that $\sum_{a \in \mathcal{A}} \pi(a) = 1$. Now define $V(\pi) \triangleq \sum_{a \in \mathcal{A}} \pi(a) a a'$; $g(\pi) \triangleq \max_{a \in \mathcal{A}} \|a\|^2_{V(\pi)^{-1}}$. The so-called *G-optimal design problem* seeks to find a distribution (design) π_* that minimizes g. In essence, sampling each arm $a \in \mathcal{A}$ in proportion to $\pi_*(a)$ minimizes the number of samples/arm-pulls needed to achieve a desired level of precision in the estimates of the arm means $\langle \theta_*, a \rangle$, $a \in \mathcal{A}$. For our purpose, we only need to solve an approximate G-optimal design problem: using the Frank-Wolfe algorithm and an appropriate initialization, one can in fact find an approximate optimal design π such that $g(\pi) \leq 2d$, and $|\mathrm{Supp}(\pi)| \leq 48d \log\log d$ [57, Chapter 3]. Accordingly, the server computes such an approximate optimal distribution π_ℓ over $\mathcal{A}_\ell$ in each epoch ℓ (line 1 of Algo. 1).

---

[3]Throughout, we assume that $\tilde{V}_\ell^{-1}$ is invertible in each epoch ℓ; this is the case when $\mathcal{A}_\ell$ spans $\mathbb{R}^d$. If $\mathcal{A}_\ell$ does not span $\mathbb{R}^d$, we can consider the lower dimensional subspace given by $\mathrm{span}(\mathcal{A}_\ell)$.

156 • *Construction of Robust Arm-Payoff Estimates and Confidence Intervals.* In each phase ℓ, the server
157 computes $T_a^{(\ell)}$ and $m_a^{(\ell)}$ for every $a \in \mathcal{A}_\ell$ as follows:

$$T_a^{(\ell)} = \left\lceil \frac{\pi_\ell(a)d}{\epsilon_\ell^2} \log\left(\frac{1}{\delta_\ell}\right) \right\rceil \ \ \text{and} \ \ m_a^{(\ell)} = \left\lceil \frac{T_a^{(\ell)}}{M} \right\rceil, \tag{5}$$

158 where $\pi_\ell(a)$ is obtained from the approximate G-optimal design problem, $\epsilon_\ell = 2^{-\ell}$, $\delta_\ell = \bar\delta/(K\ell^2)$,
159 and $\bar\delta$ is a design variable to be chosen later. The idea is to explore an arm a $T_a^{(\ell)}$ times to estimate
160 $\langle \theta_*, a \rangle$ up to a precision that scales linearly with ϵ_ℓ; in later phases, we require progressively finer
161 precision (hence, ϵ_ℓ decays exponentially with ℓ). The task of exploration is distributed among the
162 agents, with each agent i being assigned $m_a^{(\ell)}$ arm-pulls for every $a \in \mathcal{A}_\ell$. Using the rewards that
163 it observes during phase ℓ, each good agent $i \in [M] \setminus \mathcal{B}$ computes a local estimate $\hat\theta_i^{(\ell)}$ of θ_*, and
164 transmits it to the server (lines 3-7 of Algo. 1). The key question now is as follows: *How should the*
165 *server use the local estimates* $\{\hat\theta_i^{(\ell)}\}_{i\in[M]}$? Let us consider two natural strategies.

166 **Candidate Strategies.** One option could be to use the local estimates $\{\hat\theta_i^{(\ell)}\}_{i\in[M]}$ along with a
167 high-dimensional robust mean estimation algorithm to compute a robust estimate of θ_*. Yet another
168 strategy could be for the server to query the raw observations (i.e., the $y_{i,t}$'s from the agents, use an
169 univariate robust mean estimation algorithm (e.g., trimmed mean or median) to generate a "clean"
170 version of each observation, and then use these clean observations to compute a robust estimate of
171 θ_*. Although feasible, each of the above strategies can unfortunately lead to an additional $\sqrt{d}$ factor
172 in the regret bound; we discuss this point in detail in the Appendix. The main message we want to
173 convey here is that certain natural candidate solutions can lead to sub-optimal regret bounds.

174 **Main Ideas.** Our main insight is the following: to achieve near-optimal optimal regret bounds, one
175 need not go through the route of first computing a robust estimate of θ_*. As our analysis will soon
176 reveal, it suffices to instead compute robust estimates of the arm pay-offs $\{\langle \theta_*, a \rangle\}_{a\in\mathcal{A}_\ell}$ *directly* by
177 employing the estimator in line 8 of Algo. 1. The key statistical property that we exploit here is
178 that for each $a \in \mathcal{A}_\ell$ and $i \in [M] \setminus \mathcal{B}$, the quantity $\langle \theta_i^{(\ell)}, a \rangle$ is conditionally-Gaussian with mean
179 $\langle \theta_*, a \rangle$. This observation informs the choice of the median operator in line 8 of Algo. 1. Our next
180 task is to compute appropriate confidence intervals for the robust arm-mean-estimates in order to
181 eliminate sub-optimal arms. This is a delicate task as such confidence intervals need to account for
182 both statistical uncertainties *and* adversarial perturbations. Indeed, if the confidence intervals are too
183 tight, then they can lead to elimination of the optimal arm a_*; if they are too loose, then they can lead
184 to large regret. The confidence threshold γ_ℓ in line 9 of Algo. 1 strikes just the right balance; the
185 choice of such intervals is justified in Lemma 1.

186 We now state and discuss our main result concerning the performance of RCLB.

187 **Theorem 1.** *(Performance of RCLB) Suppose $\alpha < 1/2$. Given any $\delta \in (0,1)$, set $\delta' = \delta/(10K)$.*
188 *Then, RCLB guarantees that with probability at least $1 - \delta$, the following holds for each good agent*
189 *$i \in [M] \setminus \mathcal{B}$:*

$$\sum_{t=1}^{T} \langle \theta_*, a_* - a_{i,t} \rangle = \tilde{O}\left(\left(\alpha + \sqrt{1/M}\right)\sqrt{dT}\right). \tag{6}$$

190 The following is an immediate corollary on the group regret R_T.

191 **Corollary 1.** *(Bound on Group Regret) Under the conditions of Theorem 1, we have:*

$$R_T = \tilde{O}\left(\left(\alpha M + \sqrt{M}\right)\sqrt{dT}\right). \tag{7}$$

192 **Main Takeaways.** From Theorem 1, we note that RCLB guarantees sublinear regret despite the
193 presence of adversarial agents. More importantly, the regret bound in Eq. (6) has optimal dependence
194 on the model-dimension d, the horizon T, and also on the number of agents M when $\alpha = 0$ (i.e.,
195 in the absence of adversaries). When α is small, Eq. (6) reveals that one can indeed retain the
196 benefits of collaboration, and improve upon the trivial per agent regret of $\tilde{O}(\sqrt{dT})$. Interestingly, this
197 result mirrors that of a similar flavor for distributed stochastic optimization under attacks: given M
198 machines, α fraction of which are corrupt, the authors in [6] showed that no algorithm can achieve
199 statistical error lower than $\tilde{\Omega}\left(\alpha/\sqrt{T} + 1/\sqrt{MT}\right)$ for strongly convex loss functions; here, T is the

number of samples on each machine. *As far as we are aware, this is the first work to establish an analogous result for collaborative linear bandits.* Inspired by the lower bound in [6], one may ask: *Is the additive $\alpha\sqrt{T}$ term in Eq. (6) unavoidable?* We will provide a definitive answer in Section 4.

Proof Outline of Theorem 1. The first main step in our analysis of Theorem 1 is to provide guarantees on the estimates $\{\mu_a^{(\ell)}\}_{a \in \mathcal{A}_\ell}$ computed in line 8 of RCLB. This is achieved as follows.

Lemma 1. *(Robust Confidence Intervals) Fix any epoch ℓ. There exists an universal constant $C > 0$ such that for each active arm $b \in \mathcal{A}_\ell$, the following holds with probability at least $1 - \delta_\ell$:*

$$|\mu_b^{(\ell)} - \langle \theta_*, b \rangle| \leq \gamma_\ell, \quad where \quad \gamma_\ell = \sqrt{2}C\left(1 + \alpha\sqrt{M}\right)\epsilon_\ell. \tag{8}$$

Equipped with the above result, we argue that with high-probability, (i) the optimal arm a_* is never eliminated by RCLB (Lemma 4 in App. A); and (ii) in each epoch ℓ, an active arm in $\mathcal{A}_\ell$ can contribute to at most $O(\gamma_\ell)$ per-time-step regret (Lemma 5 in App. A). Putting these pieces together in a careful manner yields the desired result; we defer a detailed proof of Theorem 1 to Appendix A.

In the next section, we derive a lower bound that provides fundamental insights into the impact of the adversarial agents for the multi-agent sequential decision-making problem considered in this paper.

4 Lower Bounds

In this section, we assess the optimality of the regret bound obtained in Theorem 1. To do so, we consider a slightly different attack model: we assume that each of the agents is adversarial with probability α, independently of the other agents. Thus, the expected fraction of adversaries is α. Next, to provide a clean argument, we will focus on a class of policies Π where at each time-step t, the server assigns the *same* action to every agent, i.e., $a_{i,t} = a_t, \forall i \in [M]$. We note that all the algorithms developed in this paper adhere to policies in Π. Moreover, policies within the class Π yield the minimax optimal per-agent regret bound of order $\tilde{O}(\sqrt{dT}/\sqrt{M})$ when $\alpha = 0$. Since the standard multi-armed bandit setting [58] is a special case of the structured linear bandit setting considered here, a lower bound for the former implies one for the latter. With this in mind, let us denote by $\mathcal{E}_\mathcal{N}^{(K)}(1)$ the class of multi-armed bandits with K arms, where the reward distribution of each arm is Gaussian with unit variance. An instance $\nu_\mu \in \mathcal{E}_\mathcal{N}^{(K)}(1)$ is characterized by the mean vector $\mu \in \mathbb{R}^K$ associated with the K arms. Finally, let $R_T^{(s)}(\nu_\mu)$ denote the expected cumulative regret of the server (which is the same as that of a good agent $i \in [M] \setminus \mathcal{B}$) when it interacts with the instance ν_μ. We can now state the following result which establishes a fundamental lower bound for our problem.

Theorem 2. *(Fundamental Lower Bound) Given any policy in Π, there exist two distinct instances $\nu_\mu, \nu_{\mu'} \in \mathcal{E}_\mathcal{N}^{(2)}(1)$, and an universal constant $c > 1$, such that*

$$\max\{R_T^{(s)}(\nu_\mu), R_T^{(s)}(\nu_{\mu'})\} \geq c\alpha\sqrt{T}, \tag{9}$$

irrespective of the number of agents M.

Main Takeaways. Observe from Eq. (6) that even when M is arbitrarily large, the additive $\alpha\sqrt{T}$ term due to the adversaries remains unaffected - *Is this term truly unavoidable or just an artifact of our analysis?* Theorem 2 settles this question by revealing a fundamental performance limit: *every policy* in Π has to suffer the additive $\alpha\sqrt{T}$ regret, regardless of the number of agents. Thus, taken together, Theorems 1 and 2 provide the first set of tight, near-optimal regret guarantees for the setting considered in this paper. We consider this to be a significant contribution of our work.

Proof Idea for Theorem 2. For our setting, the standard techniques to prove lower bounds for non-adversarial bandits do not directly apply. The lower-bound proofs used for reward-corruption models [59], and attacks with a fixed budget [31], are not applicable either. This motivates us to use a new proof technique that combines information-theoretic arguments in [17] with ideas from the robust mean estimation literature [18, 19]. Specifically, for a two-armed bandit setting, we carefully construct two instances and attack strategies such that the joint distribution of rewards seen by the server is *identical* for both instances. Moreover, the instances are constructed such that (i) the optimal arm in one instance is sub-optimal for the other; and (ii) the per-time-step regret for selecting a sub-optimal arm in either instance is $\Omega(\alpha/\sqrt{T})$. For a detailed proof, see Appendix B.

Having established tight bounds for the linear bandit model in Section 2, in the sequel, we will show how our algorithmic ideas and results can be significantly extended to more general settings.

5 Extension to Generalized Linear Models with Adversaries

In this section, we will show how to achieve a regret bound akin to that in Theorem 1 for the non-linear observation model shown below [20, 21], known as the generalized linear model (GLM):

$$y_{i,t} = \mu\left(\langle\theta_*, a_{i,t}\rangle\right) + \eta_{i,t}, \tag{10}$$

where $\mu : \mathbb{R} \to \mathbb{R}$ is a continuously differentiable function typically referred to as the (inverse) *link* function, and $\eta_{i,t} \sim \mathcal{N}(0,1)$ is as before. Our goal is to now control the following notion of regret:

$$R_T^{\text{GLM}} = \mathbb{E}\left[\sum_{i\in[M]\setminus\mathcal{B}}\sum_{t=1}^{T}\left(\mu\left(\langle\theta_*, a_*\rangle\right) - \mu\left(\langle\theta_*, a_{i,t}\rangle\right)\right)\right], \tag{11}$$

where $a_* = \arg\max_{a\in\mathcal{A}}\mu(\langle\theta_*, a\rangle)$. The main technical challenge relative to the setting considered in Section 2 pertains to the construction of the robust confidence intervals. In particular, the non-linearity of the map $\mu(\cdot)$ makes it hard to apply the technique adopted in line 8 of RCLB, necessitating a different approach that we describe next. We start with the following standard assumption [20, 21].

Assumption 1. *The function $\mu : \mathbb{R} \to \mathbb{R}$ is continuously differentiable, Lipschitz with constant $k_2 \geq 1$, and such that*

$$k_1 = \min\{1, \inf_{\theta\in\Theta, a\in\mathcal{A}}\dot{\mu}(\langle\theta, a\rangle)\} > 0.$$

Here, $\dot{\mu}(\cdot)$ is used to represent the derivative of $\mu(\cdot)$.

Next, for any $\theta \in \mathbb{R}^d$, we define $h_\ell(\theta) \triangleq \sum_{a\in\text{Supp}(\pi_\ell)} m_a^{(\ell)}\mu(\langle\theta, a\rangle)a$. We now describe a variant of RCLB - dubbed RC-GLM - for generalized linear models. Notably, unlike the standard bandit algorithms [20, 21] for GLM's that build on LinUCB, RC-GLM is based on phased elimination.

Description of RC-GLM. Our algorithm uses as a sub-routine the recently proposed Iteratively Reweighted Mean Estimator for computing a robust estimate of the mean of high-dimensional Gaussian random variables with adversarial outliers [22]. Specifically, suppose we are given M d-dimensional samples $x_1, \ldots, x_M$, such that $(1-\alpha)M$ of these samples are drawn i.i.d. from $\mathcal{N}(v, \Sigma)$, where $v \in \mathbb{R}^d$ is an unknown mean vector, and $\Sigma \in \mathbb{R}^{d\times d}$ is a known covariance matrix. The remaining αM samples are adversarial outliers and can be arbitrary. The estimator in [22] takes as input the M samples, the corruption fraction α, and the covariance matrix Σ. It then outputs an estimate $\hat{v}$ of v such that with high probability, $\|\hat{v} - v\| = \tilde{O}\left(\|\Sigma\|_2^{1/2}\left(\sqrt{d/M} + \alpha\sqrt{\log(1/\alpha)}\right)\right)$. Importantly, the estimator in [22] runs in polynomial-time, and is minimax-rate-optimal. Let us now see how this estimator - described in Appendix C - can be applied to our setting.

We only describe the key differences of RC-GLM relative to RCLB here, and defer a detailed description of RC-GLM to Appendix C. To get around the difficulty posed by the non-linear link function, our main idea is to first compute a robust estimate $\hat{\theta}^{(\ell)}$ of θ_* at the server, and then use it to develop a phased elimination strategy. To that end, instead of computing a local estimate $\hat{\theta}_i^{(\ell)}$ as in RCLB, each good agent $i \in [M] \setminus \mathcal{B}$ transmits $Y_{i,\ell}$ to the server, and the server computes a vector X_ℓ as follows: $X_\ell = \text{ITW}(\{\tilde{V}_\ell^{-1/2}Y_{i,\ell}, i \in [M]\})$. Here, $\tilde{V}_\ell^{-1/2}$ and $Y_{i,\ell}$ are as in Eq. (3), and we used $\text{ITW}(\cdot)$ to denote the output of the robust estimator in [22]. Our key observation here is that for each good agent i, $\tilde{V}_\ell^{-1/2}Y_{i,\ell}$ is a d-dimensional Gaussian random variable with mean $\tilde{V}_\ell^{-1/2}h_\ell(\theta_*)$, and covariance matrix $\Sigma = I_d$, justifying the use of the robust Gaussian mean estimator in [22]. The fact that $\Sigma = I_d$ is crucial in our algorithm design as the error-bound in [22] scales with the 2-norm of Σ. Essentially, the above steps enable us to extract a statistic X_ℓ that captures information about the agents' observations during epoch ℓ. Using this statistic, the server next computes an estimate $\hat{\theta}^{(\ell)}$ of θ_* by solving $h_\ell(\hat{\theta}^{(\ell)}) = \tilde{V}_\ell^{1/2}X_\ell$,[4] and employs the following phased elimination strategy:

$$\mathcal{A}_{\ell+1} = \{a \in \mathcal{A}_\ell : \max_{b\in\mathcal{A}_\ell}\mu(\langle\hat{\theta}^{(\ell)}, b\rangle) - \mu(\langle\hat{\theta}^{(\ell)}, a\rangle) \leq 2\bar{\gamma}_\ell\}; \quad \bar{\gamma}_\ell = \bar{C}(k_2/k_1)\left(\sqrt{d} + \alpha\sqrt{M\log(1/\alpha)}\right)\epsilon_\ell,$$

where $\bar{C}$ is an universal constant known to the server. Deriving an analogue of Lemma 1 to compute the robust confidence threshold $\bar{\gamma}_\ell$ requires some work. This is achieved by exploiting the regularity properties of the link function in tandem with the confidence bounds in [22]; see Appendix C for details and a proof of our main result for RC-GLM stated below.

---

[4]We argue in Appendix C that this equation admits a unique solution.

Theorem 3. *(**Performance of Algorithm** RC-GLM) Suppose $\alpha < (5 - \sqrt{5})/10$, and $M = \Omega(\log(KT))$. Given any $\delta \in (0, 1)$, RC-GLM guarantees that with probability at least $1 - \delta$, the following holds for each good agent $i \in [M] \setminus \mathcal{B}$:*

$$\sum_{t=1}^{T} \left(\mu\left(\langle\theta_*, a_*\rangle\right) - \mu\left(\langle\theta_*, a_{i,t}\rangle\right)\right) = \tilde{O}\left((k_2/k_1)\left(\alpha\sqrt{\log\left(1/\alpha\right)} + \sqrt{d/M}\right)\sqrt{dT}\right). \quad (12)$$

Main Takeaways. Theorem 3 significantly generalizes Theorem 1 and shows that even for general non-linear observation maps, one can reap the benefits of collaboration in the presence of adversaries. The additional $\sqrt{d}$ factor in the bound of (12) relative to that in (6) is inherited from the error-rate guarantees in [22]; the task of tightening this bound is left as future work. Nonetheless, Theorem 3 is the only result we are aware of that provides adversarial-robustness guarantees for GLMs.

Algorithm 2 Robust BaseLinUCB (at Server)

Input: Confidence parameter $\bar{\delta}$, corruption fraction α, index set $\psi_t \subseteq [t-1]$, constant C from Lemma 1.
1: $A_t \leftarrow \frac{I_d}{M} + \sum_{\tau \in \psi_t} x_{\tau, a_\tau} x'_{\tau, a_\tau}$
2: **for** $i \in [M]$ **do**
3: $\quad b_{i,t} \leftarrow \sum_{\tau \in \psi_t} r_{i,\tau} x_{\tau, a_\tau}; \hat{\theta}_{i,t} \leftarrow A_t^{-1} b_{i,t}$
4: **end for**
5: **for** $a \in [K]$ **do**
6: $\quad \hat{r}_{t,a} \leftarrow \texttt{Median}\left(\{\langle\hat{\theta}_{i,t}, x_{t,a}\rangle, i \in [M]\}\right);$
7: $\quad w_{t,a} \leftarrow \left(\alpha + 2C\sqrt{\frac{\log(\frac{1}{\bar{\delta}})}{M}}\right)\|x_{t,a}\|_{A_t^{-1}}$
8: **end for**

Figure 1: Performance of RCLB for a good agent with $\alpha = 0.1$. We observe a clear benefit of collaboration with increasing M.

---

6 Robust Collaborative Contextual Bandits with Adversaries

In this section, we will consider a collaborative contextual bandit setting where at each time-step $t \in [T]$, the server and the agents observe K d-dimensional feature vectors, $\{x_{t,a} | a \in [K]\}$, with $\|x_{t,a}\| \leq 1, \forall a \in [K]$ and $\forall t \in [T]$. We assume that the adversarial agents have no control over the generation of the feature vectors. Associated with each arm $a \in [K]$, the stochastic reward observed by an agent $i \in [M]$ comes from the following observation model:

$$y_{i,t}(a) = \langle\theta_*, x_{t,a}\rangle + \eta_{i,t}(a), \quad (13)$$

where $\{\eta_{i,t}(a)\}$ are drawn i.i.d. from $\mathcal{N}(0, 1)$. At each time step t, a good agent $i \in [M] \setminus \mathcal{B}$ plays an action $a_{i,t} \in [K]$, and receives the corresponding reward $r_{i,t} \triangleq y_{i,t}(a_{i,t})$ based on the observation model in (13). The main difference of the setting considered here relative to the one in Section 2 is that the feature vectors for each arm can change over time. As a result, the optimal action $a_t^* = \arg\max_{a \in [K]} \langle\theta_*, x_{t,a}\rangle$ can change over time, making it particularly challenging to compete with a time-varying optimal action in the presence of adversaries. This dictates the need for a different algorithmic strategy compared to the one we developed in Section 1. Before we develop such a strategy, let us first formally define the performance metric of interest to us in this setting:

$$R_T^{\text{Context}} = \mathbb{E}\left[\sum_{i \in [M] \setminus \mathcal{B}} \sum_{t=1}^{T} \langle\theta_*, x_{t,a_t^*} - x_{t,a_{i,t}}\rangle\right]. \quad (14)$$

The main question we ask is: *For the contextual bandit setting described above, can one continue to hope for benefits of collaboration in the presence of adversaries?* In what follows, we will answer this question in the affirmative by developing a variant of the SUPLINREL algorithm in [24].

Description of Algorithm 3. At each time-step t, our proposed algorithm, namely Algorithm 3, scans through the set $\mathcal{A}$ of arms to determine a suitable action a_t. This scanning process (lines 4-10 of Algo. 3) is done at the server over S phases. Corresponding to each phase $s \in [S]$, the server

---
Algorithm 3 Robust Collaborative SupLinUCB for Contextual Bandits (at Server)

Input: Confidence parameter δ, corruption fraction α, and horizon T.
1: $S \leftarrow \lceil \ln T \rceil; \psi_1^{(s)} \leftarrow \emptyset, \forall s \in [S]$.
2: **for** $t \in [T]$ **do**
3:      $s \leftarrow 1$ and $\mathcal{A}_1 \leftarrow [K]$.
4:      **repeat**
5:          Use Algorithm 2 with $\bar{\delta} = \delta/(KST)$, and index set $\psi_t^{(s)}$ to compute robust estimates $\{\hat{r}_{t,a}^{(s)}, w_{t,a}^{(s)}\}$ of the means and variances of the payoffs associated with each arm $a \in \mathcal{A}_s$.
6:          If $w_{t,a}^{(s)} > 2^{-s}/\sqrt{M}$ for some $a \in \mathcal{A}_s$, then choose this arm, i.e., set $a_t = a$. Store the corresponding phase: $\psi_{t+1}^{(s)} = \psi_t^{(s)} \cup \{t\}, \psi_{t+1}^{(\ell)} = \psi_t^{(\ell)} \ \forall \ell \neq s$.
7:          Else if $w_{t,a}^{(s)} \leq 1/\sqrt{MT} \ \forall a \in \mathcal{A}_s$, then select the arm with the *highest robust upper confidence bound*: $a_t = \operatorname{argmax}_{a \in \mathcal{A}_s} \left(\hat{r}_{t,a}^{(s)} + w_{t,a}^{(s)} \right)$. Do not store this phase, i.e., $\psi_{t+1}^{(\ell)} = \psi_t^{(\ell)} \ \forall \ell \in [S]$.
8:          Else if $w_{t,a}^{(s)} \leq 2^{-s}/\sqrt{M} \ \forall a \in \mathcal{A}_s$, then update active arm-set as

$$\mathcal{A}_{s+1} = \{a \in \mathcal{A}_s | \max_{b \in \mathcal{A}_s} \left(\hat{r}_{t,b}^{(s)} + w_{t,b}^{(s)} \right) - \left(\hat{r}_{t,a}^{(s)} + w_{t,a}^{(s)} \right) \leq 2^{(1-s)}/\sqrt{M}\}.$$

9:          $s \leftarrow s + 1$.
10:      **until** an action a_t is chosen.
11:      Broadcast the chosen action a_t to every agent (i.e., $a_{i,t} = a_t, \forall i \in [M]$), and receive corresponding rewards $\{r_{i,t}\}_{i \in [M]}$. Adversarial agents can transmit arbitrary reward values.
12: **end for**
---

maintains a set $\psi_t^{(s)}$; the set $\psi_t^{(s)}$ stores all the time-steps in $[t-1]$ where an action is chosen in phase s of the scanning process based on line 6 on Algo. 3. The scanning process itself relies on Algorithm 2 as a sub-routine. Specifically, in each phase s, the server first invokes Algorithm 2 to obtain a robust estimate $\hat{r}_{t,a}^{(s)}$ of $\langle \theta_*, x_{t,a} \rangle$ for each arm $a \in \mathcal{A}_s$, along with an associated *inflated* confidence width $w_{t,a}^{(s)}$ (line 5 of Algo. 3). If the confidence width is too large for a particular arm (as in line 6), then such an arm requires exploration and is accordingly chosen to be a_t. If, on the other hand, the confidence widths of all arms are sufficiently small (as in line 7), then a_t is chosen to be the arm with the highest upper-confidence bound. Thus, we follow the principle of *optimism in the face of uncertainty here, while exercising caution to account for the presence of adversaries (via the use of inflated confidence intervals)*. If the conditions in lines 6 and 7 both fail, then the arms in $\mathcal{A}_s$ require further screening. Accordingly, we move to the next phase $s+1$, retaining only those arms that are sufficiently close to the optimal arm a_t^*; see line 8 of Algo. 3. Our main innovation lies in (i) the construction of the robust arm-estimates in Algo. 2 that account for both statistical and adversarial behavior, and (ii) the careful use of such estimates in lines 6-8 of Algo. 3 to pick the action a_t. The next result reveals that the combination of these ideas yields near-optimal regret bounds.

Theorem 4. *(**Performance of Algo. 3**) Suppose $\alpha < 1/2$. Given any $\delta \in (0,1)$, Algo. 3 guarantees that with probability at least $1-\delta$, the following holds for each good agent $i \in [M] \setminus \mathcal{B}$:*

$$\sum_{t=1}^{T} \langle \theta_*, x_{t,a_t^*} - x_{t,a_{i,t}} \rangle = \tilde{O}\left(\left(\alpha + \sqrt{1/M} \right) \sqrt{dT} \right). \tag{15}$$

Main Takeaways. For the contextual bandit setting considered here, the single-agent minimax optimal regret in the absence of adversaries is $\tilde{O}(\sqrt{dT})$ [24]. In light of the lower bound in Theorem 2, we see that Theorem 4 provides a near-optimal regret guarantee, just as Theorem 1.

Simulations. Since no other paper (that we are aware of) studies the collaborative linear bandit problem with adversaries, there are no natural baselines to compare with. Thus, to validate the theory developed in our work, we simulate the performance of RCLB in Fig. 1. Consistent with Theorem 1, we observe that RCLB guarantees sub-linear regret and demonstrates a clear benefit of collaboration despite adversarial agents. We provide several additional experiments in Appendix E.

References

[1] Jakub Konečnỳ, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.

[2] Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečnỳ, Stefano Mazzocchi, H Brendan McMahan, et al. Towards federated learning at scale: System design. *arXiv preprint arXiv:1902.01046*, 2019.

[3] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pages 1273–1282. PMLR, 2017.

[4] Yudong Chen, Lili Su, and Jiaming Xu. Distributed statistical machine learning in adversarial settings: Byzantine gradient descent. *Proceedings of the ACM on Measurement and Analysis of Computing Systems*, 1(2):1–25, 2017.

[5] Peva Blanchard, El Mahdi El Mhamdi, Rachid Guerraoui, and Julien Stainer. Machine learning with adversaries: Byzantine tolerant gradient descent. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 118–128, 2017.

[6] Dong Yin, Yudong Chen, Ramchandran Kannan, and Peter Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. In *International Conference on Machine Learning*, pages 5650–5659. PMLR, 2018.

[7] Lingjiao Chen, Zachary Charles, Dimitris Papailiopoulos, et al. Draco: Robust distributed training via redundant gradients. *arXiv preprint arXiv:1803.09877*, 2018.

[8] Dan Alistarh, Zeyuan Allen-Zhu, and Jerry Li. Byzantine stochastic gradient descent. *arXiv preprint arXiv:1803.08917*, 2018.

[9] Cong Xie, Oluwasanmi Koyejo, and Indranil Gupta. Generalized byzantine-tolerant sgd. *arXiv preprint arXiv:1802.10116*, 2018.

[10] Liping Li, Wei Xu, Tianyi Chen, Georgios B Giannakis, and Qing Ling. Rsa: Byzantine-robust stochastic aggregation methods for distributed learning from heterogeneous datasets. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 1544–1551, 2019.

[11] Avishek Ghosh, Justin Hong, Dong Yin, and Kannan Ramchandran. Robust federated learning in a heterogeneous environment. *arXiv preprint arXiv:1906.06629*, 2019.

[12] Avishek Ghosh, Raj Kumar Maity, Swanand Kadhe, Arya Mazumdar, and Kannan Ramachandran. Communication efficient and byzantine tolerant distributed learning. In *2020 IEEE International Symposium on Information Theory (ISIT)*, pages 2545–2550. IEEE, 2020.

[13] Avishek Ghosh, Raj Kumar Maity, and Arya Mazumdar. Distributed newton can communicate less and resist byzantine workers. *arXiv preprint arXiv:2006.08737*, 2020.

[14] Sai Praneeth Karimireddy, Lie He, and Martin Jaggi. Learning from history for byzantine robust optimization. In *International Conference on Machine Learning*, pages 5311–5319. PMLR, 2021.

[15] Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. 2008.

[16] Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in neural information processing systems*, 24:2312–2320, 2011.

[17] Sébastien Bubeck, Vianney Perchet, and Philippe Rigollet. Bounded regret in stochastic multi-armed bandits. In *Conference on Learning Theory*, pages 122–134. PMLR, 2013.

[18] Mengjie Chen, Chao Gao, and Zhao Ren. Robust covariance matrix estimation via matrix depth. *arXiv preprint arXiv:1506.00691*, 2015.

[19] Kevin A Lai, Anup B Rao, and Santosh Vempala. Agnostic estimation of mean and covariance. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 665–674. IEEE, 2016.

[20] Sarah Filippi, Olivier Cappe, Aurélien Garivier, and Csaba Szepesvári. Parametric bandits: The generalized linear case. In *NIPS*, volume 23, pages 586–594, 2010.

[21] Lihong Li, Yu Lu, and Dengyong Zhou. Provably optimal algorithms for generalized linear contextual bandits. In *International Conference on Machine Learning*, pages 2071–2080. PMLR, 2017.

[22] Arnak S. Dalalyan and Arshak Minasyan. All-in-one robust estimator of the gaussian mean. *The Annals of Statistics*, 2022.

[23] Lihong Li, Wei Chu, John Langford, and Robert E Schapire. A contextual-bandit approach to personalized news article recommendation. In *Proceedings of the 19th international conference on World wide web*, pages 661–670, 2010.

[24] Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

[25] Kwang-Sung Jun, Lihong Li, Yuzhe Ma, and Xiaojin Zhu. Adversarial attacks on stochastic bandits. *arXiv preprint arXiv:1810.12188*, 2018.

[26] Fang Liu and Ness Shroff. Data poisoning attacks on stochastic bandits. In *International Conference on Machine Learning*, pages 4042–4050. PMLR, 2019.

[27] Thodoris Lykouris, Vahab Mirrokni, and Renato Paes Leme. Stochastic bandits robust to adversarial corruptions. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 114–122, 2018.

[28] Anupam Gupta, Tomer Koren, and Kunal Talwar. Better algorithms for stochastic bandits with adversarial corruptions. In *Conference on Learning Theory*, pages 1562–1578. PMLR, 2019.

[29] Ilija Bogunovic, Andreas Krause, and Jonathan Scarlett. Corruption-tolerant gaussian process bandit optimization. In *International Conference on Artificial Intelligence and Statistics*, pages 1071–1081. PMLR, 2020.

[30] Evrard Garcelon, Baptiste Roziere, Laurent Meunier, Jean Tarbouriech, Olivier Teytaud, Alessandro Lazaric, and Matteo Pirotta. Adversarial attacks on linear contextual bandits. *arXiv preprint arXiv:2002.03839*, 2020.

[31] Ilija Bogunovic, Arpan Losalka, Andreas Krause, and Jonathan Scarlett. Stochastic linear bandits robust to adversarial attacks. In *International Conference on Artificial Intelligence and Statistics*, pages 991–999. PMLR, 2021.

[32] Keqin Liu and Qing Zhao. Distributed learning in multi-armed bandit with multiple players. *IEEE Transactions on Signal Processing*, 58(11):5667–5681, 2010.

[33] Dileep Kalathil, Naumaan Nayyar, and Rahul Jain. Decentralized learning for multiplayer multiarmed bandits. *IEEE Transactions on Information Theory*, 60(4):2331–2345, 2014.

[34] Soummya Kar, H Vincent Poor, and Shuguang Cui. Bandit problems in networks: Asymptotically efficient distributed allocation rules. In *2011 50th IEEE Conference on Decision and Control and European Control Conference*, pages 1771–1778. IEEE, 2011.

[35] Peter Landgren, Vaibhav Srivastava, and Naomi Ehrich Leonard. Distributed cooperative decision-making in multiarmed bandits: Frequentist and bayesian algorithms. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, pages 167–172. IEEE, 2016.

[36] Peter Landgren, Vaibhav Srivastava, and Naomi Ehrich Leonard. Distributed cooperative decision making in multi-agent multi-armed bandits. *Automatica*, 125:109445, 2021.

[37] Shahin Shahrampour, Alexander Rakhlin, and Ali Jadbabaie. Multi-armed bandits in multi-agent networks. In *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 2786–2790. IEEE, 2017.

[38] Swapna Buccapatnam, Jian Tan, and Li Zhang. Information sharing in distributed stochastic bandits. In *2015 IEEE Conference on Computer Communications (INFOCOM)*, pages 2605–2613. IEEE, 2015.

[39] Ravi Kumar Kolla, Krishna Jagannathan, and Aditya Gopalan. Collaborative learning of stochastic bandits over a social network. *IEEE/ACM Transactions on Networking*, 26(4):1782–1795, 2018.

[40] Yuanhao Wang, Jiachen Hu, Xiaoyu Chen, and Liwei Wang. Distributed bandit learning: Near-optimal regret with efficient communication. *arXiv preprint arXiv:1904.06309*, 2019.

[41] Abishek Sankararaman, Ayalvadi Ganesh, and Sanjay Shakkottai. Social learning in multi agent multi armed bandits. *Proceedings of the ACM on Measurement and Analysis of Computing Systems*, 3(3):1–35, 2019.

[42] David Martínez-Rubio, Varun Kanade, and Patrick Rebeschini. Decentralized cooperative stochastic bandits. *arXiv preprint arXiv:1810.04468*, 2018.

[43] Abhimanyu Dubey et al. Kernel methods for cooperative multi-agent contextual bandits. In *International Conference on Machine Learning*, pages 2740–2750. PMLR, 2020.

[44] Abhimanyu Dubey and Alex Pentland. Differentially-private federated linear bandits. *arXiv preprint arXiv:2010.11425*, 2020.

[45] Anusha Lalitha and Andrea Goldsmith. Bayesian algorithms for decentralized stochastic bandits. *arXiv preprint arXiv:2010.10569*, 2020.

[46] Ronshee Chawla, Abishek Sankararaman, Ayalvadi Ganesh, and Sanjay Shakkottai. The gossiping insert-eliminate algorithm for multi-agent bandits. In *International Conference on Artificial Intelligence and Statistics*, pages 3471–3481. PMLR, 2020.

[47] Ronshee Chawla, Abishek Sankararaman, and Sanjay Shakkottai. Multi-agent low-dimensional linear bandits. *arXiv preprint arXiv:2007.01442*, 2020.

[48] Avishek Ghosh, Abishek Sankararaman, and Kannan Ramchandran. Collaborative learning and personalization in multi-agent stochastic linear bandits. *arXiv preprint arXiv:2106.08902*, 2021.

[49] Mridul Agarwal, Vaneet Aggarwal, and Kamyar Azizzadenesheli. Multi-agent multi-armed bandits with limited communication. *arXiv preprint arXiv:2102.08462*, 2021.

[50] Zhaowei Zhu, Jingxuan Zhu, Ji Liu, and Yang Liu. Federated bandit: A gossiping approach. In *Abstract Proceedings of the 2021 ACM SIGMETRICS/International Conference on Measurement and Modeling of Computer Systems*, pages 3–4, 2021.

[51] Chengshuai Shi, Cong Shen, and Jing Yang. Federated multi-armed bandits with personalization. In *International Conference on Artificial Intelligence and Statistics*, pages 2917–2925. PMLR, 2021.

[52] Abhimanyu Dubey and Alex Pentland. Private and byzantine-proof cooperative decision-making. In *AAMAS*, pages 357–365, 2020.

[53] Daniel Vial, Sanjay Shakkottai, and R Srikant. Robust multi-agent multi-armed bandits. In *Proceedings of the Twenty-second International Symposium on Theory, Algorithmic Foundations, and Protocol Design for Mobile Networks and Mobile Computing*, pages 161–170, 2021.

[54] Daniel Vial, Sanjay Shakkottai, and R Srikant. Robust multi-agent bandits over undirected graphs. *arXiv preprint arXiv:2203.00076*, 2022.

[55] Aritra Mitra, Hamed Hassani, and George Pappas. Exploiting heterogeneity in robust federated best-arm identification. *arXiv preprint arXiv:2109.05700*, 2021.

[56] Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[57] Michael J Todd. *Minimum-volume ellipsoids: Theory and algorithms*. SIAM, 2016.

[58] Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2):235–256, 2002.

[59] Sayash Kapoor, Kumar Kshitij Patel, and Purushottam Kar. Corruption-tolerant bandit learning. *Machine Learning*, 108(4):687–715, 2019.