Pushing the Limits of Fewshot Anomaly Detection in Industry Vision: Graphcore

Abstract

In the area of fewshot anomaly detection (FSAD), efficient visual feature plays an essential role in memory bank $\mathcal{M}$-based methods. However, these methods do not account for the relationship between the visual feature and its rotated visual feature, drastically limiting the anomaly detection performance. To push the limits, we reveal that rotation-invariant feature property has a significant impact in industrial-based FSAD. Specifically, we utilize of graph representation in FSAD and provide a novel visual isometric invariant feature (VIIF) as anomaly measurement feature. As a result, VIIF can robustly improve the anomaly discriminating ability and can further reduce the size of redundant features stored in $\mathcal{M}$ by a large amount. Besides, we provide a novel model GraphCore via VIIFs that can fast implement unsupervised FSAD training and can improve the performance of anomaly detection. A comprehensive evaluation is provided for comparing GraphCore and other SOTA anomaly detection models under our proposed fewshot anomaly detection setting, which shows GraphCore can increase average AUC by 5.8%, 4.1%, 3.4%, and 1.6% on MVTec AD and by 25.5%, 22.0%, 16.9%, and 14.1% on MPDD for 1, 2, 4, and 8-shot cases, respectively.

1 Introduction

With the rapid development of deep vision detection technology in artificial intelligence, the detection of anomalies/defects on the surface of industrial products (including scratches, stains, missing, etc.) has received unprecedented attention. Changeover in manufacturing refers to the process of converting a line or machine from processing one product to another. Since the equipment has not been completely fine-tuned after the starting of the production line, changeover frequently results in unsatisfactory anomaly detection (AD) performance.

How to achieve rapid training of industrial product models in the changeover scenario while assuring accurate anomaly detection is a critical issue in the actual production process. The current state of AD in the industry is as follows: (1) In terms of detection accuracy, the performance of state-of-the-art (SOTA) AD models degrades dramatically during changeover. Current mainstream work utilizes a considerable amount of training data as input to train the model, as shown in Fig. 1(a). However, this will make data collecting challenging, even for unsupervised learning. As a result, many approaches based on fewshot learning at the price of accuracy have been proposed. For instance, Huang et al. (2022) employ meta learning, as shown in Fig. 1(b). While due to complicated settings, it is impossible to flexibly migrate to the new product during changeover, and the detection accuracy cannot be guaranteed. (2) In terms of training speed, when a large amount of data is utilized for training, the training progress for new goods is slowed in actual production line. As is well-known, vanilla unsupervised AD requires to collect a large amount of information. Even though meta learning works in fewshot learning, as shown in Fig. 1(b), it is still necessary to train a massive portion of previously collected data.

We state that AD of industrial products requires just a small quantity of data to achieve performance comparable to a large amount of data, i.e. a small quantity of image data can contain sufficient information to represent a large number of data. Due to the fact that industrial products are manufactured with high stability (no evident distortion of shape and color cast), the taken images lack the diversity of natural images, and there is a problem with the shooting angle or rotation. Therefore, it is more essential and necessary to extract rotation-invariant structural features. As graph

Figure 1: Different from (a) vanilla unsupervised AD and (b) fewshot unsupervised AD in meta learning. As input training samples, our setting (c) only utilizes a small number of normal samples. For our setting (c), there is no requirement to aggregate training categories in advance. The proposed model, vision isometric invariant GNN, can fast obtain the invariant feature within a few normal samples, and its accuracy outperforms models trained in a meta-learning context.

neural networks (GNNs) are capable of robustly extracting non-serialized structural features (Han et al. (2022), Bruna et al. (2013), Hamilton et al. (2017), Xu et al. (2018)), they are more suited than convolution neural networks (CNNs) to handle the problem of extracting rotation-invariant features. For this reason, the *core idea* of the proposed *GraphCore* method in this paper is to use the visual isometric invariant features (VIIFs) as the anomaly measurement features. In the method using memory bank ($\mathcal{M}$) as the AD paradigm, PatchCore (Roth et al. (2022)) uses ResNet (He et al. (2016)) as the feature extractor. However, since their features obtained by CNNs do not have rotation invariance (Dieleman et al. (2016)), a large number of redundant features are stored in $\mathcal{M}$. Note that these redundant features maybe come from multiple rotation features of the same patch structure. It will hence require a huge quantity of training data to ensure the high accuracy of the test set. To avoid these redundant features, we propose VIIFs, which not only produce more robust visual features, but also dramatically lower the size of $\mathcal{M}$ and accelerate detection.

Based on the previous considerations, the goal of our work is to handle the cold start of the production line during the changeover. As shown in Fig. 1(c), a new FSAD method, called *GraphCore*, is developed that employs a small number of normal samples to accomplish fast training and competitive AD accuracy performance of the new product. On the one hand, by utilizing a small amount of data, we would rapidly train and accelerate the speed of anomaly inference. On the other hand, because we directly train new product samples, adaptation and migration of anomalies from the old product to the new product do not occur.

Contributions. In summary, the main contributions of this work are as follows:

- We present a feature-augmented method for FSAD in order to investigate the property of visual features generated by CNNs.
- We propose a novel anomaly detection model, GraphCore, add a new VIIF into the memory bank-based AD paradigm, which can drastically reduce the quantity of redundant visual features.
- The experimental results show that the proposed VIIFs are effective and can greatly enhance the FSAD performance on MVTec AD and MPDD .

Related Work. Fewshot anomaly detection (FSAD) is an attractive research topic. However, there are only a few of papers devoted to the industrial image FSAD. Some works (Liznerski et al. (2020);

Pang et al. (2021); Ding et al. (2022)) experiment with fewshot abnormal images in the test set, which contradicts our assumptions where no abnormal images existed. And others (Wu et al. (2021); Huang et al. (2022)) conduct experiments in a meta-learning setting. This configuration has the disadvantage of requiring a high number of base class images and being incapable of addressing the shortage of data under cold-start conditions in industrial applications. Fewshot's settings in (Rudolph et al. (2021); Sheynin et al. (2021)) are similar to ours. However, the primary issue is that model training takes too long and performance is inadequate, which cannot reach the accuracy and efficiency criteria of the production changeover process. PatchCore (Roth et al. (2022)) investigated AD performance on MVTec AD in a fewshot setting with SPADE (Cohen & Hoshen (2020)) and PaDiM (Defard et al. (2021)). These three methods do not require sufficient normal images and a significant amount of training time. However, these approaches are not intended for fewshot settings, thus their performance cannot satisfy the requirements of manufacturing changeover. In this research, we propose a feature augmentation method for FSAD that can rapidly finish the training of anomaly detection models with a small quantity of data and meet manufacturing changeover requirements.

2 APPROACH

Problem Setting. Fig. 1(c) outlines the formal definition of the problem setting for the proposed FSAD. Given a training set of only n normal samples, where $n \leq 8$, from a certain category. At test time, given a normal or abnormal sample from a target category, the anomaly detection model should predict whether or not the image is anomalous and localize the anomaly region if the prediction result is anomalous.

Challenges. For the FSAD proposed in Fig. 1(c), we attempt to detect anomalies in the test sample using only a small number of normal images as the training dataset. The key challenges consist of: (1) Each category's training dataset contains only normal samples, i.e there are no annotations at the image or pixel level. (2) There are few normal samples of the test set available. In our proposed setting, there are less than 8 training samples.

Motivation. In the realistic industrial image dataset (Bergmann et al. (2019); Jezek et al. (2021)), the images under certain categories are extremely similar. Most of them can be converted to one another with simple data augmentation, such as the meta nut (Fig. 2) and the screw (Fig. 5). For instance, rotation augmentation can effectively provide a new screw dataset. Consequently, when faced with the challenges stated in Section 2, our natural inclination is to acquire additional data through data augmentation. Then, the feature memory bank (Fig. 4) can store more useful features.

Figure 2: Augmentation+PatchCore Architecture.

2.1 AUGMENTATION+PATCHCORE

As a means of validating our insight, we have adapted PatchCore (Roth et al. (2022)) to our model. We denote augmentation (rotation) with PatchCore as Aug.(R). The architecture is depicted in detail in Fig. 2. Before extracting features from the ImageNet pretrained model, we augment the data (e.g., by rotating the data).

Algorithm 1: Aug.(R) memory bank

Input : ImageNet pretrained ϕ, all normal samples $\mathcal{X}_N$, data augmentation operator α, patch feature extractor $\mathcal{P}$, memory size target l, random linear projection ψ.

Output: Patch-level augmented memory bank $\mathcal{M}$.

1 $\mathcal{M} \leftarrow \{\}$;
2 **for** $x_i \in \mathcal{X}_N$ **do**
3     $x_i^g \leftarrow \alpha(x_i)$;
4     $\mathcal{M} \leftarrow \mathcal{P}(\phi(x_i))$;
5     $\mathcal{M} \leftarrow \mathcal{P}(\phi(x_i^g))$;
6 **end for**
7 $\mathcal{M}_C \leftarrow \{\}$ //Apply coreset sampling for memory bank
8 **for** $i \in [0, \cdots, l-1]$ **do**
9     $m_i \leftarrow \underset{m \in \mathcal{M} - \mathcal{M}_C}{\arg\max} \ \underset{n \in \mathcal{M}_C}{\min} \ \|\psi(m) - \psi(n)\|_2$;
10     $\mathcal{M}_C \leftarrow \mathcal{M}_C \cup \{m_i\}$;
11 **end for**
12 $\mathcal{M} \leftarrow \mathcal{M}_C$.

In training phase, the aim of training phase is to build up a memory bank, in which store the neighbourhood aware features from all of normal samples. At test time, the test image are predicted as anomalies if at least one patch is anomalous, and pixel-level anomaly segmentation is computed via the score of each patch feature. The feature memory construction method is shown in Algorithm 1. In default, we set ResNet18 (He et al. (2016)) as the feature extraction model. Conceptually, coreset sampling (Sener & Savarese (2018)) for memory bank aims to balance the size of memory bank with the performance of anomaly detection. And the size of memory bank has a huge impact on the inference speed. In Section 3.3, we discuss the effect of sampling rate in detail.

In testing phase, with the normal patches feature bank $\mathcal{M}$, the image-level anomaly score s for the test image x^{test} is computed by the maximum score s^* between the test image's patch feature $\mathcal{P}(x^{test})$ and its respective nearest neighbour m^* in $\mathcal{M}$:

$$m^* = \underset{m^{test} \in \mathcal{P}(x^{test})}{\arg\max} \ \underset{m \in \mathcal{M}}{\arg\min} \left\|m^{test} - m\right\|_2, \tag{1}$$

$$s^* = \left\|m^{test} - m^*\right\|_2. \tag{2}$$

From Table 2 and Table 3, we can easily observed that the performance of Aug.(R) greatly outperforms the SOTA models under the proposed fewshot setting.

2.2 VISION ISOMETRIC INVARIANT FEATURE

In Section 2.1, we demonstrate heuristically that Augmentation+PatchCore outperforms SOTA models in the fewshot anomaly detection context proposed. Essentially, the data augmentation method immediately incorporates the features of normal samples into the memory bank. In other words, Augmentation+PatchCore improves the probability of locating a subset feature, allowing the anomaly score of the test image to be calculated with greater precision using Equ. (1) and Equ. (2). Therefore, we question whether it is possible to extract the invariant representational features from a small number of normal samples and add them to the feature memory bank. As demonstrated in Fig. 3, we propose a new model for feature extraction: vision isometric invariant graph neural

Figure 3: Convolution feature VS vision isometric invariant feature.

Figure 4: Vision isometric invariant GNN pipeline.

network (VIIG). The proposed model is motivated by Section 2 and tries to extract visual isometric invariant feature (VIIF) from each patch of the normal sample. As previously stated, the majority of industrial visual anomaly detection datasets are transformable via rotation, translation, and flipping. Thus, the isomorphism of GNN suited industrial visual anomaly detection excellently.

2.3 GRAPH REPRESENTATION OF IMAGE

Fig. 4 shows that the feature extraction process of GraphCore. Specifically, for a normal sample image with a size of $H \times W \times 3$, we evenly separate it as an N patch. In addition, each patch is transformed into a feature vector $f_i \in \mathbb{R}^D$. So we have the features $F = [f_1, f_2, \cdots, f_N]$, where D is the feature dimension and $i = 1, 2, \cdots, N$. We view these features as unordered nodes $\mathcal{V} = \{v_1, v_2, \cdots, v_N\}$. For certain each node v_i, we denote the K nearest neighbours $\mathcal{N}(v_i)$ and add an edge e_{ij} directed from v_j to v_i for all $v_j \in \mathcal{N}(v_i)$. Hence, each patch of normal samples can be denoted as a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. $\mathcal{E}$ refers all the edges of Graph $\mathcal{G}$.

2.4 GRAPH FEATURE PROCESSING

Fig. 4 shows the architecture of the proposed vision isometric invariant GNN. To be specific, we set the feature extraction as GCN (Kipf & Welling (2017)). We aggregate features for each node by exchanging information with its neighbour nodes. In specific, the feature extraction operates as follows:

$$\mathcal{G}' = F(\mathcal{G}, \mathcal{W}) = Update(Aggregate(\mathcal{G}, W_{aggregate}), W_{update}), \tag{3}$$

where $W_{aggregate}$ and W_{update} denote the weights of the aggregation and update operations. Both of them can be optimized in an end-to-end manner. Specifically, the aggregation operation for each node is calculated by aggregating neighboring nodes' features:

$$f_i' = h(f_i, g(f_i, \mathcal{N}(f_i), W_{aggregate}), W_{update}), \tag{4}$$

where $\mathcal{N}(f_i^l)$ denotes the set of neighbor nodes of f_i^l. Here, we employ max-relative graph convolution (Li et al. (2019)) as our operator:

$$g(\cdot) = f_i'' = max(\{f_i - f_j | j \in \mathcal{N}(x_i)\}), \tag{5}$$

$$h(\cdot) = f_i' = f_i'' W_{update}. \tag{6}$$

Figure 5: Vision isometric invariant GNN for FSAD.

(a) Vanilla Anomaly Detection   (b) Fewshot Anomaly Detection (Ours)

Figure 6: Vision GNN architecture. (a) vanilla AD and (b) our proposed FSAD.

2.5 GRAPHCORE ARCHITECTURE

Fig. 5 shows the whole architecture of GraphCore. In the training phase, the most significant difference between GraphCore and Augmentation+PatchCore is the feature memory bank construction algorithm. The feature construction algorithm is the same with Aug.(R) memory bank in Algorithm 1. Note that we use vision isometric invariant GNN as feature extractor $\mathcal{P}$ without data augmentation. In the testing phase, the computation of anomaly score $s*$ for GraphCore is highly similar to the one in Augmentation+PatchCore. The only difference is the feature extraction method for each normal patch sample.

2.6 A UNIFIED VIEW OF AUGMENTATION+PATCHCORE AND GRAPHCORE

Fig. 6 depicts a unified view of both Augmentation+PatchCore and GraphCore. GraphCore is prompted by Augmentation+PatchCore to obtain the isometric invariant feature. Therefore, Graph-Core is able to improve the probability of locating a feature subset and it allows the anomaly score of a test image to be calculated most precisely and rapidly. Table 1 shows the difference among PatchCore, Augmentation+PatchCore and GraphCore in terms of architecture details.

Table 1: Unified view for three methods.

Augmentation	Network	Model
No	ImageNet Pretrained Model	PatchCore
Rotation	ImageNet Pretrained Model	Aug.(R)
No	GNN	GraphCore

3 EXPERIMENT

3.1 EXPERIMENT SETTING

Datasets. To demonstrate the generalization of our proposed method, we conduct experiments on three datasets, namely MVTec AD (Bergmann et al. (2019)), MPDD (Jezek et al. (2021)) and MVTec LOCO AD (Bergmann et al. (2022)).

Competing Methods. RegAD (Huang et al. (2022)) is the SOTA FSAD method. It works under meta-learning setting: aggregated training on multiple categories and adapting to unseen categories, using fewshot unseen images as a support set. However, our proposed fewshot setting utilizes only a few images as a training set, and not several categories. Taking into account the fairness of the experiments, we reimplement the classical and SOTA approaches in the field of unsupervised anomaly

(a) MPDD   (b) MVTec AD

Figure 7: GraphCore VS Augmentation+PatchCore VS RegAD on various numbers of shot (K).

detection, such as SPADE (Cohen & Hoshen (2020)), STPM (Wang et al. (2021)), RD4AD (Deng & Li (2022)), CFA (Lee et al. (2022)), and PatchCore (Roth et al. (2022)), using the official source code for comparison under our fewshot setting. PatchCore-1 is the result of our reimplementation with a 1% sampling rate, PatchCore-10 and PatchCore-25 are the results at 10% and 25% sampling rates, respectively, and RegAD-L is the RegAD experiment with our fewshot setting.

3.2 COMPARISON WITH THE SOTA METHODS

The comparative findings between MVTec and MPDD are shown in Table 2. Especially, the performance of RegAD under the meta-learning setting is also listed in the table. In comparison to SOTA models, GraphCore improves average AUC by 5.8%, 4.1%, 3.4%, and 1.6% on MVTec and by 25.5%, 22.0%, 16.9%, and 14.1% on MPDD for 1, 2, 4, and 8-shot cases, respectively. From Fig. 7, it can be easily observed that GraphCore significantly outperform the SOTA approah at the image and pixel level from 1-shot to 8-shot. As can be seen, the performance of GraphCore and Augmentation+PatchCore surpass the other methods when using only a few samples (no more than 8 samples) for training.

Table 2: FSAD average results for all categories on MVTec AD and MPDD. The sampling ratio is 0.01, x|y represents image AUROC and pixel AUROC. The results for PaDiM and PatchCore-10, PatchCore-25 are reported from Roth et al. (2022). The results for RegAD-L and RegAD are reported from Huang et al. (2022). The best-performing method is in bold.

Dateset	K	Aug.(R)	GraphCore	CFA	SPADE	PaDiM	STPM	RD4AD	PatchCore-1	PatchCore-10	PatchCore-25	RegAD-L	RegAD
MVTec AD	1	87.4|94.5	**89.9|95.6**	78.8|90.7	69.8|79.1	76.1|88.2	69.7|58.2	74.4|69.0	78.5|90.1	83.4|92.0	84.1|92.4	-	82.4|-
	2	90.4|96.3	**91.9|96.9**	81.1|91.0	70.7|79.9	78.9|90.5	74.2|59.8	75.5|71.8	87.8|94.8	86.4|93.1	87.2|93.3	81.5|-	85.7|94.6
	4	92.2|96.0	**92.9|97.4**	85.0|91.3	-	71.6|80.2	74.8|60.8	76.9|72.2	89.5|95.0	-	-	84.9|-	88.2|95.8
	8	95.4|96.4	**95.9|97.8**	90.9|91.6	-	75.3|80.5	77.6|61.6	78.5|73.0	94.3|95.6	-	-	87.4|-	91.2|96.7
MPDD	1	83.9|94.7	**84.7|95.2**	58.8|77.7	-	57.5|73.9	59.2|75.1	58.5|73.2	59.2|78.5	-	-	-	57.8|-
	2	84.6|94.9	**85.4|95.4**	58.6|78.2	-	58.0|75.4	62.4|75.8	61.8|74.5	59.6|79.2	-	-	50.8|-	63.4|93.2
	4	84.9|95.2	**85.7|95.7**	59.3|78.7	-	58.3|75.9	62.6|76.2	62.1|75.5	59.8|79.8	-	-	54.2|-	68.8|93.9
	8	85.1|95.5	**86.0|95.9**	60.9|79.0	-	58.5|76.2	63.1|76.6	62.4|75.7	60.0|80.3	-	-	61.1|-	71.9|95.1

Considering that RegAD only shows detailed results of various categories above 2-shot, we only show the detailed results of 2-shot in the main text, and the results of 1-shot, 4-shot, and 8-shot are in the appendix. As shown in Table 3, GraphCore outperforms all other baseline methods in 12 out of the 15 categories at the image level, and outperforms all other baselines in 11 out of the 15 categories at the pixel level on MVTec AD. Moreover, results in Table 4 show that GraphCore outperforms all other baselines in 5 out of the 6 categories at the image level, and outperforms all other baselines in all categories at the pixel level on MPDD.

3.3 ABLATION STUDIES

Sampling Rate. When demonstrated in Fig. 8, our technique significantly improves as the sample rate increases from 0.0001 to 0.001, after which the increase in sampling rate has a flattening effect on the performance gain. In other words, as the sampling rate steadily increases, the performance of GraphCore is insensitive to the sampling rate.

Table 3: FSAD results on MVTec AD. The number of shot K is 2, the sampling ratio is 0.01, x|y represents image AUROC and pixel AUROC. The results for PaDiM and PatchCore-10, PatchCore-25 are reported from Roth et al. (2022). The results for RegAD are reported from Huang et al. (2022). The best-performing method is in bold.

Category	Aug.(R)	GraphCore	CFA	SPADE	PaDiM	STPM	RD4AD	PatchCore-1	PatchCore-10	PatchCore-25	RegAD
Bottle	99.7|98.6	**99.8|99.8**	93.7|93.5	95.7|86.8	-	93.8|84.6	91.2|81.7	99.7|98.5	-	-	99.4|98.0
Cable	94.7|96.2	**95.2**|96.3	89.3|88.9	60.4|78.6	-	60.2|51.6	65.3|65.4	94.9|**97.8**	-	-	65.1|91.7
Capsule	66.5|97.7	**73.2|97.8**	53.4|85.9	48.7|79.8	-	45.2|59.2	50.5|78.2	67.2|97.7	-	-	67.5|97.3
Carpet	99.4|99.1	**99.4|99.6**	97.6|97.9	92.1|95.6	-	90.8|60.5	92.8|74.2	99.1|99.0	-	-	96.5|98.9
Grid	75.7|79.8	81.5|80.6	80.4|**81.4**	75.8|75.9	-	72.6|61.2	75.2|76.3	61.7|67.5	-	-	**84.0**|77.4
Hazelnut	**99.7**|97.9	99.5|**98.2**	99.4|**98.2**	95.2|88.9	-	90.3|74.5	93.4|64.8	93.5|96.4	-	-	96.0|98.1
Leather	**100**|99.3	**100|99.4**	**100**|99.3	97.9|89.2	-	95.8|75.2	96.7|86.5	**100**|99.3	-	-	99.4|98.0
Meta Nut	95.0|96.8	**96.3|98.1**	68.6|89.7	61.3|59.5	-	59.4|51.1	63.4|68.9	92.0|97.1	-	-	91.4|96.9
Pill	87.8|93.9	**88.6|94.1**	67.4|91.5	60.2|57.2	-	58.7|49.9	62.8|70.2	87.4|96.8	-	-	81.3|93.6
Screw	63.6|96.0	**65.7**|96.5	58.2|**96.7**	51.3|70.2	-	51.9|51.8	54.3|60.8	48.3|90.8	-	-	52.5|94.4
Tile	**100**|99.3	**100**|96.8	99.8|81.8	90.2|82.3	-	91.4|58.2	88.9|59.2	**100**|96.0	-	-	94.3|94.3
Toothbrush	83.6|98.2	**87.3|98.6**	86.9|93.9	80.2|76.8	-	76.5|66.3	77.1|78.3	83.9|98.2	-	-	86.6|98.2
Transistor	96.3|94.1	**97.1|99.2**	72.5|80.3	51.6|73.6	-	82.4|47.5	78.1|67.8	96.9|95.0	-	-	86.0|93.4
Wood	97.1|98.4	97.5|**99.5**	98.2|92.4	50.3|89.7	-	95.8|48.4	93.7|93.8	97.2|93.0	-	-	**99.2**|93.5
Zipper	96.9|99.0	97.5|99.3	50.5|94.1	49.4|93.7	-	47.6|56.3	49.5|51.2	95.3|98.2	-	-	86.3|95.1
Average	90.4|96.3	**91.9|96.9**	81.1|91.0	70.7|79.9	78.9|90.5	74.2|59.8	75.5|71.8	87.8|94.8	86.4|93.1	87.2|93.3	85.7|94.6

Table 4: FSAD results on MPDD. The number of shot K is 2, the sampling ratio is 0.01, x|y represents image AUROC and pixel AUROC. The results for PaDiM and PatchCore-10, PatchCore-25 are reported from Roth et al. (2022). The results for RegAD are reported from Huang et al. (2022). The best-performing method is in bold.

Category	Aug.(R)	GraphCore	CFA	SPADE	STPM	RD4AD	PatchCore	RegAD
Bracket Black	66.8|92.1	67.0|**92.5**	54.3|75.8	62.4|72.8	**94.5**|75.1	91.7|75.4	58.6|78.9	63.3|-
Bracket Brown	76.1|91.9	**77.2|92.6**	66.8|77.5	59.5|71.9	62.3|73.2	58.8|73.4	70.7|76.9	59.4|-
Bracket White	87.2|97.1	**89.4|97.5**	68.7|70.8	67.2|72.4	53.8|64.2	55.6|62.4	70.4|68.1	55.6|-
Connector	98.6|97.2	**98.9|97.7**	58.5|88.2	59.2|82.8	51.6|83.4	53.7|82.3	59.2|85.2	73.0|-
Metal Plate	99.9|98.4	**99.9|99.1**	62.7|84.3	64.2|75.9	62.4|83.2	65.2|76.5	64.1|86.3	61.7|-
Tubes	79.2|92.6	**79.8|93.1**	40.7|72.8	35.6|76.8	49.6|75.6	45.9|77.1	34.3|79.5	67.1|-
Average	84.6|94.9	**85.4|95.4**	58.6|78.2	58.0|75.4	62.4|75.8	61.8|74.5	59.6|79.2	63.4|93.2

Nearest Neighbour. In Fig. 8, the green color represents the performance of GraphCore's 9 nearest neighbour search and the blue color represents the performance of GraphCore's 3 nearest neighbour search. As can be seen, increasing the number of neighbors from 3 to 9 greatly increases performance at the pixel level when the sampling rate is low, but does not enhance performance at the image level. As the sampling rate increases, the gain of the number of pixels' neighbors approaches zero.

Augmentation Methods. Fig. 9 demonstrates that the performance of PatchCore on MVTec AD and MPDD is relatively weak, but Aug.(R) demonstrates higher performance. It demonstrates heuristically that our enhancement to feature rotation is significantly effective. Moreover, Graph-

(a) MPDD   (b) MVTec AD   (c) MVTec LOCO AD

Figure 8: Ablation results on sampling rates and the number of N nearest neighbors.

(a) MPDD

(b) MVTec AD

Figure 9: GraphCore VS Augmentation+PatchCore VS PatchCore on various number of shot (K).

Figure 10: Visualization results of the proposed method on MVTec AD and MPDD.

Core outperforms Aug.(R) by a large margin, confirming our assumption that GraphCore can extract the isometric invariant feature from industrial-based anomaly detection images.

3.4 VISUALIZATION

Fig. 10 shows the visualization results obtained by our method on MVTec AD and MPDD with sampling rates of 0.01 and 1 shot, respectively. Each column represents a different item type, and the four rows, from top to bottom, are the detection image, anomaly score map, anomaly map on detection image, and ground truth. According to the results, our method can produce a satisfactory impact of anomaly localization on a variety of objects, indicating that it has strong generalizability even in the 1-shot case.

4 CONCLUSION

In this study, we introduce a new approach, GraphCore, for industrial-based fewshot visual anomaly detection. Initially, by investigating the CNN-generated feature space, we present a simple pipeline - Augmentation+PatchCore - for obtaining rotation-invariant features. It turns out that this simple baseline can significantly improve anomaly detection performance. We further propose GraphCore to capture the isometric invariant features of industrial normal samples. It outperforms the SOTA models by a large margin using only a few normal samples (≤ 8) for training. The majority of industrial datasets for anomaly detection possess isomorphism, which is a property perfectly suited to GraphCore. We will continue to push the limits of industrial-based fewshot anomaly detection in the future.

REFERENCES

Paul Bergmann, Michael Fauser, David Sattlegger, and Carsten Steger. Mvtec ad — a comprehensive real-world dataset for unsupervised anomaly detection. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9584–9592, 2019.

Paul Bergmann, Kilian Batzner, Michael Fauser, David Sattlegger, and Carsten Steger. Beyond dents and scratches: Logical constraints in unsupervised anomaly detection and localization. *International Journal of Computer Vision*, 130(4):947–969, 2022.

Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral networks and locally connected networks on graphs. *arXiv preprint arXiv:1312.6203*, 2013.

Niv Cohen and Yedid Hoshen. Sub-image anomaly detection with deep pyramid correspondences. *arXiv preprint arXiv:2005.02357*, 2020.

Thomas Defard, Aleksandr Setkov, Angelique Loesch, and Romaric Audigier. Padim: a patch distribution modeling framework for anomaly detection and localization. In *International Conference on Pattern Recognition*, pp. 475–489. Springer, 2021.

Hanqiu Deng and Xingyu Li. Anomaly detection via reverse distillation from one-class embedding. *ArXiv*, abs/2201.10703, 2022.

Sander Dieleman, Jeffrey De Fauw, and Koray Kavukcuoglu. Exploiting cyclic symmetry in convolutional neural networks. In *International conference on machine learning*, pp. 1889–1898. PMLR, 2016.

Choubo Ding, Guansong Pang, and Chunhua Shen. Catching both gray and black swans: Open-set supervised anomaly detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7388–7398, 2022.

Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017.

Kai Han, Yunhe Wang, Jianyuan Guo, Yehui Tang, and Enhua Wu. Vision gnn: An image is worth graph of nodes. *arXiv preprint arXiv:2206.00272*, 2022.

Kaiming He, X. Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. *ArXiv*, abs/1603.05027, 2016.

Chaoqin Huang, Haoyan Guan, Aofan Jiang, Ya Zhang, Michael Spratling, and Yan-Feng Wang. Registration based few-shot anomaly detection. *arXiv preprint arXiv:2207.07361*, 2022.

Stepan Jezek, Martin Jonak, Radim Burget, Pavel Dvorak, and Milos Skotak. Deep learning-based defect detection of metal parts: evaluating current methods in complex conditions. In *2021 13th International Congress on Ultra Modern Telecommunications and Control Systems and Workshops (ICUMT)*, pp. 66–71. IEEE, 2021.

Thomas Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *ArXiv*, abs/1609.02907, 2017.

Sungwook Lee, Seunghyun Lee, and Byung Cheol Song. Cfa: Coupled-hypersphere-based feature adaptation for target-oriented anomaly localization. *IEEE Access*, 10:78446–78454, 2022.

Guohao Li, Matthias Müller, Ali K. Thabet, and Bernard Ghanem. Can gcns go as deep as cnns? *ArXiv*, abs/1904.03751, 2019.

Philipp Liznerski, Lukas Ruff, Robert A Vandermeulen, Billy Joe Franks, Marius Kloft, and Klaus Robert Muller. Explainable deep one-class classification. In *International Conference on Learning Representations*, 2020.

Guansong Pang, Choubo Ding, Chunhua Shen, and Anton van den Hengel. Explainable deep few-shot anomaly detection with deviation networks. *arXiv preprint arXiv:2108.00462*, 2021.

Karsten Roth, Latha Pemula, Joaquin Zepeda, Bernhard Schölkopf, Thomas Brox, and Peter Gehler. Towards total recall in industrial anomaly detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14318–14328, 2022.

Marco Rudolph, Bastian Wandt, and Bodo Rosenhahn. Same same but differnet: Semi-supervised defect detection with normalizing flows. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 1907–1916, 2021.

Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. *arXiv: Machine Learning*, 2018.

Shelly Sheynin, Sagie Benaim, and Lior Wolf. A hierarchical transformation-discriminating generative model for few shot anomaly detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8495–8504, 2021.

Guodong Wang, Shumin Han, Errui Ding, and Di Huang. Student-teacher feature pyramid matching for anomaly detection. In *BMVC*, 2021.

Jhih-Ciang Wu, Ding-Jie Chen, Chiou-Shann Fuh, and Tyng-Luh Liu. Learning unsupervised metaformer for anomaly detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4369–4378, 2021.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.