Deconvolutional Networks on Graph Data

Abstract

Recent studies have indicated that Graph Convolutional Network (GCN) acts as a *low pass* filter in spectral domain and encodes smoothed node representations. In this paper, we consider the opposite, namely Graph Deconvolutional Network (GDN) that reconstructs graph signals from smoothed node representations. We motivate the design of GDN via a combination of inverse filters in spectral domain and de-noising layers in wavelet domain, as the inverse operation results in a *high pass* filter and may amplify the noise. We demonstrate the effectiveness of the proposed method on several tasks including graph feature imputation and graph structure generation.

1 Introduction

Autoencoders have demonstrated excellent performance on tasks such as representation learning [3] and generation [20]. Recently, several studies [48, 27] have demonstrated that the performance of autoencoders can be further improved by encoding with Convolutional Networks and decoding with Deconvolutional Networks [49]. Notably, [31] presents a novel symmetric architecture that provides a bottom-up mapping from input signals to latent hierarchical feature space with convolution operations and then maps the latent representation back to the input space with deconvolution operations. While this architecture has been successful when processing features with structures existing in the Euclidean space (e.g., images), recently there has been a surging interest in applying such a framework on non-Euclidean data like graphs. However, extending this autoencoder framework to graph-structured data requires graph deconvolutional operations, which remains open-ended and hasn't been well studied as opposed to the large body of solutions that have already been proposed for Graph Convolutional Networks (GCNs) [7, 21]. In this paper, we initiate a systematic study of Graph Deconvolutional Networks (GDNs), to reconstruct the signals smoothed by GCNs.

Most GCNs proposed by prior arts, e.g., Cheby-GCN [7] and GCN [21], exploit spectral graph convolutions [35] and Chebyshev polynomials [16] to retain coarse-grained information and avoid explicit eigen-decomposition of the graph Laplacian. Until recently, [42] and [9] have noticed that GCN [21] acts as a *low pass* filter in spectral domain and retains smoothed representations. Inspired by prior arts in the domain of signal deconvolution [23, 10, 14], we are motivated to design a GDN by an inverse operation of the *low pass* filters embodied in GCNs. Furthermore, we observe directly reversing *low pass* filters results in *high pass* filters in spectral domain and may amplify the noise. In this regard, we introduce a spectral-wavelet GDN to decode the smoothed representations into the input graph signals. The proposed spectral-wavelet GDN employs spectral graph convolutions with a *high pass* filter to obtain inversed signals and then de-noises the inversed signals in wavelet domain. In addition, we apply Maclaurin series as a fast approximation technique to compute both *high pass* filters and wavelet kernels [9].

We evaluate the effectiveness of the proposed GDN with two tasks: graph feature imputation [37, 47] and graph structure generation [20, 15]. For the former task, we further propose a graph autoencoder (GAE) framework that resembles the symmetric fashion of architectures [31]. The proposed GAE

Figure 1: Schematic diagram of the graph autoencoder perspective. We plot graphs in spatial domain together with their signal coefficients in spectral domain. In the encoding stage, we run a GCN model to derive smoothed node representations. In the decoding stage, we reconstruct the graph signal via a GDN model.

outperforms the state-of-the-arts on six benchmarks. For the latter task, our proposed GDN can enhance the generation performance of popular variational autoencoder frameworks including VGAE [20] and Graphite [15].

The contributions of this work are summarized as follows:

- We propose Graph Deconvolutional Network (GDN), the opposite operation of Graph Convolutional Network (GCN) that reconstructs graph signals from smoothed node representations.

- We study GDN from the perspective of inverse operations in spectral domain and identity the inverse operation results in *high pass* and may amplify the noise. To solve the noise issue, a de-nosing process based on graph wavelet is further proposed.

2 Preliminaries

In this work, we are given an undirected, unweighted graph $G = (V, A, X)$. V is the node set and $N = |V|$ denotes the number of nodes. The adjacency matrix $A \in \mathbb{R}^{N \times N}$ represents the graph structure. The feature matrix $X \in \mathbb{R}^{N \times d}$ represents the node attributes.

2.1 Convolution on graphs

The convolutional layers are used to derive smoothed node representations, such that nodes that are similar in topological space should be close enough in Euclidean space. Formally, the spectral graph convolution on a signal $x \in \mathbb{R}^N$ is defined as:

$$h = g_c * x = U \text{diag}(g_c(\lambda_1), \ldots, g_c(\lambda_N)) U^\top x, \tag{1}$$

where $\{\lambda_i\}_{i=1}^N$ are the eigenvalues of the normalized Laplacian matrix $L_{sym} = D^{-\frac{1}{2}} L D^{-\frac{1}{2}}$, L and D are the Laplacian and degree matrices of the input graph A respectively, and U is the eigenvector matrix of $L_{sym} = U \Lambda U^\top$. In this work, we focus on GCN [21], one of the popular convolution operations on graphs:

$$H = \text{GCN}(A, X), \tag{2}$$

where $H \in \mathbb{R}^{N \times v}$ denotes smoothed node representations. Specifically, [42] show that GCN is a *low pass* filter in spectral domain with $g_c(\lambda_i) = 1 - \lambda_i$, i.e.,

$$h_c = \sigma(U \text{diag}(g_c(\lambda)) U^\top x), \tag{3}$$

where $\sigma(\cdot)$ is the activation function.

2.2 Deconvolution on graphs

The deconvolutional layers are used to recover the original graph features given smoothed node representations. Formally, the spectral graph deconvolution on the smoothed representation $h \in \mathbb{R}^N$ is defined as:

$$x' = g_d * h = U \text{diag}(g_d(\lambda_1), \ldots, g_d(\lambda_N)) U^\top h, \tag{4}$$

With this deconvolution operation, we can use GDNs to produce fine-grained graph signals from the encoded H.

$$X' = \text{GDN}(A, H), \tag{5}$$

where $X' \in \mathbb{R}^{N \times d}$ denotes the recovered graph features. We shall further discuss our design of GDN in Section 3.

From the perspective of encoder-decoder, the convolution operation could be used as an encoder and the deconvolution operation as a decoder, We show a schematic diagram of this encoder-decoder perspective in Figure 1.

3 Graph Deconvolutional Network

In this section, we present our design of GDN. Motivated by prior arts in signal deconvolution [17], a naive deconvolutional net can be obtained using the inverse filter $g_c^{-1}(\lambda_i) = \frac{1}{1-\lambda_i}$ in spectral domain. Unfortunately, the naive deconvolutional net results in a *high pass* filter and may amplify the noise [10, 14]. This point is obvious for $g_c^{-1}(\lambda_i)$ as the signal fluctuates near $\lambda_i = 1$ if noise exists.

3.1 Noise analysis

Our target is to recover the original graph features given smoothed node representations h_c encoded by GCN [21]. Without the noise, it is naive to obtain the closed-form recovery relationship by the inverse operation $g_c^{-1}(\lambda) = \frac{1}{1-\lambda}$ directly, i.e.,

$$x = U \text{diag}(g_c^{-1}(\lambda)) U^\top \sigma^{-1}(h_c), \tag{6}$$

Here, we assume the activation function $\sigma(\cdot)$ is an inverse operator, e.g., Leaky ReLU, sigmoid, tanh. Actually, it is quite reasonable to consider such a prototypical model of invertible networks in the theoretical analysis. Otherwise, we need to address an ill-posed inverse problem instead as we automatically lose some information (e.g., null space). Hence, it is impossible to recover the ground-truth even under the noiseless model, see [1] for details.

Graph noise is ubiquitous in real-world applications. Following the convention in signal deconvolution [10] and image restoration [14], let's consider the white noise model, i.e., $\hat{h}$ is the smoothed node representations mixed with graph convolution and white noise,

$$\hat{h} = \sigma(U \text{diag}(g_c(\lambda)) U^\top x) + \epsilon, \tag{7}$$

where ϵ is the white Gaussian noise (i.e., $\epsilon \sim \mathcal{N}(0, \sigma^2 \mathbb{I}_N)$).

Next, we show that it will amplify the noise if we apply the inverse operation to the white noise model directly. That is,

$$x' = U \text{diag}(g_c^{-1}(\lambda)) U^\top \sigma^{-1}(\hat{h}), \tag{8}$$

Proposition 1. *Considering the independent white noise model* (7) *and* (8)*, if the inversed activation function is deferentiable which satisfies $\partial \sigma^{-1}(0) \geq 1$, the variance of x' is larger than the white noised ϵ added on the generative model.*

It was worthwhile mentioning that the condition regarding the inverse operator $\partial \sigma^{-1}(0) \geq 1$ is quite reasonable. Actually, it holds for many representative activation functions, including sigmoid, tanh and Leaky ReLU. Please refer to Appendix A for details. Proposition 1 shows the proposed inverse operation may introduce undesirable noise into the output graph. Thus, a de-noising process is necessary thereafter.

Figure 2: Low-order Maclaurin Series well approximate wavelet kernel and inverse wavelet kernel with $s = 1$.

3.2 The proposed GDN

To ameliorate the noise issue, we propose an efficient, hybrid spectral-wavelet deconvolutional network that performs inverse signal recovery in spectral domain first, and then conducts a de-noising step in wavelet domain to remove the amplified noise [30].

3.2.1 Inverse operator

Regarding the inverse operation in (6), the core is to explicitly compute eigen-decomposition. We propose to apply Maclaurin series approximation on $g_c^{-1}(\Lambda) = \sum_{n=0}^{\infty} \Lambda^n$ and get a fast algorithm as below:

$$U\text{diag}(g_c^{-1}(\lambda))U = \sum_{n=0}^{\infty} L_{sym}^n. \tag{9}$$

A detailed derivative of (9) can be found in Appendix E. When truncated low order approximation is used in practice with $n \leq 3$ [7], we derive a spectral filter with $g_c^{-1}(\lambda_i) = 1 + \lambda_i + \lambda_i^2 + \lambda_i^3$, which is apparently a *high pass* filter.

Following [31], we can use another activation function and trainable parameter matrix to estimate σ^{-1}, to avoid the potential non-invertible problem. Thus, the inverse operator becomes:

$$M = \sigma((I_N + \sum_{n=1}^{3} L_{sym}^n)HW_3), \tag{10}$$

where W_3 is the parameter set to be learned.

We contrast the difference between inverse operator in this work and other reconstruction methods including [50] and GALA [32].

Inverse operator vs. [50]   Compared with [50] which directly uses GCN for signal reconstruction, the proposed inverse operator demonstrates its efficacy in recovering the high frequency signals of the graph, as shown in Figure 2 (b). We shall further discuss this point in Section 3.3.

Inverse operator vs. GALA   GALA [32] can be viewed as the first-order approximation towards inverse operator in this work, with a spectral kernel of $1 + \lambda_i$. The difference is that our inverse operator can well approximate the inverse filter $g_c^{-1}(\lambda_i) = \frac{1}{1-\lambda_i}$ with third-order polynomials.

3.2.2 Wavelet de-noising

Wavelet-based methods have a strong impact on the field of de-noising, especially in image restoration when noise is amplified by inverse filters [30]. In the literature, many wavelet de-noising methods have been proposed, e.g., SureShrink [10], BayesShrink [6], and they differ in how they estimate the separating threshold. Our method generalizes these threshold ideas and automatically separates the noise from the useful information with a learning-based approach. Consider the input signal of wavelet system is mixed with Gaussian noise, the reasons why wavelet denoising works are: (1) a graph wavelet basis holds the majority of signal energy into a small number of large coefficients,

Figure 3: Illustration of road occupancy rates decoded by different approaches at 5pm on June 24, 2020 in District 7 of California. A darker color implies a higher road occupancy rate. In each figure above, we plot the reconstructed signal in spatial domain together with coefficients in spectral domain. (a) the original, (b) inverse operator (RMSE = 0.11), (c) GDN/our model (RMSE = 0.07), (d) GCN (RMSE = 0.09).

133 and (2) Gaussian noise in the original graph domain is again a Gaussian noise in wavelet domain
134 (with the same amplitude), see [17] for details. The core thus becomes how we can separate a small
135 number of large coefficients and the noise in wavelet domain. Given the latter is unknown, we adopt
136 a trainable parameter matrix to linearly transform the noise under zero and useful coefficients bigger
137 than zero, where ReLU is used to eliminate the noise.

138 Consider a set of wavelet bases $\Psi_s = (\Psi_{s1}, \ldots, \Psi_{sN})$, where each one Ψ_{si} denotes a signal
139 on graph diffused away from node i and s is a scaling parameter [43], the wavelet bases can be
140 written as $\Psi_s = Ug_s(\Lambda)U^\top$ and $g_s(\cdot)$ is a filter kernel. Following previous works GWNN [43] and
141 GRAPHWAVE [9], we use the heat kernel $g_s(\lambda_i) = e^{-s\lambda_i}$, as heat kernel admits easy calculation
142 of inverse wavelet transform with $g_s^{-1}(\lambda_i) = e^{s\lambda_i}$. In addition, we can apply Maclaurin series
143 approximation on heat kernel and neglect explicit eigen-decomposition by:

$$\Psi_s = \sum_{n=0}^{\infty} \frac{(-1)^n}{n!} s^n L_{sym}^n, \tag{11}$$

$$\Psi_s^{-1} = \sum_{n=0}^{\infty} \frac{s^n}{n!} L_{sym}^n, \tag{12}$$

144 To cope with the noise threshold estimation problem, we introduce a parameterized matrix in wavelet
145 domain and eliminate these noise coefficients via a ReLU function, in the hope of learning a separating
146 threshold from the data itself. Together with the representation M raised in Section 3.2.1, we derive
147 the reconstructed signal as:

$$X' = \Psi_s \text{ReLU}(\Psi_s^{-1} MW_4)W_5, \tag{13}$$

148 where W_4 and W_5 are trainable parameters.

We then contrast the difference between Wavelet Neural Network (WNN) in this work and other related WNNs including GWNN [43] and GRAPHWAVE [9].

Scalability An important issue in WNN is that one needs to avoid explicit eigen-decomposition to compute wavelet bases for large graphs. Both GRAPHWAVE and GWNN, though trying to avoid eigen-decomposition by exploiting Chebyshev polynomials, still rely integral operations (see Appendix D in [43]) and there is no clear way to scale up. Differently, we use Maclaurin series to approximate wavelet bases, which has explicit polynomial coefficients and can resemble the heat kernel well when $n = 3$. Please refer to Figure 2 for more details.

De-noising The purpose of both GWNN and GRAPHWAVE is to derive node presentations with localized graph convolution and flexible neighborhood, such that downstream tasks like classification can be simplified. On the contrary, our work implements wavelet neural network in the purpose of detaching the useful information and the noise amplified by inverse operator. Due to the different purpose, our work applies the activation function in wavelet domain while GWNN in the original vertex domain.

We analyze the complexity of our proposed GDN, which contains one inverse operator and one wavelet net. The complexity of both inverse operator and wavelet net is comparable to ChebNet [7], which takes $O(|E|)$ and $|E|$ is the number of edges. Thus, the complexity of GDN is $O(|E|)$.

3.3 Visualization

In Figure 3, we illustrate the difference between GDN and each component inside by visualizing the reconstructed road occupancy rates in a traffic network. The traffic network targets District 7 of California collected from Caltrans Performance Measurement System (PeMS)[1]. We select 4438 sensor stations as the node set V and collect their road average occupancy rates at 5pm on June 24, 2020. Following [25], we construct an adjacency matrix A by denoting $A_{ij} = 1$ if sensor station v_j and v_i are adjacent on a freeway along the same direction. We reconstruct road occupancy rate of each sensor station with three decoder variants: (b) inverse operator, (c) our proposed GDN, (d) GCN. Here the three variants share the same encoders.

As can be seen, while both GDN and GCN decoders can resemble the input signal in low frequency, GDN decoder retains more high frequency information. For inverse operator decoder, although keeping much high frequency information (mixed with noise), it drops lots of low frequencies, making the decoded signals less similar to the input in Euclidean space.

4 Experiments

We validate the proposed GDN on graph feature imputation [37, 47] and graph generation [20, 15]. The former task reconstructs graph features and the latter generates graph structures.

4.1 Graph feature imputation

In our model, we consider feature imputation as feature recovery on graphs. The model is trained on an incomplete version of feature matrix (training data) and further used to infer the potential missing features (test data).

Datasets We use six benchmark datasets including several domains: citation networks (Cora, Citeseer) [34], product co-purchase networks (Amaphoto, Amacomp) [28], social rating networks (Douban, Ciao[2]). For citation networks and product co-purchase networks, we use the preprocessed versions provided by [37] with uniform randomly missing rate of 10%. For Douban, we use the preprocessed dataset provided by [29]. For Ciao, we use a sub-matrix of 7,317 users and 1,000 items. Dataset statistics are summarized in Table 3 in the Appendix.

---

[1]http://pems.dot.ca.gov/
[2]https://www.ciao.co.uk/

Table 1: RMSE test comparison of different methods on graph feature imputation

Datasets	Ciao	Douban	Cora	Citeseer	Amaphoto	Amacomp
MEAN	1.385	0.850	0.503	0.503	0.414	0.417
KNN [39]	1.461	0.817	0.459	0.443	0.421	0.422
SVD [40]	1.380	0.833	0.493	0.490	0.413	0.417
MICE [5]	1.600	-	0.480	-	0.481	0.487
GAIN [46]	1.099	0.809	0.433	0.421	0.420	0.416
GRAPE [47]	1.042	0.742	0.430	0.419	0.399	0.402
Inverse decoder	1.115	0.812	0.447	0.431	0.409	0.407
GCN decoder[50]	1.132	0.826	0.439	0.434	0.410	0.409
GALA [32]	1.147	0.833	0.457	0.435	0.415	0.411
OURS	**1.011**	**0.734**	**0.415**	**0.399**	**0.391**	**0.393**

Setup Our graph autoencoder framework consists of an encoder and a decoder. Our encoder consists of two layers of Graph Convolutional Networks (GCN) [21]. Our decoder consists of one layer of proposed GDN, to produce fine-grained graphs. We use the Mean Squared Error (MSE) loss to reconstruct the features. For detailed architecture, please refer to Appendix C. For detailed hyper-parameter settings, please refer to Appendix D. We report Root Mean Squared Error (RMSE).

Baselines We compare with three commonly used imputation methods and three deep learning based imputation models:

- **MEAN**, which replaces the missing feature entries with the mean values of all observed feature entries.

- **KNN** [39], which first identifies the k-nearest neighbor samples and imputes the missing feature entries with the mean entries of these k samples. We set $k = 5$ in this work.

- **SVD** [40], which replaces the missing feature entries based on matrix completion with iterative low-rank SVD decomposition.

- **MICE** [5], which is a multiple regression method that infers missing entries by Markov chain Monte Carlo (MCMC) techniques.

- **GAIN** [46], which is a deep learning imputation model with generative adversarial training.

- **GRAPE** [47], which is the state-of-the-art deep learning imputation model based on deep graph representations.

For ablation studies of the graph autoencoder framework specified in Appendix C, we also include the results of decoders using GCN decoder [50], GALA [32], and inverse decoder in Section 3.2.1, to be compared with our proposed GDN. Besides, we compare with popular matrix completion methods in Appendix B for discrete feature recovery.

Results The test RMSE on the six benchmarks are shown in Table 1. Our method performs the best on all datasets, e.g., it beats the second best model GRAPE by 0.02 on Citeseer and 0.031 on Ciao, which shows the superiority of our methods on feature imputation. The feature imputation RMSE with respect to different missing rate is shown in Figure 4. As can be seen, our method performs the best with respect to different missing rate, e.g., it achieves 0.016 improvement over the second best model GRAPE on Citeseer when the missing rate is 70%, and 0.007 improvement over the second best model GRAPE on Amacomp when the missing rate is 30%.

Ablation study We investigate the role of wavelet de-noising in our GDN. We let the four decoder variants share the same depth of layers and parameter size. As observed in Table 1, when decoding by inverse operator, the performance is on a par with that of GCN decoders [50] and outperformed by our GDN decoders on all six datasets, indicating the effectiveness of this hybrid design. the performance of inverse decoder specified in Section 3.2.1 is always better than that of GALA [32], which shows the superiority of our third-order approximation.

Figure 4: Comparison of different methods on graph feature imputation tasks. The x-axis denotes the missing ratio while the y-axis denotes RMSE on test set.

Table 2: The effect of GDN with various graph generation methods

Datasets	MUTAG			PTC-MR			ZINC		
-	$\log p(A\|Z)$	AUC	AP	$\log p(A\|Z)$	AUC	AP	$\log p(A\|Z)$	AUC	AP
VGAE [20]	-1.101	0.716	0.427	-1.366	0.566	0.433	-1.035	0.556	0.288
VGAE + GDN	**-1.026**	**0.823**	**0.611**	**-1.351**	**0.760**	**0.602**	**-1.006**	**0.858**	**0.611**
Graphite [15]	-1.100	0.732	0.447	-1.362	0.564	0.437	-1.039	0.553	0.288
Graphite + GDN	**-1.024**	**0.818**	**0.608**	**-1.347**	**0.773**	**0.613**	**-0.998**	**0.838**	**0.567**

4.2 Graph structure generation

Data and baselines   We use three molecular graphs: MUTAG [22] containing mutagenic compounds, PTC-MR [22] containing compounds tested for carcinogenicity and ZINC [18] containing druglike organic molecules, to evaluate the performance of GDN on graph generation. Dataset statistics are summarized in Table 4 in the Appendix. We test GDN on two popular variational autoencoder framework including VGAE [20] and Graphite [15]. Our purpose is to validate if GDN helps with the generation performance.

Setup   For VGAE and Graphite, we reconstruct the graph structures using their default methods and the features using GDN. The two reconstructions share the same encoders and sample from the same latent distributions. For detailed architecture, please refer to Appendix D. We train for 200 iterations with a learning rate of 0.01. For MUTAG and PTC-MR, we use 50% samples as train set and the remaining 50% as test set. For ZINC, we use the default train-test split.

Results   Evaluating the sample quality of generative models is challenging [38]. In this work, we validate the generative performance with the log-likelihood ($\log p(A|Z)$), area under the receiver operating characteristics curve (AUC) and average precision (AP). As shown in Table 2, GDN can improve the generative performance of both VGAE and Graphite in general, e.g., it improve the AP score of Graphite by 16.1% on MUTAG , the AUC score of Graphite by 20.9% on PTC-MR and $\log p(A|Z)$ of VGAE by 0.029 on ZINC, which shows the superiority of GDN.

5   Related work

Deconvolutional networks   The area of signal deconvolution [23] has a long history in the signal processing community and is about the process of estimating the true signals given the degraded or smoothed signal characteristics [2]. Later deep learning studies [49, 31] consider deconvolutional

networks as the opposite operation for Convolutional Neural Networks (CNNs) and have mainly focused on Euclidean structures, e.g., image. For deconvolutional networks on non-Euclidean structures like graphs, the study is still sparse. [13] proposes the network deconvolution as inferring the true network given partially observed structure. [45] formulates the deconvolution as a pre-processing step on the observed signals, in order to improve classification accuracy. [50] considers recovering graph signals from the latent representation. However, it just adopts the filter design used in GCN and sheds little insight into the internal operation of GDN.

Graph autoencoders   Since the introduction of Graph Neural Networks (GNNs) [21, 7] and autoencoders (AEs), many studies [20, 15] have used GNNs and AEs to encode to and decode from latent representations. Although some encouraging progress has been achieved, there is still no work about graph deconvolution that can up-sample latent feature maps to restore their original resolutions. In this regard, current graph autoencoders bypass the difficulty via (1) non-parameterized decoders [20, 8, 24], (2) GCN decoders [15], (3) multi-layer perceptron (MLP) decoders [36], and (4) Laplacian sharpening [32].

Graph feature imputation   Feature imputation techniques can be generally classified into two groups: statistical approaches and deep learning models. The former group includes KNN [39], SVD [40], MICE [5], in which they makes assumptions about the data distribution through a parametric density function. The latter group includes GAIN [46], GRAPE [47]. Recently GRAPE [47] proposes graph feature imputation that assumes a network among items and the network is helpful in boosting the feature imputation performance. A related topic is matrix completion [29, 4, 12] in which it usually makes the assumption of finite and discrete feature values. Differently, both GRAPE and our method can recover both continuous and discrete feature values.

Graph structure generation   Graph structure generation techniques can be classified into three groups: one-shot [20, 15, 36], substructure [19] and node-by-node [26]. As this work is more related to the group of one-shot, we refer the readers to [11] for the details of other groups. The group of one-shot generates the entire graph all at once. Representative works include VGAE [20], Graphite [15] and GraphVAE [36]. Both VGAE and Graphite reconstruct graphs based on the similarities of graph structures. Differently, GraphVAE considers both the similarities of structures and node features and reconstructs node features using MLP. In this work, we show that the performance of one-shot graph generators can be improved by reconstructing node features using GDN.

6   Conclusion

In this paper, we present Graph Deconvolutional Network (GDN), the opposite of GCN that recovers graph signals from smoothed representations. The introduced GDN uses spectral graph convolutions with a *high pass* filter to obtain inversed signals and then de-noises the inversed signals in wavelet domain. The effectiveness of the proposed method is validated on graph feature imputation and graph structure generation tasks.

7   Limitation

Broadly speaking, graph signal restoration is an ill-posed problem. In this regard, the prior knowledge is important for high-quality recovery. This paper only pays attention to vanilla GCN (Kipf & Welling, 2017) and it is not clear whether the spectral-wavelet GDN ideas can be applied to other GNNs, e.g., GAT [41], GIN [44].

8   Broader Impact

This work initiates the restoration of graph signals smoothed by vanilla GCN (Kipf & Welling, 2017). As a sequence, researchers in drug design or molecule generation may benefit from this research, since the interpretation of GCN based representations is worthwhile to be further explored. On the other hand, it does facilitate adversarial attacks to GCN based fraud prevention systems.

References

[1] Lynton Ardizzone, Jakob Kruse, Sebastian Wirkert, Daniel Rahner, Eric W Pellegrini, Ralf S Klessen, Lena Maier-Hein, Carsten Rother, and Ullrich Köthe. "Analyzing inverse problems with invertible neural networks". In: *ICLR* (2019).

[2] Mark R Banham and Aggelos K Katsaggelos. "Digital image restoration". In: *IEEE signal processing magazine* 14.2 (1997), pp. 24–41.

[3] Yoshua Bengio. *Learning deep architectures for AI*. Now Publishers Inc, 2009.

[4] Rianne van den Berg, Thomas N Kipf, and Max Welling. "Graph convolutional matrix completion". In: *SIGKDD* (2018).

[5] Stef Buuren and Catharina Groothuis-Oudshoorn. "MICE: Multivariate Imputation by Chained Equations in R". In: *Journal of Statistical Software* 45 (Dec. 2011).

[6] S Grace Chang, Bin Yu, and Martin Vetterli. "Adaptive wavelet thresholding for image denoising and compression". In: *IEEE transactions on image processing* 9.9 (2000), pp. 1532–1546.

[7] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. "Convolutional neural networks on graphs with fast localized spectral filtering". In: *Advances in neural information processing systems*. 2016, pp. 3844–3852.

[8] Chenhui Deng, Zhiqiang Zhao, Yongyu Wang, Zhiru Zhang, and Zhuo Feng. "Graphzoom: A multi-level spectral approach for accurate and scalable graph embedding". In: *ICLR* (2020).

[9] Claire Donnat, Marinka Zitnik, David Hallac, and Jure Leskovec. "Learning structural node embeddings via diffusion wavelets". In: *ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*. 2018, pp. 1320–1329.

[10] David L Donoho and Jain M Johnstone. "Ideal spatial adaptation by wavelet shrinkage". In: *biometrika* 81.3 (1994), pp. 425–455.

[11] Faezeh Faez, Yassaman Ommi, Mahdieh Soleymani Baghshah, and Hamid R Rabiee. "Deep Graph Generators: A Survey". In: *arXiv preprint arXiv:2012.15544* (2020).

[12] Wenqi Fan, Yao Ma, Qing Li, Yuan He, Eric Zhao, Jiliang Tang, and Dawei Yin. "Graph Neural Networks for Social Recommendation". In: *The World Wide Web Conference*. ACM. 2019, pp. 417–426.

[13] Soheil Feizi, Daniel Marbach, Muriel Médard, and Manolis Kellis. "Network deconvolution as a general method to distinguish direct dependencies in networks". In: *Nature biotechnology* 31.8 (2013), pp. 726–733.

[14] Mário AT Figueiredo and Robert D Nowak. "An EM algorithm for wavelet-based image restoration". In: *IEEE Transactions on Image Processing* 12.8 (2003), pp. 906–916.

[15] Aditya Grover, Aaron Zweig, and Stefano Ermon. "Graphite: Iterative generative modeling of graphs". In: *The International Conference on Machine Learning (ICML)*. 2019, pp. 2434–2444.

[16] David K Hammond, Pierre Vandergheynst, and Rémi Gribonval. "Wavelets on graphs via spectral graph theory". In: *Applied and Computational Harmonic Analysis* 30.2 (2011), pp. 129–150.

[17] Jeff Irion and Naoki Saito. "Efficient approximation and denoising of graph signals using the multiscale basis dictionaries". In: *IEEE Transactions on Signal and Information Processing over Networks* 3.3 (2016), pp. 607–616.

[18] John J Irwin, Teague Sterling, Michael M Mysinger, Erin S Bolstad, and Ryan G Coleman. "ZINC: a free tool to discover chemistry for biology". In: *Journal of chemical information and modeling* 52.7 (2012), pp. 1757–1768.

[19] Wengong Jin, Regina Barzilay, and Tommi Jaakkola. "Junction tree variational autoencoder for molecular graph generation". In: *The International Conference on Machine Learning (ICML)* (2018).

[20] Thomas N Kipf and Max Welling. "Variational Graph Auto-Encoders". In: *Conference on Neural Information Processing Systems (NeurIPS) Workshop on Bayesian Deep Learning*. 2016.

[21] Thomas N. Kipf and Max Welling. "Semi-Supervised Classification with Graph Convolutional Networks". In: *The International Conference on Learning Representations (ICLR)*. 2017.

[22] Nils Kriege and Petra Mutzel. "Subgraph matching kernels for attributed graphs". In: *ICML* (2012), pp. 291–298.

[23] Deepa Kundur and Dimitrios Hatzinakos. "Blind image deconvolution". In: *IEEE signal processing magazine* 13.3 (1996), pp. 43–64.

[24] Jia Li, Jianwei Yu, Jiajin Li, Honglei Zhang, Kangfei Zhao, Yu Rong, Hong Cheng, and Junzhou Huang. "Dirichlet Graph Variational Autoencoder". In: *Neurips*. 2020.

[25] Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. "Diffusion convolutional recurrent neural network: Data-driven traffic forecasting". In: *ICLR* (2018).

[26] Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander L. Gaunt. "Constrained Graph Variational Autoencoders for Molecule Design". In: *The Thirty-second Conference on Neural Information Processing Systems* (2018).

[27] Jonathan Long, Evan Shelhamer, and Trevor Darrell. "Fully convolutional networks for semantic segmentation". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2015, pp. 3431–3440.

[28] Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. "Image-based recommendations on styles and substitutes". In: *SIGIR*. 2015, pp. 43–52.

[29] Federico Monti, Michael Bronstein, and Xavier Bresson. "Geometric matrix completion with recurrent multi-graph neural networks". In: *Neurips*. 2017, pp. 3697–3707.

[30] Ramesh Neelamani, Hyeokho Choi, and Richard Baraniuk. "ForWaRD: Fourier-wavelet regularized deconvolution for ill-conditioned systems". In: *IEEE Transactions on signal processing* 52.2 (2004), pp. 418–433.

[31] Hyeonwoo Noh, Seunghoon Hong, and Bohyung Han. "Learning deconvolution network for semantic segmentation". In: *Proceedings of the IEEE international conference on computer vision*. 2015, pp. 1520–1528.

[32] Jiwoong Park, Minsik Lee, Hyung Jin Chang, Kyuewang Lee, and Jin Young Choi. "Symmetric graph convolutional autoencoder for unsupervised graph representation learning". In: *Proceedings of the IEEE/CVF International Conference on Computer Vision*. 2019, pp. 6519–6528.

[33] Yu Rong, Wenbing Huang, Tingyang Xu, and Junzhou Huang. "DropEdge: Towards Deep Graph Convolutional Networks on Node Classification". In: *International Conference on Learning Representations*. 2020. URL: https://openreview.net/forum?id=Hkx1qkrKPr.

[34] P. Sen, G. Namata, M. Bilgic, L. Getoor, B. Galligher, and T. Eliassi-Rad. "Collective classification in network data". In: *AI magazine* 29.3 (2008), pp. 93–106.

[35] David I Shuman, Sunil K Narang, Pascal Frossard, Antonio Ortega, and Pierre Vandergheynst. "The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains". In: *IEEE signal processing magazine* 30.3 (2013), pp. 83–98.

[36] Martin Simonovsky and Nikos Komodakis. "Graphvae: Towards generation of small graphs using variational autoencoders". In: *International Conference on Artificial Neural Networks*. Springer. 2018, pp. 412–422.

[37] Hibiki Taguchi, Xin Liu, and Tsuyoshi Murata. "Graph convolutional networks for graphs containing missing features". In: *Future Generation Computer Systems* 117 (2021), pp. 155–168.

[38] Lucas Theis, Aäron van den Oord, and Matthias Bethge. "A note on the evaluation of generative models". In: *ICLR* (2016).

[39] Olga Troyanskaya, Michael Cantor, Gavin Sherlock, Pat Brown, Trevor Hastie, Robert Tibshirani, David Botstein, and Russ B Altman. "Missing value estimation methods for DNA microarrays". In: *Bioinformatics* 17.6 (2001), pp. 520–525.

[40] Olga Troyanskaya, Mike Cantor, Gavin Sherlock, Trevor Hastie, Rob Tibshirani, David Botstein, and Russ Altman. "Missing Value Estimation Methods for DNA Microarrays". In: *Bioinformatics* 17 (July 2001), pp. 520–525. DOI: 10.1093/bioinformatics/17.6.520.

[41] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. "Graph attention networks". In: *ICLR* (2018).

[42] Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. "Simplifying Graph Convolutional Networks". In: *Proceedings of the 36th International Conference on Machine Learning (ICML)*. PMLR, 2019, pp. 6861–6871.

[43] Bingbing Xu, Huawei Shen, Qi Cao, Yunqi Qiu, and Xueqi Cheng. "Graph wavelet neural network". In: *The International Conference on Learning Representations (ICLR)* (2019).

[44] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. "How powerful are graph neural networks?" In: *ICLR* (2019).

[45] Jingkang Yang and Santiago Segarra. "Enhancing geometric deep learning via graph filter deconvolution". In: *2018 IEEE Global Conference on Signal and Information Processing (GlobalSIP)*. IEEE. 2018, pp. 758–762.

[46] Jinsung Yoon, James Jordon, and Mihaela van der Schaar. "GAIN: Missing Data Imputation using Generative Adversarial Nets". In: *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*. Ed. by Jennifer G. Dy and Andreas Krause. Vol. 80. Proceedings of Machine Learning Research. PMLR, 2018, pp. 5675–5684.

[47] Jiaxuan You, Xiaobai Ma, Daisy Ding, Mykel Kochenderfer, and Jure Leskovec. "Handling Missing Data with Graph Representation Learning". In: *NeurIPS* (2020).

[48] Matthew D Zeiler and Rob Fergus. "Visualizing and understanding convolutional networks". In: *European conference on computer vision*. Springer. 2014, pp. 818–833.

[49] Matthew D Zeiler, Dilip Krishnan, Graham W Taylor, and Rob Fergus. "Deconvolutional networks". In: *2010 IEEE Computer Society Conference on computer vision and pattern recognition*. IEEE. 2010, pp. 2528–2535.

[50] Chun-Yang Zhang, Junfeng Hu, Lin Yang, CL Philip Chen, and Zhiliang Yao. "Graph deconvolutional networks". In: *Information Sciences* 518 (2020), pp. 330–340.