DATA AUGMENTATION ALONE CAN IMPROVE ADVERSARIAL TRAINING

ABSTRACT

Adversarial training suffers from the issue of robust overfitting, which seriously impairs its generalization performance. Data augmentation, which is effective at preventing overfitting in standard training, has been observed by many previous works to be ineffective in mitigating overfitting in adversarial training. This work proves that, contrary to previous findings, data augmentation alone can significantly boost accuracy and robustness in adversarial training. We find that the hardness and the diversity of data augmentation are important factors in combating robust overfitting. In general, diversity can improve both accuracy and robustness, while hardness can boost robustness at the cost of accuracy within a certain limit and degrade them both over that limit. To mitigate robust overfitting, we first propose a new crop transformation Cropshift with improved diversity compared to the conventional one (Padcrop). We then propose a new data augmentation scheme, based on Cropshift, with much improved diversity and well-balanced hardness. Empirically, our augmentation method achieves the state-of-the-art accuracy and robustness for data augmentations in adversarial training. Furthermore, it matches, or even exceeds when combined with weight averaging, the performance of the best contemporary regularization methods for alleviating robust overfitting.

1 INTRODUCTION

Adversarial training, despite its effectiveness in defending against adversarial attack, is prone to overfitting. Specifically, while performance on classifying training adversarial examples improves during the later stages of training, test adversarial robustness degenerates. This phenomenon is called *robust overfitting* (Rice et al., 2020). To alleviate overfitting, Rice et al. (2020) propose to track the model's robustness on a reserved validation data and select the checkpoint with the best validation robustness instead of the one at the end of training. This simple technique, named early-stopping (ES), matches the performance of contemporary state-of-the-art methods, suggesting that overfitting in adversarial training impairs its performance significantly. Therefore, solving robust overfitting is important for improving adversarial training.

Data augmentation is an effective technique to alleviate overfitting in standard training, but it seems to not work well in adversarial training. Almost all previous attempts (Rice et al., 2020; Wu et al., 2020; Gowal et al., 2021a; Rebuffi et al., 2021; Carmon et al., 2019) to solve robust overfitting by data augmentation have failed. Specifically, this previous work found that several advanced data augmentation methods like Cutout (DeVries & Taylor, 2017), Mixup (Zhang et al., 2018) and Cutmix (Yun et al., 2019) failed to improve the robustness of adversarially-trained models to match that of the simple augmentation Flip-Padcrop with ES, as shown in Fig. 1. Thus the method of using ES with Flip-Padcrop has been widely accepted as the "baseline" for combating robust overfitting. Even with ES, Cutout still fails to improve the robustness over the baseline, while Mixup boosts the robustness marginally ($< 0.4\%$) (Rice et al., 2020; Wu et al., 2020). This contrasts with their excellent performance in standard training. Recently, Tack et al. (2022) observed that AutoAugment (Cubuk et al., 2019) can eliminate robust overfitting and boost the robustness greatly. This, however, contradicts the result of Gowal et al. (2021a); Carmon et al. (2019) where the baseline outperforms AutoAugment in terms of robustness. Overall, to date, there has been no uncontroversial evidence showing that robust generalization can be further improved over the baseline by data augmentation alone, and no convincing explanation about this ineffectiveness.

Figure 1: Our method is the only one that significantly improves both accuracy and robustness over the baseline (Flip-Padcrop with early-stopping). Cutout and Cutmix fail to beat the baseline regarding robustness. AutoAugment achieves only a small improvement on robustness over the baseline. Robustness is evaluated against AutoAttack. See Section 5 for details of training and evaluation settings.

This work focuses on improving robust generalization ability of adversarial training by data augmentation. We first demonstrate that the superior robustness of AutoAugment claimed by Tack et al. (2022) is actually a false security since its robustness against a more reliable attack AutoAttack (AA) (Croce & Hein, 2020) (48.71%) is just slightly higher than the baseline's (48.21%) as shown in Fig. 1 (see Appendix A for a detailed discussion). We then investigate the impact of the hardness and diversity of data augmentation on the performance of adversarial training. It is found that, in general, hard augmentation can alleviate robust overfitting and improve the robustness but at the expense of clean accuracy within a certain limit of hardness. Over that limit, both robustness and accuracy decline, even though robust overfitting is mitigated more with the increase in hardness. On the other hand, diverse augmentation generally can alleviate robust overfitting and boost both accuracy and robustness. These results give us the insight that the optimal data augmentation for adversarial training should have as much diversity as possible and well-balanced hardness.

To improve robust generalization, we propose a new image transformation, Cropshift, a more diverse replacement for the conventional crop operation, Padcrop. Cropshift is used as a component in a new data augmentation scheme that we call Improved Diversity and Balanced Hardness (IDBH). Empirically, IDBH achieves the state-of-the-art robustness and accuracy among data augmentation methods in adversarial training. It improves the end robustness to be significantly higher than the robustness of the baseline augmentation with early-stopping (Fig. 1), which all previous attempts failed to achieve. Furthermore, it matches the performance of the state-of-the-art regularization methods for improving adversarial training and, when combined with weight averaging, considerably outperforms almost all of them in terms of robustness.

2 RELATED WORKS

Robust overfitting can be successfully mitigated by smoothing labels, using Knowledge Distillation (KD) (Chen et al., 2021) and Temporal Ensembling (TE) (Dong et al., 2022), and/or smoothing weights using Stochastic Weight Averaging (SWA) (Chen et al., 2021) and Adversarial Weight Perturbation (AWP) (Wu et al., 2020). Moreover, Singla et al. (2021) found that using activation functions with low curvature improved the generalization of both accuracy and robustness. Alternatively, Yu et al. (2022) attributed robust overfitting to the training examples with small loss value, and showed that enlarging the loss of those examples during training, called Minimum Loss Constrained Adversarial Training (MLCAT), can alleviate robust overfitting. Our work solves robust overfitting by data augmentation, and hence complements the above methods.

To date, it is still unclear if more training data benefits generalization in adversarial training. Schmidt et al. (2018) showed that adversarial training requires more data, compared to its standard training counterpart, to achieve the same level of generalization. In contrast, Min et al. (2021); Chen et al. (2020) proved that more training data can hurt the generalization in some particular adversarial training regimes on some simplified models and tasks. Empirically, a considerable improvement has been observed in both clean and robust accuracy when the training set is dramatically expanded, in a semi-supervised way, with unlabeled data (Carmon et al., 2019; Alayrac et al., 2019), e.g., using Robust Self-Training (RST) (Carmon et al., 2019) or with synthetic data generated by a generative model (Gowal et al., 2021b). Although data augmentation alone doesn't work well, it was observed to improve robustness to a large degree when combined with SWA (Rebuffi et al., 2021) or Consistency (CONS) regularization (Tack et al., 2022). In contrast, our work doesn't require any additional data or regularization: it improves robust generalization by data augmentation alone.

Common augmentations (He et al., 2016a) used in image classification tasks include Padcrop (padding the image at each edge and then cropping back to the original size) and Horizontal Flip. Many more complicated augmentations have been proposed to further boost generalization. Cutout (DeVries & Taylor, 2017) and Random Erasing (Zhong et al., 2020) randomly drop a region in the input space. Mixup (Zhang et al., 2018) and Cutmix (Yun et al., 2019) randomly interpolate two images, as well as their labels, into a new one. AutoAugment (Cubuk et al., 2019) employs a combination of multiple basic image transformations like Color and Rotation and automatically searches for the optimal composition of them. TrivialAugment (Müller & Hutter, 2021) matches the performance of AutoAugment with a similar schedule yet without any explicit search, suggesting that this computationally expensive process may be unnecessary. The augmentation method proposed here improves on the above methods by specifically considering the diversity and hardness of the augmentations.

3 How Data Augmentation Alleviates Robust Overfitting

This section describes an investigation into how the hardness and the diversity of data augmentation effects overfitting in adversarial training. During training, the model's robustness was tracked at each epoch using PGD10 applied to the test set. The checkpoint with the highest robustness was selected as the "best" checkpoint. Best (end) robustness/accuracy refers to the robustness/accuracy of the best (last) checkpoint. In this section, the terms accuracy and robustness refer to the end accuracy and robustness unless specified otherwise. The severity of robust overfitting was measured using the best robustness minus the end robustness. Hence, the more positive this gap in robustness the more severe the robust overfitting. The training setup is described in Appendix B.

3.1 Hardness

Hardness was measured by the Affinity metric (Gontijo-Lopes et al., 2021) adapted from standard training:

$$hardness = \frac{Robustness(M, D_{test})}{Robustness(M, D'_{test})} \tag{1}$$

where M is an arbitrary model adversarially trained on the unaugmented training data. D_{test} refers to the original test data set and D'_{test} is D_{test} with the augmentation (to be evaluated) applied. $Robustness(M, D)$ is the robust accuracy of M evaluated using PGD50 on D. Hardness is a model-specific measure. It increases as the augmentation causes the data to become easier to attack, i.e., as the perturbed, augmented, data becomes more difficult to be correctly classified.

We found that moderate levels hardness can alleviate robust overfitting and improve the robustness but at the price of accuracy. Further increasing hardness causes both accuracy and robustness to decline, even though robust overfitting is alleviated further. The value of hardness where this occurs is very sensitive to the capacity of the model. Therefore, to maximize robustness, hardness should be carefully balanced, for each model, between alleviating robust overfitting and impairing accuracy.

Experiments design. We investigated the effects of hardness in adversarial training for individual and composed augmentations. For the individual augmentations the following 12 image transformations were choosen: ShearX, ShearY, TranslateX, TranslateY, Rotate, Color, Sharpness, Brightness, Contrast, Solarize, Cutout and Cropshift (a variant of Padcrop introduced in Section 4). For each Eq. (1) was used to calibrate the strength of the augmentation (e.g. angle for Rotation) onto one of 7 levels of hardness (see Appendix B.2 for specific values), except for Color and Sharpness which were applied at 3 strengths. For simplicity, the integers 1 to 7 are used to represent these 7 degrees of hardness. Standard Cutout is allowed to cut partially outside the image, and thus the hardness is not always directly related to the nominal size of the cut-out region (strength). To ensure alignment between strength and hardness, we force Cutout to cut only inside the image and refer this variant as Cutout-i. To control for diversity, each augmentation was applied with one degree of diversity. As a result the effects of applying Cutout and Cropshift with a certain hardness is deterministic throughout training. Specifically, Cutout always cuts at the fixed location (sampled once at the beginning of training). Similarly, CropShift crops a fixed region and shifts it to the fixed location (both sampled once at the beginning of training). We name these two variants as Cutout-i-1 and CropShift-1 respectively. Models were trained with each transformation at each hardness.

Figure 2: The performance of models trained with different individual transformations (top row) and composed augmentations (bottom row). None refers to no data augmentation applied.

To investigate composed augmentations, models were trained with various multi-layered data augmentations: Flip-Padcrop (FP), FP-Cutout[Weak] (CW), FP-Cutout[Strong] (CS), FP-AutoAugment-Cutout (AuA) and FP-TrivialAugment-Cutout (TA). All of them shared the same parameters for Flip and Padcrop. CW and CS used 8x8 and 10x10 Cutout respectively. AuA and TA used 16x16 Cutout as in their original settings (Cubuk et al., 2019; Müller & Hutter, 2021). Different from the default experimental setting, augmentations here were always applied during training, and robustness was evaluated against AA since AuA was observed to fool the PGD attack (Appendix A).

Hardness increases from FP to TA as more layers stack up and/or the strength of individual components increases. Hence, this experiment can, as for the experiments with individual augmentations, be seen as an investigation into the effects of increasing hardness. Here, we are not controlling for diversity, which also increases from FP to TA roughly. However, this should not affect our conclusions as diversity boosts the accuracy and robustness (see Section 3.2), and hence, the decrease in these values that we observe with increased hardness cannot be explained by the effects of increased diversity.

Observations. It can be seen that the gap between best and end robustness drops, i.e., robust overfitting turns milder with the increase in hardness in Figs. 2a and 2d. The gap of robustness for AuA is negative in Fig. 2d because the PGD10 attack was fooled to select a vulnerable checkpoint as the best: see Appendix A for more discussion.

For accuracy and robustness, there are roughly three phases. First, both accuracy (Fig. 2b) and robustness (Fig. 2c) increase with hardness. This is only observed for some transformations like Cropshift at hardness 1 and 2. In this stage, the underlying model has sufficient capacity to fit the augmented data so it benefits from the growth of data complexity.

Second, accuracy (Fig. 2b) starts to drop while robustness (Fig. 2c) continuously increases. As the intensity of the transformation increases, the distribution of the transformed data generally deviates more from the distribution of the original data causing the mixture of them to be harder to fit for standard training. Adversarial training can be concerned as standard training plus gradient regularization (Li & Spratling, 2022). Roughly speaking, accuracy drops in this stage because the model's capacity is insufficient to fit the increasingly hard examples for the optimization of the clean loss (standard

Figure 3: Performance of the models trained using augmentations with different type diversity (top row), spatial diversity (middle row) and strength diversity (bottom row). Spatial diversity rises from the restricted variant (solid lines) to the unrestricted variant (dashed lines) for the same transformation (color) in Figs. 3d, 3e and 3f

training) under the constraint of gradient regularization. Nevertheless, robustness could still increase due to the benefit of increasing robust generalization, i.e., smaller adversarial vulnerability.

Third, accuracy (Fig. 2e) and robustness (Fig. 2f) drop together. Accuracy continues to decline due to the severer (standard) underfitting. Meanwhile, the harm of decreasing accuracy now outweighs the benefit of reduced robust overfitting, which results in the degeneration of robustness.

The graphs of Color, TranslateX and TranslateY are omitted from Figs. 2a, 2b and 2c because they exhibit exceptional behavior at some values of hardness. Inspite of this, these results generally show that, compared to no augmentation, robust overfitting is reduced and robustness is improved. These results are presented and discussed in Appendix C.1. Appendix C.2 also provides a figure showing best accuracy for individual augmentations. A more obvious downward trend with increasing hardness can be seen in this graph compared to the graph for end accuracy shown in Fig. 2b

3.2 DIVERSITY

To investigate the effects of augmentation diversity, variation in the augmentations was produced in three ways: (1) using varied types of transformations ("type diversity"); (2) varying the spatial area to augment ("spatial diversity"); and (3) increasing the variance of the strength while keeping the mean strength constant ("strength diversity").

Figure 4: Illustration Cropshift (top) and Padcrop (bottom) with equivalent hardness.

Algorithm 1. Pseudo code of Cropshift.
Note: $randint(N)$ uniformly samples an integer between $[0, N)$.

$x', \; y' = randint(N), \; N - x'$
$x, \; y = randint(x'), \; randint(y')$
$w, \; h = get\_image\_size(img)$
$w', \; h' = w - x', \; h - y'$
$cropped = crop(img, \; x, \; y, \; w', \; h')$
$aug = zeros\_like(img)$
$x, \; y = randint(x'), \; randint(y')$
$aug[x : x + w', \; y : y + h'] = cropped$

Type diversity. We uniformly drew M transformations, with fixed and roughly equivalent hardness, from the same pool of transformations as the individual experiment in Section 3.1 but excluding Cutout and Cropshift. During training, one of these M transformations was randomly sampled, with uniform probability, to be applied to each sample separately in a batch. Diversity increases as M increases from 0 (no augmentation applied) to 10 (one augmentation from a pool of 10 applied). The experiments were repeated for three levels of hardness $\{1, 2, 3\}$. For all levels of hardness, the gap of robustness (Fig. 3a) reduces, and the end robustness (Fig. 3b) and accuracy (Fig. 3c) increases, as M increases. These trends are more pronounced for higher hardness levels.

Spatial diversity. Transformations like Cutout and Cropshift (described in Section 4) have large inherent diversity due to the large number of possible crop and/or shift operations that can be performed on the same image. For example, there are 28x28 possible 4x4 pixel cutouts that could be taken from a 32x32 pixel image, all with the same strength of 4x4. In contrast, transformations like Shear and Rotation have only one, or if sign is counted, two variations at the same strength, and hence, have a much lower inherent diversity. To investigate the impact of this rich spatial diversity, we run the experiments to compare the performance of Cutout-i-1 with Cutout-i, and to compare Cropshift-1 and Cropshift, at various levels of hardness. In both cases the former variant of the augmentation method is less diverse than the latter. We observed that the rich spatial diversity in Cutout-i and Cropshift helps dramatically shrink the gap between the best and end robustness (Fig. 3d), and boost the end robustness (Fig. 3e) and accuracy (Fig. 3f) at virtually all hardness.

Strength diversity. Diversity in the strength was generated by defining four ranges of hardness: $\{4\}$, $\{3, 4, 5\}$, $\{2, 3, 4, 5, 6\}$ and $\{1, 2, 3, 4, 5, 6, 7\}$. During training each image was augmented using a strength uniformly sampled at random from the given range. Hence, for each range the hardness of the augmentation, on average, was the same, but the diversity of the augmentations increased with increasing length of the hardness range. Models trained with differing diversity were trained with each of the individual transformations defined in Section 3.1 excluding Color and Sharpness. Strength diversity for Cutout-1, Cropshift-1 and Rotate can be seen to significantly mitigate robust overfitting (Fig. 3g) and boost robustness (Fig. 3h), whereas for the other transformations it seems have no significant impact on these two metrics. Nevertheless, a clear increase in accuracy (Fig. 3i) is observed when increasing strength diversity for almost all transformations.

4 DIVERSE AND HARDNESS-BALANCED DATA AUGMENTATION

This section first describes Cropshift, our proposed version of Padcrop with enhanced diversity and disentangled hardness. Cropshift (Fig. 4; Algorithm 1) first randomly crops a region in the image and then shifts it around to a random location in the input space. The cropped region can be either square or rectangular. The strength of Cropshift is parameterized by the total number, N, of cropped rows and columns. For example, with strength 8, Cropshift removes l, r, t, b lines from the left, right, top and bottom borders respectively, such that $l + r + t + b = 8$. Cropshift significantly diversifies the augmented data in terms of both the content being cropped and the localization of the cropped content in the final input space. Furthermore, Cropshift offers a more fine-grained control on the hardness. In contrast, for Padcrop hardness is not directly related to the size of the padding, as for

example, using 4 pixel padding can results in cropped images with a variety of total image content that is trimmed (from 4 rows and 4 columns trimmed, to no rows and no columns trimmed).

To mitigate robust overfitting, we propose a new data augmentation scheme with Improved Diversity and Balanced Hardness (IDBH). Inspired by Müller & Hutter (2021), we design the high-level framework of our augmentation as a 4-layer sequence: flip, crop, color/shape and dropout. Each has distinct semantic meaning and is applied with its own probability. Specifically, we implement flip using Horizontal Flip, crop using Cropshift, dropout using Random Erasing, and color/shape using a set of Color, Sharpness, Brightness, Contrast, Autocontrast, Equalize, Shear (X and Y) and Rotate. The color/shape layer, when applied to augment an image, first samples a transformation according to a probability distribution and then samples a strength from the transformation's strength range. This distribution and the strength range of each component transformation are all theoretically available to optimize. Pseudo-code for the proposed augmentation procedure can be found in Appendix D.

The probability and the strength of each layer was jointly optimized by a heuristic search to maximize the robustness. It is important to optimize all layers together, rather than individually. First, this enables a more extensive and more fine-grained search for hardness so that a potentially better hardness balance can be attained. Moreover, it allows a certain hardness to be achieved with greater diversity. For example, raising hardness through Cropshift also improves diversity, while doing so through the color/shape layer hardly increases diversity. However, optimizing the parameters of all layers jointly adds significantly to the computational burden. To tackle this issue, the search space was reduced based on insights gained from the preliminary experiments and other work, and grid search was performed only over this smaller search space. Full details are given in Appendix D. A better augmentation schedule might be possible if a more advanced automatic search was applied like AuA. However, automatically searching data augmentation in adversarial training is extremely expensive, and was beyond the resources available to us.

IDBH improves diversity through the probabilistic multi-layered structure which results in a very diverse mixture of augmentations including individual transformations and their compositions. We further diversify our augmentation by replacing the conventional crop and dropout methods, Padcrop and Cutout, in AuA and TA with their diversity-enhanced variants Cropshift and Random Erasing respectively. IDBH enables balanced hardness, as the structure design and optimization strategy produce a much larger search space of hardness, so that we are able to find an augmentation that achieves a better trade-off between accuracy and robustness.

5 RESULTS

We adopt the following setup for training and evaluation (fuller details in Appendix B). The model architectures used were Wide ResNet34 (Zagoruyko & Komodakis, 2016) and PreAct ResNet18 (He et al., 2016b). The training method was PGD10 adversarial training (Madry et al., 2018). SWA was implemented as in Rebuffi et al. (2021). We re-optimized the strength of Cutout and Cutmix per model architecture. AuA was parameterized as in Cubuk et al. (2019) since we didn't have sufficient resource to optimize. TA is parameter-free so no tuning was needed. For PreAct ResNet18, we report the result of two variants, weak and strong, of our method with slightly different parameters (hardness), because we observed a considerable degradation of best robustness on the strong variant when combined with SWA. Robustness was evaluated against AA using the implementation of Kim (2021). The reported results are averages over three runs, and the standard deviation is reported in Appendix C.3.

5.1 STATE-OF-THE-ART DATA AUGMENTATION FOR ADVERSARIAL TRAINING

From Tab. 1 it can be seen that our method, IDBH, achieves the state-of-the-art best and end robustness for data augmentations on both architectures, and its improvement over the previous best method is significant. The robust performance is further boosted when combined with SWA. Moreover, our method is the only one on Wide ResNet34 that successfully improves the end robustness to be higher than the best robustness achieved by the baseline. On PreAct ResNet18, IDBH[strong] improves the end robustness over the baseline's best robustness by $+1.78\%$, which is much larger than the existing best record ($+0.5\%$) achieved by AuA. This suggests that data augmentation alone,

Table 1: Performance of various data augmentation methods (w.o. SWA) and their weight-averaged variants (w. SWA) for Wide ResNet34 and PreAct ResNet18 on CIFAR10. The best record is highlighted for each metric in each block. All methods were trained in the same way, except that Cutmix was trained longer for convergence as Rebuffi et al. (2021).

Augment	w.o. SWA						w. SWA					
	Accuracy (%)			Robustness (%)			Accuracy (%)			Robustness (%)		
	best	end	diff.	best	end	diff.	best	end	diff.	best	end	diff.
Wide ResNet34												
baseline	78.37	78.96	-0.58	45.11	43.84	1.26	77.76	79.47	-1.71	45.71	44.69	1.02
Cutout	77.65	78.41	-0.76	45.22	44.43	0.78	76.86	79.09	-2.23	45.74	45.37	0.37
Cutmix	74.12	75.52	-1.40	45.10	44.49	0.61	**77.95**	78.06	-0.11	45.27	45.32	-0.05
AuA	74.59	74.93	-0.34	42.62	43.28	**-0.66**	75.30	75.36	**-0.06**	43.44	43.52	**-0.08**
TA	73.19	73.37	-0.18	42.06	41.92	0.14	73.41	73.53	-0.12	42.79	42.74	0.06
IDBH (ours)	**79.07**	**79.20**	**-0.13**	**46.15**	**45.65**	0.50	77.82	**79.83**	-2.01	**46.70**	**46.26**	0.44
PreAct ResNet18												
baseline	82.50	83.99	-1.49	48.21	42.46	5.74	79.22	84.67	-5.45	49.18	42.93	6.25
Cutout	83.35	84.14	-0.79	49.18	47.75	1.43	81.98	84.37	-2.39	50.18	48.76	1.42
Cutmix	82.47	81.51	**0.96**	49.73	48.09	1.65	84.09	85.70	-1.62	50.57	47.50	3.07
AuA	83.41	84.04	-0.62	49.15	48.71	0.44	82.08	84.20	-2.12	49.53	49.59	-0.07
TA	81.68	82.26	-0.58	48.83	48.62	**0.21**	81.63	82.73	**-1.11**	49.25	49.42	**-0.17**
IDBH[weak] (ours)	**84.98**	**85.82**	-0.84	50.34	48.94	1.40	**84.18**	**86.45**	-2.27	**51.73**	49.88	1.85
IDBH[strong] (ours)	83.96	84.92	-0.97	**50.74**	**49.99**	0.75	82.98	85.49	-2.51	51.49	**50.77**	0.72

contrary to the previous failed attempts, can significantly beat the baseline augmentation with ES. More importantly, our method also presents the highest best and end accuracy on both architectures, both w. and w.o. SWA, except for Wide ResNet34 with SWA where our method is very close to the best. Overall, our method improves both accuracy and robustness achieving a much better trade-off between them.

Data augmentation was found to be sensitive to the capacity of the underlying model. As shown in Tab. 1, augmentations such as baseline, AuA and TA perform dramatically different on two architectures because they use the same configuration across the architectures. Meanwhile, augmentations like Cutout and ours achieve relatively better performance on both architectures but with different settings for hardness. For example, the optimal strength of Cutout is 8x8 on Wide ResNet34, but 20x20 on PreAct ResNet18. Therefore, it is vital for augmentation design to allow optimization with wide enough range of hardness in order to generalize across models with different capacity.

5.2 MATCHING STATE-OF-THE-ART REGULARIZERS FOR ADVERSARIAL TRAINING

Tab. 2 shows the robustness of recent regularization approaches. It can be seen that IDBH matches the best AA robustness achieved by these regularization methods, and when combined with SWA outperforms them considerably in terms of best and end AA robustness. In addition, our method also produces an end accuracy that is comparable to the best achieved by other methods. Our method fails to beat the highest PGD10 robustness, achieved by RST, but it achieves significantly higher accuracy and end PGD10 robustness. Besides, RST, as a semi-supervised learning method, relies on a tremendous amount (10 times the size of the original training set) of unlabeled data, and so requires a much longer training time which seriously limits its application. In contrast, our method doesn't require any additional data and can be applied with virtually no extra computational cost.

5.3 GENERALIZATION TO OTHER DATASETS

Our augmentation generalizes well to other datasets like SVHN and TIN (Tab. 3). It greatly reduces the severity of robust overfitting and improves both accuracy and robustness over the baseline augmentation on both datasets. The robustness on SVHN has been dramatically improved by +7.12% for best and +13.23% for end. The robustness improvement on TIN is less significant than that on the other datasets because we simply use the augmentation schedule of CIFAR10 without further optimization. Please refer to Appendix B for the training and evaluation settings.

Table 2: Performance of methods for alleviating robust overfitting for PreAct ResNet18 on CIFAR10 (assessed using PGD10 and AA). The source of the result is noted if copied from another work, otherwise, it is determined by us. All methods use the same training setting, except RST due to the use of unlabeled data, is trained for the equivalent of 400 epochs, twice many as used for others.

Method	Accuracy			PGD10			AA		
	best	end	diff.	best	end	diff.	best	end	diff.
baseline	82.50	83.99	-1.49	53.35	46.01	7.34	48.21	42.46	5.75
RST (Rice et al., 2020)	82.80	77.00	**5.80**	**59.80**	52.90	6.90	-	-	-
AWP (Yu et al., 2022)[1]	82.00	81.11	0.89	-	-	-	49.94	49.69	**0.25**
MLCAT (Yu et al., 2022)	84.10	84.77	-0.67	-	-	-	50.70	50.32	0.38
CONS (Tack et al., 2022)	**85.25**	**86.45**	-1.20	-	-	-	49.05	48.57	0.48
KD	84.51	85.40	-0.89	-	-	-	49.87	49.72	0.15
TE (Dong et al., 2022)	82.35	82.79	-0.44	55.79	54.83	**0.96**	50.59	49.62	0.97
IDBH[strong] (ours)	83.96	84.92	-0.97	55.65	54.67	0.98	50.74	49.99	0.75
IDBH[weak]+SWA (ours)	84.18	**86.45**	-2.27	57.10	54.32	2.79	**51.73**	49.88	1.85
IDBH[strong]+SWA (ours)	82.98	85.49	-2.51	56.84	**55.60**	1.24	51.49	**50.77**	0.72

[1]Yu et al. (2022) reported the robustness without accuracy, so the accuracy is copied from Wu et al. (2020)

Table 3: Performance of our augmentation for PreAct ResNet18 on SVHN and TIN.

Data	Augment	Accuracy (%)		Robustness (%)	
		best	end	best	end
SVHN	baseline	90.55	90.18	47.48	40.86
	IDBH (ours)	**93.70**	**93.92**	**54.56**	**54.09**
TIN	baseline	46.94	46.60	20.19	13.82
	IDBH (ours)	**50.91**	**51.21**	**21.29**	**19.22**

Table 4: Performance of variants of IDBH for PreAct ResNet18 on CIFAR10.

SWA	Variant	Accuracy (%)		Robustness (%)	
		best	end	best	end
w.o.	padcrop	83.74	84.82	50.15	49.25
	cropshift	**83.96**	**84.92**	**50.74**	**49.99**
w.	padcrop	83.11	85.21	51.14	49.40
	cropshift	**84.18**	**86.45**	**51.73**	**49.88**

5.4 Ablation Test

We find that Cropshift outperforms Padcrop in our augmentation framework. To compare them, we replaced Cropshift with Padcrop in IDBH and kept the remaining layers unchanged. The strength of Padcrop was then optimized for the best robustness separately for w. and w.o. SWA. As shown in Tab. 4, changing Cropshift to Padcrop in our augmentation observably degrades both accuracy and robustness both w. and w.o. SWA.

6 Conclusion

This work has investigated data augmentation as a solution to robust overfitting. We found that improving robust generalization for adversarial training requires data augmentation to be as diverse as possible while having appropriate hardness for the task and network architecture. The optimal hardness of data augmentation is very sensitive to the capacity of training model. To mitigate robust overfitting, we propose a new image transformation Cropshift and a new data augmentation scheme IDBH incorporating Cropshift. Cropshift significantly boosts the diversity and improves both accuracy and robustness compared to the conventional crop transformation. IDBH improves the diversity and allows the hardness to be better balanced compared to alternative augmentation methods. Empirically, IDBH achieves the state-of-the-art accuracy and robustness for data augmentations in adversarial training. This proves that, contrary to the previous findings, data augmentation alone can significantly improve robustness and beat the robustness achieved with baseline augmentation and early-stopping. The limit of our work is that we did not have sufficient computational resources to perform more advanced, and more expensive, automatic augmentation search like AutoAugment, which implies that the final augmentation schedule we have described may be suboptimal. Nevertheless, the proposed augmentation method still significantly improves both accuracy and robustness compared to the previous best practice.

Reproducibility Statement Our methods including both Cropshift and IDBH can be easily implemented using the popular machine learning development frameworks like PyTorch (Paszke et al., 2019). These two algorithms Cropshift and IDBH are illustrated in pseudo codes in Algorithm 1 and Algorithm 2 respectively. The procedure of optimizing IDBH is described in detail in Appendix D. The full parameters of the optimal augmentation schedules we found are described in Tab. 10 and Tab. 9. The training and evaluation settings are described in Section 5 and Appendix B. To further facilitate the reproducibility, we are going to share our code and the pre-trained models to the reviewers and area chairs once the discussion forum is open, and will finally publish them alongside the paper if accepted.

REFERENCES

Jean-Baptiste Alayrac, Jonathan Uesato, Po-Sen Huang, Alhussein Fawzi, Robert Stanforth, and Pushmeet Kohli. Are Labels Required for Improving Adversarial Robustness? In *33rd Conference on Neural Information Processing Systems (NeurIPS 2019)*, pp. 10, 2019.

Maksym Andriushchenko and Nicolas Flammarion. Understanding and Improving Fast Adversarial Training. In *Advances in Neural Information Processing Systems*, pp. 12, 2020.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled Data Improves Adversarial Robustness. In *Advances in Neural Information Processing Systems*, pp. 12, 2019.

Lin Chen, Yifei Min, Mingrui Zhang, and Amin Karbasi. More Data Can Expand The Generalization Gap Between Adversarially Robust and Standard Models. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 1670–1680. PMLR, November 2020. URL https://proceedings.mlr.press/v119/chen20q.html. ISSN: 2640-3498.

Tianlong Chen, Zhenyu Zhang, Sijia Liu, Shiyu Chang, and Zhangyang Wang. Robust Overfitting may be mitigated by properly learned smoothening. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=qZzy5urZw9.

Francesco Croce and Matthias Hein. Reliable Evaluation of Adversarial Robustness with an Ensemble of Diverse Parameter-free Attacks. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 11, 2020.

Ekin D. Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V. Le. AutoAugment: Learning Augmentation Strategies From Data. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 113–123, Long Beach, CA, USA, June 2019. IEEE. ISBN 978-1-72813-293-8. doi: 10.1109/CVPR.2019.00020. URL https://ieeexplore.ieee.org/document/8953317/.

Terrance DeVries and Graham W. Taylor. Improved Regularization of Convolutional Neural Networks with Cutout. *arXiv:1708.04552 [cs]*, November 2017. URL http://arxiv.org/abs/1708.04552. arXiv: 1708.04552.

Yinpeng Dong, Ke Xu, Xiao Yang, Tianyu Pang, Zhijie Deng, Hang Su, and Jun Zhu. Exploring Memorization in Adversarial Training. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=7gE9V9GBZaI.

Raphael Gontijo-Lopes, Sylvia Smullin, Ekin Dogus Cubuk, and Ethan Dyer. Tradeoffs in Data Augmentation: An Empirical Study. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=ZcKPWuhG6wy.

Sven Gowal, Chongli Qin, Jonathan Uesato, Timothy Mann, and Pushmeet Kohli. Uncovering the Limits of Adversarial Training against Norm-Bounded Adversarial Examples. *arXiv:2010.03593 [cs, stat]*, March 2021a. URL http://arxiv.org/abs/2010.03593. arXiv: 2010.03593.

Sven Gowal, Sylvestre-Alvise Rebuffi, Olivia Wiles, Florian Stimberg, Dan Calian, and Timothy Mann. Improving Robustness using Generated Data. In *Thirty-Fifth Conference on Neural Information Processing Systems*, pp. 16, 2021b.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, Las Vegas, NV, USA, June 2016a. IEEE. ISBN 978-1-4673-8851-1. doi: 10.1109/ CVPR.2016.90. URL http://ieeexplore.ieee.org/document/7780459/.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity Mappings in Deep Residual Networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2016b. URL http://arxiv.org/abs/1603.05027.

Hoki Kim. Torchattacks: A PyTorch Repository for Adversarial Attacks, February 2021. URL http://arxiv.org/abs/2010.01950. arXiv:2010.01950 [cs].

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7(7):3, 2015.

Lin Li and Michael Spratling. Understanding and Combating Robust Overfitting via Input Loss Landscape Analysis and Regularization. *submitted*, pp. 29, August 2022.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards Deep Learning Models Resistant to Adversarial Attacks. In *International Conference on Learning Representations*, 2018. URL http://arxiv.org/abs/1706.06083.

Yifei Min, Lin Chen, and Amin Karbasi. The curious case of adversarially robust models: More data can help, double descend, or hurt generalization. In *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, pp. 129–139. PMLR, December 2021. URL https://proceedings.mlr.press/v161/min21a.html. ISSN: 2640-3498.

Samuel G. Müller and Frank Hutter. TrivialAugment: Tuning-Free Yet State-of-the-Art Data Augmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 774–782, 2021. URL https://openaccess.thecvf.com/content/ICCV2021/html/Muller_TrivialAugment_Tuning-Free_Yet_State-of-the-Art_Data_Augmentation_ICCV_2021_paper.html.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading Digits in Natural Images with Unsupervised Feature Learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *Advances in Neural Information Processing Systems*, volume 32, pp. 8026–8037, 2019. URL https://papers.nips.cc/paper/2019/hash/bdbca288fee7f92f2bfa9f7012727740-Abstract.html.

Sylvestre-Alvise Rebuffi, Sven Gowal, Dan Andrei Calian, Florian Stimberg, Olivia Wiles, and Timothy Mann. Data Augmentation Can Improve Robustness. In *Neural Information Processing Systems*, May 2021. URL https://openreview.net/forum?id=kgVJBBThdSZ.

Leslie Rice, Eric Wong, and J Zico Kolter. Overfitting in adversarially robust deep learning. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 12, 2020.

Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially Robust Generalization Requires More Data. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://papers.nips.cc/paper/2018/hash/f708f064faaf32a43e4d3c784e6af9ea-Abstract.html.

Vasu Singla, Sahil Singla, Soheil Feizi, and David Jacobs. Low Curvature Activations Reduce Overfitting in Adversarial Training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16423–16433, 2021. URL https://openaccess.thecvf.com/content/ICCV2021/html/Singla_Low_Curvature_Activations_Reduce_Overfitting_in_Adversarial_Training_ICCV_2021_paper.html.

Jihoon Tack, Sihyun Yu, Jongheon Jeong, Minseon Kim, Sung Ju Hwang, and Jinwoo Shin. Consistency Regularization for Adversarial Robustness. *Proceedings of the AAAI Conference on Artificial Intelligence*, 36(8):8414–8422, June 2022. ISSN 2374-3468, 2159-5399. doi: 10. 1609/aaai.v36i8.20817. URL https://ojs.aaai.org/index.php/AAAI/article/view/20817.

Dongxian Wu, Shu-Tao Xia, and Yisen Wang. Adversarial Weight Perturbation Helps Robust Generalization. In *Advances in Neural Information Processing Systems*, volume 33, pp. 2958–2969, 2020. URL https://papers.nips.cc/paper/2020/hash/1ef91c212e30e14bf125e9374262401f-Abstract.html.

Chaojian Yu, Bo Han, Li Shen, Jun Yu, Chen Gong, Mingming Gong, and Tongliang Liu. Understanding Robust Overfitting of Adversarial Training and Beyond. In *Proceedings of the 39th International Conference on Machine Learning*, pp. 25595–25610. PMLR, June 2022. URL https://proceedings.mlr.press/v162/yu22b.html. ISSN: 2640-3498.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. CutMix: Regularization Strategy to Train Strong Classifiers With Localizable Features. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6023–6032, 2019. URL https://openaccess.thecvf.com/content_ICCV_2019/html/Yun_CutMix_Regularization_Strategy_to_Train_Strong_Classifiers_With_Localizable_Features_ICCV_2019_paper.html.

Sergey Zagoruyko and Nikos Komodakis. Wide Residual Networks. In *Procedings of the British Machine Vision Conference 2016*, pp. 87.1–87.12, York, UK, 2016. British Machine Vision Association. ISBN 978-1-901725-59-9. doi: 10.5244/C.30.87. URL http://www.bmva.org/bmvc/2016/papers/paper087/index.html.

Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond Empirical Risk Minimization. February 2018. URL https://openreview.net/forum?id=r1Ddp1-Rb&;noteId=r1Ddp1-Rb),.

Zhun Zhong, Liang Zheng, Guoliang Kang, Shaozi Li, and Yi Yang. Random Erasing Data Augmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 13001–13008, April 2020. doi: 10.1609/aaai.v34i07.7000. URL https://ojs.aaai.org/index.php/AAAI/article/view/7000. Number: 07.

(a) PreAct ResNet18

(b) Wide ResNet34

Figure 5: The test robustness measured using PGD (blue lines) and AA (red lines) every 10 epochs during training. Results are shown, with solid lines, for PreAct ResNet18 (top) and Wide ResNet34 (bottom) trained with AutoAugment (AuA). The dashed lines represent the best robustness of the same models trained with the baseline data augmentation method, Flip-Padcrop, rather than AuA.

A   RECONCILING THE CONTRADICTORY RESULTS FOR AUTOAUGMENT

Experimental Setting.   AutoAugment was implemented as in the original paper (Cubuk et al., 2019): Horizontal Flip in half chance, Padcrop with 4 pixels padding, Color/shape layer searched for CIFAR10, 16x16 Cutout. We adopted the implementation of the color/shape layer from PyTorch (Paszke et al., 2019). The model architectures were Wide ResNet34 and PreAct ResNet18. We trained the models using the same settings as Tack et al. (2022), which is actually our default training setting in Section 5. Robustness was evaluated against both Projected Gradient Descent (PGD) (Madry et al., 2018) with 10 steps and AutoAttack (AA) (Croce & Hein, 2020).

We observe, similar to Tack et al. (2022), that the PGD robustness of AuA-trained models increases over the baseline PGD robustness at the later stage of training for both network architectures (see Fig. 5. In contrast, the AA robustness is similar to (Fig. 5a), or is worse than (Fig. 5b), the baseline's. AA has been widely recognized as a more advanced attack that is better able to estimate adversarial robustness reliably (Croce & Hein, 2020). Therefore, we conclude that AuA fails to significantly boost the end robustness over the baseline, and the impressive improvement regarding PGD robustness is misleading. The misalignment between PGD robustness and AA robustness is more explicit in Fig. 5b, where the "best" checkpoint detected by PGD robustness is different from that of AA robustness. That's why the severity of robust overfitting is observed to be negative in Section 3.1 and Section 5.1.

Our results, and those of Tack et al. (2022), for AutoAugment on PreAct ResNet18 are inconsistent with previous work that found that the end robustness (Carmon et al., 2019), and even the best robustness (Gowal et al., 2021a), of AutoAugment is lower than the best robustness of the baseline augmentation. We suspect that these contradictory results may be partially due to inconsistent use of the term AutoAugment. Tack et al. (2022) explicitly state their AutoAugment includes Horizontal Flip, Padcrop and Cutout as in the original work (Cubuk et al., 2019). In contrast, Carmon et al. (2019); Gowal et al. (2021a) seem to refer AutoAugment as only the color/shape layer and

the remaining three component augmentations may or may not have been included. Specifically, Carmon et al. (2019) state AutoAugment is used in addition to Padcrop and Horizontal Flip, and Gowal et al. (2021a) state AutoAugment is used with the original setting, but no specific implementation information is given. Another possible account is that they used different training settings, and particularly a different capacity model, which has an important impact on the performance of data augmentations in adversarial training as shown in Secs. 3.1 and 5.1.

B EXPERIMENTAL SETTINGS

B.1 TRAINING SETUP

Section 3. The experiments in this section were based on the following settings unless otherwise specified. The model's architecture was wide-ResNet34 (Zagoruyko & Komodakis, 2016). The dataset was CIFAR10 (Krizhevsky, 2009). Data augmentation, if specified, was applied with 50% chance, i.e., half the time augmentation was applied and half the time it was not applied. Models were trained by stochastic gradient descent for 200 epochs with initial learning rate 0.1, divided by 10 at the epochs 100 and 150. The momentum was 0.9, the weight decay was 5e-4 and the batch size was 128. CrossEntropy loss was used. For both adversarial training and evaluation, we used the same attack, l_∞ projected gradient descent (Madry et al., 2018), with a perturbation budget, ϵ, of 8/255 and a step size of 2/255. The number of steps was 10 and 50 for training and evaluation respectively. Result were averaged over 5 runs. Experiments were run on Tesla V100 and A100 GPUs.

Section 5. The experimental settings were identical to those used in Section 3 unless specified below. In contrast to Section 3, data augmentation, if used, was always applied. We additionally evaluated on the datasets SVHN (Netzer et al., 2011) and Tiny ImageNet (TIN) (Le & Yang, 2015). As in previous work Yu et al. (2022), the baseline augmentation for SVHN was no data augmentation. The baseline data augmentation for TIN was the same as used for CIFAR10 i.e., Horizontal Flip (applied at half chance) and Padcrop with 4 pixel padding. Adversarial training was applied when training with TIN in exactly the same way it was as when training on CIFAR10. To train on SVHN, the initial learning rate was 0.01, the step size was 1/255 and the perturbation budget, ϵ, was increased from 0 to 8/255 linearly in the first five epochs and then kept constants for the remaining epochs in order to stabilize the training, as suggested by Andriushchenko & Flammarion (2020), otherwise, the same set-up was used as when training on CIFAR10. For adversarial evaluation, robustness on TIN was evaluated against AutoPGD (Croce & Hein, 2020) with 50 iterations and 5 restarts since we did not have access to sufficient computational resources to run AA for TIN on a PreAct ResNet18.

The size of cut-out area for Cutout was searched for within the range of {4x4, 6x6, 8x8, ..., 28x28}. The optimal size we found was 8x8 when useing Wide ResNet34 and 20x20 when using PreAct ResNet18. Following the procedure used in Yun et al. (2019), for Cutmix the value of the hyperparameter α was searched for over the range {0.1, 0.25, 0.5, 1.0, 2.0, 4.0}. The optimal α we found was 0.1 on Wide ResNet34 and 0.25 on PreAct ResNet18. Cutout and Cutmix were applied with the default (baseline) augmentations in the order of Flip-Padcrop-Cutout and -Cutmix respectively. Similarly, for AuA (and TA) augmentions were applied in the order of Flip-Padcrop-AuA (TA)-Cutout as in Cubuk et al. (2019) (Müller & Hutter (2021)).

B.2 STRENGTH AND HARDNESS OF INDIVIDUAL TRANSFORMATIONS

The 7 degrees of hardness used were: {1.04, 1.17, 1.34, 1.56, 1.87, 2.34, 3.12}. This corresponds to the denominator in Eq. (1), i.e., $Robustness(M, D'_{test})$, having values of {45, 40, 35, 30, 25, 20, 15}% as the PGD50 robustness of the model on the original test data (no data augmentation applied), i.e., $Robustness(M, D_{test})$, was 46.93%. The search range was constrained to be between 0 and 1 for the transformations Color, Sharpness, Brightness and Contrast. The corresponding strength of each individual transformation is described in Tab. 5. Note that the correspondence between strength and hardness is approximate because the real $Robustness(M, D'_{test})$ is not exactly equal to the nominal value given above, e.g., the $Robustness(M, D'_{test})$ of ShearX with strength 0.1 is only close to, instead of strictly equal to, 45%. Nevertheless, the variation between

Table 5: The strength of individual transformations corresponding to the 7 degrees of hardness.

Transform	Hardness						
	1	2	3	4	5	6	7
	Robustness(%)						
	45	40	35	30	25	20	15
	Strength						
ShearX	0.1	0.24	0.33	0.4	0.45	0.55	0.7
ShearY	0.1	0.2	0.3	0.37	0.45	0.55	0.7
TranslateX	1	3	4	6	7	9	11
TranslateY	1	3	4	6	7	9	10
Rotate	3	7	12	15	19	23	31
Contrast	0.92	0.82	0.73	0.67	0.62	0.56	0.5
Brightness	0.92	0.82	0.75	0.7	0.65	0.6	0.56
Color	0.7	0.3	0.1	-	-	-	-
Sharpness	0.7	0.3	0.01	-	-	-	-
Solarize	253	240	224	210	195	185	172
Cropshift	1	4	7	9	12	15	18
Cutout-i	3	6	9	11	13	15	18

the real and the nominal $Robustness(M, D'_{test})$ for all transformations is small so this should not effect our analysis.

C ADDITIONAL EXPERIMENTAL RESULTS

C.1 EXCEPTIONAL TRANSFORMATIONS IN HARDNESS EXPERIMENTS

The figures of Translate (X and Y) and Color present exceptional patterns, as shown in Fig. 6. First, robust overfitting and end robustness jumps abruptly, at hardness 3, to the same level of performance as training without augmentation (the gray dashed line). This suggests that training with any of them at this particular hardness does not provide a benefit, and can even impair, the robust generalization and end robustness. This is in contrast to the results produced with other values of hardness for these specific transformations, as well as the results for other augmentations. Hence, at some strengths these augmentation don't make the training data harder to fit although they, recalling how we measure the hardness, do make the test data more vulnerable to adversarial attacks. For Color, this may be due to a reduction in diversity as at hardness 3 (strength 0.1) this augmentation transforms colorful images into gray images (Fig. 7).

Second, ignoring the behavior at hardness 3 discussed above, for Translate, changing hardness does not produce the same clear trends in the three metrics that are seen with increasing hardness for the other transformations. This suggests that the complexity of data augmented by Translate doesn't increase consistently, at least within the evaluated range, with the increase in strength. A possible explanation for this is that the foreground object lies in the center of the image in most CIFAR10 samples and, therefore, translating the image will typically only remove background pixels, and introduce a black block at one border. A black block at the border is rare in the natural images, so adding this pattern to the data should increase the complexity. However, increasing the strength of Translate may have little further impact on the data complexity, because it only increases the size of the black regions while remove a few additional informative pixels from the opposite edge of the image. This contrasts with the other investigated transformations, like Shear, in which increased strength leads to increased distortion or, like Cropshift, which introduce more new patterns to the data (adding black blocks at more borders), with increasing strength. Hence, applying (versus not applying) Translate affects the three metrics observably, but increasing the strength of Translate has little effect. Overall, these exceptions reflect a defect in measure of hardness, Eq. (1), and we leave the work of improving it to the future.

Figure 6: The comparison of the exceptional transformations Color, TranslateX and TranslateY (top row) and the others (bottom row) regarding the effect of hardness on the performance of adversarial training. The results at the bottom row also appear in Fig. 2 and are re-produced here to aid comparison.

Figure 7: Illustration of the effect of Color transformation with hardness 3 (strength 0.1) on selected CIFAR10 images. The original images are in the top row, while the augmented images are in the bottom row.

Figure 8: The effect of hardness of data augmentation on (a) best accuracy, and (b) end accuracy. The results for end accuracy also appear in Fig. 2b and are re-produced here to aid comparison.

Table 6: Standard deviation of the experimental results in Tab. 1.

Augmentation	w.o. SWA				w. SWA			
	Accuracy (%)		Robustness (%)		Accuracy (%)		Robustness (%)	
	best	end	best	end	best	end	best	end
Wide ResNet 34								
baseline	0.51	0.55	0.15	0.55	0.28	0.09	0.12	0.17
Cutout	0.18	0.43	0.11	0.31	0.11	0.15	0.09	0.15
Cutmix	1.57	1.28	0.29	0.32	0.15	0.08	0.11	0.20
AuA	1.35	0.52	0.28	0.12	0.41	0.30	0.49	0.36
TA	0.33	0.64	0.54	0.28	0.25	0.29	0.11	0.23
IDBH (ours)	0.35	0.39	0.06	0.12	0.22	0.18	0.10	0.04
PreAct ResNet 18								
baseline	0.31	0.53	0.57	0.23	0.22	0.13	0.11	0.16
Cutout	0.17	0.40	0.11	0.54	0.13	0.11	0.09	0.12
Cutmix	0.46	0.36	0.33	1.10	0.39	0.09	0.21	0.03
AuA	0.43	0.51	0.38	0.22	1.43	0.06	0.24	0.16
TA	0.31	0.20	0.32	0.40	1.83	0.16	0.39	0.26
IDBH[weak] (ours)	0.21	0.12	0.15	0.15	0.35	0.08	0.16	0.24
IDBH[strong] (ours)	0.42	0.04	0.06	0.25	0.13	0.23	0.25	0.22

C.2 FIGURES OF BEST ACCURACY FOR HARDNESS EXPERIMENTS

Fig. 8a shows the best accuracy with respect to the hardness for transformations excluding Translate and Color. It shows a more obvious downward trend for accuracy with increasing hardness.

C.3 STANDARD DEVIATION DATA

Tabs. 6 and 7 provide the standard deviation data for the experimental result reported in Tab. 1 and Tab. 3 respectively. Overall, the standard deviation of the robustness, both best and end, is less than 0.6.

Table 7: Standard deviation of the experimental results in Tab. 3.

Dataset	Augmentation	Accuracy (%)		Robustness (%)	
		best	end	best	end
SVHN	baseline	0.60	0.10	0.59	0.28
	ours	0.12	0.14	0.29	0.07
TIN	baseline	0.17	0.69	0.18	0.14
	ours	0.38	0.03	0.17	0.08

Table 8: The reduced search space used for each component of IDBH. Strength "1-X" means to uniformly sample a value between 1 and X, inclusive. Note that the strength of Cropshift is discrete so "1-5" is $\{1, 2, 3, 4, 5\}$. The strength of other component augmentations is continuous unless specified otherwise. "prob." denotes the probability of applying the transformation with the specified strength. For color/shape the strength is defined by a set of individual transformations as specified in Tab. 9.

Horizontal Flip			Cropshift			Color/shape			Random Erasing		
no.	strength	prob.	no.	strength	prob.	no.	strength	prob.	no.	strength	prob.
1	-	0.5	1	1-5	0.833 (=5/6)	1	ColorBiased	1	1	-	0
			2	1-6	0.857 (=6/7)	2	ShapeBiased	1	2	0.02-0.33	0.5
			3	1-7	0.875 (=7/8)				3	0.02-0.5	0.5
			4	1-8	0.889 (=8/9)				4	0.02-0.33	1
			5	1-9	0.900 (=9/10)				5	0.02-0.5	1
			6	1-10	0.909 (=10/11)						
			7	1-11	0.917 (=11/12)						
			8	1-12	0.923 (=12/13)						

Table 9: ColorBiased and ShapeBiased realizations of the color/shape layer. The strength and "prob." have the same interpretation as Tab. 8. $\pm[0.05\text{-}0.15]$ means a range of 0.05-0.15 with a randomly chosen sign. The strength value of Rotate was discrete. The probabilities of all component transformations in both realizations sums up to 1.

Transformation	ColorBiased		ShapeBiased	
	strength	prob.	strength	prob.
Color	0.1-1.9	0.125	0.1-1.9	0.08
Brightness	0.5-1.9	0.125	0.5-1.9	0.08
Contrast	0.5-1.9	0.125	0.5-1.9	0.04
Sharpness	0.1-1.9	0.125	0.1-1.9	0.08
AutoContrast	-	0.125	-	0.04
Equalize	-	0.125	-	0.08
ShearX	$\pm[0.05\text{-}0.15]$	0.0625	0.05-0.35	0.15
ShearY	$\pm[0.05\text{-}0.15]$	0.0625	0.05-0.35	0.15
Rotate	$\pm[1\text{-}10]$	0.125	1-30	0.3

Table 10: The optimal augmentation schedules found for our method on various datasets and models.

Data	Model	Variant	Horizontal Flip		Cropshift		Color/shape		Random Erasing	
			strength	prob.	strength	prob.	strength	prob.	strength	prob.
CIFAR10	Wide ResNet34	-	-	0.5	1-5	0.833	ColorBiased	1	-	0
CIFAR10	PreAct ResNet18	weak	-	0.5	1-10	0.909	ColorBiased	1	0.02-0.33	0.5
CIFAR10	PreAct ResNet18	strong	-	0.5	1-10	0.909	ColorBiased	1	0.02-0.33	1
SVHN	PreAct ResNet18	-	-	0.5	1-8	0.889	ShapeBiased	1	0.02-0.5	1
TIN	PreAct ResNet18	-	-	0.5	1-10	0.909	ColorBiased	1	0.02-0.33	0.5

D   AUGMENTATION SCHEDULE AND OPTIMIZATION

Tab. 8 shows the reduced search space used to optimize hyperparameters for our proposed IDBH augmentation method (see Algorithm 2). The flip layer was fixed to Horizontal Flip at half chance following convention. For the crop layer, we searched over 8 combinations, where each had a different strength range (defined by a changed upper bound) and probability of applying the transformation. For Random Erasing, we considered two strength ranges, $(0.02, 0.33)$ and $(0.02, 0.5)$, and two probabilities of application, 0.5 and 1.0. In this case strength denotes the proportion of the image erased. The aspect ratio of the erased area was always uniformly sampled between 0.3 and 3.3. Apart from these 4 combinations (2×2), we add one more case where Random Erasing is never applied, i.e. where the probability is zero.

Regarding the color/shape layer, two versions were implemented: a color transformations biased (ColorBiased) version, and a shape transformations biased (ShapeBiased) version, as defined in Tab. 9. These two realizations reflect the prior expectation that different datasets prefer essentially different types of transformation in standard training (Cubuk et al., 2019). The strength range of Color/Brightness/Contrast/Sharpness partially follows (Cubuk et al., 2019), but the lower bound of Brightness/Contrast is raised to 0.5 to be exempt from extremely hard (distorted) augmentations. Based on the results of the preliminary experiments, the strength range of Shear and Rotate was selected to have a relatively small average strength for the ColorBiased version, and a modest strength in the ShapeBiased version. The color (shape) transformations in the ColorBiased (ShapeBiased) instances are assigned a greater probability of being applied. The overall strength of this layer is relatively weak so that we can have more space to fine tune the strength of other layers particularly Cropshift which can boost the diversity alongside the hardness. We realize that there are many more possible implementations of the color/shape layer, considering additional implementations would greatly increase the computational burden of optimising the augmentation hyperparamters. Nevertheless, these two implements reflect our intuition as to reasonable hyperparameters to search, and our results show that they are adequate to produce a great boost in accuracy and robustness. Overall, the total search space contains 80 $(8 \times 2 \times 5)$ possible augmentation schedules.

We performed the grid search over the reduced search space for each model architecture on each dataset separately. An exception was for TIN: due to a lack of computational resources we did not optimize our augmentation on TIN and simply used the same parameters as for CIFAR10. The optimal schedules found are described in Tab. 10. We highlight that it is necessary to optimize the parameters for different architectures since our analysis (Section 3.1), as well as our search results (Tab. 10), suggests that the optimal data augmentation is very sensitive to the model architecture. The search procedure can be sped-up by being deployed on multiple GPUs in parallel. The efficiency can be further boosted by filtering out schedules that are likely to be worse based on the feedback of already evaluated schedules. For example, if a schedule appears to be overwhelmingly hard, degrading the accuracy and robustness, it is unnecessary to evaluate schedules that are harder.

Algorithm 2. Pseudo-code for IDBH. P_x is the probability of applying the transformation x. S_y is the strength range of the transformation y. $rand()$ uniformly samples a floating-point number between 0 (inclusive) and 1 (exclusive).

Function `IDBH` (img)**:**

    if $rand() < P_{flip}$ **then**

        img = horizontal_flip(img)

    end

    if $rand() < P_{crop}$ **then**

        s = uniform_sample(S_{crop})

        img = cropshift(img, s)

    end

    if $rand() < P_{color/shape}$ **then**

        `/* taking an example of ColorBiased color/shape layer.  */`

        transform, $S_{transform}$ = sample_transform($ColorBiased$)

        s = uniform_sample($S_{transform}$)

        img = transform(img, s)

    end

    if $rand() < P_{dropout}$ **then**

        s = uniform_sample($S_{dropout}$)

        img = erase(img, s)

    end

    return img