ALPHADESIGN: A GRAPH PROTEIN DESIGN METHOD AND BENCHMARK ON ALPHAFOLD DB

ABSTRACT

While AlphaFold has remarkably advanced protein folding, the inverse problem, protein design, by which protein sequences are predicted from the corresponding 3D structures, still faces significant challenges. First of all, there lacks a large-scale benchmark covering the vast protein space for evaluating methods and models; secondly, existing methods are still low in prediction accuracy and time-inefficient inference. This paper establishes a new benchmark based on AlphaFold DB, one of the world's largest protein structure databases. Moreover, we propose a new baseline method called AlphaDesign, which achieves 5% higher recovery than previous methods and about 70 times inference speed-up in designing long protein sequences. We also reveal AlphaDesign's potential for practical protein design tasks, where the designed proteins achieve good structural compatibility with native structures. The open-source code will be released.

1 INTRODUCTION

As "life machines", proteins play vital roles in almost all cellular processes, such as transcription, translation, signaling, and cell cycle control. Understanding the relationship between protein structures and their sequences brings significant scientific impacts and social benefits in many fields, such as bioenergy, medicine, and agriculture (Huo et al., 2011; Williams et al., 2019). While AlphaFold2 has tentatively solved protein folding (Jumper et al., 2021; Wu et al., 2022; Lin et al., 2022; Mirdita et al., 2022; Li et al., 2022c) from 1D sequences to 3D structures, its reverse problem, i.e., protein design raised by (Pabo, 1983) that aims to predict amino acid sequences from known 3D structures, has fewer breakthroughs in the ML community. The main reasons hindering the research progress include: (1) The lack of large-scale standardized benchmarks; (2) The difficulty in improving protein design accuracy; (3) Many methods are neither efficient nor open-source. Therefore, we aim to benchmark protein design and develop an effective and efficient open-source method.

Previous benchmarks may suffer from biased testing and unfair comparisons. Since SPIN (Li et al., 2014) introduced the TS500 (and TS50) consisting of 500 (and 50) native structures, it has served as a standard test set for evaluating different methods (O'Connell et al., 2018; Wang et al., 2018; Chen et al., 2019; Jing et al., 2020; Zhang et al., 2020a; Qi & Zhang, 2020; Strokach et al., 2020). However, such a few proteins do not cover the vast protein space and are more likely to lead to biased tests. Besides, there are no canonical training and validation sets, which means that different methods may use various training sets. If the training data is inconsistent, how can we determine that the performance gain comes from different methods rather than biases of the data distribution? Especially when the test set is small, adding training samples that match the test set distribution could cause dramatic performance fluctuations. Considering these issues, we suggest establishing a large-scale standardized benchmark for fair and comprehensive comparisons.

Extracting expressive residue representations is a key challenge for accurate protein design, where both sequential and structural properties must be considered. For general 3D points, structural features should be rotationally and translationally invariant in the classification task. Regarding proteins, we should consider amino acids' stable structure, number, and order. Previous studies (O'Connell et al., 2018; Wang et al., 2018; Ingraham et al., 2019; Jing et al., 2020) may have overlooked some important protein features and data dependencies; thus, few of them exceeds 50% accuracy except DenseCPD (Qi & Zhang, 2020). How can protein features and neural models be designed to learn expressive residue representations?

Improving the model efficiency is necessary for rapid iteration of research and applications. Current advanced methods have severe speed defects due to the sequential prediction paradigm. For example, GraphTrans (Ingraham et al., 2019) and GVP (Jing et al., 2020) predict residues one by one during

inference rather than in parallel, which means that it calls the model multiple times to get the entire protein sequence. Moreover, DenseCPD (Qi & Zhang, 2020) takes 7 minutes to predict a 120-length protein on their server [1]. How can we improve the model efficiency while ensuring accuracy?

To address these problems, we establish a new protein design benchmark and develop a graph model called AlphaDesign to achieve SOTA accuracy and efficiency. Firstly, we compare various graph models on consistent training, validation, and testing sets, where all these datasets come from the AlphaFold Protein Structure Database (Varadi et al., 2021). In contrast to previous studies (Ingraham et al., 2019; Jing et al., 2020) that use limited-length proteins, we extend the experimental setups to length-free. Secondly, we improve the model accuracy by introducing protein angles as new features and introducing a simplified graph transformer encoder (SGT). Thirdly, we improve model efficiency by proposing a constraint-aware protein decoder (CPD) to replace the auto-regressive decoder. Experiments show that AlphaDesign significantly outperforms previous methods in accuracy (+5%) and efficiency (70+ times faster than before). We also reveal AlphaDesign's potential for practical protein design tasks, where the designed proteins achieve good structural compatibility with native structures.

2 RELATED WORK

We focus on structure-based protein design (Gao et al., 2020; Pearce & Zhang, 2021; Wu et al., 2021; Ovchinnikov & Huang, 2021; Ding et al., 2022; Strokach & Kim, 2022; Li & Koehl, 2014; Greener et al., 2018; Anand et al., 2022; Karimi et al., 2020; Cao et al., 2021; Liu et al., 2022; McPartlon et al., 2022; Huang et al., 2022; Dumortier et al., 2022; Li et al., 2022a; Maguire et al., 2021; Anishchenko et al., 2021; Li et al., 2022b), and the approaches can be categorized into MLP-based, CNN-based, and GNN-based ones. Some terms need to be explained in advance: we refer to amino acids as residues, and accuracy indicates the degree of prediction of the residues, i.e., recovery.

Problem definition The structure-based protein design aims to find the amino acids sequence $\mathcal{S} = \{s_i : 1 \leq i \leq n\}$ that folds into a known 3D structure $\mathcal{X} = \{\boldsymbol{x}_i \in \mathbb{R}^3 : 1 \leq i \leq n\}$, where n is the number of residues and the natural proteins are composed by 20 types of amino acids, i.e., $1 \leq s_i \leq 20$, and $s_i \in \mathbb{N}^+$. Formally, that is to learn a function $\mathcal{F}_\theta : \mathcal{X} \mapsto \mathcal{S}$. Because homologous proteins always share similar structures (Pearson & Sierk, 2005), the problem itself is underdetermined, i.e., the valid amino acid sequence may not be unique. In addition, the need to consider both 1D sequential and 3D structural information further increases the difficulty of algorithm design.

Table 1: Statistics of structure-based protein design methods. N_{train} is the number of training samples. TS500 and TS500 are the test sets containing 500 and 50 proteins, respectively. All results are copied from their manuscripts or related papers.

	Method	N_{train}	TS500	TS50	Code
MLP	SPIN	1,532	30.30%	30.30%	no
	SPIN2	1,532	36.60%	33.60%	no
	Wang's model	10,173	36.14%	33.00%	no
CNN	SPROF	7,134	40.25%	39.16%	PyTorch
	ProDCoNN	17,044	42.20%	40.69%	no
	DenseCPD	≤10,727	55.53%	50.71%	no
GNN	GraphTrans	18,024	–	–	PyTorch
	GVP	18,024	–	44.90%	PyTorch
	GCA	18,024	–	43.00%	PyTorch
	AlphaDesign	18,024	49.23%	48.36%	PyTorch
	ESM-IF	>1M	–	–	PyTorch
	ProteinMPNN	18,024	–	–	PyTorch

MLP-based models These methods use **m**ulti-**l**ayer **p**erceptron (MLP) to predict the type of each residue. The MLP outputs the probability of 20 amino acids for each residue, and the input feature construction is the main difference between various methods. SPIN (Li et al., 2014) integrates torsion angles (ϕ and ψ), fragment-derived sequence profiles, and structure-derived energy profiles to predict protein sequences. SPIN2 (O'Connell et al., 2018) adds backbone angles (θ and τ), local contact number, and neighborhood distance to improve the accuracy from 30% to 34%. (Wang et al., 2018) uses backbone dihedrals (ϕ, ψ and ω), the sovlent-accessible surface area of backbone atoms (C_α, N, C, and O), secondary structure types (helix, sheet, loop), $C_\alpha - C_\alpha$ distance and unit direction vectors of $C_\alpha - C_\alpha$, $C_\alpha - N$ and $C_\alpha - C$, which achieves 33.0% accuracy on 50 test proteins. The MLP methods have a high inference speed, but their accuracy is relatively low due to the partial consideration of structural information. These methods require complex feature engineering using multiple databases and computational tools, limiting their widespread usage.

CNN-based models CNN methods extract protein features directly from the 3D structure, which can be further classified as 2D CNN-based and 3D CNN-based. The 2D CNN-based SPROF (Chen

---

[1] http://protein.org.cn/densecpd.html

et al., 2019) extracts structural features from the distance matrix and improves the accuracy to 39.8%. In contrast, 3D CNN-based methods extract residue features from the atom distribution in a three-dimensional grid box. For each residue, the atomic density distribution is computed after being translated and rotated to a standard position so that the model can learn translation and rotation invariant features. ProDCoNN (Zhang et al., 2020a) designs a nine-layer 3D CNN to predict the corresponding residues at each position, which uses multi-scale convolution kernels and achieves 40.69% recovery on TS50. DenseCPD (Qi & Zhang, 2020) further uses the DensetNet architecture (Huang et al., 2017) to boost the accuracy to 50.71%. Although 3DCNN-based models improve accuracy, their inference is slow, probably because they require separate pre-processing and prediction for each residue. In addition, none of the above 3D CNN models is open-source.

Graph-based models   Graph methods represent the 3D structure as a k-NN graph, then use graph neural networks (Defferrard et al., 2016; Kipf & Welling, 2016; Veličković et al., 2017; Zhou et al., 2020; Zhang et al., 2020b; Gao et al., 2022) to learn residue representations considering structural constraints. The protein graph encodes the residue information in node vectors and constructs edges and edge features between neighboring residues. GraphTrans (Ingraham et al., 2019) combines graph encoder and autoregressive decoder to generate protein sequences. GVP (Jing et al., 2020) increases the accuracy to 44.9% by proposing the geometric vector perceptron, which learns both scalar and vector features in an equivariant and invariant manner concerning rotations and reflections. GCA (Tan et al., 2022) further improves recovery to 47.02% by introducing global graph attention. Another related work is ProteinSolver (Strokach et al., 2020), but it was mainly developed for scenarios where partial sequences are known and do not report results on standard datasets. In parallel with our work, ProteinMPNN (Dauparas et al., 2022) and ESM-IF (Hsu et al., 2022) achieve dramatic improvements, while they do not provide the training code and will be benchmarked in the future.

3 METHODS

3.1 OVERVIEW

We present the overall framework of AlphaDesign in Fig. 1. We suggest using AlphaDesign as a future baseline model because it is more accurate, straightforward, and efficient than previous methods. The methodological innovations include:

- **Expressive features**: We add new proteins angles (α, β, γ) to steadily improve the model accuracy.
- **Simplified graph encoder**: We use the **s**implified **g**raph **t**ransformer (SGT) to extract more expressive representations.
- **Fast sequence decoder**: We propose **c**onstraint-aware **p**rotein **d**ecoder (CPD) to speed up inference by replacing the autoregressive generator.

Figure 1: Overview of AlphaDesign. Compared with GraphTrans, StructGNN (Ingraham et al., 2019) and GVP (Jing et al., 2020), we add new protein features, simplify the graph transformer, and propose a confidence-aware protein decoder to improve accuracy and efficiency.

3.2 GRAPH FEATURE AND ENCODER

The protein structure can be viewed as a particular 3D point cloud in which the order of residues is known. For ordinary 3D points, there are two ways to get rotation and translation invariant features: Using particular network architectures (Fuchs et al., 2020; Satorras et al., 2021; Jing et al., 2020; Shuaibi et al., 2021) that take 3D points as input or using handicraft invariant features. For proteins, general 3D point cloud approaches cannot consider their particularity, including the regular structure and order of amino acids. Therefore, we prefer learning from the hand-designed, invariant, and protein-specific features. How to create invariant features and learn expressive representations from them remains exploring.

Graph We represent the protein as a k-NN graph derived from residues to consider the 3D dependencies, where the default k is 30. The protein graph $\mathcal{G}(A, X, E)$ consists of the adjacency matrix $A \in \{0, 1\}^{n,n}$, node features $X \in \mathbb{R}^{n,12}$, and edge features $E \in \mathbb{R}^{m,23}$. Note that n and m are the numbers of nodes and edges, and we create these features by residues' stable structure, order, and coordinates.

Figure 2: Angles of the protein backbone.

Node features As shown in Fig. 2, we consider two kinds of angles, i.e., the angles $\alpha_i, \beta_i, \gamma_i$ formed by adjacent edges and the dihedral angles ϕ_i, ψ_i, ω_i formed by adjacent surfaces, where $\alpha_i, \beta_i, \gamma_i$ are new features we introduced. For better understanding dihedral angles, it is worth stating that ϕ_{i-1} is the angle between plane $C_{i-2} - N_{i-1} - C_{\alpha_{i-1}}$ and $N_{i-1} - C_{\alpha_{i-1}} - C_{i-1}$, whose intersection is $N_{i-1} - C_{\alpha_{i-1}}$. Finally, there are 12 node features derived from $\{\sin, \cos\} \times \{\alpha_i, \beta_i, \gamma_i, \phi_i, \psi_i, \omega_i\}$.

Edge features For edge $j \rightarrow i$, we use relative rotation R_{ji}, distance r_{ji}, and relative direction u_{ji} as edge features, seeing Fig. 2. At the i-th residue's alpha carbon, we establish a local coordinate system $Q_i = (b_i, n_i, b_i \times n_i)$. The relative rotation between Q_i and Q_j is $R_{ji} = Q_i^T Q_j$ can be represented by an quaternion $q(R_{ji})$. We use radial basis $r(\cdot)$ to encode the distance between C_{α_i} and C_{α_j}. The relative direction of C_{α_j} respective to C_{α_i} is calculated by $u_{ji} = Q_i^T \frac{x_j - x_i}{||x_j - x_i||}$. In summary, there are 23 edge features: 4 (quaternion) + 16 (radial basis) + 3 (relative direction).

Simplified graph transformer Denote $\boldsymbol{h}_i^l$ and $\boldsymbol{e}_{ji}^l$ as the output feature vectors of node i and edge $j \rightarrow i$ in layer l. We use MLP to project input node and edge features into d-dimensional space, thus $\boldsymbol{h}_i^0 \in \mathbb{R}^d$ and $\boldsymbol{e}_{ji}^0 \in \mathbb{R}^d$. When considering the attention mechanisms centered in node i, the attention weight a_{ji} at the $l+1$ layer is calculated by:

$$\begin{cases} w_{ji} = MLP_1(\boldsymbol{h}_j^l || \boldsymbol{e}_{ji}^l || \boldsymbol{h}_i^l) \\ a_{ji} = \frac{\exp w_{ji}}{\sum_{k \in \mathcal{N}_i} \exp w_{ki}} \end{cases} \quad (1)$$

Figure 3: Simplified graph transformer.

where $\mathcal{N}_i$ is the neighborhood system of node i and $||$ means the concatenation operation. Here, we simplify GraphTrans (Ingraham et al., 2019) by using a single MLP to learn multi-headed attention weights instead of using separate MLPs to learn Q and K, seeing Fig. 3. The updated $\boldsymbol{h}_i^{l+1}$ is:

$$\begin{cases} \boldsymbol{v}_j = MLP_2(\boldsymbol{e}_{ji}^l || \boldsymbol{h}_j^l) \\ \boldsymbol{h}_i^{l+1} = \sum_{j \in \mathcal{N}_i} a_{ji} \boldsymbol{v}_j \end{cases} \tag{2}$$

By stacking multiple **s**implified **g**raph **t**ransformer (SGT) layers, we can obtain expressive protein representations considering 3D structural constraints by message passing.

3.3 SEQUENCE DECODER

To generate more accurate protein sequences, previous researches (Ingraham et al., 2019; Jing et al., 2020) prefer the autoregressive mechanism. However, this technique also significantly slows down the inference process because the residuals must be predicted one by one. *Can we parallelize the predictor while maintaining the accuracy?*

Figure 4: CPD: The confidence-aware protein decoder. We use two 1D CNN networks to learn confidence scores and make final predictions based on the input graph node features.

Context-aware   Previously, we have considered the 3D constraints through graph networks but ignored 1D inductive bias. As shown in Fig. 4, the input features are $\mathcal{Z}_{gnn} = \{z_1, z_2, \cdots, z_N\}$, where z_i is the feature vector of node i extracted by the encoder. In the generation phase, we use 1D CNNs to capture the local sequential dependencies based on the 3D context-aware graph node features, where the convolution kernel can be viewed as the sliding window.

Confidence-aware   Given the 3D structure $\mathcal{X} = \{x_i : 1 \leq i \leq N\}$ and protein sequence $\mathcal{S} = \{s_i : 1 \leq i \leq N\}$, the vanilla autoregressive prediction indicates $p(\mathcal{S}|\mathcal{X}) = \prod_i p(s_i|\mathcal{X}, s_{<i})$, where residues must be predicted one-by-one. We replace autoregressive connections with parallelly estimated confidence score $\boldsymbol{c}$, written as

$$\begin{cases} \boldsymbol{a} = \text{Conf}(\mathcal{X}) \\ \boldsymbol{c} = f(\boldsymbol{a}) \\ p(\mathcal{S}|\mathcal{X}) = \prod_i p(s_i|\mathcal{X}, x_i, c_i) \end{cases} \tag{3}$$

where $\text{Conf}(\cdot)$ is the model containing graph encoder and CNN decoder and outputs logit scores $\boldsymbol{a} \in \mathbb{R}^{n,20}$, $f(\cdot)$ is the function computing confidence score $\boldsymbol{c} \in \mathbb{N}^{n,1}$. The confidence score contains knowledge captured by the previous prediction and serves as a hint message to help the network correct previous predictions. Let $M = \text{ColumnMax}(\boldsymbol{a}) \in \mathbb{R}^{n,1}$ and $m = \text{ColumnSubMax}(\boldsymbol{a}) \in \mathbb{R}^{n,1}$ as the first and secondary largest logits score of $\boldsymbol{a}$, the confidence score is defined as $\boldsymbol{c} = \lfloor \frac{M}{m} \rfloor$. We clarify that [2] $f(\hat{\boldsymbol{a}}) = \lfloor \frac{\hat{a}_i}{\hat{a}_j} \rfloor$, where $\lfloor \cdot \rfloor$ indicates the floor function. By extending $\hat{\boldsymbol{a}}$ as $\boldsymbol{a}$, Eq.(5) shows the vectorized version of $f(\cdot)$. We encode the confidence score as learnable embeddings $\mathcal{C} \in \mathbb{R}^{n,128}$, concatenate them with graph features, and feed these features into another CNN decoder to get the revised predictions. Note that all CNN decoders for estimating confidence and final predictions use the same CE loss:

$$\mathcal{L} = -\sum_i \sum_{1 \leq j \leq 20} \mathbb{1}_{\{j\}}(y_i) \log(p_{i,j}). \tag{4}$$

where $p_{i,j}$ is the predicted probability that residue i's type is j, y_i is the true label and $\mathbb{1}_{\{j\}}(\cdot)$ is a indicator function.

---

[2] Let $\hat{\boldsymbol{a}} \in \mathbb{R}^{20}$. Noting i and j as the indexes of the largest and sub-largest values of $\hat{\boldsymbol{a}}$, then $M = \hat{a}_i, m = \hat{a}_j$.

4 EXPERIMENTS

We conduct systemical experiments to establish a large-scale benchmark and evaluate the proposed AlphaDesign method. Specifically, we aim to answer:

- **Q1:** What is the difference between the new bechmark and the old one?
- **Q2:** Can AlphaDesign achieve SOTA accuracy and efficiency on the new benchmark?
- **Q3:** What is important for achieving SOTA performance?

4.1 BENCHMARK COMPARATION (Q1)

Metric   Following (Li et al., 2014; O'Connell et al., 2018; Wang et al., 2018; Ingraham et al., 2019; Jing et al., 2020), we use sequence recovery to evaluate different protein design methods. Compared with other metrics, such as perplexity, recovery is more intuitive and clear, and its value is equal to the average accuracy of predicted amino acids in a single protein sequence. By default, we report the median recovery score across the entire test set.

Previous benchmark   In Table. 1, we show the old benchmark collected from previous studies, including MLP (Li et al., 2014; O'Connell et al., 2018; Wang et al., 2018), CNN (Chen et al., 2019; Zhang et al., 2020a; Qi & Zhang, 2020; Huang et al., 2017) and GNN (Ingraham et al., 2019; Jing et al., 2020; Strokach et al., 2020; Dauparas et al., 2022; Hsu et al., 2022) models. Most approaches report results on the common test set TS50 (or TS500), consisting of 50 (or 500) native structures (Li et al., 2014). We also provide the results of AlphaDesign under the same experimental protocols as GraphTrans and GVP. Although the TS50, TS500 test sets have contributed significantly to establishing benchmarks, they still do not cover a vast protein space, and do not reveal how the model performs on different proteomic data. Besides, there are no canonical training and validation sets, which means that different methods may use various training sets.

New dataset   We use the AlphaFold Protein Structure Database (until 2021.2.1) [3] (Varadi et al., 2021) to benchmark graph-based protein design methods. As shown in Table. 6 (Appendix), there are over 360,000 predicted structures by AlphaFold2 (Jumper et al., 2021) across 21 model-organism proteomes. This dataset has several advantages:

- Species-aware: This dataset provides well-organized proteomic data for different species, which is helpful to develop specialized models for each species.
- More structures: This dataset provides more than 360,000 structures, while Protein Data Bank (PDB) (Burley et al., 2021) holds just over 180,000 structures for over 55,000 distinct proteins.
- High quality: The median predictive score of AlphaFold2 reaches 92.4%, comparable to experimental techniques (Callaway, 2020). Nicholas (Fowler & Williamson, 2022) found that AlphaFold tends to be more accurate than NMR ensembles. In 2020, the CASP14 benchmark recognized AlphaFold2 as a solution to the protein–folding problem (Pereira et al., 2021).
- Missing value: There are no missing values in protein structures provided by AlphaFold DB.
- Widespread usage: AlphaFold DB has been used in many frontier works (Varadi et al., 2022; Morreale et al., 2022; Luyten et al., 2022; Alderson et al., 2022; Zhang et al., 2022; Fowler & Williamson, 2022; Shaban et al., 2022; Brems et al., 2022; Hsu et al., 2022), and we believe that investigating AlphaFold DB could yield more discoveries for protein design.

Dataset Preprocessing   It should be noted that the AlphaFold2 DB data itself may have model bias. Similar to ESM-IF (Hsu et al., 2022), we address data quality and partitioning issues through data pre-processing for each proteomic data. As suggested by (Baek & Kepp, 2022; Callaway, 2020), the MAE between the predicted and experimentally generated structures does depend on pLDDT. Thus, we filter low-quality structures whose confidence score (pLDDT) is less than 70. To prevent potential information leakage, for each proteomic data, we cluster protein sequences if their sequence similarities (Qi & Zhang, 2020; Steinegger & Söding, 2017) are higher than 30% (Qi & Zhang, 2020) and split the dataset by these clusters. As a result, the proteins belonging to the same cluster must be in one of the training, validation, and test sets. By default, we keep the ratio of the training set and test set at about 9:1 and randomly choose 100 proteins belonging to the same cluster for validation.

---

[3] https://alphafold.ebi.ac.uk

4.2 ALPHADESIGN BENCHMARK (Q2)

Overall settings We extend the experimental setups to length-free and species-aware, while most previous studies (Ingraham et al., 2019; Jing et al., 2020; Tan et al., 2022) do not explore such a vast protein space. Length-free means that the protein length may be arbitrary to generalize the model to broader situations; otherwise, the protein must be between 30 and 500 in length. Species-aware indicates that we develop a specific model for each organism's proteome to learn domain-specific knowledge. In summary, there are two settings, i.e., species-aware dataset with limited length (SL) and species-aware dataset with free length (SF). Denote the total amount of structures as N_{all}, and the i-th species has N_i structures, we have $N_{all} = \sum_{i=1}^{i=21} N_i$. As shown in Table. 6, if the length is limited, $N_{all} = 254, 636$; otherwise, $N_{all} = 365, 198$. For each proteomic data, we develop 21 models based on datasets with $N_1, N_2, \cdots, N_{21}$ structures. We report the median recovery scores across the test set. All baseline results were obtained by running their official code with the same dataset. In parallel with our work, ProteinMPNN (Dauparas et al., 2022) and ESM-IF (Hsu et al., 2022) are also proposed, but they are not provided with the full training code and will be benchmarked in the future. Due to space constraints, we introduce abbreviations such as GTrans for GraphTrans and SGNN for Struct GNN.

Hyper-parameters AlphaDesign's encoder contains ten layers of SGT, and the decoder contains three layers of CNN, where the hidden dimension is 128. We use Adam optimizer and OneCycleLR scheduler to train all models up to 100 epochs with early stop patience 20 and learning rate 0.001. In the SL setting, we set the batch size as 16 for GraphTrans, StructGNN, GCA, and AlphaDesign, and the max node number as 2000 for GVP, which indicates the maximum number of residuals per batch. In the SF setting, we change GVP's max node parameter to 3000 to make it applicable to all data. GraphTrans, StructGNN, and GCA take more GPU memories because they must pad data according to the longest chain in each batch, and we adjust the batch size to 8 to avoid memory overflow.

Table 2: SL benchmark. The length of the protein must be between 30 and 500. We highlight the **best** (or underline{suboptimal}) results in bold (or underline).

	GTrans	SGNN	GCA	GVP	Our(SF)	Gain
DANRE	44.93	55.82	62.16	63.23	**70.70**	7.47
CANAL	47.81	50.62	52.55	58.43	**61.36**	2.93
MOUSE	49.53	54.04	59.23	62.00	**68.34**	6.34
ECOLI	46.95	52.62	55.08	59.79	**60.71**	0.92
DROME	42.39	52.94	58.92	60.52	**66.67**	6.15
METJA	42.68	52.09	51.59	58.54	**62.24**	3.7
PLAF7	46.32	50.00	49.52	58.74	**61.16**	2.42
MYCTU	54.02	56.32	58.50	65.24	**68.68**	3.44
CAEEL	47.44	54.89	62.32	63.00	**70.23**	7.23
DICDI	42.15	53.14	58.41	61.54	**67.21**	5.67
TRYCC	51.13	56.18	62.35	61.33	**71.08**	8.73
YEAST	36.18	49.23	52.14	58.30	**62.50**	4.2
SCHPO	44.56	49.34	51.90	58.21	**60.64**	2.43
RAT	48.23	60.41	67.01	65.87	**75.50**	8.49
HUMAN	51.15	54.83	61.19	63.10	**69.69**	6.59
ARATH	45.78	55.56	63.08	63.83	**71.15**	7.32
MAIZE	47.06	55.42	64.86	65.00	**74.12**	9.12
LEIIN	49.48	51.33	55.33	60.22	**64.71**	4.49
STAA8	45.57	48.31	47.52	57.14	**60.00**	2.86
SOYBN	47.73	56.52	64.84	64.10	**73.96**	9.12
ORYSJ	46.29	54.62	63.64	63.64	**72.98**	9.34
Average	46.54	53.53	58.20	61.51	**67.32**	5.81

Table 3: SF benchmark. There is no constraint on the protein length. We highlight the **best** (or underline{suboptimal}) results in bold (or underline).

	GTrans	SGNN	GVP	GCA	Our(SF)	Gain
DANRE	48.82	57.24	66.18	65.14	**69.65**	3.47
CANAL	51.14	55.17	61.82	60.88	**68.45**	6.63
MOUSE	47.79	57.40	64.23	64.50	**74.07**	9.57
ECOLI	50.60	54.22	59.11	60.71	**66.22**	5.51
DROME	50.56	55.91	63.13	61.67	**71.55**	8.42
METJA	51.03	52.47	53.13	59.24	**59.64**	0.4
PLAF7	48.11	53.92	57.26	59.75	**66.01**	6.26
MYCTU	48.25	58.04	61.93	64.93	**70.57**	5.64
CAEEL	46.82	54.05	64.48	64.03	**73.17**	8.69
DICDI	55.58	56.82	64.17	62.91	**71.66**	7.49
TRYCC	48.56	59.57	64.52	66.06	**75.18**	9.12
YEAST	50.00	54.00	60.41	58.45	**66.71**	6.3
SCHPO	47.62	53.91	60.26	60.21	**66.64**	6.38
RAT	47.97	57.83	65.99	63.89	**73.54**	7.55
HUMAN	55.28	56.29	64.86	63.83	**67.43**	2.57
ARATH	48.39	57.59	66.55	64.66	**73.84**	7.29
MAIZE	56.76	58.57	67.78	65.83	**76.00**	8.22
LEIIN	54.58	56.85	63.92	62.81	63.54	-0.38
STAA8	49.36	51.43	53.85	58.46	**63.85**	5.39
SOYBN	49.94	58.44	66.25	69.23	**76.51**	7.28
ORYSJ	48.04	58.41	66.78	64.00	**75.15**	8.37
Average	50.24	56.10	62.70	62.91	**69.97**	7.06

SL&SF results We present the SL and SF benchmark in Table. 2 and Table. 3, respectively. The order of model accuracy from high to low is AlphaDesign > GVP > GCA > SGNN > GTrans. Under SL setting, AlphaDesign achieves the best recovery on all proteomic datasets and exceeds previous methods by 5.81% on average. Under SF setting, AlphaDesign is still the most accurate model, and the increased training data further improves the model, i.e., the average accuracy of AlphaDesign (SF) is 69.97% while that of AlphaDesign (SL) is 62.91%. For different proteomic datasets, the larger the data volume, the better model performance; refer to Table.6. For example, the recovery on METIJ is 58.54% when the number of structures is 1605, which will increase to 73.96% on SOYBN when the data volume increases to 41,048.

4.3 EFFICIENCY COMPARATION (Q2)

A good algorithm should have excellent computational efficiency in addition to high accuracy. We compare the inference time cost of different approaches, especially when designing long proteins commonly found in AF2DB.

Setting We evaluate various models' inference time costs under different scenarios, considering 100 proteins with short (L<500), medium (500<L<1000), and long (1000<L) lengths . As to long sequence design, we further investigate the time costs of encoder, decoder, and encoder+decoder. All experiments are conducted on an NVIDIA-V100.

Figure 5: Inference time cost when designing long proteins. We report the total inference time of different methods on 100 long proteins, which are longer than 1000. The time costs of the encoder, decoder and encoder+decoder are reported.

Table 4: Inference time costs of different methods. #Number is the number of proteins for time cost evaluation. #Avg L is the average protein length.

	Short	Medium	Long
#Number	100	100	100
#Avg L	286	724	1632
GraphTrans	47.58	262.87	378.76
StructGNN	43.63	213.87	346.63
GCA	44.99	230.64	452.71
GVP	208.85	969.51	2026.53
AlphaDesign	**1.61**	**2.77**	**5.09**

Results We show the inference time costs for designing proteins of different lengths in Table.4. When designing short proteins (L < 500), AlphaDesign is 25+ times faster than baselines; and the dominance extends to about 70 times for designing long proteins (L ≥ 500). In Fig. 5, we observe that the time costs of baselines mainly come from the autoregressive decoder, and the proposed CPD module significantly speeds up the decoding process.

4.4 ABLATION STUDY (Q3)

While AlphaDesign has shown remarkable performance, we are more interested in where the improvements come from. As mentioned before, we add new protein features, simplify the graph transformer, and propose a confidence-aware protein decoder. Whether these modifications could improve model performance?

Setting We conduct ablation studies under the SL setting. Specifically, we may replace the simplified attention module with the original GraphTrans (w/o SGT), replace the CPD module with

the autoregressive decoder of GraphTrans (w/o CPD), or remove the newly introduced angle features (w/o new feat). All experimental settings keep the same as previous SL settings.

Results and analysis The ablation results are shown in Table. 5. We conclude that: (1) The SGT module and the new features can improve the recovery rate by 2.51% and 10.85%, respectively. Most of the performance improvement comes from the new angular features, are consistent with the recent ProteinMPNN, while they focus on distance features. (2) If we replace the CPD module with the autoregressive decoder, the recovery rate will improve by 0.55%. However, the recovery improvement brought by the autoregressive decoder is marginal compared to the SGT module and the new features. Therefore, we conclude CPD module dramatically improves the evaluation speed while maintaining good recovery. (3) If we remove the introduced angular features, AlphaDesign is not as accurate as GCA and GVP, but the improvement in efficiency is still significant.

	ADesign	w/o SGT	w/o CPD	w/o new feat
DANRE	70.70	68.27	71.04	62.18
CANAL	61.36	59.00	62.53	53.45
MOUSE	68.34	65.88	68.70	60.00
ECOLI	60.71	58.27	61.05	52.97
DROME	66.67	64.22	67.11	54.45
METJA	62.24	59.23	63.10	50.61
PLAF7	61.16	57.64	62.67	50.01
MYCTU	68.68	65.21	69.57	56.02
CAEEL	70.23	67.89	70.69	57.00
DICDI	67.21	63.79	67.48	54.94
TRYCC	71.08	68.93	71.70	59.58
YEAST	62.50	59.77	63.23	49.32
SCHPO	60.64	58.14	62.05	48.67
RAT	75.50	72.91	75.54	64.50
HUMAN	69.69	67.28	70.21	58.55
ARATH	71.15	69.30	71.82	61.62
MAIZE	74.12	72.17	74.42	64.26
LEIIN	64.71	61.98	65.29	52.52
STAA8	60.00	57.87	60.33	47.31
SOYBN	73.96	72.06	73.58	63.89
ORYSJ	72.98	71.26	73.23	64.11
Average	67.32	64.81	67.87	56.47
Gain	–	-2.51	0.55	-10.85

Table 5: Ablation study under the SL setting.

4.5 VISUAL EXAMPLES

We show the potential of AlphaDesign in real applications, i.e., designing all-alpha, all-beta, and mixed proteins. We ensemble multiple models by selecting the sequence with the lowest perplexity as the final solution. We use AlphaFold2 to predict the structures of designed sequences and compare them with the reference ones. Visual examples are provided in Figure. 6.

All-alpha structure (3tld)   All-beta structure (2giy)   Mixed structure (1mgr)

(Recovery=50.00, RMSD=1.18)   (Recovery=53.07, RMSD=0.54)   (Recovery=46.39, RMSD=0.47)

Figure 6: Visual examples. For native structures, we color Helix, Sheet, and Loop with cyan, magenta, and orange, respectively. Green structures are protein chains designed by our algorithm. We provide the recovery score and structural RMSD relative to the ground truth proteins.

5 CONCLUSION

This paper establishes a new benchmark and proposes a new method (AlphaDesign) for AI-guided protein design. By introducing new protein features, simplifying the graph transformer, and proposing a confidence-aware protein decoder, AlphaDesign achieves state-of-the-art accuracy and efficiency. We hope this work will help standardize comparisons and provide inspiration for subsequent research.

REFERENCES

T Reid Alderson, Iva Pritišanac, Alan M Moses, and Julie D Forman-Kay. Systematic identification of conditionally folded intrinsically disordered regions by alphafold2. bioRxiv, 2022.

Namrata Anand, Raphael Eguchi, Irimpan I Mathews, Carla P Perez, Alexander Derry, Russ B Altman, and Po-Ssu Huang. Protein sequence design with a learned potential. Nature communications, 13 (1):1–11, 2022.

Ivan Anishchenko, Samuel J Pellock, Tamuka M Chidyausiku, Theresa A Ramelot, Sergey Ovchinnikov, Jingzhou Hao, Khushboo Bafna, Christoffer Norn, Alex Kang, Asim K Bera, et al. De novo protein design by deep network hallucination. Nature, 600(7889):547–552, 2021.

Kristoffer Torbjoern Baek and Kasper Planeta Kepp. Assessment of alphafold2 residue conformations for human proteins. bioRxiv, 2022.

Maarten A Brems, Robert Runkel, Todd O Yeates, and Peter Virnau. Alphafold predicts the most complex protein knot and composite protein knots. Protein Science, 31(8):e4380, 2022.

Stephen K Burley, Charmi Bhikadiya, Chunxiao Bi, Sebastian Bittrich, Li Chen, Gregg V Crichlow, Cole H Christie, Kenneth Dalenberg, Luigi Di Costanzo, Jose M Duarte, et al. Rcsb protein data bank: powerful new tools for exploring 3d structures of biological macromolecules for basic and applied research and education in fundamental biology, biomedicine, biotechnology, bioengineering and energy sciences. Nucleic acids research, 49(D1):D437–D451, 2021.

Ewen Callaway. 'it will change everything': Deepmind's ai makes gigantic leap in solving protein structures. Nature, pp. 203–204, 2020.

Yue Cao, Payel Das, Vijil Chenthamarakshan, Pin-Yu Chen, Igor Melnyk, and Yang Shen. Fold2seq: A joint sequence (1d)-fold (3d) embedding-based generative model for protein design. In International Conference on Machine Learning, pp. 1261–1271. PMLR, 2021.

Sheng Chen, Zhe Sun, Lihua Lin, Zifeng Liu, Xun Liu, Yutian Chong, Yutong Lu, Huiying Zhao, and Yuedong Yang. To improve protein sequence profile prediction through image captioning on pairwise residue distance map. Journal of chemical information and modeling, 60(1):391–399, 2019.

Justas Dauparas, Ivan Anishchenko, Nathaniel Bennett, Hua Bai, Robert J Ragotte, Lukas F Milles, Basile IM Wicky, Alexis Courbet, Rob J de Haas, Neville Bethel, et al. Robust deep learning based protein sequence design using proteinmpnn. bioRxiv, 2022.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. Advances in neural information processing systems, 29:3844–3852, 2016.

Wenze Ding, Kenta Nakai, and Haipeng Gong. Protein design via deep learning. Briefings in bioinformatics, 23(3):bbac102, 2022.

Baldwin Dumortier, Antoine Liutkus, Clément Carré, and Gabriel Krouk. Petribert: Augmenting bert with tridimensional encoding for inverse protein folding and design. bioRxiv, 2022.

Nicholas J Fowler and Mike P Williamson. The accuracy of protein structures in solution determined by alphafold and nmr. Structure, 2022.

Fabian B Fuchs, Daniel E Worrall, Volker Fischer, and Max Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. arXiv preprint arXiv:2006.10503, 2020.

Wenhao Gao, Sai Pooja Mahajan, Jeremias Sulam, and Jeffrey J Gray. Deep learning in protein structural modeling and design. Patterns, 1(9):100142, 2020.

Zhangyang Gao, Cheng Tan, Lirong Wu, and Stan Z Li. Semiretro: Semi-template framework boosts deep retrosynthesis prediction. arXiv preprint arXiv:2202.08205, 2022.

Joe G Greener, Lewis Moffat, and David T Jones. Design of metalloproteins and novel protein folds using variational autoencoders. Scientific reports, 8(1):1–12, 2018.

Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. bioRxiv, 2022.

Bin Huang, Tingwe Fan, Kaiyue Wang, Haicang Zhang, Chungong Yu, Shuyu Nie, Yangshuo Qi, Wei-Mou Zheng, Jian Han, Zheng Fan, et al. Accurate and efficient protein sequence design through learning concise local environment of residues. bioRxiv, 2022.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 4700–4708, 2017.

Yi-Xin Huo, Kwang Myung Cho, Jimmy G Lafontaine Rivera, Emma Monte, Claire R Shen, Yajun Yan, and James C Liao. Conversion of proteins into biofuels by engineering nitrogen flux. Nature biotechnology, 29(4):346–351, 2011.

John Ingraham, Vikas K Garg, Regina Barzilay, and Tommi Jaakkola. Generative models for graph-based protein design. 2019.

Bowen Jing, Stephan Eismann, Patricia Suriana, Raphael JL Townshend, and Ron Dror. Learning from protein structure with geometric vector perceptrons. arXiv preprint arXiv:2009.01411, 2020.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. Nature, 596(7873):583–589, 2021.

Mostafa Karimi, Shaowen Zhu, Yue Cao, and Yang Shen. De novo protein design for novel folds using guided conditional wasserstein generative adversarial networks. Journal of chemical information and modeling, 60(12):5667–5681, 2020.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. arXiv preprint arXiv:1609.02907, 2016.

Alex J Li, Mindren Lu, Israel Tilahun Desta, Vikram Sundar, Gevorg Grigoryan, and Amy E Keating. Neural network-derived potts models for structure-based protein design using backbone atomic coordinates and tertiary motifs. bioRxiv, 2022a.

Alex J Li, Vikram Sundar, Gevorg Grigoryan, and Amy E Keating. Terminator: A neural framework for structure-based protein design using tertiary repeating motifs. arXiv preprint arXiv:2204.13048, 2022b.

Jie Li and Patrice Koehl. 3d representations of amino acids—applications to protein sequence comparison and classification. Computational and structural biotechnology journal, 11(18):47–58, 2014.

Zhixiu Li, Yuedong Yang, Eshel Faraggi, Jian Zhan, and Yaoqi Zhou. Direct prediction of profiles of sequences compatible with a protein structure by neural networks with fragment-based local and energy-based nonlocal profiles. Proteins: Structure, Function, and Bioinformatics, 82(10): 2565–2573, 2014.

Ziyao Li, Xuyang Liu, Weijie Chen, Fan Shen, Hangrui Bi, Guolin Ke, and Linfeng Zhang. Uni-fold: An open-source platform for developing protein folding models beyond alphafold. bioRxiv, 2022c.

Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Sal Candido, et al. Language models of protein sequences at the scale of evolution enable accurate structure prediction. bioRxiv, 2022.

Yufeng Liu, Lu Zhang, Weilun Wang, Min Zhu, Chenchen Wang, Fudong Li, Jiahai Zhang, Houqiang Li, Quan Chen, and Haiyan Liu. Rotamer-free protein sequence design based on deep learning and self-consistency. 2022.

Yvette A Luyten, Deanna E Hausman, Juliana C Young, Lindsey A Doyle, Kerilyn M Higashi, Natalia C Ubilla-Rodriguez, Abigail R Lambert, Corina S Arroyo, Kevin J Forsberg, Richard D Morgan, et al. Identification and characterization of the wyl brxr protein and its gene as separable regulatory elements of a brex phage restriction system. Nucleic acids research, 50(9):5171–5190, 2022.

Jack B Maguire, Daniele Grattarola, Vikram Khipple Mulligan, Eugene Klyshko, and Hans Melo. Xenet: Using a new graph convolution to accelerate the timeline for protein design on quantum computers. PLoS computational biology, 17(9):e1009037, 2021.

Matt McPartlon, Ben Lai, and Jinbo Xu. A deep se (3)-equivariant model for learning inverse protein folding. bioRxiv, 2022.

Milot Mirdita, Konstantin Schütze, Yoshitaka Moriwaki, Lim Heo, Sergey Ovchinnikov, and Martin Steinegger. Colabfold: making protein folding accessible to all. Nature Methods, pp. 1–4, 2022.

Francesca E Morreale, Stefan Kleine, Julia Leodolter, Sabryna Junker, David M Hoi, Stepan Ovchinnikov, Anastasia Okun, Juliane Kley, Robert Kurzbauer, Lukas Junk, et al. Bacprotacs mediate targeted protein degradation in bacteria. Cell, 2022.

James O'Connell, Zhixiu Li, Jack Hanson, Rhys Heffernan, James Lyons, Kuldip Paliwal, Abdollah Dehzangi, Yuedong Yang, and Yaoqi Zhou. Spin2: Predicting sequence profiles from protein structures using deep neural networks. Proteins: Structure, Function, and Bioinformatics, 86(6): 629–633, 2018.

Sergey Ovchinnikov and Po-Ssu Huang. Structure-based protein design with deep learning. Current opinion in chemical biology, 65:136–144, 2021.

Carl Pabo. Molecular technology: designing proteins and peptides. Nature, 301(5897):200–200, 1983.

Robin Pearce and Yang Zhang. Deep learning techniques have significantly impacted protein structure prediction and protein design. Current opinion in structural biology, 68:194–207, 2021.

William R Pearson and Michael L Sierk. The limits of protein sequence comparison? Current opinion in structural biology, 15(3):254–260, 2005.

Joana Pereira, Adam J Simpkin, Marcus D Hartmann, Daniel J Rigden, Ronan M Keegan, and Andrei N Lupas. High-accuracy protein structure prediction in casp14. Proteins: Structure, Function, and Bioinformatics, 89(12):1687–1699, 2021.

Yifei Qi and John ZH Zhang. Densecpd: improving the accuracy of neural-network-based computational protein sequence design with densenet. Journal of chemical information and modeling, 60 (3):1245–1252, 2020.

Victor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E (n) equivariant graph neural networks. arXiv preprint arXiv:2102.09844, 2021.

Nadine M Shaban, Rui Yan, Ke Shi, Sofia N Moraes, Adam Z Cheng, Michael A Carpenter, Jason S McLellan, Zhiheng Yu, and Reuben S Harris. Cryo-em structure of the ebv ribonucleotide reductase borf2 and mechanism of apobec3b inhibition. Science advances, 8(17):eabm2827, 2022.

Muhammed Shuaibi, Adeesh Kolluru, Abhishek Das, Aditya Grover, Anuroop Sriram, Zachary Ulissi, and C Lawrence Zitnick. Rotation invariant graph neural networks using spin convolutions. arXiv preprint arXiv:2106.09575, 2021.

Martin Steinegger and Johannes Söding. Mmseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. Nature biotechnology, 35(11):1026–1028, 2017.

Alexey Strokach and Philip M Kim. Deep generative modeling for protein design. Current opinion in structural biology, 72:226–236, 2022.

Alexey Strokach, David Becerra, Carles Corbi-Verge, Albert Perez-Riba, and Philip M Kim. Fast and flexible protein design using deep graph neural networks. Cell Systems, 11(4):402–411, 2020.

Cheng Tan, Zhangyang Gao, Jun Xia, and Stan Z Li. Generative de novo protein design with global context. arXiv preprint arXiv:2204.10673, 2022.

Mihaly Varadi, Stephen Anyango, Mandar Deshpande, Sreenath Nair, Cindy Natassia, Galabina Yordanova, David Yuan, Oana Stroe, Gemma Wood, Agata Laydon, et al. Alphafold protein structure database: Massively expanding the structural coverage of protein-sequence space with high-accuracy models. Nucleic acids research, 2021.

Mihaly Varadi, Stephen Anyango, Mandar Deshpande, Sreenath Nair, Cindy Natassia, Galabina Yordanova, David Yuan, Oana Stroe, Gemma Wood, Agata Laydon, et al. Alphafold protein structure database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. Nucleic acids research, 50(D1):D439–D444, 2022.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. arXiv preprint arXiv:1710.10903, 2017.

Jingxue Wang, Huali Cao, John ZH Zhang, and Yifei Qi. Computational protein design with deep learning neural networks. Scientific reports, 8(1):1–9, 2018.

Stephen A Williams, Mika Kivimaki, Claudia Langenberg, Aroon D Hingorani, JP Casas, Claude Bouchard, Christian Jonasson, Mark A Sarzynski, Martin J Shipley, Leigh Alexander, et al. Plasma protein patterns as comprehensive indicators of health. Nature medicine, 25(12):1851–1857, 2019.

Ruidong Wu, Fan Ding, Rui Wang, Rui Shen, Xiwen Zhang, Shitong Luo, Chenpeng Su, Zuofan Wu, Qi Xie, Bonnie Berger, et al. High-resolution de novo structure prediction from primary sequence. BioRxiv, 2022.

Zachary Wu, Kadina E Johnston, Frances H Arnold, and Kevin K Yang. Protein sequence design with deep generative models. Current opinion in chemical biology, 65:18–27, 2021.

Yuan Zhang, Yang Chen, Chenran Wang, Chun-Chao Lo, Xiuwen Liu, Wei Wu, and Jinfeng Zhang. Prodconn: Protein design using a convolutional neural network. Proteins: Structure, Function, and Bioinformatics, 88(7):819–829, 2020a.

Ziwei Zhang, Peng Cui, and Wenwu Zhu. Deep learning on graphs: A survey. IEEE Transactions on Knowledge and Data Engineering, 2020b.

Zuobai Zhang, Minghao Xu, Arian Jamasb, Vijil Chenthamarakshan, Aurelie Lozano, Payel Das, and Jian Tang. Protein representation learning by geometric structure pretraining. arXiv preprint arXiv:2203.06125, 2022.

Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. AI Open, 1:57–81, 2020.

A APPENDIX

ID	Name	Structures	≤ 30	$(30, 500)$	$[500, 1000]$	> 1000
1	DANRE	24,664	27	15,460	6,573	2,604
2	CANAL	5,974	0	3,656	1,874	444
3	MOUSE	21,615	55	13,767	5,668	2,125
4	ECOLI	4,363	63	3,719	526	55
5	DROME	13,458	28	8,509	3,563	1,358
6	METJA	1,773	0	1,605	144	24
7	PLAF7	5,187	1	2,832	1,313	1,041
8	MYCTU	3,988	4	3,365	536	83
9	CAEEL	19,694	52	15,073	3,592	977
10	DICDI	12,622	3	7,663	3,367	1,589
11	TRYCC	19,036	6	12,622	5,007	1,401
12	YEAST	6,040	24	3,789	1,715	512
13	SCHPO	5,128	5	3,385	1,386	352
14	RAT	21,272	12	13,884	5,370	2,006
15	HUMAN	23,391	49	12,399	5,653	5,290
16	ARATH	27,434	42	19,885	6,389	1,118
17	MAIZE	39,299	83	29,145	8,360	1,711
18	LEIIN	7,924	0	4,276	2,505	1,143
19	STAA8	2,888	22	2,567	267	32
20	SOYBN	55,799	17	41,048	12,353	2,381
21	ORYSJ	43,649	78	35,987	6,738	846
	Sum	365,198	571	254,636	82,899	27,092

Table 6: AlphaFold DB: we show the total number of proteins N_{all}, and the number of proteins whose length within $(0, 30]$, $(30, 500]$, $(500, 1000]$ and $(1000, +\infty]$. The statistics of all proteomic data are also presented.