IMBEDDING DEEP NEURAL NETWORKS

ABSTRACT

Continuous depth neural networks, such as Neural ODEs, have refashioned the understanding of residual neural networks in terms of non-linear vector-valued optimal control problems. The common solution is to use the adjoint sensitivity method to replicate a forward-backward pass optimisation problem. We propose a new approach which explicates the network's 'depth' as a fundamental variable, thus reducing the problem to a system of forward-facing initial value problems. This new method is based on the principal of 'Invariant Imbedding' for which we prove a general solution, applicable to all non-linear, vector-valued optimal control problems with both running and terminal loss. Our new architectures provide a tangible tool for inspecting the theoretical–and to a great extent unexplained– properties of network depth. They also constitute a resource of discrete implementations of Neural ODEs comparable to classes of imbedded residual neural networks. Through a series of experiments, we show the competitive performance of the proposed architectures for supervised learning and time series prediction.

1 UNPACKING DEEP NEURAL NETWORKS

The long-standing enigma surrounding machine learning still remains paramount today: What is it that machines are learning and how may we extract meaningful knowledge from trained algorithms? Deep Neural Networks (DNNs), whilst undeniably successful, are notorious black-box secret keepers. To solve a supervised learning process, mapping vector inputs $\mathbf{x}$ to their targets $\mathbf{y}$, parameters are stored and updated in ever deepening layers with no facility to access the physical significance of the internal function approximating $\mathbf{x} \mapsto \mathbf{y}$.

We propose a new class of DNNs obtained by *imbedding* multiple networks of varying depth whilst keeping the inputs, $\mathbf{x}$, *invariant*; we call these 'Invariant Imbedding Networks' (InImNets). To illustrate the concept, Figure 1 depicts a system of projectiles fired from a range of positions $p_1 < p_2 < \cdots < p_n$ with the same initial velocity conditions $\mathbf{x}$. The red curve (initiated at p_1) is fit to a sample (circles) along a single trajectory, representing a traditional regression problem. InImNet architectures are trained on the output values $\mathbf{y} = \mathbf{y}(p_i, \mathbf{x})$ at p_n (the diamonds) as the depth p_i of the system varies. As we consider experimentally, an InImNet can learn internal system dynamics for which only external observations are possible. This analogy applies to DNN classifiers where increasing the depth from p_i to p_{i-1} outputs a classification decision for each i-step.

Figure 1: Plotted are heights $h(t; p, \mathbf{x})$ vs. lengths t of projectile curves initiated with identical initial velocities $\mathbf{x}$ at a range of points p_i along the t-axis. The red curve depicts a regression fit to a t-varying sample set; contrast with the blue InImNet training paradigm which learns the endpoints (diamonds) from varying the input position p_i.

In machine learning applications, the use of deep hidden layers, whilst sucessful, was first considered *ad hoc* in typical discrete implementations, such as a multilayer perceptrons. But following the advent of residual neural networks (He et al., 2015) which use 'Euler-step' internal updates between layers, DNN evolution is seen to emulate a continuous dynamical system (Lu et al., 2018; Ruthotto

& Haber, 2020). Thus was formed the notion of a 'Neural ODE' (Chen et al., 2018) in which the hidden network state vector $\mathbf{z}(t)$, instead of being defined at fixed layers $t \in \mathbb{N}$, is allowed to vary continuously over an interval $[p, q] \subset \mathbb{R}$. Its evolution is governed by an Ordinary Differential Equation (ODE)

$$\dot{\mathbf{z}}(t) = \mathbf{f}(t, \mathbf{z}(t), \boldsymbol{\theta}(t)); \quad \mathbf{z}(p) = \mathbf{x} \tag{1}$$

where the training function $\mathbf{f}$ is controlled by a parameter vector $\boldsymbol{\theta}(t)$ for $t \in [p, q]$. Network outputs are retrieved at $\mathbf{z}(q) = \mathbf{y}$ after fixing the endpoint $t = q$. As such, the enigmatic 'depth' of a Neural ODE is controlled by varying $t = p$, at which point we insert the initial condition $\mathbf{z}(p) = \mathbf{x}$. This dynamical description has given the theory of DNNs a new home, in the mathematical framework of optimal control (Massaroli et al., 2020; Bensoussan et al., 2020). However, the initial condition $\mathbf{z}(p) = \mathbf{x}$ remains an implicit constraint and a clear understanding of network depth remains illusive.

Our new class of InImNet architectures which may be obtained by *imbedding* networks of varying depth p whilst keeping the inputs, $\mathbf{x}$, *invariant*. Explicating these two variables throughout the network, writing $\mathbf{z}(t) = \mathbf{z}(t; p, \mathbf{x})$, has exciting conceptual consequences:

1. **Forward pass to construct the network**: InImNet state vectors $\mathbf{z}(t; p, \mathbf{x})$ are computed with respect to the depth variable p rather than $t \in [p, q]$, which is considered fixed (in practice at $t = q$). We build from the bottom up: initiate at $p = q$ with the trivial network $\mathbf{z}(q; q, \mathbf{x}) = \mathbf{x}$ and unwind the p-varying dynamics, as described in Theorem 1, by integrating

   $$\nabla_p \mathbf{z}(q; p, \mathbf{x}) = -\nabla_{\mathbf{x}} \mathbf{z}(q; p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p)) \tag{2}$$

   from $p = q$ to a greater depth p. Note that at depth p an InImNet returns a *external* output $\mathbf{z}(q; p, \mathbf{x}) \sim \mathbf{y}$, subject to training. This contrasts with convention, where one would obtain $\mathbf{z}(q; p, \mathbf{x})$ by integrating from $t = p$ to $t = q$, where $t < q$ states are considered *internal*. A general algorithm to implement the forward pass is described in Algorithm 1. The gradient operator ∇ denotes the usual vector, or Jacobian, of partial derivatives.

2. **Backpropagate independently from the forward pass**: We generalise the adjoint method of Chen et al. (2018), who was able to do away with backpropagation-by-chain rule method in favour of a continuous approach with at most bounded memory demand. With our bottom-up formulation, we are able to go one step further and do away with the initial forward pass altogether by initiating our 'imbedded' adjoint $\boldsymbol{\Lambda}(p, \mathbf{x})$ with loss gradients for the trivial network $\mathbf{z}(q; q, \mathbf{x}) = \mathbf{x}$ and computing to depth p via

   $$\nabla_p \boldsymbol{\Lambda}(p, \mathbf{x}) = -[\nabla_{\mathbf{x}} \boldsymbol{\Lambda}(p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p)) + \nabla_{\mathbf{x}} \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p))^{\mathrm{T}} \cdot \boldsymbol{\Lambda}(p, \mathbf{x})]. \tag{3}$$

   See Theorem 2 for a precise, more general explication. Backward passes may be made independently of forward passing altogether; see Theorem 2 and Algorithm 1.

3. **Pre-imposed optimality**: Working in the framework of optimal control theory, we consider both running and terminal losses–a general 'Bolza problem'–see §2.1. We give a necessary first-order criterion for optimal control (Theorem 3). In this way, we account for t-varying parameter controls $\boldsymbol{\theta}(t) = \boldsymbol{\theta}(t; p, \mathbf{x})$, omitted from the original Neural ODEs, permitting future compatibility with the recent particle-shooting models of Vialard et al. (2020).

We describe various InImNet architectures, based on the above results, in §3 to analyse regression and classification problems using both discrete and continuous designs.

Our contribution We prove that it is possible to reduce the non-linear, vector-valued optimal control problem to a system of forward-facing initial value problems. We introduce a new theoretical leap for the understanding of depth in neural networks, in particular with respect to viewing DNNs as dynamical systems (Chen et al., 2018; Massaroli et al., 2020; Vialard et al., 2020). We demonstrate that this approach may be used in creating discrete and continuous numerical DNN schemes. We verify such algorithms by successfully applying our method to benchmark experiments, which perform well on a range of complex tasks (high-dimensional rotating MNIST and bouncing balls) in comparison to state-of-the-art techniques.

Experimental performance In §4 we present some promising results for their practical functionality. These are designed to support the theoretical development of InImNets in §2 & 3 and support the proof of concept in application. We derive various successful discrete implementations,

Figure 2: **Top**: A Neural ODE constitutes a two-point boundary value problem over $t \in [p, q]$. **Bottom**: An InImNet separates the forward and backward passes into separate initial value problems along the depth variable p.

based on computing the state evolutions (2) and (3) with an Euler-step method. We also identify operational aspects in InImNets which we expect to encourage ongoing research and development. Crucially, our architectures are compatible with the various technical advancements since made to Neural ODEs, including those by Dupont et al. (2019); Davis et al. (2020); Yıldız et al. (2019); see also a study of effective ODE solvers for the continuous models (Hopkins & Furber, 2015).

Broader impact for optimal control theory Further afield, our result applies more generally as a new tool in the theory of optimal control. The mathematical technique that we apply to (1), deriving (2) and (3), is known as the Invariant Imbedding Method. The key output of the method is the reformulation of a two-point boundary value problem as a system of initial value problems, given as functions of initial value $\mathbf{x}$ and input location p alone (Meyer, 1973). This stands in the literature as an alternative to applying the calculus of variations (Liberzon, 2012; Vialard et al., 2020). For linear systems, the technique was first developed by Ambarzumian (1943) to study deep stellar atmospheres. It has since found widespread applications in engineering (Bellman & Wing, 1975), optical oceanography (Mobley, 1994), PDEs (Maynard & Scott, 1971), ODEs (Agarwal & Saraf, 1979) and control theory (Bellman et al., 1966; Kalaba & Sridhar, 1969), to name a few. The non-linear case is only touched on in the literature for scalar systems of zero terminal loss (Bellman et al., 1966; Kalaba & Sridhar, 1969)–including some numerical computations to support its efficiency (Spingarn, 1972). In this work we derive a complete invariant imbedding solution, fit for applications such as those mentioned above, for a non-linear, vector-valued Bolza problem.

Overview of the paper In §2 we give the main theorems used for InImNet architectures and more widely in the field of optimal control. Detailed derivations may be found in the appendix. In §3 we put forward various architectures to illustrate how InImnets may be utilised in learning paradigms. In §4 we describe our supporting experimental work for such architectures.

2 THE INVARIANT IMBEDDING SOLUTION

Solutions to (1) depend *implicitly* on both an input datum $\mathbf{x}$ and the input position p at which the input is cast. The $(p, \mathbf{x})$ relationship is at the heart of the invariant imbedding method which *explicates* these arguments, written into the notation as $\mathbf{z}(t) = \mathbf{z}(t; p, \mathbf{x})$. The fundamental principle is to observe the imbedding of intervals $[p + \Delta, q] \subset [p, q]$, for $0 \leq \Delta \leq p - q$, which carry solutions $\mathbf{z}(t; p + \Delta, \mathbf{x})$ to (1), whilst keeping the input, $\mathbf{x}$, to each invariant. In limiting terms as $\Delta \to 0$, the partial rate of change in depth $\nabla_p = \partial/\partial p$ is directly related to the vector gradient $\nabla_\mathbf{x}$ for the initial value $\mathbf{x}$ at p. This is controlled by the coefficient

$$\mathbf{\Phi}(p, \mathbf{x}) := \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p)). \tag{4}$$

Theorem 1. *Let $p \leq t \leq q$ and suppose $\mathbf{z}(t; p, \mathbf{x})$ and $\boldsymbol{\theta}(t; p, \mathbf{x})$ satisfies (1). Then we have the invariant imbedding relation*

$$\nabla_p \mathbf{z}(t; p, \mathbf{x}) = -\nabla_\mathbf{x} \mathbf{z}(t; p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}). \tag{5}$$

We use this result, (5) in particular, as a model to address the following learning problem. Consider a collection of input values $\mathbf{x} \in \mathbb{R}^N$ corresponding to known output values $\mathbf{y} \in \mathbb{R}^N$. We seek to extend an approximation of $\mathbf{x} \mapsto \mathbf{y}$ to larger subsets of $\mathbb{R}^N$. We proceed by choosing an interval $[p, q] \subset \mathbb{R}$ of arbitrary depth (fixing q and varying p) and postulate a state vector $\mathbf{z}(t; p, \mathbf{x})$, subject to (1), that approximates $\mathbf{y}$ at $t = q$ given the input $\mathbf{z}(p; p, \mathbf{x}) = \mathbf{x}$.

The parameter control, whilst commonly restricted in applications, is *a priori* subject to the same dependencies $\boldsymbol{\theta}(t) = \boldsymbol{\theta}(t; p, \mathbf{x})$. We denote a second coefficient related to its endpoint by

$$\mathbf{\Psi}(p, \mathbf{x}) := \boldsymbol{\theta}(p; p, \mathbf{x}) \tag{6}$$

which, for $p \le t \le q$, also satisfies the invariant imbedding relation in Theorem 1:

$$\nabla_p \boldsymbol{\theta}(t; p, \mathbf{x}) = -\nabla_\mathbf{x} \boldsymbol{\theta}(t; p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}). \tag{7}$$

2.1 THE BOLZA OPTIMISATION PROBLEM

Our optimal control problem, a Bolza problem, is subject to two forms of loss: a *terminal loss*, the discrepancy between the system outputs $\mathbf{z}(q)$ and the true outputs $\mathbf{y}$ measured by a loss function $\mathcal{T}$ on $\mathbb{R}^N$; and a *running loss*, which regulates both the state vector $\mathbf{z}(t)$ itself as it evolves over $t \in [p, q]$ but also the control $\boldsymbol{\theta}(t)$ over $[p, q]$ by a square-integrable functional $\mathcal{R}$ on $[p, q] \times \mathbb{R}^N \times \mathbb{R}^M$. Together, the minimisation problem is to find a control $\boldsymbol{\theta}(t)$ and solution $\mathbf{z}(t)$ to (1) whilst minimising the total loss

$$\mathcal{J}(\boldsymbol{\theta}; p, \mathbf{x}) := \int_p^q \mathcal{R}(t, \mathbf{z}(t; p, \mathbf{x}), \boldsymbol{\theta}(t; p, \mathbf{x}))dt + \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})). \tag{8}$$

for each known datum pair $(\mathbf{x}, \mathbf{y})$. Applying the calculus of variations, one considers small perturbations about an optimal control $\boldsymbol{\theta}$ which minimise $\mathcal{J}(\boldsymbol{\theta}; p, \mathbf{x})$ whilst determining a solution $\mathbf{z}$ to (1). The well known first-order Euler–Lagrange optimality equations (see §D.3) thus derived constitute a constrained, two-point boundary value problem as depicted in Figure 2. By contrast, the invariant imbedding method restructures the first-order optimal system as an initial value problem. The t-dependence is brushed implicitly under the rug, with numerical integration performed instead on the depth variable p.

2.2 BACKWARD LOSS PROPAGATION

The calculus of variations, introduced by Euler and Lagrange (Euler, 1766), provides a mechanism by which to find an *optimal control $\boldsymbol{\theta}$* (see Liberzon, 2012, Ch. 2). They key trick is to invoke a function called the Lagrange multiplier $\boldsymbol{\lambda}(t) = \boldsymbol{\lambda}(t; p, \mathbf{x})$, also known as the "adjoint state" (Chen et al., 2018) or "Hamiltonian momentum" (Vialard et al., 2020), which encodes the backward-propagated losses. This information is obtained by evaluating $\boldsymbol{\lambda}$ at $t = p$, to which end we introduce a third invariant imbedding coefficient

$$\mathbf{\Lambda}(p, \mathbf{x}) = \boldsymbol{\lambda}(p; p, \mathbf{x}) \tag{9}$$

to which we apply our main backward result.

Theorem 2. *For all $p \le q$ we have the initial value problem*

$$-\nabla_p \mathbf{\Lambda}(p, \mathbf{x}) = \nabla_\mathbf{x} \mathbf{\Lambda}(p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}) + \nabla_\mathbf{z}\mathbf{f}(p, \mathbf{x}, \mathbf{\Psi}(p, \mathbf{x}))^\mathrm{T} \cdot \mathbf{\Lambda}(p, \mathbf{x}) + \nabla_\mathbf{z}\mathcal{R}(p, \mathbf{x}, \mathbf{\Psi}(p, \mathbf{x})) \tag{10}$$

initiated at $p = q$ via $\mathbf{\Lambda}(q, \mathbf{x}) = \nabla_\mathbf{z}\mathcal{T}(\mathbf{x})$.

We contrast our approach of fixed $t = q$ and varying depth p versus the adjoint method of Chen et al. (2018), who fix p and vary $p \le t \le q$. Our derivation provides a new proof of the standard Euler–Lagrange equations which give the adjoint method, manifesting in our account as

$$\boldsymbol{\lambda}(p; p, \mathbf{x}) = \nabla_\mathbf{z}\mathcal{T}(\mathbf{z}(q; p, \mathbf{x})) - \int_q^p [\nabla_\mathbf{z}\mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^\mathrm{T} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_\mathbf{z}\mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta})]dt \tag{11}$$

with initial value $\boldsymbol{\lambda}(q; p, \mathbf{x}) = \nabla_\mathbf{z}\mathcal{T}(\mathbf{z}(q; p, \mathbf{x}))$ at $t = p$. Observe that in Theorem 2 the initial loss at $p = q$ is given by $\nabla_\mathbf{z}\mathcal{T}(\mathbf{z}(q; q, \mathbf{x}) = \mathbf{x})$, for the trivial network. Back-integrating this term thus does not require a forward pass of the $\mathbf{z}$-state at the cost of computing the derivatives with respect to $\nabla_\mathbf{x}\mathbf{\Lambda}(p, \mathbf{x})$. Optimising this latter process opens a new window of efficient DNNs.

2.3 A FIRST ORDER OPTIMALITY CONDITION

With the insights gleaned from optimal control theory, Vialard et al. (2020) take a different approach facilitating t-varying parameter controls $\boldsymbol{\theta}(t; p, \mathbf{x})$. This is based on assuming that $\boldsymbol{\theta}$ is optimal from the outset. This is achieved through specifying $\boldsymbol{\theta}$ by the t-varying constraint

$$\nabla_{\boldsymbol{\theta}}\mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}) + \nabla_{\boldsymbol{\theta}}\mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) = 0. \tag{12}$$

We obtain a corresponding condition for the coefficients that constitute an InImNet.

Theorem 3. *For all $p \leq q$ we have the optimality condition*

$$\nabla_{\boldsymbol{\theta}}\mathcal{R}(p, \mathbf{x}, \boldsymbol{\Psi}(p, \mathbf{x})) + \nabla_{\boldsymbol{\theta}}\mathbf{f}(p, \mathbf{x}, \boldsymbol{\Psi}(p, \mathbf{x}))^{\mathrm{T}} \cdot \boldsymbol{\Lambda}(p, \mathbf{x}) = 0. \tag{13}$$

Making the $(p, \mathbf{x})$-dependency explicit for optimal controls, this identity provides a mechanism by which the depth p itself is accessible optimise. In practice, $\boldsymbol{\Psi}(p, \mathbf{x})$, and hence $\boldsymbol{\Phi}(p, \mathbf{x})$, are derived from $\boldsymbol{\Lambda}(p, \mathbf{x})$, connected by Theorem 3 above. Together, Equations (5), (7), (10) and (13) constitute the invariant imbedding solution to the general Bolza problem as advertised.

3 INIMNET ARCHITECTURES

The architectures presented here are based upon the results of Theorems 1, 2 & 3. Whilst the processes for obtaining obtaining the p-th network state $\mathbf{z}(q; p, \mathbf{x})$ and backward adjoint $\boldsymbol{\Lambda}(p, \mathbf{x})$ are independent processes, we nevertheless describe their general form together in Algorithm 1.

Algorithm 1 Independent forward and backward pass with InImNet

---
Require: Training set of input/output pairs $(\mathbf{x}, \mathbf{y})$; evaluation points $p_1 < \cdots < p_n$; loss function $\mathcal{T}$ (see §2.1); training function $\mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})$.
Ensure: Track $\mathbf{x}$-operations for auto-differentiation, or substitute a numerical derivative (see §3.2).
    Inputs: $\mathbf{z}(q; p_i, \mathbf{x}) = \mathbf{x}$; $\boldsymbol{\Lambda}(q, \mathbf{x}) = \nabla_{\mathbf{x}}\mathcal{T}(\mathbf{x})$
    for $i = n - 1, \dots, 1$ **do**
        $\mathbf{z}(q; p_i, \mathbf{x}) = \mathbf{z}(q; p_{i+1}, \mathbf{x}) + \int_{p_{i+1}}^{p_i} \nabla_p \mathbf{z}(q; p, \mathbf{x})$ ▷ Use Theorem 1.
        $\boldsymbol{\Lambda}(p_i, \mathbf{x}) = \boldsymbol{\Lambda}(p_{i+1}, \mathbf{x}) + \int_{p_{i+1}}^{p_i} \nabla_p \boldsymbol{\Lambda}(p, \mathbf{x})$ ▷ Use Theorem 2.
    end for
    Returns: Tuple of outputs $\mathbf{z}(q; p_i, \mathbf{x})$ corresponding to networks of varying depths p_i.

In the remainder of this section we describe various discrete models to implement variants of Algorithm 1. Continuous architectures using black-box auto-differentiable ODE solvers, such as those considered by Chen et al. (2018), may be readily implemented. This approach poses interesting new avenues of research based on implementing accurate numerical alternatives to the computation of nested Jacobians. Simultaneously, the question of stability of DNN dynamics functions becomes another crucial question to answer.

For our experiments we seek to show a first-principal implementation of InImNets, and we do so by describing a discrete architecture, executing the minimum computation time whilst demonstrating high; see §3.1.

Finally, time-series data, or running losses, are not considered by Algorithm 1 but may be solved by InImNet, their dynamical structure a natural formulation for InImNets. We discuss this architecture in §3.3 and consider its application to a simple regression problem in §4.1.

3.1 DISCRETE EXPERIMENTAL ARCHITECTURE

We approximate the proposed architecture of Algorithm 1 by implementing a forward-Euler solution to the integrals in Algorithm 1. This is comparable to the original ResNet architectures (He et al., 2015). To do this we divide up the interval into a collection of layers $[p, q] = \cup_{i=1}^{n-1}[p_i, p_{i+1}]$ and rewrite the invariant imbedding equation of Theorem 1 as

$$\mathbf{z}(t; p_i, \mathbf{x}) = \mathbf{z}(t; p_{i+1}, \mathbf{x}) - (p_i - p_{i+1})\nabla_{\mathbf{x}}\mathbf{z}(t; p_{i+1}, \mathbf{x}) \cdot \boldsymbol{\Phi}(p_i, \mathbf{x}), \tag{14}$$

subject to $\mathbf{z}(p_n; p_n, \mathbf{x}) = \mathbf{x}$. Backpropagation may then be executed by either differentiating through the system, as is the standard approach, or by implementing Theorem 2 through the forward-Euler formula

$$\begin{aligned}
\mathbf{\Lambda}(p_i, \mathbf{x}) = \mathbf{\Lambda}(p_{i+1}, \mathbf{x}) \\
- (p_i - p_{i+1})[\nabla_\mathbf{x}\mathbf{\Lambda}(p_i, \mathbf{x}) \cdot \mathbf{\Phi}(p_i, \mathbf{x})) + \nabla_\mathbf{x}\mathbf{f}(p_i, \mathbf{x}, \boldsymbol{\theta}(p_i))^\mathrm{T} \cdot \mathbf{\Lambda}(p_{i+1}, \mathbf{x})].
\end{aligned} \quad (15)$$

with the initial condition $\mathbf{\Lambda}(p_n, \mathbf{x}) = \nabla_\mathbf{x}\mathcal{T}(\mathbf{x})$. To tackle computing the successive Jacobians $\nabla_\mathbf{x}\mathbf{z}(t, p, \mathbf{x})$, cf. 3.2, and incurring a high memory cost storing gradient graphs, we approximate this term by cropping the higher order gradients:

$$\nabla_\mathbf{x}\mathbf{z}(t; p_i, \mathbf{x}) = \nabla_\mathbf{x}\mathbf{z}(t; p_{i+1}, \mathbf{x}) - \nabla_\mathbf{x}\nabla_\mathbf{x}\mathbf{z}(t; p_{i+1}, \mathbf{x}) \cdot \mathbf{\Phi}(p_i, \mathbf{x}) \quad (16)$$

$$\approx \nabla_\mathbf{x}\mathbf{z}(t; p_{i+1}, \mathbf{x}) - \nabla_\mathbf{x}\mathbf{\Phi}(p_i, \mathbf{x}) \quad (17)$$

Whilst theoretically losses are easily quantifiable, we show experimentally that for this approximation an increasing the number of layers still improves the performance of the model.

3.2 Numerical approximation of input gradients

An implicit computational speed bump is the computation of the gradients $\nabla_\mathbf{x}$ in (2), (5) and (10). The immediate 'do nothing' solution is to track the gradient graphs of these terms with respect to $\mathbf{x}$ and implement automatic differentiation. Indeed, this approach does yield successful models–if one has time on their hands. Unfortunately, this approach incurs a high memory cost for deep or high dimensional networks.

We offer an alternative numerical solution. For sake of example, suppose we wish to compute $\mathbf{z}(q; p, \mathbf{x}) \in \mathbb{R}^N$ by integrating

$$\nabla_p\mathbf{z}(q; p, \mathbf{x}) = -\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}) \quad (18)$$

with respect to p. To compute the derivatives $\nabla_\mathbf{x}$ we consider perturbations of the input vector $\mathbf{x} \in \mathbb{R}^N$ of the form $\mathbf{x} \pm \Delta_i\mathbf{e}_i$ for appropriately small $\Delta_i > 0$ and $\mathbf{e}_i := (\delta_{ij})_{1 \leq j \leq N}$ for $i = 1, \ldots, N$. We then solve for the $2N + 1$ states $\mathbf{z}(q; p, \mathbf{x} \pm \Delta_i\mathbf{e}_i)$ by simultaneously integrating (18) alongside

$$\nabla_p\mathbf{z}(q; p, \mathbf{x} \pm \Delta_i\mathbf{e}_i) = -\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x} \pm \Delta_i\mathbf{e}_i) \cdot \mathbf{\Phi}(p, \mathbf{x} \pm \Delta_i\mathbf{e}_i) \quad (19)$$

where the gradients $\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x}_0)$ are modelled by

$$\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x}_0) \approx \left[\frac{\mathbf{z}(q; p, \mathbf{x}_0 + \Delta_i\mathbf{e}_i) - \mathbf{z}(q; p, \mathbf{x}_0 - \Delta_i\mathbf{e}_i)}{2\Delta_i} \right]_i \quad (20)$$

for $\mathbf{x}_0 = \mathbf{x}, \mathbf{x} \pm \Delta_i\mathbf{e}_i$, respectively. This form of numerical differentiation is known as the symmetric difference quotient. Other routines are available and should be adjusted for bespoke problems. For example, Newton's difference quotient uses a similar construction but the negative shifts are forgotten. This results in tracking $N + 1$ equations along (18) and (19) where we estimate

$$\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x}) \approx \left[\frac{\mathbf{z}(q; p, \mathbf{x} + \Delta_i\mathbf{e}_i) - \mathbf{z}(q; p, \mathbf{x})}{\Delta_i} \right]_i \quad (21)$$

and

$$\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x} + \Delta_i\mathbf{e}_i) \approx -\nabla_\mathbf{x}\mathbf{z}(q; p, \mathbf{x}). \quad (22)$$

3.3 Learning latent dynamics from end-point observations

Typical regression problems ask for a model function $\mathbf{z}(t)$ to approximate a t-varying process $\mathbf{y}(t)$ sampled a finite number of training points $\mathbf{y}(t_i)$ in a fixed region of interest $t_i \in [p, q]$. Assuming that $\mathbf{y}$ satisfies a well behaved ODE, the learning paradigm of a Neural ODE $\dot{\mathbf{z}} = \mathbf{f}$, see (1), is well suited to learn such continuous dynamics. Inherently, the initial condition $\mathbf{y}(p) = \mathbf{x}$ is assumed fixed.

InImNets are naturally structured to learn a variant of this problem: consider a t-varying process modelled by the dynamical system

$$\dot{\mathbf{y}}(t; p, \mathbf{x}) = \mathbf{g}(t, \mathbf{y}); \quad \mathbf{y}(p; p, \mathbf{x}) = \mathbf{x} \quad (23)$$

for which we are able to vary the location $p \leq q$ of an invariant initial condition $\mathbf{y}(p) = \mathbf{x}$. Suppose the sampled data is only available at the fixed output $t = q$ of the process, meaning the training data a set of the form

$$\{y_i := y(q; p_i, \mathbf{x}) | p_i \leq q\}_i. \tag{24}$$

In this way, an InImNet learns the dynamical system itself, as the initial conditions vary, from the outputs alone. Apply this to the running loss in Theorem 2 by defining

$$\mathcal{R}(t, z, \boldsymbol{\theta}) = \mathcal{R}(p, \mathbf{x}) = \sum_i C(z(t; p, \mathbf{x}), \mathbf{y}_i) \delta_{t,q} \delta_{p,p_i} \tag{25}$$

for a differentiable cost function $C \colon \mathbb{R}^N \times \mathbb{R}^N \to \mathbb{R}$. The term δ_{p,p_i} features intrinsically in Neural ODE architectures as only a single depth p is considered in a given system. We implement (25) recursively (cf. Chen et al., 2018, Figure 2) so that the discrete architecture for the adjoint reads

$$\boldsymbol{\Lambda}(p_i, \mathbf{x}) = \boldsymbol{\Lambda}(p_{i+1}, \mathbf{x}) + \nabla_{\mathbf{x}} \mathcal{R}(q; p_i, \mathbf{x})$$
$$- (p_i - p_{i+1})[\nabla_{\mathbf{x}} \boldsymbol{\Lambda}(p_i, \mathbf{x}) \cdot \boldsymbol{\Phi}(p_i, \mathbf{x})) + \nabla_{\mathbf{x}} \mathbf{f}(p_i, \mathbf{x}, \boldsymbol{\theta}(p_i))^{\mathrm{T}} \cdot \boldsymbol{\Lambda}(p_{i+1}, \mathbf{x})]. \tag{26}$$

The forward pass is executed exactly as in §3.1.

4 EXPERIMENTAL RESULTS

In this section we demonstrate the practical ability of the proposed architectures in solving benchmark problems for continuous neural networks.

4.1 PROJECTILE MOTION TIME-SERIES REGRESSION

As depicted in Figure 1, we train InImNet to learn a system of projectile curves. We execute this via the discrete running cost training paradigm in §3.3. The system considered is parameterised by $\mathbf{z} = [h, v]$, denoting vertical height and velocity, and with the t-axis proportional to horizontal position. The system ODE is of the form $\mathbf{f}(t, \mathbf{z}) = [v, -g]$ where g, gravity, is a scalar constant. We implement this in a Google Colab notebook.

4.2 ROTATING MNIST

We replicate the experimental setting from Yıldız et al. (2019) and Vialard et al. (2020), and compare with it the proposed discrete model as described in §3.1.

In this experiment, we solve the task of learning to generate a digit '3' for a sequence of 16 equally spaced rotation angles between $[0, 2\pi]$ given only the first example of the sequence. To match the experimental setting with Yıldız et al. (2019) and Vialard et al. (2020), we train the model by maximising the objective of mean squared error for all angles, except from one fixed angle (5th frame) as well as three random angles for each sample. We report the mean squared error (MSE) at the 5th frame and the standard deviation over ten different random initialisations.

The results of this experiment are given in Table 1. The details of the experimental set-up and the hyperparameters applied are given in Appendix E. The results show comparable performance to the best performing method Vialard et al. (2020) while using more computationally efficient discrete invariant imbedding formulation (see section 4.3). We approximate the InImNet dynamics function $\boldsymbol{\Phi}$ (as in Theorem 1) by a Multilayer Perceptron (MLP) with either 2 or 3 layers.

4.3 BOUNCING BALLS

As in the previous section, we replicate the experimental setting from Yıldız et al. (2019) and Vialard et al. (2020); we use the discrete method architecture in §3.1, whose hyperparameters are listed in Appendix E.2.

We see that the mean squared error of the proposed InImNet and the state-of-the-art methods are comparable while using a more computationally efficient model. We measured the time per epoch using public configuration of Google Colab for the (best-performing) up-down method of Vialard

GT

Layer 0

Layer 1

Layer 2

Layer 3

Layer 4

Figure 3: Rotating MNIST: samples from the model, $p_{\max} = 4$; 2 layer MLP

Figure 4: Bouncing balls: reported MSE for the proposed InImNet and state-of-the-art methods, results from other methods are taken from Yıldız et al. (2019) and Vialard et al. (2020)

GT

Layer 0

Layer 1

Layer 2

Layer 3

Figure 5: Bouncing balls: samples from the model, $p_{\max} = 3$; 3 layer MLP

Existing Models		InImNet	
Method	MSE $\pm \sigma$	InImNet parameters	MSE $\pm \sigma$
GPPVAE-DIS	0.0309 ± 0.00002	$p_{\max} = 1$; 2-layer MLP	0.0156 ± 0.0008
GPPVAE-JOINT	0.0288 ± 0.00005	$p_{\max} = 2$; 2-layer MLP	0.0130 ± 0.0005
ODE^{2}VAE	0.0194 ± 0.00006	$p_{\max} = 3$; 2-layer MLP	0.0126 ± 0.0007
ODE^{2}VAE-KL	0.0184 ± 0.0003	$p_{\max} = 4$; 2-layer MLP	0.0125 ± 0.0004
Vialard et al. (2020)	0.0122 ± 0.0064	$p_{\max} = 1$; 3-layer MLP	0.0176 ± 0.0010
		$p_{\max} = 2$; 3-layer MLP	0.0129 ± 0.0008
		$p_{\max} = 3$; 3-layer MLP	0.0125 ± 0.0003
		$p_{\max} = 4$; 3-layer MLP	0.0126 ± 0.0004

Table 1: Rotating MNIST: Reported MSE for the proposed InImNet and state-of-the-art methods, results from other methods are taken from Yıldız et al. (2019) and Vialard et al. (2020)
.

et al. (2020) against InImNet (with $p_{\max} = 3$; 3 layer MLP). We set the batch size to the same value of 25 as given in the configuration of the official implementation of Vialard et al. (2020). While the proposed InImNet requires 153 seconds per epoch, the method as described by Vialard et al. (2020) took 516 seconds to finish one epoch.

5 DISCUSSION AND CONCLUSIONS

We have shown that it is possible to reduce the non-linear, vector-valued optimal control problem to a system of forward-facing initial value problems. We have demonstrated that this approach may be used in creating discrete and continuous numerical schemes. In our experiments, we show that (1) for a range of complex tasks (high-dimensional rotating MNIST and bouncing balls), the discrete model exhibits promising results, competitive with the current state-of-the-art methods while being more computationally efficient; and (2) the continuous model, via the Euler method, shows promising results. Despite solving simple tasks, they show the possibility of inference in the continuous neural network by varying initial conditions of the model via 'Invariant Imbedding' instead of the well-known forward-backward pass optimisation.

We have outlined a class of DNNs which provide a new conceptual leap within the understanding of DNNs as dynamical systems. In particular, the explication of the depth variable leads to a new handle for the assessment of stacking multiple layers in DNNs. This also fits within the framework of Explainable AI, whereby an InImNet model is able to depict a valid output at every model layer.

Of course, nothing comes for free. The expense we incur is the presence of nested Jacobian terms; for example, $\nabla_{\mathbf{x}} \mathbf{z}(t; p, \mathbf{x})$. We show experimentally that our models perform well with elementary approximations for the purpose of functionality. But understanding these terms truly is deeply related to the stability of Neural ODEs over a training cycle.

In this article we do not explore the ramifications of the optimality condition of Theorem 3. With the work of (Vialard et al., 2020), in which systems are considered optimal from the outset via Theorem 3, we propose to study the variability of depth of such optimal systems.

REFERENCES

A. Agarwal and S. Saraf. Invariant embedding: A new method of solving a system of nonlinear boundary-value differential equations. *J. Math. Anal. Appl.*, 72(2):524 – 532, 1979. ISSN 0022-247X. doi: 10.1016/0022-247X(79)90245-2. URL https://doi.org/10.1016/0022-247X(79)90245-2.

V. Ambarzumian. Diffuse reflection of light by a foggy medium. *C. R. (Doklady) Acad. Sci. URSS (N.S.)*, 38:229–232, 1943.

R. Bellman and G. Wing. *An Introduction to Invariant Imbedding*, volume 8. Society for Industrial and Applied Mathematics (SIAM), 1975. ISBN 0-89871-304-8. doi: 10.1137/1.9781611971279. URL https://doi.org/10.1137/1.9781611971279.

R. Bellman, H. Kagiwada, R. Kalaba, and R. Sridhar. Invariant Imbedding and Nonlinar Filtering Theory. *J. Astronaut. Sci.*, 13:110–115, 1966. ISSN 0021-9142.

A. Bensoussan, Y. Li, D. P. C. Nguyen, M.-B. Tran, S. C. P. Yam, and X. Zhou. Machine Learning and Control Theory. *arXiv preprint*, 2020. URL `http://arxiv.org/abs/2006.05604`.

T. Q. Chen, Y. Rubanova, J. Bettencourt, and D. Duvenaud. Neural Ordinary Differential Equations. *Advances in Neural Information Processing Systems 31*, pp. 6571–6583, 2018. URL `http://papers.nips.cc/paper/7892-neural-ordinary-differential-equations`.

J. Davis, K. Choromanski, J. Varley, H. Lee, J.-J. Slotine, V. Likhosherstov, A. Weller, A. Makadia, and V. Sindhwani. Time Dependence in Non-Autonomous Neural ODEs. *arXiv preprint*, 2020. URL `http://arxiv.org/abs/2005.01906`.

E. Dupont, A. Doucet, and Y. W. Teh. Augmented Neural ODEs. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 3140–3150. Curran Associates, Inc., 2019. URL `http://papers.nips.cc/paper/8577-augmented-neural-odes.pdf`.

L. Euler. Elementa Calculi Variationum. *Novi Comment. Acad. Sci. Imp. Petropol.*, 10:51–93, 1766. URL `https://scholarlycommons.pacific.edu/euler-works/296/`.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2015.

M. Hopkins and S. Furber. Accuracy and Efficiency in Fixed-Point Neural ODE Solvers. *Neural Comput.*, 27(10):2148–2182, 2015. doi: 10.1162/NECO_a_00772. URL `https://doi.org/10.1162/NECO_a_00772`.

R. Kalaba and R. Sridhar. Invariant Imbedding and Optimal Control Theory. *J. Optim. Theory Appl.*, 4:343–351, 1969. ISSN 0022-3239. doi: 10.1007/BF00927676. URL `https://doi.org/10.1007/BF00927676`.

D. Liberzon. *Calculus of Variations and Optimal Control Theory: A Concise Introduction*. Princeton University Press, 2012. ISBN 9780691151878.

Y. Lu, A. Zhong, Q. Li, and B. Dong. Beyond Finite Layer Neural Networks: Bridging Deep Architectures and Numerical Differential Equations. In J. Dy and A. Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 3276–3285. PMLR, 10–15 Jul 2018. URL `http://proceedings.mlr.press/v80/lu18d.html`.

S. Massaroli, M. Poli, J. Park, A. Yamashita, and H. Asama. Dissecting Neural ODEs. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, pp. 3952–3963. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/293835c2cc75b585649498ee74b395f5-Paper.pdf`.

C. Maynard and M. Scott. Invariant imbedding of linear partial differential equations via generalized Riccati transformations. *J. Math. Anal. Appl.*, 36(2):432 – 459, 1971. ISSN 0022-247X. doi: 10.1016/0022-247X(71)90011-4. URL `https://doi.org/10.1016/0022-247X(71)90011-4`.

G. Meyer. *Initial Value Methods for Boundary Value Problems: Theory and Application of Invariant Imbedding*, volume 100 of *Mathematics in Science and Engineering*. Elsevier, 1973. doi: 10.1016/S0076-5392(08)62980-X. URL `https://doi.org/10.1016/S0076-5392(08)62980-X`.

C. Mobley. *Light and Water*. Academic Press, 1994. URL `http://www.oceanopticsbook.info/view/introduction/overview`.

L. Ruthotto and E. Haber. Deep Neural Networks Motivated by Partial Differential Equations. *J. Math. Imaging Vis*, 62:352—-364, 2020. doi: 10.1007/s10851-019-00903-1. URL `https://doi.org/10.1007/s10851-019-00903-1`.

K. Spingarn. Some numerical results using kalaba's new approach to optimal control and filtering. *IEEE Trans. Automat. Contr.*, 17(5):713–715, 1972. ISSN 0018-9286. doi: 10.1109/TAC.1972.1100124. URL `https://doi.org/10.1109/TAC.1972.1100124`.

F.-X. Vialard, R. Kwitt, S. Wei, and M. Niethammer. A Shooting Formulation of Deep Learning. *Advances in Neural Information Processing Systems*, 33, 2020.

Ç. Yıldız, M. Heinonen, and H. Lähdesmäki. ODE^{2}VAE: Deep generative second order ODEs with Bayesian neural networks. *Advances in Neural Information Processing Systems*, 32:13412–13421, 2019. URL `https://arxiv.org/pdf/1905.10994`.

A   GENERAL NOTATION AND CONVENTIONS

We consider all $\mathbb{R}$-vectors as column vectors, to be denoted in bold font. Let $\langle \mathbf{v}, \mathbf{w} \rangle$ denote the Euclidean product between two vectors $\mathbf{v}$ and $\mathbf{w}$. Matrix multiplication between $\mathbf{A}$ and $\mathbf{B}$ shall be denoted $\mathbf{A} \cdot \mathbf{B}$ and transposition by $\mathbf{A}^T$. For $\mathbf{v} = (v_i)_i$ introduce the gradient operator by the row vector $\nabla_{\mathbf{v}} = (\partial / \partial v_i)_i$ which operates on scalar fields as usual but also on vector fields $\mathbf{F}(\mathbf{v}) = (F_i(\mathbf{v}))_i$ to give the Jacobian matrix $\nabla_{\mathbf{v}} \mathbf{F} = (\partial F_i / \partial v_j)_{i,j}$. Then, if $\mathbf{v} = \mathbf{v}(\mathbf{w})$, the chain rule reads $\nabla_{\mathbf{w}} \mathbf{F}(\mathbf{v}(\mathbf{w})) = \nabla_{\mathbf{v}} \mathbf{F} \cdot \nabla_{\mathbf{w}} \mathbf{v}$, which could be expressed as $\partial \phi / \partial w = \langle \nabla_{\mathbf{v}} \phi, \partial \mathbf{v} / \partial w \rangle$ if $\mathbf{F} = \phi$ and $\mathbf{w} = w$ were both scalar valued. Moreover we extend the gradient notation by using it for scalars $p \in \mathbb{R}$ to denote the single partial derivative $\nabla_p = \partial / \partial p$. Define the second order gradient operator by the matrix of second order partial derivatives $\nabla_{\mathbf{v},\mathbf{w}}^2 := \nabla_{\mathbf{w}} \nabla_{\mathbf{v}} = (\partial^2 / \partial v_i \partial w_j)_{i,j}$ with respect to $\mathbf{v} = (v_i)_i$ and $\mathbf{w} = (w_i)_i$. We use the Dirac delta symbol given by $\delta_{ij} = 1$ if and only if $i = j$ and $\delta_{ij} = 0$ otherwise. The $N \times N$ identity matrix is then given by $\mathbf{1}_N := (\delta_{ij})_{1 \leq i,j \leq N}$. Lastly, for a (possibly vector valued) function $\mathbf{F}$ on $\mathbb{R}$ we write $\mathbf{F}(x) = o(x)$, implicitly with respect to $x \to 0$, to denote that $\lim_{x \to 0} \mathbf{F}(x)/x = 0$.

B   AUGMENTED STATE VARIABLES FOR CONSTANT PARAMETERS

Updates to t-varying parameter controls $\boldsymbol{\theta}(t; p, \mathbf{x})$ are a hot subject of research; see (Vialard et al., 2020; Massaroli et al., 2020) and the references. The original Neural ODEs (Chen et al., 2018) operated by assuming that $\boldsymbol{\theta} = \boldsymbol{\theta}(t; p, \mathbf{x}) \in \mathbb{R}^M$ was a constant. It was then possible to recover loss gradients for the components of $\boldsymbol{\theta}$ by augmenting the system and running the adjoint method (Chen et al., 2018, §B.2). A similar trick works in our context, with some quite remarkable consequences.

Consider an augmented state vector composed of $\mathbf{z}$, t and θ, whereby the dynamics in (1) becomes

$$\frac{d}{dt} \begin{bmatrix} \mathbf{z} \\ t \\ \boldsymbol{\theta} \end{bmatrix} = \begin{bmatrix} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) \\ 1 \\ \mathbf{0} \end{bmatrix} \tag{27}$$

with $\mathbf{z}(p) = \mathbf{x}$, $t = p$ and $\boldsymbol{\theta} = \boldsymbol{\theta}$ as the initial condition. Working through the invariant imbedding procedure, the forward process (Theorem 1) for $\mathbf{z}$ is preserved. But the backward process (Theorem 2) is revised by replacing $\boldsymbol{\Lambda}$ with the (new) components $\boldsymbol{\Lambda}^{(\mathbf{z})}$, $\boldsymbol{\Lambda}^{(t)}$ and $\boldsymbol{\Lambda}^{(\boldsymbol{\theta})}$. The first, $\boldsymbol{\Lambda}^{(\mathbf{z})}$, satisfies Theorem 2 independently of $\boldsymbol{\Lambda}^{(t)}$ and $\boldsymbol{\Lambda}^{(\boldsymbol{\theta})}$. Moreover, the assumption that $\boldsymbol{\theta} = \boldsymbol{\theta}(t)$ is constant in t implies that $\nabla_{\mathbf{z}} \mathbf{f}(p, \mathbf{x}, \boldsymbol{\Psi}(p, \mathbf{x})) = \nabla_{\mathbf{x}} \boldsymbol{\Phi}(p, \mathbf{x})$ so we deduce the new backward equation

$$\nabla_p \boldsymbol{\Lambda}^{(\mathbf{z})}(p, \mathbf{x}) = -[\nabla_{\mathbf{x}} \boldsymbol{\Lambda}^{(\mathbf{z})}(p, \mathbf{x}) \cdot \boldsymbol{\Phi}(p, \mathbf{x}) + \nabla_{\mathbf{x}} \boldsymbol{\Phi}(p, \mathbf{x})^{\mathrm{T}} \cdot \boldsymbol{\Lambda}^{(\mathbf{z})}(p, \mathbf{x}) + \nabla_{\mathbf{z}} \mathcal{R}(p, \mathbf{x}, \boldsymbol{\Psi}(p, \mathbf{x}))]. \tag{28}$$

The term $\boldsymbol{\Lambda}^{(\boldsymbol{\theta})}(p, \mathbf{x})$, corresponding to the gradient of the terminal loss with respect to the constant parameters $\boldsymbol{\theta}$, assumes the initial value

$$\boldsymbol{\Lambda}^{(\boldsymbol{\theta})}(q, \mathbf{x}) = \mathbf{0} \tag{29}$$

for whom the p-evolution (10) becomes

$$\nabla_p \boldsymbol{\Lambda}^{(\boldsymbol{\theta})}(p, \mathbf{x}) = -[\nabla_{\mathbf{x}} \boldsymbol{\Lambda}^{(\boldsymbol{\theta})}(p, \mathbf{x}) \cdot \boldsymbol{\Phi}(p, \mathbf{x}) + \boldsymbol{\Phi}_{\boldsymbol{\theta}}(p, \mathbf{x})^{\mathrm{T}} \cdot \boldsymbol{\Lambda}^{(\mathbf{z})}(p, \mathbf{x}) + \nabla_{\boldsymbol{\theta}} \mathcal{R}(p, \mathbf{x}, \boldsymbol{\Psi}(p, \mathbf{x}))], \tag{30}$$

dependant on the simultaneous solution of $\mathbf{\Lambda}^{(\mathbf{z})}(p, \mathbf{x})$.

For the t-term let us additionally assume that $\mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) = \mathbf{f}(\mathbf{z}, \boldsymbol{\theta})$ and $\mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}) = \mathcal{R}(\mathbf{z}, \boldsymbol{\theta})$. This implies that $\nabla_t \mathbf{f}(p, \mathbf{x}, \mathbf{\Psi}(p, \mathbf{x})) = \nabla_\mathbf{x} \mathbf{\Phi}(p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x})$. Then $\mathbf{\Lambda}^{(t)}(p, \mathbf{x})$, the gradient of the terminal loss with respect to $t = p$, assumes the initial value

$$\mathbf{\Lambda}^{(t)}(q, \mathbf{x}) = \langle \mathbf{\Lambda}^{(\mathbf{z})}(q, \mathbf{x}), \mathbf{\Phi}(q, \mathbf{x}) \rangle \tag{31}$$

and the p-evolution follows

$$\nabla_p \mathbf{\Lambda}^{(t)}(p, \mathbf{x}) = -[\nabla_\mathbf{x} \mathbf{\Lambda}^{(t)}(p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}) + (\nabla_\mathbf{x} \mathbf{\Phi}(p, \mathbf{x}) \cdot \mathbf{\Phi}(p, \mathbf{x}))^{\mathrm{T}} \cdot \mathbf{\Lambda}^{(\mathbf{z})}(p, \mathbf{x}) \\ + \nabla_\mathbf{x} \mathcal{R}(p, \mathbf{x}, \mathbf{\Psi}(p, \mathbf{x})) \cdot \mathbf{\Phi}(p, \mathbf{x})], \tag{32}$$

dependant on the simultaneous solution of $\mathbf{\Lambda}^{(\mathbf{z})}(p, \mathbf{x})$. This last identity is particularly exciting. It enables one to compute the loss with respect to p, the depth, itself. Given the explication of this p-variable in our Invariant Imbedding Networks, one may thus plot this loss as a function of p and isolate the minima for any given training run. Observing the flow of such minima provides great insight to the optimal depth that a network should take.

C   THE IMBEDDING RULE

InImNet architectures are based on the principle of invariant imbedding: the description of a system of a given length in terms of its imbedded sister systems. For example, consider two lengths $p_2 < p_1 < q$ such that the solution $\mathbf{z}(t; p_1, \mathbf{x})$ to (1) is known for $t \geq p_1$. The solution $\mathbf{z}(t; p_2, \mathbf{x})$ over $[p_2, q]$ restricted to $t \geq p_1$, with $\mathbf{x}$ input at p_2, may be expressed using (5) by

$$\mathbf{z}(t; p_2, \mathbf{x}) = \mathbf{z}(t; p_1, \mathbf{x}) - \int_{p_1}^{p_2} \nabla_\mathbf{x} \mathbf{z}(t; p, y) \mathbf{\Phi}(p, \mathbf{x}) dp. \tag{33}$$

In this way, two separate intervals may be adjoined by observing the imbedding rule

$$\mathbf{z}(t; p_2, \mathbf{x}) = \mathbf{z}(t; p_1, \mathbf{z}(p_1; p_2, \mathbf{x})) \tag{34}$$

where the new input $\mathbf{z}(p_1; p_2, \mathbf{x})$ is evaluated using (33) at $t = p_1$. In the case that $\mathbf{f}$ is a linear function of $\mathbf{z}$, the identity in (33) is sometimes known as the Ricatti transformation Bellman & Wing (1975). In practical computations, one should devises models, such as step-linearisation, to solve (33) by simulating the gradients $\nabla_\mathbf{x} \mathbf{z}(p_1; p, \mathbf{x})$ for $p < p_2$.

D   DERIVING THE INVARIANT IMBEDDING SOLUTION

Here we give a proof of Theorems 1, 2 and 3 which constitute an invariant imbedding solution for a non-linear, vector-valued Bolza problem. Consider the minimisation problem described in §2.1 for the ODE system (1).

D.1   VARIATIONS IN THE CONTROL

We consider the consequences of the calculus of variations (Liberzon, 2012, Ch. 2). This provides a mechanism by which to find an *optimal control* $\boldsymbol{\theta}$; that is, $\boldsymbol{\theta}$ provides a global minimum so that $\mathcal{J}(\boldsymbol{\theta}) \leq \mathcal{J}(\tilde{\boldsymbol{\theta}})$ for all piecewise continuous controls $\tilde{\boldsymbol{\theta}}$. For $\varepsilon \in \mathbb{R}$ considered close to 0, we consider controls perturbed from the optimal control $\boldsymbol{\theta}$ by

$$\boldsymbol{\theta}(t; p, \mathbf{x}) + \varepsilon \boldsymbol{\nu}(t; p, \mathbf{x}) \tag{35}$$

for an admissible perturbation $\boldsymbol{\nu}$. Following the system (1), the control in (35) determines the state (or trajectory)

$$\mathbf{z}(t; p, \mathbf{x}) + \varepsilon \boldsymbol{\eta}(t; p, \mathbf{x}) + o(\varepsilon) \tag{36}$$

where $\boldsymbol{\eta}$ is a corresponding perturbation subject to

$$\boldsymbol{\eta}(p; p, \mathbf{x}) = 0 \tag{37}$$

so that (36) agrees with $\mathbf{z}$ at $t = p$. To minimise the cost, we consider the Taylor expansion of $\mathcal{J}(\boldsymbol{\theta} + \varepsilon\boldsymbol{\nu})$ with respect to ε. We call the linear term *the first variation* of $\mathcal{J}$ at $\boldsymbol{\theta}$ which may be defined by the Gateaux derivative:

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) := \lim_{\varepsilon \to 0} \frac{\mathcal{J}(\boldsymbol{\theta} + \varepsilon\boldsymbol{\nu}) - \mathcal{J}(\boldsymbol{\theta})}{\varepsilon} \tag{38}$$

for admissible perturbations $\boldsymbol{\nu}$. For the cost function given in (8), the first variation is equal to

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) = \int_p^q \langle \nabla_{\boldsymbol{\theta}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}), \boldsymbol{\nu}(t; p, \mathbf{x}) \rangle dt + \int_p^q \langle \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}), \boldsymbol{\eta}(t; p, \mathbf{x}) \rangle dt$$
$$+ \langle \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})), \boldsymbol{\eta}(q; p, \mathbf{x}) \rangle. \tag{39}$$

The first-order, necessary condition for optimality (Liberzon, 2012, §1.3.2) is satisfied whenever

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) = 0. \tag{40}$$

An auxiliary identity for the manipulation of (39) is obtained by evaluating $\dot{\boldsymbol{\eta}}$. Differentiating (36) with respect to ε about $\varepsilon = 0$, both directly and via (1), implies that

$$\dot{\boldsymbol{\eta}}(t; p, \mathbf{x}) = \nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) \cdot \boldsymbol{\eta}(t; p, \mathbf{x}) + \nabla_{\boldsymbol{\theta}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) \cdot \boldsymbol{\nu}(t; p, \mathbf{x}). \tag{41}$$

D.2 LAGRANGE MULTIPLIERS

Introduce $\boldsymbol{\lambda}(t) \in \mathbb{R}^N$, an arbitrary vector-valued function for $t \in [p, q]$ to be specified forthwith. This is the *Lagrange multiplier*, called so as its namesake used it to multiply Equation (41) and insert it into the first variation (39). We subsequently obtain

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) = \int_p^q \langle \nabla_{\boldsymbol{\theta}} \mathcal{R}(\boldsymbol{\theta}(t; p, \mathbf{x})) + \nabla_{\boldsymbol{\theta}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t), \boldsymbol{\nu}(t; p, \mathbf{x}) \rangle dt$$
$$+ \int_p^q \langle \boldsymbol{\lambda}(t), \nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) \cdot \boldsymbol{\eta}(t; p, \mathbf{x}) - \dot{\boldsymbol{\eta}}(t; p, \mathbf{x}) \rangle dt$$
$$+ \int_p^q \langle \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}), \boldsymbol{\eta}(t; p, \mathbf{x}) \rangle dt + \langle \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})), \boldsymbol{\eta}(q; p, \mathbf{x}) \rangle. \tag{42}$$

We obtain an optimality condition by making a choice of $\boldsymbol{\lambda}(t) = \boldsymbol{\lambda}(t; p, \mathbf{x})$ such that

$$\nabla_{\boldsymbol{\theta}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}) + \nabla_{\boldsymbol{\theta}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) = 0 \tag{43}$$

for all $t \in [q, p]$; cf. (Vialard et al., 2020, (3.3)) where their "$\mathbf{p}_i$" is equal to our $-\boldsymbol{\lambda}$. The first variation (39) simplifies accordingly:

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) = \int_p^q \langle \boldsymbol{\lambda}(t; p, \mathbf{x}), \nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta}) \cdot \boldsymbol{\eta}(t; p, \mathbf{x}) - \dot{\boldsymbol{\eta}}(t; p, \mathbf{x}) \rangle dt$$
$$+ \int_p^q \langle \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}), \boldsymbol{\eta}(t; p, \mathbf{x}) \rangle dt + \langle \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})), \boldsymbol{\eta}(q; p, \mathbf{x}) \rangle. \tag{44}$$

At this point our method of invariant imbedding diverges from the classical method of Euler and Lagrange. We give a brief aside here to review the Euler–Lagrange equations as the comparison is illuminating; see §D.3. We also direct the reader to (Liberzon, 2012, §3.3-3.4) in which the classical route is explored.

D.3 THE EULER–LAGRANGE EQUATIONS

The Euler–Lagrange equations reveal how the adjoint method of Chen et al. (2018), see also (Vialard et al., 2020, §3.3), will correspond to our invariant imbedding formulation. The derivation follows from integrating (44) by parts with respect to $\dot{\boldsymbol{\eta}}$. One derives

$$\delta\mathcal{J}|_{\boldsymbol{\theta}}(\boldsymbol{\nu}) = \int_p^q \langle \nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}) + \dot{\boldsymbol{\lambda}}(t; p, \mathbf{x}), \boldsymbol{\eta}(t; p, \mathbf{x}) \rangle dt$$
$$+ \langle \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})) - \boldsymbol{\lambda}(q; p, \mathbf{x}), \boldsymbol{\eta}(q; p, \mathbf{x}) \rangle. \tag{45}$$

noting that the initial value of the perturbation is $\boldsymbol{\eta}(p; p, \mathbf{x}) = 0$ by assumption. We simplify the constant term by imposing the initial condition on $\boldsymbol{\lambda}$:

$$\boldsymbol{\lambda}(q; p, \mathbf{x}) = \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})). \tag{46}$$

Since (45) equates to 0 by the first order optimality condition (40) for all admissible perturbations $\boldsymbol{\eta}$, the fundamental lemma of the calculus of variations implies

$$\dot{\boldsymbol{\lambda}}(t; p, \mathbf{x}) = -[\nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta})]. \tag{47}$$

Equations (46) and (47) constitute the continuous analogy to backpropagation known as the "adjoint method" by Chen et al. (2018). Its formulation is thus encoded in (44) and so the forthcoming method of invariant imbedding provides a direct alternative to this backpropagation approach.

D.4 THE INVARIANT IMBEDDING METHOD

For each $0 \leq \Delta \leq q - p$ consider the family of subintervals $[p + \Delta, q]$ of $[p, q]$. Over these intervals, we imbed the systems $\mathbf{z}(t; p + \Delta, \mathbf{x})$ into $\mathbf{z}(t; p, \mathbf{x})$ whilst keeping $\mathbf{x}$, the input, invariant. This results in the partial differential equations (51) and (52) in which changes in p are equated to changes with respect to $\mathbf{x}$.

To derive these equations, we first note that over each interval the systems follow (1), which may be expressed as a finite difference equation:

$$\mathbf{z}(t; p, \mathbf{x}) = \mathbf{z}(t + \Delta; p, \mathbf{x}) - \mathbf{f}(t, \mathbf{z}(t; p, \mathbf{x}), \boldsymbol{\theta}(t; p, \mathbf{x}))\Delta + o(\Delta) \tag{48}$$

for $p \leq t \leq q - \Delta$. We then formally extend $\mathbf{z}(t; p + \Delta, \mathbf{x})$ to $t = p$ via (48) so that

$$\mathbf{z}(p; p + \Delta, \mathbf{x}) = \mathbf{x} - \mathbf{f}(p, \mathbf{z}(p; p + \Delta, \mathbf{x}), \boldsymbol{\theta}(p; p + \Delta, \mathbf{x}))\Delta + o(\Delta). \tag{49}$$

As such, the imbedding of systems over $[p + \Delta, q] \subset [p, q]$ is explicitly defined by

$$\mathbf{z}(t; p + \Delta, \mathbf{x}) = \mathbf{z}(t; p, \mathbf{x} - \mathbf{f}(p, \mathbf{z}(p; p + \Delta, \mathbf{x}), \boldsymbol{\theta}(p; p + \Delta, \mathbf{x}))\Delta + o(\Delta)) \tag{50}$$

for all $p \leq t \leq q$. To compute the partial derivative $\nabla_p \mathbf{z} = \partial \mathbf{z} / \partial p$, consider the difference $\mathbf{z}(t; p + \Delta, \mathbf{x}) - \mathbf{z}(t; p, \mathbf{x})$ in which $\mathbf{x}$ remains invariant. Substituting (50), dividing by Δ and taking the limit $\Delta \to 0^+$ one obtains *the invariant imbedding identity for the trajectory*:

$$\nabla_p \mathbf{z}(t; p, \mathbf{x}) = -\nabla_{\mathbf{x}} \mathbf{z}(t; p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x})). \tag{51}$$

Mutatis mutandis, one derives *the invariant imbedding identity for the control*:

$$\nabla_p \boldsymbol{\theta}(t; p, \mathbf{x}) = -\nabla_{\mathbf{x}} \boldsymbol{\theta}(t; p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x})). \tag{52}$$

These equations express a fundamental translational invariance property of both the optimal control and the corresponding trajectory. This proves the basic identity in Theorem 1.

D.5 INVARIANT IMBEDDING OF THE LAGRANGE MULTIPLIER

We extend the invariant imbedding relations (51) and (52) to the Lagrange multiplier $\boldsymbol{\lambda}(t; p, \mathbf{x})$. The extension is obtained by taking the gradient of (43) with respect to $\nabla_p = \partial / \partial p$ and $\nabla_{\mathbf{x}}$. Adding the resulting expressions together and using (51) and (52) to replace the terms $\nabla_p \mathbf{z}(t; p, \mathbf{x})$ and $\nabla_p \boldsymbol{\theta}(t; p, \mathbf{x})$ we derive the identity

$$\nabla_{\boldsymbol{\theta}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot (\nabla_p \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_{\mathbf{x}} \boldsymbol{\lambda}(t; p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x}))). \tag{53}$$

For non-trivial dependence of $\mathbf{f}$ on the control $\boldsymbol{\theta}$ we assume that $\nabla_{\boldsymbol{\theta}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})$ is not identically 0 implying *the invariant imbedding identity for the Lagrange multiplier, $\boldsymbol{\lambda}$*:

$$\nabla_p \boldsymbol{\lambda}(t; p, \mathbf{x}) = -\nabla_{\mathbf{x}} \boldsymbol{\lambda}(t; p, \mathbf{x}) \cdot \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x})). \tag{54}$$

These equations express a fundamental translational invariance property of both the optimal control and the corresponding trajectory.

The coefficients $\mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x}))$ and $\boldsymbol{\theta}(p; p, \mathbf{x})$ in (51) and (52) depend on the variables $(p, \mathbf{x})$ alone, independently of t. It is thus sensible to introduce the terminology

$$\boldsymbol{\Phi}(p, \mathbf{x}) := \mathbf{f}(p, \mathbf{x}, \boldsymbol{\theta}(p; p, \mathbf{x})) \in \mathbb{R}^N; \tag{55}$$

$$\boldsymbol{\Psi}(p, \mathbf{x}) := \boldsymbol{\theta}(p; p, \mathbf{x}) \in \mathbb{R}^M. \tag{56}$$

D.6   First order optimality with invariant imbedding

Here we derive an auxiliary optimality condition from the first variation (44) subject to the invariant imbedding relations (51), (52) and (54). Recall that (44) is equivalent to the adjoint-state equation of Chen et al. (2018), seen by application of the Euler–Lagrange equations; §D.3. The theory we develop here should thus also be seen as analogue to the standard backpropagation method.

The first variation (44) is equal to 0 by (40). One may take its gradient with respect to $\nabla_p = \partial/\partial p$ using Leibniz' rule and apply $\boldsymbol{\eta}(p; p, \mathbf{x}) = 0$; moreover, each occurrence of $\nabla_p \mathbf{z}$, $\nabla_p \boldsymbol{\theta}$ and $\nabla_p \boldsymbol{\lambda}$ may be substituted with their respective invariant imbedding relation. Then take the sum of the resulting equation with the gradient of (44) with respect to $\nabla_{\mathbf{x}}$ scaled by the term $\boldsymbol{\Phi}(p, \mathbf{x})$. One thus obtains the general form of the first-variation auxiliary equation:

$$\langle \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})), \nabla_p \boldsymbol{\eta}(q; p, \mathbf{x}) + \nabla_{\mathbf{x}} \boldsymbol{\eta}(q; p, \mathbf{x}) \cdot \boldsymbol{\Phi}(p, \mathbf{x}) \rangle + \langle \boldsymbol{\lambda}(p; p, \mathbf{x}), \dot{\boldsymbol{\eta}}(p; p, \mathbf{x}) \rangle$$

$$\int_p^q \langle \nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta}), \nabla_p \boldsymbol{\eta}(t; p, \mathbf{x}) + \nabla_{\mathbf{x}} \boldsymbol{\eta}(t; p, \mathbf{x}) \cdot \boldsymbol{\Phi}(p, \mathbf{x}) \rangle dt$$

$$+ \int_p^q \langle \boldsymbol{\lambda}(t; p, \mathbf{x}), \nabla_p \dot{\boldsymbol{\eta}}(t; p, \mathbf{x}) + \nabla_{\mathbf{x}} \dot{\boldsymbol{\eta}}(t; p, \mathbf{x}) \cdot \boldsymbol{\Phi}(p, \mathbf{x}) \rangle dt = 0. \quad (57)$$

The derivation of (57) requires the multiplication of higher order tensors. This is readily completed using Einstein's summation convention. Note that before specifying our choice of $\boldsymbol{\eta}$ there is no stipulation that it should adhere to an invariant imbedding rule of the form $\nabla_p \boldsymbol{\eta} = -\nabla_{\mathbf{x}} \boldsymbol{\eta} \cdot \boldsymbol{\Phi}$.

D.7   Specifying the variations to solve for the Lagrange multiplier

The auxiliary optimality condition (57) holds for all admissible perturbations $(\boldsymbol{\nu}, \boldsymbol{\eta})$. We now make specific choices to derive an initial condition for $\boldsymbol{\lambda}(t; p, \mathbf{x})$ at $t = p$. For $1 \leq j \leq N$ define the column vector

$$\boldsymbol{\eta}_j(t; p, \mathbf{x}) := ((t - p)\delta_{ij})_i. \quad (58)$$

This perturbation satisfies $\boldsymbol{\eta}_j(p; p, \mathbf{x}) = \mathbf{0}$, as required, and has derivatives given by $\dot{\boldsymbol{\eta}}_j = -\nabla_p \boldsymbol{\eta}_j = (\delta_{ij})_i$ and $\nabla_p \dot{\boldsymbol{\eta}}_j = \mathbf{0}$; whilst all gradients with respect to $\nabla_{\mathbf{x}}$ satisfy $\nabla_{\mathbf{x}} \boldsymbol{\eta}_j = \nabla_{\mathbf{x}} \dot{\boldsymbol{\eta}}_j = \mathbf{0}$. By substitution into (57) we show that

$$\boldsymbol{\lambda}(p; p, \mathbf{x}) = \nabla_{\mathbf{z}} \mathcal{T}(\mathbf{z}(q; p, \mathbf{x})) - \int_q^p [\nabla_{\mathbf{z}} \mathbf{f}(t, \mathbf{z}, \boldsymbol{\theta})^{\mathrm{T}} \cdot \boldsymbol{\lambda}(t; p, \mathbf{x}) + \nabla_{\mathbf{z}} \mathcal{R}(t, \mathbf{z}, \boldsymbol{\theta})] dt. \quad (59)$$

Note that by the fundamental theorem of calculus, the initial condition in (59) is equivalent to the adjoint equation of Chen et al. (2018).

The remaining results are then derived as follows. Theorem 2 follows directly from (59). Take the derivatives $\nabla_p \boldsymbol{\Lambda}(p, \mathbf{x})$ and $\nabla_{\mathbf{x}} \boldsymbol{\Lambda}(p, \mathbf{x})$ from the explicit formula in (59) and substitute the ∇_p terms with the invariant imbedding relations (51), (52) and (54). Letting $\nabla_{\mathbf{x}} \boldsymbol{\Lambda}(p, \mathbf{x})$ operate on $\boldsymbol{\Phi}(p, \mathbf{x})$ Theorem 2 follows by summing the two equations. The initial condition at $p = q$ follows immediately from (59). Similarly, Theorem 3 follows by specifying (40) at the endpoint $t = q$.

E   Hyperparameters of the models

E.1   Rotating MNIST

We reproduce the experimental setting from Vialard et al. (2020); the experiments have been conducted in Tensorflow 2.6.0. The autoencoder's architecture, reimplemented in Tensorflow from the official pytorch code of Vialard et al. (2020), and parameters, including the batch size, replicate the same experimental set-up. To enable the time series prediction, we append the time value to the latent representation of the autoencoder. The multilayer perceptron models use dropout regularisation for every layer except the last. The hyperparameters of the rotating MNIST model are listed in Table 2. All experiments have been run in a Google Colab GPU environment. Similar to Vialard et al. (2020), we denote as the inflation factor the size ratio between the intermediate and input MLP layers.

Hyperparameter	Value
Optimiser	Adam
Batch size	25
Initial earning rate	0.001
Epochs	500
Dropout value	0.3
Inflation factor	2
Dimension of latent space	20
Learning rate schedule	Exponential decay 0.5 every 30 epochs

Table 2: Hyperparameters for the rotating MNIST experiment

E.2 BOUNCING BALLS

The architecture of the autoencoder and experimental setting reimplements in Tensorflow 2.6.0 the one from the official code of Vialard et al. (2020), the rest of the considerations are identical to the ones given in E.1. As in the previous section, we concatenate the time parameter with the latent representation of the first three images in the autoencoder to obtain time series imbedding. The hyperparameters of the bouncing balls model are given in Table 3.

Hyperparameter	Value
Optimiser	Adam
Batch size	25
Initial earning rate	0.001
Epochs	100
Dropout value	0.3
Inflation factor	2
Dimension of latent space	50
Learning rate schedule	Exponential decay 0.5 every 30 epochs

Table 3: Hyperparameters for the Bouncing balls experiment