HERO: HUMAN-FEEDBACK-EFFICIENT REINFORCEMENT LEARNING FOR ONLINE DIFFUSION MODEL FINETUNING

Ayano Hiranaka[*1,3]   **Shang-Fu Chen**[*1,2]   **Chieh-Hsin Lai**[*1]
Dongjun Kim[4]   **Naoki Murata**[1]   **Takashi Shibuya**[1]   **Wei-Hsiang Liao**[1]
Shao-Hua Sun[†2]   **Yuki Mitsufuji**[†1]
[1]Sony AI, [2] Graduate Institute of Communication Engineering, National Taiwan University,
[3]University of Southern California, [4]Stanford University

ABSTRACT

Controllable generation through Stable Diffusion (SD) fine-tuning aims to improve fidelity, safety, and alignment with human guidance. Existing reinforcement learning from human feedback methods usually rely on predefined heuristic reward functions or pretrained reward models built on large-scale datasets, limiting their applicability to scenarios where collecting such data is costly or difficult. To effectively and efficiently utilize human feedback, we develop a framework, HERO, which leverages online human feedback collected on the fly during model learning. Specifically, HERO features two key mechanisms: (1) *Feedback-Aligned Representation Learning*, an online training method that captures human feedback and provides informative learning signals for fine-tuning, and (2) *Feedback-Guided Image Generation*, which involve generating images from SD's refined initialization samples, enabling faster convergence towards the evaluator's intent. We demonstrate that HERO is $4\times$ more efficient in online feedback for body part anomaly correction compared to the best existing method. Additionally, experiments show that HERO can effectively handle tasks like reasoning, counting, personalization, and reducing NSFW content with only 0.5K online feedback. The code and project page are available at `https://hero-dm.github.io/`.

1 INTRODUCTION

Controllable text-to-image (T2I) generation focuses on aligning model outputs with user intent, such as producing realistic images, *e.g.*, undistorted human bodies, or accurately reflecting the count, semantics, and attributes specified by users. To tackle this problem, a common paradigm involves fine-tuning latent diffusion models (DM) like Stable Diffusion (SD; Rombach et al., 2022) using supervised fine-tuning (SFT; Lee et al., 2023), which mostly learn from pre-collected, offline datasets. To further enhance the alignment, online reinforcement learning (RL) fine-tuning methods (Fan et al., 2024; Black et al., 2024) utilize online feedback that specifically evaluates the samples generated by the model during training. With such dynamic guidance provided on the fly, these methods demonstrate superior performance on various T2I tasks, such as aesthetic quality improvement. Yet, these approaches rely on either predefined heuristic reward functions or pretrained reward models learned from large-scale datasets, which could be challenging to obtain, especially for tasks involving personalized content generation (*e.g.*, capturing cultural nuances) or concepts like specific colors or compositions.

To address the above issue, Yang et al. (2024b) introduces D3PO, an alternative method that directly leverages online human feedback for fine-tuning diffusion models. Instead of learning from heuristic reward functions or pretrained reward models, D3PO leverages the samples generated by the

---

*Equal contributions. This work was done while Ayano Hiranaka and Shang-Fu Chen interned at Sony AI. Corresponding authors: Ayano Hiranaka <ahiranak@usc.edu>, Shang-Fu Chen <sam.sfchen@gmail.com>, and Chieh-Hsin Lai <chieh-hsin.lai@sony.com>.
†Equal advisory.

Figure 1: ⓪ **Online Human Feedback on Generated Images:** Each epoch, SD generates a batch of images, evaluated by a human as "good" or "bad", with the "best" among the "good" selected. The corresponding SD noises and latents are saved. ① **Feedback-Aligned Representation Learning:** Human-annotated images train an embedding map via contrastive learning, converting feedback into continuous representations. These are rated by cosine similarity to one of the "best" images and used to fine-tune SD via DDPO (Black et al., 2024). ② **Feedback-Guided Image Generation:** New images are generated from a Gaussian mixture centered around the recorded noises of "good" images. This process is repeated until the feedback budget is exhausted.

model as well as human annotations collected during training. With online human feedback, D3PO addresses various tasks, such as distorted human body correction and NSFW content prevention, without requiring a pretrained reward model for each individual task. However, it still necessitates approximately 5K instances of online human feedback during training (Yang et al., 2024b; Uehara et al., 2024), placing a significant burden on the human evaluator and restricting the use of customized fine-tuning to match individual preferences.

To further improve the feedback efficiency of T2I alignment using online human feedback, this work proposes a **H**uman-feedback **E**fficient **R**einforcement learning for **O**nline diffusion model fine-tuning framework, dubbed **HERO**, to efficiently and effectively utilize online human feedback to fine-tune a SD model, as illustrated in Figure 1. Specifically, we propose two novel components: (1) *Feedback-Aligned Representation Learning*, an online-trained embedding map that creates a representation space that implicitly captures human preferences and provides continuous reward signals for RL fine-tuning, and (2) *Feedback-Guided Image Generation*, which involve generating images from SD's refined initialization samples aligned with human intent, for faster convergence to the evaluator's preferences.

Feedback-aligned representation learning (Figure 1's ①) aims to create a representation space that implicitly reflects human preferences, offering continuous reward signals for RL fine-tining. At each epoch, SD generates a batch of images, and a human evaluator classifies the images as "good" or "bad", selecting one "best" image from the "good" set. The latents of the human-annotated images are then employed to train an embedding map through contrastive learning (Chen et al., 2020), aiming to develop a feedback-aligned representation space. By calculating the cosine similarity to the "best" representation vector in the learned representation space, we obtain a continuous evaluation for each latent. Subsequently, we utilize the computed similarity as continuous reward signals to fine-tune SD via LoRA (Hu et al., 2022).

Figure 2: **Result preview.** Randomly sampled outputs generated by HERO and baselines given the prompt *"photo of one blue rose in a vase"* are presented. Successful samples are marked with ✅, and unsuccessful samples are marked with ❌, which fail to accurately capture the specified count (more than one roses), color (non-blue roses), and context (missing vase). HERO successfully captures these aspects, outperforming the baselines.

After fine-tuning the SD for the first iteration, our feedback-guided image generation (Figure 1's ②) samples a new batch of images from a Gaussian mixture centered on the stored "good" and "best" initial noises from the previous iteration. This process facilitates the generation of images that align

with human intentions better than random initial noises, thereby enhancing the efficiency of fine-tuning. HERO effectively achieves controllable T2I generation with minimal online human feedback through iterative feedback-guided image generation, feedback-aligned representation learning, and SD model finetuning.

We conduct extensive experiments on various T2I tasks to compare HERO with existing methods. The experimental results show that HERO can effectively fine-tune SD to reliably follow given text prompts with $4\times$ fewer amount of human feedback compared to D3PO (Yang et al., 2024b). On the other hand, the results show that these tasks are difficult to solve through prompt enhancement (Winata et al., 2024) or fine-tuning approaches, *e.g.*, DreamBooth (Ruiz et al., 2023), that rely on a few reference images (Gal et al., 2023). Figure 2 presents a preview of the results. Extensive ablation studies verify the effectiveness of our proposed feedback-aligned representation learning and the technique of generating images from refined noises. Additionally, we show that the model fine-tuned by HERO demonstrates transferability to previously unseen inference prompts, showcasing that the desired concepts were acquired by the model.

2 RELATED WORKS

Recent research has explored controllable generation with SD for tasks like T2I alignment (Black et al., 2024; Prabhudesai et al., 2023), conceptual generation (Yang et al., 2024a; Zhong et al., 2023), correcting generation flaws (Zhang et al., 2023), personalization (Gal et al., 2023; Ruiz et al., 2023) and removing NSFW content (Gandikota et al., 2023; Kumari et al., 2023; Lu et al., 2024).

Supervised fine-tuning. DreamBooth (DB; Ruiz et al., 2023) and Textual Inversion (Gal et al., 2023) take images as input and fine-tunes SD via supervised learning to learn the specific subject present in the input images. However, such methods require reference images, limiting their applicability to general T2I tasks, such as conceptual generation, *e.g.*, emotional image content generation (Yang et al., 2024a), or accurately reflecting user-specified counts, semantics, and attributes (Lin et al., 2024). On the other hand, Prabhudesai et al. (2023); Gandikota et al. (2023); Xu et al. (2024); Clark et al. (2024) use pretrained reward models to calculate differentiable gradients for SD fine-tuning. However, such pretrained models are not always accessible for tasks of interest, and moreover, these methods cannot directly utilize human feedback, which is non-differentiable.

RL fine-tuning. Various methods have explored incorporating non-differentiable signals, such as human feedback, as rewards to fine-tune SD using RL. For example, DDPO (Black et al., 2024) uses predefined reward functions for tasks like compressibility, DPOK (Fan et al., 2024) leverages feedback from an AI model trained on a large-scale human dataset, and SEIKO (Uehara et al., 2024) obtain rewards from custom reward functions trained from extensive feedback datasets. Yet, these methods require a predefined reward function or reward model, which can be difficult to obtain for tasks that involve generating personalized content (*e.g.*, reflecting cultural nuances) or abstract concepts, such as specific colors or compositions (Amadeus et al., 2024; Kannen et al., 2024).

Direct preference optimization (DPO). Diffusion-DPO (Wallace et al., 2023) applies DPO (Rafailov et al., 2023) to directly utilize preference data to fine-tune SD, eliminating the need for predefined rewards. Despite encouraging their results, such a method requires a large-scale pre-collected human preference dataset *e.g.*, Diffusion-DPO uses the Pick-a-Pic dataset with 851K preference pairs, making it costly to collect and limiting its applicability to various tasks, including personalization. Instead of leveraging offline datasets, D3PO (Yang et al., 2024b) uses *online human feedback* collected on-the-fly during model training for DPO-style finetuning of SD. It demonstrates success in tasks such as body part deformation correction and content safety improvement while avoiding the demand for large-scale offline datasets. However, the amount of human feedback required for D3PO is still high, requiring 5-10k feedback instances per task, which motivates us to develop a more human-feedback-efficient framework.

3 PRELIMINARIES

Stable Diffusion (SD) operates in two stages. First, an autoencoder compresses images $\mathbf{x}$ from pixel space into latent representations $\mathbf{z}_0$, which can later be decoded back to pixel space. Second, a diffusion model (DM) is trained to model the distribution of these latent representations conditioned

on text $\mathbf{c}$. The forward diffusion process is defined as $p(\mathbf{z}_t|\mathbf{z}_0) := \mathcal{N}(\mathbf{z}_t; \alpha_t \mathbf{z}_0, \sigma_t^2 \mathbf{I})$, where α_t and σ_t are pre-defined time dependent constants for $t \in [0, T]$. Both the forward transition kernel $p(\mathbf{z}_t|\mathbf{z}_{t-1}, \mathbf{c})$ and the backward conditioned transition kernel $p(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c}, \mathbf{z}_0)$ are Gaussian with closed-form expressions. The DM is trained to predict the clean sample $\mathbf{z}_0$ using a neural network $\hat{\mathbf{z}}_\phi(\mathbf{z}_t, t, \mathbf{c})$, denoising the noisy sample $\mathbf{z}_t$ at time t:

$$p_\phi(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c}) := p\big(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c}, \mathbf{z}_0 := \hat{\mathbf{z}}_\phi(\mathbf{z}_t, t, \mathbf{c})\big)$$

by optimizing the following objective:

$$\min_\phi \mathbb{E}_{\mathbf{z}_0, \mathbf{c}, \boldsymbol{\epsilon}, t}\Big[\|\hat{\mathbf{z}}_\phi(\alpha_t \mathbf{z}_0 + \sigma_t \boldsymbol{\epsilon}, t, \mathbf{c}) - \mathbf{z}\|_2^2 \Big], \quad \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}).$$

At inference, random noise $\mathbf{z}_T$ is sampled from a prior and iteratively denoised using samplers like DDPM (Ho et al., 2020) and DDIM (Song et al., 2020a) to obtain a latent code $\mathbf{z}_0$, which is then decoded into an image. This denoising and decoding process forms a text-to-image generative model, with random noise $\mathbf{z}_T$ sampled from a prior and $\mathbf{c}$ as the user-provided prompt.

Denoising Diffusion Policy Optimization (DDPO) formulates the denoising process of diffusion models as a multi-step Markov decision process. With this formulation, one can make direct Monte Carlo estimates of the reinforcement learning objective. Given a denoising trajectory $\{\mathbf{z}_T, \mathbf{z}_{T-1}, ..., \mathbf{z}_0\}$, the denoising diffusion RL update is defined as the following:

$$\nabla_\phi \mathcal{L}_{\text{DDRL}}(\phi) = \mathbb{E}\Bigg[\sum_{t=0}^{T} \nabla_\phi \log p_\phi(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c}) r(\mathbf{z}_0, \mathbf{c}) \Bigg], \tag{1}$$

where ϕ is the diffusion model, and $r(\mathbf{x}_0, \mathbf{c})$ is the received reward computed according the output image $\mathbf{x}_0$ and the input prompt $\mathbf{c}$. Based on the above update, DDPO further utilizes the importance sampling estimator (Kakade & Langford, 2002) and the trust region clipping from Proximal Policy Optimization (PPO; Schulman et al., 2017) to perform multiple steps of optimization while maintaining the diffusion model ϕ not deviating too far from the previous iteration ϕ_{old}. The DDPO update is defined as the following:

$$\nabla_\phi \mathcal{L}_{\text{DDPO}}(\phi) = \mathbb{E}\Bigg[\sum_{t=0}^{T} \frac{p_\phi(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c})}{p_{\phi_{\text{old}}}(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c})} \nabla_\phi \log p_\phi(\mathbf{z}_{t-1}|\mathbf{z}_t, \mathbf{c}) r(\mathbf{z}_0, \mathbf{c}) \Bigg]. \tag{2}$$

4 PROBLEM SETUP AND THE PROPOSED METHOD

Given a user-specified text prompt, our goal is to fine-tune SD to generate images that align with the prompt by learning from human feedback guidance. In this paper, we focus on challenging T2I tasks that require spatial reasoning, counting, feasibility understanding, etc., as detailed in Table 1. To efficiently and effectively utilize online human feedback, we propose a **h**uman-feedback **e**fficient **r**einforcement learning for **o**nline diffusion model fine-tuning framework, dubbed **HERO**, as illustrated in Figure 1. *Feedback-Aligned Representation Learning* (Figure 1 ①) makes efficient use of limited human feedback by converting discrete feedback to informative, continuous reward signals. In addition, *Feedback-Guided Image Generation* (Figure 1 ②) leverages human-preferred noise latents from previous iterations and encourages SD outputs to align more quickly with human intention, further improving sample efficiency.

4.1 ONLINE HUMAN FEEDBACK

In the first iteration of HERO, we generate synthetic images $\mathcal{X}$ from a batch of random noises $\mathcal{Z}_T$ sampled from SD's prior distribution $\pi_{\text{HERO}}(\mathbf{z}_T) := \mathcal{N}(\mathbf{z}_T; \mathbf{0}, \mathbf{I})$ using DDIM (Song et al., 2020a; Ho et al., 2020). For each $\mathbf{z}_T \in \mathcal{Z}$, the sampling trajectories are denoted as $\{\mathbf{z}_T, \mathbf{z}_{T-1}, \cdots, \mathbf{z}_0\}$, and each $\mathbf{z}_0$ is decoded to an image for human evaluation. A human evaluator reviews $\mathcal{X}$, selects the "good" images $\mathcal{X}^+$, and labels the remaining images as $\mathcal{X}^-$. To obtain a gradation among all "good" images and all "bad" images by representation learning, we ask the evaluator to identify the "best" image in $\mathcal{X}^+$, denoted as $\mathbf{x}^{\text{best}}$. The details of our feedback-aligned representation learning are discussed in the following section and we store the following for future use: the sets of images $\mathcal{X}$, $\mathcal{X}^+$, $\mathcal{X}^-$, $\mathbf{x}^{\text{best}}$; their corresponding SD's clean latents $\mathcal{Z}_0$, $\mathcal{Z}_0^+$, $\mathcal{Z}_0^-$, $\mathbf{z}_0^{\text{best}}$ from which they are decoded; and their initial noises (at time T) $\mathcal{Z}_T$, $\mathcal{Z}_T^+$, $\mathcal{Z}_T^-$, $\mathbf{z}_T^{\text{best}}$ used in SD's sampling.

4.2 FEEDBACK-ALIGNED REPRESENTATION LEARNING

HERO fine-tunes SD with minimal online human feedback by learning representations via a contrastive objective that captures discrepancies between the best SD's clean latent $\mathbf{z}_T^{\text{best}}$, positive $\mathcal{Z}_0^+$, and negative $\mathcal{Z}_0^-$ SD's clean latents (Section 4.2.1). By calculating similarity to the best image's representation, we use these similarity scores as continuous rewards for RL fine-tuning (Section 4.2.2). This approach bypasses reward model training by directly converting human feedback into learning signals, avoiding the need for over 100k training samples typically required to train a reward model for unseen data (Wallace et al., 2023; Rafailov et al., 2023).

4.2.1 LEARNING REPRESENTATIONS

To learn a representation space of $\mathcal{Z}_0$ aligned with human feedback, we build on the contrastive learning framework of Chen et al. (2020). We design an embedding network $E_\theta(\cdot)$ to map $\mathcal{Z}_0$ into the representation space, followed by a projection head $g_\theta(\cdot)$ for loss calculation. Triplet margin loss is applied to the projection head's output:

$$
\mathcal{L}(\theta; \mathbf{z}_0^{\text{best}}, \mathcal{Z}_0^+, \mathcal{Z}_0^-) = \mathbb{E}_{\mathbf{z}_0^{\text{good}} \sim \mathcal{Z}_0^+, \mathbf{z}_0^{\text{bad}} \sim \mathcal{Z}_0^-} \max \Bigg\{ S\Big(g_\theta\big(E_\theta(\mathbf{z}_0^{\text{best}})\big), g_\theta\big(E_\theta(\mathbf{z}_0^{\text{good}})\big)\Big) \\
- S\Big(g_\theta\big(E_\theta(\mathbf{z}_0^{\text{best}})\big), g_\theta\big(E_\theta(\mathbf{z}_0^{\text{bad}})\big)\Big) + \alpha, 0 \Bigg\}.
\tag{3}
$$

$E_\theta(\mathbf{z}_0^{\text{best}})$ serves as the anchor in the contrastive loss, with $S(\cdot, \cdot)$ representing the similarity score (using cosine similarity) and α as the triplet margin set to 0.5. By using the best image in the triplet loss, we obtain a gradation within positive and negative categories based on the distance to the best sample. With the learned representation $E_\theta(\mathbf{z}_0)$ for $\mathbf{z}_0 \in \mathcal{Z}_0$, we can compute continuous rewards for RL fine-tuning.

4.2.2 SIMILARITY-BASED REWARDS COMPUTATION

After training the embedding $E_\theta(\cdot)$ on the current batch of human feedback, reward values are computed as the cosine similarity in the learned representation space between each $E_\theta(\mathbf{z}_0)$ for $\mathbf{z}_0 \in \mathcal{Z}_0$ and $E_\theta(\mathbf{z}_0^{\text{best}})$:

$$
R(\mathbf{z}_0) = \frac{E_\theta(\mathbf{z}_0) \cdot E_\theta(\mathbf{z}_0^{\text{best}})}{\max\left\{ \|E_\theta(\mathbf{z}_0)\|_2 \left\|E_\theta(\mathbf{z}_0^{\text{best}})\right\|_2, \delta \right\}} \quad \text{for each } \mathbf{z}_0 \in \mathcal{Z}_0,
\tag{4}
$$

where $\delta = 1 \times 10^{-8}$ to avoid zero division. By using the learned representations to convert simple (discrete) human feedback into continuous reward signals, we avoid the need for a large pretrained reward model or costly training of such a model.

Besides the "similarity-to-best" design, we also consider a "similarity-to-positives" design, which uses the similarity between an image and the average of all "good" images in the learned representation space. We choose the "similarity-to-best" design for its superior performance. Further discussion is available in Section 5.3.1.

4.2.3 DIFFUSION MODEL FINETUNING

DDPO fine-tunes SD by reweighting the likelihood with reward values. For a noise latent $\mathbf{z}_T \in \mathcal{Z}_T$ and its sampling trajectory $\{\mathbf{z}_T, \mathbf{z}_{T-1}, \cdots, \mathbf{z}_0\}$, we incorporate the reward $R(\mathbf{z}_0)$ from Eq. (4) into the DDPO update rule in Eq. (2) to fine-tune the SD model ϕ. To reduce costly gradient computations, we adopt LoRA (Hu et al., 2022) for fine-tuning.

4.3 FEEDBACK-GUIDED IMAGE GENERATION

After the previous iteration of fine-tuning, we propose feedback-guided image generation to facilitate the fine-tuning process by generating images that reflect human intentions. We sample the noise latents for a new batch of images from the Gaussian mixture with means centered around the human-selected "good" $\mathcal{Z}_T^+$ and "best" $\mathbf{z}_T^{\text{best}}$ SD noise latents from the previous iteration, with

a small variance ε_0. Specifically, we sample the noise latent $\mathbf{z}_T$ from the distribution $\pi_{\text{HERO}}(\mathbf{z}_T)$ defined as:

$$\pi_{\text{HERO}}(\mathbf{z}_T) = \begin{cases} \mathcal{N}(\mathbf{z}_T; \mathbf{0}, \mathbf{I}), & \text{first iteration} \\ \beta\mathcal{N}(\mathbf{z}_T; \mathbf{z}_T^{\text{best}}, \varepsilon_0^2\mathbf{I}) + \frac{(1-\beta)}{|\mathcal{Z}_T^+|} \sum_{\mathbf{z}_T^{\text{good}} \in \mathcal{Z}_T^+} \mathcal{N}(\mathbf{z}_T; \mathbf{z}_T^{\text{good}}, \varepsilon_0^2\mathbf{I}) & \text{otherwise.} \end{cases} \quad (5)$$

Here, we introduce a hyperparameter *best image ratio* β to control the proportion of the next batch sampled from the "best" image noise latent. We find that leveraging $\mathbf{z}_T^{\text{best}}$ with a larger β can accelerate training convergence to evaluator preferences but may reduce the diversity or the converged accuracy. The above tradeoff can be controlled by the best image ratio β. We generally set $\beta = 0.5$ to balance these effects. Further discussion on the *best image ratio* parameter is in Section 5.3.2.

We remark that since the variance ε_0 is small, after a few iterations, samples from $\pi_{\text{HERO}}(\mathbf{z}_T)$ still concentrate near the prior $\mathcal{N}(\mathbf{z}_T; \mathbf{0}, \mathbf{I})$ at high probability (see Proposition A.1). Also, $\mathbf{z}_T^{\text{good}}$ and $\mathbf{z}_T^{\text{best}}$ may retain semantic information about human alignment from $\mathbf{z}_0^{\text{good}}$ and $\mathbf{z}_0^{\text{best}}$, as they are connected through the finite-step discretization of the SD sampler (see Proposition A.2). Thus, these validate our proposed $\pi_{\text{HERO}}(\mathbf{z}_T)$ as refined initializations for sampling.

Given a new batch of images $\mathcal{X}$ decoded from the clean latents $\mathcal{Z}_0$ generated by SD, with corresponding initial noises $\mathcal{Z}_T$ sampled from $\pi_{\text{HERO}}(\mathbf{z}_T)$ in Eq. (5), the human evaluator provides their evaluation as described in Section 4.1. The process is repeated until the feedback budget is exhausted or the evaluator is satisfied with the generation from $\pi_{\text{HERO}}(\mathbf{z}_T)$. After obtaining the fine-tuned SD model ϕ and $\pi_{\text{HERO}}(\mathbf{z}_T)$ through HERO, we use SD random noises from refined $\pi_{\text{HERO}}(\mathbf{z}_T)$ and generate images using any DM sampler (Song et al., 2020a).

5 EXPERIMENTAL RESULTS

We demonstrate HERO's performance on a variety of tasks, including hand deformation correction, content safety improvement, reasoning, and personalization. Many of them cannot be easily solved by the pretrained model, prompt enhancement, or prior methods. A full list of tasks and their success conditions are shown in Table 1. We adopt SD v1.5 (Rombach et al., 2022) as the base T2I model, using DDIM (Ho et al., 2020; Song et al., 2020a) with 50 diffusion steps (20 for hand deformation correction for fair comparison to the baselines) as the sampler.

We compare HERO to the following baselines:

- **SD-pretrained** prompts the pretrained SD model with the original task prompt shown in Table 1.

- **SD-enhanced** prompts the pretrained SD model with an enhanced version of the prompt generated by GPT-4 (Brown, 2020; Achiam et al., 2023).

- **DreamBooth** (DB; Ruiz et al., 2023) finetunes diffusion models via supervised learning, taking images as input. We use the four best images chosen by the human evaluators as model inputs.

- **D3PO** (Yang et al., 2024b) utilize online human feedback for DPO (Rafailov et al., 2023)-based diffusion model finetuning. Due to the high feedback cost for training, this baseline is considered only for the hand anomaly correction task directly adopted from their work. Success rates are reported as presented in the original paper.

Figure 3: **Hand anomaly correction success rates.** Performance of methods except D3PO are average of 8 seeds, where each seed is evaluated on 128 images per epoch. DB, SD-P, and SD-E are DreamBooth, SD-pretrained, and SD-enhanced, respectively.

5.1 HAND DEFORMATION CORRECTION

Following the problem setup of D3PO (Yang et al., 2024b), we use the prompt *"1 hand"* for image generation and use human discretion to evaluate the normalcy of the generated hand images. Parameters such as sampling steps are set to be consistent with D3PO. In each epoch of HERO, feedback on 128 images is collected, and the human evaluator provides a total of 1152 feedback over 9 epochs.

Performance of HERO in comparison to the baselines is shown in Figure 3. As shown in Figure 3, the pretrained SD model struggles on this task, with a normalcy rate of 11.9% (SD-pretrained) and 7.5% (SD-enhanced), and DB achieves 28%. D3PO reaches 33.3% normalcy rate at 5K feedback, while HERO achieves a comparable success rate of 34.2% with only 1152 feedback (over $4\times$ more feedback efficient). The sampled images are shown in Appendix H in the appendix.

5.2 DEMONSTRATION ON THE VARIETY OF TASKS

Table 1: **Task summary.**

Task Name	Prompt	Task Categories
hand	*"1 hand"*	correction, feasibility
blue-rose	*"photo of one blue rose in a vase"*	reasoning, counting
black-cat	*"a black cat sitting inside a cardboard box"*	reasoning, feasibility, functionality
narcissus	*"narcissus by a quiet spring and its reflection in the water"*	feasibility, homonym distinction
mountain	*"beautiful mountains viewed from a train window"*	reasoning, functionality, personalization

We further demonstrate the effectivity of HERO on a variety of tasks involving reasoning, correction, feasibility and functionality quality enhancement, and personalization. Tasks are listed in Table 1, and descriptions of task success conditions and task categories are found in Appendix D. For each task, human evaluators are presented with 64 images per epoch and provide a total of 512 feedback over 8 epochs. We report the average and standard deviation of the success rates across three seeds, where success is evaluated on 64 images generated in the final epoch. For methods that require human feedback (DB and HERO), three different human evaluators were each assigned a different seed to provide feedback on. Each evaluator was also responsible for evaluating the success rates of all methods for their assigned seed. Results are shown in Table 2. For all tasks, HERO achieves a success rate at or above 75%, outperforming all baselines. This trend is consistent for all three human evaluators, suggesting HERO's robustness to individual differences among human evaluators. Sample images generated by SD-pretrained, DB, and HERO are shown in Figure 4 and more results can be found in Appendix H. While the baselines often struggle in attribute reasoning (*e.g.*, color, count), spatial reasoning (*e.g.*, inside), and feasibility (*e.g.*, reflection consistent with the subject), HERO models consistently capture these aspects correctly.

In Appendix B, we comprehensively evaluate HERO using various metrics beyond the success rate, including aesthetic quality, image diversity, and text-to-image alignment.

Table 2: **Task performance.** Mean and standard deviation of success rates of different methods on the four tasks. HERO achieves a success rate at or above 75% and outperforms all baselines, demonstrating effectiveness on a variety of tasks.

Method	blue-rose	black-cat	narcissus	mountain
SD-Pretrained	0.354 (0.020)	0.422 (0.092)	0.406 (0.077)	0.412 (0.063)
SD-Enhanced	0.479 (0.030)	0.365 (0.134)	0.276 (0.041)	0.938 (0.022)
DB	0.479 (0.085)	0.453 (0.142)	0.854 (0.092)	0.922 (0.059)
HERO (ours)	**0.807** (0.115)	**0.750** (0.130)	**0.912** (0.007)	**0.995** (0.007)

5.3 ABLATIONS

This section presents ablation studies illustrating the roles of each component of HERO. In regards to *Feedback-Aligned Representation Learning*, we investigate the effects of (1) computation of rewards using learnable feedback-aligned representations and (2) "similarity-to-best" design for reward computation. For *Feedback-Guided Image Generation*, the effect of best image ratio is explored.

5.3.1 EFFECT OF FEEDBACK-ALIGNED REPRESENTATION LEARNING AND REWARD DESIGN

The effects of using learned feedback-aligned representations and our reward design are investigated through three ablation experiments. Firstly, we demonstrate the benefit of converting discrete human feedback into continuous reward signal by investigating HERO-binary, a variant of HERO using binary rewards for training. Secondly, we explore the effect of learned representations by replacing the learned representations in HERO with SD image latents $\mathcal{Z}_0^+$ (HERO-noEmbed). Finally,

Figure 4: **Qualitative results.** The randomly generated samples for the four tasks are shown, with ✅ denoting successful samples and ❌ for failures. In the `blue-rose` task, the pretrained SD model often omits the vase, while DB generates roses with incorrect color or count. In `narcissus`, SD frequently fails to capture the subject or produces inconsistent reflections. For `black-cat`, baseline models exhibit more issues (*e.g.*, the cat's body penetrating the box). In `mountain`, baseline images often miss the window frame or depict impossible views. Our fine-tuned models mitigate these issues and show significantly higher success rates across all tasks.

we justify our choice of the "similarity-to-best" reward design by comparing it with an alternative using similarity to the average of all $\mathcal{Z}_0^+$ and z_0^{best} (HERO-positives). We test each setting on the `narcissus` task with 512 training feedback and 200 images generated by the fine-tuned model for success rate evaluation. HERO outperforms all other settings, with results summarized in Table 3.

Directly using human labels as binary rewards. An intu-
itive way to extract a reward signal from binary human feed-
back is to directly convert the feedback into a binary reward.
To investigate the effect of similarity-based conversion of hu-
man feedback to continuous rewards, we test HERO-binary, a
variant where the reward in HERO is replaced with a binary
reward. Images labeled as "good" or "best" receive a reward
of 1.0, and all other images receive a reward of 0.0. HERO-
binary only reaches 78% success rate while HERO reaches
91%. This may be because the continuous rewards contain
additional information beneficial for DDPO training: While the binary reward only labels images as
"good" or "bad", the continuous reward additionally captures a gradation of human ratings within
the "good" and "bad" categories, supplying additional information such as which "good" images are
nearly "best", and which are *barely* "good".

Table 3: **Representation learning and reward design ablation.**

Method	Success rate
SD-Pretrained	0.40
HERO-binary	0.78
HERO-noEmbed	0.76
HERO-positives	0.82
HERO	**0.91**

Computing rewards from pretrained image representations. Experiments with binary rewards
showed the benefit of using continuous rewards in the learned representation space. To further
understand HERO's use of feedback-aligned learned representations, we replace the learned repre-

Figure 5: **Effect of best image ratio β evaluated on the `black-cat` task.** Three iterations with different seeds are performed for each setting, and the mean and standard deviation of the success rate are reported separately for clearer visualization. "random" refers to the case where random noise latents are used for sampling (*good* and *best* noises latents are not used).

sentations $E_\theta(\mathcal{Z}_0)$ with SD's clean latents $\mathcal{Z}_0$, obtained by denoising SD's initial noises $\mathcal{Z}_T$, and call this setup HERO-noEmbed. Without embedding map training, $\mathcal{Z}_0^+$ no longer cluster around z_0^{best}, making a "similarity-to-best" reward design impractical. Thus, we only consider the "similarity-to-positives" reward design for this ablation. While HERO-positives achieves 82% success, HERO-noEmbed reaches 76%, highlighting the advantage of learned representations. Training the embedding map also enables the "similarity-to-best" reward design, which yields superior performance.

Computing reward as similarity to average of all "good" representations. The reward in HERO is computed as the similarity to z_0^{best}. However, another natural choice is to compute similarity to the average of all $\mathcal{Z}_0^+$. Comparing this "similarity-to-positives" design to the "similarity-to-best" design employed in HERO, we find that the "similarity-to-best" design achieves 91% success, while the "similarity-to-positives" design reaches 82%. We adopt the "similarity-to-best" design, which empirically gives superior performance.

5.3.2 EFFECT OF BEST IMAGE RATIO IN FEEDBACK-GUIDED IMAGE GENERATION

To investigate the effect of the best image ratio, we compare the performance of the `black-cat` task for $\beta = 0.0, 0.5, 1.0$. Further, we compare to the case where the images are sampled from random SD noise latents to demonstrate the benefit of using $\mathcal{Z}_T^+$ and z_T^{best} as initial noises for image generation. Results are shown in Figure 5. Sampling all images from the z_T^{best} ($\beta = 1.0$) reaches an average of 70.8% success at the end of the training. However, as the high standard deviation in the initial stage of training suggests, over-exploiting a single "best" noise latent can cause instability in training, potentially causing the model to settle on a suboptimal output. Sampling uniformly from $\mathcal{Z}_T^+$ and z_T^{best} ($\beta = 0.0$) results in a similar success rate as $\beta = 1.0$, but is less likely to converge to a suboptimal point. We empirically find that, for our tasks, $\beta = 0.5$ results in the highest success rate while avoiding the risks of fully relying on the single "best" noise latent, thus using $\beta = 0.5$ for our experiments. When images are sampled from random SD noise latents, the task success rate does not grow significantly slower in the given amount of feedback, demonstrating the benefit of using $\mathcal{Z}_T^+$ and z_T^{best} for efficient fine-tuning.

5.4 TRANSFERABILITY

While HERO is trained to optimize for a single input prompt, we observe that some personal preferences and general concepts learned from one prompt can generalize to other related prompts in some cases.

Transfer of personal preference. In the `mountain` task, we observe the transfer of learned individual preferences. Two human evaluators trained two separate models for the `mountain` task, where one evaluator preferred green scenery while the other preferred snowy scenery. Each evaluator's trained model as well as the corresponding $\mathcal{Z}_T^+$ and z_T^{best} are used to generate images for a related task *"hiker watching beautiful mountains from the top of a hill"*. As shown in Figure 6, the preference for green or snowy scenery transfers to this new task.

Transfer of content safety. To further investigate whether a general concept, such as content safety, learned through one task can transfer to another, we prompt the SD model using the prompt *"sexy"* and train it to reduce NSFW content in the generated images. The fine-tuned model (as well as the saved $\mathcal{Z}_T^+$ and z_T^{best}) are used to generate images from a set of 14 potentially-unsafe prompts used in D3PO's content safety task. Utilizing the finetuned model and the saved SD noise latents significantly improves the content safety rate from 57.5% of the pretrained SD model to 87.0%, demonstrating HERO-finetuned model's potential to transfer a general concept learned from one prompt to a set of related, unseen prompts. Visual results are shown in Figure 7, and the full list of prompts with more results are shown in Appendix H in the appendix.

Figure 6: **Demonstration of personal preference transferability.** Models trained with two distinct personal preferences (*green* and *snowy*) generate images that inherit these preferences when prompted with a similar task (*"hiker watching beautiful mountains from the top of a hill"*).

Figure 7: **Qualitative results for the NSFW content hidden task showcasing transferability of HERO.** The images were randomly generated using the potentially unsafe prompt set provided by Yang et al. (2024b). The model is the HERO-finetuned version, trained with the *"sexy"* prompt to reduce nudity. The safety rate improves from 57.5% (pretrained SD) to 87.0% (HERO), showing HERO's ability to transfer the concept of safety to unseen, potentially unsafe prompts.

6 CONCLUSION

This work presents HERO, a framework that uses online human feedback to fine-tune SD with RLHF. By learning a representation aligned with feedback, we capture human preferences and turn simple feedback into a continuous reward that enhances DDPO fine-tuning. Starting with human-preferred image noise speeds up the alignment with preferences. Together, these elements make HERO much more efficient, needing 4 times less feedback than the baseline. It also shows potential for transferring personal preferences and concepts to similar tasks.

ACKNOWLEDGMENTS

We sincerely thank the reviewers for their constructive feedback, which greatly helped improve this work. We are also deeply grateful to our colleague, Takida Yuhta, for revising the manuscript and providing valuable comments. Their contributions have been instrumental in enhancing the quality of this paper. Shao-Hua Sun was supported by the Yushan Fellow Program by the Ministry of Education, Taiwan.

REFERENCES

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Marcellus Amadeus, William Alberto Cruz Castañeda, André Felipe Zanella, and Felipe Rodrigues Perche Mahlow. From pampas to pixels: Fine-tuning diffusion models for ga\'ucho heritage. *arXiv preprint arXiv:2401.05520*, 2024.

Kevin Black, Michael Janner, Yilun Du, Ilya Kostrikov, and Sergey Levine. Training diffusion models with reinforcement learning. In *The Twelfth International Conference on Learning Representations*, 2024.

Tom B Brown. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *Advances in neural information processing systems*, 33:9912–9924, 2020.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

Kevin Clark, Paul Vicol, Kevin Swersky, and David J. Fleet. Directly fine-tuning diffusion models on differentiable rewards. In *The Twelfth International Conference on Learning Representations*, 2024.

Ying Fan, Olivia Watkins, Yuqing Du, Hao Liu, Moonkyung Ryu, Craig Boutilier, Pieter Abbeel, Mohammad Ghavamzadeh, Kangwook Lee, and Kimin Lee. Dpok: reinforcement learning for fine-tuning text-to-image diffusion models. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, 2024.

Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit Haim Bermano, Gal Chechik, and Daniel Cohen-or. An image is worth one word: Personalizing text-to-image generation using textual inversion. In *The Eleventh International Conference on Learning Representations*, 2023.

Rohit Gandikota, Joanna Materzynska, Jaden Fiotto-Kaufman, and David Bau. Erasing concepts from diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Yaozhong Hu. Semi-implicit euler-maruyama scheme for stiff stochastic equations. In *Stochastic Analysis and Related Topics V: The Silivri Workshop, 1994*, pp. 183–202. Springer, 1996.

Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *Proceedings of the Nineteenth International Conference on Machine Learning*, pp. 267–274, 2002.

Nithish Kannen, Arif Ahmad, Marco Andreetto, Vinodkumar Prabhakaran, Utsav Prabhu, Adji Bousso Dieng, Pushpak Bhattacharyya, and Shachi Dave. Beyond aesthetics: Cultural competence in text-to-image models. *arXiv preprint arXiv:2407.06863*, 2024.

Dongjun Kim, Chieh-Hsin Lai, Wei-Hsiang Liao, Naoki Murata, Yuhta Takida, Toshimitsu Uesaka, Yutong He, Yuki Mitsufuji, and Stefano Ermon. Consistency trajectory models: Learning probability flow ode trajectory of diffusion. In *International Conference on Learning Representations*, 2024a.

Dongjun Kim, Chieh-Hsin Lai, Wei-Hsiang Liao, Yuhta Takida, Naoki Murata, Toshimitsu Uesaka, Yuki Mitsufuji, and Stefano Ermon. Pagoda: Progressive growing of a one-step generator from a low-resolution diffusion teacher. *arXiv preprint arXiv:2405.14822*, 2024b.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *Proceedings of the International Conference on Learning Representations*, 2015.

Yuval Kirstain, Adam Polyak, Uriel Singer, Shahbuland Matiana, Joe Penna, and Omer Levy. Pick-a-pic: An open dataset of user preferences for text-to-image generation. *Advances in Neural Information Processing Systems*, 36:36652–36663, 2023.

Nupur Kumari, Bingliang Zhang, Sheng-Yu Wang, Eli Shechtman, Richard Zhang, and Jun-Yan Zhu. Ablating concepts in text-to-image diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 22691–22702, 2023.

Chieh-Hsin Lai, Yuhta Takida, Naoki Murata, Toshimitsu Uesaka, Yuki Mitsufuji, and Stefano Ermon. Fp-diffusion: Improving score-based diffusion models by enforcing the underlying score fokker-planck equation. In *International Conference on Machine Learning*, pp. 18365–18398. PMLR, 2023a.

Chieh-Hsin Lai, Yuhta Takida, Toshimitsu Uesaka, Naoki Murata, Yuki Mitsufuji, and Stefano Ermon. On the equivalence of consistency-type models: Consistency models, consistent diffusion models, and fokker-planck regularization. *arXiv preprint arXiv:2306.00367*, 2023b.

Kimin Lee, Hao Liu, Moonkyung Ryu, Olivia Watkins, Yuqing Du, Craig Boutilier, Pieter Abbeel, Mohammad Ghavamzadeh, and Shixiang Shane Gu. Aligning text-to-image models using human feedback. *arXiv preprint arXiv:2302.12192*, 2023.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *ICML*, 2022.

Wang Lin, Jingyuan Chen, Jiaxin Shi, Yichen Zhu, Chen Liang, Junzhong Miao, Tao Jin, Zhou Zhao, Fei Wu, Shuicheng Yan, et al. Non-confusing generation of customized concepts in diffusion models. *arXiv preprint arXiv:2405.06914*, 2024.

Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. Mace: Mass concept erasure in diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6430–6440, 2024.

Mihir Prabhudesai, Anirudh Goyal, Deepak Pathak, and Katerina Fragkiadaki. Aligning text-to-image diffusion models with reward backpropagation. *arXiv preprint arXiv:2310.03739*, 2023.

Alec Radford, Jong Wook Kim, Chris Hallacy, A. Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10684–10695, 2022.

Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, June 2023.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2020a.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2020b.

Masatoshi Uehara, Yulai Zhao, Kevin Black, Ehsan Hajiramezanali, Gabriele Scalia, Nathaniel Lee Diamant, Alex M Tseng, Sergey Levine, and Tommaso Biancalani. Feedback efficient online fine-tuning of diffusion models. In *Proceedings of the 41st International Conference on Machine Learning*, 2024.

Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge university press, 2018.

Dimitri von Rütte, Elisabetta Fedele, Jonathan Thomm, and Lukas Wolf. Fabric: Personalizing diffusion models with iterative feedback, 2023.

Bram Wallace, Meihua Dang, Rafael Rafailov, Linqi Zhou, Aaron Lou, Senthil Purushwalkam, Stefano Ermon, Caiming Xiong, Shafiq Joty, and Nikhil Naik. Diffusion model alignment using direct preference optimization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023.

Genta Indra Winata, Hanyang Zhao, Anirban Das, Wenpin Tang, David D Yao, Shi-Xiong Zhang, and Sambit Sahu. Preference tuning with human feedback on language, speech, and vision tasks: A survey. *arXiv preprint arXiv:2409.11564*, 2024.

Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. Imagereward: Learning and evaluating human preferences for text-to-image generation. *Advances in Neural Information Processing Systems*, 36, 2024.

Jingyuan Yang, Jiawei Feng, and Hui Huang. Emogen: Emotional image content generation with text-to-image diffusion models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2024a.

Kai Yang, Jian Tao, Jiafei Lyu, Chunjiang Ge, Jiaxin Chen, Weihan Shen, Xiaolong Zhu, and Xiu Li. Using human feedback to fine-tune diffusion models without any reward model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8941–8951, 2024b.

Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3836–3847, 2023.

Shanshan Zhong, Zhongzhan Huang, Wushao Wen, Jinghui Qin, and Liang Lin. Sur-adapter: Enhancing text-to-image pre-trained diffusion models with large language models. In *The 31st ACM International Conference on Multimedia*, 2023.